Task-invariant and task-specific perceptual asymmetries

Matan Mazor[1] & Stephen M. Fleming[1,2,3]

[1] Wellcome Centre for Human Neuroimaging, UCL

[2] Max Planck UCL Centre for Computational Psychiatry and Ageing Research

[3] Department of Experimental Psychology, UCL

Author Note

Correspondence concerning this article should be addressed to Matan Mazor, 12 Queen Square, London WC1N 3BG. E-mail: mtnmzor@gmail.com

Abstract

Subjective confidence judgments are more aligned with objective performance following decisions about the presence, rather than the absence, of a stimulus or a memory. Here we ask whether this metacognitive asymmetry reflects a conceptual difference between the higher-level representation of presence and absence, or alternatively result from distributional properties of these two types of representations. By leveraging the visual search asymmetry phenomenon, we ask whether a metacognitive asymmetry exists for discrimination decisions about stimulus pairs that differ by the presence of a stimulus feature.

Keywords: keywords

Word count: 2214

Task-invariant and task-specific perceptual asymmetries

Introduction

Representing the absence of objects is more cognitively demanding than representing their presence. This is evident in slower reactions to stimulus absence than stimulus presence in visual search (e.g, Wolfe, 1998) and visual near-threshold detection (Mazor, Friston, & Fleming, 2020), in lower and less reliable subjective confidence ratings for inference about absence (Kanai, Walsh, & Tseng, 2010; Kellij, Fahrenfort, Lau, Peters, & Odegaard, 2018; Meuwese, Loon, Lamme, & Fahrenfort, 2014), in a general difficulty to form associations with absence (Newman, Wolff, & Hearst, 1980), and in the late acquisition of the explicit representation of absence in development (e.g., Sainsbury, 1971; Coldren & Haaf, 2000).

The perceptual presence/absence asymmetry is one instance of a more general difficulty in inferring absence from the absence of evidence (*argument from ignorance*; Locke, 1836). Perceptual and cognitive systems have evolved to represent presences, and absence is assumed as a default state (*rarity assumption*; Oaksford, 2002; Oaksford & Chater, 2001). As a result, presence can be inferred from bottom-up sensory signals, but absence is never explicitly represented in the sensory channels and must instead by inferred based on top-down expectations about the likelihood of detection a hypothetical signal, had it been present. This form of higher-order reasoning is known as *argument from epistemic closure*, or *argument from self knowledge* (*If it was true, I would have known it*; Walton, 1992; De Cornulier, 1988).

Evidence from visual search suggests that the presence/absence asymmetry is not exclusive to the representation of entire objects, but operates at the level of object features too. In their seminal paper, Treisman and Souther (1985) demonstrated that searching for an object that is marked by a distinguishing feature (for example, searching for a Q among Os) is easier than searching for an object that is marked by the absence of a distinguishing feature (searching for an O among Qs). Treisman and Gormican (1988) then used this

search-asymmetry as a litmus test for what counts as feature presence and what counts as feature absence in early vision. For example, the fact that C-in-O search is easier than O-in-C search was used as evidence for that free ends, rather than shape-closeness, are positively encoded in vision. The asymmetry between magenta-in-red and red-in-magenta searches was explained as resulting from blue being present in magenta but absent in red. In the same way curvature and tilt were identified as positive visual features based on search time benefits for tilted-in-vertical and curved-in-straight searches, compared with the inverse searches.



Figure 1. It is easier to find the circle with the vertical line among plain circles (left panel) than vice versa. Adapted from Wolfe (2001)

Contextual effects have led Treisman and Gormican (1988) to further propose that search asymmetry may sometimes reflect a deviation from a default state (also termed null, prototypical, or standard state). This standard state is affected by prior knowledge and available context. The contents of the default state are partly hard-coded into the wiring of the system, and partly learned and change according to context. For example, the Q-in-O/O-in-Q asymmetry is evident already at 3 months of age, suggesting that it corresponds to a core feature of the perceptual system (Adler & Gallego, 2014; Colombo, Ryther, Frick, & Gifford, 1995). Other aspects of the default state are sensitive to context and prior experience; for example, searching for an inverted letter among canonically presented letters is easier than the inverse search (Frith, 1974; Wang, Cavanagh, & Green,

1994). This similar effect for feature presence and deviation from a default state is consistent with the idea that search asymmetry reveals a true asymmetry in our cognitive modeling of the world, where absence is assumed as default unless evidence is available for the contrary (Oaksford, 2002; Oaksford & Chater, 2001). Indeed, and in line with the proposal that an explicit representation of absence is cognitively demanding and is not available without the active engagement of attention, Treisman and Gormican (1988) interpreted search asymmetries as revealing a categorical difference between pre-attentive parallel search and attention-guided serial search. According to their account, parallel search is not available when searching for a target that is marked by the absence, or the lesser quantity, of a feature, and when searching for a prototypical stimulus among deviant distractors.

In contrast, probabilistic parallel models of visual search, inspired by Signal Detection Theory, frame search asymmetry effects not as marking a categorical difference between serial and parallel search, but as reflecting the effect of stimulus uncertainty on the noisiness of the search process which is always parallel (Dosher, Han, & Lu, 2004; Vincent, 2011). In Signal-Detection models, decisions are taken based on a single perceptual sample that is drawn from a probability distribution. In the context of visual search, participants are assumed to use this noisy sample to decide whether the visual array included the target stimulus, or not. Vincent (2011) demonstrated that differences in search efficiency can be accounted for by the *sigma ratio*: the relative difference in internal uncertainty associated with the two stimulus categories. He found support for his sigma-ratio account in the slope of standardized ROC curves, extracted from subjective confidence estimates in a vertical/tilted visual search task with briefly presented (94 ms) search arrays. According to his analysis, the advantage for tilted-in-vertical compared with vertical-in-tilted search can reflect the higher perceptual uncertainty that is associated with tilted stimuli, compared with vertical ones. Similarly, reverse correlation analysis revealed higher variability in the internal representation of Q (feature-present), compared to O (feature absent) stimuli (Saiki, 2008). However, not all SDT analyses of search asymmetry converged to the same conclusions about

the variance ratio. Dosher et al. (2004) used a speed accuracy trade-off (SAT) method to compare the predictions of parallel and serial models of visual search asymmetry for C and O. By presenting the search array for 50-100 ms, and probing participants for a response at different timepoints after stimulus offset, they were able to recover the increase in accuracy as a function of time for both C-in-O and O-in-C searches. A model-comparison favored a probabilistic parallel model for both search types, but in contrast with the results of Vincent (2011) the error probabilities in the winning model were consistent with an unequal-variance SDT model in which the C (feature-presence) distribution was marked by a *lower* standard deviation than the O (feature-absent) distribution.

A third interpretation of the search-asymmetry phenomenon is that some asymmetries reflect a confounded asymmetry in the experimental design, rather than a true cognitive asymmetry in the processing of the two stimulus types (Rosenholtz, 2001). One source of experimental asymmetry that is often neglected is that of the background. Rosenholtz pointed to the fact that the background is often more similar to one of the stimulus types (for example, the background is upright and not tilted, or gray and not chromatic). As a result, the background intervenes with the search process more in one condition compared to the other. In other cases, two search tasks may seem symmetric when assuming one representational space, but asymmetry is revealed when considering alternative ones. This is the case of fast and slow oscillating targets: the two are symmetric when represented on a speed/direction coordinate system, but an asymmetry emerges when plotting the distractor and targets in two-dimensional velocity space.

These three interpretation presented here may not be entirely mutually exclusive. As pointed out by Treisman and Gormican (1988), and in line with Weber's law and with the noise profile of biological neurons, the positive representation of features and objects may be more variable, or noisy, than the representation of their absence. The unequal variance identified by signal detection models may be based in this qualitative differnce between the two classes of representation. Furthermore, a prallel search model may account for search

asymmetry for presentation times below the time taken to complete a saccade, but an additional level of asymmetry, governed by endogeneous attention mechanisms, may be necessary to account for search times in natural displays that are not limited in time. Indeed, while the parallel models of Vincent (2011) and Dosher et al. (2004) draw a link between unequal variance and asymptotic accuracy for short display times, they do not provide an explanation for the difference in search time and search slopes for long presentation times. Finally, it is not clear that all search asymmetries reflect the same underlying mechanism. While search asymmetry between moving and stationary items is amenable to Rosenholtz' argument about background interference, it is unclear how this explanation would account for the effects of inverted-letters or curvature asymmetries.

To date, this feature-level presence/absence asymmetry has only been demonstrated in the visual search domain, making it difficult to decide between alternative explanations. Here we ask whether a similar feature-level asymmetry is evident in three other domains where presence/absence asymmetry has been documented at the object level: response inhibition, metacognition, and working memory. By triagulating the feature-level asymmetry across six features and four tasks, we aim to obtain a better understanding of feature-level asymmetries, and to determine whether these asymmetries originate from identical, partly overlapping, or completely distinct mechanisms. We now turn to motivate our choice of experimental tasks, before describing our experimental design in detail in the methods section.

Confidence in visual detection

In a typical detection task, participants are asked to decide whether a faint stimulus was present or absent. Subjective confidence ratings following "target absent" judgments are commonly lower, and less correlated with objective accuracy, than following "target present" judgments (Kanai et al., 2010; Kellij et al., 2018; Mazor et al., 2020; Meuwese et al., 2014). This *metacognitive asymmetry* is present not only for detection tasks, but also for recognition memory (Higham, Perfect, & Bruno, 2009) and lexicality judgments (Fleming & Dolan,

2010) – both can be described as detection among items in an internal representation space (memory storage, orthographic lexicon). According to one interpretation, this metacognitive asymmetry reflects a qualitative difference between the metacognitive representations of decisions that are driven by the presence or the absence of evidence (Meuwese et al., 2014). One variant of this interpretation posits that the metacognitive evaluation of negative judgments is more computationally demanding because instead of relying on evidence for absence, it relies on the counterfactual likelihood of evidence for presence (contrast "I saw it was not there" with "If it was there I would not have missed it"; Mazor et al., 2020). In contrast, this asymmetry can also be interpreted as reflecting an asymmetry in the perceptual and cognitive uncertainties that are associated with the representations of presence and absence. For example, Kellij et al. (2018) successfully replicated the metacognitive asymmetry effect in a simple Signal Detection model with higher variance for the signal distribution. Their model did not have to posit any asymmetry in higher-order processes in order to fit the empirical data.

Crucially for our study, metacognitive asymmetry is not observed for discrimination judgments, where a decision is made about the identity of the stimulus instead of it presence. For example, when asking participants to decide whether it was a fish or a different animal that appeared in a degraded image, confidence ratings for the two responses are similarly indicative of true objective accuracy (Meuwese et al., 2014). It is unclear whether a metacognitive asymmetry is expected for discrimination judgments between stimulus features that show a search-asymmetry. Thus, in the context of our investigation, asking for confidence judgments following discrimination judgments for our selected stimuli will serve two purposes. First, it will allow us to directly test the hypothesis that search and metacognitive asymmetry originate from the same underlying mechanism by looking at individual and stimulus-related differences in the two measures. Second, with confidence ratings in discrimination we will get a measure of the relative variability for the two stimulus types that is independent of visual search. This measure can then inform and constrain

theories of search asymmetry, for example, support or rule out theories that rely on unequal-variance assumptions to explain search time differences.

Searching for one *Q* among 10 *O*'s is easier than searching for one *O* among 10 *Q*s.

Over the years researchers proposed different theoretical accounts for this phenomenon. Treisman and Souther (1985) proposed that visual search is more efficient when searching for the presence, rather than the absence, of a stimulus feature. According to this account, the letter *Q* is marked by an additional feature (a diagonal line) compared to the baseline *O*. Similarly, blue is present in magenta but absent in red. Treisman and Gormican (1988) then used search-asymmetry as a litmus test for what counts as presence and what counts as absence in early vision. For example, the fact that *C*-in-*O* search is easier than *O*-in-*C* search was used as evidence for that "free ends", rather than shape-closeness, are positively encoded in vision. Contextual effects have led Treisman and Gormican (1988) to further propose that search asymmetry can in some cases originate from a deviation from a default state (also termed null, prototypical, or standard state). This standard state is affected by prior knowledge and available context, for example searching for a tilted line among vertical distractors is easier than the inverse search, but this effect reverses when the search array is displayed inside a tilted frame (Treisman & Gormican, 1988). The contents of the default state are partly hard-coded into the wiring of the system (like in the case of color) and partly affected by expectations that are sensitive to context and prior experience (like in the cases of viewing direction or familiarity with letters; Von Grünau & Dubé, 1994; Wang et al., 1994).

In this study, we will compare perceptual, cognitive, and metacognitive asymmetries across several stimulus features and four tasks, in order to ask whether these asymmetries reflect the behavioural signature of identical, partly-overlapping, or completely distinct mechanisms. We will test the hypothesis that these four asymmetries result from differences in the shape of the underlying signal distributions for the two stimulus categories.

More specifically, this study is set to test the following hypotheses:

1. **Hypothesis 1**: Metacognitive asymmetry, measured as the area between the two response conditional ROC curves, follows the same direction as search asymmetry.

This hypothesis will be tested for the following stimulus features for which search asymmetry has been demonstrated: addition of a stimulus part, open ends, color, curvature, orientation and familiarity. We will test Hypothesis 1 separately for each stimulus feature, by replicating the original search asymmetry (for example, Q-in-O search is more efficient that O-in-Q search) and testing the null hypothesis that metacognitive sensitivity (measured as the area under the response conditional ROC curve) for the efficient target (e.g., Q) is equal to or lower than metacognitive sensitivity for the inefficient target (e.g., for the case of Q/O, $H_o = auROC_Q \leq auROC_O$).

2. **Hypothesis 2**: Response-inhibition asymmetry, measured with the Go/No-go task, follows the same direction as search asymmetry.

This hypothesis will be tested separately for the same six stimulus features. We will test Hypothesis 2 separately for each stimulus feature, by replicating the original search asymmetry (for example, Q-in-O search is more efficient that O-in-Q search) and testing the null hypothesis that response-inhibition (measured as Go/No-go accuracy) when the efficient target (e.g., Q) is used as a go-signal, is equal to or lower than response-inhibition for when the inefficient target is used as a go-signal (e.g., for the case of Q/O, $H_o = Acc_Q \leq Acc_O$).

2. **Hypothesis 2**: Individual differences in the direction and magnitude of search asymmetry positively covary with individual differences in the direction and magnitude of metacognitive asymmetry. This hypothesis will be tested globally for the 6 experiments by fitting a mixed-effects linear model using the `brms` package (Bürkner & Buerkner, 2016).

Methods

We report how we determined our sample size, all data exclusions (if any), all manipulations, and all measures in the study.

Participants

For each of the six experiments, we will collect data until we reach 200 included participants (after applying our pre-registered exclusion criteria). With 200 participants, we will have a statistical power of 95% to detect effects of size 0.23, which is about half the effect size we observed for metacognitive asymmetry and less than fifth the effect size we observed for search slopes in our pilot sample.

Multi-level MCMC simulations, assuming an average correlation of 0.29 across the six tasks between search and metacognitive asymmetries, indicated a statistical power of 97% to reject the null hypothesis for Hypothesis 2.

Material

Procedure

Experiments will be identical, except for the identity of the target and distractor stimuli. In what follows we will describe the procedure for the stimulus pair "*Q*" and "*O*". See Experiment here: https://visual-search-c-o.glitch.me

The Experiment will comprise three parts ("challenges") presented in pseudorandomized order.

1. The first part will comprise 32 visual search trials. In these trials participants will search for one "*Q*" in an array of 1, 2, 4 or 8 "*O*" distractors. The target stimulus will be present in half of the trials, and absent in the other half. Participants will be

instructed to use their keyboard to indicate whether the target was present (press J) or absent (press F) as quickly and accurately as possible. Each trial will start with an instruction screen, indicating the search target (500-1000 ms), followed by the presentation of the search array. The search array will remain visible until a response is recorded. Feedback about accuracy will be delivered. To motivate accurate responses, the feedback screen will remain for 1000 ms following correct responses and for 4000 ms following incorrect responses. The visual search block will start with four practice trials of distractor set-size 4 that will not be included in the final analysis. The actual block of 32 trials will start once all four practice trials are answered correctly, otherwise additional practice trials will be delivered.

2. The second part will be identical to the first part, except for the identity of the target stimulus. Here "O" will server as target and "Q" as distractor.

3. In the third part, participants will make discrimination judgments between masked Q and O stimuli, and rate their subjective decision confidence on a continuous scale. After a fixation cross (500 ms), the target stimulus will be presented in the center of the screen for 50 ms, followed by a mask (100 ms). Stimulus onset asynchrony will be calibrated online in a 1-up-2-down procedure (Levitt, 1971), with a multiplicative step factor of 0.9, and starting from 30 milliseconds. Participants will then use their keyboard to make a discrimination judgment. Following their response, subjective confidence ratings will be given on an analog scale by controlling the size of a colored circle with the computer mouse. High confidence will be mapped to a big, blue circle, and low confidence to a small, red circle. The confidence rating phase will terminate once participants click their mouse, but not before 2000 ms. No feedback will be delivered about accuracy.

We will test the following stimulus features in separate experiments:



Figure 2. Experiment structure. Three experimental parts will be delivered in pseudorandomized order: a discrimination task with subjective confidence ratings, and two visual search tasks with different distractor/target assignments. Asymmetry effects will be tested for six stimulus features in six separate experiments.

1. **Addition of a stimulus part**. *Q* and *O* will be used as stimuli (Treisman & Souther, 1985).
2. **Open ends**. *C* and *O* will be used as stimuli (Takeda & Yagi, 2000; Treisman & Gormican, 1988; Treisman & Souther, 1985).
3. **Color**. Red and magenta dots will be used as stimuli (Treisman & Gormican, 1988).
4. **Curvature**. Straight and curved lines will be used as stimuli (Treisman & Gormican, 1988).
5. **Orientation**. Vertical and tilted lines will be used as stimuli (Treisman & Gormican, 1988).
6. **Familiarity**. Reversed and normal *N* will be used as stimuli (Frith, 1974).

Data analysis

We will use R (Version 3.6.0; R Core Team, 2019) and the R-packages *BayesFactor* (Version 0.9.12.4.2; Morey & Rouder, 2018), *brms* (Version 2.13.0; Bürkner, 2018), *broom* (Version 0.5.6; Robinson & Hayes, 2020), *cowplot* (Version 1.0.0; Wilke, 2019), *dplyr* (Version 1.0.0; Wickham et al., 2020), *ggplot2* (Version 3.3.1; Wickham, 2016), *papaja* (Version 0.1.0.9942; Aust & Barth, 2020), and *tidyr* (Version 1.1.0; Wickham & Henry, 2020) for all our analyses.

Rejection criteria. Participants will be excluded for performing below 70% accuracy in one or two of the search tasks, for performing below 60% accuracy in the discrimination task, for having extremely fast or slow reaction times in one or more of the tasks (below 250 milliseconds or above 5 seconds in more than 25% of the trials), and for failing the comprehension check. For the response-conditional ROC analysis, only participants that committed at least one error of each error type (for example, mistaking a *Q* of *O* and mistaking an *O* for *Q*), will be included.

Trials with response-time below 250 milliseconds or above 5 seconds will be excluded.

Only correct visual search trials will be analyzed.

Dependent variables and analysis plan. The following measures will be extracted for each participant: 1. The difference between the area under the response-conditional type-2 ROC curves for the two responses [e.g., "Q" and "O"]: Δ_m. The area between the two curves is a measure of metacognitive asymmetry. This difference will be used to test Hypothesis 1. 2. The difference between search slopes for the two visual search tasks (defined as β_1 in the linear regression model $RT = \beta_0 + \beta_1 set_size$, collapsed across both "yes" and "no" responses): Δ_s. The difference between the curves is a measure of search asymmetry. This difference will be used to test Hypothesis 1. 3. The relative difference between the area under the response-conditional type-2 ROC curves for the two responses (Δ_m^{rel}) will be defined as the area between the two curves, divided by the sum of the areas under the two curves. This relative difference will be used in the hierarchical model to test Hypothesis 2. 4. The relative difference between search slopes for the two visual search tasks (Δ_s^{rel}) will be defined as the difference between the two search slopes, divided by their sum. This relative difference will be used in the hierarchical model to test Hypothesis 2.

For each of the six experiments, Hypothesis 1 (metacognitive asymmetry follows the same direction as search asymmetry) will be tested using a one tailed t-test at the group level with $\alpha = 0.05$. In case of a null result, a two one-sided test (TOST procedure; Schuirmann, 1987) will be adopted to test the null hypothesis that $|\Delta_m|$ is higher than the smallest effect size of interest (0.05 in auROC units, ranging from 0 to 1), or that $|\Delta_s|$ is higher than the smallest effect size of interest (1 millisecond/item).

Hypothesis 2 (search and metacognitive asymmetries covary) will be tested globally for the 6 experiments by fitting a mixed-effects linear model using the `brms` package (Bürkner & Buerkner, 2016). The following mixed-effects linear model will be fitted to the data: $\Delta_s^{rel} \sim 1 + \Delta_m^{rel} + (1 + \Delta_m^{rel}|exp)$ where exp denoted the specific experiment in which the subject participated. The population-level coefficient for Δ_s^{rel} will be compared against 0. We will conclude that the two effects are correlated at the population level if the lower bound of the 95% credible interval for this coefficient will by higher than 0.05. We will

conclude that the correlation falls within our Region of Practical Equivalence (Kruschke, 2013) if the entire credible interval will fall within the region $[-0.05, 0.05]$.

References

Adler, S. A., & Gallego, P. (2014). Search asymmetry and eye movements in infants and adults. *Attention, Perception, & Psychophysics*, *76*(6), 1590–1608.

Aust, F., & Barth, M. (2020). *papaja: Create APA manuscripts with R Markdown*. Retrieved from https://github.com/crsh/papaja

Bürkner, P.-C. (2018). Advanced Bayesian multilevel modeling with the R package brms. *The R Journal*, *10*(1), 395–411. https://doi.org/10.32614/RJ-2018-017

Bürkner, P.-C., & Buerkner, M. P.-C. (2016). Package "brms".

Coldren, J. T., & Haaf, R. A. (2000). Asymmetries in infants' attention to the presence or absence of features. *The Journal of Genetic Psychology*, *161*(4), 420–434.

Colombo, J., Ryther, J. S., Frick, J. E., & Gifford, J. J. (1995). Visual pop-out in infants: Evidence for preattentive search in 3-and 4-month-olds. *Psychonomic Bulletin & Review*, *2*(2), 266–268.

De Cornulier, B. (1988). Knowing whether, knowing who, and epistemic closure. *Questions and Questioning*, 182–192.

Dosher, B. A., Han, S., & Lu, Z.-L. (2004). Parallel processing in visual search asymmetry. *Journal of Experimental Psychology: Human Perception and Performance*, *30*(1), 3.

Fleming, S. M., & Dolan, R. J. (2010). Effects of loss aversion on post-decision wagering: Implications for measures of awareness. *Consciousness and Cognition*, *19*(1), 352–363.

Frith, U. (1974). Acurious effect with reversed letters explained by a theory of schema. *Perception & Psychophysics*, *16*(1), 113–116.

Higham, P. A., Perfect, T. J., & Bruno, D. (2009). Investigating strength and frequency effects in recognition memory using type-2 signal detection theory. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *35*(1), 57.

Kanai, R., Walsh, V., & Tseng, C.-h. (2010). Subjective discriminability of invisibility: A framework for distinguishing perceptual and attentional failures of awareness. *Consciousness and Cognition*, *19*(4), 1045–1057.

Kellij, S., Fahrenfort, J., Lau, H., Peters, M. A., & Odegaard, B. (2018). The foundations of introspective access: How the relative precision of target encoding influences metacognitive performance.

Kruschke, J. (2013). How much of a bayesian posterior distribution falls inside a region of practical equivalence (rope). *Doing Bayesian Data Analysis Web Blog Post*.

Levitt, H. (1971). Transformed up-down methods in psychoacoustics. *The Journal of the Acoustical Society of America*, *49*(2B), 467–477.

Locke, J. (1836). An essay concerning human understanding (bk. Iv. *Chap. XXVII*.

Mazor, M., Friston, K. J., & Fleming, S. M. (2020). Distinct neural contributions to metacognition for detecting, but not discriminating visual stimuli. *Elife*, *9*, e53900.

Meuwese, J. D., Loon, A. M. van, Lamme, V. A., & Fahrenfort, J. J. (2014). The subjective experience of object recognition: Comparing metacognition for object detection and object categorization. *Attention, Perception, & Psychophysics*, *76*(4), 1057–1068.

Morey, R. D., & Rouder, J. N. (2018). *BayesFactor: Computation of bayes factors for common designs*. Retrieved from https://CRAN.R-project.org/package=BayesFactor

Newman, J. P., Wolff, W. T., & Hearst, E. (1980). The feature-positive effect in adult human subjects. *Journal of Experimental Psychology: Human Learning and Memory*, *6*(5), 630.

Oaksford, M. (2002). Contrast classes and matching bias as explanations of the effects of negation on conditional reasoning. *Thinking & Reasoning*, *8*(2), 135–151.

Oaksford, M., & Chater, N. (2001). The probabilistic approach to human reasoning. *Trends in Cognitive Sciences*, *5*(8), 349–357.

R Core Team. (2019). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from https://www.R-project.org/

Robinson, D., & Hayes, A. (2020). *Broom: Convert statistical analysis objects into tidy tibbles*. Retrieved from https://CRAN.R-project.org/package=broom

Rosenholtz, R. (2001). Search asymmetries? What search asymmetries? *Perception & Psychophysics*, *63*(3), 476–489.

Saiki, J. (2008). Stimulus-driven mechanisms underlying visual search asymmetry revealed by classification image analyses. *Journal of Vision*, *8*(4), 30–30.

Sainsbury, R. (1971). The "feature positive effect" and simultaneous discrimination learning. *Journal of Experimental Child Psychology*, *11*(3), 347–356.

Schuirmann, D. J. (1987). A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. *Journal of Pharmacokinetics and Biopharmaceutics*, *15*(6), 657–680.

Takeda, Y., & Yagi, A. (2000). Inhibitory tagging in visual search can be found if search stimuli remain visible. *Perception & Psychophysics*, *62*(5), 927–934.

Treisman, A., & Gormican, S. (1988). Feature analysis in early vision: Evidence from search asymmetries. *Psychological Review*, *95*(1), 15.

Treisman, A., & Souther, J. (1985). Search asymmetry: A diagnostic for preattentive processing of separable features. *Journal of Experimental Psychology: General*, *114*(3), 285.

Vincent, B. T. (2011). Search asymmetries: Parallel processing of uncertain sensory information. *Vision Research*, *51*(15), 1741–1750.

Von Grünau, M., & Dubé, S. (1994). Visual search asymmetry for viewing direction. *Perception & Psychophysics*, *56*(2), 211–220.

Walton, D. (1992). Nonfallacious arguments from ignorance. *American Philosophical Quarterly*, *29*(4), 381–387.

Wang, Q., Cavanagh, P., & Green, M. (1994). Familiarity and pop-out in visual search. *Perception & Psychophysics*, *56*(5), 495–500.

Wickham, H. (2016). *Ggplot2: Elegant graphics for data analysis*. Springer-Verlag New York. Retrieved from https://ggplot2.tidyverse.org

Wickham, H., François, R., Henry, L., & Müller, K. (2020). *Dplyr: A grammar of data manipulation*. Retrieved from https://CRAN.R-project.org/package=dplyr

Wickham, H., & Henry, L. (2020). *Tidyr: Tidy messy data*. Retrieved from https://CRAN.R-project.org/package=tidyr

Wilke, C. O. (2019). *Cowplot: Streamlined plot theme and plot annotations for 'ggplot2'*. Retrieved from https://CRAN.R-project.org/package=cowplot

Wolfe, J. M. (1998). What can 1 million trials tell us about visual search? *Psychological Science*, *9*(1), 33–39.

Wolfe, J. M. (2001). Asymmetries in visual search: An introduction. *Perception & Psychophysics*, *63*(3), 381–389.

Supplementary information

Pilot data and analysis

Pilot Experiment 1

30 participants were recruited from Prolific for our pilot experiment. We followed the procedure described in the Methods section, using *Q* and *O* as our stimuli. The experiment took about 10 minutes to complete. Subjects were paid £1.25 for their participation.

Mean accuracy was 0.80 in the discrimination task, 0.96 in the Q-in-O search task, and 0.95 in the O-in-Q search task. We excluded participants for performing below 70% accuracy in one or two of the search tasks, for performing below 60% accuracy in the discrimination task, for having extremely fast or slow reaction times in one or more of the tasks (below 250 milliseconds or above 5 seconds in more than 25% of the trials), and for failing the comprehension check. Overall we excluded 0 participants, leaving 30 participants for the main analysis.

Visual search task: search asymmetry

Search time analysis was performed on correct trials with reaction time between 250 and 5000 milliseconds. Search slopes for the response time/set size function were extracted for each participant, task and response, and then subjected to a two-way analysis of variance. As expected, we observed significant effects for target identity (mean search slope for *Q-in-O* search: 18.93 ms/item; mean search slope for *O-in-Q* search: 54.89 ms/item; $F(1, 116) = 44.39$, $MSE = 873.80$, $p < .001$) and response (mean search slope for target absent responses: 48.04; mean search slope for target present responses: 25.78; $F(1, 116) = 17.01$, $MSE = 873.80$, $p < .001$; see Figure 3). An interaction effect was also significant ($F(1, 116) = 8.91$, $MSE = 873.80$, $p = .003$). These results match previous

Table 1

Effect	F	df_1	df_2	MSE	p	$\hat{\eta}^2_G$
Target	44.39	1	116	873.80	$< .001$	.277
Response	17.01	1	116	873.80	$< .001$	.128
Target × Response	8.91	1	116	873.80	.003	.071

reports of steeper search slopes for searching a circle among circles crossed by a line than for the inverse search (e.g., Treisman & Souther, 1985).

Discrimination task: metacognitive asymmetry

Mean accuracy in the discrimination task was 0.81 ($M = 0.81$, 95% CI [0.77, 0.84]). Participants showed no consistent bias in their responses ($M = 0.53$, 95% CI [0.48, 0.57]). On a scale of 0 to 1, mean confidence level was 0.56 ($M = 0.56$, 95% CI [0.47, 0.64]). Confidence was higher for correct than for incorrect responses ($M_d = 0.15$, 95% CI [0.09, 0.21], $t(29) = 5.24$, $p < .001$).

Q responses were similar to detection "stimulus presence" responses in several ways. First, response times were faster for Q than for O responses ($M_d = -149.38$, 95% CI [-241.39, -57.38], $t(29) = -3.32$, $p = .002$). Second, confidence was generally higher for Q responses ($M_d = 0.10$, 95% CI [0.05, 0.16], $t(29) = 3.63$, $p = .001$). Lastly, in order to measure metacognitive asymmetry, we extracted the response-conditional type-2 ROC (rc-ROC) curves for the two responses (Q and O) in the discrimination task. This was done by plotting the cumulative distribution of confidence ratings (high to low) for correct responses against the same distribution for incorrect responses. The area under the rc-ROC curve (auROC) was then taken as a measure of metacognitive sensitivity (Kanai et al., 2010; Meuwese et al., 2014). This analysis was available only for those participats that had at least



Figure 3. A: Median search time by distractor set size for the two search tasks and two responses. Correct responses only. Error bars represent the standard error of the median. B: mean search slope per target (Q or O) and response (present or absent). Error bars represent the standard error of the mean.

one of each error type (Q miskaen for O and vice versa). Indeed, auAUC for Q responses ($M = 0.67$, 95% CI [0.61, 0.74]) was significantly higher than for O responses ($M = 0.59$, 95% CI [0.53, 0.65]; $t(20) = 2.15$, $p = .044$; Cohen's d = 0.47; see Figure 4.), mirroring the metacognitive asymmetry for detection judgments.

Similar to Vincent (2011), we observed shallow standardized ROC (zROC) curves ($M = 0.69$ $t(29) = -6.70$, $p < .001$ for a t test on the log slopes). Shallow zROC curves are typical of situations where the signal distribution for one category is broader than for the other (Kellij et al., 2018; Vincent, 2011).



Figure 4. response conditional ROC curves for the two discrimination responses. The area under the curve is a measure of metacognitive sensitivity. Bottom right inset: distributions of the area under the curve for the two responses, across participants. Overall, participants had lower metacognitive insight into the accuracy of their "O" responses.

Pilot Experiment 2

Go/No-go task: response inhibition.

Participants

A total of 30 participants were recruited from Prolific. Participants were Native English Speakers and had a minimum approval rate of 0.9. They were paid £0.50 for their participation, in addition to a bonus payment of up to £0.32. The experiment took 4 minutes to complete.

Experimental design

On each trial, participants were presented with a fixation cross (500 ms) followed by one of two shapes (500 ms). They were asked to respond with a key press within 500 ms to one shape ("go" trials), but not to the other ("no-go" trials). Participants were awarded a point for responding on "go" trials and for not responding on "no-go" trials. Points were later translated to a bonus payment with a conversion rate of £0.0025 per point. .

After Reading the information sheet and signing the consent form, participants were instructed about the task. In the following practice part, participants had 8 practice trials in which they responded to a club, but not to a heart. The practice block was followed by a verbal comprehension test ("Please describe the task in your own words"), which was followed by the main task.

The main task consisted of 128 trials, separated into four blocks of 32 trials each. In two blocks, participants responded to the appearance of a ring intersected by a line, but not to the appearance of a ring. In the other two blocks, participants responded to the appearance of a ring, but not to the appearance of a ring intersected by a line. The order of blocks was interleaved. The first block was chosen at random with 50% probability.

Exclusion

Participants were excluded for performing below chance and for failing the comprehension check. After exclusion, we had datasets from 30 participants.

Results

Overall accuracy was very high ($M = 0.93$, 95% CI [0.90, 0.96]).

Accuracy was higher for blocks in which a response was required for Q ($M = 0.94$, 95% CI [0.91, 0.98]) than for O ($M = 0.92$, 95% CI [0.89, 0.95]; $M_d = 0.02$, 95% CI [0.01, 0.04], $t(29) = 3.19$, $p = .003$; see Fig. 5).

No difference was observed between the reaction times for the two block types (median reaction time in Q-target blocks 358.39; median reaction time in O-target blocks: 370.75; t-test on the log-transformed reaction times: $M = 0.00$ 95% HDI $[-0.02, 0.02]$, $\mathrm{BF}_{01} = 4.53$).



Figure 5. Accuracy as a function of target in the Go/No-go task.

Pilot Experiment 3

Change Detection

Participants

A total of 38 participants were recruited from Prolific. Participants were Native English Speakers and had a minimum approval rate of 0.95. They were paid £0.63 for their

participation, in addition to a bonus payment of up to £0.32 (average bonus paid: £0.28). The experiment took 5 minutes to complete.

Experimental design

On each trial, participants were presented with an array of randomly positioned stimuli (500 ms). All stimuli belonged to one of two classes (for example, the letters "O" and "Q"). The array disappeared from the screen for an interval of 900 ms, and then reappeared. On half of the trials, the second array was the identical to the first array, and on the other half one stimulus changed between the first and second arrays. Participants were instructed to press "J" if they detected a change, or "F" if they believed no change has taken place. There was no time pressure on making a response. Points were awarded for correct responses, and points were later translated to a bonus payment with a conversion rate of £0.005 per point.

After Reading the information sheet and signing the consent form, participants were instructed about the task. A practice part included 4 trials in which participants detected a change in an array of 3 Xs and Ws (two Xs and one W or vice versa). The practice part ended once three out of four trials were answered correctly, otherwise an additional practice block was delivered. The practice block was followed by an explanation about the scoring system and bonus payment. Then, the main part of the experiment started.

The main task consisted of 64 trials, separated into four blocks of 16 trials each. The two stimulus classes used for the main experiment were the letters Q (feature positive) and O (feature negative). The number of stimuli on the screen was odd in all trials, and the difference between the number of Os and Qs was always one, for both the first and the second display. Change trials were classified into two conditions: feature addition (O to Q) and deletion (Q to O). No-change trials were classified into the same two classes based on the contents of the first display: if the first display contained more Os, the trial was classified as a no-addition trial, and if there were more Qs, the trial was classified as a no-deletion

trial. Each block included all possible combinations of our three experimental factors: change (yes or no), condition (addition or deletion), and set-size. For a first batch of 8 participant, set sizes were 1,3,5,7,9 and 11. For the remaining 30 participants, set sizes were 1,3,5, and 7. Trials with set size 1 were used as attention checks, and were not included in the main analysis.

Exclusion

Participants were excluded for performing below 80% in trials with set size 1, or for responding too quickly (RT<250 ms) or too slowly (RT>5 sec) in more than 25% of the trials. After exclusion, we had datasets from 38 participants.

Results

Overall accuracy was around 75% ($M = 0.75$, 95% CI [0.72, 0.79]). Accuracy was significantly higher for addition trials than for deletion trials ($M_d = 0.05$, 95% CI [0.01, 0.09], $t(37) = 2.65$, $p = .012$). Analysis of variance revealed a marginally significant interaction of this effect with set-size ($F(1.73, 63.87) = 2.97$, $MSE = 0.05$, $p = .066$, $\hat{\eta}^2_G = .011$). No interaction was observed between addition/deletion and the presence of change ($F(1, 37) = 0.50$, $MSE = 0.03$, $p = .482$).



Figure 6. Accuracy in the change detection task as a function of condition (feature addition or deletion) and set size. Error bars represent the standard error of the mean.



Figure 7. Hit-rate in the change detection task (accuracy in change trials only) as a function of condition (feature addition or deletion) and set size. Error bars represent the standard error of the mean.