



# DATAWAY

## FIBER OPTIC CABLE

# DATAWAY Fiber Optic Drop Cable 4-Fiber, G.657A2, PE, 3.0 mm

Bend-insensitive singlemode drop cable for FTTH/FTTx subscriber access and building cabling.

### Product Identity

BRAND

**DATAWAY**

PART NO.

**DW-O-D-C-A2-PE-1000**

EAN

**8586026270020**



### Overview

DATAWAY fiber optic drop cable is designed for FTTH and FTTx access links, combining bend-insensitive G.657A2 fiber with compact cable construction for indoor, outdoor or aerial subscriber connections depending on the jacket type.

### Key Features

- 4-fiber construction for FTTH drop and access cabling
- G.657A2 bend-insensitive singlemode fiber
- PE jacket for structured cabling installation
- 1000 m supply length
- Suitable for customer drops, building entry and passive optical access networks

# Technical Specifications

DATAWAY Fiber Optic Drop Cable 4-Fiber, G.657A2, PE, 3.0 mm

| Ordering Information |  | Specification       |
|----------------------|--|---------------------|
| Part Number          |  | DW-O-D-C-A2-PE-1000 |
| SKU                  |  | 12513               |
| EAN                  |  | 8586026270020       |

| Cable Construction |  | Specification |
|--------------------|--|---------------|
| Fiber count        |  | 4             |
| Fiber type         |  | G.657A2       |
| Jacket             |  | PE            |
| Cable diameter     |  | 3.0 mm        |
| Package length     |  | 1000 m        |
| Cable type         |  | DROP          |

| Mechanical / Performance |  | Specification       |
|--------------------------|--|---------------------|
| Tension, short term      |  | 700                 |
| Tension, long term       |  | 240                 |
| Crush, short term        |  | 700                 |
| Crush, long term         |  | 300                 |
| Operating temperature    |  | -5 to +40 degrees C |
| Reaction to fire class   |  | Eca                 |

| Published Product Parameters |  | Specification       |
|------------------------------|--|---------------------|
| Package length               |  | 1000 m              |
| Crush, long term             |  | 300                 |
| Crush, short term            |  | 700                 |
| Weight                       |  | 8.7                 |
| Temperature                  |  | -5 to +40 degrees C |
| Connector                    |  | SC                  |