



DATAWAY

FIBER OPTIC PLC SPLITTER

DATAWAY PLC Splitter 1 x 32, 0.9 mm, G.657A1, SC/APC

Mini-module PLC optical splitter for FTTH/FTTx passive optical distribution networks.

Product Identity

BRAND

DATAWAY

PART NO.

DW-PLC-1X32-SCA-SCA

EAN

8586026273182



Overview

DATAWAY PLC splitter is designed for passive optical network signal distribution from one input fiber to multiple output fibers. The mini-module format supports compact installation in ODF, splice closures, distribution boxes and FTTH access networks.

Key Features

- 1 x 32 optical splitting configuration
- G.657A1 bend-insensitive singlemode fiber
- SC/APC termination option
- Compact MINI steel module construction
- Broad 1260-1650 nm operating wavelength range

Technical Specifications

DATAWAY PLC Splitter 1 x 32, 0.9 mm, G.657A1, SC/APC

Ordering Information	Specification
Part Number	DW-PLC-1X32-SCA-SCA
SKU	632
EAN	8586026273182

Optical / Construction	Specification
Splitter type	PLC splitter, 1 x 32
Connector	SC / APC
Construction	MINI STEEL modul
Fiber type	G.657A1
Fiber diameter	0.9 mm
Operating wavelength	1260-1650 nm

Application / Performance	Specification
Network type	FTTH/FTTx passive optical network
Operating temperature	-40 to +85 degrees C
Installation	ODF, distribution box, splice closure or access network cabinet
Reference insertion loss	<= 17.2 dB reference
Return loss	APC >= 60 dB reference when connectorized

Published Product Parameters	Specification
Split ratio	1 x 32
Connector	SC / APC
Construction	MINI STEEL modul
Fiber type	G.657A1
Operating wavelength	1260-1650 nm
Operating temperature	-40 to +85 degrees C