


DATAWAY PRODUCT DATA SHEET			
U/FTP Cat 6A Copper Cables for Indoor Applications			
Type	U/FTP CAT6A 4*2*23AWG LSZH		
Application			
Suitable for structured premises cabling			
For transmission of digital and analogue voice and data signals.			
Especially suitable for all Class E _A applications.			
ISDN,Ethernet 10 Base-T,Fast Ethernet 100 Base-T,Gigabit Ethernet 1000Base-T ,10G Base-T.(IEEE 802.3)			
Token Ring4/16Mbit/s,TP-PMD/TP/DDI 125Mbit/s,ATM 155Mbit/s.(IEEE 802.5)			
Standard			
IEC 61156-5			
ANSI/TIA-568.2-D			
ISO/IEC 11801			
Construction			
Conductors	Material	-----	Solid Bare Copper
	Conductors Size	mm	0.56+/-0.01
Insulation	Material	-----	PE(Skin-Foam-Skin)
	Diameter	mm	1.32+/-0.05
	Average Thickness	mm	0.38+/-0.05
Cabling	Direction	-----	S
	No. of Insulation	Pair	4
Shielding	Material	-----	Al-Foil Screened
Drain wire	Material	-----	26AWG TC
Jacket	Material	-----	LSZH
	Diameter	mm	7.5+/-0.3
	Average Thickness	mm	0.63+/-0.1
	Flame Rate	-----	EN50575 B2ca

Electrical characteristics								
1.Impedance	4 - 100MHz 100±15 (ohms)		5.Transfer Impedance		Max1000 mohms/m@100MHz			
	100 - 200MHz 100±22 (ohms)		6 Coupling Attenuation		55 dB			
	200 - 500MHz 100±32 (ohms)		7.Installation temperature		0~50℃			
2.Max. Conductor DC Resistance 20℃ 73.2(ohms/km)			8.Operation temperature			-20~60℃		
3.Resistance unbalance (%) Max 5								
4.Pair-to-Ground Capacitance Unbalance ≤330 (pF/100m)								
Nominal Transmission Characteristics								
Frequence	Min. RL	Max. IL	Max. PD	Max. SKEW	Min. NEXT	Min. PSNEXT	Min. ACR-F	Min. PSACR-F
(MHz)	(dB/100M)	(dB/100M)	(ns/100M)	(ns/100M)	(dB/100M)	(dB/100M)	(dB/100M)	(dB/100M)
4	23.0	3.8	552	45	65.3	63.3	55.8	52.8
8	24.0	5.3	546	45	60.8	58.8	49.7	46.7
10	25.0	5.3	545	45	59.3	57.3	47.8	44.8
16	25.0	7.5	543	45	56.2	54.2	43.7	40.7
20	25.0	8.4	542	45	54.8	52.8	41.8	38.8
31.25	23.6	10.5	540	45	51.9	49.9	37.9	34.9
62.5	21.5	15.0	539	45	47.4	45.4	31.9	28.9
100	20.1	19.1	538	45	44.3	42.3	27.8	24.8
200	18.0	27.6	537	45	39.8	37.8	21.8	18.8
300	16.8	34.3	536	45	37.1	35.1	18.3	15.3
400	15.9	40.1	536	45	35.3	33.3	15.8	12.8
500	15.2	45.3	536	45	33.8	31.8	13.8	10.8
construction:								
					core: P1: White/Blue-Blue P2: White/Orange-Orange P3: White/Green-Green P4: White/Brown-Brown			
Note: The above transmission performance for the 100M, 20 ± 2 °C under the conditions tested								