

Messaging-service API Documentation

Table of Contents

[CommunicationsResource](#)

-
- [POST /communications](#)
- [DELETE /communications/{communicationId}](#)
- [GET /communications/page/{pageNumber}/limit/{pageSize}](#)
- [GET /communications/{communicationId}](#)
- [POST /communications/search](#)
- [PUT /communications/{communicationId}](#)

[ConversationsResource](#)

-
- [POST /conversations](#)
- [DELETE /conversations/{conversationId}](#)
- [GET /conversations/page/{pageNumber}/limit/{pageSize}](#)
- [GET /conversations/{conversationId}](#)
- [POST /conversations/search](#)
- [PUT /conversations/{conversationId}](#)

[StatusResource](#)

-
- [POST /status](#)
- [DELETE /status/{statusId}](#)
- [GET /status/page/{pageNumber}/limit/{pageSize}](#)
- [GET /status/{statusId}](#)
- [POST /status/search](#)
- [PUT /status/{statusId}](#)

POST /communications

createCommunications (createCommunicationsUsingPOST)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

communications [Communications](#) (required)

Body Parameter — communications

Return type

EntityModel«Communications»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

201

Created [EntityModel«Communications»](#)

401

Unauthorized

403

Forbidden

404

Not Found

DELETE /communications/{communicationId}

deleteCommunications (deleteCommunicationsUsingDELETE)

Path parameters

communicationId (required)

Path Parameter — communicationId

Return type

Object

Example data

Content-Type: application/json

```
"{}"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [Object](#)

204

No Content

401

Unauthorized

403

Forbidden

GET /communications/page/{pageNumber}/limit/{pageSize}

retrieveAllCommunications (retrieveAllCommunicationsUsingGET)

Path parameters

pageNumber (required)

Path Parameter — pageNumber format: int32

pageSize (required)

Path Parameter — pageSize format: int32

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK

206

Partial Content [CollectionModel«List«Communications»»](#)

401

Unauthorized

403

Forbidden

404

Not Found

GET /communications/{communicationId}

retrieveCommunications (retrieveCommunicationsUsingGET)

Path parameters

communicationId (required)

Path Parameter — communicationId

Return type

EntityModel«Communications»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [EntityModel«Communications»](#)

401

Unauthorized

403

Forbidden

404

Not Found

POST /communications/search

searchForCommunications (searchForCommunicationsUsingPOST)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

search [object](#) (required)

Body Parameter — search

Return type

CollectionModel<List<Communications>>

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [CollectionModel<List<Communications>>](#)

201

Created

401

Unauthorized

403

Forbidden

404

Not Found

PUT /communications/{communicationId}

updateCommunications (updateCommunicationsUsingPUT)

Path parameters

communicationId (required)

Path Parameter — communicationId

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

communications [Communications](#) (required)

Body Parameter — communications

Return type

Object

Example data

Content-Type: application/json

```
"{}"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [Object](#)

201

Created

401

Unauthorized

403

Forbidden

404

Not Found

ConversationsResource

POST /conversations

createConversations (createConversationsUsingPOST)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

conversations [Conversations](#) (required)

Body Parameter — conversations

Return type

EntityModel«Conversations»

Example data

Content-Type: application/json

```
" "
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

201

Created [EntityModel«Conversations»](#)

401
Unauthorized
403
Forbidden
404
Not Found

DELETE /conversations/{conversationId}

deleteConversations (deleteConversationsUsingDELETE)

Path parameters

conversationId (required)
Path Parameter — conversationId

Return type

Object

Example data

Content-Type: application/json

```
"{}"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200
OK [Object](#)
204
No Content
401
Unauthorized
403
Forbidden

GET /conversations/page/{pageNumber}/limit/{pageSize}

retrieveAllConversations (retrieveAllConversationsUsingGET)

Path parameters

pageNumber (required)
Path Parameter — pageNumber format: int32

pageSize (required)
Path Parameter — pageSize format: int32

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK

206

Partial Content [CollectionModel«List«Conversations»»](#)

401

Unauthorized

403

Forbidden

404

Not Found

GET /conversations/{conversationId}

retrieveConversations (retrieveConversationsUsingGET)

Path parameters

conversationId (required)

Path Parameter — conversationId

Return type

EntityModel«Conversations»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [EntityModel«Conversations»](#)

401

Unauthorized

403

Forbidden

404

Not Found

POST /conversations/search

searchForConversations (searchForConversationsUsingPOST)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

search [object](#) (required)

Body Parameter — search

Return type

CollectionModel«List«Conversations»»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [CollectionModel«List«Conversations»»](#)

201

Created

401

Unauthorized

403

Forbidden

404

Not Found

PUT /conversations/{conversationId}

updateConversations (updateConversationsUsingPUT)

Path parameters

conversationId (required)

Path Parameter — conversationId

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

conversations [Conversations](#) (required)

Body Parameter — conversations

Return type

Object

Example data

Content-Type: application/json

```
"{}"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200
OK [Object](#)
201
Created
401
Unauthorized
403
Forbidden
404
Not Found

StatusResource

POST /status

createStatus (createStatusUsingPOST)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

statuses [Status](#) (required)
Body Parameter — statuses

Return type

EntityModel«Status»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

201
Created [EntityModel«Status»](#)
401
Unauthorized
403
Forbidden
404
Not Found

DELETE /status/{statusId}

deleteStatus (deleteStatusUsingDELETE)

Path parameters

statusId (required)

Return type

Object

Example data

Content-Type: application/json

```
"{}"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [Object](#)

204

No Content

401

Unauthorized

403

Forbidden

GET /status/page/{pageNumber}/limit/{pageSize}

retrieveAllStatuses (retrieveAllStatusesUsingGET)

Path parameters

pageNumber (required)

Path Parameter — pageNumber format: int32

pageSize (required)

Path Parameter — pageSize format: int32

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK

206

Partial Content [CollectionModel«List«Status»»](#)

401

Unauthorized

403

Forbidden

404

Not Found

GET /status/{statusId}

retrieveStatus ([retrieveStatusUsingGET](#))

Path parameters

statusId (required)

Path Parameter — statusId

Return type

EntityModel«Status»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [EntityModel«Status»](#)

401

Unauthorized

403

Forbidden

404

Not Found

POST /status/search

searchForStatus ([searchForStatusUsingPOST](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

search [object](#) (required)

Body Parameter — search

Return type

CollectionModel«List«Status»»

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [CollectionModel«List«Status»»](#)

201

Created

401

Unauthorized

403

Forbidden

404

Not Found

PUT /status/{statusId}

updateStatus (updateStatusUsingPUT)

Path parameters

statusId (required)

Path Parameter — statusId

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

statuses [Status](#) (required)

Body Parameter — statuses

Return type

Object

Example data

Content-Type: application/json

```
"{}"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [Object](#)

201

Created

401

Unauthorized

403

Forbidden

404

Not Found
