

# **Data Structures**

Gabriel Istrate

May 13, 2024


Why did we want dynamic sets to start with ?

- To improve algorithms.
- First part of today: complete Computational geometry

Second part: Augmenting Data Structures (e.g. Red-Black Trees)

- What happens if a data structure doesn't support all the operations you want ?
- **Augment it**: modify it to support the new operations.
- Might need to add additional fields. These need to be maintained.

- **Convex hull of a set of points:** smallest convex polygon that contains the set of points.
- place elastic rubber band around set of points and let it shrink.
- Two algorithms: Graham's Scan  $O(n \log n)$ .
- Jarvis's March  $O(n \cdot h)$ ,  $h$  the number of points on the convex hull.
- Other algorithms:
- **Incremental:** points sorted from left to right forming sequence  $p_1, \dots, p_n$ . At stage  $i$  add  $p_i$  to convex hull  $CH(p_1, \dots, p_{i-1})$ , forming  $CH(p_1, \dots, p_i)$ .
- **Divide-and-conquer:** divide into leftmost  $n/2$  points and rightmost  $n/2$  points. Compute convex hulls and combine them.
- **Prune-and-search method.**



**Figure 33.6** A set of points  $Q = \{p_0, p_1, \dots, p_{12}\}$  with its convex hull  $\text{CH}(Q)$  in gray.


- Maintains a stack  $S$  of candidate points.
- Each point of  $Q$  is pushed onto the stack.
- Points not in  $CH(Q)$  eventually popped from the stack.
- $TOP(S)$ ,  $NEXT - TO - TOP(S)$ : stack functions, do not change its contents.
- Stack returned by the algorithm: points of  $CH(Q)$  in counterclockwise order.

# Convex hull algorithm

GRAHAM-SCAN( $Q$ )







- 1 let  $p_0$  be the point in  $Q$  with the minimum  $y$ -coordinate,  
or the leftmost such point in case of a tie
- 2 let  $\langle p_1, p_2, \dots, p_m \rangle$  be the remaining points in  $Q$ ,  
sorted by polar angle in counterclockwise order around  $p_0$   
(if more than one point has the same angle, remove all but  
the one that is farthest from  $p_0$ )
- 3 PUSH( $p_0, S$ )
- 4 PUSH( $p_1, S$ )
- 5 PUSH( $p_2, S$ )
- 6 **for**  $i \leftarrow 3$  **to**  $m$
- 7     **do while** the angle formed by points NEXT-TO-TOP( $S$ ), TOP( $S$ ),  
                  and  $p_i$  makes a nonleft turn
- 8         **do** POP( $S$ )
- 9         PUSH( $p_i, S$ )
- 10 **return**  $S$

# Graham's Scan: Example



**Figure 33.7** The execution of GRAHAM-SCAN on the set  $Q$  of Figure 33.6. The current convex hull contained in stack  $S$  is shown in gray at each step. (a) The sequence  $\langle p_1, p_2, \dots, p_{12} \rangle$  of points numbered in order of increasing polar angle relative to  $p_0$ , and the initial stack  $S$  containing  $p_0, p_1$ , and  $p_2$ . (b)–(k) Stack  $S$  after each iteration of the for loop of lines 6–9. Dashed lines show nonleft turns, which cause points to be popped from the stack. In part (h), for example, the right turn at angle  $\angle p_1 p_8 p_9$  causes  $p_8$  to be popped, and then the right turn at angle  $\angle p_6 p_7 p_9$  causes  $p_7$  to be popped. (l) The convex hull returned by the procedure, which matches that of Figure 33.6.

# Graham's Scan: Example






# Graham's Scan: Correctness and Performance


- Invariant: at the beginning of each iteration of the for loop stack  $S$  contains (from bottom to top) exactly the vertices of  $CH(Q_{i-1})$  in counterclockwise order.
- Line 1:  $\theta(n)$  time.
- Sorting  $\theta(n \log n)$  time.
- Testing for left/right turn: vector product  $\theta(1)$  time.
- The rest of the algorithm  $O(n)$  time.

# Graham's Scan: Correctness



**Figure 33.8** The proof of correctness of GRAHAM-SCAN. (a) Because  $p_i$ 's polar angle relative to  $p_0$  is greater than  $p_j$ 's polar angle, and because the angle  $\angle p_k p_j p_i$  makes a left turn, adding  $p_i$  to  $\text{CH}(Q_j)$  gives exactly the vertices of  $\text{CH}(Q_j \cup \{p_i\})$ . (b) If the angle  $\angle p_r p_i p_0$  makes a nonleft turn, then  $p_i$  is either in the interior of the triangle formed by  $p_0, p_r$ , and  $p_i$  or on a side of the triangle, and it cannot be a vertex of  $\text{CH}(Q_i)$ .

- uses a technique known as gift wrapping.
- Simulates wrapping a piece of paper around set  $Q$ .
- Start at the same point  $p_0$  as in Graham's scan.
- Pull the paper to the right, then higher until it touches a point. This point is a vertex in the convex hull. Continue this way until we come back to  $p_0$ .
- Formally: start at  $p_0$ . Choose  $p_1$  as the point with the smallest polar angle from  $p_0$ . Choose  $p_2$  as the point with the smallest polar angle from  $p_1 \dots$
- $\dots$  until we reached the highest point  $p_k$ .
- We have constructed the right chain.
- Construct the left chain by starting from  $p_k$  and measuring polar angles with respect to the negative x-axis.



**Figure 33.9** The operation of Jarvis's march. The first vertex chosen is the lowest point  $p_0$ . The next vertex,  $p_1$ , has the smallest polar angle of any point with respect to  $p_0$ . Then,  $p_2$  has the smallest polar angle with respect to  $p_1$ . The right chain goes as high as the highest point  $p_3$ . Then, the left chain is constructed by finding smallest polar angles with respect to the negative x-axis.

# Augmenting Data Structures

- What if no existing data structure fits your needs ?
- Invent a new one, or ...
- More realistic (in practice): **slightly modify a "standard" data structure to support more operations.**
- Done by **storing extra information in it**
- Not always straightforward: new information **must be updated and maintained** by D.S. operations.

# Augmenting Data Structures


Example: two data structures obtained by modifying red-black trees

- **First data structure:** supports **order statistics** queries on a dynamic set.
  - Find  $i$ 'th number in a set or the rank of an element.
- **Second data structure:** maintain a set of **intervals** (e.g. time intervals).
- Plus: **a general result about augmenting Data Structures.**

# Dynamic order statistics

- **Order statistic tree:** red-black tree with one extra field per node: **size of the subtree rooted at that node.**
- Thus fields: *key, color, p, left, right, size.*
- $size[nil[T]] = 0.$
- $size[x] = size[left[x]] + size[right[x]] + 1.$
- Supports **OS – SELECT**( $x, i$ ): return  $i$ 'th smallest element in the tree rooted at  $x$ .  $O(\log n)$  time.
- Supports **OS – RANK**( $T, x$ ): return the rank of  $x$  in the tree  $T$ .  $O(\log n)$  time.

# Order statistics tree





## Selecting $i$ 'th element

- If  $i = \text{size}[\text{left}(x)] + 1$  then (by *BST* property) node  $x$  is the  $i$ 'th element. Return  $x$ .
- If  $i \leq \text{size}[\text{left}(x)]$  then node is in  $\text{left}[x]$ .  $i$ 'th element. Call procedure recursively.
- If  $i > \text{size}[\text{left}(x)] + 1$  then node is in  $\text{right}[x]$ .  $i - \text{size}[\text{left}(x)]$ 'th element. Call procedure recursively.
- Running time: proportional to the height of the tree:  $O(\log n)$ .

OS-SELECT( $x, i$ )

1  $r \leftarrow \text{size}[\text{left}[x]] + 1$

2 **if**  $i = r$

3     **then return**  $x$

4 **elseif**  $i < r$

5     **then return** OS-SELECT( $\text{left}[x], i$ )

6 **else return** OS-SELECT( $\text{right}[x], i - r$ )

OS-RANK( $T, x$ )

1  $r \leftarrow \text{size}[\text{left}[x]] + 1$

2  $y \leftarrow x$

3 **while**  $y \neq \text{root}[T]$

4     **do if**  $y = \text{right}[p[y]]$

5         **then**  $r \leftarrow r + \text{size}[\text{left}[p[y]]] + 1$

6          $y \leftarrow p[y]$

7 **return**  $r$


# Rank of an element

- Perform inorder traversal.
- Return rank of node  $x$  in this traversal.
- Move pointer  $y$  from  $x$  up towards  $root(T)$ .
- Maintains the following invariant: at the start of each iteration of the while loop,  $r$  is the rank of  $key[x]$  in the subtree rooted at  $y$ .
- If  $y$  is a right child, add the size of its left child to the count.
- Each iteration:  $O(1)$  time.  $y$  goes up the tree, time complexity  $O(\log n)$ .

# Maintaining subtree sizes: Insertion.

- During LEFT/RIGHT rotations.
- INSERTION. First phase: go from the root to the frontier, inserting the new node as the child of an existing node. new node gets size of 1. Each node from  $x$  to the path: size increases by 1.  $O(\log n)$ .
- Second phase: go up the tree, changing colors, and maintaining the red-black property by rotations.
- Second phase: changes via LEFT/RIGHT rotations.
- LEFT-ROTATE: add lines
  - $size[y] \leftarrow size[x]$ .
  - $size[x] \leftarrow size[left[x]] + size[right[x]] + 1$ .
- to rotation pseudocode.
- RIGHT-ROTATE: symmetric.

# Maintaining *size* during rotations.



## Maintaining subtree sizes: Deletion.

- DELETION: two phases.
- First phase: delete node. Update tree size on the path from the node to the top. Decrement by 1 for each node.
- Rotations: as for insertion.

# How to augment a data structure

- Four steps:
- 1. Choose underlying data structure.
- 2. Determine additional information to be maintained.
- 3. Verify that additional information can be maintained in the D.S. operations.
- 4. develop new operations required by new fields.



## How to augment a data structure (II)

1. Choose red-black trees. Clue: supports other dynamic set operations on total order: MINIMUM, MAXIMUM, SUCCESSOR, PREDECESSOR.
2. We didn't need field size to implement OS-SELECT, OS-RANK, but then operations wouldn't run in  $O(\log n)$  time. Additional information to be maintained: sometimes pointer rather than data.
3. Ideally only a few elements need to be updated to maintain D.S. E.g. if we simply stored in each node its rank in the tree then OS-SELECT and OS-UPDATE would be efficient but inserting a smallest node causes changes in the whole tree.
4. Developed OS-SELECT, OS-RANK. Occasionally, instead of new operations, speed-up old ones.

# Augmenting red-black trees


## Theorem

Let  $f$  be a field that augments a RB tree of  $n$  nodes, and *suppose the contents of  $f$  for node  $x$  can be computed in  $O(1)$  using only information in node  $x$ ,  $\text{left}[x]$  and  $\text{right}[x]$ , including  $f[\text{left}[x]]$  and  $f[\text{right}[x]]$ .* Then *we can maintain the values of  $f$  in all nodes in  $T$  during insertion and deletion without asymptotically affecting  $O(\log n)$  performance.*

Proof idea: change in field  $f$  at a node  $x$  propagates only to ancestors of  $x$  in the tree.

- closed interval:  $[t_1, t_2]$ . Also open, half-open intervals.
- $i = [t_1, t_2]$ .  $low[i] = t_1$ ,  $high[i] = t_2$ .
- $i$  and  $i'$  overlap if  $i \cap i' \neq \emptyset$ . That is  $low[i] \leq high[i']$  and  $low[i'] \leq high[i]$ .
- Want: Data structure representing a dynamic set of intervals.
- Must support the following operations:
- *INTERVAL – INSERT*( $T, x$ ): adds element  $x$ , whose *int* field contains an interval.
- *INTERVAL – DELETE*( $T, x$ ): removes element  $x$  from  $T$ .
- *INTERVAL – SEARCH*( $T, i$ ): return pointer to an element  $x$  such that  $int[x]$  overlaps  $i$ , or *nil* if no such element found.


- Any two intervals satisfy **interval trichotomy**: three alternatives:
  - $i$  and  $i'$  overlap.
  - $i$  is to the left of  $i'$  ( $high[i] < low[i']$ ).
  - $i$  is to the right of  $i'$  ( $low[i] > high[i']$ ).



**Figure 14.3** The interval trichotomy for two closed intervals  $i$  and  $i'$ . (a) If  $i$  and  $i'$  overlap, there are four situations; in each,  $low[i] \leq high[i']$  and  $low[i'] \leq high[i]$ . (b) The intervals do not overlap, and  $high[i] < low[i']$ . (c) The intervals do not overlap, and  $high[i'] < low[i]$ .

# Interval trees: Implementation

1. Possible clue: **intervals (partial) ordering**. Might try to modify a total order. Then **red-black tree**. Each node  $x$  stores an interval  $int[x]$ .
  - $key[x] = low[int[x]]$ .
2. Additional info:  $max[x]$ , the maximum value of any endpoint of an interval stored in the subtree rooted at  $x$ .
3. Maintain info:  $max[x] = \max(high[int[x]], max[left[x]], max[right[x]])$ .
4. By applying previous theorem: insertion/deletion  $O(\log n)$  while maintaining  $max[x]$ .



- finds a node in tree  $T$  whose interval overlaps interval  $i$ , returns sentinel node  $nil[T]$  if no overlapping interval found.
- Search starts at the root and proceeds downwards.
- Chooses *left* or *right* subtree based on the maximum element in the left subtree of  $x$ .
- If  $max[left[x]]$  is  $\geq low[i]$  (of course,  $left[x] \neq nil[T]$ ) go left.
- otherwise go right.
- takes  $O(\log n)$  time since each basic loop takes  $O(1)$  time and the height of the RB tree is  $O(\log n)$ .

INTERVAL-SEARCH( $T, i$ )

```
1   $x \leftarrow \text{root}[T]$ 
2  while  $x \neq \text{nil}[T]$  and  $i$  does not overlap  $\text{int}[x]$ 
3      do if  $\text{left}[x] \neq \text{nil}[T]$  and  $\text{max}[\text{left}[x]] \geq \text{low}[i]$ 
4          then  $x \leftarrow \text{left}[x]$ 
5          else  $x \leftarrow \text{right}[x]$ 
6  return  $x$ 
```



# Correctness of INTERVAL-SEARCH

- Why is it enough to examine a single path ?
- Idea: search proceeds in a "safe direction".
- INVARIANT: If tree  $T$  contains an interval that overlaps  $i$  then there is such an interval in the subtree rooted at  $x$ .
- Initialization: clearly satisfied,  $x = \text{root}[T]$ .
- Either line 4 or line 5 executed.
- Line 5 executed: because  $\text{left}[x] = \text{nil}[T]$  or  $\max[\text{left}[x]] < \text{low}[i]$ . The subtree rooted at  $\text{left}[x]$  does not contain any interval that overlaps  $i$ .
- If such an interval is found in  $T$ , it must be in  $\text{right}[x]$ .

# Correctness of INTERVAL-SEARCH

- Line 4 executed: contrapositive of loop invariant holds.
- If there is no such an interval in the subtree rooted at  $left[x]$  then there is no such interval in tree  $T$ .
- Since line 4 executed  $max[left[x]] \geq low[i]$ . There exists  $i'$  with  $high[i'] = max[left[x]] \geq low[i]$ .
- $i$  and  $i'$  do not overlap, by assumption. By trichotomy  $high[i] < low[i']$ .
- $i''$  interval in  $right[x]$ . Intervals keyed on the low endpoints.
- $high[i] < low[i'] \leq low[i'']$ .
- Conclusion: no interval in  $right[x]$  (and thus in  $T$ ) overlaps  $i$ .

## Outline:

- Search in secondary storage
- B-Trees
  - ▶ properties
  - ▶ search
  - ▶ insertion

# Complexity Model

# Complexity Model

- Basic assumption so far: *data structures fit completely in main memory (RAM)*
  - ▶ all basic operations have the same cost
    - ▶ even this is a rough approximation, since the main-memory system is not at all “flat”

# Complexity Model

- Basic assumption so far: *data structures fit completely in main memory (RAM)*
  - ▶ all basic operations have the same cost
    - ▶ even this is a rough approximation, since the main-memory system is not at all “flat”
- However, some applications require more storage than what fits in main memory
  - ▶ we must use data structures that reside in *secondary storage* (i.e., disk)

# Complexity Model

- Basic assumption so far: *data structures fit completely in main memory (RAM)*
  - ▶ all basic operations have the same cost
    - ▶ even this is a rough approximation, since the main-memory system is not at all “flat”
- However, some applications require more storage than what fits in main memory
  - ▶ we must use data structures that reside in *secondary storage* (i.e., disk)

***Disk is 10,000–100,000 times slower than RAM***






- In a balanced *binary* tree,  $n$  keys require a tree of height  $h = \lfloor \log_2 n \rfloor$ 
  - ▶ all the important operations require access to  $O(h)$  nodes
  - ▶ each one accounting for *one or very few* basic operations

- In a balanced *binary* tree,  $n$  keys require a tree of height  $h = \lfloor \log_2 n \rfloor$ 
  - ▶ all the important operations require access to  $O(h)$  nodes
  - ▶ each one accounting for *one or very few* basic operations
- **Idea:** store several keys and pointers to children nodes in a single node


- In a balanced *binary* tree,  $n$  keys require a tree of height  $h = \lfloor \log_2 n \rfloor$ 
  - ▶ all the important operations require access to  $O(h)$  nodes
  - ▶ each one accounting for *one or very few* basic operations
- **Idea:** store several keys and pointers to children nodes in a single node
  - ▶ in practice we **increase the degree** (or *branching factor*) of each node up to  $d > 2$ , so  $h = \lfloor \log_d n \rfloor$ 
    - ▶ in practice  $d$  can be as high as a few thousands

- In a balanced *binary* tree,  $n$  keys require a tree of height  $h = \lfloor \log_2 n \rfloor$ 
  - ▶ all the important operations require access to  $O(h)$  nodes
  - ▶ each one accounting for *one or very few* basic operations
- **Idea:** store several keys and pointers to children nodes in a single node
  - ▶ in practice we **increase the degree** (or *branching factor*) of each node up to  $d > 2$ , so  $h = \lfloor \log_d n \rfloor$ 
    - ▶ in practice  $d$  can be as high as a few thousands




E.g., if  $d = 1000$ , then  
**only three accesses** ( $h = 2$ )  
cover **up to one billion keys**

# Definition of a B-Tree




# Definition of a B-Tree



- Every node  $x$  has the following fields
  - ▶  $x.n$  is the number of keys stored at each node


# Definition of a B-Tree



■ Every node  $x$  has the following fields

- ▶  $x.n$  is the number of keys stored at each node
- ▶  $x.key[1] \leq x.key[2] \leq \dots x.key[x.n]$  are the  $x.n$  keys stored in nondecreasing order

# Definition of a B-Tree




■ Every node  $x$  has the following fields

- ▶  $x.n$  is the number of keys stored at each node
- ▶  $x.key[1] \leq x.key[2] \leq \dots x.key[x.n]$  are the  $x.n$  keys stored in nondecreasing order
- ▶  $x.leaf$  is a Boolean flag that is **TRUE** if  $x$  is a *leaf node* or **FALSE** if  $x$  is an *internal node*




# Definition of a B-Tree




■ Every node  $x$  has the following fields

- ▶  $x.n$  is the number of keys stored at each node
- ▶  $x.key[1] \leq x.key[2] \leq \dots x.key[x.n]$  are the  $x.n$  keys stored in nondecreasing order
- ▶  $x.leaf$  is a Boolean flag that is TRUE if  $x$  is a *leaf node* or FALSE if  $x$  is an *internal node*
- ▶  $x.c[1], x.c[2], \dots, x.c[x.n + 1]$  are the  $x.n + 1$  pointers to its children, if  $x$  is an *internal node*

## Definition of a B-Tree (2)




## Definition of a B-Tree (2)



- The keys  $x.key[i]$  delimit the ranges of keys stored in each subtree

## Definition of a B-Tree (2)



- The keys  $x.key[i]$  delimit the ranges of keys stored in each subtree

$x.c[1] \longrightarrow$  subtree containing keys  $k \leq x.key[1]$

$x.c[2] \longrightarrow$  subtree containing keys  $k, x.key[1] \leq k \leq x.key[2]$

$x.c[3] \longrightarrow$  subtree containing keys  $k, x.key[2] \leq k \leq x.key[3]$

$\dots$

$x.c[x.n + 1] \longrightarrow$  subtree containing keys  $k, k \geq x.key[x.n]$


## Definition of a B-Tree (3)

## Definition of a B-Tree (3)

- *All leaves have the same depth*

# Definition of a B-Tree (3)

- *All leaves have the same depth*
- Let  $t \geq 2$  be the *minimum degree* of the B-tree
  - ▶ every node other than the root must have *at least  $t - 1$  keys*
  - ▶ every node must contain *at most  $2t - 1$  keys*
    - ▶ a node is *full* when it contains exactly  $2t - 1$  keys
    - ▶ a full node has  $2t$  children







```
B-Tree-Search( $x, k$ )
1   $i = 1$ 
2  while  $i \leq x.n$  and  $k > x.key[i]$ 
3       $i = i + 1$ 
4  if  $i \leq x.n$  and  $k == x.key[i]$ 
5      return ( $x, i$ )
6  if  $x.leaf$ 
7      return NIL
8  else Disk-Read( $x.c[i]$ )
9      return B-Tree-Search( $x.c[i], k$ )
```

# Height of a B-Tree

# Height of a B-Tree

- **Theorem:** the height of a B-tree containing  $n \geq 1$  keys and with a minimum degree  $t \geq 2$  is

$$h \leq \log_t \frac{n+1}{2}$$

# Height of a B-Tree

- **Theorem:** the height of a B-tree containing  $n \geq 1$  keys and with a minimum degree  $t \geq 2$  is

$$h \leq \log_t \frac{n+1}{2}$$

*Proof:*

- ▶  $n \geq 1$ , so the root has at least one key (and therefore two children)

# Height of a B-Tree

- **Theorem:** the height of a B-tree containing  $n \geq 1$  keys and with a minimum degree  $t \geq 2$  is

$$h \leq \log_t \frac{n+1}{2}$$

*Proof:*

- ▶  $n \geq 1$ , so the root has at least one key (and therefore two children)
- ▶ every other node has at least  $t$  children

# Height of a B-Tree

- **Theorem:** the height of a B-tree containing  $n \geq 1$  keys and with a minimum degree  $t \geq 2$  is

$$h \leq \log_t \frac{n+1}{2}$$

*Proof:*

- ▶  $n \geq 1$ , so the root has at least one key (and therefore two children)
- ▶ every other node has at least  $t$  children
- ▶ in the worst case, there are two subtrees (of the root) each one containing a total of  $(n-1)/2$  keys, and each one consisting of  $t$ -degree nodes, with each node containing  $t-1$  keys

- **Theorem:** the height of a B-tree containing  $n \geq 1$  keys and with a minimum degree  $t \geq 2$  is

$$h \leq \log_t \frac{n+1}{2}$$

*Proof:*

- ▶  $n \geq 1$ , so the root has at least one key (and therefore two children)
- ▶ every other node has at least  $t$  children
- ▶ in the worst case, there are two subtrees (of the root) each one containing a total of  $(n-1)/2$  keys, and each one consisting of  $t$ -degree nodes, with each node containing  $t-1$  keys
- ▶ each subtree contains  $1 + t + t^2 \cdots + t^{h-1}$  nodes, each one containing  $t-1$  keys



- **Theorem:** the height of a B-tree containing  $n \geq 1$  keys and with a minimum degree  $t \geq 2$  is

$$h \leq \log_t \frac{n+1}{2}$$

*Proof:*

- ▶  $n \geq 1$ , so the root has at least one key (and therefore two children)
- ▶ every other node has at least  $t$  children
- ▶ in the worst case, there are two subtrees (of the root) each one containing a total of  $(n-1)/2$  keys, and each one consisting of  $t$ -degree nodes, with each node containing  $t-1$  keys
- ▶ each subtree contains  $1 + t + t^2 \cdots + t^{h-1}$  nodes, each one containing  $t-1$  keys, so

$$n \geq 1 + 2(t^{h-1} - 1)$$