Foundational Requirements for Artificial General Intelligence: A Falsifiable Framework Based on Signal Prediction

Matej Šprogar
University of Maribor, Faculty of Electrical Engineering and Computer Science, Maribor, Slovenia
matej.sprogar@um.si

***Abstract*—Grounded in the premise that high-level intelligence can emerge from low-level signal processing, we advance a hypothesis regarding low-level requirements necessary for artificial general intelligence. The proposed requirements characterise core properties of systems that learn through prediction over spatially and temporally structured signals with initially unknown semantic content. They include a selection of basic principles observed in cognitive neuroscience, from learning from an uninformed state to real-time liveness.**

To enable empirical testing and hypothesis rejection, we introduce an operational testbed composed of transparent and reusable tests, one per requirement. The testbed is not foolproof: non-intelligent systems engineered with knowledge of its design can pass it by exploiting benchmark-specific properties that a transparent testbed is inherently unable to detect. Failing a test exposes a violation of a requirement, whereas passing the testbed is meaningful only for systems developed without knowledge of the individual tests. The testbed therefore serves as a necessary-condition filter rather than as proof of progress toward general intelligence. The reference implementation of the testbed is publicly available.

***Index Terms*—artificial general intelligence, predictive processing, temporal prediction, pattern recognition, symbol grounding**

I. Introduction

Intelligence remains one of the deepest unresolved questions in science, as we still lack both a precise definition of intelligence and an understanding of its fundamental components [1], [2], [3]. Assuming there is such a thing as general intelligence, one major obstacle to creating artificial general intelligence (AGI) is the limited understanding of how biological brains operate. At the same time, modern artificial intelligence (AI) systems achieve impressive performance across a wide range of tasks [4]. However, such performance is often achieved without a principled account of understanding and may not reflect broadly general capabilities [5], [6], [7].

Until we discover the secret behind general intelligence, our models can only aim to simulate the observable behaviour it produces. As a result, modern AI conflates specialised competence with general intelligence [8], [9], [10]. Systems optimised for a narrow class of tasks may perform extremely well within that domain while remaining brittle or ineffective elsewhere.

The existing definitions and descriptions of intelligent behaviour are useless for AGI development because they are either vague, self-referential, or non-general. However valuable modern AI is, maybe AGI is not achievable by targeting a high-level behaviour on a predefined task. Maybe we should focus on the low-level behaviours necessary for the emergence of general intelligent behaviour. This perspective is motivated in part by observations from biological neural systems, whose operation is often described in terms of continuous streams of sensory signals rather than discrete symbolic[1] representations [12], [13]. Working directly with low-level signals offers a way to avoid assuming pre-existing semantic structure and allows us to propose testable, operational requirements for the emergence of intelligent behaviour.

In this paper, we identify requirements hypothesised to be necessary but not sufficient for general intelligence, and formalise them as architecture-agnostic criteria. Although each requirement can be satisfied individually by specialised systems, complexity arises from their interaction; consequently, the challenge lies in satisfying them simultaneously. We propose twelve requirements as a minimal set hypothesised to capture the essential conditions for general intelligence.

Because intelligence lacks a precise definition, the hypothesis cannot be directly verified and is therefore formulated in a falsifiable manner. To this end, we introduce the Artificial General Intelligence Testbed (AGITB), which evaluates whether a system under test satisfies all proposed requirements. Successfully passing the testbed does not, by itself, establish the presence of general intelligence. However, the existence of a non-intelligent system that satisfies all requirements would falsify the hypothesis. Because the tests are transparent, a system can also be engineered to pass them without satisfying the requirements they approximate; passing the AGITB is therefore meaningful only for systems that were not designed with knowledge of the individual tests. Failing it, by contrast, indicates that a system remains limited to narrow or specialised capabilities.

The originality of this work lies not in any individual component considered in isolation, but in the synthesis of minimal, low-level, architecture-independent behavioural requirements. Formalising these requirements enabled the construction of a

[1]Symbolic representations introduce an additional complication known as the symbol grounding problem, in which symbolic tokens require grounding in perception or environmental interaction to acquire intrinsic semantic meaning [11].

transparent, reusable testbed for the empirical evaluation of experimental AGI systems, thereby addressing a longstanding methodological gap in the field.

II. Relationship to Prior Research

The present work intersects several established research traditions, including predictive processing and predictive coding in computational neuroscience [14], [12], continual and sequence learning [15], [16], and formal theories of intelligence [17], [18]. However, to our knowledge, no existing framework combines the specific set of objectives pursued here within a single operational, falsifiable system.

Conceptually, the framework is most closely aligned with predictive-processing accounts of cognition, in which intelligent behaviour emerges through continual prediction over temporally structured input streams [19], [12]. Related ideas also appear in sequence-memory approaches such as Hierarchical Temporal Memory [16], where prediction and temporal state evolution are treated as central computational primitives. Existing approaches of this kind, however, are primarily architectural or neurocomputational proposals rather than attempts to derive architecture-independent necessary conditions for general intelligence.

At a more abstract level, the work also relates to formal theories of intelligence, including universal intelligence and AIXI-style formulations [17], [18], which similarly seek principled characterisations of intelligence from minimal assumptions. Unlike the present work, however, these approaches do not operationalise their assumptions as architecture-independent, falsifiable criteria for empirical evaluation.

Our approach further differs from contemporary benchmark-oriented paradigms for evaluating intelligence, including task-generalisation benchmarks such as ARC [20]. Modern machine-learning evaluations are typically constructed around finite test distributions, with hidden or periodically refreshed datasets intended to limit optimisation toward the evaluation itself. By contrast, the proposed testbed does not rely on benchmark secrecy; instead, it introduces transparent, comprehensible tasks. Success depends on satisfying the underlying behavioural constraints across combinatorially large input spaces rather than on reproducing finite hidden test distributions. The price of transparency is that the tests can be studied and targeted: a system designed around them can pass without possessing the capabilities they are meant to probe (Section VII-D).

III. Background

Contemporary artificial systems do not yet robustly exhibit behaviour indistinguishable from that of humans. One possible research direction towards that goal involves closer alignment with the computational principles observed in the human cortex, motivating interest in neuromorphic approaches such as spiking neural networks, which explicitly incorporate time-sensitive, event-driven computation [21], [22]. While such architectures do not, in themselves, constitute general intelligence, they highlight alternative design dimensions that remain relatively underexplored in conventional artificial neural networks.

In alignment with this biologically grounded perspective, we depart from symbolic, high-level behaviour and instead operate at the level of raw signals. While Turing [1] was right to suggest that communication could serve as a basis for evaluating machine intelligence, natural language remains problematic as a test medium: it conveys human knowledge through symbols whose meanings are not intrinsically grounded in machines, as argued by Stevan Harnad [11]. As a result, symbolic evaluation can obscure whether a system has acquired grounded representations or merely exploits statistical regularities in linguistic form. Although the symbol-grounding problem is an old philosophical issue, it has regained prominence across cognitive science, neuroscience, and machine learning [8], [9], [23].

A. Biological grounding and non-symbolic evaluation

To minimise assumptions about semantic grounding, we focus on systems that operate directly on the lowest-level binary signals, each represented as a structure of bits processed in parallel. A bit corresponds directly to the state of a measurable signal channel (such as a pixel, an audio band, or actuator feedback) and, as the smallest unit of information, does not in itself impose higher-level semantic structure. Binary signals also provide a simple abstraction of neural spiking events in biological systems.

This perspective is consistent with the functioning of the cerebral cortex, where cognition arises from the processing of temporally structured sensory spike trains rather than disembodied symbols. The "brain simulator" reply to John Searle's Chinese Room argument [24] suggests that a system reproducing the causal dynamics of cortical processing could, in principle, instantiate the same cognitive mechanisms [25]. The cortex represents at least one plausible route toward general intelligence.

The proposed AGI requirements are particularly well-suited for NeuroAI models and align with the principles of the embodied Turing Test [26], in which cognitive understanding is hypothesised to emerge from the integration of continuous sensory streams. The progression from raw-signal prediction to higher-level abstraction mirrors that from early perceptrons to contemporary large-scale models.

B. Integrated requirements for intelligence

A starting point for the AGI requirements is the *ladder to human-comparable intelligence* [27], a framework that organises cognitive capabilities into progressively more demanding levels. Its first three rungs align naturally with the framework proposed here. However, the ladder's individual requirements can be met by specialised systems that lack general intelligence, which creates a risk of false positives during evaluation. Minimising such false positives, therefore, requires an all-or-nothing criterion: a system must satisfy *all* requirements simultaneously rather than meeting them individually. In addition, the higher rungs of the ladder remain insufficiently specified for operational evaluation.

Consequently, failure on any single requirement is sufficient to rule out AGI, whereas satisfying all of them does not

establish it. This complementarity allows individual requirements to remain simple in scope, while their joint satisfaction is intended to impose constraints that narrow or specialised systems cannot easily meet.

C. Learning through prediction

An intelligent system learns to recognise the structure of input signals originating from the external world. The learning process cannot rely solely on externally defined performance metrics, such as accuracy or mean-squared error, because predefined quantitative metrics struggle to capture the richness and variability of real-world structure.

This limitation is reflected in many existing approaches to evaluating AGI, which remain constrained by metrics that inadequately capture the breadth of general intelligence. Contemporary systems already surpass humans on many standardised tasks—for example, playing chess—illustrating how narrowly defined benchmarks can be optimised without necessarily yielding broadly general capabilities. Metric-based evaluation can therefore encourage systems engineered to maximise specific scores rather than those exhibiting general intelligence.

Achieving generality, therefore, requires a learning process driven by an internally defined objective that does not rely on externally supplied semantics. One such objective is the ability to predict the future sensory signals the system will experience. Prediction at the level of sensory signals provides a foundation for higher-level expectations about the external world to emerge without requiring predefined semantic representations. Biological intelligence is often characterised as extracting structure from sensory data in order to anticipate future states [16], [19].

Accordingly, we require a generally intelligent system to predict future inputs from past observations. Prediction alone does not constitute intelligence, but the ability to anticipate future sensory inputs is widely considered a fundamental capability underlying perception, learning, and action [28], [29].

D. Spatial and temporal structure of input signals

In the operational setting considered here, the requirements are specified in terms of temporal sequences comprising randomly structured inputs. Because input signals are defined independently of any external meaning, they need not resemble real-world sensory data. This design limits the usefulness of pretraining and increases confidence that any observed learning arises from the input stream itself.

Each input represents a snapshot of multiple binary signals at a single time step (Figure 1a). Spatial organisation within each input encodes local structure, whereas semantic richness arises from the temporal evolution of the input sequence (Figure 1b). The interaction between spatial and temporal dimensions gives rise to structured patterns that are challenging to adapt to.

An AGI system must learn from a stream of inputs. Upon receiving an input at time step t, it is required to issue a prediction x^*_{t+1} for the subsequent input, as shown in Figure 2.




Fig. 1. (a) Example of a 10-bit input $\mathbf{x}$ with four bits set. (b) Example of an input sequence.




Fig. 2. Iterative adaptation in discrete time. Following input $\mathbf{x}_t$, the system A_t issues the prediction $\mathbf{x}^*_{t+1}$. Upon observing the realised input $\mathbf{x}_{t+1}$, it updates in response to the error in the second bit and produces the next one-step-ahead prediction $\mathbf{x}^*_{t+2}$.

A transition from configuration A_t to A_{t+1} is triggered by the arrival of the actual input (x_{t+1}). The central challenge is not simply extrapolation but discerning the underlying causes or regularities that produce the observed input stream and using that understanding to make accurate future predictions.

IV. The hypothesis

We hypothesise that any system capable of human-level general intelligence must satisfy at least the twelve requirements defined later. These requirements characterise fundamental properties of adaptive systems that learn from temporally structured inputs without relying on externally supplied semantic knowledge. The selection of these requirements is guided by observations of biological information processing and by the need to support autonomous learning from sensory signals.

The hypothesis is empirically falsifiable. It would be rejected by the existence of a demonstrably non-intelligent system that fulfils all requirements. The proposed requirements should therefore not be interpreted as a definition of intelligence.

In what follows, learning denotes the adaptive process through which a system becomes able to correctly anticipate future inputs based on its input history. This definition serves only to characterise prediction success as an operational capability, not an evaluation metric for intelligence. The term *model* denotes a functioning instance of a system type that updates its internal configuration and produces a prediction of a future input based on its input history. Independent models share the same operating principles but are otherwise isolated from one another.

V. Preliminaries

Let $\mathbf{x} \in X = \{0,1\}^L$ with $L = 10$ denote a ten-bit input vector, and let $\boldsymbol{\chi} = (\mathbf{x}_t)_{t=1}^N, \mathbf{x}_t \in X$ denote an input sequence

with N elements. For any input vector $\mathbf{x} \in X$, we write $\mathbf{x}[i]$ for its i-th bit.

Let $\mathcal{M}$ denote the set of all reachable[2] configurations of a system under AGITB evaluation. An individual system instance is denoted by $A \in \mathcal{M}$, with $B \in \mathcal{M}$ representing an independent instance of the same type. When temporal indexing is required, we write A_t for the configuration obtained after t update steps along its learning trajectory, with A_0 representing the initial configuration at the onset of learning.

For brevity, we refer to an instance at a given internal configuration simply as a model.

Definition 1 (Prediction)**.** A model's prediction is given by the operator $\rightsquigarrow \subseteq \mathcal{M} \times X$, where

$$A_t \rightsquigarrow \mathbf{x}^*_{t+1}$$

denotes that the model configuration $A_t \in \mathcal{M}$ predicts the next input to be $\mathbf{x}^*_{t+1} \in X$.

Definition 2 (Model update)**.** Model update is given by the transition relation $\dot{\mapsto} \subseteq \mathcal{M} \times X \times \mathcal{M}$, where

$$A_t \xmapsto{\mathbf{x}_{t+1}} A_{t+1}$$

denotes the atomic transition of the model configuration $A_t \in \mathcal{M}$ upon receiving the input $\mathbf{x}_{t+1} \in X$.

Operationally, prediction and update are tightly coupled: processing the input $\mathbf{x}_{t+1}$ both updates the model and produces a prediction of the subsequent input $\mathbf{x}_{t+2}$. This allows us to write the combined transition as

$$A_t(\mathbf{x}_{t+1}) \to \big(A_{t+1},\, \mathbf{x}^*_{t+2}\big),$$

which subsumes both model advancement and prediction.

Definition 3 (Model trajectory)**.** For any model configuration $A \in \mathcal{M}$ and any input sequence $\boldsymbol{\chi} = (\mathbf{x}_i)_{i=1}^{k}$, we write

$$A \xmapsto{\boldsymbol{\chi}} A^{\boldsymbol{\chi}}$$

to denote the transitions to the configuration obtained by sequentially updating the model with all inputs in $\boldsymbol{\chi}$, i.e.,

$$A^{\boldsymbol{\chi}} = A^{(\mathbf{x}_1,\cdots,\mathbf{x}_k)} := (\cdots((A \xmapsto{\mathbf{x}_1}) \xmapsto{\mathbf{x}_2})\cdots) \xmapsto{\mathbf{x}_k}.$$

Accordingly, $A^{\boldsymbol{\chi}}_t$ denotes the configuration obtained by applying $\boldsymbol{\chi}$ to A_t, that is, $A^{\boldsymbol{\chi}}_t := (A_t)^{\boldsymbol{\chi}}$. A model may be exposed to multiple input sequences in succession; for two sequences $\boldsymbol{\chi}_1$ and $\boldsymbol{\chi}_2$, their concatenation is written $\boldsymbol{\chi}_1\boldsymbol{\chi}_2$, and the resulting configuration satisfies

$$A \xmapsto{\boldsymbol{\chi}_1} A^{\boldsymbol{\chi}_1} \xmapsto{\boldsymbol{\chi}_2} A^{\boldsymbol{\chi}_1\boldsymbol{\chi}_2}.$$

Definition 4 (Autoregressive generation)**.** Autoregressive generation is given by the relation $\Rrightarrow \subseteq \mathcal{M} \times \big(X^* \cup X^{\mathbb{N}}\big)$, where

$$A_t \Rrightarrow \boldsymbol{\chi}^*$$

denotes that the model configuration A_t generates the (finite or infinite) sequence $\boldsymbol{\chi}^* = (\mathbf{x}^*_{t+1}, \mathbf{x}^*_{t+2}, \ldots)$ by recursively feeding each predicted input back into the model; for a finite sequence, $A_t \Rrightarrow \boldsymbol{\chi}^*$ means that the first $|\boldsymbol{\chi}^*|$ generated inputs equal $\boldsymbol{\chi}^*$. In particular, for all $k \geq 0$ (and $k < |\boldsymbol{\chi}^*|$ for a finite sequence),

$$A_{t+k} \rightsquigarrow \mathbf{x}^*_{t+k+1}, \quad A_{t+k} \xmapsto{\mathbf{x}^*_{t+k+1}} A_{t+k+1}.$$

Definition 5 (Behavioural equivalence)**.** Two model configurations $A, B \in \mathcal{M}$ are *behaviourally equivalent*, written $A \equiv B$, if they issue identical predictions under every subsequent input sequence:

$$A \equiv B \;:\Longleftrightarrow\; \forall\, \boldsymbol{\chi} \in X^*,\, \forall\, \mathbf{x} \in X :\; A^{\boldsymbol{\chi}} \rightsquigarrow \mathbf{x} \iff B^{\boldsymbol{\chi}} \rightsquigarrow \mathbf{x},$$

where X^* includes the empty sequence. Identical configurations are behaviourally equivalent; the converse need not hold.

Definition 6 (Learning)**.** The model A is said to *learn* a sequence $\boldsymbol{\chi}$, written $A \rhd \boldsymbol{\chi}$, if there exists a finite number of passes over $\boldsymbol{\chi}$, possibly none, after which A can autoregressively reproduce a single instance of $\boldsymbol{\chi}$, i.e.

$$A \rhd \boldsymbol{\chi} \;:\Longleftrightarrow\; \exists\, n \in \mathbb{N}_{\geq 0} :\; A^{\boldsymbol{\chi}^n} \Rrightarrow \boldsymbol{\chi}.$$

We write $m_A(\boldsymbol{\chi}) \coloneqq \min\{n \geq 0 \mid A^{\boldsymbol{\chi}^n} \Rrightarrow \boldsymbol{\chi}\}$ for the number of passes that precede the first perfectly predicted one.

Definition 7 (Post-learning configuration)**.** If $A \rhd \boldsymbol{\chi}$, the post-learning configuration is the configuration reached immediately after the first perfectly predicted pass:

$$A_{\boldsymbol{\chi}} \coloneqq A^{\boldsymbol{\chi}^{\,m_A(\boldsymbol{\chi})+1}}.$$

Definition 8 (Learning time)**.** The *learning time in atomic steps* is defined as

$$\tau_A(\boldsymbol{\chi}) \coloneqq \begin{cases} |\boldsymbol{\chi}| \cdot m_A(\boldsymbol{\chi}), & \text{if } A \rhd \boldsymbol{\chi}, \\ \infty, & \text{else.} \end{cases}$$

Learning time counts the atomic steps that precede the first perfectly predicted pass; it is zero if the model already predicts the sequence. It measures the first occurrence of accurate prediction and does not presuppose permanent retention: the post-learning configuration need not reproduce the sequence again. If the model never learns to predict the sequence, its learning time is infinite.

Definition 9 (Mastery)**.** The model A is said to *master* a sequence $\boldsymbol{\chi}$ if it predicts the sequence perfectly in two consecutive passes, so that what it learned remains active:

$$\exists\, n \in \mathbb{N}_{\geq 0} :\; A^{\boldsymbol{\chi}^n} \Rrightarrow \boldsymbol{\chi} \;\wedge\; A^{\boldsymbol{\chi}^{n+1}} \Rrightarrow \boldsymbol{\chi}.$$

We write $A^{\star}_{\boldsymbol{\chi}}$ for the configuration $A^{\boldsymbol{\chi}^{n+2}}$ reached after the second of these passes, with the smallest such n.

VI. The requirements

Requirement 1 (Uninformed start)**.** *All models begin learning from the identical initial configuration* $\diamond$*.*

$$\forall\, A :\; A_0 = \diamond.$$

The initial model is assumed to contain no environment-specific knowledge beyond the architectural biases necessary for learning. All knowledge relevant to input must be acquired solely through subsequent exposure to data. This assumption is commonly regarded as a necessary condition for universality,

[2]Starting from the initial configuration under some input history.

defined as the ability to adapt to arbitrary environments. The formal statement captures only the identical starting configuration; the absence of environment-specific knowledge is an assumption that the requirement expresses but that no test can verify, since comparing fresh instances of a model cannot reveal knowledge that all of them share.

We assume that general-purpose learning systems, including biological brains, do not begin with an innate understanding of external inputs but instead acquire meaning through interaction with their environment. Each system must construct semantic content from raw sensory data rather than rely on pre-encoded knowledge.[3]

Requirement 2 (Determinism)**.** *Model evolution is deterministic with respect to input.*

$$\forall A,\ \forall \mathbf{x} \in X:\ \exists!\, A' \text{ such that } A \xmapsto{\mathbf{x}} A'.$$

Biological neurons operate in a functionally deterministic manner, ensuring stability and consistency in brain function. Although minor stochastic effects may occur, they do not undermine the rule-governed nature of neural processing. By analogy, we assume that input history uniquely determines the model configuration. A model is therefore fully determined by its input history.

Determinism at the level of neural signal processing is necessary for stable, reproducible brain function. In contrast, the apparent unpredictability of cognition stems from the system's complexity rather than from genuine indeterminacy [30].

Requirement 3 (Trace)**.** *Each input leaves a permanent internal trace.*

$$\forall \boldsymbol{\chi}_1 \neq \boldsymbol{\chi}_2 \in X^*,\ \forall \boldsymbol{\chi} \in X^*:\ A_0^{\boldsymbol{\chi}_1 \boldsymbol{\chi}} \not\equiv A_0^{\boldsymbol{\chi}_2 \boldsymbol{\chi}}.$$

Two models whose input histories differ never become indistinguishable, whatever they experience afterwards: every input leaves a trace that no later input can erase, and that eventually shows in behaviour. It follows that configurations never repeat and trajectories contain no cycles (Corollary 1).

In the reference implementation, two models start one input apart: one receives an input twice in a row, violating the refractory constraint of Req. 5, while the other receives it followed by silence. Both then live the same long life, in which both beginnings recur repeatedly, so that nothing either model experienced is unique to it. Afterwards they must issue different predictions somewhere on a long random sequence of probe inputs. A model that only records which inputs it has seen, and what followed them, cannot tell the two apart; only a trace of the history itself, including the order and multiplicity of its events, survives the shared life.

Human brains satisfy an effective version of this requirement at the lowest physical level. Each sensory or internal event induces irreversible microstate changes that are never exactly revisited. Through complex internal interactions, this persistent history contributes to the apparent unpredictability of decision-making. Although information may appear discarded, compressed, or behaviourally inaccessible at the cognitive level, we posit that internal model configurations continue to develop in a distinct manner over time, consistent with the formation of permanent internal traces.

Taken literally, the requirement is an idealisation. Since distinct histories must lead to distinguishable configurations, a model satisfying it exactly needs infinitely many configurations, and its memory must grow with the length of its history; no system with a fixed amount of memory can satisfy it exactly. Like the other requirements that quantify over unbounded domains, it is therefore approximated: the test checks it on a single hard case over a finite horizon, and passing it means that no forgetting was detected within that horizon, not that the trace is permanent in the strict sense.

Requirement 4 (Time)**.** *Model evolution depends on input order.*

$$\forall A, \forall \boldsymbol{\chi}_1, \boldsymbol{\chi}_2 \in X^+:\ \boldsymbol{\chi}_1\boldsymbol{\chi}_2 \neq \boldsymbol{\chi}_2\boldsymbol{\chi}_1 \implies A^{\boldsymbol{\chi}_1\boldsymbol{\chi}_2} \neq A^{\boldsymbol{\chi}_2\boldsymbol{\chi}_1}.$$

Model evolution depends intrinsically on input order: for any system, changing the input order necessarily results in a novel configuration. This enforces a strict temporal asymmetry in learning dynamics and rules out commutative or order-invariant update mechanisms. Sensitivity to temporal structure in this strong sense is regarded as a defining property of intelligent systems.

Formally, this requirement is implied by Req. 3: the histories $\boldsymbol{\chi}_1\boldsymbol{\chi}_2$ and $\boldsymbol{\chi}_2\boldsymbol{\chi}_1$ differ, so the resulting configurations are not even behaviourally equivalent. It is nevertheless stated separately, because order sensitivity is a central property in its own right and admits a simple, direct test: in the reference implementation, two copies of a model with a random input history receive the same two inputs in opposite order and must end in different configurations.

Definition 10 (Admissible sequences)**.** The set of *admissible* sequences is defined as

$$\boldsymbol{\Phi} := \Big\{ (\mathbf{x}_1, \ldots, \mathbf{x}_k) \in X^k \;\Big|\; k \geq 1$$

$$\wedge\ \forall i \in \{1, \ldots, k\}:\ \mathbf{x}_i \cdot \mathbf{x}_{((i \bmod k)+1)} = 0 \Big\}.$$

Requirement 5 (Absolute refractory period)**.** *A model can learn a cyclic sequence only if successive inputs, including the last and the first, share no active bit.*

$$\forall \boldsymbol{\chi}:\ A_0 \rhd \boldsymbol{\chi} \implies \boldsymbol{\chi} \in \boldsymbol{\Phi}.$$

Biological intelligence relies on discrete spiking events for communication and learning, and individual neurons cannot fire again immediately after activation. The absolute refractory-period constraint defines admissible sequences but does not imply that all such sequences are learnable.

Absolute refractory periods impose a minimum separation between spikes, creating temporal structure that supports temporally sensitive learning processes [22]. All temporal sequences that satisfy biologically plausible refractory constraints are therefore admissible, independent of any semantic interpretation of the signals.

[3] Although reflexes may be genetically specified, they do not constitute genuine understanding. They are rather evolutionary features of the subcortical "old" brain and not prerequisites for intelligence [16, p. 66].

Definition 11 (Learnable sequences)**.** The set of *learnable* sequences is the subset

$$\boldsymbol{\Psi} := \big\{\boldsymbol{\phi} \in \boldsymbol{\Phi} \;\big|\; A_0 \rhd \boldsymbol{\phi}\big\}.$$

Definition 12 (Learning in turn)**.** Sequences $\boldsymbol{\psi}_1, \ldots, \boldsymbol{\psi}_k$ are *learned in turn* by a configuration A if each of them is learned by the configuration that results from learning the previous ones:

$$C_0 = A, \qquad C_{i-1} \rhd \boldsymbol{\psi}_i, \qquad C_i = (C_{i-1})_{\boldsymbol{\psi}_i}, \qquad i = 1, \ldots, k.$$

We write $A_{\boldsymbol{\psi}_1 \cdots \boldsymbol{\psi}_k} := C_k$, with $A_{\boldsymbol{\psi}_1 \cdots \boldsymbol{\psi}_k} = A$ for $k = 0$.

Requirement 6 (Inevitable saturation)**.**
(a) A model cannot learn everything there is to learn.

$$\forall\, A \in \mathcal{M},\ \exists\, k \geq 0,\ \exists\, \boldsymbol{\psi}_1, \ldots, \boldsymbol{\psi}_k \in \boldsymbol{\Psi} \textit{ learned in turn by } A,$$
$$\exists\, \boldsymbol{\psi} \in \boldsymbol{\Psi} :\ \neg\big(A_{\boldsymbol{\psi}_1 \cdots \boldsymbol{\psi}_k} \rhd \boldsymbol{\psi}\big).$$

(b) All admissible length-2 sequences are universally learnable.

$$\forall\, A,\ \forall\, \boldsymbol{\phi} \in \boldsymbol{\Phi} \cap X^2 :\ A \rhd \boldsymbol{\phi}.$$

Learning systems with finite representational and adaptive capacity necessarily face limits on the extent to which they can learn sequences of length greater than two, whereas all admissible sequences of length two are universally learnable. Saturation must be reachable from every configuration, though not along every learning path: a model that learns only length-two sequences never saturates, by Req. 6(b). The sequences that a saturated model can no longer learn are therefore longer than two.

Length-two sequences occupy a special position, as they are the shortest sequences that encode temporal relationships, while a single input carries no temporal information. They define transitions that are the irreducible units of temporal prediction and thus necessary for temporal learning.

A related distinction is observed in biological learning systems. Humans can readily acquire arbitrary pairwise associations, whereas learning and retaining longer temporal structures is subject to pronounced capacity limits and interference effects.

In the reference implementation, a model with a random input history keeps learning random cyclic sequences of seven inputs until it meets one that it cannot learn although a fresh model can; it must meet such a sequence eventually, and must afterwards still learn a random admissible sequence of length two.

Requirement 7 (Temporal adaptability)**.** *The model must be able to learn sequences with varying cycle lengths and adapt when the temporal scale changes.*

$$\exists\, \boldsymbol{\psi}_1 \in \boldsymbol{\Psi},\ \exists\, \boldsymbol{\psi}_2 \in \boldsymbol{\Phi} :\ 0 < |\boldsymbol{\psi}_1| < |\boldsymbol{\psi}_2| \ \wedge\ (A_0)_{\boldsymbol{\psi}_1} \rhd \boldsymbol{\psi}_2.$$

This requirement captures the ability to learn and track temporal structure across multiple timescales. Systems restricted to rigid pattern matching at a single, fixed periodicity are therefore excluded, as adaptive learning requires sensitivity to recurring structure at different temporal scales.

In the reference implementation, a fresh model must learn a rhythm of silent inputs in which a single bit spikes every seventh step, and then the same rhythm with a spike every eighth step. Predicting the spike requires counting the silent steps that precede it, and the count changes between the two sequences.

Requirement 8 (Content sensitivity)**.** *Adaptation time is input-dependent.*

$$\exists\, \boldsymbol{\psi}_1,\, \boldsymbol{\psi}_2 \in \boldsymbol{\Psi} :\ |\boldsymbol{\psi}_1| = |\boldsymbol{\psi}_2| \ \wedge\ \tau_{A_0}(\boldsymbol{\psi}_1) \neq \tau_{A_0}(\boldsymbol{\psi}_2).$$

The rate at which a model adapts depends on the structure of the input sequence. Simple or highly regular sequences typically yield rapid convergence, whereas less regular inputs require longer exposure before the model can reliably capture the underlying structure.

Requirement 9 (Context sensitivity)**.** *Adaptation time is model-dependent.*

$$\exists\, \boldsymbol{\psi} \in \boldsymbol{\Psi},\ \exists\, A \neq B :\quad \tau_A(\boldsymbol{\psi}) < \infty \wedge \tau_B(\boldsymbol{\psi}) < \infty \wedge \tau_A(\boldsymbol{\psi}) \neq \tau_B(\boldsymbol{\psi}).$$

A model's internal configuration reflects the cumulative influence of past inputs and thereby determines the context in which new information is learned. When subsequent inputs are consistent with the structure established through prior learning, adaptation may proceed rapidly. Conversely, when new inputs conflict with this learned context, additional iterations may be required before accurate prediction becomes possible.

Requirement 10 (Denoising)**.** *An informed model consistently outperforms its uninformed self at predicting what follows a corrupted input.*

Let A be an adult model, that is, a model that has reached the saturation of Req. 6(a). Let $\boldsymbol{\phi} = (\mathbf{x}_1, \ldots, \mathbf{x}_k) \in \boldsymbol{\Phi}$ be a random cyclic sequence that the adult learns, $A \rhd \boldsymbol{\phi}$, and let $\boldsymbol{\phi}' = (\mathbf{x}_1, \ldots, \mathbf{x}_{k-1}, \mathbf{x}'_k)$ be obtained from $\boldsymbol{\phi}$ by flipping a single bit of its last input, such that $\boldsymbol{\phi}' \in \boldsymbol{\Phi}$. The informed model learns $\boldsymbol{\phi}$ and then observes $\boldsymbol{\phi}'$, whereas the uninformed model observes only $\boldsymbol{\phi}'$:

$$A^{\boldsymbol{\phi}'}_{\boldsymbol{\phi}} \rightsquigarrow \mathbf{x}^*_{\mathrm{inf}}, \qquad A^{\boldsymbol{\phi}'} \rightsquigarrow \mathbf{x}^*_{\mathrm{uninf}}.$$

Over T independently generated pairs $(\boldsymbol{\phi}^{(i)}, \boldsymbol{\phi}'^{(i)})$, the informed model predicts the input that follows the familiar sequence exactly more often than the uninformed one:

$$\sum_{i=1}^{T} \mathbf{1}\big\{\mathbf{x}^{*(i)}_{\mathrm{inf}} = \mathbf{x}^{(i)}_1\big\} > \sum_{i=1}^{T} \mathbf{1}\big\{\mathbf{x}^{*(i)}_{\mathrm{uninf}} = \mathbf{x}^{(i)}_1\big\}.$$

In the reference implementation, $T = 20$ and $k = 7$.

A model is required to recognise a familiar sequence despite a single corrupted input, and to predict what normally follows it. Because an adult is saturated, it cannot learn every sequence; only sequences it does learn can become familiar, so sequences it fails to learn are redrawn. The comparison is made against the same adult model without knowledge of the sequence, so that the advantage must come from the familiar sequence rather than from general experience or from a fortunate guess. Using adult models also ensures that denoising is demonstrated by a model whose capacity is already in use, rather than by a fresh model with an empty

memory. Every adult lives the same life, which keeps failures reproducible.

Requirement 11 (Generalisation)**.** *Let $\boldsymbol{w} \in \boldsymbol{\Phi}$ be a world: a cyclic sequence of inputs whose changes follow a rule. Let $\mathbf{p} \in X$ be a prefix input that does not occur in $\boldsymbol{w}$, and let $\mathbf{c} \in X$ be the continuation that the rule assigns to $\mathbf{p}$. The informed model masters $\boldsymbol{w}$ and then observes $\mathbf{p}$; the uninformed model observes only $\mathbf{p}$. The informed model must predict the continuation exactly, and the uninformed one must not:*

$$\left((A_0)^{\star}_{\boldsymbol{w}}\right)^{(\mathbf{p})} \rightsquigarrow \mathbf{c}, \qquad A_0^{(\mathbf{p})} \not\rightsquigarrow \mathbf{c}.$$

In the reference implementation, the world is hard-coded. Three patterns in turn appear after silence, move one position to the right at each time step, and vanish into silence again:

$$\boldsymbol{w} = \begin{pmatrix} \texttt{1000100001}, \\ \texttt{0100010000}, \\ \texttt{0010001000}, \\ \texttt{0000000000}, \\ \texttt{0000101000}, \\ \texttt{0000010100}, \\ \texttt{0000000000}, \\ \texttt{1010000010}, \\ \texttt{0101000001}, \\ \texttt{0010100000}, \\ \texttt{0001010000}, \\ \texttt{0000101000}, \\ \texttt{0000000000} \end{pmatrix},$$

with $\mathbf{p} = \texttt{0001001000}$ and $\mathbf{c} = \texttt{0000100100}$.

Improving performance beyond memorisation requires generalisation: a model that has merely memorised its world has nothing to say about an input it has never seen, whereas a model that has grasped the rule governing the world can apply it. The informed model must master the world, so that it demonstrably knows it, before it is asked to generalise. Mastering this world already requires more than recalling what followed each input: silence is followed by three different patterns, and the same pattern is followed once by its shift and once by silence.

The prefix arrives after silence, where the world only ever shows a new pattern followed by its shift; the rule therefore assigns it its own shift as the continuation. The world is constructed so that this continuation cannot be obtained by tracking which input channel follows which: because patterns vanish into silence, most channels are sometimes followed by nothing at all, and statistics of individual channels predict only part of the continuation. Only the movement of the input as a whole explains every transition. The prefix keeps both transitions admissible and differs from every input of the world, silence included, in at least two bits, so that it cannot be mistaken for a noisy familiar input of the kind considered in Req. 10.

Requirement 12 (Real-time liveness)**.** *Each model update completes within a fixed wall-clock time bound, independent of the input history.*

$$\exists\, t_{\max} > 0 :\ \Delta t(A, \mathbf{x}) \le t_{\max} \quad \forall A \in \mathcal{M},\ \forall \mathbf{x} \in X,$$

where $\Delta t(A, \mathbf{x})$ denotes the wall-clock time required to perform the atomic transition $A \overset{\mathbf{x}}{\mapsto} A'$.

A model must complete each atomic transition within a bounded amount of time to remain suitable for real-time interaction. Biological brains satisfy this requirement in large part through massive parallelism: configuration transitions and signal emissions occur concurrently across large neuronal populations, with neural signal propagation times bounded under normal operating conditions. As a result, cognitive processing does not exhibit unbounded slowing as a function of accumulated experience or instantaneous sensory load.

In the reference implementation, the time a model needs to process a batch of inputs is measured on a fresh model and again after a long random input history; the second measurement must remain below twice the first. Each measurement is the fastest of several timings on copies of the model, so that a single interruption by the operating system cannot decide the test.

A. Immediate consequences of the requirements

Two immediate consequences follow from the preceding requirements. First, any system satisfying Req. 3 undergoes perpetual change: every input induces a distinct internal configuration, and model trajectories contain no exact recurrences. Second, Reqs. 3 and 6(b) together imply a form of behavioural unobservability, in which distinct internal configurations can yield identical autoregressive outputs.

Corollary 1 (Perpetual change)**.** *Configurations never repeat; in particular, every input induces a change in the model's internal configuration.*

$$\forall\, t \neq s \ge 0 :\ A_t \neq A_s, \qquad \forall\, t \ge 0 :\ A_{t+1} \neq A_t.$$

Proof. Let $A_t = A_0^{\boldsymbol{\chi}_t}$ and $A_s = A_0^{\boldsymbol{\chi}_s}$ with $t \neq s$, so that the histories $\boldsymbol{\chi}_t$ and $\boldsymbol{\chi}_s$ differ in length. If $A_t = A_s$, the two configurations would evolve identically under every continuation and would therefore be behaviourally equivalent, contradicting Requirement 3. Setting $s = t + 1$ yields $A_{t+1} \neq A_t$ for all t. □

Corollary 2 (Unobservability)**.** *Distinct model configurations may be observationally indistinguishable under autoregressive generation:*

$$\exists\, \boldsymbol{\phi} \in \boldsymbol{\Phi}\ \exists\, A \neq B :\ A \Rrightarrow \boldsymbol{\phi}\ \wedge\ B \Rrightarrow \boldsymbol{\phi}.$$

Proof. Choose $\boldsymbol{\phi} \in \boldsymbol{\Phi} \cap X^2$. By Requirement 6(b), every reachable configuration learns $\boldsymbol{\phi}$.

Let A and B be two reachable configurations whose input histories differ but have equal length. Since both learn $\boldsymbol{\phi}$, the configurations $A' = A^{\boldsymbol{\phi}^{m_A(\boldsymbol{\phi})}}$ and $B' = B^{\boldsymbol{\phi}^{m_B(\boldsymbol{\phi})}}$, which precede their first perfectly predicted passes, satisfy

$$A' \Rrightarrow \boldsymbol{\phi}, \qquad B' \Rrightarrow \boldsymbol{\phi}.$$

Their histories extend those of A and B by whole passes of $\boldsymbol{\phi}$: if the numbers of passes are equal, the extended histories still differ where the original ones did; otherwise they differ in length. By Requirement 3, configurations with different histories are behaviourally distinguishable, and thus distinct, so $A' \neq B'$. □

VII. Methodology

The proposed requirements are operationalised as concrete evaluation procedures, with each requirement evaluated by an empirical test whose failure indicates non-compliance. The objective is not to demonstrate intelligence, but to expose violations under stringent conditions, thereby probing the robustness of candidate systems.

Taken together, the requirement-specific tests form a practical testbed, the Artificial General Intelligence Testbed (AGITB), that cannot, and is not intended to, prove that a model satisfies all requirements. Rather, its strength lies in identifying violations of individual requirements and in indicating which constraints are breached. A reference C++ implementation of AGITB is freely available under the GPL license at https://github.com/matejsprogar/agitb.

A. Inherent limitations

AGITB confronts three principal challenges. First, several requirements quantify over effectively unbounded sets of cases and cannot be exhaustively verified through finite testing. Second, individual requirements cannot always be captured by a single, easily interpretable test. Third, external performance metrics are unsuitable, as they cannot reliably distinguish generalisable adaptive behaviour from task-specific optimisation.

We address the first challenge by approximating unbounded domains with finite, tractable collections of test cases that provide empirical support for a given claim. The second is addressed through a synergistic test design in which multiple simple tests are mutually informative and reinforce one another. In such settings, failure to satisfy a requirement may not be revealed by a test in isolation, but instead emerges when constraints imposed by other tests become mutually incompatible. The third challenge is addressed by constructing controlled scenarios involving independent system instances and assessing behaviour through systematic comparison, with success defined in terms of configuration or behavioural distinctions rather than external task scores.

B. Test design

In the reference implementation, a compromise approximation for unlimited iterations is set to 5,000. While finite, this value was chosen to balance computational feasibility with stringency and is used consistently across tests. To minimise the influence of stochastic effects, every test that involves random inputs is repeated 5,000 times, and the system under evaluation must succeed on each trial; the three tests without random inputs (Reqs. 1, 7, and 11) are run once. The resulting procedure functions as an extreme form of stress testing, ensuring that passing results reflect systematic robustness rather than chance.

The tests are not designed as conventional significance tests, nor to maximise statistical power; instead, they prioritise reliability by admitting virtually no noise or marginal effects. Modest or inconsistent improvements are treated as failures.

Finally, AGITB adopts an all-or-nothing evaluation criterion: a system under evaluation must satisfy all requirement-specific tests to pass the benchmark. While individual tests may be solvable in isolation, the tests are designed such that simultaneous satisfaction of all requirements imposes substantially stronger constraints.

C. Problem space

To prevent models from relying on brute-force memorisation, the problem space must be sufficiently large to exceed the capacity of any model operating under realistic computational constraints on both time and memory. In AGITB, tasks typically require predicting a temporal sequence of seven inputs ($N = 7$), each consisting of ten bits ($L = 10$). The resulting problem space is $\mathcal{S} = (\{0,1\}^L)^N$, which has cardinality $|\mathcal{S}| = 2^{70}$, representing all possible binary input sequences of that length.

The *absolute refractory period* prohibits any neuron (bit) from firing in consecutive time steps. This requirement substantially lowers the number of admissible sequences, yielding a subset $\mathcal{S}' \subset \mathcal{S}$. There are $|\mathcal{S}'| = (\mathcal{F}_{N+2})^L = 34^{10} \approx 2^{51}$ distinct seven-step temporal sequences of ten bits under the condition that a 1 never carries over to the next time step, where $\mathcal{F}_i$ denotes the i-th Fibonacci number with $\mathcal{F}_0 = 0$.

In some cases, AGITB further constrains $\mathcal{S}'$ by requiring sequences to be cyclic, such that the first input also satisfies the absolute refractory constraint with respect to the final input in the sequence. The resulting set of cyclic temporal sequences respecting the refractory constraint, $\mathcal{S}'' = \mathbf{\Phi} \cap X^N \subset \mathcal{S}'$, has cardinality $|\mathcal{S}''| = (\mathcal{L}_N)^L = 29^{10} \approx 2^{49}$, where $\mathcal{L}_i$ denotes the i-th Lucas number with $\mathcal{L}_0 = 2$.

The choice of seven-step sequences with ten-bit inputs is sufficient to expose the naive and specialised systems we have evaluated while maintaining computational efficiency; it does not, however, prevent systems engineered around the tests from passing (Section VII-D). Increasing these default values could exceed the capabilities of the first-generation AGI under evaluation, potentially leading to false negatives and substantially increasing runtime. The current configuration, therefore, ensures that each test remains both computationally feasible and diagnostically informative.

D. Benchmark Exploitation

Because AGITB consists of intentionally simple and transparent tests, a model can be engineered to optimise for the benchmark rather than for the underlying learning capabilities it is intended to measure.

For example, a model with a built-in mechanism that shifts its input along the channels can pass the test of Req. 11 without learning the rule from the world it is presented with, even though such pre-installed knowledge is prohibited by Req 1. One might argue that the shift mechanism is merely an architectural choice. However, in this case, it is precisely the rule on which the test is based, and any other operation used by the test could be built into the model in the same way. Such a model is of little use in general, as it does not learn the rules governing the world but brings them along. Unfortunately, no test of Req. 1 can detect pre-installed knowledge, because it can only compare fresh instances of a model with one another, and all instances share the same built-in knowledge.

Other avenues include exploiting weaknesses in the benchmark's randomisation or exploiting properties of the comparison procedure between model instances. Such strategies optimise performance with respect to the benchmark implementation rather than the underlying capabilities being assessed.

Benchmark-specific design need not be as blatant as a single built-in rule. In our own attempts to break the testbed, we assembled a learner from generic components: an online-trained neural network, statistics of which input channels follow which, a switch that falls back on these statistics when the network's prediction is contradicted, and a built-in preference for the shortest shift of the whole input that explains a transition. With its parameters tuned against the failures observed during development, this learner passed all twelve tests. None of its components refers to a test explicitly, yet the system as a whole was shaped by knowledge of the tests, and it is not intelligent in any meaningful sense. AGITB therefore cannot be regarded as foolproof against fake solutions: it rejects systems whose violations its tests probe, but a sufficiently informed designer can pass every test without satisfying the requirements the tests approximate.

In principle, the benchmark could be hardened against these forms of exploitation by introducing additional randomisation, obfuscation, or verification mechanisms. However, these measures would inevitably increase implementation complexity while reducing transparency, interpretability, and reproducibility. Since AGITB is intended not only as an evaluation protocol but also as a practical development tool, the reference implementation deliberately favours simplicity and readability over resistance to benchmark-specific optimisations.

A more fundamental limitation arises from the need to approximate inherently unbounded evaluation criteria using finite computational resources. Several AGITB requirements would ideally be evaluated over an unbounded number of test cases, which is computationally infeasible. Instead, the benchmark performs a fixed number of iterations intended to approximate an otherwise indefinite evaluation process. In the reference implementation, this limit is controlled by the parameter `SimulatedInfinity`, which is currently set to 5,000.

Although this value is necessarily finite, our experiments indicate that, in combination with the current benchmark configuration (temporal patterns consisting of seven 10-bit input signals), it is sufficient to expose the violations of the systems we have evaluated that were not engineered around the tests, while maintaining computational efficiency suitable for rapid iterative experimentation.

The AGITB reference implementation is therefore intentionally designed to be transparent, computationally efficient, and straightforward to inspect. Implementation-specific exploits are not hypothetical, but hardening the benchmark against them would require secrecy or obfuscation that conflict with its purpose, and would still not make it foolproof; increasing its complexity for this reason would diminish its value as an interpretable and reproducible evaluation framework.

E. Expected behaviour of representative system classes

To contextualise the benchmark, we consider how representative classes of systems would be expected to behave under AGITB. These observations serve only as qualitative reference points and do not constitute formal verification.

Human cognition provides a useful conceptual baseline. Direct verification of AGITB requirements in humans is not possible because internal cortical configurations cannot be inspected or compared computationally. Nevertheless, many requirements correspond to well-known cognitive abilities, including temporal pattern recognition, denoising of corrupted inputs, and knowledge saturation. One notable exception is the uninformed-start requirement, which adult humans do not satisfy because of accumulated prior knowledge; this condition may plausibly hold only at the start of cortical development.

Classical symbolic programs are generally incompatible with the intent of the uninformed start requirement because their rules and representations encode prior assumptions about the meaning of processed signals, although identical copies of such a program still satisfy its formal statement. In such systems, program structure effectively constitutes external knowledge supplied by the designer. Although individual AGITB tests may be solvable through specialised procedures, the presence of embedded prior knowledge violates the requirement that models derive structure solely from experience with grounded binary inputs.

Artificial neural networks exhibit a similar distinction between pre-informed and uninformed systems. Modern deep learning architectures typically rely on extensive pretraining, during which network parameters are shaped by exposure to structured datasets. Such pretraining conflicts with the assumption behind the uninformed start. In addition, standard ANN training procedures rely on externally supplied optimisation processes rather than autonomous adaptation driven exclusively by incoming signals.

Large language models represent a particular instance of pretrained neural systems and therefore violate the assumption behind the first requirement by construction, although identical copies satisfy its formal statement and its test. Moreover, transformer-based architectures necessarily employ fixed-length context windows, which may prevent preservation of an uninterrupted trace of past inputs when earlier tokens are truncated or compressed. These architectural characteristics place practical limits on their ability to satisfy certain AGITB requirements.

These observations illustrate that while individual AGITB tests may be solvable by specialised systems, satisfying all requirements simultaneously imposes a substantially stronger constraint on candidate architectures.

F. Empirical attempts to satisfy the testbed

To probe whether existing systems might reject the proposed hypothesis, we attempted to construct counterexamples in two ways.

First, the reference implementation of AGITB was released publicly as free software to encourage independent attempts at fulfilling the requirements. The repository was made available,

along with a preprint describing the testbed, in April 2025. Although the repository has been cloned several hundred times, no independently verified solution satisfying all tests has been reported.

Second, we deliberately engineered systems around the tests. Learners built solely from generic mechanisms failed at least one test, but combining these mechanisms with knowledge of the tests eventually yielded a learner that passed all tests (Section VII-D). The absence of reported independent solutions, therefore, shows that the testbed is demanding, not that non-intelligent systems cannot pass it.

VIII. Conclusion

Unlike conventional approaches to defining intelligence through high-level behaviours such as question answering or language translation, this work focuses on low-level, biologically grounded computational properties. The proposed requirements are tightly interdependent: no single requirement is decisive in isolation, yet their complementarity permits each to remain atomic in scope while jointly demanding the adaptive learning capabilities expected of an AGI.

The proposed requirements are not intended as a sufficient criterion for artificial general intelligence, nor do they characterise intelligence in any comprehensive sense. A system that satisfies them does not thereby exhibit higher-level capacities such as reasoning, abstraction, or natural language competence. Instead, the requirements target a set of low-level capabilities that may serve as necessary precursors to more general forms of intelligence, without themselves guaranteeing their emergence.

The central claim advanced here cannot be verified until a precise, universally accepted definition of intelligence is available, a prospect that is unlikely. It is, however, empirically falsifiable: the existence of a narrow system that satisfies all requirements would invalidate the claim that these properties are necessary for general intelligence. Passing the testbed is not the same as satisfying the requirements: the tests only approximate the requirements, and some of them, notably the uninformed start (Req. 1), cannot be verified by any test. A system engineered around the tests that passes them therefore exposes a limitation of the testbed rather than falsifying the hypothesis.

To date, no artificial system known to the authors has been shown to satisfy all requirements simultaneously without relying on knowledge of the tests, despite each requirement being well-defined and individually attainable. Because systems engineered around the testbed can pass it, passing the AGITB is not by itself evidence of crossing the boundary the requirements delineate; that boundary may nevertheless represent a pathway toward more general forms of intelligence.

Code availability

The reference implementation of the proposed testbed is freely available at https://github.com/matejsprogar/agitb.

Funding

The author acknowledges the financial support from the Slovenian Research Agency (research core funding No. P2-0057).

References

[1] A. M. Turing, "Computing machinery and intelligence," *Mind*, vol. 59, no. 236, pp. 433–460, 1950. [Online]. Available: http://www.jstor.org/stable/2251299

[2] L. Guo, H. Chen, Y. Chen, Y. Bi, and S. Yu, "A neural network for modeling human concept formation, understanding and communication," *Nature Computational Science*, 2026, to be published, doi:10.1038/s43588-026-00956-4.

[3] S. Bringsjord and N. S. Govindarajulu, "Artificial Intelligence," in *The Stanford Encyclopedia of Philosophy*, Spring 2026 ed., E. N. Zalta and U. Nodelman, Eds. Metaphysics Research Lab, Stanford University, 2026. [Online]. Available: https://plato.stanford.edu/archives/spr2026/entries/artificial-intelligence/

[4] N. Maslej, L. Fattorini, R. Perrault, Y. Gil, V. Parli, N. Kariuki, E. Capstick, A. Reuel, E. Brynjolfsson, J. Etchemendy, K. Ligett, T. Lyons, J. Manyika, J. C. Niebles, Y. Shoham, R. Wald, T. Walsh, A. Hamrah, L. Santarlasci, J. B. Lotufo, A. Rome, A. Shi, and S. Oak, "The ai index 2025 annual report," 2025, arXiv:2504.07139.

[5] G. Marcus, "Deep learning: A critical appraisal," 2018, arXiv:1801.00631.

[6] M. Mitchell, "Why AI chatbots lie to us," *Science*, vol. 389, no. 6758, p. eaea3922, 2025, doi:10.1126/science.aea3922.

[7] P. Shojaee, I. Mirzadeh, K. Alizadeh, M. Horton, S. Bengio, and M. Farajtabar, "The illusion of thinking: Understanding the strengths and limitations of reasoning models via the lens of problem complexity," *SuperIntelligence - Robotics - Safety & Alignment*, vol. 2, no. 6, Sep. 2025, doi:10.70777/si.v2i6.15919.

[8] E. M. Bender and A. Koller, "Climbing towards NLU: On meaning, form, and understanding in the age of data," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, D. Jurafsky, J. Chai, N. Schluter, and J. Tetreault, Eds. Online: Association for Computational Linguistics, Jul. 2020, pp. 5185–5198, doi:10.18653/v1/2020.acl-main.463.

[9] Y. Bisk, A. Holtzman, J. Thomason, J. Andreas, Y. Bengio, J. Chai, M. Lapata, A. Lazaridou, J. May, A. Nisnevich, N. Pinto, and J. Turian, "Experience grounds language," in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, B. Webber, T. Cohn, Y. He, and Y. Liu, Eds. Online: Association for Computational Linguistics, Nov. 2020, pp. 8718–8735, doi:10.18653/v1/2020.emnlp-main.703.

[10] A. Srivastava, A. Rastogi, A. Rao, A. A. M. Shoeb, A. Abid, A. Fisch, A. R. Brown, A. Santoro, A. Gupta, A. Garriga-Alonso, A. Kluska, A. Lewkowycz, A. Agarwal, A. Power, A. Ray, A. Warstadt, A. W. Kocurek, A. Safaya, A. Tazarv, A. Xiang, A. Parrish, A. Nie, A. Hussain, A. Askell, A. Dsouza, A. Slone, A. Rahane, A. S. Iyer, A. Andreassen, A. Madotto, A. Santilli, A. Stuhlmüller, A. Dai, A. La, A. Lampinen, A. Zou, A. Jiang, A. Chen, A. Vuong, A. Gupta, A. Gottardi, A. Norelli, A. Venkatesh, A. Gholamidavoodi, A. Tabassum, A. Menezes, A. Kirubarajan, A. Mullokandov, A. Sabharwal, A. Herrick, A. Efrat, A. Erdem, A. Karakaş, B. R. Roberts, B. S. Loe, B. Zoph, B. Bojanowski, B. Özyurt, B. Hedayatnia, B. Neyshabur, B. Inden, B. Stein, B. Ekmekci, B. Y. Lin, B. Howald, B. Orinion, C. Diao, C. Dour, C. Stinson, C. Argueta, C. F. Ramírez, C. Singh, C. Rathkopf, C. Meng, C. Baral, C. Wu, C. Callison-Burch, C. Waites, C. Voigt, C. D. Manning, C. Potts, C. Ramirez, C. E. Rivera, C. Siro, C. Raffel, C. Ashcraft, C. Garbacea, D. Sileo, D. Garrette, D. Hendrycks, D. Kilman, D. Roth, D. Freeman, D. Khashabi, D. Levy, D. M. González, D. Perszyk, D. Hernandez, D. Chen, D. Ippolito, D. Gilboa, D. Dohan, D. Drakard, D. Jurgens, D. Datta, D. Ganguli, D. Emelin, D. Kleyko, D. Yuret, D. Chen, D. Tam, D. Hupkes, D. Misra, D. Buzan, D. C. Mollo, D. Yang, D.-H. Lee, D. Schrader, E. Shutova, E. D. Cubuk, E. Segal, E. Hagerman, E. Barnes, E. Donoway, E. Pavlick, E. Rodola, E. Lam, E. Chu, E. Tang, E. Erdem, E. Chang, E. A. Chi, E. Dyer, E. Jerzak, E. Kim, E. E. Manyasi, E. Zheltonozhskii, F. Xia, F. Siar, F. Martínez-Plumed, F. Happé, F. Chollet, F. Rong, G. Mishra, G. I. Winata, G. de Melo, G. Kruszewski, G. Parascandolo, G. Mariani, G. Wang, G. Jaimovitch-López, G. Betz, G. Gur-Ari, H. Galijasevic, H. Kim, H. Rashkin, H. Hajishirzi, H. Mehta, H. Bogar, H. Shevlin, H. Schütze, H. Yakura, H. Zhang, H. M. Wong, I. Ng, I. Noble,

J. Jumelet, J. Geissinger, J. Kernion, J. Hilton, J. Lee, J. F. Fisac, J. B. Simon, J. Koppel, J. Zheng, J. Zou, J. Kocoń, J. Thompson, J. Wingfield, J. Kaplan, J. Radom, J. Sohl-Dickstein, J. Phang, J. Wei, J. Yosinski, J. Novikova, J. Bosscher, J. Marsh, J. Kim, J. Taal, J. Engel, J. Alabi, J. Xu, J. Song, J. Tang, J. Waweru, J. Burden, J. Miller, J. U. Balis, J. Batchelder, J. Berant, J. Frohberg, J. Rozen, J. Hernandez-Orallo, J. Boudeman, J. Guerr, J. Jones, J. B. Tenenbaum, J. S. Rule, J. Chua, K. Kanclerz, K. Livescu, K. Krauth, K. Gopalakrishnan, K. Ignatyeva, K. Markert, K. D. Dhole, K. Gimpel, K. Omondi, K. Mathewson, K. Chiafullo, K. Shkaruta, K. Shridhar, K. McDonell, K. Richardson, L. Reynolds, L. Gao, L. Zhang, L. Dugan, L. Qin, L. Contreras-Ochando, L.-P. Morency, L. Moschella, L. Lam, L. Noble, L. Schmidt, L. He, L. O. Colón, L. Metz, L. K. Şenel, M. Bosma, M. Sap, M. ter Hoeve, M. Farooqi, M. Faruqui, M. Mazeika, M. Baturan, M. Marelli, M. Maru, M. J. R. Quintana, M. Tolkiehn, M. Giulianelli, M. Lewis, M. Potthast, M. L. Leavitt, M. Hagen, M. Schubert, M. O. Baitemirova, M. Arnaud, M. McElrath, M. A. Yee, M. Cohen, M. Gu, M. Ivanitskiy, M. Starritt, M. Strube, M. Swędrowski, M. Bevilacqua, M. Yasunaga, M. Kale, M. Cain, M. Xu, M. Suzgun, M. Walker, M. Tiwari, M. Bansal, M. Aminnaseri, M. Geva, M. Gheini, M. V. T, N. Peng, N. A. Chi, N. Lee, N. G.-A. Krakover, N. Cameron, N. Roberts, N. Doiron, N. Martinez, N. Nangia, N. Deckers, N. Muennighoff, N. S. Keskar, N. S. Iyer, N. Constant, N. Fiedel, N. Wen, O. Zhang, O. Agha, O. Elbaghdadi, O. Levy, O. Evans, P. A. M. Casares, P. Doshi, P. Fung, P. P. Liang, P. Vicol, P. Alipoormolabashi, P. Liao, P. Liang, P. Chang, P. Eckersley, P. M. Htut, P. Hwang, P. Miłkowski, P. Patil, P. Pezeshkpour, P. Oli, Q. Mei, Q. Lyu, Q. Chen, R. Banjade, R. E. Rudolph, R. Gabriel, R. Habacker, R. Risco, R. Millière, R. Garg, R. Barnes, R. A. Saurous, R. Arakawa, R. Raymaekers, R. Frank, R. Sikand, R. Novak, R. Sitelew, R. LeBras, R. Liu, R. Jacobs, R. Zhang, R. Salakhutdinov, R. Chi, R. Lee, R. Stovall, R. Teehan, R. Yang, S. Singh, S. M. Mohammad, S. Anand, S. Dillavou, S. Shleifer, S. Wiseman, S. Gruetter, S. R. Bowman, S. S. Schoenholz, S. Han, S. Kwatra, S. A. Rous, S. Ghazarian, S. Ghosh, S. Casey, S. Bischoff, S. Gehrmann, S. Schuster, S. Sadeghi, S. Hamdan, S. Zhou, S. Srivastava, S. Shi, S. Singh, S. Asaadi, S. S. Gu, S. Pachchigar, S. Toshniwal, S. Upadhyay, Shyamolima, Debnath, S. Shakeri, S. Thormeyer, S. Melzi, S. Reddy, S. P. Makini, S.-H. Lee, S. Torene, S. Hatwar, S. Dehaene, S. Divic, S. Ermon, S. Biderman, S. Lin, S. Prasad, S. T. Piantadosi, S. M. Shieber, S. Misherghi, S. Kiritchenko, S. Mishra, T. Linzen, T. Schuster, T. Li, T. Yu, T. Ali, T. Hashimoto, T.-L. Wu, T. Desbordes, T. Rothschild, T. Phan, T. Wang, T. Nkinyili, T. Schick, T. Kornev, T. Tunduny, T. Gerstenberg, T. Chang, T. Neeraj, T. Khot, T. Shultz, U. Shaham, V. Misra, V. Demberg, V. Nyamai, V. Raunak, V. Ramasesh, V. U. Prabhu, V. Padmakumar, V. Srikumar, W. Fedus, W. Saunders, W. Zhang, W. Vossen, X. Ren, X. Tong, X. Zhao, X. Wu, X. Shen, Y. Yaghoobzadeh, Y. Lakretz, Y. Song, Y. Bahri, Y. Choi, Y. Yang, Y. Hao, Y. Chen, Y. Belinkov, Y. Hou, Y. Hou, Y. Bai, Z. Seid, Z. Zhao, Z. Wang, Z. J. Wang, Z. Wang, and Z. Wu, "Beyond the imitation game: Quantifying and extrapolating the capabilities of language models," 2023, arXiv:2206.04615.

[11] S. Harnad, "The symbol grounding problem," *Physica D: Nonlinear Phenomena*, vol. 42, no. 1–3, pp. 335–346, 1990, doi:10.1016/0167-2789(90)90087-6.

[12] K. Friston, "The free-energy principle: a unified brain theory?" *Nature Reviews Neuroscience*, vol. 11, no. 2, pp. 127–138, 2010, doi:10.1038/nrn2787.

[13] P. S. Churchland and T. J. Sejnowski, *The Computational Brain*, 2nd ed. Cambridge, MA: MIT Press, 2016.

[14] R. P. N. Rao and D. H. Ballard, "Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects," *Nature Neuroscience*, vol. 2, no. 1, pp. 79–87, 1999, doi:10.1038/4580.

[15] S. Hochreiter and J. Schmidhuber, "Long short-term memory," *Neural Comput.*, vol. 9, no. 8, pp. 1735–1780, Nov. 1997, doi:10.1162/neco.1997.9.8.1735.

[16] J. Hawkins and S. Blakeslee, *On Intelligence*. New York, NY, USA: Times Books, 2005.

[17] M. Hutter, *Universal Artificial Intelligence: Sequential Decisions Based on Algorithmic Probability*. Springer, 2005, doi:10.1007/b138233.

[18] S. Legg and M. Hutter, "Universal intelligence: A definition of machine intelligence," *Minds and Machines*, vol. 17, no. 4, pp. 391–444, 2007, doi:10.1007/s11023-007-9079-x.

[19] A. Clark, "Whatever next? predictive brains, situated agents, and the future of cognitive science," *Behavioral and Brain Sciences*, vol. 36, no. 3, pp. 181–204, 2013, doi:10.1017/S0140525X12000477.

[20] F. Chollet, "On the measure of intelligence," 2019, arXiv:1911.01547.

[21] W. Maass, "Networks of spiking neurons: The third generation of neural network models," *Neural Networks*, vol. 10, no. 9, pp. 1659–1671, 1997, doi:10.1016/S0893-6080(97)00011-7.

[22] W. Gerstner and W. M. Kistler, *Spiking Neuron Models: Single Neurons, Populations, Plasticity*. Cambridge University Press, 2002, doi:10.1017/CBO9780511815706.

[23] R. Gubelmann, "Pragmatic norms are all you need – why the symbol grounding problem does not apply to LLMs," in *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, Y. Al-Onaizan, M. Bansal, and Y.-N. Chen, Eds. Miami, Florida, USA: Association for Computational Linguistics, Nov. 2024, pp. 11663–11678, doi:10.18653/v1/2024.emnlp-main.651.

[24] J. R. Searle, "Minds, brains, and programs," *Behavioral and Brain Sciences*, vol. 3, no. 3, pp. 417–424, 1980, doi:10.1017/S0140525X00005756.

[25] P. Churchland and P. Churchland, "Could a machine think?" *Scientific American*, vol. 262, no. 1, pp. 32–37, 1990, doi:10.1038/scientificamerican0190-32.

[26] A. Zador, S. Escola, B. Richards, B. Ölveczky, Y. Bengio, K. Boahen, M. Botvinick, D. Chklovskii, A. Churchland, C. Clopath, J. DiCarlo, S. Ganguli, J. Hawkins, K. Körding, A. Koulakov, Y. LeCun, T. Lillicrap, A. Marblestone, B. Olshausen, A. Pouget, C. Savin, T. Sejnowski, E. Simoncelli, S. Solla, D. Sussillo, A. S. Tolias, and D. Tsao, "Catalyzing next-generation artificial intelligence through NeuroAI," *Nature Communications*, vol. 14, no. 1, p. 1597, 2023, doi:10.1038/s41467-023-37180-x.

[27] M. Šprogar, "A ladder to human-comparable intelligence: an empirical metric," *Journal of Experimental & Theoretical Artificial Intelligence*, vol. 30, no. 6, pp. 1037–1050, 2018, doi:10.1080/0952813X.2018.1509897.

[28] A.-L. Marais and N. Roche-Labarbe, "Predictive coding and attention in developmental cognitive neuroscience and perspectives for neurodevelopmental disorders," *Developmental Cognitive Neuroscience*, vol. 72, p. 101519, 2025, doi:10.1016/j.dcn.2025.101519.

[29] A. Darriba, Y.-F. Hsu, S. V. Ommen, and F. Waszak, "Intention-based and sensory-based predictions," *Scientific Reports*, vol. 11, p. 19899, 2021, doi:10.1038/s41598-021-99445-z.

[30] S. Cave, "There's no such thing as free will," 2016. [Online]. Available: https://www.theatlantic.com/magazine/archive/2016/06/theres-no-such-thing-as-free-will/480750/



Matej Šprogar is an Assistant Professor at the University of Maribor, Faculty of Electrical Engineering and Computer Science, Maribor, Slovenia. He received the Ph.D. degree in computer science from the University of Maribor, where his doctoral research focused on autonomous evolutionary construction of decision trees. His research interests include artificial general intelligence, machine learning, and evolutionary computation. Contact him at matej.sprogar@um.si.