



**Customer**  
**Global Steel Trading Ltd.**  
Commerce Way 789  
2000 Antwerp  
BE  
[orders@globalsteel.example.com](mailto:orders@globalsteel.example.com)

**Manufacturer**  
**ACME Metal Works GmbH**  
Industrial Park 123  
52066 Aachen  
DE  
[quality@acme-metal.example.com](mailto:quality@acme-metal.example.com)  
**Goods Receiver**  
**Global Steel Trading Ltd. - Rotterdam Warehouse**  
Harbor District 45  
Pier 7  
3089 Rotterdam  
NL

**Digital Material Passport**

ID	DMP-METAL-006	Version	1.0.0
Issue Date	2025-05-18	Certificate Type	EN 10204 3.1

**Business Transaction**

<b>Order</b>		<b>Delivery</b>	
Order ID	PO-65478	Delivery ID	DN-98761
Position	1-10	Position	All
Date	2025-04-15	Date	2025-05-17
Quantity	75000 kg	Quantity	75000 kg

**Product Information**

Product Name	Structural Steel S355J2+N - Various Shapes
Batch ID	H-79513-03
Heat Treatment	Normalized
Surface Condition	Hot-rolled
Production Date	2025-05-16
Country of Origin	DE

**Product Norms**

Designation	EN 10025-2 (2019)
Grade	S355J2+N

**Material Designations**

System	EN
Designation	1.0577

**Chemical Analysis**

Heat Number	H-79513
Melting Process	BOF+LF
Casting Date	2025-05-15
Casting Method	ContinuousCasting
Sample Location	Ladle

Elements

Symbol	C	Mn	Si	P	S	CEV
Unit	%	%	%	%	%	%
Min	-	-	-	-	-	-
Max	0.2	1.6	0.5	0.025	0.02	0.45
Actual	0.17	1.47	0.25	0.017	0.011	0.42

Formula Definitions

**CEV** = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15

Mechanical Properties

Property	Symbol	Actual	Minimum	Maximum	Method	Status
Tensile Strength	Rm	525 MPa	470	630	EN ISO 6892-1	-
Yield Strength	ReH	385 MPa	355		EN ISO 6892-1	-
Elongation after fracture	A	23 %	20		EN ISO 6892-1	-
Charpy V-notch Impact - Energy	KV	42 J	27		EN ISO 148-1	-

Supplementary Tests

Property	Actual	Target/Min	Maximum	Method	Status																																																																								
Product Details -- Item 1: IPE - Beam	Array data (see below)	-		Dimensional Inspection	✓																																																																								
<table><tr><th>Parameter</th><th>Value</th><th>Unit</th></tr><tr><td>Form</td><td></td><td></td></tr><tr><td>Beam</td><td></td><td></td></tr><tr><td>Height</td><td></td><td></td></tr><tr><td>200</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>FlangeWidth</td><td></td><td></td></tr><tr><td>100</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>FlangeThickness</td><td></td><td></td></tr><tr><td>8.5</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>WebThickness</td><td></td><td></td></tr><tr><td>5.6</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>Length</td><td></td><td></td></tr><tr><td>12000</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>Quantity</td><td></td><td></td></tr><tr><td>15</td><td></td><td></td></tr><tr><td>pieces</td><td></td><td></td></tr><tr><td>Weight</td><td></td><td></td></tr><tr><td>15000</td><td></td><td></td></tr><tr><td>kg</td><td></td><td></td></tr></table>	Parameter	Value	Unit	Form			Beam			Height			200			mm			FlangeWidth			100			mm			FlangeThickness			8.5			mm			WebThickness			5.6			mm			Length			12000			mm			Quantity			15			pieces			Weight			15000			kg							
Parameter	Value	Unit																																																																											
Form																																																																													
Beam																																																																													
Height																																																																													
200																																																																													
mm																																																																													
FlangeWidth																																																																													
100																																																																													
mm																																																																													
FlangeThickness																																																																													
8.5																																																																													
mm																																																																													
WebThickness																																																																													
5.6																																																																													
mm																																																																													
Length																																																																													
12000																																																																													
mm																																																																													
Quantity																																																																													
15																																																																													
pieces																																																																													
Weight																																																																													
15000																																																																													
kg																																																																													
Product Details -- Item 2: HEA - Beam	Array data (see below)	-		Dimensional Inspection	✓																																																																								
<table><tr><th>Parameter</th><th>Value</th><th>Unit</th></tr><tr><td>Form</td><td></td><td></td></tr><tr><td>Beam</td><td></td><td></td></tr><tr><td>Height</td><td></td><td></td></tr><tr><td>240</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>FlangeWidth</td><td></td><td></td></tr><tr><td>240</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>FlangeThickness</td><td></td><td></td></tr><tr><td>12</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>WebThickness</td><td></td><td></td></tr><tr><td>7.5</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>Length</td><td></td><td></td></tr><tr><td>8000</td><td></td><td></td></tr><tr><td>mm</td><td></td><td></td></tr><tr><td>Quantity</td><td></td><td></td></tr><tr><td>20</td><td></td><td></td></tr><tr><td>pieces</td><td></td><td></td></tr><tr><td>Weight</td><td></td><td></td></tr><tr><td>20000</td><td></td><td></td></tr><tr><td>kg</td><td></td><td></td></tr></table>	Parameter	Value	Unit	Form			Beam			Height			240			mm			FlangeWidth			240			mm			FlangeThickness			12			mm			WebThickness			7.5			mm			Length			8000			mm			Quantity			20			pieces			Weight			20000			kg							
Parameter	Value	Unit																																																																											
Form																																																																													
Beam																																																																													
Height																																																																													
240																																																																													
mm																																																																													
FlangeWidth																																																																													
240																																																																													
mm																																																																													
FlangeThickness																																																																													
12																																																																													
mm																																																																													
WebThickness																																																																													
7.5																																																																													
mm																																																																													
Length																																																																													
8000																																																																													
mm																																																																													
Quantity																																																																													
20																																																																													
pieces																																																																													
Weight																																																																													
20000																																																																													
kg																																																																													
Product Details -- Item 3: Angle	Array data (see below)	-		Dimensional Inspection	✓																																																																								

Validation

---

We hereby certify that all material described above has been manufactured and tested in accordance with the requirements of EN 10025-2:2019 and EN 10204:2004 type 3.1. The results comply with the requirements for S355J2+N steel grade.

Validated By

Name	Title	Department	Date
Klaus Müller	Quality Control Manager	Quality Assurance	2025-05-18

Data schema maintained by [Material Identity](https://schemas.materialidentity.org/metals-schemas/v0.1.0/schema.json). <https://schemas.materialidentity.org/metals-schemas/v0.1.0/schema.json>