ACME METALS

Digital Material Passport

ID **DMP-METAL-001** - *Version* **1.0.0**
Issue Date **2025-05-14** - *Certificate Type* **EN 10204 3.1**

Manufacturer	Customer	Business Transaction
ACME Metal Works GmbH Industrial Park 123 52066 Aachen DE quality@acme-metal.example.com	**Engineering Solutions Ltd.** Tech Park Way 45 Cardiff CF14 5DU GB procurement@engisolutions.example.com	**Order** PO-78901 · **5000 kg** Pos. 10 · 2025-04-20 **Delivery** DN-56789 · **5000 kg** Pos. 1 · 2025-05-12

Product

Product Name	Structural Steel S355J2	*Name (EN)*	1.0577
Batch ID	H-10987-02	*Shape*	RoundBar - D 50 mm - Length 6000 mm
Surface Condition	Hot-rolled	*Packaging*	Hexagonal bundles of 5 pieces with wire binding in good condition.
Weight	5000 kg	*Product Norm*	EN 10025-2 (2019)
Production Date	2025-05-09	*HS Code*	720839 - Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated
Country of Origin	DE	*CN8 (EU)*	72083900 - Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated, of a thickness of 4.75 mm or more
Specification	EN 10025-2 - Rev 2019		

Heat Treatment

Process: **Normalizing** - *Lot:* HT-2024-11-15-B47 - *Furnace:* FURNACE-03 - *Date:* 2024-11-15

Stage	*Temperature*	*Duration*	*Cooling*	*Atmosphere*
Austenitizing	920 C			

Chemical Analysis

Heat Number **H-10987** - *Melting Process* **EAF+LF** - *Casting Method* **ContinuousCasting** - *Casting Date* **2025-05-08** - *Sample Location* **Ladle**

Symbol	*Unit*	*Min*	*Max*	*Actual*
C	%		0.2	0.18
Mn	%		1.6	1.45
Si	%		0.5	0.25
P	%		0.025	0.018

Symbol	*Unit*	*Min*	*Max*	*Actual*
S	%		0.02	0.012
N	%		0.009	0.006
CEV	%		0.45	0.42

CEV = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15: 0.42%

Mechanical Properties

Property	*Symbol*	*Actual*	*Minimum*	*Maximum*	*Method*
Tensile Strength[1]	Rm	508 / 510 / 512 MPa - Average 510 - Min 508 - Max 512	470 MPa	630 MPa	EN ISO 6892-1
Yield Strength[1]	ReH	378 / 380 / 382 MPa - Average 380 - Min 378 - Max 382	355 MPa		EN ISO 6892-1
Elongation after fracture[1]	A	21.5 / 22 / 22.5 % - Average 22 - Min 21.5 - Max 22.5 - Std Dev 0.5	20 %		EN ISO 6892-1

[1] 3 specimens tested

Validation

We hereby certify that the material described above has been manufactured and tested in accordance with the requirements of EN 10204:2004 type 3.1 and the specified standards. The results comply with the requirements.

Validated by **Johann Weber**, Quality Inspector, Quality Assurance - 2025-05-14

- ✓ Material is of German origin
- ✓ 100% of the material is from European Union sources
- ✓ Material is of non-Russian origin *(EU Regulation No. 833/2014)*
- ✓ Material is conflict-free and sourced responsibly *(OECD Due Diligence Guidance)*