

A01 Manufacturer's plant Steel Mill SE Stahlstrasse 1 Linz 4040, AT A06 Purchaser Steel Trading AG Handelsgasse 1 Berlin 10115, DE

### **Commercial transaction**

A02 Type of inspection document Mill Certificate EN 10204 3.1

A03 Document number 1866645/001

A05 Originator of the document Factory Production Control

A07 Purchaser order number 0334/2019/ZZS

A08 Manufacturer's work order number 958722
A09 Purchaser article number TR-12456

A97 Order position 1

A98 Delivery number DN-1583836 A99 Aviso number AV-87682933

**Supplementary information** 

A10 Buyer Reference Number BRN-1583836
A11 Buyer Reference Date 23/10/2018

## **Production description**

B01 Product Seamleass Steel Tubes Hot Roild

B02 Specification of the product

Steel designation S355J2H, P355NH/TC1, E355+N

 Product norm
 EN 10219-1:2006

 Mass norm
 EN 10220

Material norm EN 10297-1:2003-06

B03 Any supplementary requirements Ausführung lt. EN 10219 Teil 1+2 /--/

B04 Delivery conditionnormalizedB06 Marking of the productSST 200x150x6B07 Identification of the product7282841B08 Number of pieces16

**B09 Product dimensions** 

Form Rectangular tube

 Width
 200 mm

 Height
 150 mm

 Wall thickness
 6.5 mm

 B10 Length
 12000 mm

 B11 Product mass
 1.5 mm

 B12 Theoretical mass
 5738.3 kg

 B13 Actual mass
 5739.3 kg

**Supplementary information** 

*B*99 *B*99 1607219/0001\_20181023\_1529

## Inspection

C00 Batch number Charge Chemical Analysis

#### **Chemical composition**

	C71	C72	C73	C74	C75	C76	C77	C78	C79
Symb	ool C	Si	Mn	Р	S	Al	Cr	Ni	Мо
Unit	%	%	%	%	%	%	%	%	%
Actus	J 0 1500	0.0050	1 0000	0.0140	0.0070	0.0410	0.0200	n nnan	0.0020

#### Supplementary information

# Inspection

Inspection						
C00 Batch number	Charge TensileTest					
CO2 Direction of the test piece	0001 längs					
C03 Test temperature	-20 Celsius					
Tensile test						
C11 Yield or proof strength Streckgrenze ReH/RP0,2	377.12 MPa					
C12 Tensile strength Zugfestigkeit Rm	456.18 MPa					
C13 Elongation after fracture Bruchdehnung A5/A80	29.7 %					
Supplementary information						
C14 Re/Rm	0.83					
C15 Sample Identifier	10001011/175508					
Inspection						
C00 Batch number	Charge HardnessTe	st				
C03 Test temperature	-20 Celsius					
Hardness test						
C30 Method of test	Brunell					
C31 Individual values	71.3, 84.2, 85.2J					
C32 Mean value	80.3 J	min 78.5 J	max 90.6 J			
Inspection						
C00 Batch number	Charge NotchedImp	pactTest				
C03 Test temperature	-20 Celsius	-				
Notched bar impact test						
C40 Type of test piece	0001 längs					
C41 Width of test piece	5 mm					
C42 Individual values	71.2, 84.2, 85.2J					
C43 Mean value	80.3 J	min 78.5 J	max 90.6 J			
Supplementary information						
C44 Sample Identifier	10001011/175508					
Other tests						
D01 Marking, identification, surface appearance, shape and dimensional properties	Marking					
Nondestructive tests						
D02 Visual En 10219-1	100 %	Positive				
D03 Non destructive test EN ISO 10893-2	100 %	Positive				
D04 Dimensional Inspection EN 10219-2	1 Lot	Positive				
Other product tests						
D51 Tensile flattening test	100 %	Positive				
Validation						
Z01 Statement of compliance	We hereby certify, the material described a been tested and corterms of the order.	above has nplies with the				

has been created by a data processing system and does not contain a personal signature but the name and the offical address of the appointet department.



Z02 Date of issue and validationZ03 Stamp of the inspection representative

23/10/2018 John D. Keller Quality Manager

#### **Supplementary information**

205 Quality Department Tel. 206 Quality Department Fax 207 Quality Department Email 208 Ultra Green Steel 209 Steel Mill Green Steel +43 732 1000 8888 +43 732 1000 8889 quality@steelmill.se https://www.steelmill.com/ultragreensteel



Data schema maintained by Material Identity

https://schemas.materialidentity.org/en10168-schemas/v0.5.0/schema.json