ACME METALS

Digital Material Passport

ID **DMP-METAL-006** - *Version* **1.0.0**
Issue Date **2025-05-18** - *Certificate Type* **EN 10204 3.1**

Manufacturer	Customer	Business Transaction
ACME Metal Works GmbH Industrial Park 123 52066 Aachen DE quality@acme-metal.example.com	**Global Steel Trading Ltd.** Commerce Way 789 2000 Antwerp BE orders@globalsteel.example.com	**Order** PO-65478 · **75000 kg** Pos. 1-10 · 2025-04-15 **Delivery** DN-98761 · **75000 kg** Pos. All · 2025-05-17

Goods Receiver
Global Steel Trading Ltd. - Rotterdam Warehouse
Harbor District 45
Pier 7
3089 Rotterdam
NL

Product

Product Name	Structural Steel S355J2+N - Various Shapes	*Name (EN)*	1.0577
Batch ID	H-79513-03	*Marking*	S355J2+N laser marked on web surface with clear legibility.
Surface Condition	Hot-rolled	*Packaging*	Crated bundles of 10 pieces with steel straps in good condition.
Weight	75000 kg	*Product Norm*	EN 10025-2 (2019)
Production Date	2025-05-16	*HS Code*	721633 - H sections of iron or non-alloy steel
Country of Origin	DE	*CN8 (EU)*	72163300 - H-sections of iron or non-alloy steel
Specification	1180-1/ ISO GENERIC - HR - Rev 2024-11-07	*HTS (US)*	7216330000 - H-sections of iron or nonalloy steel

Chemical Analysis

Heat Number **H-79513** - *Melting Process* **BOF+LF** - *Casting Method* **ContinuousCasting** - *Casting Date* **2025-05-15** - *Sample Location* **Ladle**

Symbol	*Unit*	*Min*	*Max*	*Actual*
C	%		0.2	0.17
Mn	%		1.6	1.47
Si	%		0.5	0.25

Symbol	*Unit*	*Min*	*Max*	*Actual*
P	%		0.025	0.017
S	%		0.02	0.011
CEV	%		0.45	0.42

CEV = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15: 0.42%

Mechanical Properties

Property	*Symbol*	*Actual*	*Minimum*	*Maximum*	*Method*
Tensile Strength[1]	Rm	523 / 525 / 527 MPa - Average 525 - Min 523 - Max 527	470 MPa	630 MPa	EN ISO 6892-1
Yield Strength[1]	ReH	383 / 385 / 387 MPa - Average 385 - Min 383 - Max 387	355 MPa		EN ISO 6892-1
Elongation after fracture[1]	A	22.5 / 23 / 23.5 % - Average 23 - Min 22.5 - Max 23.5	20 %		EN ISO 6892-1
Charpy V-notch Impact Energy 3 specimens tested at -20°C	KV	40 / 42 / 44 J - Average 42 - Min 40 - Max 44 - Std Dev 2	27 J		EN ISO 148-1

[1] 3 specimens tested

Validation

We hereby certify that all material described above has been manufactured and tested in accordance with the requirements of EN 10025-2:2019 and EN 10204:2004 type 3.1. The results comply with the requirements for S355J2+N steel grade.

Validated by **Klaus Müller**, Quality Control Manager, Quality Assurance - 2025-05-18