



**Manufacturer**  
**ACME Metal Works GmbH**  
Industrial Park 123  
52066Aachen  
DE  
[quality@acme-metal.example.com](mailto:quality@acme-metal.example.com)

**Customer**  
**Engineering Solutions Ltd.**  
Tech Park Way 45  
Cardiff  
CF14 5DU  
GB  
[procurement@engisolutions.example.com](mailto:procurement@engisolutions.example.com)

**Digital Material Passport**

ID	DMP-METAL-001	Version	1.0.0
Issue Date	2025-05-14	Certificate Type	EN 10204 3.1

**Business Transaction**

<b>Order</b>		<b>Delivery</b>	
Order ID	PO-78901	Delivery ID	DN-56789
Position	10	Position	1
Date	2025-04-20	Date	2025-05-12
Quantity	5000 kg	Quantity	5000 kg
<b>Specification</b>			
Name	EN 10025-2	Revision	2019

**Product Information**

Product Name	Structural Steel S355J2
Batch ID	H-10987-02
Surface Condition	Hot-rolled
Production Date	2025-05-09
Country of Origin	DE

**Customs Classification**

HS Code	720839
Standard Description	Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated
CN8 (EU)	72083900
Description (EU)	Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated, of a thickness of 4.75 mm or more

**Product Norms**

Standard	EN 10025-2 (2019)
----------	-------------------

**Material Designations**

Name (EN)	1.0577
-----------	--------

**Product Shape**

Form	RoundBar
Length	6000 mm

Diameter

50 mm

Delivery Conditions

Bundles

Type	Hexagonal
Quantity	5
Material	Wire binding
Condition	Good

Heat Treatment

Process	Lot	Furnace	Date	
Normalizing	HT-2024-11-15-B47	FURNACE-03	2024-11-15	
Stages				
Stage	Temperature	Duration	Cooling	Atmosphere
Austenitizing	920 C			

Chemical Analysis

Heat Number	H-10987
Melting Process	EAF+LF
Casting Date	2025-05-08
Casting Method	ContinuousCasting
Sample Location	Ladle

Elements

Symbol	C	Mn	Si	P	S	N	CEV
Unit	%	%	%	%	%	%	%
Min	-	-	-	-	-	-	-
Max	0.2	1.6	0.5	0.025	0.02	0.009	0.45
Actual	0.18	1.45	0.25	0.018	0.012	0.006	0.42

Formula Definitions

CEV = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15: 0.42%

Mechanical Properties

Property	Symbol	Actual	Minimum	Maximum	Method	Status
<b>Tensile Strength</b> 3 specimens tested					EN ISO 6892-1	-
<b>Individual Values</b>			# 1	# 2	# 3	
Value [MPa ]			508	510	512	
<b>Statistics</b>	<b>Mean</b>		<b>Min/Max</b>		<b>Std Dev</b>	
	510		508 / 512			
<b>Yield Strength</b> 3 specimens tested					EN ISO 6892-1	-
<b>Individual Values</b>			# 1	# 2	# 3	
Value [MPa ]			378	380	382	
<b>Statistics</b>	<b>Mean</b>		<b>Min/Max</b>		<b>Std Dev</b>	
	380		378 / 382			
<b>Elongation after fracture</b> 3 specimens tested					EN ISO 6892-1	-
<b>Individual Values</b>			# 1	# 2	# 3	
Value [% ]			21.5	22	22.5	
<b>Statistics</b>	<b>Mean</b>		<b>Min/Max</b>		<b>Std Dev</b>	
EN ISO 6892-1 statistical analysis	22		21.5 / 22.5		0.5 ( Sample )	

Validation

We hereby certify that the material described above has been manufactured and tested in accordance with the requirements of EN 10204:2004 type 3.1 and the specified standards. The results comply with the requirements.

Individual Statements

- ✓ Material is of German origin
- ✓ 100% of the material is from European Union sources
- ✓ Material is of non-Russian origin (EU Regulation No. 833/2014)
- ✓ Material is conflict-free and sourced responsibly (OECD Due Diligence Guidance)

Validated By

Name	Title	Department	Date
Johann Weber	Quality Inspector	Quality Assurance	2025-05-14