



Manufacturer  
华强钢铁有限公司  
CN  
518000  
深圳市  
工业开发区钢铁大道888号  
quality@huaqiangsteel.com.cn

Customer  
GLOBAL INDUSTRIES  
Business Park  
20000Commerce City  
FR

Digital Material Passport

|            |                 |                  |              |
|------------|-----------------|------------------|--------------|
| ID         | DMP-X12345-2024 | Version          | 1.0.0        |
| Issue Date | 2024-04-22      | Certificate Type | EN 10204 3.1 |

Business Transaction

|          |            |             |            |
|----------|------------|-------------|------------|
| Order    |            | Delivery    |            |
| Order ID | ORD98765   | Delivery ID | DEL45678   |
| Date     | 2024-01-15 | Date        | 2024-02-27 |
| Quantity | 100 pcs    | Quantity    | 250.0 kg   |

Product Information

|                   |                                           |
|-------------------|-------------------------------------------|
| Product Name      | Flat Bar Alloy 40 x 4 x 6000 mm (STD-101) |
| Batch ID          | B12345                                    |
| Surface Condition | T66                                       |

Material Designations

|             |             |
|-------------|-------------|
| System      | AA          |
| Designation | Al 6060 T66 |

Product Shape

|           |         |
|-----------|---------|
| Form      | FlatBar |
| Length    | 6000 mm |
| Width     | 40 mm   |
| Thickness | 4 mm    |

Chemical Analysis

|             |        |
|-------------|--------|
| Heat Number | H98765 |
|-------------|--------|

Elements

| Symbol | Si     | Fe     | Cu     | Mn    | Mg     | Cr    | Zn    | Ni     | Pb     | Ti     | N    |
|--------|--------|--------|--------|-------|--------|-------|-------|--------|--------|--------|------|
| Unit   | %      | %      | %      | %     | %      | %     | %     | %      | %      | %      | ppm  |
| Min    | 0.3    | 0.1    | -      | -     | 0.35   | -     | -     | -      | -      | -      | -    |
| Max    | 0.6    | 0.3    | 0.1    | 0.1   | 0.6    | 0.05  | 0.15  | 0.05   | 0.05   | 0.1    | 2000 |
| Actual | 0.4502 | 0.1625 | 0.0005 | 0.056 | 0.3795 | 0.004 | 0.005 | 0.0051 | 0.0012 | 0.0148 | 200  |

Mechanical Properties

| Property       | Symbol | Actual | Minimum | Maximum | Method | Status |
|----------------|--------|--------|---------|---------|--------|--------|
| Yield Strength |        |        |         |         |        | -      |

|                   |        |               |       |         |
|-------------------|--------|---------------|-------|---------|
| Individual Values |        | # 1           | # 2   | # 3     |
| Value [MPa ]      |        | 171.2         | 172.5 | 174.0   |
| Statistics        | Mean   | Min/Max       |       | Std Dev |
|                   | 172.56 | 171.2 / 174.0 |       |         |

Tensile Strength

|                   |        |               |       |         |
|-------------------|--------|---------------|-------|---------|
| Individual Values |        | # 1           | # 2   | # 3     |
| Value [MPa ]      |        | 219.8         | 220.3 | 221.0   |
| Statistics        | Mean   | Min/Max       |       | Std Dev |
|                   | 220.35 | 219.8 / 221.0 |       |         |

Elongation

|                   |       |             |      |         |
|-------------------|-------|-------------|------|---------|
| Individual Values |       | # 1         | # 2  | # 3     |
| Value [% ]        |       | 12.5        | 12.8 | 13.2    |
| Statistics        | Mean  | Min/Max     |      | Std Dev |
|                   | 12.83 | 12.5 / 13.2 |      |         |

Hardness

|                               |      |         |     |                    |     |     |
|-------------------------------|------|---------|-----|--------------------|-----|-----|
| Individual Values             |      | # 1     | # 2 | # 3                | # 4 | # 5 |
| Value [HBW ]                  |      | 74      | 75  | 76                 | 75  | 76  |
| Statistics                    | Mean | Min/Max |     | Std Dev            |     |     |
| ASTM E10 statistical analysis | 75.2 | 74 / 76 |     | 0.84<br>( Sample ) |     |     |

Validation

We hereby certify that the product mentioned above fulfills the specifications according to the European Standards EN 755-8. The material described has been tested and complies with terms of the order contract.

Validated By

|            |                 |                   |            |
|------------|-----------------|-------------------|------------|
| Name       | Title           | Department        | Date       |
| John Smith | Quality Manager | Quality Assurance | 2024-04-22 |



Data schema maintained by [Material Identity](https://schemas.materialidentity.org/metals-schemas/v0.1.0/schema.json).