



Manufacturer  
华强钢铁有限公司  
CN  
518000  
深圳市  
工业开发区钢铁大道888号  
quality@huaqiangsteel.com.cn

Customer  
GLOBAL INDUSTRIES  
Business Park  
20000 Commerce City  
FR

Digital Material Passport

|            |                 |                  |              |
|------------|-----------------|------------------|--------------|
| ID         | DMP-X12345-2024 | Version          | 1.0.0        |
| Issue Date | 2024-04-22      | Certificate Type | EN 10204 3.1 |

Business Transaction

|          |            |             |            |
|----------|------------|-------------|------------|
| Order    |            | Delivery    |            |
| Order ID | ORD98765   | Delivery ID | DEL45678   |
| Date     | 2024-01-15 | Date        | 2024-02-27 |
| Quantity | 100 pcs    | Quantity    | 250.0 kg   |

Product Information

|                   |                                           |
|-------------------|-------------------------------------------|
| Product Name      | Flat Bar Alloy 40 x 4 x 6000 mm (STD-101) |
| Batch ID          | B12345                                    |
| Surface Condition | T66                                       |

Material Designations

|             |             |
|-------------|-------------|
| System      | AA          |
| Designation | Al 6060 T66 |

Product Shape

|           |         |
|-----------|---------|
| Form      | FlatBar |
| Length    | 6000 mm |
| Width     | 40 mm   |
| Thickness | 4 mm    |

Chemical Analysis

|             |        |
|-------------|--------|
| Heat Number | H98765 |
|-------------|--------|

Elements

| Symbol | Si     | Fe     | Cu     | Mn    | Mg     | Cr    | Zn    | Ni     | Pb     | Ti     | N    |
|--------|--------|--------|--------|-------|--------|-------|-------|--------|--------|--------|------|
| Unit   | %      | %      | %      | %     | %      | %     | %     | %      | %      | %      | ppm  |
| Min    | 0.3    | 0.1    | -      | -     | 0.35   | -     | -     | -      | -      | -      | -    |
| Max    | 0.6    | 0.3    | 0.1    | 0.1   | 0.6    | 0.05  | 0.15  | 0.05   | 0.05   | 0.1    | 2000 |
| Actual | 0.4502 | 0.1625 | 0.0005 | 0.056 | 0.3795 | 0.004 | 0.005 | 0.0051 | 0.0012 | 0.0148 | 200  |

Mechanical Properties

| Property         | Symbol | Actual     | Minimum | Maximum | Method | Status |
|------------------|--------|------------|---------|---------|--------|--------|
| Yield Strength   | Rp0.2  | 172.56 MPa |         |         |        | -      |
| Tensile Strength | Rm     | 220.35 MPa |         |         |        | -      |
| Elongation       | A50%   | 12.83 %    |         |         |        | -      |
| Hardness         | HB     | 75 HBW     |         |         |        | -      |

Validation

We hereby certify that the product mentioned above fulfills the specifications according to the European Standards EN 755-8. The material described has been tested and complies with terms of the order contract.

Validated By

| Name       | Title           | Department        | Date       |
|------------|-----------------|-------------------|------------|
| John Smith | Quality Manager | Quality Assurance | 2024-04-22 |



Data schema maintained by [Material Identity](https://schemas.materialidentity.org/metals-schemas/v0.0.1/schema.json). <https://schemas.materialidentity.org/metals-schemas/v0.0.1/schema.json>