

Digital Material Passport

ID **DMP-METAL-013** - Version **1.0.0**
Issue Date **2025-05-14** - Certificate Type **EN 10204 3.1**

Manufacturer		Customer	Business Transaction							
ACME Metal Works GmbH Industrial Park 123 52066 Aachen DE quality@acme-metal.example.com		Engineering Solutions Ltd. Tech Park Way 45 Cardiff CF14 5DU GB procurement@engisolutions.example.com	Order	PO-78901 · 5000 kg Pos. 10 · 2025-04-20						
			Delivery	DN-56789 · 5000 kg Pos. 1 · 2025-05-12						
Product										
Product Name	Structural Steel S355J2	Name (EN)	1.0577							
Batch ID	H-10987-02	Shape	RoundBar - D 50 mm - Length 6000 mm							
Strand ID	3	Packaging	Hexagonal bundles of 5 pieces with wire binding in good condition.							
Billet Number	B-4471-01	Product Norm	EN 10025-2 (2019)							
Billet Number	B-4471-02	HS Code	720839 - Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated							
Bundle Number	BDL-118	CN8 (EU)	72083900 - Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated, of a thickness of 4.75 mm or more							
Surface Condition	Hot-rolled									
Weight	5000 kg									
Production Date	2025-05-09									
Country of Origin	DE									
Country of Melt and Pour	CN									
Specification	EN 10025-2 - Rev 2019 - 2019-11-01									
Heat Treatment										
Process: Normalizing - Lot: HT-2024-11-15-B47 - Furnace: FURNACE-03 - Date: 2024-11-15										
Stage	Temperature	Duration	Cooling	Atmosphere						
Austenitizing	920 C									
Chemical Analysis										
Heat Number H-10987 - Melting Process EAF+LF - Casting Method ContinuousCasting - Casting Date 2025-05-08 - Sample Location Ladle										
Symbol	C	Mn	Si	P	S	N	CEV			
Unit	%	%	%	%	%	%	%			
Min										
Max	0.20	1.60	0.50	0.025	0.020	0.009	0.45			
Actual	0.18	1.45	0.25	0.018	0.012	0.006	0.42			
CEV = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15: 0.42%										
Mechanical Properties										
Tensile Strength ¹	Symbol	1	2	3	Average	Min	Max	Spec Min	Spec Max	Method
Value [MPa]	Rm	508	510	512	510	508	512	470	630	EN ISO 6892-1
Yield Strength ¹	Symbol	1	2	3	Average	Min	Max	Spec Min	Method	
Value [MPa]	ReH	378	380	382	380	378	382	355	EN ISO 6892-1	
Elongation after fracture ¹	Symbol	1	2	3	Average	Min	Max	Std Dev	Spec Min	Method
Value [%]	A	21.5	22	22.5	22	21.5	22.5	0.5	20	EN ISO 6892-1
¹ 3 specimens tested										
Validation										
We hereby certify that the material described above has been manufactured and tested in accordance with the requirements of EN 10204:2004 type 3.1 and the specified standards. The results comply with the requirements.						Validated by Johann Weber , Quality Inspector, Quality Assurance - 2025-05-14				