

Digital Material Passport

Manufacturer	Customer	Business Transaction	
ACME Metal Works GmbH Industrial Park 123 52066 Aachen DE quality@acme-metal.example.com	Precision Aerospace Inc. Aviation Boulevard 789 Mountain View 94043 US materials@precision-aero.example.com	Order	PO-34567 · 500 kg Pos. 3 · 2025-04-25
		Delivery	DN-89012 · 500 kg Pos. 1 · 2025-05-14

Product

Product Name	Aluminum Alloy 7075-T6	Name (AA)	7075-T6
Batch ID	H-43210-01	Number (UNS)	A97075
Surface Condition	Rolled	Shape	Plate - Width 1000 mm - Thickness 10 mm - Length 2000 mm
Weight	500 kg	Product Norm	AMS 4045 (2023)
Production Date	2025-05-12		
Country of Origin	DE		

Chemical Analysis

Heat Number H-43210 - Melting Process VAR - Casting Method VacuumCasting - Casting Date 2025-05-10 - Sample Location Ladle

Symbol	Al	Zn	Mg	Cu	Cr	F1
Unit	%	%	%	%	%	
Min		5.1	2.1	1.2	0.18	0.18
Max		6.1	2.9	2	0.28	0.28
Actual	89.7	5.6	2.4	1.5	0.22	0.22

F1 = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15: 0.22

Mechanical Properties

Property	Symbol	Actual	Minimum	Maximum	Method	Status
Tensile Strength ¹	Rm	570 / 572 / 574 MPa - Average 572 - Min 570 - Max 574 - Std Dev 2	530 MPa		ASTM E8	✓
0.2% Yield Strength ¹	Rp0.2	503 / 505 / 507 MPa - Average 505 - Min 503 - Max 507 - Std Dev 2	480 MPa		ASTM E8	✓
Elongation ¹	A	10.8 / 11.2 / 11 % - Average 11 - Min 10.8 - Max 11.2	10 %		ASTM E8	✓

¹ 3 specimens tested

Physical Properties

Property	Symbol	Actual	Target/Min	Maximum	Method	Status
Density	ρ	2.81 g/cm³	2.81 g/cm³		ASTM B311	✓
Coefficient of Thermal Expansion	α	23.4 10 ⁻⁶ /K	23.5 10 ⁻⁶ /K		ASTM E228	✓
Temperature range: 20-100°C						
Thermal Conductivity	λ	130 W/(m·K)	120 W/(m·K)		ASTM E1461	✓
At 25°C						
Specific Heat Capacity	c _p	862 J/(kg·K)	860 J/(kg·K)		ASTM E1269	✓
At 25°C						
Electrical Resistivity	ρ _e	0.0538 μΩ·m		0.055 μΩ·m	ASTM B193	✓
At 20°C						
Poisson's Ratio	ν	0.33	0.33		ASTM E132	✓
Melting Range	T _m	477 - 635 °C	475 - 635 °C		ASTM E1142	✓
Relative Magnetic Permeability	μ _r	1.00002		1.0001	ASTM A342	✓
Surface Roughness	R _a	0.8 μm		1.6 μm	ISO 4287	✓
Emissivity	ε	0.09		0.11	ASTM E408	✓
At 25°C						
Surface Tension	γ	0.875 N/m	0.87 N/m		ASTM D971	✓
Diffusion Coefficient	D	2.3E-9 m²/s	2.2E-9 m²/s		ASTM E1559	✓
Purity					ISO 4967 method B	
Plate II, inspected area approx. 200 mm²						

Inclusion type	A fine	A thick	B fine	B thick	C fine	C thick	D fine	D thick	DS
Value	1	1	1.5	0.5	0.5	0	1	0.5	0.5
Max	2.5	2	2	1	1.5	1	1.5	1	1.5

Validation

We hereby certify that the material described above has been manufactured and tested in accordance with AMS 4045 and the specified test methods. All results are within the specified limits.

Validated by **Elsa Müller**, Materials Engineer, Quality Assurance - 2025-05-15