

Manufacturer	Customer	Business Transaction	
ACME Metal Works GmbH Industrial Park 123 52066 Aachen DE quality@acme-metal.example.com	Precision Aerospace Inc. Aviation Boulevard 789 Mountain View 94043 US materials@precision-aero.example.com	Order	PO-34567 · 500 kg Pos. 3 · 2025-04-25
		Delivery	DN-89012 · 500 kg Pos. 1 · 2025-05-14

Product

Product Name	Aluminum Alloy 7075-T6	Name (AA)	7075-T6
Batch ID	H-43210-01	Number (UNS)	A97075
Surface Condition	Rolled	Shape	Plate - Width 1000 mm - Thickness 10 mm - Length 2000 mm
Weight	500 kg	Product Norm	AMS 4045 (2023)
Production Date	2025-05-12		
Country of Origin	DE		

Chemical Analysis

Heat Number H-43210 - Melting Process VAR - Casting Method VacuumCasting - Casting Date 2025-05-10 - Sample Location Ladle

Symbol	Al	Zn	Mg	Cu	Cr	F1
Unit	%	%	%	%	%	
Min		5.1	2.1	1.2	0.18	0.18
Max		6.1	2.9	2.0	0.28	0.28
Actual	89.7	5.6	2.4	1.5	0.22	0.22

F1 = C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15: 0.22

Mechanical Properties

Tensile Strength ¹	Symbol	1	2	3	Average	Min	Max	Std Dev	Spec Min	Method	Status
Value [MPa]	Rm	570	572	574	572	570	574	2	530	ASTM E8	✓
0.2% Yield Strength ¹	Symbol	1	2	3	Average	Min	Max	Std Dev	Spec Min	Method	Status
Value [MPa]	Rp0.2	503	505	507	505	503	507	2	480	ASTM E8	✓
Elongation ¹	Symbol	1	2	3	Average	Min	Max	Spec Min	Method	Status	
Value [%]	A	10.8	11.2	11	11	10.8	11.2	10	ASTM E8	✓	

¹ 3 specimens tested

Physical Properties

Property	Symbol	Actual	Target/Min	Maximum	Method	Status
Density	ρ	2.81 g/cm³	2.81 g/cm³		ASTM B311	✓
Coefficient of Thermal Expansion Temperature range: 20-100°C	α	23.4 10 ⁻⁶ /K	23.5 10 ⁻⁶ /K		ASTM E228	✓
Thermal Conductivity At 25°C	λ	130 W/(m·K)	120 W/(m·K)		ASTM E1461	✓
Specific Heat Capacity At 25°C	cp	862 J/(kg·K)	860 J/(kg·K)		ASTM E1269	✓
Electrical Resistivity At 20°C	ρe	0.0538 μΩ·m		0.0550 μΩ·m	ASTM B193	✓
Poisson's Ratio	ν	0.33	0.33		ASTM E132	✓
Melting Range	Tm	477 - 635 °C	475 - 635 °C		ASTM E1142	✓
Relative Magnetic Permeability	μr	1.00002		1.00010	ASTM A342	✓
Surface Roughness	Ra	0.8 μm		1.6 μm	ISO 4287	✓
Emissivity At 25°C	ε	0.09		0.11	ASTM E408	✓
Surface Tension	γ	0.875 N/m	0.870 N/m		ASTM D971	✓
Diffusion Coefficient	D	0.0000000023 m²/s	0.0000000022 m²/s		ASTM E1559	✓
Purity Plate II, inspected area approx. 200 mm²					ISO 4967 method B	

Inclusion type	A fine	A thick	B fine	B thick	C fine	C thick	D fine	D thick	DS
Max	2.5	2	2	1	1.5	1	1.5	1	1.5
Value	1	1	1.5	0.5	0.5	0	1	0.5	0.5

Validation

We hereby certify that the material described above has been manufactured and tested in accordance with AMS 4045 and the specified test methods. All results are within the specified limits.

Validated by **Elsa Müller**, Materials Engineer, Quality Assurance - 2025-05-15