Table 3 Physical properties of the SA, GG, and SA/GG films

	Thickn	ess (μm)	TS (M	IPa)	EB (%))	WVP ($\times 10^{-11} \text{ g/(m s Pa)}$
(a) Thickness	s, TS, EB and W	VP of the SA, G	G, and SA/GG f	ilms				
SA	33.25 ± 0.62^{d}		33.30 ± 1.31^{b}		8.37 ± 0.40^{d}		7.21 ± 0.16^{b}	
GG	51.53 ± 1.19^{a}		$26.61 \pm 0.73^{\circ}$		15.62 ± 0.35^{a}		11.17 ± 0.56^{a}	
S1	35.16 ± 1.08^{cd}		33.34 ± 1.11^{b}		10.13 ± 0.34^{c}		7.32 ± 0.60^{a}	
S2	35.14 ± 1.23^{cd}		33.73 ± 1.30^{b}		12.05 ± 0.33^{b}		7.28 ± 0.28^{a}	
S3	34.44 ± 0.39^{d}		34.11 ± 0.94^{b}		15.27 ± 0.30^{a}		7.19 ± 0.19^{a}	
S4	$35.85 \pm 0.76^{\text{cd}}$		34.65 ± 1.06^{b}		$9.93 \pm 0.50^{\circ}$		7.31 ± 0.33^{a}	
S5	37.43 ± 0.93^{b}		37.81 ± 1.11^{a}		8.60 ± 0.34^{d}		7.48 ± 0.29^{a}	
Film type	Light transi	nission (%)						Opacity
	800 nm	600 nm	500 nm	400 nm	350 nm	280 nm	200 nm	

SA	89.01	87.49	86.09	82.96	79.25	70.41	0.21	2.01 ± 0.02^{d}
S1	81.73	79.5	78.21	73.78	70.26	59.15	0.27	$3.24 \pm 0.03^{\circ}$
S2	81.34	76.94	75.08	72.40	66.93	54.95	0.14	$3.28 \pm 0.04^{\circ}$
S3	79.96	76.28	75.05	71.33	66.26	52.22	0.12	3.32 ± 0.06^{bc}
S4	79.77	75.67	74.43	70.03	64.87	49.50	0.09	3.45 ± 0.06^{ab}
S5	77.78	75.06	72.12	66.31	61.80	47.24	0.07	3.54 ± 0.06^{a}

^aThe same superscript letter in the same column means that the two values are not statistically significantly different (p > 0.05) as per the Duncan's multiple range test

Conclusions

In this paper, SA, GG, and SA/GG blend films were prepared by a solvent-casting method. The experimental results show that the performance of the SA/GG blend films are better than that of a single component membrane, especially the SA film is improved in brittleness and flexibility. The mechanical properties showed that, at an SA/GG ratio of 5:1, the EB was 15.27% (an 82.4% increased relative to that of the pure alginate film). The SEM, FTIR-ATR and XRD results revealed that SA has good compatibility with GG, whereby GG is uniformly dispersed in the film structure of SA. The rheological properties confirm the synergy between SA and GG. More importantly, compared to that of the pure SA film, the thermal stability of SA/GG blend films was enhanced. In summary, strong interactions (hydrogen bonding and electrostatic interactions) exist between SA and GG. SA/GG blend films with high mechanical strength, light barrier properties and thermal stability are promising biomaterials and packaging materials with wide application prospects.

Author contributions Conceptualization, funding acquisition and Supervision, JX; methodology, investigation, data curation, TC, and YL; project administration and supervision, JX, XF, XG and XM; sample preparation and collection, YB, YZ; formal analysis and writing,

TC. All authors have read and agreed to the published version of the manuscript.

Funding This work was supported by the project of "Integrated Technology and industrialization of Deep processing of Red Algae Polysaccharide" (Project Number: 2012FJ08).

Compliance with ethical standards

Conflict of interest The authors declare no conflict of interest.

References

- K.R. Aadil, D. Prajapati, H. Jha, Improvement of physcio-chemical and functional properties of alginate film by *Acacia* lignin. Food Packag. Shelf Life. 10, 25–33 (2016)
- M. Guido, S. Sarcognato, G. Pelletti, Sequential development of hepatocellular carcinoma and liver angiosarcoma in a vinyl chloride–exposed worker. Hum. Pathol. 57, 193–196 (2016)
- T.-H. Yuan, J.-L. Chen, R.-H. Shie, Y.-P. Yeh, Y.-H. Chen, C.-C. Chan, Liver fibrosis associated with potential vinyl chloride and ethylene dichloride exposure from the petrochemical industry. Sci. Total Environ. 739, 139920 (2020)
- R. Geyer, J.R. Jambeck, K.L.J.S.A. Law, Findings from university of California in science provides new insights (production, use, and fate of all plastics ever made). Sci. Adv. 3, 7 (2017)
- S. Ghani, H. Barzegar, M. Noshad, M. Hojjati, The preparation, characterization and in vitro application evaluation of



^bData are given as the mean of three replicates ± standard deviation

^cParallel experiments: ten strips were used for each test