



**ADVANCED
TECHNOLOGY
DAYS**

28. i 29. STUDENI 2024.
CINESTAR ARENA ZAGREB

JSON in the world of MSSQL

github.com/matesic-damir/presentations

Damir Matešić, M. Sc. Inf.

- Senior Database Architect @SPAN.eu
- AD 2018 - Leading Data Events in Croatia
- AD 2019 - Introduced SQL/Data Saturday in Croatia
- AD 2020 - Co-founder & organizer of #Dataweekender...
- W: blog.matesic.info
- @: dmatesic@gmail.com
- in: [linkedin.com/in/dmatesic](https://www.linkedin.com/in/dmatesic)



Storing JSON in a SQL Database





MS SQL 2016

SQL 2 JSON

- Pretty much like creating XML data (FOR XML) -> **FOR JSON**
- Two modes supported:
 - **FOR JSON AUTO**
 - **FOR JSON PATH**
- Additional options
 - **INCLUDE_NULL_VALUES**
 - **ROOT**
 - **WITHOUT_ARRAY_WRAPPER**

SQL 2 JSON – data conversion

Source data type	Destination data type
Char, Varchar, Nchar, NVarchar, Text, Ntext, Date, DateTime, DateTime2, DateTimeOffset, Time, UniqueIdentifier, Smallmoney, Money, XML, HierarchyId, Sql_Variant	String
Tinyint, Smallint, Int, Bigint, Decimal, Float, Numeric	Number
Bit	Boolean
Binary, Varbinary, Image, Rowversion, Timestamp	Base 64 encoded string
null	null
geography, geometry, and CLR-based user defined data types	not supported

```

SELECT
    C.[CustomerID]
    , C.[CustomerName]
    , C.PhoneNumber
    , C.FaxNumber
    , C.WebsiteURL
    , GETDATE() AS DataDateTime
FROM
    [Sales].[Customers] AS C
FOR JSON AUTO;

```

```

[
  {
    "CustomerID": 1,
    "CustomerName": "Tailspin Toys (Head Office)",
    "PhoneNumber": "(308) 555-0100",
    "FaxNumber": "(308) 555-0101",
    "WebsiteURL": "http://www.tailspintoys.com",
    "DataDateTime": "2024-08-27T09:56:45.490"
  },
  {
    "CustomerID": 5,
    "CustomerName": "Tailspin Toys (Gasport, NY)",
    "PhoneNumber": "(212) 555-0100",
    "FaxNumber": "(212) 555-0101",
    "WebsiteURL": "http://www.tailspintoys.com/Gasport",
    "DataDateTime": "2024-08-27T09:56:45.490"
  }
]

```

```

SELECT
    C.[CustomerID]
    , C.[CustomerName]
    , C.PhoneNumber AS 'Contact.Phone'
    , C.FaxNumber AS 'Contact.Fax'
    , C.WebsiteURL
    , GETDATE() AS DataDateTime
FROM
    [Sales].[Customers] AS C
FOR JSON PATH;

```

```

[
  {
    "CustomerID": 1,
    "CustomerName": "Tailspin Toys (Head Office)",
    "Contact": {
      "Phone": "(308) 555-0100",
      "Fax": "(308) 555-0101"
    },
    "WebsiteURL": "http://www.tailspintoys.com",
    "DataDateTime": "2024-08-27T09:59:42.907"
  },
  {
    "CustomerID": 5,
    "CustomerName": "Tailspin Toys (Gasport, NY)",
    "Contact": {
      "Phone": "(212) 555-0100",
      "Fax": "(212) 555-0101"
    },
    "WebsiteURL": "http://www.tailspintoys.com/Gasport",
    "DataDateTime": "2024-08-27T09:59:42.907"
  }
]

```


JSON 2 SQL

- OPENJSON
- rowset function (table-valued function)
- Two types of return tables:
 - Default schema
 - Explicit schema

OPENJSON - default schema

- OPENJSON (Expression, [Path])
 - Expression – JSON object in Unicode text format
 - Path – optional argument to specify a fragment (sub-node) of the input expression
- Return - table result with three columns
 - Key
 - Value

0 -> null

1 -> string

2 -> int

3 -> true/false

4 -> array

5 -> object

```

DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://blog.matesic.info",
  "Born": 1979,
  "Pets": null,
  "BornAfterWoodstock": true,
  "FavoriteDrinks": [
    {"Name": "Gin and tonic", "Drink": "Occasionally"},
    {"Name": "Craft beer", "Drink": "Occasionally"},
    {"Name": "Coffee with milk", "Drink": "Daily"},
    {"Name": "Cold water", "Drink": "Daily"}],
  "Parents": {"Mom": "Iva", "Dad": "Boris"}
}';

SELECT * FROM OPENJSON(@JSON_data);

```

	key	value	type
1	Name	John Doe	1
2	BlogURL	http://blog.matesic.info	1
3	Born	1979	2
4	Pets	NULL	0
5	BornAfterWoodstock	true	3
6	FavoriteDrinks	[{"Name": "Gin and tonic", "Drink": "Occasiona...	4
7	Parents	{"Mom": "Iva", "Dad": "Boris"}	5

OPENJSON - explicit schema

- OPENJSON (Expression, [Path])
- [WITH (
 - columnName dataType [columnPath] [AS JSON]
 - [, columnName dataType [columnPath] [AS JSON]]
 -)]
- **columnName** – Name of the output column
- **dataType** – Data type of the output column
- **columnPath** – Optional argument to specify a fragment (sub-node) of the column
- **AS JSON** – Optional argument to specify that the referenced property contains an inner JSON object or array. If used, the column must be NVARCHAR(MAX) data type
- WITH keyword - at least one column must be specified!!!

```

DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://blog.matesic.info",
  "Born": 1979,
  "Pets": null,
  "BornAfterWoodstock": true,
  "FavoriteDrinks": [
    {"Name": "Gin and tonic", "Drink": "Occasionally"}, {"Name": "Craft beer", "Drink": "Occasionally"},
    {"Name": "Coffe with milk", "Drink": "Daily"}, {"Name": "Cold water", "Drink": "Daily"}],
  "Parents": {"Mom": "Iva", "Dad": "Boris"}
}';

-- SELECT * FROM OPENJSON(@JSON_data) WITH (
    Name NVARCHAR(256) '$.Name',
    [Blog URL] NVARCHAR(256) '$.BlogURL',
    Born INT '$.Born',
    Pets NVARCHAR(256) '$.Pets',
    [Favorite drinks] NVARCHAR(MAX) '$.FavoriteDrinks' AS JSON,
    Parents NVARCHAR(MAX) '$.Parents' AS JSON
) Data;

```

	Name	Blog URL	Bom	Pets	Favorite drinks	Parents
1	John Doe	http://blog.matesic.info	1979	NULL	[{"Name": "Gin and tonic", "Drink": "Occasiona...	{"Mom": "Iva", "Dad": "Boris"}

JSON_VALUE

- extracts a scalar value (primitive data type) from a JSON string
- JSON_VALUE (Expression, [Path])
 - **Expression** – JSON object in Unicode text format
 - **Path** – optional argument to specify a fragment (sub-node) of the input expression
- Return – result of nvarchar(4000) data type with the same collation as in the input expression.
- Can be used in SELECT, WHERE, and ORDER BY clauses

```

DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://blog.matesic.info",
  "Born": 1979,
  "Pets":null,
  "BornAfterWoodstock": true,
  "FavoriteDrinks": [
    {"Name": "Gin and tonic","Drink": "Occasionally"}, {"Name": "Craft beer","Drink": "Occasionally"},
    {"Name": "Coffe with milk","Drink": "Daily"}, {"Name": "Cold water","Drink": "Daily"}],
  "Parents": {"Mom": "Iva","Dad": "Boris"}
}';

SELECT
JSON_VALUE(@JSON_data, '$.Name') AS Name,
JSON_VALUE(@JSON_data, '$.BlogURL') AS BlogURL,
JSON_VALUE(@JSON_data, '$.Spouse') AS Spouse,
JSON_VALUE(@JSON_data, '$.BornAfterWoodstock') AS BornAfterWoodstock,
JSON_VALUE(@JSON_data, '$.FavoriteDrinks[0].Name') AS FavoriteDrink,
JSON_VALUE(@JSON_data, '$.NonExistingNode') AS NonExistingNode,
JSON_VALUE(@JSON_data, '$.Parents') AS Parents;

```

Name	BlogURL	Pets	BomAfterWoodstock	FavoriteDrink	NonExistingNode	Parents
John Doe	http://blog.matesic.info	NULL	true	Gin and tonic	NULL	NULL

JSON_QUERY

- extract a JSON fragment or to get a complex value (object or array)
- JSON_QUERY (Expression, [Path])
 - **Expression** – JSON object in Unicode text format
 - **Path** – optional argument to specify a fragment (sub-node) of the input expression
- Return – nvarchar(max) if the input string is defined as (n)varchar(max); otherwise -> nvarchar(4000)


```

DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http:\\www.microsoft.com",
  "Born": 1979,
  "Pets":null,
  "BornAfterWoodstock": true,
  "FavoriteColors": ["Red", "Purple", "Green"]
}';

SELECT
  JSON_QUERY(@JSON_data, '$.Name') AS Name
  , JSON_QUERY(@JSON_data, '$.BornAfterWoodstock') AS BornAfterWoodstock
  , JSON_QUERY(@JSON_data, '$.FavoriteColors') AS FavoriteColors
  , JSON_QUERY(@JSON_data, '$.FavoriteColors[1]') AS SecondColor

```

Name	BornAfterWoodstock	FavoriteColors	SecondColor
NULL	NULL	["Red", "Purple", "Green"]	NULL

Modifying JSON data

- JSON_MODIFY (expression , path , newValue)
 - **Expression** – JSON object in Unicode text format
 - **Path** – A JSON path expression that specifies the property to update
 - **newValue** – The new value for the property specified by path
- Return - updated JSON string
- Adding, Removing, Updating JSON property
- Multiple changes

```
-- Adding currently presenting - 1 (bool)
DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com"
}';
PRINT JSON_MODIFY(@JSON_data, '$."Currently presenting"', CAST(1 AS BIT))
```

```
-- Adding MS SQL meetups - array
DECLARE @MeetupList NVARCHAR(256) = N'["New SQL 2016/2017 functions","SQL & JSON"]';
DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com"
}';
PRINT JSON_MODIFY(@JSON_data, '$.Meetups', JSON_QUERY(@MeetupList));
```

```
-- Removing FavoriteDrinks node
DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com",
  "FavoriteDrinks": [
    {"Name": "Gin and tonic", "Drink": "Occasionally"},
    {"Name": "Craft beer", "Drink": "Occasionally"},
    {"Name": "Coffe with milk", "Drink": "Daily"},
    {"Name": "Cold water", "Drink": "Daily"}
  ],
  "Meetups": ["New SQL 2016/2017 functions", "SQL & JSON"]
}';
PRINT JSON_MODIFY(@JSON_data, '$.FavoriteDrinks', NULL);
```

```
-- Update JSON property to NULL instead of remove - strict!
DECLARE @JSON_data NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com",
  "FavoriteDrinks": [
    {"Name": "Gin and tonic", "Drink": "Occasionally"},
    {"Name": "Craft beer", "Drink": "Occasionally"},
    {"Name": "Coffe with milk", "Drink": "Daily"},
    {"Name": "Cold water", "Drink": "Daily"}
  ],
  "Meetups": ["New SQL 2016/2017 functions", "SQL & JSON"]
}';
PRINT JSON_MODIFY(@JSON_data, 'strict $.FavoriteDrinks', NULL);
```

```
{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com",
  "Currently presenting":true
}
```

```
{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com",
  "Meetups": ["New SQL 2016/2017 functions", "SQL & JSON"]
}
```

```
{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com",
  "Meetups": ["New SQL 2016/2017 functions", "SQL & JSON"]
}
```

```
{
  "Name": "John Doe",
  "BlogURL": "http://www.microsoft.com",
  "FavoriteDrinks": null,
  "Meetups": ["New SQL 2016/2017 functions", "SQL & JSON"]
}
```

ISJSON

- To JSON or not to JSON ?
 - ISJSON (expression)
-
- Expression – The string to test
 - Return – int
 - - 1 - string contains valid JSON
 - - 0 - string is not valid JSON
 - - NULL - input expression is NULL

```
{  
  "Name": "John Doe",  
  "Name": "John Doe",  
  "BlogURL": "http:\\\\www.microsoft.com"  
}
```

T&T - Import JSON from a file

```
SELECT [key], [value], [type]
FROM OPENROWSET (BULK 'C:\Temp\JSON_data.json', SINGLE_CLOB) AS x
CROSS APPLY OPENJSON(BulkColumn);
```

key	value	type
Name	John Doe	1
BlogURL	http://blog.matesic.info	1
Meetups	["New SQL 2016/2017 functions...	4

T&T - Indexing JSON data

```
USE WideWorldImporters;
GO
DROP TABLE IF EXISTS dbo.JSONIndexing;
GO
CREATE TABLE dbo.JSONIndexing(
    [CustomerID] INT NOT NULL,
    [CustomerData] NVARCHAR(2000) NULL,
    CONSTRAINT PK_JSONIndexing PRIMARY KEY CLUSTERED([CustomerID])
);
GO
INSERT INTO dbo.JSONIndexing ([CustomerID], [CustomerData])
SELECT
    [CustomerID]
    , ( SELECT
        C1.[CustomerName] AS Name
        , PC1.FullName AS PrimaryContact
        , C1.PhoneNumber AS 'Contact.Phone', C1.FaxNumber AS 'Contact.Fax'
        , C1.WebsiteURL
        , C1.DeliveryAddressLine1 AS 'Delivery.AddressLine1', C1.DeliveryAddressLine2 AS 'Delivery.AddressLine2'
        , C1.DeliveryPostalCode AS 'Delivery.PostalCode', DC.CityName AS 'Delivery.CityName'
        , C1.PostalAddressLine1 'Postal.AddressLine1' , C1.PostalAddressLine2 'Postal.AddressLine2', C1.PostalPostalCode AS 'Postal.PostalCode'
        , PC.CityName AS 'Postal.CityName'
      FROM
        [Sales].[Customers] C1
        LEFT JOIN [Application].[People] PC1 ON C1.PrimaryContactPersonID = PC1.PersonID
        LEFT JOIN [Application].[Cities] DC ON C1.DeliveryCityID = DC.CityID
        LEFT JOIN [Application].[Cities] PC ON C1.PostalCityID = PC.CityID
      WHERE
        C1.CustomerID = C.CustomerID FOR JSON PATH, WITHOUT_ARRAY_WRAPPER)
FROM [Sales].[Customers] C
GO
```

```
-- Select Idaho City customers
SELECT *
FROM dbo.JSONIndexing
WHERE JSON_VALUE([CustomerData], '$.Postal.CityName') LIKE '%Idaho City%';
```




Table 'JSONIndexing'. Scan count 1, logical reads 75
CPU time = 15 ms

```
-- Add computed column with index
ALTER TABLE dbo.JSONIndexing ADD Customer_City AS JSON_VALUE([CustomerData], '$.Postal.CityName');
CREATE INDEX IDX_Customer_City ON dbo.JSONIndexing(Customer_City);

-- Select Idaho City customers
SELECT *
FROM dbo.JSONIndexing
WHERE JSON_VALUE([CustomerData], '$.Postal.CityName') LIKE '%Idaho City%';
```




Table 'JSONIndexing'. Scan count 1, logical reads 7
CPU time = 0 ms

T&T – Compare records with hash

```
SELECT
    P.*
    , ColumnHashCode =
        HASHBYTES (
            'SHA2_512'
            , (SELECT J.* FROM [Person].[Person] J WHERE J.BusinessEntityID = P.BusinessEntityID FOR JSON AUTO)
        )
FROM
    [Person].[Person] P
```

BusinessEntityID	PersonType	NameStyle	Title	FirstName	MiddleName	LastName	Suffix	EmailPromotion	AdditionalContactInfo	ColumnHashCode
1	EM	0	NULL	Ken	J	Sánchez	NULL	0	NULL	0xD290929D52056B2A70D92FFE3A0D8951AED91A782C0AE0E...
2	EM	0	NULL	Terri	Lee	Duffy	NULL	1	NULL	0xF49354271A5E16AE732901E52A67E879712671F90DC52B677..
3	EM	0	NULL	Roberto	NULL	Tamburello	NULL	0	NULL	0xB9139ED4C434E939B8D7870F57F5245EA532C9B458DA5B00..
4	EM	0	NULL	Rob	NULL	Walters	NULL	0	NULL	0x6E87EA80F2ADCC5D25E59FCC35A9F6BA8C7D469AF40AD95..
5	EM	0	Ms.	Gail	A	Erickson	NULL	0	NULL	0x5C1880E25FAB556C1E65655D4DF23FBDD643D4BAF210BD2..

MS SQL 2022

ISJSON

```
1 SELECT ISJSON(' [{"First name": "Bob", "Last name": "Doe"}] ');
0 SELECT ISJSON(' [{"First name": "Bob", "Last name": "Doe"}] ');

DECLARE @JSON_data1 NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "Born": 1979,
  "FavoriteDrinks": [{"Name": "Gin and tonic", "Drink": "Occasionally"}, {"Name": "Coffe with milk", "Drink": "Daily"}]
}';
1 SELECT ISJSON(@JSON_data1);

DECLARE @JSON_data2 NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "Born": 1979,
  "FavoriteDrinks": [{"Name": "Gin and tonic", "Drink": "Occasionally"}, {"Name": "Coffe with milk", "Drink": "Daily"}]
}';
1 SELECT ISJSON(@JSON_data2, VALUE);
0 SELECT ISJSON ('test string', VALUE)
1 SELECT ISJSON (' [{"First name": "Bob", "Last name": "Doe"}] ', VALUE)

DECLARE @JSON_data3 NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "BornAfterWoodstock": true,
  "FavoriteDrinks": [{"Name": "Gin and tonic", "Drink": "Occasionally"}, {"Name": "Coffe with milk", "Drink": "Daily"}]
}';
1 SELECT ISJSON (@JSON_data3, OBJECT)
0 SELECT ISJSON ('"test string"', OBJECT)

DECLARE @JSON_data4 NVARCHAR(MAX) = N'{
  "Name": "John Doe",
  "Born": 1979,
  "FavoriteDrinks": [{"Name": "Gin and tonic", "Drink": "Occasionally"}, {"Name": "Coffe with milk", "Drink": "Daily"}]
}';
0 SELECT ISJSON (@JSON_data4, ARRAY)
1 SELECT ISJSON (' [{"Name": "Gin and tonic", "Drink": "Occasionally"}, {"Name": "Coffe with milk", "Drink": "Daily"}] ', ARRAY)
1 SELECT ISJSON ('"test string"', SCALAR)
0 SELECT ISJSON ('test string', SCALAR)
```

JSON_PATH_EXISTS

```
DROP TABLE IF EXISTS sql_requests_table_json_object;
```

```
GO
```

```
SELECT JSON_OBJECT('command': r.command, 'status': r.status, 'database_id': r.database_id, 'wait_type': r.wait_type, 'wait_resource': r.wait_resource, 'user': s.is_user_process) as json_object, r.command
```

```
INTO sql_requests_table_json_object
```

```
FROM sys.dm_exec_requests r
```

```
JOIN sys.dm_exec_sessions s
```

```
ON r.session_id = s.session_id
```

```
ORDER BY r.session_id;
```

```
GO
```

```
SELECT * FROM sql_requests_table_json_object;
```

```
GO
```

json_object	command
{"command":"TASK MANAGER","status":"sleeping","databas...	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","databas...	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","databas...	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","databas...	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","databas...	TASK MANAGER

```
SELECT
```

```
    JSON_PATH_EXISTS(json_object, '$.status')
```

```
    , JSON_PATH_EXISTS(command, '$.status')
```

```
FROM sql_requests_table_json_object;
```

1	1	0
2	1	0
3	1	0
4	1	0
5	1	0

JSON_OBJECT

```
DROP TABLE IF EXISTS sql_requests_table_json_object;
GO
SELECT JSON_OBJECT(
    'command': r.command, 'status': r.status, 'database_id': r.database_id, 'wait_type': r.wait_type
    , 'wait_resource': r.wait_resource, 'user': s.is_user_process) as json_object, r.command
INTO sql_requests_table_json_object
FROM sys.dm_exec_requests r
JOIN sys.dm_exec_sessions s
ON r.session_id = s.session_id
ORDER BY r.session_id;
GO
SELECT * FROM sql_requests_table_json_object;
GO
```

json_object	command
{"command":"TASK MANAGER","status":"sleeping","database_id":1,"wait_type":null,"wait_resource":"","user":false}	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","database_id":1,"wait_type":null,"wait_resource":"","user":false}	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","database_id":1,"wait_type":null,"wait_resource":"","user":false}	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","database_id":1,"wait_type":null,"wait_resource":"","user":false}	TASK MANAGER
{"command":"TASK MANAGER","status":"sleeping","database_id":1,"wait_type":null,"wait_resource":"","user":false}	TASK MANAGER

JSON_ARRAY

```
DROP TABLE IF EXISTS sql_requests_json_array;
GO
SELECT r.session_id, JSON_ARRAY(r.command, r.status, r.database_id, r.wait_type, r.wait_resource, s.is_user_process) as json_array, r.command
INTO sql_requests_json_array
FROM sys.dm_exec_requests r
JOIN sys.dm_exec_sessions s
ON r.session_id = s.session_id
ORDER BY r.session_id;
GO
SELECT * FROM sql_requests_json_array;
GO
```

session_id	json_array	command
1	["TASK MANAGER","sleeping",1,"",false]	TASK MANAGER
2	["TASK MANAGER","sleeping",1,"",false]	TASK MANAGER
3	["TASK MANAGER","sleeping",1,"",false]	TASK MANAGER
4	["TASK MANAGER","sleeping",1,"",false]	TASK MANAGER
5	["TASK MANAGER","sleeping",1,"",false]	TASK MANAGER

MS SQL (2025) Azure (preview)

JSON_OBJECTAGG

- Constructs a JSON object from an aggregation of SQL data or columns
- The key/value pairs can be specified as input values,

```
SELECT TOP(5) c.object_id, JSON_OBJECTAGG(c.name:c.column_id) AS columns
FROM sys.columns AS c
GROUP BY c.object_id;
```

object_id	columns
3	{"bitpos":12,"cid":6,"colguid":13,"hbcolid":3,"maxinrowlen":8,"nullbit":11,"offset":10,"ordkey":7,"ordlock":14,"rcmodified":4,"rscolid":2,"rsid":1,"status":9,"ti":5}
5	{"cmprilevel":9,"fgidfs":7,"fillfact":10,"idmajor":3,"idminor":4,"lockres":17,"maxint":13,"maxleaf":12,"maxnullbit":11,"minint":15,"minleaf":14,"numpart":5,"ownertype":2,"rcrows":8,"rowsetid":1,"rsguid":16,"scope_id":18,"status":6}
6	{"cloneid":6,"dbfragid":8,"id":1,"partid":3,"rowsetid":7,"segid":5,"status":9,"subid":2,"version":4}
7	{"aud":1,"fgid":5,"ownerid":3,"pcdata":10,"pcreserved":11,"pcused":9,"pgfirst":6,"pgfirstiam":8,"pgroot":7,"status":4,"type":2}
8	{"fileid":2,"filename":4,"name":3,"status":1}

JSON_ARRAYAGG

- Constructs a JSON array from an aggregation of SQL data or columns

```
SELECT TOP(5) c.object_id, JSON_ARRAYAGG(c.name ORDER BY c.column_id) AS column_list
FROM sys.columns AS c
GROUP BY c.object_id;
```

object_id	column_list
3	["rsid","rscolid","hbcolid","rcmodified","ti","cid","ordkey","maxinrowlen","status","offset","nullbit","bitpos","colguid","ordlock"]
5	["rowsetid","ownertype","idmajor","idminor","numpart","status","fgidfs","rcrows","cmprlevel","fillfact","maxnullbit","maxleaf","maxint","minleaf","minint","rsguid","lockres","scope_id"]
6	["id","subid","partid","version","segid","cloneid","rowsetid","dbfragid","status"]
7	["auid","type","ownerid","status","fgid","pgfirst","pgroot","pgfirstiam","pcused","pcdata","pcreserved"]
8	["status","fileid","name","filename"]

JSON data type

- The new native JSON data type that stores JSON documents in a native binary format
- The JSON type provides a high-fidelity storage of JSON documents optimized for easy querying and manipulation, and provides the following benefits over storing JSON data in varchar or nvarchar:
 - More efficient reads, as the document is already parsed
 - More efficient writes, as the query can update individual values without accessing the entire document
 - More efficient storage, optimized for compression
 - No change in compatibility with existing code

JSON data type

- There are no special index types for JSON data for now (SQL 2025)
- Can't be used as key column in a CREATE INDEX statement!
- Can be specified as an included column in an index definition
- Can appear in the WHERE clause of a filtered index

```

DROP TABLE IF EXISTS [dbo].[OrdersJSON];
DROP TABLE IF EXISTS [dbo].[OrdersN];

CREATE TABLE [dbo].[OrdersJSON]
(
    [order_id] [INT] NOT NULL,
    [order_details] [JSON] NOT NULL,
    CONSTRAINT [PK_OrdersJSON] PRIMARY KEY CLUSTERED ([order_id] ASC)
);

CREATE TABLE [dbo].[OrdersN]
(
    [order_id] [INT] NOT NULL,
    [order_details] [NVARCHAR](MAX) NOT NULL,
    CONSTRAINT [PK_OrdersN] PRIMARY KEY CLUSTERED ([order_id] ASC)
);

INSERT INTO dbo.OrdersJSON
(
    order_id,
    order_details
)
SELECT OrderID, (SELECT o.* FROM sales.orders o WHERE o.OrderID=f.orderid FOR JSON AUTO) FROM Sales.Orders f;

INSERT INTO dbo.OrdersN
(
    order_id,
    order_details
)
SELECT OrderID, (SELECT o.* FROM sales.orders o WHERE o.OrderID=f.orderid FOR JSON AUTO) FROM Sales.Orders f;

SELECT TOP(100) * FROM dbo.OrdersJSON;
SELECT TOP(100) * FROM dbo.OrdersN;

```

order_id	order_details
1	[{"OrderID":1,"CustomerID":832,"SalespersonPersonID":2,"ContactPersonID":3032,"BackorderOrderID":45,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
2	[{"OrderID":2,"CustomerID":803,"SalespersonPersonID":8,"ContactPersonID":3003,"BackorderOrderID":46,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
3	[{"OrderID":3,"CustomerID":105,"SalespersonPersonID":7,"ContactPersonID":1209,"BackorderOrderID":47,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
4	[{"OrderID":4,"CustomerID":57,"SalespersonPersonID":16,"PickedByPersonID":3,"ContactPersonID":1113,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
5	[{"OrderID":5,"CustomerID":905,"SalespersonPersonID":3,"ContactPersonID":3105,"BackorderOrderID":48,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
6	[{"OrderID":6,"CustomerID":976,"SalespersonPersonID":13,"PickedByPersonID":3,"ContactPersonID":3176,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
7	[{"OrderID":7,"CustomerID":575,"SalespersonPersonID":8,"ContactPersonID":2349,"BackorderOrderID":49,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
8	[{"OrderID":8,"CustomerID":964,"SalespersonPersonID":7,"ContactPersonID":3164,"BackorderOrderID":50,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",

order_id	order_details
1	[{"OrderID":1,"CustomerID":832,"SalespersonPersonID":2,"ContactPersonID":3032,"BackorderOrderID":45,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
2	[{"OrderID":2,"CustomerID":803,"SalespersonPersonID":8,"ContactPersonID":3003,"BackorderOrderID":46,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
3	[{"OrderID":3,"CustomerID":105,"SalespersonPersonID":7,"ContactPersonID":1209,"BackorderOrderID":47,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
4	[{"OrderID":4,"CustomerID":57,"SalespersonPersonID":16,"PickedByPersonID":3,"ContactPersonID":1113,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
5	[{"OrderID":5,"CustomerID":905,"SalespersonPersonID":3,"ContactPersonID":3105,"BackorderOrderID":48,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
6	[{"OrderID":6,"CustomerID":976,"SalespersonPersonID":13,"PickedByPersonID":3,"ContactPersonID":3176,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
7	[{"OrderID":7,"CustomerID":575,"SalespersonPersonID":8,"ContactPersonID":2349,"BackorderOrderID":49,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",
8	[{"OrderID":8,"CustomerID":964,"SalespersonPersonID":7,"ContactPersonID":3164,"BackorderOrderID":50,"OrderDate":"2013-01-01","ExpectedDeliveryDate":"2013-01-02",

TableName	SchemaName	rows	TotalSpaceKB	TotalSpaceMB	UsedSpaceKB	UsedSpaceMB	UnusedSpaceKB	UnusedSpaceMB
OrdersN	dbo	73595	53512	52.26	53368	52.12	144	0.14
OrdersJSON	dbo	73595	39432	38.51	39232	38.31	200	0.20

```

SELECT
    JSON_VALUE(order_details, '$[0].CustomerID') AS CustomerID,
    COUNT(*) AS Cnt
FROM [dbo].[OrdersJSON]
WHERE JSON_VALUE(order_details, '$[0].CustomerID') = 1050
GROUP BY JSON_VALUE(order_details, '$[0].CustomerID')
ORDER BY CustomerID;

```

```

SELECT
    JSON_VALUE(order_details, '$[0].CustomerID') AS CustomerID,
    COUNT(*) AS Cnt
FROM [dbo].[OrdersN]
WHERE JSON_VALUE(order_details, '$[0].CustomerID') = 1050
GROUP BY JSON_VALUE(order_details, '$[0].CustomerID')
ORDER BY CustomerID;

```

```

SELECT * FROM [dbo].[OrdersJSON] O CROSS APPLY OPENJSON(O.order_details)

```

```

SELECT *
FROM [dbo].[OrdersJSON] O
    CROSS APPLY
    OPENJSON(CAST(O.order_details AS NVARCHAR(MAX)))
    WITH
    (
        OrderID INT '$.OrderID',
        OrderDate DATE '$.OrderDate'
    ) F
WHERE F.OrderDate = '2013-01-25';

```

```

SELECT *
FROM [dbo].[OrdersN] O
    CROSS APPLY
    OPENJSON(O.order_details)
    WITH
    (
        OrderID INT '$.OrderID',
        OrderDate DATE '$.OrderDate'
    ) F
WHERE F.OrderDate = '2013-01-25';

```

Table 'Worktable'. Scan count 0, logical reads 0
 Table 'OrdersJSON'. Scan count 1, logical reads 4904

SQL Server Execution Times:
 CPU time = 172 ms, elapsed time = 169 ms.

Table 'OrdersN'. Scan count 5, logical reads 7005
 Table 'Worktable'. Scan count 0, logical reads 0

SQL Server Execution Times:
 CPU time = 372 ms, elapsed time = 95 ms.

Msg 13665, Level 16, State 2, Line 53
 OpenJson support not yet supported for JSON native data type.

Table 'OrdersJSON'. Scan count 1, logical reads 4904

SQL Server Execution Times:
 CPU time = 1563 ms, elapsed time = 1588 ms.

Table 'OrdersN'. Scan count 1, logical reads 6671

SQL Server Execution Times:
 CPU time = 593 ms, elapsed time = 583 ms.



THANK YOU