

Update a file through a Python algorithm

Project description

At my organization, access to restricted content is controlled with an allow list of IP addresses. The "allow_list.txt" file identifies these IP addresses. A separate remove list identifies IP addresses that should no longer have access to this content. I created an algorithm to automate updating the "allow_list.txt" file and remove these IP addresses that should no longer have access.

Open the file that contains the allow list

For the first part of the algorithm, I opened the "allow_list.txt" file. First, I assigned this file name as a string to the `import_file` variable:

```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"
```

Then, I used a `with` statement to open the file:

```
# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:
```

In my algorithm, the `with` statement is used with the `.open()` function in read mode to open the allow list file for the purpose of reading it. The purpose of opening the file is to allow me to access the IP addresses stored in the allow list file. The `with` keyword will help manage the resources by closing the file after exiting the `with` statement. In the code `with open(import_file, "r") as file:`, the `open()` function has two parameters. The first identifies the file to import, and then the second indicates what I want to do with the file. In this case, "r" indicates that I want to read it. The code also uses the `as` keyword to assign a variable named `file`; `file` stores the output of the `.open()` function while I work within the `with` statement.

Read the file contents

In order to read the file contents, I used the `.read()` method to convert it into the string.

```
with open(import_file, "r") as file:

    # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

    ip_addresses = file.read()
```

When using an `.open()` function that includes the argument `"r"` for “read,” I can call the `.read()` function in the body of the `with` statement. The `.read()` method converts the file into a string and allows me to read it. I applied the `.read()` method to the `file` variable identified in the `with` statement. Then, I assigned the string output of this method to the variable `ip_addresses`.

In summary, this code reads the contents of the `"allow_list.txt"` file into a string format that allows me to later use the string to organize and extract data in my Python program.

Convert the string into a list

In order to remove individual IP addresses from the allow list, I needed it to be in list format. Therefore, I next used the `.split()` method to convert the `ip_addresses` string into a list:

```
# Use `.split()` to convert `ip_addresses` from a string to a list

ip_addresses = ip_addresses.split()
```

The `.split()` function is called by appending it to a string variable. It works by converting the contents of a string to a list. The purpose of splitting `ip_addresses` into a list is to make it easier to remove IP addresses from the allow list. By default, the `.split()` function splits the text by whitespace into list elements. In this algorithm, the `.split()` function takes the data stored in the variable `ip_addresses`, which is a string of IP addresses that are each separated by a whitespace, and it converts this string into a list of IP addresses. To store this list, I reassigned it back to the variable `ip_addresses`.

Iterate through the remove list

A key part of my algorithm involves iterating through the IP addresses that are elements in the `remove_list`. To do this, I incorporated a `for` loop:

```
# Build iterative statement
# Name loop variable `element`
# Loop through `remove_list`

for element in remove_list:
```

The `for` loop in Python repeats code for a specified sequence. The overall purpose of the `for` loop in a Python algorithm like this is to apply specific code statements to all elements in a sequence. The `for` keyword starts the `for` loop. It is followed by the loop variable `element` and the keyword `in`. The keyword `in` indicates to iterate through the sequence `ip_addresses` and assign each value to the loop variable `element`.

Remove IP addresses that are on the remove list

My algorithm requires removing any IP address from the allow list, `ip_addresses`, that is also contained in `remove_list`. Because all of the elements in `remove_list` are also in the `ip_addresses` list, and because the `ip_addresses` list does not contain duplicates, I was able to incorporate the `.remove()` method into the body of my `for` loop in the following way:

```
for element in remove_list:

    # use the `.remove()` method to remove
    # elements from `ip_addresses`

    ip_addresses.remove(element)
```

Because the IP addresses in the `remove_list` must be deleted from the `ip_addresses` list, I applied `.remove()` to `ip_addresses`. I passed in the loop variable `element` as the argument so that each IP address that was in the `remove_list` would be removed from `ip_addresses`.

Update the file with the revised list of IP addresses

As a final step in my algorithm, I needed to update the allow list file with the revised list of IP addresses. To do so, I first needed to convert the list back into a string. I used the `.join()` method for this:

```
# Convert `ip_addresses` back to a string so that it can be written into the text file

ip_addresses = " ".join(ip_addresses)
```

The `.join()` method combines all items in an iterable into a string. The `.join()` method is applied to a string containing characters that will separate the elements in the iterable once joined into a string. In this algorithm, I used the `.join()` method to create a string from the list `ip_addresses` so that I could pass it in as an argument to the `.write()` method when writing to the file `"allow_list.txt"`. I used a single space `(" ")` as the separator.

Then, I used another `with` statement and the `.write()` method to update the file:

```
# Build `with` statement to rewrite the original file
with open(import_file, "w") as file:
    # Rewrite the file, replacing its contents with `ip_addresses`
    file.write(ip_addresses)
```

This time, I used a second argument of `"w"` with the `open()` function in my `with` statement. This argument indicates that I want to open a file to write over its contents. When using this argument `"w"`, I can call the `.write()` function in the body of the `with` statement. The `.write()` function writes string data to a specified file and replaces any existing file content.

In this case I wanted to write the updated allow list as a string to the file `"allow_list.txt"`. This way, the restricted content will no longer be accessible to any IP addresses that were removed from the allow list. To rewrite the file, I appended the `.write()` function to the file object `file` that I identified in the `with` statement. I passed in the `ip_addresses` variable as the argument to specify that the contents of the file specified in the `with` statement should be replaced with the data in this variable.

Summary

I created an algorithm that removes IP addresses identified in a `remove_list` variable from the `"allow_list.txt"` file of approved IP addresses. This algorithm involved opening the file, converting it to a string to be read, and then converting this string to a list stored in the variable `ip_addresses`. I then iterated through the IP addresses in `remove_list` and removed each of those IP addresses from the `ip_addresses` list with the `.remove()` method. After this, I used the `.join()` method to convert the `ip_addresses` back into a string so that I could write over the contents of the `"allow_list.txt"` file with the revised list of IP addresses.