

A Lean 4 Proof that the Discounted Advantage Is an Unbiased Policy-Gradient Weight

LiZhi Zhou

Project artifact: github.com/math-proof/lemma

Bellman: [V, Q](#), induction: [truncated](#), limit: [REINFORCE](#)

Unbiased advantage estimate: [Lean 4](#)

Abstract

Advantage-weighted policy gradients replace the Monte-Carlo return in REINFORCE by a return minus a state-value baseline, usually written as a discounted sum of temporal-difference errors. That this substitution leaves the gradient unchanged is standard folklore, but the classical arguments are informal about conditioning on null events, about exchanging gradients, infinite sums and expectations, and about the telescoping of an infinite series. We machine-check the statement in Lean 4 with mathlib. The model is a discounted Markov decision process with finite state and action spaces, bounded rewards, and a differentiable stochastic policy π_θ whose parameter θ ranges over an arbitrary real normed space; the law of a trajectory is mathlib’s Ionescu-Tulcea measure. With the exact state values V_t and the advantage $\hat{A}_t = \sum_{k \geq 0} \gamma^k (r_{t+k} + \gamma V_{t+k+1}(s_{t+k+1}) - V_{t+k}(s_{t+k}))$, we prove

$$\sum_t' \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \sum_t' \gamma^t \mathbb{E}_\theta[\hat{A}_t \nabla_\theta \log \pi_\theta(a_t | s_t)].$$

The action-value (occupancy-measure) form of the policy gradient theorem for finite MDPs has been formalized in Lean 4 before, by Zhang [26]. Our development works at the level of trajectories: we formalize the Bellman equations of the model, a one-step recursion for $\nabla_\theta V_t$, and its unrolling by induction into an exact truncated policy-gradient identity with remainder $\gamma^n \mathbb{E}[\nabla_\theta V_n(s_n)]$, whose limit $n \rightarrow \infty$ gives the action-value and the REINFORCE (return-weighted) forms of the theorem; the unbiased advantage estimate above is the main result. The main innovation behind the development is what we call textbook syntactic sugar for limits, expectations and probabilities in Lean: surface notation that compresses verbose measure-theoretic expressions into near-textbook form while elaborating to complete, machine-checked definitions. All theorems depend only on the axioms `propext`, `Classical.choice` and `Quot.sound`. We also report that the reward-independence hypothesis carried by these statements is not used by any proof.

1 Introduction

The policy gradient theorem [22] expresses the gradient of the expected discounted return of a parametrised policy as an expectation of the score $\nabla_\theta \log \pi_\theta(a | s)$ weighted by an action value. REINFORCE [25] weights the score by the sampled return instead. Subtracting a state-dependent baseline does not change the expectation and can reduce variance [25, 3]; with the state-value function as baseline one obtains the advantage, and a discounted sum of temporal-difference residuals of the value function is the $\lambda = 1$ member of generalized advantage estimation [20]. Textbook treatments [21] derive all of this in a few lines.

Those lines hide several analytic steps: the objective is an infinite discounted series, the derivative must be exchanged with that series and with expectations over infinite trajectories, conditional expectations such as $\mathbb{E}[\cdot | s_t = x]$ are undefined at unreachable states, and the telescoping of $\sum_k \gamma^k (\gamma V(s_{t+k+1}) - V(s_{t+k}))$ needs convergence of the boundary term. This

paper records a Lean 4 [2] development, built on mathlib [23, 18] inside the `lemma` library [7], in which each of these steps is checked.

Contributions. The action-value form of the policy gradient theorem for finite MDPs was formalized in Lean 4 earlier by Zhang [26]; Section 2 compares the two developments. Relative to that work, this paper contributes the five items below. Each Lean statement is named by its module path, which links to its interactive page.

1. **Textbook syntactic sugar** (Sections 3 and 4, the primary innovation). Mathlib’s probability notation is measure-theoretic: it names integrals, conditional expectations given a sub- σ -algebra and conditional measures on sets, but it has no textbook notation for limits or for the expectation and probability of named random variables conditioned on observed values. The library adds surface syntax for $\lim$, $\mathbb{E}$ and $\mathbb{P}$ in Lean 4 that compresses such measure-theoretic expressions into near-textbook forms, such as `lim [n → ∞] e = a`, `ℰ[x: π] (f x | y = y0)` and `ℙ[π] (x = x0 | y = y0)`, while keeping their complete semantics: the limit forms are macros that elaborate to mathlib’s filter statements, and the $\mathbb{E}/\mathbb{P}$ forms are macros over a small set of library definitions built from mathlib’s pushforward measures, Radon–Nikodym derivatives and integrals, with no new axioms. We call this *textbook syntactic sugar*: surface syntax that mirrors textbook notation while elaborating to complete, machine-checked definitions; in effect a form of information compression, the most concise notation that still carries the complete semantics. (The generic term *syntactic sugar* goes back to Landin [5].) Statements written with it read almost like the corresponding textbook formulas. In this paper the limit notation is used in Lemma 3.1; the policy-gradient statements are still written in mathlib’s integral notation (Section 4).
2. **Unbiased advantage estimate** (Section 8, the main result). Weighting the score by the discounted sum of temporal-difference residuals of the value function leaves the policy gradient unchanged: `Tensor.EqDot.Grad.Expect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.unbiased_advantage_estimate` [15].
3. **REINFORCE form** (Section 7.4). The policy gradient theorem with the score weighted by the return, `Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.IsFinite.policy_gradient_theorem` [12]; the action-value form `Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.IsFinite.Q_Function` [11] is obtained on the way.
4. **Proof by induction** (Section 7). A one-step recursion for $\nabla_{\theta} V_t$, `Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.recursion` [17], its unrolling by induction, `Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.induct` [16], into an exact truncated identity with remainder $\gamma^n \mathbb{E}[\nabla_{\theta} V_n(s_n)]$, `Tensor.Eq.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient` [14], and the passage to the limit $n \rightarrow \infty$. To our knowledge, this is the first Lean 4 proof of the theorem that follows the textbook derivation, made rigorous by induction (Section 2).
5. **Trajectory-level model** (Sections 5 and 6). A discounted MDP with finite S , A and a parametrised policy whose parameter ranges over an arbitrary real normed space; the law of a trajectory is mathlib’s Ionescu-Tulcea measure `Kernel.trajMeasure`, the value functions V_t, Q_t are conditional expectations, and the Bellman equations are `Tensor.And.Eq.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.Bellman` [10].

Section 3 illustrates the limit notation with `Real.Eq_0.Lim.of.LtAbs.IsFinite` [9], and Section 4 also describes the colour convention with which the library’s renderer displays the statements.

2 Related work

The policy gradient theorem is due to Sutton et al. [22]; the likelihood-ratio estimator and the use of a reinforcement baseline go back to Williams [25]. Greensmith, Bartlett and Baxter [3] analyse baselines as variance-reduction devices, and Schulman et al. [20] introduce generalized advantage estimation, whose $\lambda = 1$ case is the advantage studied here. Standard references for finite MDPs are Puterman [19] and Sutton and Barto [21].

Formalizations. CertRL [24] formalizes convergence of value and policy iteration in Coq, and Chevallier and Fleuriot [1] formalize finite MDPs with rewards in Isabelle/HOL, including the Bellman equation, the existence of an optimal policy for $\gamma < 1$, and value and policy iteration; neither treats policy gradients. In Lean 4, TorchLean [6] proves structural and dynamic-programming facts about MDPs and Bellman operators and contains policy-gradient and PPO training code, but no policy gradient theorem. Closest to this paper is the `PolicyGradient` module of Zhang’s `rl-theory-in-lean` [26], an experimental, largely machine-generated development (its commits are co-authored with an AI assistant) that was committed in March 2026 and later withdrawn from the project’s main branch; it remains accessible at the cited commit. For finite state and action spaces and a policy with finitely many real parameters, it proves in Lean 4 the discounted policy gradient theorem in the occupancy-measure form

$$\nabla_{\theta} J(\theta) = (1 - \gamma)^{-1} \sum_{s,a} d^{\pi_{\theta}}(s) \pi_{\theta}(a \mid s) Q^{\pi_{\theta}}(s, a) \nabla_{\theta} \log \pi_{\theta}(a \mid s),$$

together with a recursion for the gradient of the value function, the log-derivative trick, the Fisher information matrix and the natural policy gradient. That development defines the value function as the fixed point of the Bellman operator (Banach’s fixed-point theorem), obtains its differentiability from $V = (I - \gamma P_{\theta})^{-1} r_{\theta}$, solves the gradient recursion by linear algebra and expands the solution as a Neumann series, which it repackages through the discounted state-occupancy measure $d^{\pi_{\theta}}$; it requires a strictly positive policy and has no trajectories, returns or advantages. Ours works at the level of trajectories: the law of a trajectory is `mathlib’s Kernel.trajMeasure` [18], an implementation of the Ionescu-Tulcea theorem [4], the value functions are conditional expectations, and the parameter ranges over an arbitrary real normed space; besides the action-value form we prove the REINFORCE form and, as the main result, the unbiased advantage estimate. To the best of our knowledge (based on searches of GitHub, arXiv and the web), this is the first Lean 4 proof of the policy gradient theorem that follows the textbook’s pen-and-paper derivation and makes it rigorous by mathematical induction: the textbook [21, §13.2] repeatedly unrolls the one-step recursion and ends with an ellipsis, whereas we prove, by induction on the number n of unrolled steps, an exact finite- n identity with an explicit remainder $\gamma^n \mathbb{E}[\nabla_{\theta} V_n(s_n)]$ over the trajectory measure, from which the infinite-horizon theorem follows by a limit $n \rightarrow \infty$. The only other formal proof we are aware of [26] instead uses a fixed-point characterization and a Neumann series and does not proceed by induction. The two proofs share only their textbook starting point, the one-step gradient recursion of Sutton et al. [22] and the log-derivative trick; otherwise they differ in their definitions, proof route and final statements, and ours was developed independently.

3 Limits as in textbooks

Mathlib states convergence with filters, `Filter.Tendsto  $f$  atTop ( $\mathcal{N} a$ )`, and names a limit value with `Filter.limUnder`; it has no notation that reads like $\lim_{n \rightarrow \infty} e = a$ in a textbook. The library adds a family of macros for that purpose. The two forms used below are

$$\begin{aligned} \lim [n \rightarrow \infty] e = a &\implies \text{Filter.Tendsto } (\text{fun } n \Rightarrow e) \text{ Filter.atTop (nhds } a), \\ \lim [n \rightarrow \infty] e &\implies \text{Filter.limUnder Filter.atTop (fun } n \Rightarrow e). \end{aligned}$$

The same scheme covers $n \rightarrow -\infty$ (`atBot`), a point $x \rightarrow x_0$ (the punctured neighbourhood filter $\mathcal{N}_{\neq}(x_0)$), and one-sided limits $x \rightarrow x_0^+$, $x \rightarrow x_0^-$; the type of the bound variable may be given explicitly, as in $\lim [(n : \mathbb{N}) \rightarrow \infty] e = a$. The library also defines the arrows $x \rightarrow \infty$ and $x \rightarrow 0$ for ordered fields with infinitesimals, meaning that x is infinite, respectively infinitesimal (via `ArchimedeanClass.mk`); they play no role in this paper. In the other direction, an unexpander prints `Filter.Tendsto (fun n => e) atTop (nhds a)` back as $\lim [n \rightarrow \infty] e = a$ in the Lean infoview, and the lemma.cn renderer typesets it as $\lim_{n \rightarrow \infty} e = a$.

Two points matter.

1. **Pure syntax.** The notation consists of macros and pretty-printer unexpanders only. After elaboration nothing of it remains: the metaprogram of Section 9 finds *no* constant of the notation's module in the dependency graph of any theorem in this paper. It adds nothing to the trusted base.
2. **Equation means convergence.** The equation form is parsed as a whole, at higher priority than the bare form, so $\lim [n \rightarrow \infty] e = a$ asserts that the sequence converges to a . It is not the equation $\limUnder(\dots) = a$: `limUnder` is defined through a choice and returns an unspecified value when the sequence diverges, so such an equation could hold for a divergent sequence. We therefore always use the equation form.

Lemma 3.1 ([Real.Eq_0.Lim.of.LtAbs.IsFinite](#) [9]). *Let $\gamma \in \mathbb{R}$ and $x : \mathbb{N} \rightarrow \mathbb{R}$ with $|\gamma| < 1$ and $\{|x_n| : n \in \mathbb{N}\}$ bounded above. Then $\lim_{n \rightarrow \infty} \gamma^n x_n = 0$.*

In Lean the conclusion is written $\lim [n \rightarrow \infty] \gamma \wedge n * x n = 0$, which elaborates to `Filter.Tendsto (fun n =>  $\gamma \wedge n * x n$ ) atTop (nhds 0)`. The proof splits on the sign of γ ; for $0 < \gamma < 1$ it squeezes $|\gamma^n x_n| \leq \gamma^n M$ with `mathlib's tendsto_pow_atTop_nhds_zero_of_lt_one` and `squeeze_zero_norm`. Lemma 3.1 is used twice below: for the remainder of the truncated policy gradient (Section 7.4) and for the boundary term of the telescoping sum (Section 8).

4 Expectation and probability notation

Motivation. Mathlib's probability notation is measure-theoretic. `Mathlib/Probability/Notation.lean` provides $P[X]$ and $\mathbb{E}[X]$ for the integral of X against P and against the ambient measure `volume`, $P[X|m]$ and $\mathbb{E}[X|m]$ for the conditional expectation given a sub- σ -algebra m , $\mathbb{P}$ for `volume` itself, and notation for almost-sure (in)equality and Radon–Nikodym derivatives; `Mathlib/Probability/ConditionalProbability.lean` provides the conditional measure $\mu[|s] = \mu(s)^{-1}\mu|_s$, its value $\mu[t|s]$, and the variant $\mu[|X \leftarrow x]$ for conditioning on $\{X = x\}$. In all of these the measure, the random variable as a function on the sample space, and the conditioning set or σ -algebra are written out explicitly. What is missing is textbook notation: the expectation or probability of named random variables under a given law, conditioned on an observed value, as in $\mathbb{E}[G_t | S_t = s]$ or $\mathbb{P}(X = x | Y = y)$, together with the distinction between a random variable and an observed value. Such quantities have to be written as explicit integrals against conditional or pushforward measures. The value function of Section 5 is an example, and the binder syntax of this section compresses a conditional expectation of the same kind:

textbook	$V_t^\theta(x) = \sum'_k \gamma^k \mathbb{E}_\theta[r_{t+k} s_t = x]$
mathlib form (our model)	$\sum'_k \gamma^k * \int \omega, r (t + k) \omega \partial(\text{M.traj } \theta)[s \ t^{-1}, \{x\}]$
binder syntax	$\mathbb{E}[x : \pi](f \ x \mid y = y_0)$
unfolded to mathlib	$\int a, f \ a \ \partial(\text{ReferenceMeasure.measure.withDensity fun a } \mapsto ((\pi.\text{map fun } \omega \mapsto (x \ \omega, y \ \omega)).\text{rnDeriv ReferenceMeasure.measure (a, y_0) / } (\pi.\text{map } y).\text{rnDeriv ReferenceMeasure.measure } y_0))$

The last row is a representative, slightly simplified unfolding: the macro produces the library term `Expectation.condRV  $\pi$   $x$   $y$   $f$   $y_0$` , which unfolds to the displayed integral for the complex-valued (Bochner) instance of the library’s expectation class, up to $\beta\eta$ -reduction and coercions. This binder syntax and the limit notation of Section 3 make up the textbook syntactic sugar of Section 1, which accounts for a major part of the development effort behind the library code used here. Its role is information compression: each surface form elaborates to a unique term built from `mathlib` and library definitions, so the concise notation still carries the complete semantics.

4.1 Binder syntax

The library defines a binder syntax for expectations of random variables $x : \Omega \rightarrow \alpha$ on a probability space (Ω, π) . Brackets list what is integrated; parentheses hold the integrand, optionally followed by a condition after `|`.

Lean surface form	meaning
$\mathbb{E}[x : \pi] (f \ x)$	scalar $\mathbb{E}_\pi[f(x)]$
$\mathbb{E}[x : \pi] (f \ x \mid y = y_0)$	scalar, conditioned on the observation $y = y_0$
$\mathbb{E}[x : \pi] (f \ x \mid y)$	random in y : $\omega \mapsto \mathbb{E}_\pi[f(x) \mid y = y(\omega)]$
$\mathbb{E}[x : \pi \mid y] ((x + y)^2)$	integrate x , leave y free: a random variable in y

Several integrated variables ($\mathbb{E}[x, z : \pi] (\dots)$) are packed into their joint law, which is not the product of marginals unless the variables are independent. Probabilities use the same pattern: $\mathbb{P}[\pi] (x = x_0)$ is the probability that x takes the value x_0 , $\mathbb{P}[\pi] (x = x_0 \mid y = y_0)$ is a conditional probability at a fixed observation, $\mathbb{P}[\pi] (x = x_0 \mid y)$ is the random quantity $\omega \mapsto \mathbb{P}(x = x_0 \mid y = y(\omega))$, and a bare $\mathbb{P}[\pi] (x)$ is the density evaluated at the random point $x(\omega)$. In these forms `=` reads “evaluated at”, $\wedge$ packs a joint point, and `|` is conditioning.

4.2 Colours

The `lemma.cn` renderer typesets every Lean statement in L^AT_EX and colours identifiers by their probabilistic role. The rules, read off the renderer’s source, are:

- **red: random variable.** A variable declared as a function $\Omega \rightarrow \alpha$ out of the sample space of a probability measure (a measure carrying `IsProbabilityMeasure` or the library’s `PSpace` instance); the integrated variable of an $\mathbb{E}$ binder; the variable on the left of `=` in a $\mathbb{P}$ event.
- **magenta: random argument.** A random variable used as the argument of a function, so that the whole expression is itself random: the free variables after `|` inside $\mathbb{E}$ brackets, the conditioning list in $\mathbb{E}(\dots \mid y)$, and the bare factors in $\mathbb{P}(x)$ or $\mathbb{P}(x \mid y)$.
- **Black: observed value.** Ordinary, deterministic terms, such as the fixed values x_0, y_0 of an observation.

Thus $\mathbb{E}[y \mid x = x]$ is a number, while $\mathbb{E}[y \mid x]$ is the random variable obtained by substituting $x(\omega)$ for x in it. We use the same convention in this paper: s_t, a_t, r_t are red, x, u, y are black states and actions, and $V_t(s_t)$, printed with a magenta argument, is a function of the state evaluated along the trajectory.

4.3 What the policy-gradient statements use

The theorems of Sections 6–8 are written directly with `mathlib`’s Bochner integral and conditional measure rather than with the binder syntax: $\mathbb{E}_\theta[f]$ is $\int \omega, f \ \omega \ \partial \mathbf{M}.\text{traj} \ \theta$, and $\mathbb{E}_\theta[f \mid B]$ is the integral against $(\mathbf{M}.\text{traj} \ \theta) \llbracket B \rrbracket$, where `mathlib` defines $\mu \llbracket B \rrbracket = \mu(B)^{-1} \mu|_B$.

When $\mu(B) = 0$ this is the zero measure, so a conditional expectation at an unreachable state is 0; several hypotheses below are therefore restricted to *reachable* pairs (t, x) , those with $\mathbb{P}_\theta(\mathbf{s}_t = x) \neq 0$. We also recall that Lean’s `tsun` ($\sum'$) is the sum of a summable family and 0 otherwise.

5 The MDP model

Definition 5.1 (Model). *Let S and A be finite types with the discrete σ -algebra and let Θ be a real normed space. A policy is a function $\pi : \Theta \rightarrow S \rightarrow A \rightarrow \mathbb{R}$, written $\pi_\theta(u \mid x)$, with $\pi_\theta(u \mid x) \geq 0$ and $\sum_u \pi_\theta(u \mid x) = 1$. An environment consists of an initial probability measure ι on S , a Markov kernel T from $S \times A$ to S , a Markov kernel R from $S \times A$ to $\mathbb{R}$ (the reward law), and a bound $R_{\max}$ with $R(x, u)(\mathbb{R} \setminus [-R_{\max}, R_{\max}]) = 0$ for all (x, u) . A model M is an environment together with a policy.*

A trajectory is a sequence $\omega \in (S \times A \times \mathbb{R})^\mathbb{N}$ of stages; the coordinates are $\mathbf{s}_t(\omega)$, $\mathbf{a}_t(\omega)$, $\mathbf{r}_t(\omega)$. One stage from a state x is drawn by the kernel $\kappa_\theta(x) = \delta_x \otimes (\pi_\theta(\cdot \mid x) \otimes R)$: the action is sampled from the policy and the reward from $R(x, \cdot)$. The stage chain has kernel $K_\theta(x, u, \rho) = (\kappa_\theta \circ T)(x, u)$, which ignores the reward ρ , and first-stage law $\mu_0 = \kappa_\theta \circ \iota$.

Definition 5.2 (Trajectory measure). $\mathbb{P}_\theta = \text{Kernel.trajMeasure } \mu_0 (K_\theta)_n$ on $(S \times A \times \mathbb{R})^\mathbb{N}$, where the n -th kernel reads only the last stage of the history.

This is the Ionescu-Tulcea extension [4] of the stage chain, provided by `mathlib` [18]; it is a probability measure. The law is time-homogeneous and Markov by construction: nothing beyond the kernels is assumed about the trajectory.

Definition 5.3 (Value functions). For $\gamma \in \mathbb{R}$, $t \in \mathbb{N}$, $x \in S$, $u \in A$,

$$V_t^\theta(x) = \sum'_k \gamma^k \mathbb{E}_\theta[\mathbf{r}_{t+k} \mid \mathbf{s}_t = x], \quad Q_t^\theta(x, u) = \sum'_k \gamma^k \mathbb{E}_\theta[\mathbf{r}_{t+k} \mid \mathbf{s}_t = x, \mathbf{a}_t = u].$$

The discounted return from time t is $G_t = \sum'_k \gamma^k \mathbf{r}_{t+k}$.

The model file also proves that on reachable states $V_t^\theta(x)$ equals a time-free closed form $V_c^\theta(x)$, that $|Q_t^\theta| \leq (1 - \gamma)^{-1} |R_{\max}|$, and that almost surely G_t is a convergent series with the same bound. The objective is $J(\theta) = \sum'_t \gamma^t \mathbb{E}_\theta[\mathbf{r}_t]$; a model lemma (`obj_hasFDerivAt`) shows that, for $\gamma \in [0, 1)$ and a differentiable policy with uniformly bounded gradient, J is Fréchet differentiable with

$$\nabla_\theta J(\theta) = \sum'_t \gamma^t \nabla_\theta \mathbb{E}_\theta[\mathbf{r}_t]. \quad (1)$$

All policy-gradient statements below have the right-hand side of (1) as their left-hand side.

Standing hypotheses. We abbreviate the recurring hypotheses:

- (D) $\gamma \in [0, 1)$;
- (P1) $\theta \mapsto \pi_\theta(u \mid x)$ is differentiable for every x, u ;
- (P2) $\sup_{\theta, x, u} \|\nabla_\theta \pi_\theta(u \mid x)\| < \infty$;
- (I) for every t , $\mathbf{r}_t$ is independent of the history $(\mathbf{s}_i, \mathbf{a}_i)_{i < t}$ under $\mathbb{P}_\theta$.

Hypothesis (I) appears in the statements; Section 9 shows it is not used by their proofs.

6 Bellman equations

Theorem 6.1 (Bellman equations [10]). *Assume (I) at time t and (D), and let $V_t = V_t^\theta$, $Q_t = Q_t^\theta$. Then for all $x \in S$, $u \in A$:*

$$\begin{aligned} V_t(x) &= \mathbb{E}_\theta [Q_t(x, a_t) \mid s_t = x], \\ V_t(x) &= \mathbb{E}_\theta [r_t + \gamma V_{t+1}(s_{t+1}) \mid s_t = x], \\ Q_t(x, u) &= \mathbb{E}_\theta [r_t + \gamma V_{t+1}(s_{t+1}) \mid s_t = x, a_t = u]. \end{aligned}$$

The three equalities are assembled from `Tensor.EqExpect.of.Eq_Expect.V_Function` (the policy average of Q_t), `Tensor.EqExpect.of.Eq_Conditioned.Bellman.V_Function` and `Tensor.EqExpect.of.Eq_Conditioned.Bellman.Q_Function`. Both sides vanish when the conditioning event is null. The first lemma needs only (D); the doc comments of the other two record that their independence hypothesis is unnecessary for a Markov model, and in Lean it is an unused, underscore-named argument. For $\gamma = 1$ the Lean series `tsum` of a non-summable family is 0, and the first identity fails, which is why (D) is required.

7 The policy gradient theorem by induction

The route to the policy gradient theorem in the library differentiates the Bellman equation once, unrolls the result by induction on the horizon, integrates over the initial state, and finally lets the horizon tend to infinity.

7.1 One-step recursion

Theorem 7.1 (Recursion [17]). *Assume (I) at time t , (D), (P1), (P2), and let x be reachable at time t . Then*

$$\nabla_\theta V_t(x) = \sum_u Q_t(x, u) \nabla_\theta \pi_\theta(u \mid x) + \gamma \sum_y \mathbb{P}_\theta(s_{t+1} = y \mid s_t = x) \nabla_\theta V_{t+1}(y),$$

where $\nabla_\theta V_t(x)$ is the Fréchet derivative of $\theta \mapsto V_t^\theta(x)$, and Q, V are the value functions of the model regarded as functions of θ .

The proof rewrites V_t by its closed form and uses the model lemma `grad.V_rec`, the derivative of the Bellman equation of Theorem 6.1; the conditional transition probability is then identified with the kernel $\sum_u \pi_\theta(u \mid x) T(x, u, y)$.

7.2 Unrolling by induction

Theorem 7.2 (Unrolled recursion [16]). *Assume (I) for every t , (D), (P1), (P2), and let x be reachable at time 0. Then for every $n \in \mathbb{N}$,*

$$\begin{aligned} \nabla_\theta V_0(x) &= \sum_{t < n} \gamma^t \sum_y \mathbb{P}_\theta(s_t = y \mid s_0 = x) \sum_u Q_t(y, u) \nabla_\theta \pi_\theta(u \mid y) \\ &\quad + \gamma^n \sum_y \mathbb{P}_\theta(s_n = y \mid s_0 = x) \nabla_\theta V_n(y). \end{aligned}$$

Proof sketch. The conditional probabilities are replaced by the t -step kernel $P_\theta^t(x, y)$. Induction on n : the case $n = 0$ is trivial. For $n + 1$, the remainder $\gamma^n \sum_y P_\theta^n(x, y) \nabla_\theta V_n(y)$ is expanded with Theorem 7.1 at every y with $P_\theta^n(x, y) \neq 0$ (such y are reachable at time n); the resulting double sum is collapsed by the Chapman–Kolmogorov identity $P_\theta^{n+1}(x, z) = \sum_y P_\theta^n(x, y) P_\theta^1(y, z)$. $\square$

7.3 The truncated identity

Theorem 7.3 (Truncated policy gradient [14]). *Assume (I) for every t , (D), (P1), (P2). Then for every $n \in \mathbb{N}$,*

$$\sum_t' \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \mathbb{E}_\theta \left[\sum_{t < n} \gamma^t Q_t(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t) \right] + \gamma^n \mathbb{E}_\theta [\nabla_\theta V_n(s_n)].$$

Proof sketch. By the model lemma `grad_obj`, the left-hand side equals $\sum_x \iota(x) \nabla_\theta V_c^\theta(x)$. For each x with $\iota(x) \neq 0$, Theorem 7.2 expands $\nabla_\theta V_0(x)$. On the right, the lemma `E_score` evaluates $\mathbb{E}_\theta[g(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)] = \sum_y \mathbb{P}_\theta(s_t = y) \sum_u g(y, u) \nabla_\theta \pi_\theta(u \mid y)$, which is the log-derivative identity $\pi \nabla_\theta \log \pi = \nabla_\theta \pi$ summed against the law of (s_t, a_t) ; the state marginal is $\mathbb{P}_\theta(s_t = y) = \sum_x \iota(x) P_\theta^t(x, y)$. Both sides are then equal finite sums. $\square$

Despite the finite sum over $t < n$, Theorem 7.3 concerns the discounted infinite-horizon objective: it is an exact identity for every truncation level, with an explicit remainder. It is not a statement about a finite-horizon MDP.

7.4 Passing to the limit

Letting $n \rightarrow \infty$ in Theorem 7.3 gives the policy gradient theorem, first with action values and then in REINFORCE form.

Theorem 7.4 (Policy gradient, action-value form [11]). *Assume (I) for every t , (D), (P1), (P2), and*

$$(B_{\nabla V}) \sup\{\|\nabla_\theta V_t(x)\| : \mathbb{P}_\theta(s_t = x) \neq 0\} < \infty.$$

Then

$$\sum_t' \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \sum_t' \gamma^t \mathbb{E}_\theta [Q_t(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)].$$

Proof sketch. The remainder satisfies $\|\mathbb{E}_\theta[\nabla_\theta V_n(s_n)]\| \leq \max(B, 0)$, because only reachable states carry mass; hence $\lim_{n \rightarrow \infty} \gamma^n \|\mathbb{E}_\theta[\nabla_\theta V_n(s_n)]\| = 0$ by Lemma 3.1, and `tendsto_zero_iff_norm_tendsto_zero` turns this into $\lim_{n \rightarrow \infty} \gamma^n \mathbb{E}_\theta[\nabla_\theta V_n(s_n)] = 0$. Each term of the right-hand series is bounded by $\gamma^t |A| (1 - \gamma)^{-1} |R_{\max}| \max(C, 0)$, with C the bound of (P2), so the series is summable. Integral and finite sum are exchanged, the partial sums of the right-hand series converge to its `tsum` (`HasSum.tendsto_sum_nat`), and the two limits coincide by uniqueness of limits (`tendsto_nhds_unique`). $\square$

Lemma 7.5 (Tower property [13]). *Under (I) at time t and (D), $\mathbb{E}_\theta[G_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)] = \mathbb{E}_\theta[Q_t(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)]$.*

Theorem 7.6 (Policy gradient, REINFORCE form [12]). *Assume (I) for every t , (D), (P1), (P2), and that $\|\sum_k' \gamma^k \nabla_\theta \mathbb{E}_\theta[r_{t+k} \mid s_t = x]\|$ is bounded over reachable pairs (t, x) . Then*

$$\sum_t' \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \sum_t' \gamma^t \mathbb{E}_\theta [G_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)].$$

The bound is converted into $(B_{\nabla V})$ by the model lemma `sum_grad_cond`, which exchanges ∇_θ with the series on reachable states; then Theorem 7.4 and Lemma 7.5 give the claim termwise.

How limits are handled. Throughout, infinite sums are Lean's `tsum` and every limit is an explicit `Filter.Tendsto` statement (written with the notation of Section 3 where convenient). The objective and the returns are `tsums` whose summability comes from domination by a geometric series (`summable_geometric_of_lt_one`, `Summable.of_norm_bounded`, `Summable.mul_right`; for the returns also `hasSum_geometric_of_lt_one`). The gradient is exchanged with the discounted series by `mathlib`'s `hasFDerivAt_tsum`, which yields (1) and the analogous statement

for V_c^θ . Passing from partial sums to the `tsum` uses `HasSum.tendsto_sum_nat` together with `tendsto_nhds_unique`. No dominated-convergence theorem and no interchange of an integral with a series is cited: expectations of functions of (s_t, a_t) reduce to finite sums over $S \times A$ (model lemmas `E_score` and `E_s1`), which is where finiteness of the state and action spaces is used.

8 Main result: the unbiased advantage estimate

Theorem 8.1 (Unbiased advantage estimate [15]). *Let $V : \Theta \rightarrow \mathbb{N} \rightarrow S \rightarrow \mathbb{R}$ satisfy $V_t^\theta(x) = \sum'_k \gamma^k \mathbb{E}_\theta[r_{t+k} \mid s_t = x]$ for all θ, t, x . Assume (I) for every t , (D), (P1), (P2), and*

$$(B_{\nabla V}) \sup\{\|\nabla_\theta V_t(x)\| : \mathbb{P}_\theta(s_t = x) \neq 0\} < \infty;$$

$$(B_V) \sup\{|V_t^\theta(x)| : \mathbb{P}_\theta(s_t = x) \neq 0\} < \infty.$$

Define the advantage

$$\hat{A}_t = \sum'_k \gamma^k (r_{t+k} + \gamma V_{t+k+1}^\theta(s_{t+k+1}) - V_{t+k}^\theta(s_{t+k})).$$

Then

$$\sum'_t \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \sum'_t \gamma^t \mathbb{E}_\theta[\hat{A}_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)].$$

By (1) the left-hand side is $\nabla_\theta J(\theta)$. The summand of $\hat{A}_t$ is $\gamma^k \delta_{t+k}$ with the temporal-difference residual $\delta_j = r_j + \gamma V_{j+1}(s_{j+1}) - V_j(s_j)$, so $\hat{A}_t$ is the generalized advantage estimator with $\lambda = 1$ [20] computed with the exact value function.

Proof. Step 1: reduce to REINFORCE. Hypothesis $(B_{\nabla V})$ is rewritten, through `sum_grad_cond`, into the bound required by Theorem 7.6, which turns the left-hand side into

$$\sum'_t \gamma^t \mathbb{E}_\theta[G_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)].$$

It remains to show, for each t ,

$$\mathbb{E}_\theta[\hat{A}_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)] = \mathbb{E}_\theta[G_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)].$$

Step 2: telescoping, almost surely. Almost surely the series $\sum_k \gamma^k r_{t+k}$ converges to G_t (model lemma `G_hasSum`), and every visited state is reachable (`reach_ae`), so (B_V) gives $|V_k(s_k(\omega))| \leq B$ for all k . Put $b_k = \gamma^k V_{t+k}^\theta(s_{t+k}(\omega))$. Then $\gamma^k \delta_{t+k} = \gamma^k r_{t+k} + (b_{k+1} - b_k)$, the differences are summable because $|b_{k+1} - b_k| \leq 2B\gamma^k$, and $\lim_{k \rightarrow \infty} b_k = 0$ by Lemma 3.1; hence $\sum_k (b_{k+1} - b_k) = -b_0$ and

$$\hat{A}_t = G_t - V_t(s_t) \quad \mathbb{P}_\theta\text{-almost surely.}$$

Step 3: the baseline vanishes. By linearity of the integral (both integrands are integrable), $\mathbb{E}_\theta[\hat{A}_t \nabla_\theta \log \pi_\theta] = \mathbb{E}_\theta[G_t \nabla_\theta \log \pi_\theta] - \mathbb{E}_\theta[V_t(s_t) \nabla_\theta \log \pi_\theta]$. The model lemma `E_h_score` states $\mathbb{E}_\theta[h(s_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)] = 0$ for every $h : S \rightarrow \mathbb{R}$; it rests on the zero-mean score identity $\sum_u \pi_\theta(u \mid x) \nabla_\theta \log \pi_\theta(u \mid x) = 0$ (`score_zero`), which in Lean needs no positivity of π because the terms with $\pi_\theta(u \mid x) = 0$ vanish. A conditional version with a positivity hypothesis is `Random.ExpectConditionedGrad_LogProb.eq.Zero.policy` [8]. $\square$

Remark 8.2. Steps 2 and 3 use only that V is a function of (t, x) bounded along reachable states; the defining equation of V is used in Step 1 and through $(B_{\nabla V})$. This suggests that the same identity holds for any bounded critic in place of the exact value function. The Lean statement does not claim this.

9 Formalization artifact

Modules. Each theorem above links to its module at commit `c7c71c4` of [7] (prefix `Lemma.` omitted). The model, its Markov-chain lemmas and its differentiability lemmas live in three further files under the namespace `PolicyGradient`.

Checking. The project uses Lean `v4.33.1` with `mathlib`. `lake build` of the main module completes without errors, and neither it nor any of the local modules it imports contains `sorry`, `admit` or a new `axiom`. `#print axioms`, run from a scratch file outside the repository, reports for Theorems [6.1](#), [7.1](#), [7.2](#), [7.3](#), [7.4](#), [7.6](#) and [8.1](#), for Lemma [7.5](#) and for the three Bellman components the axioms `propext`, `Classical.choice`, `Quot.sound` and nothing else. A metaprogram run from the same scratch file walks the dependency graphs of Theorems [7.1](#), [7.2](#), [7.3](#), [7.4](#), [7.6](#) and [8.1](#): the notation module of Section [3](#) is imported, but none of its 94 declarations occurs in any of them.

The independence hypothesis is unused. In the chain leading to Theorem [8.1](#), hypothesis (I) is passed down unchanged and is finally received only by Theorem [7.1](#) and Lemma [7.5](#). In both, the argument is named `h0`. A second metaprogram, run from the same file, opens the proof terms of these two lemmas and confirms that the bound variable for (I) does not occur in their bodies. Hence the whole chain, including Theorem [8.1](#), remains valid with (I) deleted; the current statements simply carry a redundant hypothesis.

10 Discussion and limitations

The reward-independence hypothesis. Taken at face value, (I) is restrictive: in an MDP the reward r_t depends on (s_t, a_t) , which is correlated with the earlier states and actions, so (I) fails for most reward kernels. As shown in Section [9](#), no proof uses it. It survives in the statements as a legacy of how the conjectures were first written; removing it from the signatures is the most immediate clean-up.

Regularity hypotheses. (P2) asks for a gradient bound uniform in θ , x and u . It holds for example for a softmax policy with bounded features, since then $\nabla_{\theta}\pi_{\theta}(u \mid x) = \pi_{\theta}(u \mid x)(\phi(x, u) - \sum_{u'} \pi_{\theta}(u' \mid x)\phi(x, u'))$, but it excludes policies whose gradient grows with θ . $(B_{\nabla V})$ is a hypothesis on a derived quantity; we expect it to follow from (P2) and the reward bound for $\gamma < 1$, and (B_V) to follow from $|V_t| \leq (1 - \gamma)^{-1}|R_{\max}|$, which the model already proves for Q_t . Neither derivation is formalized yet.

Scope. The state and action spaces are finite, rewards are bounded, and the discount satisfies $\gamma < 1$; average-reward, undiscounted episodic, and continuous-space settings are not covered. The parameter space Θ is an arbitrary real normed space, so the result is not limited to tabular parametrisations. The statements are about exact expectations and the exact value function. They say nothing about variance, about sampled or bootstrapped estimates with a learned critic, about GAE with $\lambda < 1$, or about convergence of stochastic gradient ascent. The value functions carry a time index; the model proves that on reachable states they agree with a time-independent closed form, but the statements are phrased with the indexed version. Finally, the left-hand side of every theorem is $\sum_t' \gamma^t \nabla_{\theta} \mathbb{E}_{\theta}[r_t]$; its identification with $\nabla_{\theta} J(\theta)$ is the separate lemma [\(1\)](#).

11 Conclusion

We have formalized, in Lean 4 on top of mathlib, a discounted MDP with a parametrised policy and its Ionescu-Tulcea trajectory law; its Bellman equations; a recursion for the gradient of the value function and its unrolling by induction into an exact truncated policy-gradient identity; the limit in both the action-value and the REINFORCE form; and the fact that replacing the return by the discounted sum of temporal-difference residuals of the value function leaves the policy gradient unchanged. The proofs use only the standard axioms, and the one restrictive-looking hypothesis in the statements is unused and can be removed.

Perfecting the textbook syntactic sugar of Sections 3 and 4 is the main direction for future optimization of the code. The policy-gradient statements of this paper are still written in mathlib’s integral and conditional-measure notation. Extending the $\mathbb{E}/\mathbb{P}$ binder forms so that such statements can be written in them directly (for example to real-valued integrands, since the library’s expectation class currently has instances for $[0, \infty]$ -valued, extended-real-valued, complex-valued and vector- or tensor-valued observables, and to conditioning on events under the trajectory measure), and extending the layer to further textbook constructs, would bring the formal statements closer to the formulas of the paper.

Acknowledgements

The formalization uses Lean 4 and mathlib [2, 23]. Interactive statements of the modules cited in this paper are available at lemma.cn.

References

- [1] Mark Chevallier and Jacques Fleuriot. Formalising the foundations of discrete reinforcement learning in Isabelle/HOL. arXiv:2112.05996, <https://arxiv.org/abs/2112.05996>, 2021.
- [2] Leonardo de Moura and Sebastian Ullrich. The Lean 4 theorem prover and programming language. In *Automated Deduction – CADE 28*, volume 12699 of *LNCS*, pages 625–635. Springer, 2021.
- [3] Evan Greensmith, Peter L. Bartlett, and Jonathan Baxter. Variance reduction techniques for gradient estimates in reinforcement learning. *Journal of Machine Learning Research*, 5:1471–1530, 2004.
- [4] Olav Kallenberg. *Foundations of Modern Probability*. Springer, 2nd edition, 2002.
- [5] Peter J. Landin. The mechanical evaluation of expressions. *The Computer Journal*, 6(4):308–320, 1964.
- [6] lean-dojo. TorchLean: Formalizing neural networks in Lean. GitHub repository, <https://github.com/lean-dojo/TorchLean>, 2026.
- [7] math proof. lemma: machine-checked tensor calculus. <https://github.com/math-proof/lemma>, 2026.
- [8] math proof. Random.Expect_ConditionedGrad_LogProb.eq.Zero.policy. http://www.lemma.cn/lean/?module=Random.Expect_ConditionedGrad_LogProb.eq.Zero.policy, 2026.
- [9] math proof. Real.Eq_0.Lim.of.LtAbs.IsFinite. http://www.lemma.cn/lean/?module=Real.Eq_0.Lim.of.LtAbs.IsFinite, 2026.

- [10] math proof. Tensor.And.Eq.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.Bellman. http://www.lemma.cn/lean/?module=Tensor.And.Eq.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.Bellman, 2026.
- [11] math proof. Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.IsFinite.Q_Function. http://www.lemma.cn/lean/?module=Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.IsFinite.Q_Function, 2026.
- [12] math proof. Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.IsFinite.policy_gradient_theorem. http://www.lemma.cn/lean/?module=Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.IsFinite.policy_gradient_theorem, 2026.
- [13] math proof. Tensor.Eq.Expect.Grad.Log.Pr.of.Eq_Conditioned.Q_Function.discounted. http://www.lemma.cn/lean/?module=Tensor.Eq.Expect.Grad.Log.Pr.of.Eq_Conditioned.Q_Function.discounted, 2026.
- [14] math proof. Tensor.Eq.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient. http://www.lemma.cn/lean/?module=Tensor.Eq.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient, 2026.
- [15] math proof. Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.unbiased_advantage_estimate. http://www.lemma.cn/lean/?module=Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.unbiased_advantage_estimate, 2026.
- [16] math proof. Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.induct. http://www.lemma.cn/lean/?module=Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.induct, 2026.
- [17] math proof. Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.recursion. http://www.lemma.cn/lean/?module=Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.recursion, 2026.
- [18] Mathlib community. The Lean mathematical library. https://leanprover-community.github.io/mathlib4_docs/, 2026.
- [19] Martin L. Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. Wiley, 1994.
- [20] John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016. arXiv:1506.02438.
- [21] Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, 2nd edition, 2018.
- [22] Richard S. Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in Neural Information Processing Systems*, volume 12, pages 1057–1063. MIT Press, 2000.
- [23] The mathlib Community. The Lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP)*, pages 367–381. ACM, 2020.
- [24] Koundinya Vajjha, Avraham Shinnar, Barry Trager, Vasily Pestun, and Nathan Fulton. CertRL: Formalizing convergence proofs for value and policy iteration in Coq. In *Proceedings of the 10th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP)*, pages 18–31. ACM, 2021. arXiv:2009.11403.

- [25] Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8(3–4):229–256, 1992.
- [26] Shangdong Zhang. rl-theory-in-lean: RLTheory/Algorithm/PolicyGradient.lean, commit 2a9d01a. GitHub, 30 March 2026, <https://github.com/ShangdongZhang/rl-theory-in-lean/commit/2a9d01a236961b1c9bc451a8926346364fc66e7f>, 2026. Experimental, largely machine-generated development (commits co-authored with an AI assistant), committed in March 2026 and later withdrawn from the project’s main branch; still accessible at this commit.