

A Lean 4 Perspective on NLP: from CRF to PPO

LiZhi Zhou

Project artifact: [math-proof/lemma](#)

Markov product: P_t , forward recursion, NLL: $\log Z - \text{score}$, Viterbi: $\max$

forward-backward: $z_t \beta_t$, Bellman: V, Q , REINFORCE: [Lean 4](#)

Unbiased advantage estimate: [Lean 4](#), generalized advantage estimate: [Lean 4](#)

Abstract

Linear-chain conditional random fields (CRFs) for sequence labeling and proximal policy optimization (PPO) for reinforcement learning from feedback look like unrelated corners of NLP. We organize a Lean 4 account of the path between them around three results: the forward and backward propagation of the linear-chain CRF, the Bellman equation, and the policy gradient theorem with its REINFORCE and generalized-advantage-estimation (GAE) forms. All three rest on one device: a Markov structure turns a sum over exponentially many paths (or over an infinite horizon) into a one-step recursion, run forward for the CRF partition function and backward for suffix sums and for the value function. We say exactly what is machine-checked in Lean 4 with `mathlib`. For the CRF we formalize the Markov product, the decomposition of the log-score into transition and emission terms, the forward recursion in log-sum-exp form with $-\log p(y \mid x) = \log Z(x) - \text{score}(x, y)$, the Viterbi max-plus recursion (maximal value only), and a forward-backward theorem for an arbitrary chain of real weights: the forward recursion, the backward recursion, the identity $\sum_{ys: y_{s_t}=a} P_m(ys) = z_t(a) \beta_t(a)$ for the total weight of the paths through label a at time t , and the independence of Z from the cut t . For reinforcement learning we formalize a discounted Markov decision process (MDP) with finite state and action spaces and its trajectory measure, the Bellman equations, the policy gradient theorem by induction on the horizon in truncated, action-value and REINFORCE form, the zero-mean score identity that makes a baseline vanish, the unbiased discounted advantage, and GAE with the exact value function for every $\lambda \in [0, 1]$. Not formalized, and labeled as such, are the normalized posterior and pairwise marginals, the identity $\nabla \log Z = \mathbb{E}[\nabla \text{score}]$, the Viterbi argmax, and every ingredient of the PPO algorithm (clipped surrogate, importance ratio, KL and value clipping, learned critic); the analogy between the forward, backward and Bellman recursions, and the comparison of sequence labeling with sequence-to-sequence generation, are conceptual and are not Lean theorems. All checked theorems depend only on the axioms `propext`, `Classical.choice` and `Quot.sound`.

1 Introduction

Sequence labeling with a linear-chain CRF [10, 50] and reinforcement learning from human feedback with PPO [44, 59, 38] are usually taught in different chapters. The first is supervised: an observed sentence x is mapped to a tag sequence y of the same length by maximizing $\log p(y \mid x)$. The second is a reinforcement-learning algorithm: a language model generates tokens, a scalar reward judges the finished text, and the policy is updated by a clipped policy-gradient step. This paper is about what they share, seen through what we have been able to prove in Lean 4 [6] on top of `mathlib` [53, 36], in the `lemma` library [15].

Three core topics. The paper is organized around three results, each with its own section and its own Lean statements.

1. **Forward and backward propagation of the linear-chain CRF** (Section 5). The forward recursion $z_{t+1}(a) = \sum_b z_t(b) \psi_{t+1}(b, a)$ computes the partition function Z in $O(mk^2)$ operations instead of summing k^{m+1} label paths; the backward recursion $\beta_t(a) = \sum_c \psi_{t+1}(a, c) \beta_{t+1}(c)$ summarizes the suffix, and $z_t(a)\beta_t(a)$ is the total weight of the label paths through a at time t , the numerator of the posterior marginal. Lean has the forward recursion with $-\log p(y \mid x) = \log Z - \text{score}$ for the hidden-Markov-conditional case, the Viterbi value recursion, and a forward-backward theorem (Theorem 5.4) for an arbitrary chain of weights.
2. **The Bellman equation** (Section 6). For a discounted MDP with finite state and action spaces, the value function satisfies $V_t(s_t) = \mathbb{E}[r_t + \gamma V_{t+1}(s_{t+1}) \mid s_t = s_t]$, and likewise for the action value Q_t ; Lean proves this for the trajectory measure of the MDP.
3. **The policy gradient theorem, REINFORCE and GAE** (Section 7). $\nabla_\theta \mathbb{E}[\sum_t' \gamma^t r_t] = \mathbb{E}[\sum_t' \gamma^t G_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)]$ is proved by induction on the horizon, with a finite-horizon identity that has an explicit remainder; replacing G_t by the unbiased advantage, or by the generalized advantage $\hat{A}_t^\lambda$ built from the exact value function, leaves the gradient unchanged.

Section 8 says which parts of PPO lie outside these statements, and Section 9 is a short conceptual comparison of sequence labeling with sequence-to-sequence generation that is not a theorem.

The common thread. In every model of this paper the probability of a length- n object is a product of one-step factors (the Markov assumption), so its logarithm is a sum of per-step terms: the CRF score, the log-probability of a trajectory, the log-likelihood of a sentence under a language model. Two consequences are used. First, sums over exponentially many paths are computed by a one-step recursion: the forward and backward recursions of the CRF are a sum-product dynamic program (and Viterbi its max-sum version), and the Bellman recursion is an expectation recursion of the same shape, run backward in time (Section 6.3). We present this as an analogy, not as a theorem: no Lean statement relates the CRF recursions to the Bellman recursion. Second, when each step factor sums to one, $\sum_a p(a) = 1$ implies $\mathbb{E}_{a \sim p}[\nabla_\theta \log p(a)] = 0$, which is why a baseline can be subtracted from a policy gradient without changing it (Section 7.2).

Contributions.

1. CRF propagation (Sections 4 and 5): the Markov product `crf.markov`, the log-score `crf.markov.logits` and `crf.logits`, the forward recursion with $-\log p(y \mid x) = \log Z - \text{score}$, `y_given_x`, the Viterbi value recursion `crf.viterbi`, and the new forward-backward theorem `crf.forward_backward`, whose hypotheses are the one-step prefix factorization and the backward recursion (Theorem 5.4).
2. The Bellman equation `Bellman` on a trajectory-level MDP whose trajectory law has a proved Markov property (`joint_succ`, `hist_step`) (Section 6).
3. The policy gradient theorem by induction on the horizon, in truncated, action-value and REINFORCE form (`policy_gradient_theorem`), the unbiased advantage estimate `unbiased_advantage_estimate` and GAE with the exact value function for all $\lambda \in [0, 1]$, `generalized_advantage_estimate`, with its weighted-average form (Section 7).
4. An explicit statement of what is *not* covered, in particular the ingredients of PPO (Sections 8 and 12), and two comparison tables (Section 10).

The textbook syntactic sugar of the library for limits, expectations and probabilities, which makes the Lean statements read like the formulas of the paper, is summarised in Section 3.

Honest scope. (i) The downstream log-domain CRF lemmas (logits, forward recursion with the negative log-likelihood, Viterbi) take the one-step prefix factorization as a *hypothesis*; for the probabilistic form it is derived from the emission and first-order Markov conditional independences (Theorem 4.3), but it is not derived from a concrete construction of the model. (ii) The backward recursion is formalized only inside the forward-backward theorem (Theorem 5.4), which is a statement about arbitrary real weights: it does not define the CRF distribution $p(y \mid x) = \prod_t \psi_t / Z$ as a model, and the normalized posterior marginals, the pairwise marginals, the identity $\nabla \log Z = \mathbb{E}[\nabla \text{score}]$ and the Viterbi argmax with back-pointers are *not* formalized. (iii) There is no sequence-to-sequence, teacher-forcing, exposure-bias or label-bias lemma. (iv) The MDP is formalized; PPO is not: there is no clipped surrogate, importance ratio, KL penalty, value clipping, learned critic, or monotone-improvement or convergence statement. (v) GAE is proved only with the exact value function, for finite state and action spaces, bounded rewards and $\gamma < 1$. Sections 6.3, 9 and 10 contain conceptual comparisons and are labeled as such.

2 Background and related work

HMMs, MEMMs and CRFs. A hidden Markov model (HMM) [40] is generative: it models the joint $p(x, y) = \prod_t p(y_t \mid y_{t-1}) p(x_t \mid y_t)$ with locally normalized factors. Maximum-entropy Markov models (MEMMs) [37] are discriminative but still locally normalized, $\prod_t p(y_t \mid y_{t-1}, x)$, and suffer from the label bias problem; conditional random fields [10] remove it by normalizing globally with one partition function $Z(x)$ over whole label sequences. Sutton and McCallum [50] give the standard tutorial treatment, including the forward, backward and Viterbi recursions. Neural CRFs put a neural network under the unary scores: Collobert et al. [5] train a sentence-level likelihood with transition scores, Huang et al. [8], Lample et al. [11] and Ma and Hovy [14] use a BiLSTM encoder with a CRF layer, and Andor et al. [1] argue for globally normalized transition-based networks. Su Jianlin’s blog gives a concise derivation in Chinese of the CRF loss and its recursive normalizer [46]; further CRF-related posts are listed on the site’s search page [47]. GlobalPointer is a span-based alternative to CRF for NER [48].

Sequence-to-sequence models and exposure bias. Neural sequence-to-sequence models [49, 2, 55] factor $p(y \mid x) = \prod_t p(y_t \mid x, y_{<t})$ and are trained with the true prefix (teacher forcing) but decoded with their own; this mismatch is called exposure bias and is attacked by scheduled sampling [3], sequence-level training [41] and beam-search optimization [57]. A small example in which beam search with a larger beam returns a better sequence is in Section 9.

Policy gradients, GAE and PPO. The policy gradient theorem is due to Sutton et al. [52], the likelihood-ratio estimator and the reinforcement baseline to Williams [56]; Greensmith, Bartlett and Baxter [7] analyse baselines as variance reducers. Schulman et al. [43] introduced generalized advantage estimation, used there with trust region policy optimization (TRPO) [42]; TRPO predates GAE and does not define it. PPO [44] replaces the trust-region constraint by a clipped surrogate objective and computes its advantages with a truncated (finite-horizon) GAE, its Eqs. (10)–(11). RLHF for language models [59, 38] runs PPO on tokens with a reward-model score and a KL penalty to a reference model, and GRPO [45] is a PPO variant without a learned critic. Standard references for finite MDPs are Puterman [39] and Sutton and Barto [51].

Formalizations. CertRL [54] formalizes convergence of value and policy iteration in Coq, and Chevallier and Fleuriot [4] formalize finite MDPs with rewards in Isabelle/HOL, including the Bellman equation, the existence of an optimal policy for $\gamma < 1$, and value and policy iteration; neither treats policy gradients. In Lean 4, TorchLean [13] proves structural and dynamic-programming facts about MDPs and Bellman operators and contains policy-gradient and PPO

training code, but no policy gradient theorem. Closest to Section 7 is the `PolicyGradient` module of Zhang’s `rl-theory-in-lean` [58], an experimental, largely machine-generated development (its commits are co-authored with an AI assistant) that was committed in March 2026 and later withdrawn from the project’s main branch; it remains accessible at the cited commit. For finite state and action spaces and a policy with finitely many real parameters it proves the occupancy-measure form $\nabla_{\theta} J(\theta) = (1 - \gamma)^{-1} \sum_{s,a} d^{\pi_{\theta}}(s) \pi_{\theta}(a \mid s) Q^{\pi_{\theta}}(s, a) \nabla_{\theta} \log \pi_{\theta}(a \mid s)$ via a Banach fixed point and a Neumann series, requires a strictly positive policy, and has no trajectories, returns or advantages. Ours works at the level of trajectories: the law of a trajectory is `mathlib’s Kernel1.trajMeasure` [36], an implementation of the Ionescu-Tulcea theorem [9], the value functions are conditional expectations, and we prove the exact finite-horizon identity of the textbook derivation [51, §13.2] by induction before passing to the limit. To the best of our knowledge, based on searches of GitHub, arXiv and the web, this is the first Lean 4 proof that follows the textbook derivation; the two proofs share only the textbook starting point (the one-step recursion of [52] and the log-derivative trick), and ours was developed independently. We are not aware of earlier Lean 4 formalizations of CRF forward or backward recursions.

3 Lean notation in brief

The statements below are written in the library’s *textbook syntactic sugar*: surface syntax that compresses verbose measure-theoretic or filter-theoretic expressions into near-textbook form while elaborating to complete, machine-checked definitions, with no new axioms (the generic term *syntactic sugar* goes back to Landin [12]). We recall only what the later sections use.

Lean surface form	meaning
<code>lim [n → ∞] e = a</code>	<code>Filter.Tendsto (fun n => e) atTop (nhds a)</code> ; always the equation form, which asserts convergence
<code>ℰ[x : π] (f x y = y0)</code>	$\mathbb{E}_{\pi}[f(\textcolor{red}{x}) \mid \textcolor{blue}{y} = y_0]$, the expectation under <code>mathlib’s</code> conditional measure; 0 at a null event
<code>ℙ[π] (x = x0 y = y0)</code>	$\mathbb{P}_{\pi}(\textcolor{red}{x} = x_0 \mid \textcolor{blue}{y} = y_0)$ (densities w.r.t. counting measure give probability masses)
<code>x[:n]</code>	the random vector $(\textcolor{red}{x}_0, \dots, \textcolor{red}{x}_{n-1})$; for a plain sequence f , <code>f[:n]</code> is $(f_0, \dots, f_{n-1})$
<code>(ℙ[π] (...)) : ℝ).log</code>	$\log \mathbb{P}_{\pi}(\dots)$ (the scoped coercion $[0, \infty] \rightarrow \mathbb{R}$ is not a global instance)
<code>∇[θ] e, sup[x] e < ∞</code>	$\nabla_{\theta} e$ (Riesz representative of the Fréchet derivative); e bounded above
<code>max[ys : Fin t → Y] f ys, v.exp.sum.log</code>	$\max_{ys} f(ys)$ over a finite index type; $\log \sum_b e^{v_b}$ (<code>v.exp</code> , <code>v.sum</code> , <code>v.max</code> act pointwise or reduce a vector)

Colours. The renderer of `lemma.cn` typesets every statement in L^AT_EX and colours identifiers by probabilistic role: **red** for a random variable (a function on the sample space, the integrated variable of an $\mathbb{E}$ binder, the left side of $=$ in a $\mathbb{P}$ event), **magenta** for a random argument (a random variable used as the argument of a function, so that the expression is itself random), and black for an observed value. We use the same convention: $\textcolor{red}{s}_t, \textcolor{blue}{a}_t, \textcolor{red}{r}_t$ are red, s_t, a_t, x, u, y are values, and $V_t(\textcolor{red}{s}_t)$ is a function of the state evaluated along the trajectory.

Conditioning at null events and limits. Because $\mu[\cdot \mid B] = \mu(B)^{-1} \mu|_B$ is the zero measure when $\mu(B) = 0$, a conditional expectation at an unreachable state is 0; hypotheses on value functions are therefore restricted to *reachable* values s_t , those with $\mathbb{P}_{\theta}(\textcolor{red}{s}_t = s_t) \neq 0$. Infinite sums are Lean’s `tsum` ($\sum'$, the sum of a summable family and 0 otherwise), and every limit is

an explicit `Filter.Tendsto` statement. The only limit lemma we state is the following, used for the remainder of the truncated policy gradient (Section 7).

Lemma 3.1 ([Lim.of.LtAbs.IsFinite](#) [19]). *Let $\gamma \in \mathbb{R}$ and $x : \mathbb{N} \rightarrow \mathbb{R}$ with $|\gamma| < 1$ and $\{x_n : n \in \mathbb{N}\}$ bounded above. Then $\lim_{n \rightarrow \infty} \gamma^n x_n = 0$.*

4 The Markov assumption in Lean

The common property. Whatever the application, a first-order Markov assumption says that the probability of a length- n object is a product of n one-step factors, each of which looks back a bounded amount in the right state space. Two consequences are used throughout this paper: (i) the logarithm of the product is the sum of the logarithms of the factors, so a score is a sum of per-step terms; (ii) the product can be built, summed, maximised or differentiated by induction on the length, which gives linear-time recursions. What differs from model to model is how the factors are normalized (Section 10).

4.1 The assumption as a factorization

Fix a sentence, that is, an observed sequence xo , and a finite or countable label type $\mathcal{Y}$. For label sequences $ys : \mathbb{N} \rightarrow \mathcal{Y}$ let $P_t(ys)$ denote the joint probability $\mathbb{P}(x[:t+1] = xo[:t+1] \wedge y[:t+1] = ys[:t+1])$ of the first $t + 1$ observations and labels.

Definition 4.1 (`IsHiddenMarkovSeq`). *Let $P : \mathbb{N} \rightarrow (\mathbb{N} \rightarrow \mathcal{Y}) \rightarrow \mathbb{R}$, $\pi : \mathcal{Y} \rightarrow \mathbb{R}$, $T : \mathcal{Y} \rightarrow \mathcal{Y} \rightarrow \mathbb{R}$ and $E : \mathbb{N} \rightarrow \mathcal{Y} \rightarrow \mathbb{R}$. Then `IsHiddenMarkovSeq P  $\pi$  T E` states that for every ys ,*

$$P_0(ys) = E_0(ys_0) \pi(ys_0), \quad P_{t+1}(ys) = P_t(ys) \cdot T(ys_t, ys_{t+1}) E_{t+1}(ys_{t+1}) \quad (t \in \mathbb{N}).$$

In the reading we use, $\pi(a) = \mathbb{P}(y_0 = a)$, $T(a, b) = \mathbb{P}(y_{i+1} = b \mid y_i = a)$ and $E_i(b) = \mathbb{P}(x_i = xo_i \mid y_i = b)$. The probabilistic version `IsHiddenMarkovPr  $\pi$  x y xo` states the same two equations directly in probability notation: $\mathbb{P}(x[:1] = xo[:1] \wedge y[:1] = ys[:1]) = \mathbb{P}(x_0 = xo_0 \mid y_0 = ys_0) \mathbb{P}(y_0 = ys_0)$ and

$$\begin{aligned} \mathbb{P}(x[:t+2] = xo[:t+2] \wedge y[:t+2] = ys[:t+2]) \\ = \mathbb{P}(x[:t+1] = \dots \wedge y[:t+1] = \dots) \mathbb{P}(y_{t+1} \mid y_t) \mathbb{P}(x_{t+1} = xo_{t+1} \mid y_{t+1}). \end{aligned}$$

`IsHiddenMarkovFac` is the same factorization for an abstract prefix family P ; the theorem `IsHiddenMarkovPr.toFac` passes from the probabilistic version to it, and `IsHiddenMarkovSeq.prefix` (also for `IsHiddenMarkovFac`) proves by induction on t that P_t depends only on the first $t + 1$ labels. These are the definitions and helper theorems that the CRF lemmas below take as hypotheses.

Remark 4.2 (Hypothesis versus derivation). *The abstract factorization `IsHiddenMarkovSeq` is assumed by the logits lemma of Theorem 5.1. For the probabilistic version `IsHiddenMarkovPr` the factorization is derived from conditional independences. An observation depends on the past only through the current label, $x_{t+1} \perp (x[:t+1], y[:t+1]) \mid y_{t+1}$, and a label depends on the past only through its predecessor, $y_{t+1} \perp (x[:t+1], y[:t]) \mid y_t$. Theorem 4.3 shows that these two conditional independences imply the product form, and `IsHiddenMarkovPr.of.CondIndep.CondIndep` packages the one-step equations as `IsHiddenMarkovPr`. They have to be read as conditional independences: the marginal independences (for instance $x_{t+1} \perp (x[:t+1], y[:t+1])$ without conditioning on y_{t+1}) do not imply the factorization (take x_0 constant, y_0, y_1 independent fair bits and $x_1 = y_0 \oplus y_1$, with a little noise to make all probabilities positive). By contrast, the Markov property of the MDP trajectory law of Section 6.1 follows from the construction of the law (`joint_succ`, `hist_step`), not from assumed independences; the treatment of the two sides is asymmetric.*

4.2 The product form

Theorem 4.3 ([crf.markov](#) [18]). *Let x_i, y_i be measurable discrete random variables (countable ranges, counting reference measures) on a probability space with a standard Borel sample space, and suppose that for every t*

$$x_{t+1} \perp (x[:t+1], y[:t+1]) \mid y_{t+1}, \quad y_{t+1} \perp (x[:t+1], y[:t]) \mid y_t.$$

Then for every x_0, y_0 and t ,

$$\begin{aligned} & \mathbb{P}(x[:t+1] = x_0[:t+1] \wedge y[:t+1] = y_0[:t+1]) \\ &= \mathbb{P}(x_0 = x_0 \mid y_0 = y_0) \mathbb{P}(y_0 = y_0) \prod_{i=1}^t \mathbb{P}(y_i = y_i \mid y_{i-1} = y_{i-1}) \mathbb{P}(x_i = x_i \mid y_i = y_i). \end{aligned}$$

The proof is induction on t with `Finset.prod_Ico_succ_top`. The one-step identity is the chain rule $\mathbb{P}(C \cap F \cap E) = \mathbb{P}(C) \frac{\mathbb{P}(F \cap G)}{\mathbb{P}(G)} \frac{\mathbb{P}(E \cap F)}{\mathbb{P}(F)}$ for the past event $C = \{x[:t+1] = x_0[:t+1], y[:t+1] = y_0[:t+1]\}$, $E = \{x_{t+1} = x_{0,t+1}\}$, $F = \{y_{t+1} = y_{0,t+1}\}$ and $G = \{y_t = y_{0,t}\} \supseteq C$; it follows by clearing denominators in the two conditional independences. No non-vanishing hypothesis is needed, because if a conditioning event is null then both sides vanish (the module name keeps the historical `Ne_0`).

4.3 Conditional independence: the standard bricks

Three library lemmas formalize the conditional-independence vocabulary in which the Markov assumption is usually stated. Let x, y, z be measurable random variables on a probability space.

- [CondIndep.of.Indep_Joint](#): if $x \perp (y, z)$ then $x \perp y \mid z$.
- [Indep_Joint.of.CondIndep.Indep](#): if $z \perp x \mid y$ and $z \perp y$ then $z \perp (x, y)$.
- [All_Imp_EqProbSCond.of.CondIndep](#): if $x \perp y \mid z$ then, almost everywhere on the reference measures, $\mathbb{P}(x \mid y, z) = \mathbb{P}(x \mid z)$ whenever $\mathbb{P}(y, z) \neq 0$; this is the Markov property in conditional form.

The chain rule used to factor a joint probability one variable at a time is the discrete lemma [ProbCond.eq.Mul.ProbCond](#): for variables with countable ranges and counting reference measures, $\mathbb{P}(x \wedge y \mid z) = \mathbb{P}(x \mid z) \mathbb{P}(y \mid x \wedge z)$. It is two-variable and pointwise; the n -step chain rule for the hidden Markov sequence is Theorem 4.3. It is reduced to the measure-level form [MulMeasure.eq.MulMeasure.of.CondIndep](#) of conditional independence, $\mathbb{P}(x=u, y=v, z=w) \mathbb{P}(z=w) = \mathbb{P}(x=u, z=w) \mathbb{P}(y=v, z=w)$ (obtained from the third lemma above, with no non-vanishing hypothesis), and to the identification [ProbCond.eq.Div.of.Eq_Count.Eq_Count](#) of $\mathbb{P}(x \mid y)$ with a ratio of measures.

5 Forward and backward propagation of the linear-chain CRF

This is the first core topic. A linear-chain CRF assigns to a label sequence $ys \in \mathcal{Y}^{m+1}$ a weight that is a product of one-step factors, and its partition function Z is the sum of these weights over all k^{m+1} label sequences. The Markov structure makes two sums computable in linear time: the *forward* recursion over prefixes (Section 5.2) and the *backward* recursion over suffixes (Section 5.3); a third recursion over the same chain, with $\max$ in place of $\sum$, is Viterbi (Section 5.4). Sections 5.2 and 5.4 are stated for the hidden-Markov-conditional instance in the log domain; Section 5.3 is a purely algebraic statement about arbitrary real weights, to which the hidden Markov factorization is an instance.

5.1 From the product to the score

Write $G(a, b) = \log \mathbb{P}(y_{i+1} = a \mid y_i = b)$ for the transition score into a from b , $e_t(a) = \log \mathbb{P}(x_t = x_{ot} \mid y_t = a)$ for the emission (unary) score, and $s_t(ys) = \log P_t(ys)$ for the log-score of a label prefix. All probabilities are assumed strictly positive in the following statements.

Theorem 5.1 ([crf.markov.logits](#) [27]). *Under $IsHiddenMarkovSeq P \pi T E$ with $P, T, E > 0$, $s_t = \log P_t$, $x_t = \log E_t$ and $G(a, b) = \log T(b, a)$, for every $t > 0$:*

$$s_t(ys) = G(ys_t, ys_{t-1}) + s_{t-1}(ys) + x_t(ys_t).$$

Theorem 5.2 ([crf.logits](#) [34]). *Assume $IsHiddenMarkovPr \pi x y x_o$, positivity of $\mathbb{P}(y_0 = a)$, $\mathbb{P}(y_{i+1} = a \mid y_i = b)$ and $\mathbb{P}(x_t = x_{ot} \mid y_t = a)$, and the definitions of s_t , e_t , G above. Then for every ys ,*

$$\begin{aligned} s_{t+1}(ys) &= G(ys_{t+1}, ys_t) + s_t(ys) + e_{t+1}(ys_{t+1}), \\ s_t(ys) &= \log \mathbb{P}(y_0 = ys_0) + \sum_{i=1}^t G(ys_i, ys_{i-1}) + \sum_{i=0}^t e_i(ys_i). \end{aligned}$$

The second line is the textbook linear-chain CRF score: a sum of unary (emission) terms and pairwise (transition) terms. It is exactly the *log of a Markov product is a sum of per-step terms* property of Section 4; the neural CRFs [8, 11, 14] replace e_t by the output of a network and treat G as a free matrix, and the derivations of Su [46] start from the same additive form.

5.2 Forward propagation: log-sum-exp and the forward recursion

Two pointwise facts about the softmax are in the library: [Log.Softmax.eq.Add.LogSumExp](#), $\log \frac{e^{x_i}}{\sum_j e^{x_j}} = x_i - \log \sum_j e^{x_j}$, and [Le_LogSumExp](#), $x_i \leq \log \sum_j e^{x_j}$; its Jacobian is [Grad.Softmax.eq.Mul.Softmax](#): with $\sigma_j = e^{F_j} / \sum_i e^{F_i}$, $\partial \sigma_j = \sigma_j (\partial F_j - \sum_i \sigma_i \partial F_i)$.

For the forward recursion let $\mathcal{Y}$ be finite with k elements, fix a length $m + 1$, and put

$$z_t(a) = \sum_{ys \in \mathcal{Y}^{t+1}, ys_t = a} e^{s_t(ys)}, \quad \alpha_t(a) = \log z_t(a).$$

Thus $z_t(a)$ is a brute-force sum over k^t label prefixes, and $Z = \sum_b z_m(b)$ is the sum over all k^{m+1} label paths.

Theorem 5.3 ([y_given_x](#) [35]). *Under the hypotheses of Theorem 5.2 (with positive prefix probabilities),*

$$\alpha_{t+1}(a) = \log \sum_{b \in \mathcal{Y}} \exp(\alpha_t(b) + G(a, b)) + e_{t+1}(a),$$

and for every label sequence ys ,

$$-\log \mathbb{P}(y[:m+1] = ys[:m+1] \mid x[:m+1] = x_o[:m+1]) = \log \sum_{b \in \mathcal{Y}} e^{\alpha_m(b)} - s_m(ys).$$

Since $\sum_b e^{\alpha_m(b)} = Z$ by definition, the second line is the CRF negative log-likelihood $-\log p(y \mid x) = \log Z(x) - \text{score}(x, y)$, and the first line is the forward recursion that computes Z in $O(mk^2)$ time instead of k^{m+1} terms: Lean checks that the recursion agrees with the brute-force definition of z_t by induction on t (a splitting of the sum over $\mathcal{Y}^{t+1}$ by its last label, [Fintype.sum_snoc](#)). This is the recursion that computes the normalizer recursively thanks to the Markov assumption, and that Sutton and McCallum [50] present as the forward algorithm for linear-chain CRFs. In the probability domain, with $P_t = e^{s_t}$, it reads $z_{t+1}(a) = (\sum_b z_t(b) \mathbb{P}(y_{t+1} = a \mid y_t = b)) \mathbb{P}(x_{t+1} = x_{ot+1} \mid y_{t+1} = a)$; this is the form that Theorem 5.4 proves for arbitrary weights, together with its backward counterpart.

5.3 Backward propagation and the forward-backward identity

The forward variable $z_t(a)$ summarizes the prefix $ys_0, \dots, ys_t$ ending in the label a . The *backward* variable $\beta_t(a)$ summarizes the suffix $ys_{t+1}, \dots, ys_m$ that may follow the label a at time t . Their product is the total weight of all label sequences through a at time t , so $z_t(a)\beta_t(a)/Z$ is the posterior marginal $\mathbb{P}(y_t = a \mid x)$ of the hidden-Markov reading. We state the Lean theorem for arbitrary real weights, because neither positivity nor normalization is needed for the recursions.

Setting. Let $\mathcal{Y}$ be a finite type, $\psi_0 : \mathcal{Y} \rightarrow \mathbb{R}$ and $\psi_t : \mathcal{Y} \rightarrow \mathcal{Y} \rightarrow \mathbb{R}$ ($t \geq 1$) arbitrary real functions, and $P_t : (\mathbb{N} \rightarrow \mathcal{Y}) \rightarrow \mathbb{R}$ prefix weights with

$$P_0(ys) = \psi_0(ys_0), \quad P_{t+1}(ys) = P_t(ys) \psi_{t+1}(ys_t, ys_{t+1}) \quad (t \in \mathbb{N}). \quad (1)$$

The hidden Markov factorization of Definition 4.1 is the instance $\psi_0(a) = E_0(a)\pi(a)$ and $\psi_t(a, b) = T(a, b)E_t(b)$ (and `IsHiddenMarkovFac` is the instance with time-dependent transition probabilities): the two hypotheses of the theorem below are exactly the two fields of these definitions, so the instantiation is the projections `(h ys).1` and `(h ys).2 t`. The same equation (1) with a free positive $\psi_t(y_{t-1}, y_t, x)$ at a fixed input x is the unnormalized weight of a linear-chain CRF; the theorem does not define the normalized distribution $\prod_t \psi_t / Z$ as a model. Put

$$z_t(a) = \sum_{ys \in \mathcal{Y}^{t+1}, ys_t = a} P_t(ys) \quad (\text{for } P_t = e^{s_t} \text{ this is the } z_t \text{ of Section 5.2}),$$

fix the length $m + 1$, and let the backward variable satisfy

$$\beta_m(a) = 1, \quad \beta_t(a) = \sum_{c \in \mathcal{Y}} \psi_{t+1}(a, c) \beta_{t+1}(c) \quad (t < m).$$

Theorem 5.4 (`crf.forward_backward` [21]). *Under the setting above, for every $a \in \mathcal{Y}$:*

- (a) (forward recursion) $z_0(a) = \psi_0(a)$ and $z_{t+1}(a) = \sum_{b \in \mathcal{Y}} z_t(b) \psi_{t+1}(b, a)$ for every t ;
- (b) (forward-backward identity) for every $t \leq m$,

$$\sum_{ys \in \mathcal{Y}^{m+1}, ys_t = a} P_m(ys) = z_t(a) \beta_t(a);$$

- (c) (the partition function does not depend on the cut) for every $t \leq m$,

$$\sum_{a \in \mathcal{Y}} z_t(a) \beta_t(a) = \sum_{a \in \mathcal{Y}} z_m(a) = Z.$$

Here $Z = \sum_{ys \in \mathcal{Y}^{m+1}} P_m(ys)$ is the partition function; item (c) is stated in the file with $\sum_a z_m(a)$, which equals Z by definition of z_m (grouping the paths by their last label) and is the Z of Theorem 5.3 in the hidden-Markov instance. The formal statement has no positivity hypothesis and no probability space; the label sequences are the functions $\text{Fin}(m+1) \rightarrow \mathcal{Y}$, padded to a function on $\mathbb{N}$ as in the other CRF lemmas, and β is any function satisfying the two displayed backward equations.

Proof idea. Part (a) is the splitting of the sum over $\mathcal{Y}^{t+2}$ by its last label (`Fintype.sum_snoc`, as in Theorem 5.3) together with the fact that P_t depends only on the first $t+1$ labels, which is proved by induction on t from (1). For part (b) fix t and a and let $u_j(c)$ be the sum of $P_j(ys)$ over $ys \in \mathcal{Y}^{j+1}$ with $ys_t = a$ and $ys_j = c$ ($j \geq t$). The same splitting gives $u_{j+1}(c) = \sum_b u_j(b) \psi_{j+1}(b, c)$, and $u_t(c) = z_t(a)$ if $c = a$ and 0 otherwise. A downward induction on t shows $\sum_c u_m(c) = \sum_a u_t(a) \beta_t(a)$ for every initial vector u_t obeying the recursion; in the inductive step one interchanges two finite sums and applies the backward equation. Part (c) is the same induction applied to $u = z$, using $\beta_m = 1$. Everything is a finite-sum manipulation; the cost of the recursions is $O(mk^2)$ for $k = |\mathcal{Y}|$.

Reading. In the hidden-Markov reading, $P_m(ys) = \mathbb{P}(x[:m+1] = xo[:m+1] \wedge y[:m+1] = ys[:m+1])$ and $Z = \mathbb{P}(x = xo)$, so item (b) says that $z_t(a)\beta_t(a)$ equals $\mathbb{P}(x = xo, y_t = a)$, and dividing by Z gives the posterior marginal $\mathbb{P}(y_t = a \mid x = xo)$. The division is the Bayes step that the proof of Theorem 5.3 already carries out for a whole path; the normalized marginal is *not* a separate Lean statement. Item (c) is the sanity check that every cut t yields the same Z ; it is what makes the forward-backward pair a consistent decomposition rather than two unrelated recursions. Rabiner [40] and Sutton and McCallum [50] present the forward and backward recursions in the textbook form. The log-domain version of the backward recursion is the same statement for $\log \beta$ with $\log \sum \exp$; it is not separately formalized.

5.4 Viterbi: the max-plus recursion

Replacing sum by maximum and the logarithm by the identity gives the second recursion. Let $v_t(a) = \max_{ys \in \mathcal{Y}^{t+1}, y_{st}=a} s_t(ys)$.

Theorem 5.5 (`crf.viterbi` [22]). *Under the same hypotheses,*

$$v_{t+1}(a) = e_{t+1}(a) + \max_{b \in \mathcal{Y}} (v_t(b) + G(a, b)),$$

$$\max_{ys \in \mathcal{Y}^{m+1}} \mathbb{P}(x[:m+1] = xo[:m+1] \wedge y[:m+1] = ys) = \exp \max_{b \in \mathcal{Y}} v_m(b).$$

Only the maximal *value* is computed; there is no `argmax` and no `backpointer`, so the decoded sequence itself is not formalized. The forward recursions of Theorems 5.3 and 5.5 are two instances of one recursion on the same chain, over the log semiring ($\oplus = \log\text{-sum-exp}$, $\otimes = +$) and the max-plus semiring ($\oplus = \max$, $\otimes = +$) respectively; in Lean they are proved separately, and the semiring unification is a remark, not a theorem. (The quantity v_t is unrelated to the backward variable β_t of Section 5.3.)

5.5 HMM versus CRF: what the statements say and do not say

HMM. A hidden Markov model [40] is *generative* and *locally normalized*:

$$p(x, y) = \prod_t p(y_t \mid y_{t-1}) p(x_t \mid y_t), \quad Z = 1,$$

each factor being a probability distribution in its own argument.

Linear-chain CRF. A linear-chain CRF [10, 50] is *discriminative* and *globally normalized*:

$$p(y \mid x) = \frac{1}{Z(x)} \prod_t \psi_t(y_{t-1}, y_t, x), \quad Z(x) = \sum_{y' \in \mathcal{Y}^n} \prod_t \psi_t(y'_{t-1}, y'_t, x),$$

with arbitrary non-negative potentials ψ_t that need not be probabilities, and one partition function $Z(x)$ that is a sum over k^n label paths. The Markov assumption is what makes $Z(x)$ computable by the forward recursion of Theorem 5.3, or equivalently by the forward-backward pair of Theorem 5.4. In terms of the score recursion of Theorem 5.2, a CRF is the HMM score recursion with the local-normalization constraint removed: the potentials $\psi_t = e^{G+e_t}$ are free, and what remains of the probability is $e^{\text{score}}/Z(x)$.

What Lean covers. Theorems 5.2–5.3 and 5.5 are the HMM-*conditional* instance: $\psi_t(y_{t-1}, y_t, x) = \mathbb{P}(y_t \mid y_{t-1}) \mathbb{P}(x_t = xo_t \mid y_t)$ with positive probabilities, for which $Z(x)$ is the evidence $\mathbb{P}(x = xo)$. Theorem 5.4 covers the forward and backward recursions for arbitrary real weights ψ_t , hence the algebra of a general-potential CRF at a fixed input; but a general-potential CRF (arbitrary ψ_t , a trainable transition matrix that is not a conditional

distribution, hence a genuinely global Z) is *not* defined as a model, and the quantities that need that model are not formalized. The Lean conclusion $-\log p = \log Z - \text{score}$ is therefore the statement that makes the CRF loss precise in the case that is provable from the factorization hypothesis, not a proof about CRFs in general.

6 The Bellman equation

This is the second core topic. The CRF lemmas fix an observed sentence and sum over labels; here the randomness is a whole trajectory, and the Markov structure is that of a decision process: the next state and reward depend on the past only through the current state and action. The Bellman equation says that the value of a state is the expected immediate reward plus the discounted value of the next state, a one-step recursion that replaces an infinite-horizon expectation.

6.1 Model and trajectory measure

Definition 6.1 (Model). *Let S and A be finite types with the discrete σ -algebra and Θ a real normed space. A policy is $\pi : \Theta \rightarrow S \rightarrow A \rightarrow \mathbb{R}$, written $\pi_\theta(u \mid x)$, with $\pi_\theta(u \mid x) \geq 0$ and $\sum_u \pi_\theta(u \mid x) = 1$ (local normalization: $Z = 1$ at every step). An environment consists of an initial probability measure ι on S , a Markov kernel T from $S \times A$ to S , a Markov kernel R from $S \times A$ to $\mathbb{R}$ with support in $[-R_{\max}, R_{\max}]$.*

A trajectory is a sequence $\omega \in (S \times A \times \mathbb{R})^{\mathbb{N}}$ of stages with coordinates s_t, a_t, r_t . One stage from x is drawn by $\kappa_\theta(x) = \delta_x \otimes (\pi_\theta(\cdot \mid x) \otimes R)$ and the stage chain has kernel $K_\theta(x, u, \rho) = (\kappa_\theta \circ T)(x, u)$. The trajectory measure $\mathbb{P}_\theta = \text{Kernel.trajMeasure } \mu_0 (K_\theta)_n$ is the Ionescu-Tulcea extension [9] provided by mathlib, with n -th kernel reading only the last stage of the history. Informally (the product formula is not a separate Lean statement), the finite-dimensional marginals have the Markov-product shape $\iota(s_0) \prod_t \pi_\theta(a_t \mid s_t) T(s_{t+1} \mid s_t, a_t) R(\cdot \mid s_t, a_t)$. Its logarithm is a sum of per-step terms, and since the transition and reward factors do not depend on θ , *the score of a trajectory is the sum of the scores of its actions*, $\sum_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)$. This is the MDP counterpart of the CRF score of Theorem 5.2; Lean uses it only through the expectation lemma `E_score` below.

The Markov property is a theorem here. In contrast to Remark 4.2, where the factorization follows from assumed conditional independences, the Markov property of $\mathbb{P}_\theta$ is proved from the construction. The model file contains `joint_succ`: the law of (ω_t, ω_{t+1}) is the law of ω_t composed with the kernel K_θ , and `hist_step`: for a bounded measurable φ ,

$$\mathbb{E}[\varphi(h_n, \omega_{n+1})] = \int \left(\int \varphi(h, z) dK_\theta(\text{last } h)(z) \right) d\text{law}(h_n)(h),$$

where $h_n = (\omega_0, \dots, \omega_n)$ is the history and `last  $h$` is its last stage, together with iterated versions (`hist_mul`, `hist_iter`) used below. The joint law of state and action factors as $\mathbb{P}(s_t = x, a_t = u) = \mathbb{P}(s_t = x) \pi_\theta(u \mid x)$ (`ProbJoint.eq.Mul_Prob_Pr`).

6.2 Value functions and the Bellman equations

For $\gamma \in [0, 1)$, the discounted return from t is $G_t = \sum_k' \gamma^k r_{t+k}$, and $V_t^\theta(s_t) = \mathbb{E}[G_t \mid s_t]$, $Q_t^\theta(s_t, a_t) = \mathbb{E}[G_t \mid s_t, a_t]$. The objective is $J(\theta) = \mathbb{E}_\theta[\sum_t' \gamma^t r_t] = \sum_t' \gamma^t \mathbb{E}_\theta[r_t]$. The model file shows that on reachable states V_t^θ equals a time-free closed form, that $|V_t|, |Q_t| \leq (1 - \gamma)^{-1} R_{\max}$, and that J is Fréchet differentiable for a differentiable policy with uniformly bounded gradient. We assume throughout: (D) $\gamma \in [0, 1)$; (P1) $\theta \mapsto \pi_\theta(u \mid x)$ is differentiable; (P2) $\sup_{\theta, x, u} \|\nabla_\theta \pi_\theta(u \mid x)\| < \infty$. Bounds on V_t and $\nabla_\theta V_t$ are derived, not assumed.

Theorem 6.2 (Bellman equations [20]). *Assume (D) and let V, Q satisfy $V_t(s_t) = \mathbb{E}_\theta[G_t \mid \mathbf{s}_t]$, $Q_t(s_t, a_t) = \mathbb{E}_\theta[G_t \mid \mathbf{s}_t, \mathbf{a}_t]$. Then*

$$\begin{aligned} V_t(s_t) &= \mathbb{E}_\theta[Q_t(s_t, \mathbf{a}_t) \mid \mathbf{s}_t], \\ V_t(s_t) &= \mathbb{E}_\theta[\mathbf{r}_t + \gamma V_{t+1}(\mathbf{s}_{t+1}) \mid \mathbf{s}_t], \\ Q_t(s_t, a_t) &= \mathbb{E}_\theta[\mathbf{r}_t + \gamma V_{t+1}(\mathbf{s}_{t+1}) \mid \mathbf{s}_t, \mathbf{a}_t]. \end{aligned}$$

In the Lean file the three identities are stated for every t and every pair (x, u) with no reachability hypothesis: at a null conditioning event both sides are 0 (Section 3). The proof combines the tower property of conditional expectation with the Markov property of the trajectory law of the previous subsection. Read from $t + 1$ to t , the second identity is a *backward* recursion for the value function, the same direction as the recursion for β_t in Theorem 5.4; Section 6.3 compares the two without claiming a theorem. The gradient of this recursion is the first step of the policy gradient theorem (Theorem 7.1).

6.3 Forward, backward and Bellman recursions side by side (analogy)

This subsection is an analogy, not a theorem: no Lean statement relates the CRF recursions to the Bellman recursion. Table 1 lists the four one-step recursions of this paper, the aggregation each performs over the Markov chain, the direction in which it runs, and the Lean statement that proves it.

Recursion	One step	Direction	Aggregation	Lean
CRF forward	$z_{t+1}(a) = \sum_b z_t(b) \psi_{t+1}(b, a)$	forward in t	sum over prefixes (sum-product)	Theorem 5.4(a); log form Theorem 5.3
CRF backward	$\beta_t(a) = \sum_c \psi_{t+1}(a, c) \beta_{t+1}(c)$	backward in t	sum over suffixes (sum-product)	Theorem 5.4(b),(c)
Viterbi	$v_{t+1}(a) = e_{t+1}(a) + \max_b (v_t(b) + G(a, b))$	forward in t	max over prefixes (max-sum)	Theorem 5.5 (value only)
Bellman	$V_t(s_t) = \mathbb{E}_\theta[\mathbf{r}_t + \gamma V_{t+1}(\mathbf{s}_{t+1}) \mid \mathbf{s}_t]$	backward in t	expectation over the next state and reward	Theorem 6.2

Table 1: One-step recursions on a Markov chain. The first three are dynamic programs over label paths; the Bellman recursion is a dynamic program over trajectories.

Formally, if one drops the reward in the Bellman recursion and imposes a terminal value, it becomes $V_t(s) = \sum_c K(s, c) V_{t+1}(c)$ for the one-step kernel K of the state chain, which has exactly the shape of the backward recursion $\beta_t(a) = \sum_c \psi_{t+1}(a, c) \beta_{t+1}(c)$ with $\psi \leftrightarrow K$ and $\beta_m \leftrightarrow V_m$. The differences are real: K is a probability kernel ($\sum_c K(s, c) = 1$) whereas ψ is an unnormalized weight, the Bellman recursion carries a reward source term and a discount, and the Lean value function is an infinite-horizon conditional expectation, not a finite suffix sum. What the recursions share is the mechanism: a Markov structure replaces a global sum by a one-step recursion, forward when the quantity is built from the past, backward when it is built from the future.

7 The policy gradient theorem: REINFORCE and GAE

This is the third core topic. The policy gradient theorem expresses the gradient of the expected discounted return as an expectation of the return times the score $\nabla_\theta \log \pi_\theta(\mathbf{a}_t \mid \mathbf{s}_t)$ of the action

actually taken. Lean proves it by induction on the horizon from the Bellman recursion, in three forms: a truncated form with an explicit remainder (Theorem 7.2), an action-value form, and the REINFORCE form (Theorem 7.3). Because local normalization makes the score zero-mean (Lemma 7.4), the return may be replaced by an advantage, which gives the unbiased advantage estimate and GAE (Section 7.3).

7.1 The policy gradient theorem by induction

Theorem 7.1 (Recursion [33], unrolling [32]). *Assume (D), (P1), (P2) and let s_0 be reachable. Then $\nabla_\theta V_t(s_t) = \sum_u Q_t(s_t, u) \nabla_\theta \pi_\theta(u \mid s_t) + \gamma \sum_y \mathbb{P}_\theta(s_{t+1} = y \mid s_t) \nabla_\theta V_{t+1}(y)$ at reachable s_t , and for every n ,*

$$\nabla_\theta V_0(s_0) = \sum_{t < n} \gamma^t \sum_y \mathbb{P}_\theta(s_t = y \mid s_0) \sum_u Q_t(y, u) \nabla_\theta \pi_\theta(u \mid y) + \gamma^n \sum_y \mathbb{P}_\theta(s_n = y \mid s_0) \nabla_\theta V_n(y).$$

The second identity is proved by induction on n , expanding the remainder with the first and collapsing the double sum by the Chapman–Kolmogorov identity.

Theorem 7.2 (Truncated policy gradient [26]). *Assume (D), (P1), (P2). For every $n \in \mathbb{N}$,*

$$\sum_t' \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \mathbb{E}_\theta \left[\sum_{t < n} \gamma^t Q_t(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t) \right] + \gamma^n \mathbb{E}_\theta [\nabla_\theta V_n(s_n)].$$

The proof evaluates $\mathbb{E}_\theta[g(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)] = \sum_y \mathbb{P}_\theta(s_t = y) \sum_u g(y, u) \nabla_\theta \pi_\theta(u \mid y)$, the log-derivative trick $\pi \nabla_\theta \log \pi = \nabla_\theta \pi$ against the law of (s_t, a_t) . Despite the finite sum, the theorem concerns the discounted infinite-horizon objective: it is exact for every truncation level, with an explicit remainder. Letting $n \rightarrow \infty$, with the remainder going to 0 by Lemma 3.1 and the bound on $\nabla_\theta V_n$ over reachable states, gives the action-value form [23] $\sum_t' \gamma^t \nabla_\theta \mathbb{E}_\theta[r_t] = \sum_t' \gamma^t \mathbb{E}_\theta[Q_t(s_t, a_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)]$, and with the tower property [25], $\mathbb{E}_\theta[G_t \nabla_\theta \log \pi_\theta] = \mathbb{E}_\theta[Q_t \nabla_\theta \log \pi_\theta]$, the REINFORCE form.

Theorem 7.3 (Policy gradient, REINFORCE form [24]). *Let Θ be a real Hilbert space, S and A carry counting measure, and assume (D), (P1), (P2). Then*

$$\nabla_\theta \mathbb{E}_\theta \left[\sum_t' \gamma^t r_t \right] = \mathbb{E}_\theta \left[\sum_t' \gamma^t G_t \nabla_\theta \log \pi_\theta(a_t \mid s_t) \right].$$

Here the series sit inside the expectation; this is possible because rewards are bounded, and the shared lemmas [Log.Pr.of.Bounded](#) and [Bounded.Discount](#) exchange series and expectations.

7.2 Normalization gives a zero-mean score

The property that links the local normalization of Definition 6.1 to variance reduction is the following.

Lemma 7.4 ([Expect_ConditionedGrad_LogProb.eq.Zero](#) [16]). *Let $p : \Theta \rightarrow A \rightarrow \mathbb{R}$ with $\sum_a p_{\theta'}(a) = 1$ for all θ' , $p_\theta(a) > 0$ and $\theta' \mapsto p_{\theta'}(a)$ differentiable at θ . Then $\mathbb{E}_{a \sim p_\theta} [\nabla_\theta \log p_\theta(a)] = \sum_a p_\theta(a) \nabla_\theta \log p_\theta(a) = 0$.*

The proof is one line: $p \nabla_\theta \log p = \nabla_\theta p$, and $\nabla_\theta \sum_a p = \nabla_\theta 1 = 0$. Its conditional form for the policy of the trajectory model is [LogProb.eq.Zero.policy](#) [17]: $\mathbb{E}_\theta[\nabla_\theta \log \pi_\theta(a_t \mid s_t) \mid s_t = x] = 0$ for a positive differentiable policy. Inside the model file the same fact is used without positivity (terms with $\pi_\theta(u \mid x) = 0$ vanish): for every $h : S \rightarrow \mathbb{R}$, $\mathbb{E}_\theta[h(s_t) \nabla_\theta \log \pi_\theta(a_t \mid s_t)] = 0$ ([E_h_score](#)). This is why a baseline depending only on the state leaves the policy gradient unchanged, the step used in Section 7.3. For a globally normalized CRF the analogue is different: $\mathbb{E}_{p(y|x)}[\nabla_\theta \log p(y \mid x)] = 0$ holds as well, but $\nabla_\theta \log p = \nabla_\theta \text{score} - \mathbb{E}[\nabla_\theta \text{score}]$ contains the partition function; the identity $\nabla_\theta \log Z = \mathbb{E}[\nabla_\theta \text{score}]$ is not formalized.

7.3 Unbiased advantage and generalized advantage estimation

Let $\delta_j = r_j + \gamma V_{j+1}(s_{j+1}) - V_j(s_j)$ be the temporal-difference residual of a value function V .

Theorem 7.5 (Unbiased advantage estimate [31]). *Let Θ be a real Hilbert space, S and A carry counting measure, assume (D), (P1), (P2), and let $V_t^\theta(s_t) = \mathbb{E}_\theta[G_t \mid s_t]$ for all θ, t and all reachable s_t . With $\hat{A}_t = \sum_k' \gamma^k \delta_{t+k}$,*

$$\nabla_\theta \mathbb{E}_\theta \left[\sum_t' \gamma^t r_t \right] = \mathbb{E}_\theta \left[\sum_t' \gamma^t \hat{A}_t \nabla_\theta \log \pi_\theta(a_t \mid s_t) \right].$$

For bounded V the series telescopes to $\hat{A}_t = G_t - V_t(s_t)$, so Theorem 7.5 reduces to Theorem 7.3 plus the vanishing of the baseline term $\mathbb{E}_\theta[V_t(s_t) \nabla_\theta \log \pi_\theta] = 0$ of Section 7.2.

Theorem 7.6 (Generalized advantage estimate [29]). *Under the hypotheses of Theorem 7.5, let $\lambda \in [0, 1]$ and $\hat{A}_t^\lambda = \sum_k' (\gamma\lambda)^k \delta_{t+k}$. Then*

$$\nabla_\theta \mathbb{E}_\theta \left[\sum_t' \gamma^t r_t \right] = \mathbb{E}_\theta \left[\sum_t' \gamma^t \hat{A}_t^\lambda \nabla_\theta \log \pi_\theta(a_t \mid s_t) \right].$$

For $\lambda \in [0, 1)$ the weighted-average form $\hat{A}_t^\lambda = (1 - \lambda) \sum_{k \geq 0} \lambda^k \sum_{i \leq k} \gamma^i \delta_{t+i}$ of Schulman et al. [43] gives the same identity [30], via the series identity [28]. The reason is that, for the exact value function, $\mathbb{E}[\delta_{n+1} \psi(s_t, a_t)] = 0$ for $t \leq n$ (Markov property and Bellman equation), so only the first residual survives against the score. The statements concern the exact value function: with an approximate critic the terms $k \geq 1$ need not have zero mean and $\lambda < 1$ is biased [43]; that is not formalized.

8 PPO: what Lean covers and what it does not

MDP versus PPO. The MDP is a *model*; PPO is an *algorithm* defined on top of it. Everything in Sections 6 and 7 is about the model: the trajectory measure and its Markov property, the Bellman equations, the policy gradient theorem, the advantage and GAE. PPO [44] adds an importance ratio $\rho_t(\theta) = \pi_\theta(a_t \mid s_t) / \pi_{\theta_{\text{old}}}(a_t \mid s_t)$, a clipped surrogate

$$L^{\text{CLIP}}(\theta) = \hat{\mathbb{E}}_t \left[\min(\rho_t(\theta) \hat{A}_t, \text{clip}(\rho_t(\theta), 1 - \epsilon, 1 + \epsilon) \hat{A}_t) \right],$$

several epochs of minibatch stochastic updates on the same rollouts, a learned value network trained with a value loss (often clipped), an entropy bonus, and in RLHF [59, 38] a per-token KL penalty to a reference policy. None of these is formalized.

What the theorems give for PPO. (i) The advantage estimator of PPO is a truncated GAE (its Eqs. (10)–(11)); Theorem 7.6 justifies, for the exact value function, the *untruncated* estimator as an unbiased weight of the score inside the policy gradient. (ii) At $\theta = \theta_{\text{old}}$ the ratio is 1 and $\nabla_\theta \rho_t = \nabla_\theta \log \pi_\theta(a_t \mid s_t)$, so the gradient of the unclipped surrogate is the integrand of Theorem 7.6; this one-line calculus remark is not a Lean statement. (iii) The language-model case is an MDP with state $(x, y_{<t})$, action the next token, deterministic transition and the reward at the last token; this instance is not formalized either (Section 9).

What is not covered. There is no clipped surrogate or importance ratio, no TRPO-style KL constraint or KL penalty (the library has $\text{KL} \geq 0$, `Random.KL.ge.Zero`, which does not enter any PPO statement), no value clipping, no learned critic or its bias, no truncated-horizon GAE, no reward model, no minibatch sampling, and no monotone-improvement or convergence claim. Lean justifies the (truncated) GAE advantage estimator *inside the policy gradient*; it does not justify the clipped objective.

9 Beyond the core: labeling versus generation (conceptual)

This section is a comparison, not a theorem, and it is not part of the three core topics. The library has no sequence-to-sequence, teacher-forcing, exposure-bias or label-bias lemma; what it has are the two building blocks that the comparison combines.

Two normalizations of the same numerator. Let $\text{score}(x, y) = \sum_t f_t(y_{<t}, y_t; x)$ be an additive score. A *globally normalized* model sets $p(y \mid x) = e^{\text{score}(x, y)} / Z(x)$ with $Z(x) = \sum_{y'} e^{\text{score}(x, y')}$, so that $-\log p = \log Z(x) - \text{score}(x, y)$; for a linear chain, Theorem 5.3 computes Z exactly. A *locally normalized* model normalizes every step by its own softmax, $p(y \mid x) = \prod_t p(y_t \mid x, y_{<t})$ with $p(y_t \mid \cdot) = e^{f_t} / \sum_v e^{f_t(v)}$, so that

$$-\log p(y \mid x) = \sum_t \left(\log \sum_v e^{f_t(v)} - f_t(y_t) \right) = \sum_t (\log Z_t - f_t(y_t)).$$

Each summand is exactly the Lean identity [Log.Softmax.eq.Add.LogSumExp](#) of Section 5; the product-to-sum step is the same *log of a Markov product is a sum* property. The two models have the same numerator and differ only in the denominator: one $Z(x)$ against a product of per-step normalizers. The MEMM [37] is the locally normalized sibling of the CRF, and its label-bias problem (a state with few outgoing transitions passes all its mass on regardless of the observation) is the counterpart of the exposure bias of sequence-to-sequence models. Andor et al. [1] make the same case for globally normalized neural parsers.

What changes from labeling to generation.

1. *Alignment and observation.* In labeling, $|y| = |x|$ and x is observed in full at every position; in generation the output length is variable, there is no alignment, and the generated prefix $y_{<t}$ is part of the conditioning of step t .
2. *The Markov structure is relocated.* A linear-chain CRF is first-order in the *labels* and arbitrary in x ; an autoregressive model $p(y_t \mid x, y_{<t})$ conditions on the *whole prefix*, so it is Markov only in the enlarged state $(x, y_{<t})$. In that state space the transition is deterministic (append the chosen token), and the Markov property is trivial.
3. *Normalizer.* $Z(x)$ over k^n paths is computable by dynamic programming in $O(nk^2)$ because of first-order dependence; for a prefix-conditioned model the global sum over V^n sequences has no such recursion, which is why one normalizes locally.
4. *Inference.* Viterbi is exact for the chain; greedy, beam and sampling are approximate for generation.
5. *Training.* Labeling minimizes the supervised $\log Z$ -score. Generation is trained by teacher-forced cross-entropy, which needs the true prefix, or by expected reward, which is where policy gradients enter (Section 7).

A beam-search example. Consider a two-step example with $p(a) = 0.6$, $p(c) = 0.4$, $p(b \mid a) = 0.55$, $p(d \mid a) = 0.45$, $p(b \mid c) = 0.1$, $p(d \mid c) = 0.9$. Greedy decoding (beam size 1) returns (a, b) with probability 0.33; beam size 2 returns (c, d) with probability 0.36, the global maximum among the four sequences (0.33, 0.27, 0.04, 0.36). A locally normalized model is committed to its per-step decisions. This example is not checked in Lean.

10 Comparison tables

10.1 The Markov assumption across models

Table 2 compares what is factorized, what each factor conditions on, how it is normalized, and what is in Lean. The rows are the models of this paper; *conditioned on* is the information a factor may use. In every row the probability of a length- n object is a product of one-step factors, which gives (i) a sum of local terms in the log, (ii) a linear-time recursion (forward, backward, Viterbi, Bellman, value iteration) and (iii) induction on t as the proof technique (induction on t for the CRF lemmas; `hist_step` and the unrolling for the MDP).

Model	Factorized	Conditioned on	Normalization	Lean
HMM	$p(x, y) = \prod_t p(y_t \mid y_{t-1}) p(x_t \mid y_t)$ (generative)	previous label; emission on current label only	local, $Z = 1$	<code>IsHiddenMarkovSeq/Pr</code> , <code>crf.markov</code> (from conditional independences)
Linear-chain CRF	$p(y \mid x) = \frac{1}{Z(x)} \prod_t \psi_t(y_{t-1}, y_t, x)$ (discriminative)	adjacent labels; x arbitrary, fully observed	global $Z(x)$ over k^n paths	HMM-conditional instance: <code>crf.logits</code> , log Z -score, <code>crf.viterbi</code> ; forward and backward recursions for arbitrary weights (<code>crf.forward_backward</code>); general ψ_t as a model, normalized marginals and $\nabla \log Z$ not formalized
MEMM	$\prod_t p(y_t \mid y_{t-1}, x)$	previous label and x	local, per-step softmax	not formalized
MDP / policy gradient	$\iota(s_0) \prod_t \pi_\theta(a_t \mid s_t) T(s_{t+1} \mid s_t, a_t)$	next state and reward depend on (s_t, a_t) only; policy on s_t only	local, $Z = 1$	trajectory measure, <code>joint_succ</code> , <code>hist_step</code> , Bellman, policy gradient, advantage, GAE
PPO (algorithm)	same trajectory law; objective L^{CLIP} with ratio ρ_t and learned critic	as MDP	local, $Z = 1$	none : clipped surrogate, ratio, KL, value clipping, learned critic not formalized; only the (truncated) GAE advantage inside the policy gradient is justified (exact V)
Autoregressive LM	$\prod_t p(y_t \mid x, y_{<t})$	full prefix	local, per-step softmax	not formalized (only log-softmax and the two-variable chain rule); as an MDP with state $(x, y_{<t})$ the Markov property is trivial

Table 2: The Markov assumption in the models of this paper. HMM versus CRF differ in normalization (local versus global) and in what is modelled ($p(x, y)$ versus $p(y \mid x)$); MDP versus PPO differ in kind (model versus algorithm).

10.2 Sequence labeling versus sequence-to-sequence generation

Table 3 summarizes Section 9; it is a conceptual comparison. Only the entries marked “Lean” are theorems; everything else is a conceptual comparison.

	Sequence labeling (CRF)	Seq2seq generation (LM / PPO)
Input / alignment	aligned, $ y = x $, x fully observed	unaligned, variable length; the generated prefix is part of the conditioning
Normalization	global partition function over k^n label sequences	locally normalized token softmax
Dependence	adjacent labels (first order) and all of x	full prefix $y_{<t}$ (and x); Markov only in the state $(x, y_{<t})$
Training	supervised likelihood, $\text{NLL} = \log Z - \text{score}$ (Lean, HMM-conditional case)	teacher-forced cross-entropy, or expected reward (policy gradient / PPO)
Inference	exact dynamic programming: forward, backward, Viterbi (Lean: forward and backward sums; Viterbi values only)	approximate: greedy, beam, sampling
Failure mode	label bias if locally normalized (MEMM); invalid tag sequences with independent softmax	exposure bias; beam-size anomaly (the example of Section 9)
Gradient	$\nabla_{\theta} \text{NLL} = \mathbb{E}_{\text{model}}[\text{features}] - \text{empirical}$ (not in Lean)	$\nabla_{\theta} \mathbb{E}[R] = \mathbb{E}[\sum_t \gamma^t \hat{A}_t \nabla_{\theta} \log \pi_{\theta}(a_t s_t)]$ (Lean, finite S, A , exact V); $\mathbb{E}[\nabla_{\theta} \log \pi] = 0$ (Lean)

Table 3: Sequence labeling versus sequence-to-sequence generation.

11 Formalization artifact

Modules and version. Each theorem links to its module in [15] (prefix `Lemma.` omitted). The statements of this paper are those of the working tree following commit 5a58c908e: the CRF lemmas (Section 5), including the new forward-backward lemma of Theorem 5.4, the file with `IsHiddenMarkovSeq`, the advantage and GAE files and their helper lemmas were uncommitted when this was written. The temporal-difference lemmas (`delta_ae_bdd`, `E_delta_psi`, `E_sum_delta`) are in the advantage file of the trajectory model; the bounds `V_bdd` and `gradV_bdd` used in place of hypotheses on V and $\nabla_{\theta} V$ are in the differentiability file. The project uses Lean v4.33.1 with mathlib (revision 0df444a).

Checking. None of the cited modules contains `sorry`, `admit` or a new axiom. `#print axioms` reports for the declarations of Theorems 4.3–5.5, for the log-softmax, conditional-independence, chain-rule and zero-score lemmas of Sections 4–7.2, and for Theorems 6.2–7.6 and the helper lemmas, the axioms `propxt`, `Classical.choice`, `Quot.sound` and nothing else.

12 Discussion, limitations and conclusion

Regularity. The reinforcement-side theorems use finite S and A with counting measure, bounded rewards, $\gamma < 1$, differentiability and a uniform gradient bound (P1), (P2). The bounds on V_t and $\nabla_{\theta} V_t$ are derived from these, not assumed. The labeling-side theorems assume strictly positive probabilities so that logarithms are defined.

What is not formalized. We list the gaps that matter for the story of this paper.

- *General CRF.* The log-domain lemmas cover only the hidden-Markov-conditional instance; a CRF with arbitrary positive potentials $\psi_t(y_{t-1}, y_t, x)$ and its normalization $Z(x)$ is not defined as a model. The Markov structure enters the downstream lemmas as a factorization hypothesis (`IsHiddenMarkovSeq`, `IsHiddenMarkovPr`, or the chain (1) of Theorem 5.4); `IsHiddenMarkovPr` is derived from conditional independences (Theorem 4.3), but no CRF construction yields it.

- *Inference.* The forward recursion, the backward recursion and the forward–backward identity (Theorem 5.4) and the Viterbi *value* are covered. Not covered: the normalized posterior and the pairwise marginals, the gradient $\nabla_{\theta} \log Z = \mathbb{E}[\nabla_{\theta} \text{score}]$, the log-domain backward recursion, and an argmax Viterbi path with back-pointers.
- *Generation.* There is no sequence-to-sequence model, no teacher-forcing lemma, no statement about label bias or exposure bias, and no language-model-as-MDP instance. Section 9 is a comparison, not a theorem.
- *Analogy.* The correspondence between the forward, backward and Bellman recursions (Section 6.3) is not a Lean statement.
- *PPO.* No clipped objective, importance ratio, KL or value clipping, learned critic, truncated GAE, reward model, monotone improvement or convergence (Section 8).
- *GAE.* Only the exact value function; $\lambda < 1$ with an approximate critic introduces bias that is not analysed.
- *Spaces.* S, A finite; continuous or token-vocabulary-sized spaces are covered only to the extent that they are finite.

Reading the pieces together. What Lean does establish is the shared mechanism: a Markov product turns into a sum of per-step terms; recursions over the chain replace sums over exponentially many paths (forward and backward for the CRF, Viterbi, Bellman for the value function); and normalization of a local factor turns its score into a zero-mean term. Which normalization one chooses decides whether the recursion computes a partition function (CRF), a probability that is already one (HMM, policy), or a maximum (Viterbi). These are the objects that appear on the way from CRF to PPO.

Conclusion. We gave a Lean 4 account of three recursions on the path from linear-chain CRFs to policy-gradient reinforcement learning. For the CRF, we formalized the Markov product, the log-score decomposition, the forward recursion with the negative log-likelihood, the Viterbi value recursion, and a forward–backward theorem for arbitrary weights with the backward recursion and the identity $\sum_{ys_t=a} P_m(ys) = z_t(a)\beta_t(a)$. For reinforcement learning, we formalized the MDP trajectory measure, the Bellman equations, the policy gradient theorem in truncated, action-value and REINFORCE form, the zero-mean score, the unbiased advantage and GAE with the exact V . We separated carefully what is a theorem from what is a conceptual comparison. Natural next steps are the pairwise and normalized marginals and the identity $\nabla_{\theta} \log Z = \mathbb{E}[\nabla_{\theta} \text{score}]$ for a general-potential CRF, a Viterbi argmax with back-pointers, a locally normalized autoregressive model as an MDP with deterministic transitions, and the importance-ratio identity behind the PPO surrogate.

Acknowledgements. Mathlib [53, 36] provides the measure theory and analysis on which every theorem here rests. Su Jianlin’s articles on his blog Scientific Spaces were the guide to the CRF material [46, 47].

References

- [1] Daniel Andor, Chris Alberti, David Weiss, Aliaksei Severyn, Alessandro Presta, Kuzman Ganchev, Slav Petrov, and Michael Collins. Globally normalized transition-based neural networks. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2016. ACL Anthology P16-1231; arXiv:1603.06042.

- [2] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In *International Conference on Learning Representations*, 2015. arXiv:1409.0473.
- [3] Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. In *Advances in Neural Information Processing Systems*, volume 28, 2015. arXiv:1506.03099.
- [4] Mark Chevallier and Jacques Fleuriot. Formalising the foundations of discrete reinforcement learning in Isabelle/HOL. arXiv:2112.05996, <https://arxiv.org/abs/2112.05996>, 2021.
- [5] Ronan Collobert, Jason Weston, Léon Bottou, Michael Karlen, Koray Kavukcuoglu, and Pavel Kuksa. Natural language processing (almost) from scratch. *Journal of Machine Learning Research*, 12:2493–2537, 2011. arXiv:1103.0398.
- [6] Leonardo de Moura and Sebastian Ullrich. The Lean 4 theorem prover and programming language. In *Automated Deduction – CADE 28*, volume 12699 of *LNCS*, pages 625–635. Springer, 2021.
- [7] Evan Greensmith, Peter L. Bartlett, and Jonathan Baxter. Variance reduction techniques for gradient estimates in reinforcement learning. *Journal of Machine Learning Research*, 5:1471–1530, 2004.
- [8] Zhiheng Huang, Wei Xu, and Kai Yu. Bidirectional LSTM-CRF models for sequence tagging, 2015. arXiv:1508.01991.
- [9] Olav Kallenberg. *Foundations of Modern Probability*. Springer, 2nd edition, 2002.
- [10] John D. Lafferty, Andrew McCallum, and Fernando C. N. Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. In *Proceedings of the 18th International Conference on Machine Learning (ICML)*, pages 282–289, 2001.
- [11] Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. Neural architectures for named entity recognition. In *Proceedings of NAACL-HLT 2016*, pages 260–270, 2016. arXiv:1603.01360.
- [12] Peter J. Landin. The mechanical evaluation of expressions. *The Computer Journal*, 6(4):308–320, 1964.
- [13] lean-dojo. TorchLean: Formalizing neural networks in Lean. GitHub repository, <https://github.com/lean-dojo/TorchLean>, 2026.
- [14] Xuezhe Ma and Eduard Hovy. End-to-end sequence labeling via bi-directional LSTM-CNNs-CRF. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 1064–1074, 2016. arXiv:1603.01354.
- [15] math proof. lemma: machine-checked tensor calculus. <https://github.com/math-proof/lemma>, 2026.
- [16] math proof. Random.Expect_ConditionedGrad_LogProb.eq.Zero. http://www.lemma.cn/lean/?module=Random.Expect_ConditionedGrad_LogProb.eq.Zero, 2026.
- [17] math proof. Random.Expect_ConditionedGrad_LogProb.eq.Zero.policy. http://www.lemma.cn/lean/?module=Random.Expect_ConditionedGrad_LogProb.eq.Zero.policy, 2026.

- [18] math proof. `Random.Prob.eq.Mul_Prod_MulProbS.of.Ne_0.Eq.Eq.Eq`. http://www.lemma.cn/lean/?module=Random.Prob.eq.Mul_Prod_MulProbS.of.Ne_0.Eq.Eq.Eq, 2026.
- [19] math proof. `Real.Eq_0.Lim.of.LtAbs.IsFinite`. http://www.lemma.cn/lean/?module=Real.Eq_0.Lim.of.LtAbs.IsFinite, 2026.
- [20] math proof. `Tensor.And.Eq.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.Bellman`. http://www.lemma.cn/lean/?module=Tensor.And.Eq.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.Bellman, 2026.
- [21] math proof. `Tensor.And.of.All_Eq_Sum_Mul.All_Eq_1.All_Eq_Mul.All_Eq.forward_backward`. http://www.lemma.cn/lean/?module=Tensor.And.of.All_Eq_Sum_Mul.All_Eq_1.All_Eq_Mul.All_Eq.forward_backward, 2026.
- [22] math proof. `Tensor.And.of.Ne_0.Eq.Eq.Eq`. http://www.lemma.cn/lean/?module=Tensor.And.of.Ne_0.Eq.Eq.Eq, 2026.
- [23] math proof. `Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.IsFinite.Q_Function`. http://www.lemma.cn/lean/?module=Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.IsFinite.Q_Function, 2026.
- [24] math proof. `Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.IsFinite.policy_gradient_theorem`. http://www.lemma.cn/lean/?module=Tensor.Eq.Dot.Grad.Expect.of.Eq_Conditioned.IsFinite.policy_gradient_theorem, 2026.
- [25] math proof. `Tensor.Eq.Expect.Grad.Log.Pr.of.Eq_Conditioned.Q_Function.discounted`. http://www.lemma.cn/lean/?module=Tensor.Eq.Expect.Grad.Log.Pr.of.Eq_Conditioned.Q_Function.discounted, 2026.
- [26] math proof. `Tensor.Eq.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient`. http://www.lemma.cn/lean/?module=Tensor.Eq.Grad.Expect.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient, 2026.
- [27] math proof. `Tensor.Eq.of.Ne_0.Eq.Eq.Eq.Eq_log.Eq_log.Eq_log`. http://www.lemma.cn/lean/?module=Tensor.Eq.of.Ne_0.Eq.Eq.Eq.Eq_log.Eq_log.Eq_log, 2026.
- [28] math proof. `Tensor.EqDot.of.IsFinite.generalized_advantage_estimate`. http://www.lemma.cn/lean/?module=Tensor.EqDot.of.IsFinite.generalized_advantage_estimate, 2026.
- [29] math proof. `Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.generalized_advantage_estimate`. http://www.lemma.cn/lean/?module=Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.generalized_advantage_estimate, 2026.
- [30] math proof. `Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.In_Ico.generalized_advantage_estimate`. http://www.lemma.cn/lean/?module=Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.In_Ico.generalized_advantage_estimate, 2026.
- [31] math proof. `Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.unbiased_advantage_estimate`. http://www.lemma.cn/lean/?module=Tensor.EqDot_GradExpect.of.Eq_Conditioned.Eq_Expect.IsFinite.IsFinite.unbiased_advantage_estimate, 2026.

- [32] math proof. `Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.induct`. http://www.lemma.cn/lean/?module=Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.induct, 2026.
- [33] math proof. `Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.recurson`. http://www.lemma.cn/lean/?module=Tensor.EqGrad.of.Eq_Conditioned.Eq_Expect.Eq_Expect.policy_gradient.recurson, 2026.
- [34] math proof. `Tensor.Imp.of.Eq`. <http://www.lemma.cn/lean/?module=Tensor.Imp.of.Eq>, 2026.
- [35] math proof. `Tensor.Imp_Eq_Add_LogSumExp.EqNegLogProb.of.Ne0ProbJoint.Indep.y_given_x`. http://www.lemma.cn/lean/?module=Tensor.Imp_Eq_Add_LogSumExp.EqNegLogProb.of.Ne0ProbJoint.Indep.y_given_x, 2026.
- [36] Mathlib community. The Lean mathematical library. https://leanprover-community.github.io/mathlib4_docs/, 2026.
- [37] Andrew McCallum, Dayne Freitag, and Fernando C. N. Pereira. Maximum entropy Markov models for information extraction and segmentation. In *Proceedings of the 17th International Conference on Machine Learning (ICML)*, pages 591–598, 2000.
- [38] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, 2022. arXiv:2203.02155.
- [39] Martin L. Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. Wiley, 1994.
- [40] Lawrence R. Rabiner. A tutorial on hidden Markov models and selected applications in speech recognition. *Proceedings of the IEEE*, 77(2):257–286, 1989.
- [41] Marc’Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. Sequence level training with recurrent neural networks. In *International Conference on Learning Representations*, 2016. arXiv:1511.06732.
- [42] John Schulman, Sergey Levine, Philipp Moritz, Michael Jordan, and Pieter Abbeel. Trust region policy optimization. In *Proceedings of the 32nd International Conference on Machine Learning*, 2015. arXiv:1502.05477.
- [43] John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016. arXiv:1506.02438.
- [44] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017. arXiv:1707.06347.
- [45] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models, 2024. arXiv:2402.03300.
- [46] Jianlin Su. CRF in a nutshell (Guoke zhong de tiaojian sui ji chang). Scientific Spaces (kexue.fm) blog post, in Chinese, <https://spaces.ac.cn/archives/4695>, 2017.

- [47] Jianlin Su. Scientific spaces: search results for “CRF”. <https://spaces.ac.cn/search/CRF/>, 2026.
- [48] Jianlin Su, Ahmed Murtadha, Shengfeng Pan, Jing Hou, Jun Sun, Wanwei Huang, Bo Wen, and Yunfeng Liu. Global pointer: Novel efficient span-based approach for named entity recognition, 2022. arXiv:2208.03054.
- [49] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to sequence learning with neural networks. In *Advances in Neural Information Processing Systems*, volume 27, 2014. arXiv:1409.3215.
- [50] Charles Sutton and Andrew McCallum. An introduction to conditional random fields. *Foundations and Trends in Machine Learning*, 4(4):267–373, 2012. arXiv:1011.4088.
- [51] Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, 2nd edition, 2018.
- [52] Richard S. Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in Neural Information Processing Systems*, volume 12, pages 1057–1063. MIT Press, 2000.
- [53] The mathlib Community. The Lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP)*, pages 367–381. ACM, 2020.
- [54] Koundinya Vajjha, Avraham Shinnar, Barry Trager, Vasily Pestun, and Nathan Fulton. CertRL: Formalizing convergence proofs for value and policy iteration in Coq. In *Proceedings of the 10th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP)*, pages 18–31. ACM, 2021. arXiv:2009.11403.
- [55] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. arXiv:1706.03762.
- [56] Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8(3–4):229–256, 1992.
- [57] Sam Wiseman and Alexander M. Rush. Sequence-to-sequence learning as beam-search optimization. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2016. arXiv:1606.02960.
- [58] Shangdong Zhang. rl-theory-in-lean: RLTheory/Algorithm/PolicyGradient.lean, commit 2a9d01a. GitHub, 30 March 2026, <https://github.com/ShangdongZhang/rl-theory-in-lean/commit/2a9d01a236961b1c9bc451a8926346364fc66e7f>, 2026. Experimental, largely machine-generated development (commits co-authored with an AI assistant), committed in March 2026 and later withdrawn from the project’s main branch; still accessible at this commit.
- [59] Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B. Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences, 2019. arXiv:1909.08593.

Interactive statements of the modules cited in this paper are available at lemma.cn; the project is on [GitHub](#): [Lean 4](#).