Practical 11 (Post-lab):

Aim: Implementing a Virtual Memory System with Demand Paging where pages are loaded into memory only when needed, optimizing memory usage and minimizing page faults.

Code:

```
~
  GNU nano 8.7
#include <stdio.h>

int main() {
    int pages[50], frames[10];
    int n, f, i, j, k, flag, page_faults = 0, index = 0;

    printf("Enter number of pages: ");
    scanf("%d", &n);

    printf("Enter page reference string:\n");
    for(i = 0; i < n; i++) {
        scanf("%d", &pages[i]);
    }

    printf("Enter number of frames: ");
    scanf("%d", &f);

    // Initialize frames
    for(i = 0; i < f; i++) {
        frames[i] = -1;
    }

    printf("\nPage\tFrames\n");

    for(i = 0; i < n; i++) {
        flag = 0;

        // Check if page is already in frame
        for(j = 0; j < f; j++) {
            if(frames[j] == pages[i]) {
                flag = 1;
                break;
            }
        }

        // If page not found → page fault
        if(flag == 0) {
            frames[index] = pages[i];
            index = (index + 1) % f;
            page_faults++;
        }

        // Print frames
        printf("%d\t", pages[i]);
        for(k = 0; k < f; k++) {
            if(frames[k] != -1)
                printf("%d ", frames[k]);
            else
                printf("- ");
        }
        printf("\n");
    }

    printf("\nTotal Page Faults = %d\n", page_faults);

    return 0;
}
```

Output:

```
MAYUR LAP MSYS ~
$ nano postlab.c

MAYUR LAP MSYS ~
$ gcc postlab.c -o postl

MAYUR LAP MSYS ~
$ ./postlab
Enter number of pages: 8
Enter page reference string:
1 2 3 4 1 2 5 1
Enter number of frames: 3

Page    Frames
1       1 - -
2       1 2 -
3       1 2 3
4       4 2 3
1       4 1 3
2       4 1 2
5       5 1 3
1       5 1 3
Total Page Faults = 7
```