

1 version 1: Linear pQ with γ on T

$$\begin{aligned} \min E(Q, T) &= \frac{1}{2} \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) \, dx dt + \frac{\gamma}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 \, dx \\ \begin{cases} \rho c \dot{T}(x, t) = \nabla \cdot (k(x) \nabla T(x, t)) + Q(x, t) & \text{in } \Omega \times (0, t_F) \\ -k(x) \partial_{\nu} T(x, t) = h(x) (T(x, t) - T_{\text{out}}(x, t)) & \text{on } \partial\Omega \times [0, t_F] \\ T(x, 0) = T_{\text{ini}}(x) \end{cases} \\ Q \in U_{\text{ad}} &= \{Q \in L^2(\Omega \times (0, t_F)) \mid 0 \leq Q(x, t) \leq Q_{\text{max}}(x) \text{ a.e.}\} \end{aligned} \quad (\text{SE})$$

where $T(x, t)$ temperature in K (Henning: I will use °C, but written K is better), $Q(x, t)$ heating output in $\frac{W}{m^2}$, $p(t)$ price, ρ density in $\frac{kg}{m^3}$, c heat capacity in $\frac{J}{kg \cdot K}$, $k(x)$ heat transfer coefficient in $\frac{W}{m \cdot K}$, $h(x)$ convective heat transfer coefficient in $\frac{W}{m^2 \cdot K}$, 0 morning start time

Remember that $\partial_{\nu} T$ is the outer normal derivative with respect to x and any initial data (or end data) would have to satisfy the PDE.

SE and WSE In order to solve the (SE) we will use a more basic method, in which we separate between the spacial and temporal derivatives and first solve the PDE in space using approximations of the time derivatives and then the ODE in time or we try to decouple both variables as much as possible to get a linear system in block structure. This is done by Gridap automatically. Thus, we need the weak formulation only in space (so a semi-weak formulation of the whole system). Here we will give it in its weak form remarking that every time integral of the (WSE) for the (SWF) would be replaced by "for all $t \in (0, t_F)$ ", because computing the derivative of the energy functional is easier this way without losing track of the t , and get with the test space $H_1^1(\Omega \times (0, t_F))$ where $\Gamma = \Omega \times \{0\}$

$$\begin{aligned} \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) \, dx dt &= \int_0^{t_F} \int_{\Omega} \nabla \cdot (k(x) \nabla T(x, t)) \phi(x, t) + Q(x, t) \phi(x, t) \, dx dt \\ &= \int_0^{t_F} \int_{\Omega} -k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) + Q(x, t) \phi(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} k(x) \partial_{\nu} T(y, t) \phi(x, t) \, dy dt \\ &= \int_0^{t_F} \int_{\Omega} -k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) + Q(x, t) \phi(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y, t)) \phi(x, t) \, dy dt \end{aligned}$$

giving us the weak formulation

$$\int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) \, dx dt = \int_0^{t_F} \int_{\Omega} -k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) + Q(x, t) \phi(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y, t)) \phi(y, t) \, dy dt \quad (\text{WSE})$$

and thus

$$\begin{aligned} a_{\text{SE}}(T, \phi) &= \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) + k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T(y, t) \phi(y, t) \, dy dt, \\ l_{\text{SE}}(\phi) &= \int_0^{t_F} \int_{\Omega} Q(x, t) \phi(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T_{\text{out}}(y, t) \phi(y, t) \, dy dt \end{aligned}$$

By Lax-Milgram there exists a unique solution $T(x, t)$ and thus we can define a solution operator $S : L^2(\Omega \times (0, t_F)) \rightarrow H^1(\Omega \times (0, t_F))$, $S(Q) = T$.

Henning: remember that each boundary integral could be rewritten with the Trace operator, might be helpful for the next part. When writing the (WSE) the open interval for $t \in (0, t_F)$ is important.

Lagrangian + AE From the optimisation functional and the (WSE) we get the Lagrangian as

$$L(T, Q, W) = \frac{1}{2} \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) \, dx dt + \frac{\gamma}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 \, dx + \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) + k(x) \nabla T(x, t) \cdot \nabla W(x, t) - Q(x, t) W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y, t)) W(y, t) \, dy dt$$

which gives us the weak formulation of the adjoint (AE) as (notice that the second term contains $\dot{\psi}$ which in the (WSE) would be zero and thus needs to be solved differently: in that case we are actually only looking for the derivative of the x dependent T , so that the derivative $\partial_{T(x)}T(x, t)$ does not give 1 but a time dependent function)

$$L_T(T, Q, W)\psi = \gamma \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t_F) dx + \int_0^{t_F} \int_{\Omega} \rho c \dot{\psi}(x, t) W(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) dy dt$$

By Green for the t variable (integration by parts) we get

$$\int_0^{t_F} \int_{\Omega} \rho c \dot{\psi}(x, t) W(x, t) dx dt = - \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) dx dt + \left[\int_{\Omega} \rho c \psi(x, t) W(x, t) dx \right]_0^{t_F} = - \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) dx dt + \int_{\Omega} \rho c \psi(x, t_F) W(x, t_F) dx$$

when assuming $W(x, 0) = 0$ a.e. (because W has to be able to operate as test function for (SE)) and thus $\psi \in H_{\Gamma}^1(\Omega \times (0, t_F))$, which gives the weak version as

$$0 = \int_{\Omega} \gamma (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t_F) + \rho c \psi(x, t_F) W(x, t_F) dx + \int_0^{t_F} \int_{\Omega} -\rho c \dot{W}(x, t) \psi(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) dy dt$$

or when setting the end condition based on the first integral simply as

$$\int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) - k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) dx dt = - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) dy dt \quad (\text{WAE})$$

Also by Green for any $t \in (0, t_F)$ it is

$$\int_{\Omega} k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) dx = - \int_{\Omega} \nabla \cdot (k(x) \nabla W(x, t)) \psi(x, t) dx + \int_{\partial\Omega} k(y) \partial_{\nu} W(y, t) \psi(y, t) dy$$

With these it is

$$L_T(T, Q, W)\psi = \gamma \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t_F) dx - \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) + \nabla \cdot (k(x) \nabla W(x, t)) \psi(x, t) dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) - k(y) \partial_{\nu} W(y, t) \psi(y, t) dy dt + \int_{\Omega} \rho c \psi(x, t_F) W(x, t_F) dx$$

giving the strong version

$$\begin{cases} \rho c \dot{W}(x, t) = -\nabla \cdot (k(x) \nabla W(x, t)) & \text{in } \Omega \times (0, t_F) \\ k(y) \partial_{\nu} W(y, t) = h(y) W(y, t) & \text{on } \partial\Omega \times [0, t_F] \\ W(x, t_F) = -\frac{\gamma}{\rho c} (T(x, t_F) - T_{\text{fin}}(x)) & \text{in } \Omega \end{cases} \quad (\text{AE})$$

Thus, we can see that the (AE) has to be solved backwards in time. For the (AE) we have

$$a_{\text{AE}}(W, \psi) = \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) - k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) dy dt \quad l_{\text{AE}}(\psi) = 0$$

By Lax-Milgram there exists a unique solution $W(x, t)$ and thus a solution operator $S^* : L^2(\Omega) \rightarrow H^1(\Omega \times (0, t_F))$, $S^*(T(x, t_F) - T_{\text{fin}}(x)) = W(x, t)$.

Henning: Actually, we get the (AE) by the variation principle and not by differentiation, which does not fully make sense here (see 1).

adjoint forward Since the (AE) has to be solved backwards in time, which is not possible with the software we are using (although implementation would be just as is) we introduce $\widetilde{W}(x, t) = W(x, t_F - t)$. By the (AE) this function satisfies

$$\begin{cases} \rho c \dot{\widetilde{W}}(x, t) = \nabla \cdot (k(x) \nabla \widetilde{W}(x, t)) & \text{in } \Omega \times (0, t_F) \\ k(y) \partial_{\nu} \widetilde{W}(y, t) = h(y) \widetilde{W}(y, t) & \text{on } \partial\Omega \times [0, t_F] \\ \widetilde{W}(x, 0) = -\frac{\gamma}{\rho c} (T(x, t_F) - T_{\text{fin}}(x)) & \text{in } \Omega \end{cases} \quad (\text{AE}')$$

which can now be solved forward in time. The weak version is

$$\int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{\widetilde{W}}(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla \widetilde{W}(x, t) dx dt = \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) \widetilde{W}(y, t) dy dt \quad (\text{WAE})$$

For the (AE') we have

$$a_{\text{AE}}(\widetilde{W}, \psi) = \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{\widetilde{W}}(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla \widetilde{W}(x, t) dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) \widetilde{W}(y, t) dy dt \quad l_{\text{AE}}(\psi) = 0 \quad (1)$$

which then gives us the original adjoint as $W(x, t) = \widetilde{W}(x, t_F - t)$.

Variation In order to find the adjoint, we introduce a small variation δT of T in the respective space and look at the difference this variation makes on L (this is like computing $L(T_1, Q, W) - L(T_2, Q, W)$, remember that the adjoint is a measure for the sensitivity of the functional with respect to T).

$$\begin{aligned}\delta_T L(T, Q, W) &= \frac{\gamma}{2} \int_{\Omega} \delta_T |T(x, t_F) - T_{\text{fin}}(x)|^2 dx + \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) - k(x) \nabla \delta T(x, t) \cdot \nabla W(x, t) dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (\delta T(y, t) - T_{\text{out}}(y)) W(y, t) dy dt \\ &= \gamma \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \delta T(x, t_F) dx - \int_0^{t_F} \int_{\Omega} \rho c \delta T(x, t) \dot{W}(x, t) dx dt + \int_{\Omega} \rho c \delta T(x, t_F) W(x, t_F) dx - \int_0^{t_F} \int_{\Omega} k(x) \nabla \delta T(x, t) \cdot \nabla W(x, t) dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (\delta T(y, t) - T_{\text{out}}(y)) W(y, t) dy dt\end{aligned}$$

where we used the same as above and $\delta T(x, 0) = 0$ because of the initial value condition, which fixes the T s there and because the term is linear. Also for the first term we used Taylor giving us $x^2 = x_0^2 + 2x(x - x_0) + o((x - x_0)^2)$, giving us $\delta_x(x - a)^2 = (x - a)^2 - (x_0 - a)^2 = 2(x - a)(x - x_0) + o(x - x_0) = 2(x - a)\delta_x$.

Solution operator + gradient Now we introduce the solution operator S , which for a given Q gives the solution T of the (SE), so $T = S(Q)$. With this we can introduce the reduced energy functional

$$e(Q) = \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) dx dt + \frac{\gamma}{2} \int_{\Omega} |S(Q)(x, t_F) - T_{\text{fin}}(x)|^2 dx \quad (2)$$

In order to find the gradient of e we differentiate it and find by noting that S is linear and therefore has derivative $S'(Q)h = Sh$

$$e'(Q)h = \int_0^{t_F} \int_{\Omega} p(t) h(x, t) dx dt + \gamma \int_{\Omega} (S(Q)(x, t_F) - T_{\text{fin}}(x)) Sh dx \quad (3)$$

$$= \langle p|h \rangle + \langle S(Q) - T_{\text{fin}} | Sh \rangle|_{t=t_F} = \langle p|h \rangle + \gamma \langle S^*(S(Q) - T_{\text{fin}}) | h \rangle|_{t=t_F} \equiv p - \rho c W \quad (4)$$

where S^* is the solution operator for (AE) and W is the solution

2 Linear pQ with λ on Q

$$\begin{aligned}\min E(Q, T) &= \frac{\gamma}{2} \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) dx dt + \frac{1}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 dx \\ \begin{cases} \rho c \dot{T}(x, t) = \nabla \cdot (k(x) \nabla T(x, t)) + Q(x, t) & \text{in } \Omega \times (0, t_F) \\ -k(x) \partial_{\nu} T(x, t) = h(x) (T(x, t) - T_{\text{out}}(x, t)) & \text{on } \partial\Omega \times [0, t_F] \\ T(x, 0) = T_{\text{ini}}(x) \end{cases} & \quad (SE) \\ Q \in U_{\text{ad}} = \{Q \in L^2(\Omega \times (0, t_F)) \mid 0 \leq Q(x, t) \leq Q_{\text{max}}(x) \text{ a.e.}\} \end{aligned}$$

SE and WSE

$$\int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) dx dt = \int_0^{t_F} \int_{\Omega} -k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) + Q(x, t) \phi(x, t) dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) \phi(y, t) dy dt \quad (\text{WSE})$$

and thus

$$\begin{aligned}a_{\text{SE}}(T, \phi) &= \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) + k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T(y, t) \phi(y, t) dy dt, \\ l_{\text{SE}}(\phi) &= \int_0^{t_F} \int_{\Omega} Q(x, t) \phi(x, t) dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T_{\text{out}}(y) \phi(y, t) dy dt\end{aligned}$$

By Lax-Milgram there exists a unique solution $T(x, t)$ and thus we can define a solution operator $S : L^2(\Omega \times (0, t_F)) \rightarrow H^1(\Omega \times (0, t_F))$, $S(Q) = T$.

Lagrangian + AE From the optimisation functional and the (WSE) we get the Lagrangian as

$$\begin{aligned}
L(T, Q, W) &= \frac{\gamma}{2} \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) \, dx dt + \frac{1}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 dx + \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) + k(x) \nabla T(x, t) \cdot \nabla W(x, t) - Q(x, t) W(x, t) \, dx dt \\
&\quad + \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) W(y, t) \, dy dt \\
L_T(T, Q, W) \psi &= \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t_F) dx + \int_0^{t_F} \int_{\Omega} \underbrace{\rho c \dot{\psi}(x, t) W(x, t)}_{\substack{\rho c \psi(x, t) \dot{W}(x, t) \\ + k(x) \nabla \psi(x, t) \cdot \nabla W(x, t)}} \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) \, dy dt \\
&\quad - \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) \, dx dt + \left[\int_{\Omega} \rho c \psi(x, t) W(x, t) \, dx \right]_0^{t_F} \\
&= - \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) \, dx dt + \int_{\Omega} \rho c \psi(x, t_F) W(x, t_F) \, dx
\end{aligned}$$

which gives the weak version as

$$0 = \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t_F) dx + \int_0^{t_F} \int_{\Omega} -\rho c \dot{W}(x, t) \psi(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) \, dy dt$$

or when setting the end condition based on the first integral simply as

$$\int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) - k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) \, dy dt = 0 \quad (\text{WAE})$$

Also by Green for any $t \in (0, t_F)$ it is

$$\int_{\Omega} k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) \, dx = - \int_{\Omega} \nabla \cdot (k(x) \nabla W(x, t)) \psi(x, t) \, dx + \int_{\partial\Omega} k(y) \partial_{\nu} W(y, t) \psi(y, t) \, dy$$

With these it is

$$L_T(T, Q, W) \psi = \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t) dx - \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) + \nabla \cdot (k(x) \nabla W(x, t)) \psi(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) - k(y) \partial_{\nu} W(y, t) \psi(y, t) \, dy dt + \int_{\Omega} \rho c \psi(x, t_F) W(x, t_F) \, dx$$

giving the strong version

$$\begin{cases} \rho c \dot{W}(x, t) = -\nabla \cdot (k(x) \nabla W(x, t)) & \text{in } \Omega \times (0, t_F) \\ k(y) \partial_{\nu} W(y, t) = h(y) W(y, t) & \text{on } \partial\Omega \times [0, t_F] \\ W(x, t_F) = -\frac{1}{\rho c} (T(x, t_F) - T_{\text{fin}}(x)) & \text{in } \Omega \end{cases} \quad (\text{AE})$$

Thus, we can see that the (AE) has to be solved backwards in time. For the (AE) we have

$$\alpha_{\text{AE}}(W, \psi) = \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{W}(x, t) - k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) W(y, t) \, dy dt \quad l_{\text{AE}}(\psi) = 0$$

By Lax-Milgram there exists a unique solution $W(x, t)$ and thus a solution operator $S^* : L^2(\Omega) \rightarrow H^1(\Omega \times (0, t_F))$, $S^*(T(x, t_F) - T_{\text{fin}}(x)) = W(x, t)$.

Henning: Actually, we get the (AE) by the variation principle and not by differentiation, which does not fully make sense here (see 1).

adjoint forward Since the (AE) has to be solved backwards in time, which is not possible with the software we are using (although implementation would be just as is) we introduce $\widetilde{W}(x, t) = W(x, t_F - t)$. By the (AE) this function satisfies

$$\begin{cases} \rho c \dot{\widetilde{W}}(x, t) = \nabla \cdot (k(x) \nabla \widetilde{W}(x, t)) & \text{in } \Omega \times (0, t_F) \\ k(y) \partial_{\nu} \widetilde{W}(y, t) = h(y) \widetilde{W}(y, t) & \text{on } \partial\Omega \times [0, t_F] \\ \widetilde{W}(x, 0) = -\frac{1}{\rho c} (T(x, t_F) - T_{\text{fin}}(x)) & \text{in } \Omega \end{cases} \quad (\text{AE}')$$

which can now be solved forward in time. The weak version is

$$\int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{\widetilde{W}}(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla \widetilde{W}(x, t) \, dx dt = \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) \widetilde{W}(y, t) \, dy dt \quad (\text{WAE})$$

For the (AE') we have

$$a_{\text{AE}}(\widetilde{W}, \psi) = \int_0^{t_F} \int_{\Omega} \rho c \psi(x, t) \dot{\widetilde{W}}(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla \widetilde{W}(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) \psi(y, t) \widetilde{W}(y, t) \, dy dt \quad l_{\text{AE}}(\psi) = 0 \quad (5)$$

which then gives us the original adjoint as $W(x, t) = \widetilde{W}(x, t_F - t)$.

Variation In order to find the adjoint, we introduce a small variation δT of T in the respective space and look at the difference this variation makes on L (this is like computing $L(T_1, Q, W) - L(T_2, Q, W)$, remember that the adjoint is a measure for the sensitivity of the functional with respect to T).

$$\begin{aligned} \delta_T L(T, Q, W) &= \frac{1}{2} \int_{\Omega} \delta T(x, t_F) - T_{\text{fin}}(x) \big|^2 dx + \int_0^{t_F} \int_{\Omega} \rho c \delta T(x, t) W(x, t) - k(x) \nabla \delta T(x, t) \cdot \nabla W(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (\delta T(y, t) - T_{\text{out}}(y)) W(y, t) \, dy dt \\ &= \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \delta T(x, t_F) dx - \int_0^{t_F} \int_{\Omega} \rho c \delta T(x, t) \dot{W}(x, t) \, dx dt + \int_{\Omega} \rho c \delta T(x, t_F) W(x, t_F) \, dx - \int_0^{t_F} \int_{\Omega} k(x) \nabla \delta T(x, t) \cdot \nabla W(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (\delta T(y, t) - T_{\text{out}}(y)) W(y, t) \, dy dt \end{aligned}$$

where we used the same as above and $\delta T(x, 0) = 0$ because of the initial value condition, which fixes the T s there and because the term is linear. Also for the first term we used Taylor giving us $x^2 = x_0^2 + 2x(x - x_0) + o((x - x_0)^2)$, giving us $\delta_x(x - a)^2 = (x - a)^2 - (x_0 - a)^2 = 2(x - a)(x - x_0) + o(x - x_0) = 2(x - a)\delta_x$.

Solution operator + gradient Now we introduce the solution operator S , which for a given Q gives the solution T of the (SE), so $T = S(Q)$. With this we can introduce the reduced energy functional

$$e(Q) = \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) \, dx dt + \frac{\gamma}{2} \int_{\Omega} |S(Q)(x, t_F) - T_{\text{fin}}(x)|^2 dx \quad (6)$$

In order to find the gradient of e we differentiate it and find by noting that S is linear and therefore has derivative $S'(Q)h = Sh$

$$e'(Q)h = \int_0^{t_F} \int_{\Omega} p(t) h(x, t) \, dx dt + \gamma \int_{\Omega} (S(Q)(x, t_F) - T_{\text{fin}}(x)) Sh \, dx \quad (7)$$

$$= \langle p|h \rangle + \langle S(Q) - T_{\text{fin}} | Sh \rangle|_{t=t_F} = \langle p|h \rangle + \gamma \langle S^*(S(Q) - T_{\text{fin}}) | h \rangle|_{t=t_F} \equiv p - \rho c W \quad (8)$$

where S^* is the solution operator for (AE) and W is the solution

3 version 2: quadratic pQ with λ on T

$$\begin{aligned} \min E(Q, T) &= \frac{1}{2} \int_0^{t_F} \int_{\Omega} (p(t) Q(x, t))^2 \, dx dt + \frac{\gamma}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 dx \\ &\begin{cases} \rho c \dot{T}(x, t) = \nabla \cdot (k(x) \nabla T(x, t)) + Q(x, t) & \text{in } \Omega \times (0, t_F) \\ -k(x) \partial_{\nu} T(x, t) = h(x) (T(x, t) - T_{\text{out}}(x, t)) & \text{on } \partial\Omega \times [0, t_F] \\ T(x, 0) = T_{\text{ini}}(x) \end{cases} \quad (\text{SE}) \\ Q &\in U_{\text{ad}} = \{Q \in L^2(\Omega \times (0, t_F)) \mid 0 \leq Q(x, t) \leq Q_{\text{max}}(x) \text{ a.e.}\} \end{aligned}$$

In this case mostly everything stays the same.

SE and WSE We have the weak formulation

$$\int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) \, dx dt = \int_0^{t_F} \int_{\Omega} -k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) + Q(x, t) \phi(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) \phi(y, t) \, dy dt \quad (\text{WSE})$$

and thus

$$a_{\text{SE}}(T, \phi) = \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) \phi(x, t) + k(x) \nabla T(x, t) \cdot \nabla \phi(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T(y, t) \phi(y, t) \, dy dt,$$

$$l_{\text{SE}}(\phi) = \int_0^{t_F} \int_{\Omega} Q(x, t) \phi(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T_{\text{out}}(y) \phi(y, t) \, dy dt$$

By Lax-Milgram there exists a unique solution $T(x, t)$ and thus we can define a solution operator $S : L^2(\Omega \times (0, t_F)) \rightarrow H^1(\Omega \times (0, t_F))$, $S(Q) = T$.

Lagrangian + AE One difference is the Lagrangian which is

$$L(T, Q, W) = \frac{1}{2} \int_0^{t_F} \int_{\Omega} (p(t) Q(x, t))^2 \, dx dt + \frac{\gamma}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 \, dx + \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) - k(x) \nabla T(x, t) \cdot \nabla W(x, t) - Q(x, t) W(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) W(y, t) \, dy dt \quad (9)$$

Solution operator + gradient Now we introduce the solution operator S , which for a given Q gives the solution T of the (SE), so $T = S(Q)$. With this we can introduce the reduced energy functional

$$e(Q) = \frac{1}{2} \int_0^{t_F} \int_{\Omega} (p(t) Q(x, t))^2 \, dx dt + \frac{\gamma}{2} \int_{\Omega} |S(Q)(x, t_F) - T_{\text{fin}}(x)|^2 \, dx \quad (10)$$

In order to find the gradient of e we differentiate it and find by noting that S is linear and therefore has derivative $S'(Q)h = Sh$

$$\begin{aligned} e'(Q)h &= \int_0^{t_F} \int_{\Omega} p^2(t) Q(x, t) h(x, t) \, dx dt + \gamma \int_{\Omega} (S(Q)(x, t_F) - T_{\text{fin}}(x)) Sh \, dx \\ &= \langle p^2 Q | h \rangle + \gamma \langle S(Q) - T_{\text{fin}} | Sh \rangle|_{t=t_F} = \langle p^2 Q | h \rangle + \langle \gamma S^*(S(Q) - T_{\text{fin}}) | h \rangle|_{t=t_F} \hat{=} p^2 Q - W \end{aligned}$$

Thus, without box constraints from the condition $e'(Q) = 0$ we would get $Q = \frac{1}{p^2} W$ and can use the projection of that onto the box for our case (see bang bang).

We can also get the gradient by the (VI) which we get by $L_Q = 0$ as

$$0 = L_Q(T, Q, W)h = \int_0^{t_F} \int_{\Omega} p^2(t) Q(x, t) h(x, t) \, dx dt - \int_0^{t_F} \int_{\Omega} W(x, t) h(x, t) \, dx dt = \langle p^2 Q - W, h \rangle_{L^2(\Omega \times (0, t_F))}$$

This property has to hold for every $h \in Q_{\text{ad}} - Q$ for the Q from the integral, which gives us the bang-bang result.

Optimal step size We found out that the gradient of the reduced cost is $\nabla e(Q) = p^2 Q - W$, so in the gradient descent algorithm we will go into the negative of that direction and we can actually compute the optimal step size. Consider a given iteration k and the computed control Q_k , state T_k and adjoint W_k . Also let $v_k = -\nabla e(Q) = -(p^2 Q - W)$, $I = [t_0, t_F]$ and define as the step-length-dependent function we want to minimise in the iteration

$$g(s) = e(Q_k + s v_k)$$

Then we can rewrite

$$\begin{aligned} g(s) &= e(Q_k + s v_k) \\ &= \frac{1}{2} \|p(Q_k + s v_k)\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|S(Q_k + s v_k) - T_{\text{fin}}\|_{L^2(\Omega)}^2|_{t=t_F} \\ &= \frac{1}{2} \|p Q_k\|_{L^2(\Omega \times I)}^2 + s \langle p^2 Q_k, v_k \rangle_{L^2(\Omega \times I)} + \frac{s^2}{2} \|p v_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|T_k - T_{\text{fin}}\|_{L^2(\Omega)}^2|_{t=t_F} + \gamma s \langle T_k - T_{\text{fin}}, S v_k \rangle_{L^2(\Omega)}|_{t=t_F} + s^2 \frac{\gamma}{2} \|S v_k\|_{L^2(\Omega)}^2|_{t=t_F} \\ &= s^2 \left(\frac{1}{2} \|p v_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|S v_k\|_{L^2(\Omega)}^2|_{t=t_F} \right) + s \left(\langle p^2 Q_k, v_k \rangle_{L^2(\Omega \times I)} + \gamma \langle T_k - T_{\text{fin}}, S v_k \rangle_{L^2(\Omega)}|_{t=t_F} \right) + 1 \left(\frac{1}{2} \|p Q_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|T_k - T_{\text{fin}}\|_{L^2(\Omega)}^2|_{t=t_F} \right) \\ &= s^2 \left(\frac{1}{2} \|p v_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|S v_k\|_{L^2(\Omega)}^2|_{t=t_F} \right) + s \left(\langle p^2 Q_k, v_k \rangle_{L^2(\Omega \times I)} + \gamma \langle S^*(T_k - T_{\text{fin}}), v_k \rangle_{L^2(\Omega)}|_{t=t_F} \right) + 1 \left(\frac{1}{2} \|p Q_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|T_k - T_{\text{fin}}\|_{L^2(\Omega)}^2|_{t=t_F} \right) \\ &= s^2 \left(\frac{1}{2} \|p v_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|S v_k\|_{L^2(\Omega)}^2|_{t=t_F} \right) + s \left(\langle p^2 Q_k, v_k \rangle_{L^2(\Omega \times I)} + \langle W_k, v_k \rangle_{L^2(\Omega)}|_{t=t_F} \right) + 1 \left(\frac{1}{2} \|p Q_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|T_k - T_{\text{fin}}\|_{L^2(\Omega)}^2|_{t=t_F} \right) \\ &= s^2 \left(\frac{1}{2} \|p v_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|S v_k\|_{L^2(\Omega)}^2|_{t=t_F} \right) - s \|v_k\|_{L^2(\Omega \times I)}^2 + 1 \left(\frac{1}{2} \|p Q_k\|_{L^2(\Omega \times I)}^2 + \frac{\gamma}{2} \|T_k - T_{\text{fin}}\|_{L^2(\Omega)}^2|_{t=t_F} \right) \end{aligned}$$

This is a quadratic function in s and has the minimum in

$$s_{\min} = \frac{\|v_k\|_{L^2(\Omega \times I)}^2}{\|pv_k\|_{L^2(\Omega \times I)}^2 + \gamma \|Sv_k\|_{L^2(\Omega)}^2|_{t=t_F}}$$

which requires to solve the (SE) again with input v_k instead of Q_k .

4 Version 3

$$\begin{aligned} \min E(Q, T) &= \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) \, dx dt \\ \begin{cases} \rho c \dot{T}(x, t) = \nabla \cdot (k(x) \nabla T(x, t)) + Q(x, t) & \text{in } \Omega \times (0, t_F) \\ -k(x) \partial_{\nu} T(x, t) = h(x) (T(x, t) - T_{\text{out}}(x, t)) & \text{on } \partial\Omega \times [0, t_F] \\ T(x, 0) = T_{\text{ini}}(x) \end{cases} \\ Q \in U_{\text{ad}} &= \{Q \in L^2(\Omega \times (0, t_F)) \mid 0 \leq Q(x, t) \leq Q_{\max}(x) \text{ a.e.}\} \\ T(x, t_F) &\geq T_{\text{fin}}(x) \end{aligned} \quad (\text{SE})$$

The (SE) and thus (WSE) is the same. But we get a new Lagrangian multiplier $\mu \geq 0$ and the Lagrangian is

$$L(T, q, W, \mu) = \int_0^{t_F} \int_{\Omega} p(t) Q(x, t) \, dx dt + \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) + k(x) \nabla T(x, t) \cdot \nabla W(x, t) - Q(x, t) W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) W(y, t) \, dy dt + \int_{\Omega} \mu(x) (T(x, t_F) - T_{\text{fin}}(x)) \, dx$$

5 Version 4

$$\begin{aligned} \min E(Q_t, T) &= \frac{1}{2} \int_0^{t_F} (p(t) Q_t(t))^2 \int_{\Omega} Q_{\text{pos}}^2(x) \, dx dt + \frac{\gamma}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 \, dx \\ \begin{cases} \rho c \dot{T}(x, t) = \nabla \cdot (k(x) \nabla T(x, t)) + Q_t(t) Q_{\text{pos}}(x) & \text{in } \Omega \times (0, t_F) \\ -k(x) \partial_{\nu} T(x, t) = h(x) (T(x, t) - T_{\text{out}}(x, t)) & \text{on } \partial\Omega \times [0, t_F] \\ T(x, 0) = T_{\text{ini}}(x) \end{cases} \\ Q \in U_{\text{ad}} &= \{Q \in L^2(\Omega \times (0, t_F)) \mid 0 \leq Q(x, t) \leq Q_{\max}(x) \text{ a.e.}\} \\ T(x, t_F) &\geq T_{\text{fin}}(x) \end{aligned} \quad (\text{SE})$$

We assume the heat of the heater has the form $Q(x, t) = Q_t(t) Q_{\text{pos}}(x)$, where Q_{pos} is an indicator function describing the (not changing) position of the heater and Q_t describes the power output between 0 and $Q_{\max}$. So Q is represented by Q_t describing what setting the thermostat is on, and we can focus just on that function.

$$\begin{aligned} L(Q_t, T, W) &= \frac{1}{2} \int_0^{t_F} (p(t) Q_t(t))^2 \int_{\Omega} Q_{\text{pos}}^2(x) \, dx dt + \frac{\gamma}{2} \int_{\Omega} |T(x, t_F) - T_{\text{fin}}(x)|^2 \, dx + \int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) + k(x) \nabla T(x, t) \cdot \nabla W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y, t)) W(y, t) \, dy dt + \int_0^{t_F} Q_t(t) \int_{\Omega} Q_{\text{pos}}(x) W(x, t) \, dx dt \\ L_T(Q_t, T, W) \psi &= \gamma \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) \psi(x, t_F) \, dx + \int_0^{t_F} \int_{\Omega} \underbrace{\rho c \dot{\psi}(x, t) W(x, t)}_{\left[\int_{\Omega} \rho c \psi(x, t) W(x, t) \right]_{t=0}^{t=t_F} - \int_0^{t_F} \int_{\Omega} \rho c \dot{W}(x, t) \psi(x, t) \, dx dt} + k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) W(y, t) \psi(y, t) \, dy dt \\ &= \int_{\Omega} (\gamma (T(x, t_F) - T_{\text{fin}}(x)) + \rho c W(x, t_F)) \psi(x, t_F) \, dx + \int_0^{t_F} \int_{\Omega} -\rho c \dot{W}(x, t) \psi(x, t) + k(x) \nabla \psi(x, t) \cdot \nabla W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) W(y, t) \psi(y, t) \, dy dt \\ &= \int_{\Omega} (\gamma (T(x, t_F) - T_{\text{fin}}(x)) + \rho c W(x, t_F)) \psi(x, t_F) \, dx - \int_0^{t_F} \int_{\Omega} \rho c \dot{W}(x, t) \psi(x, t) + \nabla \cdot (k(x) \nabla W(x, t)) \psi(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) W(y, t) \psi(y, t) + k(x) \partial_{\nu} W(y, t) \, dy dt \\ L_{Q_t}(Q_t, T, W) h &= \int_0^{t_F} p^2(t) Q_t(t) h(t) \int_{\Omega} Q_{\text{pos}}^2(x) \, dx dt + \int_0^{t_F} h(t) \int_{\Omega} Q_{\text{pos}}(x) W(x, t) \, dx dt \end{aligned} \quad (\text{WAE})$$

Thus, we have the (AE)

$$\begin{cases} \rho c \dot{W}(x, t) = -\nabla \cdot (k(x) \nabla W(x, t)) & \text{in } \Omega \times (0, t_F) \\ -k(x) \partial_\nu W(x, t) = h(x) W(x, t) & \text{on } \partial\Omega \times [0, t_F] \\ W(x, t_F) = -\frac{\gamma}{\rho c} (T(x, t_F) - T_{\text{fin}}(x)) \end{cases} \quad (\text{SE})$$

and the gradient

$$\nabla e(Q_t) = p^2(t) Q_t(t) \int_{\Omega} Q_{\text{pos}}^2(x) dx + \int_{\Omega} Q_{\text{pos}}(x) W(x, t) dx$$

6 Projection Property

Theorem 1. *Let V be a linear space (=vector space), $M \subseteq V$ a closed convex set, $f : V \rightarrow \mathbb{R}$ a strictly convex function and consider the unconstrained and constraint minimisation problems*

$$\min_{x \in V} f(x) \quad \text{and} \quad \min_{x \in M} f(x).$$

Then each problem has at most one solution and if the unconstrained problem has a solution $x_V \in \text{argmin}_{x \in V} f(x)$ then the projection $\pi(x_V)$ is the solution to the constrained problem.

Proof. (i) Since M is arbitrary, proving that the constrained problem has at most one solution proves the claim also for the other case by setting $M = V$. Assuming there are two solution $x^1, x^2 \in M$, then $(x^1, x^2) \subseteq M$ by convexity of M and for every $x \in (x^1, x^2)$ by strict convexity of f it is $f(x) < \lambda f(x^1) + (1 - \lambda) f(x^2) = 1 \cdot \min_{y \in M} f(y)$, contradicting the minimality of x^1, x^2 .

(ii) Assume the minimum over M , denoted by x_M , would not be the projection. Then $f(x_V) < f(\pi(x_V))$, $f(x_V) < f(x_M)$ by (i) and $f(x_M) < f(\pi(x_V))$ and thus $f(x_V) < f(x_M) < f(\pi(x_V))$. x_M has to be in the boundary of M , otherwise we could as in (i) go a little bit into direction of x_V (better: the direction is $x_V - x_M$) and have smaller values. Connecting any two points on the triangle $T = \text{span}\{x_V, x_M, \pi(x_V)\}$ we thus get $f(x) < f(\pi(x_V))$ for every $x \in T \setminus \{\pi(x_V)\}$ $\square$

7 Remark: minimal time interval

If we consider the system without the boundary term, so without heat loss to the outside, then in order to be able to achieve an end temperature close to T_{fin} we need enough time, precisely

$$t = \frac{|\Omega|}{|Q_{\text{ad}}|} \frac{T_{\text{fin}} - T_{\text{ini}}}{\max Q}$$

much time, which corresponds to heating the room in average to the final temperature using maximum output all the time.

For small time intervalls we either get a bigger error in the corresponding term of the energy or need a big $\max Q$. Looking at the Theta-method with Y_n being any solution (of SE or AE) for only a given time t_n the next solution for t_{n+1} with the help of the right hand side extracted by looking at the time change of the system will be

$$Y_{n+1} = Y_n + \Delta t (\theta F(t_n, Y_n) + (1 - \theta) F(t_{n+1}, Y_{n+1}))$$

which gets solved by the Newton method iterating over k

$$Y_{n+1}^{k+1} = Y_{n+1}^k - \left(G'(Y_{n+1}^k) \right)^{-1} G(Y_{n+1}^k)$$

where

$$G(Y) = Y - \Delta t (\theta F(t_n, Y_n) + (1 - \theta) F(t_{n+1}, Y)) - Y_n, \quad G'(Y) = I - (1 - \theta) \Delta t \partial_Y F(t_{n+1}, Y)$$

8 Adjoint

Theorem 2. *The Adjoint solution operator from version 2 satisfies*

$$\langle S^*(T - T_{\text{fin}}), h \rangle = \langle T - T_{\text{fin}}, S(h) \rangle$$

Proof. We remind about the weak forms (WSE) with test function W and (WAE) (from L_T before using Green) with test function T

$$\int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) dx dt = \int_0^{t_F} \int_{\Omega} -k(x) \nabla T(x, t) \cdot \nabla W(x, t) + Q(x, t) W(x, t) dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) W(y, t) dy dt \quad (\text{WSE})$$

$$\int_0^{t_F} \int_{\Omega} \rho c \dot{T}(x, t) W(x, t) dx dt = - \int_0^{t_F} \int_{\Omega} k(x) \nabla T(x, t) \cdot \nabla W(x, t) dx dt - \gamma \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) T(x, t_F) dx - \int_0^{t_F} \int_{\partial\Omega} h(y) W(y, t) T(y, t) dy dt \quad (\text{WAE})$$

Subtracting (WAE) from (WSE) we get

$$0 = \int_0^{t_F} \int_{\Omega} Q(x, t) W(x, t) \, dx dt + \int_0^{t_F} \int_{\partial\Omega} h(y) T_{\text{out}}(y) W(y, t) \, dy dt + \gamma \int_{\Omega} (T(x, t_F) - T_{\text{fin}}(x)) T(x, t_F) \, dx$$

With these it is

$$\begin{aligned} \langle W, S(Q) \rangle &= \int_0^{t_F} \int_{\Omega} W(x, t) T(x, t) \, dx dt \\ &= \int_0^{t_F} \int_{\Omega} W(x, t) \left(T_{\text{ini}}(x) + \int_0^t \dot{T}(x, s) \, ds \right) \, dx dt \\ &= \int_0^{t_F} \int_{\Omega} W(x, t) T_{\text{ini}}(x) + \int_0^t \dot{T}(x, s) W(x, t) \, ds \, dx dt \\ &= \int_0^{t_F} \int_{\Omega} W(x, t) T_{\text{ini}}(x) + \int_0^t \dot{T}(x, s) W(x, t) \, ds \, dx dt \\ &= \end{aligned}$$

□

In general it looks like this

Theorem 3. *Assume the problem is*

where N contains only linear Terms of Q and T .

Proof. The Lagrangian is

$$L(Q, T, W) = E(Q, T) + W N(Q, T)$$

and the adjoint equation is

$$L_T(Q, T, W)h = E_T(Q, T) + W N_T(Q, T)h$$

□

9 Pontryagin's minimum (maximum) principle

See [14]. We can also get the optimal adjoint by Pontryagin's minimum principle, which may be used here to even out some holes in our argumentation. We assume version 2.

Theorem 4 (Pontryagin's minimum principle (version [14])). *Consider the problem*

$$\begin{aligned} \min_{q \in Q} \Phi(y(t_f)) + \int_0^{t_f} F(y(t), q(t)) \, dt \\ \dot{y} = f(y(t), q(t)), \quad y(0) = y_0 \end{aligned}$$

Let the Hamiltonian be given by $H(q, y, p, t) = F(y(t), q(t)) + p(t)f(y(t), q(t))$. Then the optimal adjoint solves

$$\dot{p} = H_y \quad p(t_f) = \Phi_y(y(t_f))$$

Identifying the functions for our problem and using $y = T$, $q = Q$, $p = W$ we get (notice that here we write everything in the strong version)

$$\begin{aligned}\Phi(T(t_f)) &= \int_{\Omega} (T(x, t_f) - T_{\text{fin}}(x))^2 \, dx \\ F(T(t), Q(t)) &= \int_{\Omega} (pQ)^2 \, dx \\ f(T(t), Q(t)) &= \frac{1}{\rho c} (\nabla \cdot (k(x) \nabla T(x, t)) + Q(x, t)) \\ H(Q, T, W, t) &= \int_{\Omega} (pQ)^2 \, dx - \int_0^{t_F} \int_{\Omega} k(x) \nabla T(x, t) \cdot \nabla W(x, t) - Q(x, t) W(x, t) \, dx dt - \int_0^{t_F} \int_{\partial\Omega} h(y) (T(y, t) - T_{\text{out}}(y)) W(y, t) \, dy dt\end{aligned}$$

and thus the adjoint satisfies

$$\dot{W}(x, t)h =$$

10 Other

- Remember the Courant-Friedrichs-Lewy (CFL) condition: If the numerical solution is screwed up it might be because space step length / time step length is too small. Honestly, I do not know the specific condition for that problem, it might even be reversed here, but this should be considered.
- Galerkin method or Ritz method - mention them and I think we use Galerkin
- Pontryagin's maximum principle??? Gives the adjoint of a system like ours, but it might be hard to transform

11 Remarks Henning

[22] Introduction/motivation when saying the problem has been studied by others, conclusion when saying what other models can be studied (they study a 3D model with radiation term and consider a Navier-Stokes model)
Either for the adjoint or the Variation you could state that this is the sensitivity of E with respect to T.
Heat conduction in room/problem statement and justification: [10]
Gridap citing or when talking about software: [2] [26]
Pontryafin's minimum principle, a direct solution method [25]
[23] Introduction/motivation when saying the problem has been studied by others, model, conclusion when talking about other models
[20] other numerical methods
[17] weak formulation, numerical method (discretisation, semi-discretisation, FE method), when saying that we use a direct method, other methods (IPOPT), Lagrangian
[15] model (chapter 6), parameters, in conclusion when talking about other models, FE, Lagrangian, Rayleigh-Ritz + Galerkin
[14] model, Lagrangian, Variation of Lagrangian, numerical method with gradient
[13] model (esp chapter 5), parameters, conclusion other models (include radiation, Stefan-Boltzmann constant)
[12] other numerical method, slightly other model including solar transfer
[11] unique solution of quadratic problem, numerical solution has error in $O(h^2)$ using discretisation and weak form, our gradient method, active set method
[10] model, analytical solution
[9] extended problem for multiple flats, simplex method like
[8] model, error bound in equation (1.4), weak form, adjoint, regularity of solution, FE
[7] model, FE
[6] model + advanced nonlinear model (for conclusion), finite difference method
[5] for everything about PDEs (sobolev spaces, weak formulationheat equation, solution theorem)
[4] model, Pontryagin's minimum principle,, Lagrangian (or here: Hamiltonian), indirect method
[3] general convex optimisation theory, spaces, projection
[1] sobolev spaces, differentiability ... general stuff
[19] Variational analysis (weak formulation is good), differentiation in banach spaces, optimisation with variation

- [18] adjoint operator, generalised differentiability, Pontryagin’s maximum principle (chap 9.6), semi-discretised problem (here: solve dynamical systems after that)
- [24] Tröltzsch ... you know whats in there (this is the german version)
- [16] variational analysis (weak formulation is good), fundamental theorem of variational analysis, general optimal control, minimum principle
- [17] model, weak formulation, FE, Lagrangian
- [21] general problems, Lagrangian, good choices for gamma (page 196 ff.), optimality conditions

References

- [1] Hans Wilhelm Alt. *Linear Functional Analysis*. Universitext. London: Springer, 2016. ISBN: 978-1-4471-7279-6 978-1-4471-7280-2. DOI: 10.1007/978-1-4471-7280-2. URL: <http://link.springer.com/10.1007/978-1-4471-7280-2> (visited on 04/17/2025).
- [2] Santiago Badia and Francesc Verdugo. “Gridap: An extensible Finite Element toolbox in Julia”. In: *Journal of Open Source Software* 5.52 (Aug. 2020), p. 2520. ISSN: 2475-9066. DOI: 10.21105/joss.02520. URL: <https://joss.theoj.org/papers/10.21105/joss.02520> (visited on 04/26/2025).
- [3] Heinz H. Bauschke and Patrick L. Combettes. *Convex Analysis and Monotone Operator Theory in Hilbert Spaces*. CMS Books in Mathematics. Cham: Springer International Publishing, 2017. ISBN: 978-3-319-48310-8 978-3-319-48311-5. DOI: 10.1007/978-3-319-48311-5. URL: <https://link.springer.com/10.1007/978-3-319-48311-5> (visited on 03/26/2025).
- [4] Francesco Biral, Enrico Bertolazzi, and Paolo Bosetti. “Notes on Numerical Methods for Solving Optimal Control Problems”. In: *IEEEJ Journal of Industry Applications* 5.2 (2016), pp. 154–166. ISSN: 2187-1094, 2187-1108. DOI: 10.1541/ieejjia.5.154. URL: https://www.jstage.jst.go.jp/article/ieejjia/5/2/5_154/_article (visited on 03/31/2025).
- [5] Lawrence C. Evans. *Partial differential equations*. 2nd ed. Graduate studies in mathematics v. 19. Providence, R.I: American Mathematical Society, 2010. ISBN: 978-0-8218-4974-3.
- [6] Stefan M. Filipov et al. “A Coupled PDE-ODE Model for Nonlinear Transient Heat Transfer with Convection Heating at the Boundary: Numerical Solution by Implicit Time Discretization and Sequential Decoupling”. In: *Axioms* 12.4 (Apr. 2023), p. 323. ISSN: 2075-1680. DOI: 10.3390/axioms12040323. URL: <https://www.mdpi.com/2075-1680/12/4/323> (visited on 02/23/2025).
- [7] Mark Gockenbach and Kristin Schmidtke. “Newton’s law of heating and the heat equation”. In: *Involve, a Journal of Mathematics* 2.4 (Oct. 2009), pp. 419–437. ISSN: 1944-4176. DOI: 10.2140/involve.2009.2.419. URL: <http://msp.org/involve/2009/2-4/p05.xhtml> (visited on 04/09/2025).
- [8] Wei Gong, Michael Hinze, and Zhaojie Zhou. *A finite element method for Dirichlet boundary control problems governed by parabolic PDEs*. Oct. 2014. DOI: 10.48550/arXiv.1410.0136. arXiv: 1410.0136 [math]. URL: <http://arxiv.org/abs/1410.0136> (visited on 04/23/2025).
- [9] Stig-Inge Gustafsson and Mikael Rönqvist. “Optimal heating of large block of flats”. In: *Energy and Buildings* 40.9 (Jan. 2008), pp. 1699–1708. ISSN: 03787788. DOI: 10.1016/j.enbuild.2008.02.027. URL: <https://linkinghub.elsevier.com/retrieve/pii/S0378778808000595> (visited on 02/19/2025).
- [10] David W. Hahn and M. Necati Özşık. *Heat conduction*. 3rd ed. Hoboken, N.J: Wiley, 2012. ISBN: 978-0-470-90293-6.
- [11] M. Hinze. “A Variational Discretization Concept in Control Constrained Optimization: The Linear-Quadratic Case”. In: *Computational Optimization and Applications* 30.1 (Jan. 2005), pp. 45–61. ISSN: 0926-6003, 1573-2894. DOI: 10.1007/s10589-005-4559-5. URL: <http://link.springer.com/10.1007/s10589-005-4559-5> (visited on 04/23/2025).
- [12] Chenzi Huang et al. “Energy Optimal Control of a Multivalent Building Energy System using Machine Learning.” in: *Proceedings of the 10th International Conference on Smart Cities and Green ICT Systems*. Online Streaming, — Select a Country —: SCITEPRESS - Science and Technology Publications, 2021, pp. 57–66. ISBN: 978-989-758-512-8. DOI: 10.5220/0010478500570066. URL: <https://www.scitepress.org/DigitalLibrary/Link.aspx?doi=10.5220/0010478500570066> (visited on 02/18/2025).
- [13] Frank P. Incropera et al., eds. *Fundamentals of heat and mass transfer*. 6th ed. Hoboken, NJ: John Wiley, 2007. ISBN: 978-0-471-45728-2.
- [14] Peter Jaksch. “Implementation of an adjoint thermal solver for inverse problems”. In: *European Conference on Turbomachinery Fluid Dynamics and hermodynamics*. Stockholm, Sweden, 2017. DOI: 10.29008/ETC2017-336. URL: <http://www.euroturbo.eu/publications/proceedings-papers/ETC2017-336/> (visited on 04/06/2025).
- [15] Roland W. Lewis, Perumal Nithiarasu, and Kankanhalli N. Seetharamu. *Fundamentals of the Finite Element Method for Heat and Fluid Flow*. 1st ed. Wiley, Apr. 2004. ISBN: 978-0-470-84788-6 978-0-470-01416-5. DOI: 10.1002/0470014164. URL: <https://onlinelibrary.wiley.com/doi/book/10.1002/0470014164> (visited on 04/12/2025).
- [16] Daniel Liberzon. *Calculus of Variations and Optimal Control Theory: A Concise Introduction*. 1st ed. Princeton: Princeton University Press, 2012. ISBN: 978-0-691-15187-8 978-1-4008-4264-3.
- [17] Florian Loos. “Eine direkte Methode für Optimalsteuerungsprobleme mit parabolischen Differentialgleichungen”. PhD thesis. URL: <https://www.yumpu.com/de/document/read/21659314/eine-direkte-methode-fur-optimalsteuerungsprobleme-universitat> (visited on 04/01/2025).
- [18] David Gilbert Luenberger. *Optimization by Vector Space Methods*. Professional Series. John Wiley & Sons Inc, 1969.
- [19] Boris S. Mordukhovich. *Variational Analysis and Generalized Differentiation I*. Vol. 330. Grundlehren der mathematischen Wissenschaften. Berlin, Heidelberg: Springer, 2006. ISBN: 978-3-540-25437-9 978-3-540-31247-5. DOI: 10.1007/3-540-31247-1. URL: <http://link.springer.com/10.1007/3-540-31247-1> (visited on 07/03/2023).
- [20] Joshua L. Pulsipher et al. “A Unifying Modeling Abstraction for Infinite-Dimensional Optimization”. In: *Computers & Chemical Engineering* 156 (Jan. 2022), p. 107567. ISSN: 00981354. DOI: 10.1016/j.compchemeng.2021.107567. arXiv: 2106.12689 [math]. URL: <http://arxiv.org/abs/2106.12689> (visited on 03/31/2025).
- [21] Robert F. Stengel. *Optimal Control and Estimation*. New York: Dover Publications, 1994. ISBN: 978-1-62198-652-2.
- [22] Mounir Tabarki and Slah Ben Mabrouk. “Modeling and Eperimentation of Heat Exchanges in a Room Heated by Radiator”. In: *Journal of Thermophysics and Heat Transfer* 26.1 (Jan. 2012), pp. 161–171. ISSN: 0887-8722, 1533-6808. DOI: 10.2514/1.T3696. URL: <https://arc.aiaa.org/doi/10.2514/1.T3696> (visited on 04/11/2025).
- [23] Siri Hofstad Trapnes. “Optimal Temperature Control of Rooms”. In: ().
- [24] Fredi Tröltzsch. *Optimale Steuerung partieller Differentialgleichungen: Theorie, Verfahren und Anwendungen*. 2., überarbeitete Auflage. SpringerLink Bücher. Wiesbaden: Vieweg+Teubner, 2009. ISBN: 978-3-8348-0885-1 978-3-8348-9357-4. DOI: 10.1007/978-3-8348-9357-4.
- [25] Thijs Van Keulen. “Indirect solution for optimal control problems with a pure state constraint”. In: *IFAC Proceedings Volumes* 47.3 (2014), pp. 2456–2461. ISSN: 14746670. DOI: 10.3182/20140824-6-ZA-1003.01626. URL: <https://linkinghub.elsevier.com/retrieve/pii/S1474667016419786> (visited on 04/04/2025).
- [26] Francesc Verdugo and Santiago Badia. “The software design of Gridap: A Finite Element package based on the Julia JIT compiler”. In: *Computer Physics Communications* 276 (July 2022), p. 108341. ISSN: 0010-4655. DOI: 10.1016/j.cpc.2022.108341. URL: <https://www.sciencedirect.com/science/article/pii/S0010465522000595> (visited on 04/26/2025).