

Afrimoney Integration Document

Document version : 4.0

Contents

1. Document Information	4
1.1. Purpose	4
1.2. Scope	4
1.3. Audience	4
1.4. Definitions and Acronyms	4
2. Document History	4
3. Introduction	4
3.1. Prerequisites to follow before starting integration testing	4
3.2. Generate authentication token	5
3.2.1. Functional description	5
3.2.2. API definition	5
3.2.3. Sample	6
4. User Interface	6
4.1. Merchant balance enquiry	6
4.1.1. Functional description	6
4.1.2. API definition	6
4.1.3. Sample	8
4.2. Merchant payment (Merchant initiated)	9
4.2.1. Functional description	9
4.2.2. API definition	10
4.2.3. Sample	12
4.3. Transaction status enquiry using external transaction ID	13
4.3.1. Function description	13
4.3.2. API definition	13
4.3.3. Sample	14
4.4. Transaction status enquiry using Afrimoney transaction ID	16
4.4.1. Function description	16
4.4.2. API definition	16
4.4.3. Sample	18
4.5. Merchant payment call-back	19
4.5.1. Function description	19
4.5.2. API definition	19
4.5.3. Sample	20

4.6. Subscriber information enquiry	20
4.6.1. Function description	20
4.6.2. API definition	20
4.6.3. Sample	22
4.7. CASHIN	23
4.7.1. Function description	23
4.7.2. API definition	24
4.7.3. Sample	25

1. Document Information

This chapter gives an introduction to the scope and organization of the document.

1.1. Purpose

The objective of this document is to describe the APIs being called between different interface and Mobiquity and to provide the Request and Response messages which will be used by ex-entity to use Mobiquity services. Along with this all pre-requisites are also mentioned which needs to be taken care before SIT.

1.2. Scope

The scope of this document is for Mobiquity core. This document covers the Messages to integrate interfaces and Mobiquity system.

1.3. Audience

technical Teams

1.4. Definitions and Acronyms

This section provides a list of all definitions, acronyms and terms required to properly interpret the document.

2. Document History

Version	Description of Changes	Date	Author
1.0	Initial document: Integration with Africell	2021-01-19	Anshika Aggarwal
2.0	Updated for Call back sample request	2021-01-20	Pankaj Jain
3.0	Added User Enquiry and Balance Enquiry API	2021-03-03	Anshika Aggarwal
4.0		2021-09-27	Nathan Delma

3. Introduction

3.1. Prerequisites to follow before starting integration testing

The third party will provide:

1. The company name
2. The filled VPN form for the network configuration
3. Optionally the test and production call-back URLs for the merchant service

Afrimoney will provide

1. mobile number of the account created for the integration,
2. the PIN of the created account,
3. the API client key
4. the API client secret

3.2. Generate authentication token

3.2.1. Functional description

In order to authenticate you need to prepare an authentication header from the provided API client key and the API client secret. The generated token must be used in the header of APIs for authentication. The APIs require HTTP basic authentication.

3.2.2. API definition

Request

URL	https://10.14.10.163:8280/token
Method	POST
Header	Content-Type: application/x-www-form-urlencoded
Header	Authorization: Basic <Base64-encoded-client_key:client_secret>

Response

Tag	Fields	Example	Max Length	Optional/Mandatory	Remarks
access_token		4cb5783550b0-3fa08e87ecb319184f0b		M	Response Type
scope		am_application_scope default		M	Transaction ID of the request performed
token_type		Bearer		M	
expires_in		120		M	

3.2.3. Sample

request

```
curl -k -d "grant_type=client_credentials" -H "Authorization: Basic
aUhzMUG2dENuUDVuUmVuamtod3NaX1R1N1JRYTpjY1FZQXB5TWNUYUtpZkdTU2RfcIVEUE00Y2dh"
H "Content-Type: application/x-www-form-urlencoded" https://10.14.10.163:8243/token -v
```

Response

```
{"access_token":"4cb57835-50b0-3fa0-8e87-ecb319184f0b","scope":"am_application_scope
default","token_type":"Bearer","expires_in":9223372036854775}-
```

4. User Interface

4.1. Merchant balance enquiry

4.1.1. Functional description

Third Party Merchant can view his current wallet balance through this API.

4.1.2. API definition

Request

URL	http://10.14.10.163:8280/UserInfoJ/1.0
Method	POST
Header	Content-Type: application/json
Header	Authorization: Bearer <authorization_token>

Tag	Fields	Example	Max Length	Optional/ Mandatory	Remarks
Type	RBEREQ	RBEREQ	10	M	Request type
MSISDN	<Sender MSISDN>	9942222	15	M	All MSISDN should be without country code.
PROVIDER	< PROVIDER>	101		M	Provider id of topup operator
PAYID	< PAY ID>	12		M	

MPIN	<Sender MPIN>	1234	4	M	MPIN is a login pin which can be different or same for different group of bearers. e.g USSD/WEB bearers share one MPIN and STK/J2ME bearers share another MPIN.
PIN	<Sender PIN>	3946	4	O	System preference is to control whether tPin is required or not. This pin is required when credit/debit or service charge is levied. mPin & tPin can be same/different based on another preference. Numeric Only.
LANGUAGE1	<Sender Language>	1	1	O (Tag is mandatory)	Numeric only Payer Language Code This code must be defined in Mobiquity system.
CELLID	<CELLID>	Cellid1234	15	O	Cell Id is coming from third party (TAG IS OPTIONAL)
FTXNID	<FTXNID>	FTXNID	15	O	FTXNID is coming from third party (TAG IS OPTIONAL)
BLOCKSMS	<BLOCKSMS>	PAYER	5	O	Value can be one of these -> PAYER, PAYEE, BOTH

Response

Tag	Fields	Example	Max Length	Optional/Mandatory	Remarks
TYPE	RBERESP	RBERESP	10	M	Response Type
TXNID	<Transaction Id>	XX121126.18 21.C00002	20	M	Transaction ID of the request performed
TXNSTATUS	<Transaction Status>	200	5	M	Transaction Status i.e. Transaction OK (200), Failed and Other status
BALANCE	Mobiquity Account Balance	100	10	M	Numeric only
FRBALANCE	Frozen balance (Occupied in some pending transactions)	10	10	M	Numeric only
FICBALANCE	Fund in clearance balance.	10	10	M	Numeric only
OTHERWALLETS	Other wallets such as Remittance or Commission. This is displayed when IS_COMMISSION_WALLET_REQUIRED is true or IS_REMITTANCE_WAL	NA	NA	O	NA

	LET_REQUIRED is true.				
WALLETNAME	Wallet name can be remittance or commission	10	10	O	Remittance or Commission
BALANCE	Balance of the WALLETNAME.	10	10	0	Numeric only
FBALANCE	Frozen balance of the WALLETNAME.	10	10	0	Numeric only
<TRID>	<transfer ID>			M	
IVR-RESPONSE	IVR-RESPONSE	1107#1946 #		M	IVR-RESPONSE Code

4.1.3. Sample

Request curl --location --request POST 'http://10.14.10.163:8280/UserInfoJ/1.0'

```
\
--header 'Authorization: Bearer 4cb57835-50b0-3fa0-8e87-ecb319184f0b' \
--header 'Content-Type: application/json' \
--data-raw '{"COMMAND":{
  "TYPE": "RBEREQ",
  "MSISDN": "080317441",
  "PROVIDER": "101",
  "PAYID": "12",
  "MPIN": "1234",
  "LANGUAGE1": "1"
}}'
```

Response

```
{
  "COMMAND": {
    "PAYER_MLIMITCUST": "999999999900",
    "PAYER_DLIMITCUST": "999999999900",
    "FICBALANCE": "0.00",
    "TXNID": "RB210611.1212.C10043",
    "BALANCE": "0.00",
    "IVR-RESPONSE": "1107#0.00#",
    "MESSAGE": "Success",
    "PAYEE_DLIMITCUST": "999999999900",
    "USERTYPE": "CHANNEL",
    "OTHERWALLETS": {
      "FBALANCE": "0.00",
```

```
"WALLETNAME": "Commission",  
"BALANCE": "0.00"  
},  
"FRBALANCE": "0.00",  
"TYPE": "RBERESP",  
"PAYEE_MLIMITCUST": "999999999900",  
"TXNSTATUS": "200",  
"TRID": "033200219202106111212C0025"  
}  
}
```

4.2. Merchant payment (Merchant initiated)

4.2.1. Functional description

Afrimoney exposes its merchant payment API for external merchants. External merchant should consume Mobiquity API and send the request with all mandatory information to Mobiquity. Based on received request, Mobiquity would execute the payment and send back response to the external merchant.

Customer here can be a subscriber or channel user.

The merchant gets registered in the Mobiquity system through channel user management module. Once registered in Mobiquity, every merchant is assigned a wallet where it would receive the payment credits.

Process Flow

Customer will go to e-commerce portal to buy goods / services

At the checkout page, there will be a payment option "pay with Afrimoney"

The customer will then enter his mobile number in the ecommerce portal

The ecommerce portal (which will be registered as a merchant in Mobiquity) will initiate "merchant Payment" API by passing its mobile number / agent code in the request as transactor and the subscriber / channel user's mobile number as the sender, and the initiator will be the transactor

This merchant payment will be 2 step, where Mobiquity will pause the txn for 2nd party approval and send a SMS to the subscriber / channel user asking for his confirmation.

This in Async flow, in the sense Mobiquity will send a response to the calling ecommerce system that it successfully received the payment request and is processing it.

The subscriber will then accept / reject the merchant payment request from USSD / mobile app.

Any transaction which does not get a confirmation within x minutes (Configurable) should time out and be marked as a failed transaction

Mobiquity will process the transaction and send a notification to the callback url exposed by the ecommerce portal whether txn was accepted or rejected by the user and whether it was successfully processed by Mobiquity.

The merchant can check the status of an initiated payment from the transaction enquiry APIs

4.2.2. API definition

Request

URL	http://10.14.10.163:8280/MerchantPayment/1.0
Method	POST
Header	Content-Type: application/json
Header	Authorization: Bearer <authorization_token>

Tag	SubTag	Fields	Example	Max Length	Optional/Mandatory	Remarks
serviceCode		serviceCode	MERCHPAY	10	O	Request Type
bearerCode		bearerCode	USSD	15	M	Mode at which transaction happens
language		language	en		O	If language value is specified response will be in that particular language, If the input does not contain the language - the we use system default language to respond
initiator		initiator	transactor		M	Initiator is who initiated the transaction

transaction Amount		transactionAmount	100	10	M	Numeric Only. Should accept
language		language	en			Language
currency		currency	101		M	Type of currency accepted in transaction
externalReferenceId		externalReferenceId	EXT1234		O	External ReferenceID
remarks		remarks	CashIn		O	Remarks of service
transactor	idType	idType	mobileNumber	1	M	Id type of transactor(mobileNumber,loginId,userCode)
transactor	idValue	idValue	7701536457	16	M	Id value is the value of id Type
transactor	productId	productId	12		M	Type of wallet of transactor
transactor	mpin	mpin	1357	4	M	Numeric Only. MPIN is a login pin which can be different or same for different group of bearers. e.g USSD/WEB bearers share one MPIN and STK/J2ME bearers share another MPIN.
sender	idType	idType	mobileNumber		M	Id Type of sender(mobileNumber,loginId)
sender	idValue	idValue	7700995695		M	Id value
sender	productId	productId	12		M	Type of wallet of receiver

Response

Tag	Sub Tag	Fields	Example	Max Length	Optional/ Mandatory	Remarks
serviceRequestId		serviceRequestId	0f7986b9-cde3-43eeb307-74c4ccedc8f7	255	M	Uniquely determines service flow
serviceFlow		serviceFlow	MERCHPAY	255	M	Service code of response

message		message	Merchant Payment transaction of RUB 6 has been successfully completed between the sender: 7700032323 and receiver: 7700032323. Txn ID: MP161109.0355.A000 07		M	Response Details
transaction Status		transactionStatus	TI	255	M	Transaction status , successfully initiated on TI
transaction Id		transactionId	MP161109.0355.A00 007		M	Mobiquity Transaction ID for the Bill Payment Transaction. Used for informative purpose.
status		status	Paused		M	Status, Paused : successfully initiated and is waiting for confirmation

4.2.3. Sample

Request curl --location --request POST

```
'http://10.14.10.163:8280/MerchantPayment/1.0' \
--header 'Authorization: Bearer 46391608-d7c5-32a4-8f6c-938792cd84ee' \
--header 'Content-Type: application/json' \
--data '{
  "serviceCode": "MERCHPAY",
  "transactionAmount": "1000",
  "initiator": "transactor",
  "currency": "101",
  "bearerCode": "WEBSERVICE",
  "language": "en",
  "externalReferenceId": "EXT323532",
  "remarks": "Range rover",
  "transactor": {
    "idType": "mobileNumber",
    "productId": "12",
    "idValue": "033200223",
    "mpin": "1234"
  },
  "sender": {
    "idType": "mobileNumber",
```

```

"productId": "12",
"idValue": "077928289"
}
}
'Response
{
"receiverLastName": "Bet",
"senderMobileNumber": "077928289",
"code": "second.party.authentication.required",
"serviceRequestId": "a27fe964-aaf5-4fa1-a353-d882c9423e78",
"transactionReference": "MP210916.1740.15297",
"transactionStatus": "TI",
"mfsTenantId": "mfsPrimaryTenant",
"descriptionText": "Range rover",
"serviceFlow": "MERCHPAY",
"message": "Your transaction request has been initiated, and is now pending
confirmation",
"type": "MERCHPAY",
"transactionId": "MP210916.1740.15297",
"originalServiceRequestId": "a27fe964-aaf5-4fa1-a353-d882c9423e78",
"externalReferenceId": "EXT323532",
"txnStatus": "TI",
"receiverMobileNumber": "033200223",
"currency": "101",
"originalTransactionReference": "EXT323532",
"senderLastName": "Delma",
"remarks": "Range rover",
"status": "PAUSED"
}

```

4.3. Transaction status enquiry using external transaction ID

4.3.1. Function description

This API is used to get the status of the transaction based on the third party Txn ID of the original transaction.

4.3.2. API definition

Request

URL	http://10.14.10.163:8280/UserInfo/1.0
Method	POST
Header	Content-Type: application/json
Header	Authorization: Bearer <authorization_token>

Tag	Fields	Example	Max Length	O/M	Remarks
TYPE	FTXENQ	FTXENQ	10	M	Request Type

FTXNID	FTXNID of original Transaction which is enquired	Dsfsd2342343	Alphanumeric (20)	M	FTXNID of original Transaction which is enquired
MERCHANTCODE	Agent code of the channel user	4	15	O	Is mandatory when SYSTEM tag value is not a "WALLET".
USERTYPE	User type as Payer or Payee	PAYER/PAYEE	NA	O	Is mandatory when SYSTEM tag value is not a "WALLET".
SYSTEM	The system who is invoking the API	MERCHANT/WALLET	NA	M	The system who is invoking the API, like MERCHANT/WALLET

Response

Tag	Fields	Example	Max Length	O/M	Remarks
TYPE	FTXNENQRESP	FTXNENQRESP	10	M	Response Type
TXNID	Transaction ID	FE151005.1525.C00002	25	M	Transaction ID generated for transaction.
TXNSTATUS	Transaction Status	200	6	M	Various transaction status Failed, Under process etc
MESSAGE	Response Message	SUCCESS	100	M	Response message corresponding to Transaction Status
STATUSCODE	Status code of the transaction enquired	TS, TF, TA, TPI, TIP, TI		M	Transfer ID
STATUSVALUE	Status value of the transaction enquired	SUCCESS, FAILED, IN PROGRESS		M	Transaction ID generated for transaction.
TRANSID	Transaction ID	DW151221.1745.C00001	25	M	Transaction ID of original transaction
FTXNID	FTXNID	Jsdnfw12131	30	M	FTXNID of original transaction
TRID	Transfer ID	201509161308C0010	20	M	Transfer ID

4.3.3. Sample

Request curl --location --request POST 'http://10.14.10.163:8280/UserInfo/1.0' \

```
--header 'Authorization: Bearer 4cb57835-50b0-3fa0-8e87-ecb319184f0b' \
--header 'Content-Type: application/json' \ --data-raw '{"COMMAND":
{
  "TYPE": "FTXNENQ",
  "FTXNID": "EXT323532"
}}'
```

Response

```
{
  "COMMAND": {
    "REFTXNSTATE": "TF",
    "TXNMODE": "",
    "REFTXNSTATUS": "cancel.transaction.timeout",
    "TXNID": "TI210611.1158.C10033",
    "TXNAMT": "1000.0",
    "MESSAGE": "Success",
    "REFMESSAGE": "",
    "TXNDATE": "30/03/2021",
    "REFERENCEID": "MP210323.2217.20460",
    "SERVICE": "MERCHPAY",
    "TYPE": "TRANSRESP",
    "STRUCT": [
      {
        "COMM_PAYER_PAID": "0",
        "PROVIDER1": "101",
        "DATA": "SENDER",
        "USERTYPE": "SUBSCRIBER",
        "FROM": "077928289",
        "TAX_PAYER_PAID": "",
        "BALBFTRANS1": "0",
        "BALAFTRANS1": "0",
        "FEES_PAYER_PAID": "0",
        "PAYID1": "12",
        "COMM_PAYER_REC": "0",
        "NAME": "SUBS SUBS"
      },
      {
        "BALAFTRANS": "0",
        "FEES_PAYEE_PAID": "0",
        "COMM_PAYEE_REC": "0",
        "PAYID": "12",
        "BALBFTRANS": "1000.0",
        "COMM_PAYEE_PAID": "0",
        "CHANNEL_CODE": "59301",
        "NAME": "startimes tv",
        "DATA": "RECEIVER",
        "TAX_PAYEE_PAID": "",
        "USERTYPE": "CHANNEL",
        "PROVIDER": "101",
        "TO": "033200203"
      }
    ],
    "TXNSTATUS": "200",
    "TRID": "202106111158C0020",
    "TXNTIME": "11:13"
  }
}
```

4.4. Transaction status enquiry using Afrimoney transaction ID

4.4.1. Function description

This API is used to get the status of the transaction based on the Afrimoney Txn ID.

4.4.2. API definition

Request

URL	http://10.14.10.163:8280/UserInfo/1.0
Method	POST
Header	Content-Type: application/json
Header	Authorization: Bearer <authorization_token>

Fields	Description	Example	Mandatory (M)/Optional (O)/Tag Mandatory Only (T)	Type of Input & Max Length
TYPE	Request Type of the service.	TRANSREQ	M	Alphabetical (10)
REFERENCEID	Transaction ID for the transaction	CO121313.1 121.C00002	M	Alphanumeric (20)

Response

Fields	Description	Example	Mandatory (M)/Optional (O)	Type of Input & Max Length
TYPE	Response Type of the service.	CLTRESP	M	Alphabetical (10)
TXNID	Transaction ID for the transaction	TH121313.11 21.C00002	M	Alphanumeric (20)
REFERENCEID	Transaction ID of the Original Transaction	CO121313.1 121.C00002	M	Alphanumeric (20)
REFTXNSTATUS	Transaction Status of Original transaction	200	M	Numeric (10)
REFMESSAGE	Message displayed in original transaction	Success	M	Alphanumeric (600)
TXNSTATUS	Status of the request	200	M	Numeric (10)

TRID	TRID (Tango Request ID) is used as a unique identification number for each request defined as MSISDN DATE HOUR MIN Internal ID of request	7711223355 2011102010 15C0003	M	Alphanumeric (Max MSISDN Length as per system preferences + 17)
PROVIDER	Provider ID	101	M	Numeric (3)
MESSAGE	Details for the transactions of the subscriber	Success	M	Alphanumeric (600)
TXNAMT	Amount of the transaction	10	M	Numeric (19)
TXNDATE	Transaction date	41710	M	Numeric (As per system preference)
TXNTIME	Transaction Time	0,3958333333	M	HH:mm (24 HR format)
STRUCT	Holds the details of Sender of the enquiry is done	NA	M	NA
DATA	Holds type of user for which enquiry is done	Sender	M	Alphabetic (9)
USERTYPE	It is the type of user for which enquiry is being done CHANNEL SUBSCRIBER	CHANNEL	M	Alphabetic (9)
SERVICE	Service type of the transaction	CASHIN	M	Alphabetical (20)
FROM	Mobile number of the Payee	91274282	M	Numeric (As per system preference)
Fields	Description	Example	Mandatory (M)/Optional (O)	Type of Input & Max Length
	involved in the transaction			
TO	Mobile number of the Payee involved in the transaction	91274282	M	Numeric (As per system preference)
TXNTYPE	Entry type for the subscriber, i.e. whether the subscriber was a payer (DR) or payee (CR)	DR	M	Alphabetical (2)
TXNMODE	Sub Transaction type sent in the request	W2B	O	Alphanumeric (20)
PAYID	Wallet ID used for the transaction	12	M	Numeric (2)
BALBFTRANS	Balance for the Payer before transaction	100	M	Numeric (19)
BALBFTRANS1	Balance for the Payee before transaction	100	M	Numeric (19)
BALAFTRANS	Balance for the Payer after transaction	100	M	Numeric (19)

BALAFTRANS1	Balance for the Payee after transaction	100	M	Numeric (19)
FEES_PAYER_PAID	Service charge/fees paid by the payer	1	T	Numeric (19)
FEES_PAYEE_PAID	Service charge/fees paid by the payee		T	Numeric (19)
COMM_PAYER_REC	Commission received by the payer user	1	T	Numeric (19)
COMM_PAYEE_PAID	Commission paid by the payee user	1	T	Numeric (19)
COMM_PAYEE_REC	Commission received by the payee user	1	T	Numeric (19)
TAX_PAYER_PAID	Tax paid by the payer user	1	T	Numeric (19)
TAX_PAYEE_PAID	Tax paid by the payer user	1	T	Numeric (19)

4.4.3. Sample

Request curl --location --request POST 'http://10.14.10.163:8280/UserInfo/1.0'

```
\
--header 'Authorization: Bearer 4cb57835-50b0-3fa0-8e87-ecb319184f0b' \
--header 'Content-Type: application/json' \ --data-raw '{"COMMAND":
{
  "TYPE": "TRANSREQ",
  "REFERENCEID": "MP210323.2217.20460"
}}'
```

Response

```
{
  "COMMAND": {
    "REFTXNSTATE": "TF",
    "TXNMODE": "",
    "REFTXNSTATUS": "cancel.transaction.timeout",
    "TXNID": "TI210611.1158.C10033",
    "TXNAMT": "1000.0",
    "MESSAGE": "Success",
    "REFMESSAGE": "",
    "TXNDATE": "30/03/2021",
    "REFERENCEID": "MP210323.2217.20460",
    "SERVICE": "MERCHPAY",
    "TYPE": "TRANSRESP",
    "STRUCT": [
      {
        "COMM_PAYER_PAID": "0",
        "PROVIDER1": "101",
        "DATA": "SENDER",
        "USERTYPE": "SUBSCRIBER",
```

```

    "FROM": "077928289",
    "TAX_PAYER_PAID": "",
    "BALBFTRANS1": "0",
    "BALAFTRANS1": "0",
    "FEES_PAYER_PAID": "0",
    "PAYID1": "12",
    "COMM_PAYER_REC": "0",
    "NAME": "SUBS SUBS"
  },
  {
    "BALAFTRANS": "0",
    "FEES_PAYEE_PAID": "0",
    "COMM_PAYEE_REC": "0",
    "PAYID": "12",
    "BALBFTRANS": "1000.0",
    "COMM_PAYEE_PAID": "0",
    "CHANNEL_CODE": "59301",
    "NAME": "startimes tv",
    "DATA": "RECEIVER",
    "TAX_PAYEE_PAID": "",
    "USERTYPE": "CHANNEL",
    "PROVIDER": "101",
    "TO": "033200203"
  }
],
"TXNSTATUS": "200",
"TRID": "202106111158C0020",
"TXNTIME": "11:13"
}
}

```

4.5. Merchant payment call-back

4.5.1. Function description

4.5.2. API definition

Request

Tag	Fields	Example	Max Length	Optional/ Mandatory	Remarks
MMTransactionID		MP210115.0028.B50372	10	M	Afrimoney transaction ID

txnStatus		success		M	Status of the transaction
Amount		20000		M	Amount of the transaction
SenderMSISDN		077928289		M	

Response

4.5.3. Sample

Request

```
{
  "MMTransactionID": "MP210115.0028.B50372",
  "txnStatus": "success",
  "Amount": "20.0",
  "SenderMSISDN": "232235556"
}
```

Response

4.6. Subscriber information enquiry

4.6.1. Function description

4.6.2. API definition

Request

URL	http://10.14.10.163:8280/UserInfo/1.0
Method	POST
Header	Content-Type: application/json
Header	Authorization: Bearer <authorization_token>

Tag	Fields	Example	Max Length	Optional/ Mandatory	Remarks
TYPE	<<ADD NEW KEY>>	USERINFOREQ	10	M	Request Type
LEVEL	<Info Requested>			M	Valid value HIGH Detailed
INPUTTYPE	<Party Identification Type>			M	Valid value MSISDN AGENT_CODE

IDENTIFICATION	< Party Identification>			M	Mobile number should be without country code. If INPUTTYPE is MSISDN, then Mobile Number should be provided, if INPUTTYPE is AGENT_CODE, agent code should be provided
BLOCKSMS	<BLOCKSMS>	PAYER		O	Value can be one of these -> PAYER, PAYEE, BOTH
LANGUAGE 1	<Payer Language>	0	1	O	Numeric only Payer Language Code This code must be defined in Mobiquity system
CELLID	<CELLID>	Cellid1234	15	O	Cell Id is coming from third party (TAG IS OPTIONAL)
FTXNID	<FTXNID>	FTXNID	15	O	FTXNID is coming from third party(TAG IS OPTIONAL)
USERROLE	<User Role>	CUSTOMER		O	CHANNEL or CUSTOMER has to be provided otherwise by default considered as CHANNEL

Response

Tag	Fields	Example	Max Length	Optional/Mandatory	Remarks
TYPE	<<Add New Key>>		10	M	Response Type
TXNSTATUS	<Transaction Status>	200	5	M	Various transaction status Failed, Under process etc.
MESSAGE	<Response Message>			M	If Party Exists: SUCCESS <Party Name> with registered <mobile Number> is valid in the system. If Party doesn't exist: ERROR Party with < Party Identification Type> <Party identifier> is not valid.
TRID	<Transfer ID>	2088994466 2014121715 47C0016		M	Transfer ID
FNAME				M	Party First Name, if exist
LNAME				M	Party Last Name, if exist
NAME				M	Party full name
MSISDN				M	Party Mobile Number, if exist
AGENT_CODE				M	Applicable if Party is channel user only.

ID_NUMBER				M	If party type was blank in request and party exist both as consumer and channel user then the response should have both the identification as consumer and channel user.
LANGUAGE				M	Preferred language of party
STATUS				M	Valid values Active Suspended
BAR_DESCRIPTION				M	Valid values Barred as Sender Barred as Receiver Barred as both
PARENTMSISDN				O	If Enquiry is for Pseudo then it contains Pseudo User Parent Mobile Number
EMAIL				O	Contains Email Id of Consumer or Channel or Pseudo User
The following block is detail information block and it is optional. The block will repeat twice if party exist as both consumer and channel user and <Party Type> in request is blank. If party Type in request is consumer, then only single block should come for consumer. If party type in response is channel user then only channel user block should come.					
USER_TYPE					Valid Values Consumer Channel User
DOMAINCODE					A valid domain defined in the system
CATEGORY_CODE					A valid category defined in the system
PROVIDER_ID					Default MFS Provider of the party
PAYMENT_INSTRUMENT_ID					Default wallet type of the party
GRADE_CODE					Grade Code of the user

4.6.3. Sample

Request curl --location --request POST 'http://10.14.10.163:8280/UserInfo/1.0' \

```
--header 'Authorization: Bearer {{a_token}}' \
--header 'Content-Type: text/plain' \
--data-raw '{
```

```
"COMMAND": {
  "TYPE": "USERINFOREQ",
  "LEVEL": "HIGH",
  "INPUTTYPE": "MSISDN",
  "IDENTIFICATION": "077928289"
}
```

Response

```
{
  "COMMAND": {
    "LANGUAGE": "1",
    "ID_NUMBER": "077928289",
    "MSISDN": "077928289",
    "LNAME": "SUBS",
    "EMAIL": "",
    "DETAIL": {
      "CATEGORY_CODE": "SUBS",
      "DEFAULT_CURRENCY": "LE",
      "GRADE_CODE": "SUBS",
      "USER_TYPE": "SUBSCRIBER",
      "USER_ID": "PT23277928289",
      "PROVIDER_ID": "101",
      "DOMAINCODE": "SUBS",
      "PAYMENT_INSTRUMENT_ID": "12"
    },
    "FNAME": "SUBS",
    "NAME": "SUBS SUBS",
    "MESSAGE": "SUCCESS",
    "STATUS": "Y",
    "DEFAULT_PROVIDER_NAME": "MFS1",
    "DOB": "01-Jan-1900",
    "GENDER": "Male",
    "DEFAULT_PROVIDER_ID": "101",
    "TYPE": "USERINFORESP",
    "TXNSTATUS": "200",
    "TRID": "202106111144C0019",
    "BAR_DESCRIPTION": "N"
  }
}
```

4.7. CASHIN

4.7.1. Functional description

This API allow the merchant to send money from his own wallet to a subscriber wallet.

4.7.2. API definition

Request

URL	http://10.14.10.163:8280/CashIn/1.0
Method	POST
Header	Content-Type: application/json
Header	Authorization: Bearer <authorization_token>

Tag	SubTag	Fields	Example	Max Length	Optional/Mandatory	Remarks
serviceCode		serviceCode	CASHIN	10	O	Request Type
bearerCode		bearerCode	WEBSERVICE	15	M	Mode at which transaction happens
language		Language	en		O	If language value is specified response will be in that particular language, If the input does not contain the language - the we use
						system default language to respond
Initiator		Initiator	transactor		M	Initiator is who initiated the transaction
transaction Amount		transaction Amount	100	10	M	Numeric Only. Should accept. Refer to Afrimoney transaction allowed limits
Currency		Currency	101		M	Type of currency accepted in transaction
externalReferenceId		externalReferenceId	EXT1234		M	External ReferenceID. can be used in transaction enquiry API to check the status of an initiated transaction. make this value globally unique
remarks		remarks	CashIn		O	Remarks of service
transactor	idType	idType	mobileNumber	1	M	Id type of transactor(mobileNumber,loginId,userCode)
transactor	idValue	idValue	7701536457	16	M	Id value is the value of id Type. refer to SL number plan
transactor	productId	productId	12		M	Type of wallet of transactor
transactor	mpin	Mpin	1357	4	M	Numeric Only. MPIN is a login pin which can be different or same for different group of bearers. e.g USSD/WEB bearers share one MPIN and STK/J2ME bearers share another MPIN.

receiver	idType	idType	mobileNumber		M	Id Type of receiver (mobileNumber,loginId)
receiver	idValue	idValue	7700099999		M	Id value. refer to SL number plan
receiver	productId	productId	12		M	Type of wallet of receiver

Response

Tag	Sub Tag	Fields	Example	Max Length	Optional/ Mandatory	Remarks
serviceRequestId		serviceRequestId	f491f6b1-aa9b-43de93b0c85eda706a2c	255	M	Uniquely determines service flow
serviceFlow		serviceFlow	CASHIN	255	M	Service code of response
message		message	Cash In transaction of RUB 10 has been successfully completed between the sender: 7701536457 and receiver: 7700099999. Txn ID: CI161108.0404.A00011		M	Response Details
transactionStatus		transactionStatus	Success	255	M	Transaction status
transactionId		transactionId	CI161108.0404.A00011		M	Mobiquity Transaction ID for the Bill Payment Transaction. Used for informative purpose.
status		status	SUCCEEDED		M	Status

4.7.3. Sample

Request curl --location --request POST 'http://10.14.10.163:8280/CashIn/1.0'

```
\
--header 'Authorization: Bearer 4cb57835-50b0-3fa0-8e87-ecb319184f0b' \
--header 'Content-Type: application/json' \
--data-raw '{
  "serviceCode": "CASHIN",
  "bearerCode": "WEBSERVICE",
  "transactionAmount": "1000",
  "currency": "101",
  "externalReferenceId": "EXT12",
}
```

```
"remarks": "Deposit",
"initiator": "transactor",
"language": "en",
"transactor": {
  "idType": "mobileNumber",
  "idValue": "080317441",
  "productId": "12",
  "mpin": "1234"
},
"receiver": {
  "idType": "mobileNumber",
  "idValue": "077121212",
  "productId": "12"
}
}'
```

Response

```
{
  "receiverLastName": "dcfasd",
  "transactionDetails": {
    "receiver": {
      "commissionReceived": [],
      "netAmountReceived": {
        "amount": 1000,
        "accountNumber": "101120001483316",
        "currencyCode": "LE",
        "productName": "Normal"
      },
      "moneyPaid": [],
      "serviceChargePaid": [],
      "serviceTaxPaid": [],
      "moneyReceived": [
        {
          "amount": 1000,
          "accountNumber": "101120001483316",
          "currencyCode": "LE",
          "productName": "Normal"
        }
      ],
      "commissionTaxPaid": [],
      "commissionPaid": []
    },
    "sender": {
      "commissionReceived": [],
      "netAmountPaid": {
        "amount": 1000,
        "accountNumber": "101120001483537",
        "currencyCode": "LE",
        "productName": "Normal"
      }
    }
  }
}
```

```

"moneyPaid": [
  {
    "amount": 1000,
    "accountNumber": "101120001483537",
    "currencyCode": "LE",
    "productName": "Normal"
  }
],
"serviceChargePaid": [
  {
    "amount": 0,
    "accountNumber": "101120001483537",
    "currencyCode": "LE",
    "productName": "Normal"
  }
],
"totalServiceChargePaid": {
  "amount": 0,
  "currencyCode": "LE"
},
"serviceTaxPaid": [],
"moneyReceived": [],
"commissionTaxPaid": [],
"commissionPaid": []
},
"senderMobileNumber": "033200219",
"debitParty": [
  {
    "amount": 1000,
    "accountNumber": "101120001483537",
    "currencyCode": "LE",
    "productName": "Normal"
  }
],
"serviceRequestId": "ed7e14e3-9079-4d68-ac66-3d2a1abc6b4e",
"descriptionText": "Deposit",
"serviceFlow": "CASHIN",
"type": "CASHIN",
"originalServiceRequestId": "ed7e14e3-9079-4d68-ac66-3d2a1abc6b4e",
"externalReferenceId": "EXT12",
"netServiceChargePaidBySender": 0,
"netCreditAmount": 1000,
"txnStatus": "TS",
"currency": "101",
"originalTransactionReference": "EXT12",
"senderLastName": "nB",
"transactionReference": "C1210611.1223.80091",
"transactionStatus": "TS",
"mfsTenantId": "mfsPrimaryTenant",

```

```
"message": "Cash In successful for 077121212 Amount LE 1000 Balance 99000.00 Txn  
ID:  
CI210611.1223.80091",  
  "transactionId": "CI210611.1223.80091",  
  "netDebitAmount": 1000,  
  "receiverMobileNumber": "077121212",  
  "creditParty": [  
    {  
      "amount": 1000,  
      "accountNumber": "101120001483316",  
      "currencyCode": "LE",  
      "productName": "Normal"  
    }  
  ],  
  "remarks": "Deposit",  
  "status": "SUCCEEDED"  
}
```