## ES120 Spring 2018 – Midterm 1 Review

## Matheus Fernandes

March 8, 2018

## **Document Disclaimer**

The list provided below is by no means comprehensive and if you find anything missing that you would like to add please let me know. This review session has been created without prior knowledge of the problems in the exam and should not be treated in any way as hints to problems that will be asked in the exam. We will do our best to go over the topics of the course in detail however please do your own reading of chapters 1,2 and 3 as well as other topics not included in the book. If you find any typos please let me know and I will update and push a new version to Github ASAP.

You may also find my notes from a previous year helpful: http://fer.me/es120notes

This document was edited last on Tuesday 6th March, 2018 at 4:06pm

## **Topics Covered Summary**

- 1. Introduction Concepts of Stress
  - Normal Stress  $\sigma = \frac{P}{A}$ , where A is perpendicular to direction of force

  - Shearing Stress  $\tau_{ave} = \frac{P}{A}$ , where A is parallel to the direction of force Stresses under general loading conditions Determining the different components of stress from FBD such as  $\sigma_{xx}$ ,  $\sigma_{yy}$  and  $\tau_{xy}$ .

  - <u>Ultimate stress</u>  $\sigma_U = \frac{P_u}{A}$  <u>Factor of Safety</u> F.S. = <u>ultimate load</u> = <u>ultimate stress</u>
     <u>Truss Systems</u> How to efficiently solve a truss system using method of sections
- 2. Stress and Strain Axial Loading
  - Strain  $\epsilon = \frac{\delta}{L}$
  - Elastic Stress-Strain Diagram Linear Relationship
  - Plastic Stress-Strain Diagram Ideal plasticity with yield stress  $\sigma_Y$
  - True Stress and True Strain Difference between True and Engineering is the cross-sectional area. True stress uses A of deformed specimen.
  - Hooke's Law  $\sigma = E\epsilon$
  - Modulus of Elasticity E
  - Elastic vs. Plastic Behavior of Material Necking, yield stress, rupture etc.
  - Fatigue In cases of cyclic loading, rupture will occur at a stress much lower than the static breaking strength; this phenomenon is called fatigue.
  - Deformations of Members Under Axial Loading  $\delta = \frac{PL}{AE}$
  - Statically Indeterminate Problems Problems that cannot be determined using statics, but where we need to formulate a compatibility constraint. This occurs when we have more reaction forces to solve for than we have equations.
  - Problems involving temperature changes Thermal strain  $\epsilon_T = \alpha \Delta T$ . This does not create a stress until it is statically constrained and as per superposition the thermal strain becomes mechanical strain.
  - Superposition Method In statically indeterminate problems we remove redundant loads and apply superposition to solve for the different unknown loads.

March 8, 2018 ES120 Midterm Review

- <u>Poisson's Ratio</u> Relates lateral and axial strains through  $\nu=-\frac{\text{lateral strain}}{\text{axial strain}}$  Multiaxial loading Loading through multiple axis and the relationship to strain
- Generalized Hooke's Law Generalized relationship between all stresses, strains and material parameters through equations of form  $\epsilon_x=rac{1}{E}\left(\sigma_xu\sigma_yu\sigma_z
  ight)$ ,  $\epsilon_y=rac{1}{E}\left(\sigma_yu\sigma_xu\sigma_z
  ight)$ ,

$$\epsilon_z = \frac{1}{E} \left( \sigma_z - \nu \sigma_y - \nu \sigma_x \right)$$
• Plane Strain  $-\epsilon_z = 0$ 

- Plane Stress  $\sigma_z = 0$
- Bulk Modulus Change of volume per unit volume described by  $k=\frac{E}{3(1-2\nu)}$
- Shearing Strain Nondimensional deformation due to shearing stress  $\gamma_{xy}$
- Hooke's law for shearing stress and strain  $\tau_{xy} = G\gamma_{xy}$  Modulus of Rigidity Empirical value to relates shear stress to shear strain G. Analogous to modulus of elasticity E.
- Relation among  $E, \nu, G \frac{E}{2G} = 1 + \nu$  Stress Concentrations  $K = \frac{\sigma_{max}}{\sigma_{avg}}$
- Plastic Deformation Elastoplastic material stress strain curve. Gain intuition from this curve.
- · Residual Stresses Stresses left in a part post plastic deformation
- 3. Torsion