

Ruby on Rails 5.x

Do início ao fim!

Criando as views (new e edit) para as Questões

Criando as views (new e edit) para as Questões

- Comece alterando **views/admins_backoffice/questions/new.html.erb**

```
<%= render partial:
'admins_backoffice/questions/shared/form',
      locals: { action_message: 'Novo' } %>
```

Criando as views (new e edit) para as Questões

- Depois altere **views/admins_backoffice/questions/edit.html.erb**

```
<%= render partial:  
  'admins_backoffice/questions/shared/form',  
  locals: { action_message: 'Editando' } %>
```

Criando as views (new e edit) para as Questões

- Depois altere **views/admins_backoffice/questions/shared/_form.html.erb**

```
<div class="row">
  <div class="col-lg-12">
    <h1 class="page-header"><%= action_message %></h1>
  </div>
  <!-- /.col-lg-12 -->
</div>

<div class="row">
```

Criando as views (new e edit) para as Questões

```
<% if @question.errors.any? %>
  <div class="alert alert-danger alert-dismissible">
    <button type="button" class="close" data-dismiss="alert"
aria-hidden="true">×</button>

    <ul>
      <% @question.errors.full_messages.each do |message| %>
        <li> <%= message %> </li>
      <% end %>
    </ul>
  </div>
<% end %>
```

Criando as views (new e edit) para as Questões

```
<div class="col-lg-12">
  <div class="panel panel-default">
    <div class="panel-heading">
      <%= "#{action_message} Pergunta" %>
    </div>
    <div class="panel-body">
      <div class="row">
        <div class="col-lg-6">
          <%= form_with(model: [ :admins_backoffice,
@question ], local: true) do |form| %>

            <div class="form-group">
              <%= form.label :description %>
              <%= form.text_field :description,
class:"form-control", placeholder:"Descrição do pergunta...", rows:
5  %>

            </div>
```

Criando as views (new e edit) para as Questões

```

        <div class="form-group">
          <%= form.label :subject %>
          <%= form.collection_select(:subject_id,
Subject.all.order(:description), :id, :description, {}, { class:"form-control" } ) %>
        </div>

        <button type="submit" class="btn btn-default">Salvar</button>
      <% end %>
    </div>
    <!-- /.col-lg-6 (nested) -->
  </div>
  <!-- /.row (nested) -->
</div>
<!-- /.panel-body -->
</div>
<!-- /.panel -->
</div>
<!-- /.col-lg-12 -->
</div>
```


Criando as views (new e edit) para as Questões

- Depois altere **app/controllers/admins_backoffice/questions_controller.rb**

```
def update
  if @question.update(params_question)
    redirect_to admins_backoffice_questions_path, notice: "Questão
    atualizado com sucesso!"
  else
    render :edit
  end
end
```

Criando as views (new e edit) para as Questões

- Depois altere **app/controllers/admins_backoffice/questions_controller.rb**

```
def create
  @question = Question.new(params_question)
  if @question.save
    redirect_to admins_backoffice_questions_path, notice: "Questão cadastrada com sucesso!"
  else
    render :new
  end
end
```