

Ruby on Rails 5.x

Do início ao fim!



Refatorando a Task de respostas

Refatorando a Task de respostas

- Altere **lib/tasks/dev.rake**

```
desc "Adiciona perguntas e respostas"
task add_answers_and_questions: :environment do
  Subject.all.each do |subject|
    rand(5..10).times do |i|
      params = create_question_params(subject)
      answers_array = params[:question][:answers_attributes]

      add_answers(answers_array)
      elect_true_answer(answers_array)

      Question.create!(params[:question])
    end
  end
end
```

Refatorando a Task de respostas

- Adicione em **lib/tasks/dev.rake**, após o **private**

```
def create_question_params(subject = Subject.all.sample)
  { question: {
    description: "#{Faker::Lorem.paragraph} #{Faker::Lorem.question}",
    subject: subject,
    answers_attributes: []
  }
}
end
```

```
def create_answer_params(correct = false)
  { description: Faker::Lorem.sentence, correct: correct }
end
```

Refatorando a Task de respostas

- Adicione em **lib/tasks/dev.rake**, após o **private**

```
def add_answers(answers_array = [])
  rand(2..5).times do |j|
    answers_array.push(create_answer_params)
  end
end

def elect_true_answer(answers_array = [])
  selected_index = rand(answers_array.size)
  answers_array[selected_index] = create_answer_params(true)
end
```