

Solving the Rubik's Cube with A*

Artificial Intelligence and Reasoning, Lab 1

Mathias CHEBBAH Lamine BETRAOUI Bouna SALL Hugues BARBIER

Universite Paris Dauphine, PSL
Master 1 MIAE

June 2026


The problem

- A Rubik's Cube has six faces of nine stickers.
- Each face can turn, which mixes the colors.
- The cube is solved when each face is one color.
- It has about 4.3×10^{19} configurations.

Our goal: write the solve button.

Find a list of moves back to the solved cube.

We use search, as seen in Lecture 2.



A scrambled cube, drawn as a net.

The cube as a search problem


We use the five components of Lecture 2.

- **State:** a cube configuration.
- **Actions:** the twelve quarter turns.
- **Transition:** a turn permutes the stickers.
- **Goal test:** every face is uniform.
- **Cost:** each move costs one.

The shortest move list is the optimal solution.

The branching factor is twelve, so the tree is $O(12^d)$.

A blind search cannot go deep. We need a heuristic.




The goal state: every face uniform.

The classes

We followed the statement closely, in Java.

- **Cube:** faces, the twelve turns, isSolved.
- **State:** a node, with g , h and expand.
- **Astar:** the solve method.
- **StateSet:** the explored set.
- **PriorityQueueState:** the frontier.
- **Heuristic:** the interface and two versions.

The turns come from a real 3D model of the cube.
We built each class test first, with thirty six tests.



The four packages.

The A* algorithm


A* expands the node with the smallest value

$$f(n) = g(n) + h(n).$$

- $g(n)$ is the cost from the start.
- $h(n)$ estimates the cost to the goal.
- An admissible h never overestimates.
- With an admissible h , A* is optimal.
- With $h = 0$, A* is a uniform cost search.

UCS orders by g only, so it is blind.

A* adds h , so it expands far fewer states.



The leaf with the smallest f is expanded first. Both UCS and A* return the same optimal plan.


Heuristic 1: the sticker relaxation

A relaxation drops some rules of the problem.
Here each sticker may move on its own.

- Each sticker must reach its correct face.
- Distance is 0, 1 or 2 quarter turns.
- We sum over all 54 stickers.
- We divide by 12 stickers moved per turn.

$$h_{\text{label}} = \frac{1}{12} \sum_{s=1}^{54} d(s).$$

After one turn, the sum is 12, so $h = 1$.
This is admissible, so A* stays optimal.



Distance to the correct face: same 0,
next 1, opposite 2.


Heuristic 2: the piece relaxation

Here each piece may move on its own.

- A piece is a corner or an edge.
- One turn moves four corners and four edges.
- We count the misplaced pieces.
- The centers are fixed, so we ignore them.

$$h_{\text{cube}} = \max \left(\left\lceil \frac{\text{misplaced corners}}{4} \right\rceil, \left\lceil \frac{\text{misplaced edges}}{4} \right\rceil \right).$$

This is also admissible. The sticker one is stronger.



C: corner (3 stickers)


E: edge (2 stickers)

Results

- UCS blows up around depth six.
- There it expands about 500k states.
- Both heuristics scale to depth ten.
- Plans stay optimal, same length.
- The sticker heuristic is the strongest.
- Memory is the first limit, not time.


Expanded states, averaged over five cubes:

Depth	UCS	Cube	Label
6	503 575	450	400
9	fails	386 257	46 577



Conclusion

- We solved the cube with A*, as in the course.
- A* returns an optimal solution.
- A good heuristic gives huge savings.
- The heuristic changes the effort, not the answer.
- UCS fails from about seven moves.
- The main limit of A* is memory.



Our simulator and its solve button.

Thank you for your attention.