



*A free, open-source alternative to Mathematica*

The Mathics Team

February 14, 2021

# Contents

<b>I.</b>	<b>Manual</b>	<b>5</b>
1.	Introduction	6
2.	Installation and Running	8
3.	Language Tutorials	9
4.	Examples	22
5.	Django-based Web Interface	25
<b>II.</b>	<b>Reference of Built-in Symbols</b>	<b>27</b>
I.	Evaluation	28
II.	Control Statements	32
III.	Date and Time	37
IV.	Graphics (3D)	41
V.	Input and Output	45
VI.	Plotting	55
VII.	Logic	65
VIII.	Scoping	68
IX.	Random number generation	72
X.	Combinatorial Functions	76
XI.	Global System Information	79
XII.	The Main Loop	82
XIII.	Quantities	83
XIV.	Solving Recurrence Equations	85
XV.	Patterns and Rules	86
XVI.	Mathematical Functions	93
XVII.	Functional Programming	103
XVIII.	Compilation	105

<b>XIX.</b>	<b>Options and Default Arguments</b>	<b>107</b>
<b>XX.</b>	<b>Comparison</b>	<b>110</b>
<b>XXI.</b>	<b>Linear algebra</b>	<b>114</b>
<b>XXII.</b>	<b>Attributes</b>	<b>121</b>
<b>XXIII.</b>	<b>Assignment</b>	<b>126</b>
<b>XXIV.</b>	<b>Tensors</b>	<b>135</b>
<b>XXV.</b>	<b>Structure</b>	<b>138</b>
<b>XXVI.</b>	<b>Exponential, Trigonometric and Hyperbolic Functions</b>	<b>145</b>
<b>XXVII.</b>	<b>Drawing Graphics</b>	<b>152</b>
<b>XXVIII.</b>	<b>Manipulate</b>	<b>170</b>
<b>XXIX.</b>	<b>Number theoretic functions</b>	<b>171</b>
<b>XXX.</b>	<b>XML</b>	<b>176</b>
<b>XXXI.</b>	<b>Differential Equations</b>	<b>177</b>
<b>XXXII.</b>	<b>Strings and Characters</b>	<b>178</b>
<b>XXXIII.</b>	<b>Optimization</b>	<b>190</b>
<b>XXXIV.</b>	<b>Image[] and image related functions.</b>	<b>191</b>
<b>XXXV.</b>	<b>Special Functions</b>	<b>201</b>
<b>XXXVI.</b>	<b>Physical and Chemical data</b>	<b>210</b>
<b>XXXVII.</b>	<b>Calculus</b>	<b>212</b>
<b>XXXVIII.</b>	<b>Integer Functions</b>	<b>217</b>
<b>XXXIX.</b>	<b>List Functions</b>	<b>220</b>
<b>XL.</b>	<b>Mathematical Constants</b>	<b>244</b>
<b>XLI.</b>	<b>Algebraic Manipulation</b>	<b>247</b>
<b>XLII.</b>	<b>Numeric Evaluation</b>	<b>253</b>
<b>XLIII.</b>	<b>File Operations</b>	<b>258</b>
<b>XLIV.</b>	<b>Importing and Exporting</b>	<b>274</b>
<b>III.</b>	<b>License</b>	<b>279</b>
<b>A.</b>	<b>GNU General Public License</b>	<b>280</b>
<b>B.</b>	<b>Included software and data</b>	<b>289</b>



**Part I.**

**Manual**

# 1. Introduction

*Mathics*—to be pronounced like “Mathematics” without the “emat”—is a general-purpose computer algebra system (CAS). It is meant to be a free, open-source alternative to *Mathematica*®. It is free both as in “free beer” and as in “freedom”. There are various online mirrors running *Mathics* but it is also possible to run *Mathics* locally. A list of mirrors can be found at the *Mathics* home-page, <https://mathics.org>.

The programming language of *Mathics* is meant

to resemble *Wolfram*’s famous *Mathematica*® as much as possible. However, *Mathics* is in no way affiliated or supported by *Wolfram*. *Mathics* will probably never have the power to compete with *Mathematica*® in industrial applications; yet, it might be an interesting alternative for educational purposes.

For implementation details see <https://github.com/mathics/Mathics/wiki>.

## Contents

---

Why yet another CAS? . . .	6	Who is behind it? . . .	7
What does it offer? . . .	6		
What is missing? . . .	7		

---

## Why yet another CAS?

*Mathematica*® is great, but it has one big disadvantage: It is not free. On the one hand, people might not be able or willing to pay hundreds of dollars for it; on the other hand, they would still not be able to see what’s going on “inside” the program to understand their computations better. That’s what free software is for!

*Mathics* aims at combining the best of both worlds: the beauty of *Mathematica*® backed by a free, extensible Python core which includes a rich set of Python tools numeric computation, <https://numpy.org/numpy>, and symbolic mathematics, <https://sympy.org>.

Of course, there are drawbacks to the *Mathematica*® language, despite all its beauty. It does not really provide object orientation and especially encapsulation, which might be crucial for big software projects. Nevertheless, *Wolfram* still managed to create their amazing *Wolfram* | *Alpha* entirely with *Mathematica*®, so it can’t be too bad!

However, it is not even the intention of *Mathics* to be used in large-scale projects and calculations—at least not as the main framework—but rather as a tool for quick explorations and in educating people who might later

switch to *Mathematica*®.

## What does it offer?

Some of the most important features of *Mathics* are

- a powerful functional programming language,
- a system driven by pattern matching and rules application,
- rationals, complex numbers, and arbitrary-precision arithmetic,
- lots of list and structure manipulation routines,
- an interactive graphical user interface right in the Web browser using MathML (apart from a command line interface),
- creation of graphics (e.g. plots) and display in the browser using SVG for 2D graphics and WebGL for 3D graphics,
- export of results to L<sup>A</sup>T<sub>E</sub>X (using Asymptote for graphics),
- a very easy way of defining new functions in Python,
- an integrated documentation and testing system.

## What is missing?

There are lots of ways in which *Mathics* could still be improved.

Most notably, performance is still slow, so any serious usage in cutting-edge industry or research will fail, unfortunately. Although Cython can be used to speed up parts of *Mathics*, more is needed to speed up pattern matching. Replacing recursion with iteration may help here.

Apart from performance issues, new features such as more functions in various mathematical fields like calculus, number theory, or graph theory are still to be added.

In the future we intend to make better use of the graphics available in the excellent packages:

- `sympy` plotting, <https://docs.sympy.org/latest/modules/plotting.html>
- `matplotlib` pyplot, [https://matplotlib.org/api/pyplot\\_api.html](https://matplotlib.org/api/pyplot_api.html), and

- `networkx`, <https://networkx.github.io/>

## Who is behind it?

*Mathics* was created by Jan Pöschk in 2011. From 2013 to about 2017 it had been maintained mostly by Angus Griffith and Ben Jones. Since then, a number of others have been people involved in *Mathics*; the list can be found in the `AUTHORS.txt` file, <https://github.com/mathics/Mathics/blob/master/AUTHORS.txt>.

If you have any ideas on how to improve *Mathics* or even want to help out yourself, please contact us!

Welcome to *Mathics*, have fun!

## 2. Installation and Running

*Mathics* runs natively on a computer that has Python or PyPy 3.6 or later installed. Since *Mathics* relies on *sympy* which in turn relies on *numpy*, you will need at least those installed.

Since installation may change, see <https://github.com/mathics/Mathics/wiki/Installing-and-Running> for the most recent instructions for installing from PyPI, source, or from *docker*.



## 3. Language Tutorials

The following sections are introductions to the basic principles of the language of *Mathics*. A few examples and functions are presented. Only their most common usages are listed; for a full description of a Symbols possible arguments, options, etc., see its entry in the Reference of

Built-in Symbols.

However if you google for “Mathematica Tutorials” you will find easily dozens of other tutorials which are applicable. Be warned though that *Mathics* does not yet offer the full range and features and capabilities of *Mathematica*®.

### Contents

---

Basic calculations . . .	10	Lists . . . . .	12	Graphics Introduction	
Symbols and		The Structure of Things	13	Examples . . . . .	20
Assignments . . .	11	Functions and Patterns	15	3D Graphics . . . . .	20
Comparisons and		Control Statements . .	15	Plotting Introduction	
Boolean Logic . .	11	Scoping . . . . .	16	Examples . . . . .	21
Strings . . . . .	11	Formatting Output . .	18		

---

### Basic calculations

*Mathics* can be used to calculate basic stuff:

```
>> 1 + 2
3
```

To submit a command to *Mathics*, press Shift+Return in the Web interface or Return in the console interface. The result will be printed in a new line below your query.

*Mathics* understands all basic arithmetic operators and applies the usual operator precedence. Use parentheses when needed:

```
>> 1 - 2 * (3 + 5) / 4
-3
```

The multiplication can be omitted:

```
>> 1 - 2 (3 + 5) / 4
-3
```

```
>> 2 4
8
```

Powers can be entered using ^:

```
>> 3 ^ 4
81
```

Integer divisions yield rational numbers:

```
>> 6 / 4
3
2
```

To convert the result to a floating point number, apply the function N:

```
>> N[6 / 4]
1.5
```

As you can see, functions are applied using square braces [ and ], in contrast to the common notation of ( and ). At first hand, this might seem strange, but this distinction between function application and precedence change is necessary to allow some general syntax structures, as you will see later.

*Mathics* provides many common mathematical functions and constants, e.g.:

```
>> Log[E]
1
```

```
>> Sin[Pi]
0
```

```
>> Cos[0.5]
0.877583
```

When entering floating point numbers in your query, *Mathics* will perform a numerical evalua-

tion and present a numerical result, pretty much like if you had applied  $N$ .

Of course, *Mathics* has complex numbers:

```
>> Sqrt[-4]
2I
>> I ^ 2
-1
>> (3 + 2 I)^ 4
-119 + 120I
>> (3 + 2 I)^ (2.5 - I)
43.663 + 8.28556I
>> Tan[I + 0.5]
0.195577 + 0.842966I
```

*Abs* calculates absolute values:

```
>> Abs[-3]
3
>> Abs[3 + 4 I]
5
```

*Mathics* can operate with pretty huge numbers:

```
>> 100!
93 326 215 443 944 152 681 699 ~
~238 856 266 700 490 715 968 ~
~264 381 621 468 592 963 895 ~
~217 599 993 229 915 608 941 ~
~463 976 156 518 286 253 697 920 ~
~827 223 758 251 185 210 916 864 ~
~000 000 000 000 000 000 000 000
```

(! denotes the factorial function.) The precision of numerical evaluation can be set:

```
>> N[Pi, 100]
3.141592653589793238462643~
~383279502884197169399375~
~105820974944592307816406~
~286208998628034825342117068
```

Division by zero is forbidden:

```
>> 1 / 0
Indeterminateexpression1/0encountered.
ComplexInfinity
```

Other expressions involving *Infinity* are evaluated:

```
>> Infinity + 2 Infinity
∞
```

In contrast to combinatorial belief,  $0^0$  is undefined:

```
>> 0 ^ 0
Indeterminateexpression0^0encountered.
Indeterminate
```

The result of the previous query to *Mathics* can be accessed by %:

```
>> 3 + 4
7
>> % ^ 2
49
```

## Symbols and Assignments

Symbols need not be declared in *Mathics*, they can just be entered and remain variable:

```
>> x
x
```

Basic simplifications are performed:

```
>> x + 2 x
3x
```

Symbols can have any name that consists of characters and digits:

```
>> iAm1Symbol ^ 2
iAm1Symbol^2
```

You can assign values to symbols:

```
>> a = 2
2
>> a ^ 3
8
>> a = 4
4
>> a ^ 3
64
```

Assigning a value returns that value. If you want to suppress the output of any result, add a ; to the end of your query:

```
>> a = 4;
```

Values can be copied from one variable to another:

```
>> b = a;
```

Now changing *a* does not affect *b*:

```
>> a = 3;
>> b
4
```

Such a dependency can be achieved by using “delayed assignment” with the `:=` operator (which does not return anything, as the right side is not even evaluated):

```
>> b := a ^ 2

>> b
9

>> a = 5;

>> b
25
```

## Comparisons and Boolean Logic

Values can be compared for equality using the operator `==`:

```
>> 3 == 3
True

>> 3 == 4
False
```

The special symbols `True` and `False` are used to denote truth values. Naturally, there are inequality comparisons as well:

```
>> 3 > 4
False
```

Inequalities can be chained:

```
>> 3 < 4 >= 2 != 1
True
```

Truth values can be negated using `!` (logical *not*) and combined using `&&` (logical *and*) and `||` (logical *or*):

```
>> !True
False

>> !False
True

>> 3 < 4 && 6 > 5
True
```

`&&` has higher precedence than `||`, i.e. it binds stronger:

```
>> True && True || False && False
True

>> True && (True || False) && False
False
```

## Strings

Strings can be entered with `"` as delimiters:

```
>> "Hello world!"
Hello world!
```

As you can see, quotation marks are not printed in the output by default. This can be changed by using `InputForm`:

```
>> InputForm["Hello world!"]
"Hello world!"
```

Strings can be joined using `<>`:

```
>> "Hello" <> " " <> "world!"
Hello world!
```

Numbers cannot be joined to strings:

```
>> "Debian" <> 6
Stringexpected.
Debian<>6
```

They have to be converted to strings using `ToString` first:

```
>> "Debian" <> ToString[6]
Debian6
```

## Lists

Lists can be entered in *Mathics* with curly braces `{` and `}`:

```
>> mylist = {a, b, c, d}
{a, b, c, d}
```

There are various functions for constructing lists:

```
>> Range[5]
{1, 2, 3, 4, 5}

>> Array[f, 4]
{f[1], f[2], f[3], f[4]}

>> ConstantArray[x, 4]
{x, x, x, x}

>> Table[n ^ 2, {n, 2, 5}]
{4, 9, 16, 25}
```

The number of elements of a list can be determined with `Length`:

```
>> Length[mylist]
4
```

Elements can be extracted using double square

braces:

```
>> mylist[[3]]  
c
```

Negative indices count from the end:

```
>> mylist[[-3]]  
b
```

Lists can be nested:

```
>> mymatrix = {{1, 2}, {3, 4}, {5,  
6}};
```

There are alternate forms to display lists:

```
>> TableForm[mymatrix]
```

```
1 2  
3 4  
5 6
```

```
>> MatrixForm[mymatrix]
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{pmatrix}$$

There are various ways of extracting elements from a list:

```
>> mymatrix[[2, 1]]  
3
```

```
>> mymatrix[;;, 2]  
{2, 4, 6}
```

```
>> Take[mylist, 3]  
{a, b, c}
```

```
>> Take[mylist, -2]  
{c, d}
```

```
>> Drop[mylist, 2]  
{c, d}
```

```
>> First[mymatrix]  
{1, 2}
```

```
>> Last[mylist]  
d
```

```
>> Most[mylist]  
{a, b, c}
```

```
>> Rest[mylist]  
{b, c, d}
```

Lists can be used to assign values to multiple variables at once:

```
>> {a, b} = {1, 2};
```

```
>> a  
1
```

```
>> b  
2
```

Many operations, like addition and multiplication, “thread” over lists, i.e. lists are combined element-wise:

```
>> {1, 2, 3} + {4, 5, 6}  
{5, 7, 9}
```

```
>> {1, 2, 3} * {4, 5, 6}  
{4, 10, 18}
```

It is an error to combine lists with unequal lengths:

```
>> {1, 2} + {4, 5, 6}
```

*Objectsofunequallengthcannotbecombined.*

```
{1, 2} + {4, 5, 6}
```

## The Structure of Things

Every expression in *Mathics* is built upon the same principle: it consists of a *head* and an arbitrary number of *children*, unless it is an *atom*, i.e. it can not be subdivided any further. To put it another way: everything is a function call. This can be best seen when displaying expressions in their “full form”:

```
>> FullForm[a + b + c]  
Plus[a, b, c]
```

Nested calculations are nested function calls:

```
>> FullForm[a + b * (c + d)]  
Plus[a, Times[b, Plus[c, d]]]
```

Even lists are function calls of the function `List`:

```
>> FullForm[{1, 2, 3}]  
List[1, 2, 3]
```

The head of an expression can be determined with `Head`:

```
>> Head[a + b + c]  
Plus
```

The children of an expression can be accessed like list elements:

```
>> (a + b + c)[[2]]  
b
```

The head is the 0th element:

```
>> (a + b + c)[[0]]
Plus
```

The head of an expression can be exchanged using the function `Apply`:

```
>> Apply[g, f[x, y]]
g[x, y]

>> Apply[Plus, a * b * c]
a + b + c
```

`Apply` can be written using the operator `@@`:

```
>> Times @@ {1, 2, 3, 4}
24
```

(This exchanges the head `List` of `{1, 2, 3, 4}` with `Times`, and then the expression `Times[1, 2, 3, 4]` is evaluated, yielding 24.) `Apply` can also be applied on a certain *level* of an expression:

```
>> Apply[f, {{1, 2}, {3, 4}}, {1}]
{f[1, 2], f[3, 4]}
```

Or even on a range of levels:

```
>> Apply[f, {{1, 2}, {3, 4}}, {0, 2}]
f[f[1, 2], f[3, 4]]
```

`Apply` is similar to `Map (/@)`:

```
>> Map[f, {1, 2, 3, 4}]
{f[1], f[2], f[3], f[4]}

>> f /@ {{1, 2}, {3, 4}}
{f[{1, 2}], f[{3, 4}]}
```

The atoms of *Mathics* are numbers, symbols, and strings. `AtomQ` tests whether an expression is an atom:

```
>> AtomQ[5]
True

>> AtomQ[a + b]
False
```

The full form of rational and complex numbers looks like they were compound expressions:

```
>> FullForm[3 / 5]
Rational[3, 5]

>> FullForm[3 + 4 I]
Complex[3, 4]
```

However, they are still atoms, thus unaffected

by applying functions, for instance:

```
>> f @@ Complex[3, 4]
3 + 4 I
```

Nevertheless, every atom has a head:

```
>> Head /@ {1, 1/2, 2.0, I, "a string", x}
{Integer, Rational, Real,
 Complex, String, Symbol}
```

The operator `===` tests whether two expressions are the same on a structural level:

```
>> 3 === 3
True

>> 3 == 3.0
True
```

But

```
>> 3 === 3.0
False
```

because 3 (an `Integer`) and 3.0 (a `Real`) are structurally different.

## Functions and Patterns

Functions can be defined in the following way:

```
>> f[x_] := x ^ 2
```

This tells *Mathics* to replace every occurrence of `f` with one (arbitrary) parameter `x` with `x ^ 2`.

```
>> f[3]
9

>> f[a]
a2
```

The definition of `f` does not specify anything for two parameters, so any such call will stay unevaluated:

```
>> f[1, 2]
f[1, 2]
```

In fact, *functions* in *Mathics* are just one aspect of *patterns*: `f[x_]` is a pattern that *matches* expressions like `f[3]` and `f[a]`. The following patterns are available:

```

_ or Blank[]
    matches one expression.
Pattern[x, p]
    matches the pattern p and stores the value
    in x.
x_ or Pattern[x, Blank[]]
    matches one expression and stores it in x.
__ or BlankSequence[]
    matches a sequence of one or more ex-
    pressions.
___ or BlankNullSequence[]
    matches a sequence of zero or more ex-
    pressions.
_h or Blank[h]
    matches one expression with head h.
x_h or Pattern[x, Blank[h]]
    matches one expression with head h and
    stores it in x.
p | q or Alternatives[p, q]
    matches either pattern p or q.
p ? t or PatternTest[p, t]
    matches p if the test t[p] yields True.
p /; c or Condition[p, c]
    matches p if condition c holds.
Verbatim[p]
    matches an expression that equals p,
    without regarding patterns inside p.

```

As before, patterns can be used to define func-  
tions:

```

>> g[s___] := Plus[s] ^ 2

>> g[1, 2, 3]
36

```

MatchQ[*e*, *p*] tests whether *e* matches *p*:

```

>> MatchQ[a + b, x_ + y_]
True

>> MatchQ[6, _Integer]
True

```

ReplaceAll (/.) replaces all occurrences of a  
pattern in an expression using a Rule given by  
->:

```

>> {2, "a", 3, 2.5, "b", c} /.
    x_Integer -> x ^ 2
{4, a, 9, 2.5, b, c}

```

You can also specify a list of rules:

```

>> {2, "a", 3, 2.5, "b", c} /. {
    x_Integer -> x ^ 2.0, y_String
    -> 10}
{4., 10, 9., 2.5, 10, c}

```

ReplaceRepeated (//.) applies a set of rules re-  
peatedly, until the expression doesn't change  
anymore:

```

>> {2, "a", 3, 2.5, "b", c} //. {
    x_Integer -> x ^ 2.0, y_String
    -> 10}
{4., 100., 9., 2.5, 100., c}

```

There is a “delayed” version of Rule which can  
be specified by :> (similar to the relation of := to  
=):

```

>> a :> 1 + 2
a:>1 + 2

>> a -> 1 + 2
a- > 3

```

This is useful when the right side of a rule  
should not be evaluated immediately (before  
matching):

```

>> {1, 2} /. x_Integer -> N[x]
{1, 2}

```

Here, N is applied to *x* before the actual match-  
ing, simply yielding *x*. With a delayed rule this  
can be avoided:

```

>> {1, 2} /. x_Integer :> N[x]
{1., 2.}

```

While ReplaceAll and ReplaceRepeated sim-  
ply take the first possible match into ac-  
count, ReplaceList returns a list of all possi-  
ble matches. This can be used to get all subse-  
quences of a list, for instance:

```

>> ReplaceList[{a, b, c}, {___, x__,
    , ___} -> {x}]
{{a}, {a, b}, {a, b,
    c}, {b}, {b, c}, {c}}

```

ReplaceAll would just return the first expres-  
sion:

```

>> ReplaceAll[{a, b, c}, {___, x__,
    ___} -> {x}]
{a}

```

In addition to defining functions as rules for cer-  
tain patterns, there are *pure* functions that can be  
defined using the & postfix operator, where ev-  
erything before it is treated as the function body  
and # can be used as argument placeholder:

```

>> h = # ^ 2 &;

>> h[3]
9

```

Multiple arguments can simply be indexed:

```
>> sum = #1 + #2 &;  
  
>> sum[4, 6]  
10
```

It is also possible to name arguments using Function:

```
>> prod = Function[{x, y}, x * y];  
  
>> prod[4, 6]  
24
```

Pure functions are very handy when functions are used only locally, e.g., when combined with operators like Map:

```
>> # ^ 2 & /@ Range[5]  
{1,4,9,16,25}
```

Sort according to the second part of a list:

```
>> Sort[{{x, 10}, {y, 2}, {z, 5}},  
#1[[2]] < #2[[2]] &]  
{{y,2}, {z,5}, {x,10}}
```

Functions can be applied using prefix or postfix notation, in addition to using []:

```
>> h @ 3  
9  
  
>> 3 // h  
9
```

## Control Statements

Like most programming languages, *Mathics* has common control statements for conditions, loops, etc.:

If[*cond*, *pos*, *neg*]  
returns *pos* if *cond* evaluates to True, and *neg* if it evaluates to False.  
Which[*cond1*, *expr1*, *cond2*, *expr2*, ...]  
yields *expr1* if *cond1* evaluates to True, *expr2* if *cond2* evaluates to True, etc.  
Do[*expr*, {*i*, *max*}]  
evaluates *expr* *max* times, substituting *i* in *expr* with values from 1 to *max*.  
For[*start*, *test*, *incr*, *body*]  
evaluates *start*, and then iteratively *body* and *incr* as long as *test* evaluates to True.  
While[*test*, *body*]  
evaluates *body* as long as *test* evaluates to True.  
Nest[*f*, *expr*, *n*]  
returns an expression with *f* applied *n* times to *expr*.  
NestWhile[*f*, *expr*, *test*]  
applies a function *f* repeatedly on an expression *expr*, until applying *test* on the result no longer yields True.  
FixedPoint[*f*, *expr*]  
starting with *expr*, repeatedly applies *f* until the result no longer changes.

```
>> If[2 < 3, a, b]  
a  
  
>> x = 3; Which[x < 2, a, x > 4, b,  
x < 5, c]  
c
```

Compound statements can be entered with ;. The result of a compound expression is its last part or Null if it ends with a ;.

```
>> 1; 2; 3  
3  
  
>> 1; 2; 3;
```

Inside For, While, and Do loops, Break[] exits the loop and Continue[] continues to the next iteration.

```
>> For[i = 1, i <= 5, i++, If[i ==  
4, Break[]]; Print[i]]  
1  
2  
3
```

## Scoping

By default, all symbols are “global” in *Mathics*, i.e. they can be read and written in any part of your program. However, sometimes “local” variables are needed in order not to disturb the global namespace. *Mathics* provides two ways to support this:

- *lexical scoping* by `Module`, and
- *dynamic scoping* by `Block`.

```
Module[{vars}, expr]
  localizes variables by giving them a temporary name of the form name$number, where number is the current value of $ModuleNumber. Each time a module is evaluated, $ModuleNumber is incremented.

Block[{vars}, expr]
  temporarily stores the definitions of certain variables, evaluates expr with reset values and restores the original definitions afterwards.
```

Both scoping constructs shield inner variables from affecting outer ones:

```
>> t = 3;

>> Module[{t}, t = 2]
2

>> Block[{t}, t = 2]
2

>> t
3
```

`Module` creates new variables:

```
>> y = x ^ 3;

>> Module[{x = 2}, x * y]
2x3
```

`Block` does not:

```
>> Block[{x = 2}, x * y]
16
```

Thus, `Block` can be used to temporarily assign a value to a variable:

```
>> expr = x ^ 2 + x;

>> Block[{x = 3}, expr]
12

>> x
x
```

`Block` can also be used to temporarily change the value of system parameters:

```
>> Block[{$RecursionLimit = 30}, x
= 2 x]
Recursiondepthof30exceeded.
$Aborted

>> f[x_] := f[x + 1]; Block[{
$IterationLimit = 30}, f[1]]
Iterationlimitof30exceeded.
$Aborted
```

It is common to use scoping constructs for function definitions with local variables:

```
>> fac[n_] := Module[{k, p}, p = 1;
  For[k = 1, k <= n, ++k, p *= k
]; p]

>> fac[10]
3 628 800

>> 10!
3 628 800
```

## Formatting Output

The way results are formatted for output in *Mathics* is rather sophisticated, as compatibility to the way *Mathematica*® does things is one of the design goals. It can be summed up in the following procedure:

1. The result of the query is calculated.
2. The result is stored in `Out` (which `%` is a shortcut for).
3. Any `Format` rules for the desired output form are applied to the result. In the console version of *Mathics*, the result is formatted as `OutputForm`; `MathMLForm` for the `StandardForm` is used in the interactive Web version; and `TeXForm` for the `StandardForm` is used to generate the  $\text{\LaTeX}$  version of this documentation.
4. `MakeBoxes` is applied to the formatted result, again given either `OutputForm`, `MathMLForm`, or `TeXForm` depending on the execution context of *Mathics*. This yields a new expression consisting of “box constructs”.
5. The boxes are turned into an ordinary string and displayed in the console, sent to the browser, or written to the documentation  $\text{\LaTeX}$  file.



As a consequence, there are various ways to implement your own formatting strategy for custom objects.

You can specify how a symbol shall be formatted by assigning values to `Format`:

```
>> Format[x] = "y";

>> x
y
```

This will apply to `MathMLForm`, `OutputForm`, `StandardForm`, `TeXForm`, and `TraditionalForm`.

```
>> x // InputForm
x
```

You can specify a specific form in the assignment to `Format`:

```
>> Format[x, TeXForm] = "z";

>> x // TeXForm
\text{z}
```

Special formats might not be very relevant for individual symbols, but rather for custom functions (objects):

```
>> Format[r[args___]] = "<an r
object>";

>> r[1, 2, 3]
<an r object>
```

You can use several helper functions to format expressions:

```
Infix[expr, op]
    formats the arguments of expr with infix
    operator op.
Prefix[expr, op]
    formats the argument of expr with prefix
    operator op.
Postfix[expr, op]
    formats the argument of expr with postfix
    operator op.
StringForm[form, arg1, arg2, ...]
    formats arguments using a format string.
```

```
>> Format[r[args___]] = Infix[{args
}, "~"];

>> r[1, 2, 3]
1 ~ 2 ~ 3

>> StringForm["'1' and '2'", n, m]
n and m
```

There are several methods to display expressions in 2-D:

```
Row[{...}]
    displays expressions in a row.
Grid[{{...}}]
    displays a matrix in two-dimensional
    form.
Subscript[expr, i1, i2, ...]
    displays expr with subscript indices i1, i2,
    ...
Superscript[expr, exp]
    displays expr with superscript (exponent)
    exp.
```

```
>> Grid[{{a, b}, {c, d}}]
  a  b
  c  d

>> Subscript[a, 1, 2] // TeXForm
a_{1,2}
```

If you want even more low-level control of how expressions are displayed, you can override `MakeBoxes`:

```
>> MakeBoxes[b, StandardForm] = "c
";

>> b
c
```

This will even apply to `TeXForm`, because `TeXForm` implies `StandardForm`:

```
>> b // TeXForm
c
```

Except some other form is applied first:

```
>> b // OutputForm // TeXForm
b
```

`MakeBoxes` for another form:

```
>> MakeBoxes[b, TeXForm] = "d";

>> b // TeXForm
d
```

You can cause a much bigger mess by overriding `MakeBoxes` than by sticking to `Format`, e.g. generate invalid XML:

```
>> MakeBoxes[c, MathMLForm] = "<not
closed";

>> c // MathMLForm
<not closed
```

However, this will not affect formatting of ex-

pressions involving  $c$ :

```
>> c + 1 // MathMLForm
<math display="block"><mstyle
  mathvariant="sans-serif">
  <mrow><mn>1</mn>
  <mo>+</mo> <mi>c</mi>
</mrow></mstyle></math>
```

That's because MathMLForm will, when not overridden for a special case, call StandardForm first. Format will produce escaped output:

```
>> Format[d, MathMLForm] = "<not
  closed";

>> d // MathMLForm
<math display="block"><mstyle
  mathvariant="sans-serif">
  <mtxt>&lt;not&nbsp;closed</mtxt>
</mstyle></math>

>> d + 1 // MathMLForm
<math display="block"><mstyle
  mathvariant="sans-serif"><mrow>
  <mn>1</mn> <mo>+</mo>
  <mtxt>&lt;not&nbsp;closed</mtxt>
</mrow></mstyle></math>
```

For instance, you can override MakeBoxes to format lists in a different way:

```
>> MakeBoxes[{items___},
  StandardForm] := RowBox[{"[",
  Sequence @@ Riffle[MakeBoxes /@
  {items}, " ", "]" } ]

>> {1, 2, 3}
[123]
```

However, this will not be accepted as input to Mathics anymore:

```
>> [1 2 3]

>> Clear[MakeBoxes]
```

By the way, MakeBoxes is the only built-in symbol that is not protected by default:

```
>> Attributes[MakeBoxes]
[HoldAllComplete]
```

MakeBoxes must return a valid box construct:

```
>> MakeBoxes[squared[args___],
  StandardForm] := squared[args] ^
  2
```

```
>> squared[1, 2]
Power[squared[1,2],
  2]isnotavalidboxstructure.

>> squared[1, 2] // TeXForm
Power[squared[1,2],
  2]isnotavalidboxstructure.
```

= The desired effect can be achieved in the following way:

```
>> MakeBoxes[squared[args___],
  StandardForm] := SuperscriptBox[
  RowBox[{MakeBoxes[squared], "["},
  RowBox[Riffle[MakeBoxes[#] & /@
  {args}, " "], "]" ]], 2]

>> squared[1, 2]
squared[1,2]^2
```

You can view the box structure of a formatted expression using ToBoxes:

```
>> ToBoxes[m + n]
RowBox[{m, +, n}]
```

The list elements in this RowBox are strings, though string delimiters are not shown in the default output form:


```
>> InputForm[%]
RowBox[{"m","+", "n"}]
```

## Graphics Introduction Examples


Two-dimensional graphics can be created using the function Graphics and a list of graphics primitives. For three-dimensional graphics see the following section. The following primitives are available:

```
Circle[{x, y}, r]
  draws a circle.
Disk[{x, y}, r]
  draws a filled disk.
Rectangle[{x1, y1}, {x2, y2}]
  draws a filled rectangle.
Polygon[{{x1, y1}, {x2, y2}, ...}]
  draws a filled polygon.
Line[{{x1, y1}, {x2, y2}, ...}]
  draws a line.
Text[text, {x, y}]
  draws text in a graphics.
```

```
>> Graphics[{Circle[{0, 0}, 1]}]
```



```
>> Graphics[{Line[{{0, 0}, {0, 1}, {1, 1}, {1, -1}}], Rectangle[{0, 0}, {-1, -1}]]
```



Colors can be added in the list of graphics primitives to change the drawing color. The following ways to specify colors are supported:

`RGBColor[r, g, b]`  
specifies a color using red, green, and blue.

`CMYKColor[c, m, y, k]`  
specifies a color using cyan, magenta, yellow, and black.

`Hue[h, s, b]`  
specifies a color using hue, saturation, and brightness.

`GrayLevel[l]`  
specifies a color using a gray level.

All components range from 0 to 1. Each color

function can be supplied with an additional argument specifying the desired opacity ("alpha") of the color. There are many predefined colors,

such as Black, White, Red, Green, Blue, etc.

```
>> Graphics[{Red, Disk[]}]
```





Table of hues:

```
>> Graphics[Table[{Hue[h, s], Disk[{12h, 8s}]}], {h, 0, 1, 1/6}, {s, 0, 1, 1/4}]]
```




Colors can be mixed and altered using the following functions:

`Blend[{color1, color2}, ratio]`  
mixes *color1* and *color2* with *ratio*, where a ratio of 0 returns *color1* and a ratio of 1 returns *color2*.

`Lighter[color]`  
makes *color* lighter (mixes it with White).

`Darker[color]`  
makes *color* darker (mixes it with Black).

```
>> Graphics[{Lighter[Red], Disk[]}]
```



Graphics produces a GraphicsBox:

```
>> Head[ToBoxes[Graphics[{Circle[]}]]]
```

GraphicsBox

## 3D Graphics

Three-dimensional graphics are created using the function Graphics3D and a list of 3D primitives. The following primitives are supported so far:

```
Polygon[{{x1, y1, z1}, {x2, y2, z3}, ...}]
```

draws a filled polygon.


```
Line[{{x1, y1, z1}, {x2, y2, z3}, ...}]
```

draws a line.

```
Point[{x1, y1, z1}]
```

draws a point.

```
>> Graphics3D[Polygon[{{0,0,0}, {0,1,1}, {1,0,0}}]]
```



Colors can also be added to three-dimensional primitives.

```
>> Graphics3D[{0, Orange, Polygon[{{0,0,0}, {1,1,1}, {1,0,0}}]], Axes->True]
```

```
Graphics3DBox[List[StyleBox[Graphics[List[EdgeForm[Graphics3DBox[Polygon[{{0,0,0}, {1,1,1}, {1,0,0}], Rule[ImageSize, 16]], Rule[ImageSizeMultipliers, List[1, 1]], Polygon3DBox[List[List[0, 0, 0], List[1, 1, 1], List[1, 0, 0]]], Rule[$OptionSyntax, Ignore], Rule[AspectRatio, Automatic], Rule[Axes, True], Rule[AxesStyle, List[]], Rule[Background, Automatic], Rule[BoxRatios, Automatic], Rule[ImageSize, Automatic], Rule[LabelStyle, List[]], Rule[Lighting, Automatic], Rule[PlotRange, Automatic], Rule[PlotRangePadding, Automatic], Rule[TicksStyle, List[]], Rule[ViewPoint, List[1.3, -2.4, 2.]]]isnotavalidboxstructure.
```

Graphics3D produces a Graphics3DBox:


```
>> Head[ToBoxes[Graphics3D[{Polygon[]}]]]
```

Graphics3DBox

## Plotting Introduction Examples


*Mathics* can plot functions:

```
>> Plot[Sin[x], {x, 0, 2 Pi}]
```




You can also plot multiple functions at once:

```
>> Plot[{Sin[x], Cos[x], x ^ 2}, {x, -1, 1}]
```




Two-dimensional functions can be plotted using `DensityPlot`:

```
>> DensityPlot[x ^ 2 + 1 / y, {x, -1, 1}, {y, 1, 4}]
```



You can use a custom coloring function:


```
>> DensityPlot[x ^ 2 + 1 / y, {x, -1, 1}, {y, 1, 4}, ColorFunction -> (Blend[{Red, Green, Blue}, #]&)]
```



One problem with `DensityPlot` is that it's still very slow, basically due to function evaluation being pretty slow in general—and `DensityPlot` has to evaluate a lot of functions.

Three-dimensional plots are supported as well:

```
>> Plot3D[Exp[x] Cos[y], {x, -2, 1}, {y, -Pi, 2 Pi}]
```



## 4. Examples

### Contents

Curve sketching . . . .	22	Linear algebra . . . . .	23	Dice . . . . .	24
-------------------------	----	--------------------------	----	----------------	----

### Curve sketching

Let's sketch the function

```
>> f[x_] := 4 x / (x ^ 2 + 3 x + 5)
```

The derivatives are

```
>> {f'[x], f''[x], f'''[x]} //
```

Together

$$\left\{ \begin{array}{l} \frac{-4(-5+x^2)}{(5+3x+x^2)^2}, \\ \frac{8(-15-15x+x^3)}{(5+3x+x^2)^3}, \\ \frac{-24(-20-60x-30x^2+x^4)}{(5+3x+x^2)^4} \end{array} \right\}$$

To get the extreme values of f, compute the zeroes of the first derivatives:

```
>> extremes = Solve[f'[x] == 0, x]
```

$$\left\{ \left\{ x \rightarrow -\sqrt{5} \right\}, \left\{ x \rightarrow \sqrt{5} \right\} \right\}$$

And test the second derivative:

```
>> f''[x] /. extremes // N
```

$$\{1.65086, -0.064079\}$$

Thus, there is a local maximum at  $x = \text{Sqrt}[5]$  and a local minimum at  $x = -\text{Sqrt}[5]$ . Compute the inflection points numerically, chopping imaginary parts close to 0:

```
>> inflections = Solve[f''[x] == 0, x] // N // Chop
```

$$\left\{ \left\{ x \rightarrow -1.0852 \right\}, \left\{ x \rightarrow -3.21463 \right\}, \left\{ x \rightarrow 4.29983 \right\} \right\}$$

Insert into the third derivative:

```
>> f'''[x] /. inflections
```

$$\{-3.67683, 0.694905, 0.00671894\}$$

Being different from 0, all three points are actual inflection points. f is not defined where its denominator is 0:

```
>> Solve[Denominator[f[x]] == 0, x]
```

$$\left\{ \left\{ x \rightarrow -\frac{3}{2} - \frac{I}{2}\sqrt{11} \right\}, \left\{ x \rightarrow -\frac{3}{2} + \frac{I}{2}\sqrt{11} \right\} \right\}$$

These are non-real numbers, consequently f is defined on all real numbers. The behaviour of f at the boundaries of its definition:

```
>> Limit[f[x], x -> Infinity]
```


$$0$$

```
>> Limit[f[x], x -> -Infinity]
```

$$0$$

Finally, let's plot f:

```
>> Plot[f[x], {x, -8, 6}]
```



### Linear algebra

Let's consider the matrix

```
>> A = {{1, 1, 0}, {1, 0, 1}, {0, 1, 1}};
```

```
>> MatrixForm[A]

$$\begin{pmatrix} 1 & 1 & 0 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{pmatrix}$$

```

We can compute its eigenvalues and eigenvectors:

```
>> Eigenvalues[A]
{2, -1, 1}

>> Eigenvectors[A]
{{1, 1, 1}, {1, -2, 1}, {-1, 0, 1}}
```

This yields the diagonalization of A:

```
>> T = Transpose[Eigenvectors[A]];
MatrixForm[T]

$$\begin{pmatrix} 1 & 1 & -1 \\ 1 & -2 & 0 \\ 1 & 1 & 1 \end{pmatrix}$$


>> Inverse[T] . A . T // MatrixForm

$$\begin{pmatrix} 2 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$


>> % == DiagonalMatrix[Eigenvalues[A]]
True
```

We can solve linear systems:

```
>> LinearSolve[A, {1, 2, 3}]
{0, 1, 2}

>> A . %
{1, 2, 3}
```

In this case, the solution is unique:

```
>> NullSpace[A]
{}
```

Let's consider a singular matrix:

```
>> B = {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}};

>> MatrixRank[B]
2

>> s = LinearSolve[B, {1, 2, 3}]
 $\left\{-\frac{1}{3}, \frac{2}{3}, 0\right\}$ 

>> NullSpace[B]
{{1, -2, 1}}
```

```
>> B . (RandomInteger[100] * %[[1]] + s)
{1, 2, 3}
```

## Dice

Let's play with dice in this example. A Dice object shall represent the outcome of a series of rolling a dice with six faces, e.g.:

```
>> Dice[1, 6, 4, 4]
Dice[1, 6, 4, 4]
```

Like in most games, the ordering of the individual throws does not matter. We can express this by making Dice Orderless:


```
>> SetAttributes[Dice, Orderless]

>> Dice[1, 6, 4, 4]
Dice[1, 4, 4, 6]
```

A dice object shall be displayed as a rectangle with the given number of points in it, positioned like on a traditional dice:

```
>> Format[Dice[n_Integer?(1 <= # <= 6 &)] := Block[{p = 0.2, r = 0.05}, Graphics[{EdgeForm[Black], White, Rectangle[], Black, EdgeForm[], If[OddQ[n], Disk[{0.5, 0.5}, r], If[MemberQ[{2, 3, 4, 5, 6}, n], Disk[{p, p}, r], If[MemberQ[{2, 3, 4, 5, 6}, n], Disk[{1 - p, 1 - p}, r], If[MemberQ[{4, 5, 6}, n], Disk[{p, 1 - p}, r], If[MemberQ[{4, 5, 6}, n], Disk[{1 - p, p}, r], If[n === 6, {Disk[{p, 0.5}, r], Disk[{1 - p, 0.5}, r}]}], ImageSize -> Tiny]]


>> Dice[1]
```



The empty series of dice shall be displayed as an empty dice:

```
>> Format[Dice[]] := Graphics[{EdgeForm[Black], White, Rectangle[]}, ImageSize -> Tiny]
```


```
>> Dice[]
```



Any non-empty series of dice shall be displayed as a row of individual dice:

```
>> Format[Dice[d___Integer?(1 <= #
  <= 6 &)]] := Row[Dice /@ {d}]
```

```
>> Dice[1, 6, 4, 4]
```



Note that *Mathics* will automatically sort the given format rules according to their “generality”, so the rule for the empty dice does not get overridden by the rule for a series of dice. We can still see the original form by using `InputForm`:

```
>> Dice[1, 6, 4, 4] // InputForm
Dice[1, 4, 4, 6]
```

We want to combine `Dice` objects using the `+` operator:


```
>> Dice[a___] + Dice[b___] ^:= Dice
  [Sequence @@ {a, b}]
```

The `^:=` (`UpSetDelayed`) tells *Mathics* to associate this rule with `Dice` instead of `Plus`, which is protected—we would have to unprotect it first:

```
>> Dice[a___] + Dice[b___] := Dice[
  Sequence @@ {a, b}]
TagPlusinDice[a___]
+ Dice[b___]isProtected.
$Failed
```

We can now combine dice:

```
>> Dice[1, 5] + Dice[3, 2] + Dice
  [4]
```




Let’s write a function that returns the sum of the rolled dice:

```
>> DiceSum[Dice[d___]] := Plus @@ {
  d}

>> DiceSum @ Dice[1, 2, 5]
8
```

And now let’s put some dice into a table:

```
>> Table[{Dice[Sequence @@ d],
  DiceSum @ Dice[Sequence @@ d]},
  {d, {{1, 2}, {2, 2}, {2, 6}}}]
// TableForm
```



It is not very sophisticated from a mathematical point of view, but it’s beautiful.



## 5. Django-based Web Interface

In the future we plan on providing an interface to Jupyter as a separate package. However currently as part *Mathics*, we distribute a browser-based interface using Django 3.1. Since a Jupyter-based interface seems preferable to the home-grown interface described here, it is doubtful whether there will be future improvements to the this interface.

When you enter Mathics in the top after the Mathics logo and the word “Mathics” you’ll see a *menubar*.

It looks like this:



### Contents

---

Saving and Loading  
Worksheets . . . . 25

Persistence of Mathics  
Definitions in a  
Session . . . . . 26

Keyboard Commands . 26

---

### Saving and Loading Worksheets

<subsection title=“Saving Worksheets”>


Worksheets exist in the browser window only and are not stored on the server, by default. To save all your queries and results, use the *Save* button which is the middle graphic of the menu bar. It looks like this:



Depending on browser, desktop, and OS-settings, the “Ctrl+S” key combination may do the same thing.

<subsection title=“Loading Worksheets”>

Saved worksheets can be loaded again using the *File Open* button which is the left-most button in the menu bar. It looks like this:



Depending on browser, desktop, and OS-settings, the “Ctrl+O” key combination may do the same thing.

### Persistence of Mathics Definitions in a Session

When you use the Django-based Web interface of *Mathics*, a browser session is created. Cookies have to be enabled to allow this. Your session holds a key which is used to access your definitions that are stored in a database on the server. As long as you don’t clear the cookies in your browser, your definitions will remain even when you close and re-open the browser.

This implies that you should not store sensitive, private information in *Mathics* variables when using the online Web interface. In addition to their values being stored in a database on the server, your queries might be saved for debugging purposes. However, the fact that they are transmitted over plain HTTP should make you aware that you should not transmit any sensitive information. When you want to do calculations with that kind of stuff, simply install *Mathics* locally!

If you are using a public terminal, to erase all your definitions and close the browser window. When you use *Mathics* in a browser, use the command `Quit []` or its alias, `Exit []`.

Normally, when you reload the current page in a browser using the default url, e.g `http://localhost:8000`, all of the previous in-

put and output disappears, even though definitions as described above do not, unless Quit [] or Exit [] is entered as described above.

However if you want a URL that will that records the input entered the *Generate Input Hash* button does this. The button looks like this:



For example, assuming you have a *Mathics* server running at port 8000 on localhost, and you enter the url `http://localhost:8000/#cXVlcmllcz14`, you should see a single line of input containing `x` entered.

Of course, what the value of this is when evaluated depends on whether `x` has been previously defined.

## Keyboard Commands

There are some keyboard commands you can use in the Django-based Web interface of *Mathics*.

### Shift+Return

This evaluates the current cell (the most important one, for sure). On the right-hand side you may also see an "=" button which can be clicked to do the same thing.

### Ctrl+D

This moves the cursor over to the documentation pane on the right-hand side. From here you can preform a search for a pre-defined *Mathics* function, or symbol. Clicking on the "?" symbol on the right-hand side does the same thing.

### Ctrl+C

This moves the cursor back to document code pane area where you type *Mathics* expressions

### Ctrl+S

Save worksheet

### Ctrl+O

Open worksheet

Keyboard commands behavior depends the browser used, the operating system, desktop settings, and customization. We hook into the desktop "Open the current document" and "Save the current document" functions that many desktops provide. For example see: [https://help.ubuntu.com/community/KeyboardShortcuts#Finding\\_keyboard\\_shortcuts](https://help.ubuntu.com/community/KeyboardShortcuts#Finding_keyboard_shortcuts)

Often, these shortcut keyboard command are only recognized when a textfield has focus; otherwise, the browser might do some browser-specific actions, like setting a bookmark etc.

## **Part II.**

# **Reference of Built-in Symbols**

# I. Evaluation

## Contents

---

Evaluate . . . . .	28	In . . . . .	29	\$RecursionLimit . . . . .	30
\$HistoryLength . . . . .	28	\$IterationLimit . . . . .	29	ReleaseHold . . . . .	30
Hold . . . . .	28	\$Line . . . . .	29	Sequence . . . . .	31
HoldComplete . . . . .	29	Out . . . . .	30	Unevaluated . . . . .	31
HoldForm . . . . .	29	Quit . . . . .	30		

---

## Evaluate

`Evaluate[expr]`  
forces evaluation of *expr*, even if it occurs  
inside a held argument or a `Hold` form.

Create a function *f* with a held argument:

```
>> SetAttributes[f, HoldAll]
```

```
>> f[1 + 2]
f[1 + 2]
```

`Evaluate` forces evaluation of the argument,  
even though *f* has the `HoldAll` attribute:

```
>> f[Evaluate[1 + 2]]
f[3]
```

```
>> Hold[Evaluate[1 + 2]]
Hold[3]
```

```
>> HoldComplete[Evaluate[1 + 2]]
HoldComplete[Evaluate[1 + 2]]
```

```
>> Evaluate[Sequence[1, 2]]
Sequence[1, 2]
```

## \$HistoryLength

`$HistoryLength`  
specifies the maximum number of `In` and  
`Out` entries.

```
>> $HistoryLength
100
```

```
>> $HistoryLength = 1;
```

```
>> 42
```

```
42
```

```
>> %
```

```
42
```

```
>> %%
```

```
%3
```

```
>> $HistoryLength = 0;
```

```
>> 42
```

```
42
```

```
>> %
```

```
%7
```

## Hold

`Hold[expr]`  
prevents *expr* from being evaluated.

```
>> Attributes[Hold]
{HoldAll, Protected}
```

## HoldComplete

`HoldComplete[expr]`  
prevents *expr* from being evaluated, and  
also prevents `Sequence` objects from be-  
ing spliced into argument lists.

```
>> Attributes[HoldComplete]
{HoldAllComplete, Protected}
```

## HoldForm

`HoldForm[expr]`  
is equivalent to `Hold[expr]`, but prints as *expr*.

```
>> HoldForm[1 + 2 + 3]
1 + 2 + 3
```

`HoldForm` has attribute `HoldAll`:

```
>> Attributes[HoldForm]
{HoldAll, Protected}
```

## In

`In[k]`  
gives the *k*th line of input.

```
>> x = 1
1
>> x = x + 1
2
>> Do[In[2], {3}]
>> x
5
>> In[-1]
5
>> Definition[In]
Attributes[In] = {Protected}
In[6] = Definition[In]
In[5] = In[-1]
In[4] = x
In[3] = Do[In[2], {3}]
In[2] = x = x + 1
In[1] = x = 1
```

## \$IterationLimit

`$IterationLimit`  
specifies the maximum number of times  
a reevaluation of an expression may hap-  
pen.

Calculations terminated by `$IterationLimit`  
return `$Aborted`:

```
> $IterationLimit = 1000 # FIX Later # #> Clear-
All[f]; # #> f[x_, 0] := x; f[x_, n_] := Module[{y =
x + 1}, f[y, n - 1]]; # #> Block[{$IterationLimit =
20}, f[0, 100]] # = 100 # #> ClearAll[f];
```

## \$Line

`$Line`  
holds the current input line number.

```
>> $Line
1
>> $Line
2
>> $Line = 12;
>> 2 * 5
10
>> Out[13]
10
>> $Line = -1;
Non - negative integer expected.
```

## Out

`Out[k]`  
*%k*  
gives the result of the *k*th input line.  
*%*, *%%*, etc.  
gives the result of the previous input line,  
of the line before the previous input line,  
etc.

```
>> 42
42
>> %
42
```

```
>> 43;

>> %
43

>> 44
44

>> %1
42

>> %%
44

>> Hold[Out[-1]]
Hold[%]

>> Hold[%4]
Hold[%4]

>> Out[0]
Out[0]
```

## Quit

```
Quit[]
    Terminates the Mathics session.
Quit[n]
    Terminates the mathics session with exit
    code n.
```

```
Exit[]
    Terminates the Mathics session.
Exit[n]
    Terminates the mathics session with exit
    code n.
```

## \$RecursionLimit

```
$RecursionLimit
    specifies the maximum allowable recursion
    depth after which a calculation is terminated.
```

Calculations terminated by \$RecursionLimit return \$Aborted:

```
>> a = a + a
Recursiondepthof200exceeded.
$Aborted
```

```
>> $RecursionLimit
200

>> $RecursionLimit = x;
Cannotset$RecursionLimittox;valuemustbeanintegerbetween

>> $RecursionLimit = 512
512

>> a = a + a
Recursiondepthof512exceeded.
$Aborted
```

## ReleaseHold

```
ReleaseHold[expr]
    removes any Hold, HoldForm,
    HoldPattern or HoldComplete head
    from expr.
```

```
>> x = 3;

>> Hold[x]
Hold[x]

>> ReleaseHold[Hold[x]]
3

>> ReleaseHold[y]
y
```

## Sequence

```
Sequence[x1, x2, ...]
    represents a sequence of arguments to a
    function.
```

Sequence is automatically spliced in, except when a function has attribute SequenceHold (like assignment functions).

```
>> f[x, Sequence[a, b], y]
f[x, a, b, y]

>> Attributes[Set]
{HoldFirst, Protected, SequenceHold}

>> a = Sequence[b, c];

>> a
Sequence[b, c]
```

Apply Sequence to a list to splice in arguments:

```
>> list = {1, 2, 3};  
  
>> f[Sequence @@ list]  
f[1, 2, 3]
```

Inside Hold or a function with a held argument, Sequence is spliced in at the first level of the argument:

```
>> Hold[a, Sequence[b, c], d]  
Hold[a, b, c, d]
```

If Sequence appears at a deeper level, it is left unevaluated:

```
>> Hold[{a, Sequence[b, c], d}]  
Hold[{a, Sequence[b, c], d}]
```

However, unevaluated sequences are kept:

```
>> g[Unevaluated[Sequence[a, b, c]]]  
g[Unevaluated[Sequence[a, b, c]]]
```

## Unevaluated

`Unevaluated[expr]`  
temporarily leaves *expr* in an unevaluated form when it appears as a function argument.

Unevaluated is automatically removed when function arguments are evaluated:

```
>> Sqrt[Unevaluated[x]]  
 $\sqrt{x}$   
  
>> Length[Unevaluated[1+2+3+4]]  
4
```

Unevaluated has attribute HoldAllComplete:

```
>> Attributes[Unevaluated]  
{HoldAllComplete, Protected}
```

Unevaluated is maintained for arguments to non-executed functions:

```
>> f[Unevaluated[x]]  
f[Unevaluated[x]]
```

Likewise, its kept in flattened arguments and sequences:

```
>> Attributes[f] = {Flat};  
  
>> f[a, Unevaluated[f[b, c]]]  
f[a, Unevaluated[b], Unevaluated[c]]  
  
>> g[a, Sequence[Unevaluated[b],  
Unevaluated[c]]]  
g[a, Unevaluated[b], Unevaluated[c]]
```

## II. Control Statements

### Contents

---

Abort . . . . .	32	FixedPoint . . . . .	33	NestWhile . . . . .	35
Break . . . . .	32	FixedPointList . . . . .	34	Return . . . . .	35
Catch . . . . .	32	For . . . . .	34	Switch . . . . .	35
CompoundExpression (;) . . . . .	33	If . . . . .	34	Throw . . . . .	35
Continue . . . . .	33	Interrupt . . . . .	34	Which . . . . .	36
Do . . . . .	33	Nest . . . . .	34	While . . . . .	36
		NestList . . . . .	35		

---

### Abort

**Abort []**  
aborts an evaluation completely and returns \$Aborted.

```
>> Print["a"]; Abort[]; Print["b"]
a
$Aborted
```

### Break

**Break []**  
exits a For, While, or Do loop.

```
>> n = 0;

>> While[True, If[n>10, Break[]]; n
    =n+1]

>> n
11
```

### Catch

**Catch ['expr']**  
returns the argument of the first Throw generated in the evaluation of expr.

**Catch ['expr', 'form']**  
returns value from the first Throw['value','tag'] for which form matches 'tag'.

**Catch ['expr', 'form', 'f']**  
returns the argument of the first 'Throw' generated in the evaluation of 'expr'.

Exit to the enclosing Catch as soon as Throw is evaluated: « Catch[r; s; Throw[t]; u; v ] = t

Define a function that can “throw an exception”:  
« f[x\_] := If[x > 12, Throw[overflow], x!] = ...

The result of Catch is just what is thrown by Throw:  
« Catch[f[1] + f[15]] = overflow « Catch[f[1]+f[4]] = 24

### CompoundExpression (;)

**CompoundExpression [e1, e2, ...]**  
e1; e2; ...  
evaluates its arguments in turn, returning the last result.

```
>> a; b; c; d
d
```

If the last argument is omitted, Null is taken:



```
>> a;
```

## Continue

`Continue[]`  
continues with the next iteration in a `For`, `While`, or `Do` loop.

```
>> For[i=1, i<=8, i=i+1, If[Mod[i,2] == 0, Continue[]]; Print[i]]
1
3
5
7
```

## Do

`Do[expr, {max}]`  
evaluates *expr* *max* times.

`Do[expr, {i, max}]`  
evaluates *expr* *max* times, substituting *i* in *expr* with values from 1 to *max*.

`Do[expr, {i, min, max}]`  
starts with *i* = *max*.

`Do[expr, {i, min, max, step}]`  
uses a step size of *step*.

`Do[expr, {i, {i1, i2, ...}}]`  
uses values *i1*, *i2*, ... for *i*.

`Do[expr, {i, imin, imax}, {j, jmin, jmax}, ...]`  
evaluates *expr* for each *j* from *jmin* to *jmax*, for each *i* from *imin* to *imax*, etc.

```
>> Do[Print[i], {i, 2, 4}]
2
3
4

>> Do[Print[{i, j}], {i,1,2}, {j,3,5}]
{1,3}
{1,4}
{1,5}
{2,3}
{2,4}
{2,5}
```

You can use `Break[]` and `Continue[]` inside `Do`:

```
>> Do[If[i > 10, Break[], If[Mod[i,2] == 0, Continue[]]; Print[i]], {i, 5, 20}]
5
7
9
```

## FixedPoint

`FixedPoint[f, expr]`  
starting with *expr*, iteratively applies *f* until the result no longer changes.

`FixedPoint[f, expr, n]`  
performs at most *n* iterations.

```
>> FixedPoint[Cos, 1.0]
0.739085

>> FixedPoint[#+1 &, 1, 20]
21
```

## FixedPointList

`FixedPointList[f, expr]`  
starting with *expr*, iteratively applies *f* until the result no longer changes, and returns a list of all intermediate results.

`FixedPointList[f, expr, n]`  
performs at most *n* iterations.

```
>> FixedPointList[Cos, 1.0, 4]
{1., 0.540302, 0.857~
~553, 0.65429, 0.79348}
```

Observe the convergence of Newton's method for approximating square roots:

```
>> newton[n_] := FixedPointList[.5(# + n/#)&, 1.];

>> newton[9]
{1., 5., 3.4, 3.02353, 3.00009, 3., 3., 3.}
```


Plot the "hailstone" sequence of a number:

```
>> collatz[1] := 1;

>> collatz[x_ ? EvenQ] := x / 2;

>> collatz[x_] := 3 x + 1;
```

```
>> list = FixedPointList[collatz,
14]
{14, 7, 22, 11, 34, 17, 52, 26, 13,
40, 20, 10, 5, 16, 8, 4, 2, 1, 1}
```



```
>> ListLinePlot[list]
```

## For

`For[start, test, incr, body]`  
 evaluates *start*, and then iteratively *body*  
 and *incr* as long as *test* evaluates to True.  
`For[start, test, incr]`  
 evaluates only *incr* and no *body*.  
`For[start, test]`  
 runs the loop without any body.

Compute the factorial of 10 using For:

```
>> n := 1

>> For[i=1, i<=10, i=i+1, n = n * i
]

>> n
3 628 800

>> n == 10!
True
```

## If

`If[cond, pos, neg]`  
 returns *pos* if *cond* evaluates to True, and  
*neg* if it evaluates to False.  
`If[cond, pos, neg, other]`  
 returns *other* if *cond* evaluates to neither  
 True nor False.  
`If[cond, pos]`  
 returns Null if *cond* evaluates to False.

```
>> If[1<2, a, b]
a
```

If the second branch is not specified, Null is taken:

```
>> If[1<2, a]
a

>> If[False, a] //FullForm
Null
```

You might use comments (inside (\* and \*)) to make the branches of If more readable:

```
>> If[a, (*then*)b, (*else*)c];
```

## Interrupt

`Interrupt[]`  
 Interrupt an evaluation and returns  
 \$Aborted.

```
>> Print["a"]; Interrupt[]; Print["
b"]
a
$Aborted
```

## Nest

`Nest[f, expr, n]`  
 starting with *expr*, iteratively applies *f* *n*  
 times and returns the final result.

```
>> Nest[f, x, 3]
f[f[f[x]]]

>> Nest[(1+#)^2 &, x, 2]
(1 + (1 + x)2)2
```

## NestList

`NestList[f, expr, n]`  
 starting with *expr*, iteratively applies *f* *n*  
 times and returns a list of all intermedi-  
 ate results.

```
>> NestList[f, x, 3]
{x, f[x], f[f[x]], f[f[f[x]]]}
```


```
>> NestList[2 # &, 1, 8]
{1, 2, 4, 8, 16, 32, 64, 128, 256}
```

Chaos game rendition of the Sierpinski triangle:

```
>> vertices = {{0,0}, {1,0}, {.5,
.5 Sqrt[3]}};

>> points = NestList[.5(vertices[[
RandomInteger[{1,3}] ] + #)&,
{0.,0.}, 2000];

>> Graphics[Point[points],
ImageSize->Small]
```



## NestWhile

`NestWhile[f, expr, test]`  
applies a function *f* repeatedly on an expression *expr*, until applying *test* on the result no longer yields True.

`NestWhile[f, expr, test, m]`  
supplies the last *m* results to *test* (default value: 1).

`NestWhile[f, expr, test, All]`  
supplies all results gained so far to *test*.

Divide by 2 until the result is no longer an integer:

```
>> NestWhile[#/2&, 10000, IntegerQ]
625
2
```

## Return

`Return[expr]`  
aborts a function call and returns *expr*.

```
>> f[x_] := (If[x < 0, Return[0]];
x)

>> f[-1]
0
```

```
>> Do[If[i > 3, Return[]]; Print[i
], {i, 10}]
```

```
1
2
3
```

Return only exits from the innermost control flow construct.

```
>> g[x_] := (Do[If[x < 0, Return
[0]], {i, {2, 1, 0, -1}}]; x)

>> g[-1]
-1
```

## Switch

`Switch[expr, pattern1, value1, pattern2, value2, ...]`  
yields the first *value* for which *expr* matches the corresponding *pattern*.

```
>> Switch[2, 1, x, 2, y, 3, z]
y
```

```
>> Switch[5, 1, x, 2, y]
Switch[5, 1, x, 2, y]
```

```
>> Switch[5, 1, x, 2, y, _, z]
z
```

```
>> Switch[2, 1]
Switch called with 2 arguments. Switch must be called with an odd number of arguments.
Switch[2, 1]
```

## Throw

`Throw['value']`  
stops evaluation and returns 'value' as the value of the nearest enclosing `Catch`.

`Catch['value', 'tag']`  
is caught only by 'Catch[expr, form]', where tag matches form.

Using Throw can affect the structure of what is returned by a function:

```
« NestList[#^2 + 1 &, 1, 7] = ... «
Catch[NestList[If[# > 1000, Throw[#, #^2 + 1] &,
1, 7]] = 458330 « Throw[1] = Null
```

## Which

```
Which[cond1, expr1, cond2, expr2, ...]  
  yields expr1 if cond1 evaluates to True,  
  expr2 if cond2 evaluates to True, etc.
```

```
>> n = 5;  
  
>> Which[n == 3, x, n == 5, y]  
y  
  
>> f[x_] := Which[x < 0, -x, x ==  
0, 0, x > 0, x]  
  
>> f[-3]  
3
```

If no test yields True, Which returns Null:

```
>> Which[False, a]
```

If a test does not evaluate to True or False, evaluation stops and a Which expression containing the remaining cases is returned:

```
>> Which[False, a, x, b, True, c]  
Which[x, b, True, c]
```

Which must be called with an even number of arguments:

```
>> Which[a, b, c]  
Whichcalledwith3arguments.  
Which[a, b, c]
```

## While

```
While[test, body]  
  evaluates body as long as test evaluates to  
  True.  
While[test]  
  runs the loop without any body.
```

Compute the GCD of two numbers:

```
>> {a, b} = {27, 6};  
  
>> While[b != 0, {a, b} = {b, Mod[a,  
  , b]}];  
  
>> a  
3
```

# III. Date and Time

## Contents

<code>AbsoluteTime</code> . . . . .	37	<code>DateString</code> . . . . .	39	<code>TimeConstrained</code> . . . .	40
<code>AbsoluteTiming</code> . . . . .	37	<code>\$DateStringFormat</code> . . .	39	<code>TimeRemaining</code> . . . . .	40
<code>DateDifference</code> . . . . .	38	<code>EasterSunday</code> . . . . .	39	<code>TimeUsed</code> . . . . .	40
<code>DateList</code> . . . . .	38	<code>Pause</code> . . . . .	39	<code>\$TimeZone</code> . . . . .	40
<code>DatePlus</code> . . . . .	38	<code>SessionTime</code> . . . . .	39	<code>Timing</code> . . . . .	40
		<code>\$SystemTimeZone</code> . . .	39		

## AbsoluteTime

`AbsoluteTime[]`  
gives the local time in seconds since epoch January 1, 1900, in your time zone.

`AbsoluteTime[{y, m, d, h, m, s}]`  
gives the absolute time specification corresponding to a date list.

`AbsoluteTime["string"]`  
gives the absolute time specification for a given date string.

`AbsoluteTime[{"string", {e1, e2, ...}}]`  
takes the date string to contain the elements "ei".

```
>> AbsoluteTime[]
3.82229 × 109

>> AbsoluteTime[{2000}]
3 155 673 600

>> AbsoluteTime[{"01/02/03", {"Day", "Month", "YearShort"}}]
3 253 046 400

>> AbsoluteTime["6 June 1991"]
2 885 155 200

>> AbsoluteTime[{"6-6-91", {"Day", "Month", "YearShort"}}]
2 885 155 200
```

## AbsoluteTiming

`AbsoluteTiming[expr]`  
evaluates *expr*, returning a list of the absolute number of seconds in real time that have elapsed, together with the result obtained.

```
>> AbsoluteTiming[50!]
{0.000329494, 30 414 093 ~
~201 713 378 043 612 608 166 ~
~064 768 844 377 641 568 ~
~960 512 000 000 000 000}

>> Attributes[AbsoluteTiming]
{HoldAll, Protected}
```

## DateDifference

`DateDifference[date1, date2]`  
returns the difference between *date1* and *date2* in days.

`DateDifference[date1, date2, unit]`  
returns the difference in the specified *unit*.

`DateDifference[date1, date2, {unit1, unit2, ...}]`  
represents the difference as a list of integer multiples of each *unit*, with any remainder expressed in the smallest unit.

```
>> DateDifference[{2042, 1, 4},
{2057, 1, 1}]
5476

>> DateDifference[{1936, 8, 14},
{2000, 12, 1}, "Year"]
{64.3425, Year}

>> DateDifference[{2010, 6, 1},
{2015, 1, 1}, "Hour"]
{40200, Hour}

>> DateDifference[{2003, 8, 11},
{2003, 10, 19}, {"Week", "Day"}]
{{9, Week}, {6, Day}}
```

## DateList

**DateList[]**  
returns the current local time in the form  
{year, month, day, hour, minute, second}.

**DateList[time]**  
returns a formatted date for the number  
of seconds *time* since epoch Jan 1 1900.

**DateList[{y, m, d, h, m, s}]**  
converts an incomplete date list to the  
standard representation.

**DateString[string]**  
returns the formatted date list of a date  
string specification.

**DateString[string, {e1, e2, ...}]**  
returns the formatted date list of a *string*  
obtained from elements *ei*.

```
>> DateList[0]
{1900, 1, 1, 0, 0, 0.}

>> DateList[3155673600]
{2000, 1, 1, 0, 0, 0.}

>> DateList[{2003, 5, 0.5, 0.1,
0.767}]
{2003, 4, 30, 12, 6, 46.02}

>> DateList[{2012, 1, 300., 10}]
{2012, 10, 26, 10, 0, 0.}

>> DateList["31/10/1991"]
{1991, 10, 31, 0, 0, 0.}
```

```
>> DateList["1/10/1991"]
The interpretation of 1/10/
1991 is ambiguous.
{1991, 1, 10, 0, 0, 0.}

>> DateList[{"31/10/91", {"Day", "
Month", "YearShort"}}]
{1991, 10, 31, 0, 0, 0.}

>> DateList[{"31 10/91", {"Day", "
", "Month", "/"}, "YearShort"}}]
{1991, 10, 31, 0, 0, 0.}
```

If not specified, the current year assumed

```
>> DateList[{"5/18", {"Month", "Day
"}}]
{2021, 5, 18, 0, 0, 0.}
```

## DatePlus

**DatePlus[date, n]**  
finds the date *n* days after *date*.

**DatePlus[date, {n, "unit"}]**  
finds the date *n* units after *date*.

**DatePlus[date, {{n1, "unit1"}, {n2, "
unit2"}, ...}]**  
finds the date which is *n<sub>i</sub>* specified units  
after *date*.

**DatePlus[n]**  
finds the date *n* days after the current  
date.

**DatePlus[offset]**  
finds the date which is offset from the  
current date.

Add 73 days to Feb 5, 2010:

```
>> DatePlus[{2010, 2, 5}, 73]
{2010, 4, 19}
```

Add 8 weeks and 1 day to March 16, 1999:

```
>> DatePlus[{2010, 2, 5}, {{8, "
Week"}, {1, "Day"}}]
{2010, 4, 3}
```

## DateString

`DateString[]`  
returns the current local time and date as a string.

`DateString[elem]`  
returns the time formatted according to *elems*.

`DateString[{e1, e2, ...}]`  
concatenates the time formatted according to elements *ei*.

`DateString[time]`  
returns the date string of an `AbsoluteTime`.

`DateString[{y, m, d, h, m, s}]`  
returns the date string of a date list specification.

`DateString[string]`  
returns the formatted date string of a date string specification.

`DateString[spec, elems]`  
formats the time in turns of *elems*. Both *spec* and *elems* can take any of the above formats.

The current date and time:

```
>> DateString[];

>> DateString[{1991, 10, 31, 0, 0},
  {"Day", " ", "MonthName", " ",
  "Year"}]
31 October 1991

>> DateString[{2007, 4, 15, 0}]
Sun 15 Apr 2007 00:00:00

>> DateString[{1979, 3, 14}, {"
DayName", " ", "Month", "-", "
YearShort"}]
Wednesday 03-79
```

Non-integer values are accepted too:

```
>> DateString[{1991, 6, 6.5}]
Thu 6 Jun 1991 12:00:00
```

## \$DateStringFormat

`$DateStringFormat`  
gives the format used for dates generated by `DateString`.

```
>> $DateStringFormat
{DateTimeShort}
```

## EasterSunday

`EasterSunday[year]`  
returns the date of the Gregorian Easter Sunday as {year, month, day}.

```
>> EasterSunday[2000]
{2000, 4, 23}

>> EasterSunday[2030]
{2030, 4, 21}
```

## Pause

`Pause[n]`  
pauses for *n* seconds.

```
>> Pause[0.5]
```

## SessionTime

`SessionTime[]`  
returns the total time in seconds since this session started.

```
>> SessionTime[]
80.4442
```

## \$SystemTimeZone

`$SystemTimeZone`  
gives the current time zone for the computer system on which Mathics is being run.

```
>> $SystemTimeZone
-5.
```

## TimeConstrained

`TimeConstrained[expr, t]`  
evaluates *expr*, stopping after *t* seconds.  
`TimeConstrained[expr, t, failexpr]`  
returns *failexpr* if the time constraint is not met.

```
>> TimeConstrained[Integrate[Sin[x]
^1000000,x],1]
$Aborted

>> TimeConstrained[Integrate[Sin[x]
^1000000,x], 1, Integrate[Cos[x]
,x]]
Sin[x]

>> s=TimeConstrained[Integrate[Sin[
x] ^ 3, x], a]
Numberofsecondsaisnotapositivemachine
— sizednumberorInfinity.

TimeConstrained  $\left[ \int \sin[x]^3 dx, a \right]$ 

>> a=1; s
 $-\cos[x] + \frac{\cos[x]^3}{3}$ 
```

Possible issues: for certain time-consuming functions (like `simplify`) which are based on `sympy` or other libraries, it is possible that the evaluation continues after the timeout. However, at the end of the evaluation, the function will return `$`  
*Aborted* and the results will not affect the state of the mathics kernel.

## TimeRemaining

`TimeRemaining[]`  
Gives the number of seconds remaining until the earliest enclosing `TimeConstrained` will request the current computation to stop.  
`TimeConstrained[expr, t, failexpr]`  
returns *failexpr* if the time constraint is not met.

If `TimeConstrained` is called out of a `TimeConstrained` expression, returns 'Infinity'

```
>> TimeRemaining[]
∞

>> TimeConstrained[1+2; Print[
TimeRemaining[]], 0.9]
0.899228
```

## TimeUsed

`TimeUsed[]`  
returns the total CPU time used for this session, in seconds.

```
>> TimeUsed[]
315.998
```

## \$TimeZone

`$TimeZone`  
gives the current time zone to assume for dates and times.

```
>> $TimeZone
-5.
```

## Timing

`Timing[expr]`  
measures the processor time taken to evaluate *expr*. It returns a list containing the measured time in seconds and the result of the evaluation.

```
>> Timing[50!]
{0.00022684, 30 414 093 201 713 378 ~
~043 612 608 166 064 768 844 377 ~
~641 568 960 512 000 000 000 000}

>> Attributes[Timing]
{HoldAll, Protected}
```



## IV. Graphics (3D)

### Contents

---


Cuboid . . . . .	42	Line3DBox . . . . .	43	Sphere . . . . .	44
Graphics3D . . . . .	43	Point3DBox . . . . .	43	Sphere3DBox . . . . .	44
Graphics3DBox . . . . .	43	Polygon3DBox . . . . .	43		

---

### Cuboid

`Cuboid[{xmin, ymin, zmin}]`  
is a unit cube.  
`Cuboid[{xmin, ymin, zmin}, {xmax,  
ymax, zmax}]`  
represents a cuboid extending from  
{*xmin*, *ymin*, *zmin*} to {*xmax*, *ymax*, *zmax*}.

```
>> Graphics3D[Cuboid[{0, 0, 1}]]
```




```
>> Graphics3D[{Red, Cuboid[{0, 0, 0}, {1, 1, 0.5}], Blue, Cuboid
[{0.25, 0.25, 0.5}, {0.75, 0.75, 1}]}]
```

```
Graphics3DBox[List[StyleBox[Graphics[List[Edge
RGBColor[1, 0, 0], Rectangle[List[0,
0]]], Rule[ImageSize, 16]],
Rule[ImageSizeMultipliers, List[1,
1]]], Polygon3DBox[List[List[List[0.,
0., 0.], List[0., 1., 0.], List[0., 1., 0.5]],
List[List[0., 0., 0.], List[0., 0., 0.5],
List[0., 1., 0.5]], List[List[1., 0.,
0.], List[1., 1., 0.], List[1., 1., 0.5]],
List[List[1., 0., 0.], List[1., 0., 0.5],
List[1., 1., 0.5]], List[List[0., 0.,
0.], List[1., 0., 0.], List[1., 0., 0.5]],
List[List[0., 0., 0.], List[0., 0., 0.5],
List[1., 0., 0.5]], List[List[0., 1.,
0.], List[1., 1., 0.], List[1., 1., 0.5]],
List[List[0., 1., 0.], List[0., 1., 0.5],
List[1., 1., 0.5]], List[List[0., 0.,
0.], List[0., 1., 0.], List[1., 1., 0.]],
List[List[0., 0., 0.], List[1., 0., 0.], List[1.,
1., 0.]], List[List[0., 0., 0.5], List[0., 1.,
0.5], List[1., 1., 0.5]], List[List[0., 0.,
0.5], List[1., 0., 0.5], List[1., 1., 0.5]]],
StyleBox[Graphics[List[EdgeForm[GrayLevel[0]],
RGBColor[0, 0, 1], Rectangle[List[0,
0]]], Rule[ImageSize, 16]],
Rule[ImageSizeMultipliers, List[1, 1]]],
Polygon3DBox[List[List[List[0.25, 0.25
, 0.5], List[0.25, 0.75, 0.5], List[0.25, 0.75
, 1.]], List[List[0.25, 0.25, 0.5], List[0.25,
0.25, 1.], List[0.25, 0.75, 1.]], List[List[
0.75, 0.25, 0.5], List[0.75, 0.75, 0.5], List[
0.75, 0.75, 1.]], List[List[0.75, 0.25, 0.5],
List[0.75, 0.25, 1.], List[0.75, 0.75, 1.]],
List[List[0.25, 0.25, 0.5], List[0.75, 0.25,
0.5], List[0.75, 0.25, 1.]], List[List[0.25,
0.25, 0.5], List[0.25, 0.25, 1.], List[0.75,
0.25, 1.]], List[List[0.25, 0.75, 0.5], List[
0.75, 0.75, 0.5], List[0.75, 0.75, 1.]],
List[List[0.25, 0.75, 0.5], List[0.25, 0.75,
1.], List[0.75, 0.75, 1.]], List[List[0.25
, 0.25, 0.5], List[0.25, 0.75, 0.5], List[
0.75, 0.75, 0.5]], List[List[0.25, 0.25,
0.5], List[0.75, 0.25, 0.5], List[0.75, 0.75,
0.5]], List[List[0.25, 0.25, 1.], List[0.25,
0.75, 1.], List[0.75, 0.75, 1.]], List[List[
0.25, 0.25, 1.], List[0.75, 0.25, 1.], List[
0.75, 0.75, 1.]]], Rule[$OptionSyntax,
Ignore], Rule[AspectRatio, Automatic],
Rule[Axes, False], Rule[AxesStyle,
List[]], Rule[Background, Automatic],
Rule[BoxRatios, Automatic],
Rule[ImageSize, Automatic]
```

## Graphics3D

`Graphics3D[primitives, options]`  
represents a three-dimensional graphic.  
See also the Section “Plotting” for a list of Plot options.

```
>> Graphics3D[Polygon[{0,0,0},
{0,1,1}, {1,0,0}]]]
```



In TeXForm, Graphics3D creates Asymptote figures:

```
>> Graphics3D[Sphere[]] // TeXForm

\begin{asy}
import three;
import solids;
size(6.6667cm, 6.6667cm);
currentprojection=perspective(2.6,-4.8,4.0);
currentlight=light(rgb(0.5,0.5,1),
specular=red, (2,0,2), (2,2,2), (0,2,2));
draw(surface(sphere((0, 0, 0), 1)),
rgb(1,1,1));
draw(((1,-1,-1)-(1,-1,-1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,1,-1)-(1,1,-1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,-1,1)-(1,-1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,1,1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,-1,-1)-(1,1,-1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,-1,-1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,-1,-1)-(1,-1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,-1,-1)-(1,-1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,-1,-1)-(1,-1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,1,-1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw(((1,1,-1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
\end{asy}
```

## Graphics3DBox

## Line3DBox

## Point3DBox

## Polygon3DBox


## Sphere

`Sphere[{x, y, z}]`  
is a sphere of radius 1 centered at the point {x, y, z}.

`Sphere[{x, y, z}, r]`  
is a sphere of radius  $r$  centered at the point {x, y, z}.

`Sphere[{x1, y1, z1}, {x2, y2, z2}, ..., r]`  
is a collection spheres of radius  $r$  centered at the points {x1, y2, z2}, {x2, y2, z2}, ...

```
>> Graphics3D[Sphere[{0, 0, 0}, 1]]
```



```
>> Graphics3D[{Yellow, Sphere[{{-1,
  0, 0}, {1, 0, 0}, {0, 0, Sqrt
[3.]}}], 1]]

Graphics3DBox[List[StyleBox[Graphics[List[EdgeForm[GrayLevel[0]],
RGBColor[1, 1, 0], Rectangle[List[0,
0]]], Rule[ImageSize, 16]],
Rule[ImageSizeMultipliers, List[1,
1]]], Sphere3DBox[List[List[-1, 0, 0],
List[1, 0, 0], List[0, 0, 1.732050807~
~5688772]], 1]], Rule[$OptionSyntax,
Ignore], Rule[AspectRatio, Automatic],
Rule[Axes, False], Rule[AxesStyle,
List[]], Rule[Background, Automatic],
Rule[BoxRatios, Automatic],
Rule[ImageSize, Automatic],
Rule[LabelStyle, List[]], Rule[Lighting,
Automatic], Rule[PlotRange,
Automatic], Rule[PlotRangePadding,
Automatic], Rule[TicksStyle,
List[]], Rule[ViewPoint, List[1.3,
- 2.4, 2.]]]isnotavalidboxstructure.
```

## Sphere3DBox

# V. Input and Output

## Contents

BaseForm . . . . .	45	MessageName (::) . . . . .	48	StyleBox . . . . .	52
BoxData . . . . .	45	NonAssociative . . . . .	48	Subscript . . . . .	52
ButtonBox . . . . .	46	NumberForm . . . . .	49	SubscriptBox . . . . .	52
Center . . . . .	46	Off . . . . .	49	Subsuperscript . . . . .	52
Check . . . . .	46	On . . . . .	49	SubsuperscriptBox . . . . .	52
Format . . . . .	46	OutputForm . . . . .	49	Superscript . . . . .	52
FullForm . . . . .	46	Postfix (//) . . . . .	49	SuperscriptBox . . . . .	52
General . . . . .	47	Precedence . . . . .	50	SympyForm . . . . .	52
Grid . . . . .	47	Prefix (@) . . . . .	50	Syntax . . . . .	52
GridBox . . . . .	47	Print . . . . .	50	TableForm . . . . .	53
Infix . . . . .	47	PythonForm . . . . .	50	TagBox . . . . .	53
InputForm . . . . .	47	Quiet . . . . .	51	TeXForm . . . . .	53
InterpretationBox . . . . .	47	Right . . . . .	51	TemplateBox . . . . .	53
Left . . . . .	47	Row . . . . .	51	TextData . . . . .	53
MakeBoxes . . . . .	48	RowBox . . . . .	51	ToBoxes . . . . .	53
MathMLForm . . . . .	48	StandardForm . . . . .	51	TooltipBox . . . . .	53
MatrixForm . . . . .	48	StringForm . . . . .	51	\$UseSansSerif . . . . .	54
Message . . . . .	48	Style . . . . .	52		

## BaseForm

BaseForm[expr, n]  
prints numbers in expr in base n.

```
>> BaseForm[33, 2]
100 0012

>> BaseForm[234, 16]
ea16

>> BaseForm[12.3, 2]
1 100.010011001100110012

>> BaseForm[-42, 16]
-2a16

>> BaseForm[x, 2]
x

>> BaseForm[12, 3] // FullForm
BaseForm[12, 3]
```

Bases must be between 2 and 36:

```
>> BaseForm[12, -3]
Positivemachine
-sizedintegerexpectedatposition2inBaseForm[12,
-3].
MakeBoxes[BaseForm[12, -3],
StandardForm]isnotavalidboxstructure.

>> BaseForm[12, 100]
Requestedbase100mustbebetween2and36.
MakeBoxes[BaseForm[12, 100],
StandardForm]isnotavalidboxstructure.
```

## BoxData

BoxData[...]  
is a low-level representation of the contents of a typesetting cell.

## ButtonBox

ButtonBox[boxes]

is a low-level box construct that represents a button in a notebook expression.

## Center

Center

is used with the ColumnAlignments option to Grid or TableForm to specify a centered column.

## Check

Check[expr, failexpr]

evaluates *expr*, and returns the result, unless messages were generated, in which case it evaluates and *failexpr* will be returned.

Check[expr, failexpr, {s1::t1,s2::t2,...}]

checks only for the specified messages.

Return err when a message is generated:

```
>> Check[1/0, err]
      Infiniteexpression1/0encountered.
      err
```

Check only for specific messages:

```
>> Check[Sin[0^0], err, Sin::argx]
      Indeterminateexpression0^0encountered.
      Indeterminate
```

```
>> Check[1/0, err, Power::infy]
      Infiniteexpression1/0encountered.
      err
```

## Format

Format[expr]

holds values specifying how *expr* should be printed.

Assign values to Format to control how particular expressions should be formatted when

printed to the user.

```
>> Format[f[x___]] := Infix[{x}, "~"]
>> f[1, 2, 3]
      1 ~ 2 ~ 3
>> f[1]
      1
```

Raw objects cannot be formatted:

```
>> Format[3] = "three";
      Cannotassigntorawobject3.
```

Format types must be symbols:

```
>> Format[r, a + b] = "r";
      Formattypea + bisnotasymbol.
```

Formats must be attached to the head of an expression:

```
>> f /: Format[g[f]] = "my f";
      Tagfnotfoundortoodeepforanassignedrule.
```

## FullForm

FullForm[expr]

displays the underlying form of *expr*.

```
>> FullForm[a + b * c]
      Plus[a, Times[b, c]]
>> FullForm[2/3]
      Rational[2, 3]
>> FullForm["A string"]
      "A string"
```

## General

General

is a symbol to which all general-purpose messages are assigned.

```
>> General::argr
      '1' called with 1 argument;
      '2' arguments are expected.
>> Message[Rule::argr, Rule, 2]
      Rulecalledwith1argument;2argumentsareexpected.
```

## Grid

`Grid[{{a1, a2, ...}, {b1, b2, ...}, ...}]`  
formats several expressions inside a `GridBox`.

```
>> Grid[{{a, b}, {c, d}}]
      a  b
      c  d
```

## GridBox

`GridBox[{{...}, {...}}]`  
is a box construct that represents a sequence of boxes arranged in a grid.  
# » `MathMLForm[TableForm[{{a,b},{c,d}}]]` # =

...

## Infix

`Infix[expr, oper, prec, assoc]`  
displays *expr* with the infix operator *oper*, with precedence *prec* and associativity *assoc*.

`Infix` can be used with `Format` to display certain forms with user-defined infix notation:

```
>> Format[g[x_, y_]] := Infix[{x, y}, "#", 350, Left]

>> g[a, g[b, c]]
      a#(b#c)

>> g[g[a, b], c]
      a#b#c

>> g[a + b, c]
      (a + b)#c

>> g[a * b, c]
      ab#c

>> g[a, b] + c
      c + a#b

>> g[a, b] * c
      c(a#b)
```

```
>> Infix[{a, b, c}, {"+", "-"}]
      a + b - c
```

## InputForm

`InputForm[expr]`  
displays *expr* in an unambiguous form suitable for input.

```
>> InputForm[a + b * c]
      a + b * c

>> InputForm["A string"]
      "A string"

>> InputForm[f' [x]]
      Derivative[1] [f] [x]

>> InputForm[Derivative[1, 0] [f] [x]]
      Derivative[1, 0] [f] [x]
```

## InterpretationBox

`InterpretationBox[...]`  
is a low-level box construct that displays as boxes but is interpreted on input as *expr*.

## Left

`Left`  
is used with operator formatting constructs to specify a left-associative operator.

## MakeBoxes

`MakeBoxes[expr]`  
is a low-level formatting primitive that converts *expr* to box form, without evaluating it.  
`\( ... \)`  
directly inputs box objects.

String representation of boxes

```
>> \(\mathbf{x} \wedge 2\)\n      SuperscriptBox[x, 2]\n\n>> \(\mathbf{x} \sub 2\)\n      SubscriptBox[x, 2]\n\n>> \(\mathbf{a} \mathbf{+} \mathbf{b} \mathbf{\%} \mathbf{c}\)\n      UnderoverscriptBox[a, b, c]\n\n>> \(\mathbf{a} \mathbf{\&} \mathbf{b} \mathbf{\%} \mathbf{c}\)\n      UnderoverscriptBox[a, c, b]\n\n>> \(\mathbf{x} \mathbf{\&} \mathbf{y} \mathbf{\}\)\n      OverscriptBox[x, y]\n\n>> \(\mathbf{x} \mathbf{\+} \mathbf{y} \mathbf{\}\)\n      UnderscriptBox[x, y]
```

## MathMLForm

`MathMLForm[expr]`  
displays *expr* as a MathML expression.

```
>> MathMLForm[HoldForm[Sqrt[a^3]]]\n      <math display="block"><mstyle\n        mathvariant="sans-serif">\n        <msqrt><msup><mi>a</mi>\n        <mn>3</mn></msup>\n        </msqrt></mstyle></math>\n\n>> MathMLForm[\[Mu]]\n      <math display="block"><mstyle\n        mathvariant="sans-serif">\n        <mi></mi></mstyle></math>
```

# This can causes the TeX to fail # » MathML-  
Form[Graphics[Text[""]]] # = ...  
= ...

## MatrixForm

`MatrixForm[m]`  
displays a matrix *m*, hiding the underlying list structure.

```
>> Array[a, {4, 3}]/MatrixForm\n      \(\begin{matrix} a[1, 1] & a[1, 2] & a[1, 3] \\ a[2, 1] & a[2, 2] & a[2, 3] \\ a[3, 1] & a[3, 2] & a[3, 3] \\ a[4, 1] & a[4, 2] & a[4, 3] \end{matrix}\)
```

## Message

`Message[symbol::msg, expr1, expr2, ...]`  
displays the specified message, replacing placeholders in the message text with the corresponding expressions.

```
>> a::b = "Hello world!"\n      Hello world!\n\n>> Message[a::b]\n      Hellowworld!\n\n>> a::c := "Hello '1', Mr 00'2'!"\n\n>> Message[a::c, "you", 3 + 4]\n      Helloyou, Mr007!
```

## MessageName (::)

`MessageName[symbol, tag]`  
*symbol::tag*  
identifies a message.

`MessageName` is the head of message IDs of the form `symbol::tag`.

```
>> FullForm[a::b]\n      MessageName[a, "b"]
```

The second parameter `tag` is interpreted as a string.

```
>> FullForm[a::"b"]\n      MessageName[a, "b"]
```

## NonAssociative

`NonAssociative`  
is used with operator formatting constructs to specify a non-associative operator.



## NumberForm

`NumberForm[expr, n]`  
prints a real number *expr* with *n*-digits of precision.  
`NumberForm[expr, {n, f}]`  
prints with *n*-digits and *f* digits to the right of the decimal point.

```
>> NumberForm[N[Pi], 10]
3.141592654

>> NumberForm[N[Pi], {10, 5}]
3.14159
```

## Off

`Off[symbol::tag]`  
turns a message off so it is no longer printed.

```
>> Off[Power::infy]

>> 1 / 0
ComplexInfinity

>> Off[Power::indet, Syntax::com]

>> {0 ^ 0,}
{Indeterminate, Null}
```

## On

`On[symbol::tag]`  
turns a message on for printing.

```
>> Off[Power::infy]

>> 1 / 0
ComplexInfinity

>> On[Power::infy]

>> 1 / 0
Infiniteexpression1/0encountered.
ComplexInfinity
```

## OutputForm


`OutputForm[expr]`  
displays *expr* in a plain-text form.

```
>> OutputForm[f'[x]]
f'[x]

>> OutputForm[Derivative[1, 0][f][x]]
Derivative[1, 0][f][x]

>> OutputForm["A string"]
A string

>> OutputForm[Graphics[Rectangle[]]]
```



## Postfix (//)

`x // f`  
is equivalent to `f[x]`.

```
>> b // a
a[b]

>> c // b // a
a[b[c]]
```

The postfix operator `//` is parsed to an expression before evaluation:

```
>> Hold[x // a // b // c // d // e
// f]
Hold[f[e[d[c[b[a[x]]]]]]]
```

## Precedence

`Precedence[op]`  
returns the precedence of the built-in operator *op*.

```
>> Precedence[Plus]
310.

>> Precedence[Plus] < Precedence[
Times]
True
```

Unknown symbols have precedence 670:

```
>> Precedence[f]
670.
```

Other expressions have precedence 1000:

```
>> Precedence[a + b]
1000.
```

## Prefix (@)

$f @ x$   
is equivalent to  $f[x]$ .

```
>> a @ b
a[b]

>> a @ b @ c
a[b[c]]

>> Format[p[x_]] := Prefix[{x},
"[*"]

>> p[3]
*3

>> Format[q[x_]] := Prefix[{x}, "~
", 350]

>> q[a+b]
~ (a + b)

>> q[a*b]
~ ab

>> q[a]+b
b+ ~ a
```

The prefix operator @ is parsed to an expression before evaluation:

```
>> Hold[a @ b @ c @ d @ e @ f @ x]
Hold[a[b[c[d[e[f[x]]]]]]]
```

## Print

`Print[expr, ...]`  
prints each *expr* in string form.

```
>> Print["Hello world!"]
Helloworld!

>> Print["The answer is ", 7 * 6,
"."]
Theansweris42.
```

## PythonForm

`PythonForm[expr]`  
returns an approximate equivalent of *expr* in Python, when that is possible. We assume that Python has sympy imported. No explicit import will be include in the result.

```
>> PythonForm[Infinity]
math.inf

>> PythonForm[Pi]
sympy.pi

>> E // PythonForm
sympy.E

>> {1, 2, 3} // PythonForm
[1, 2, 3]
```

## Quiet

`Quiet[expr, {s1::t1, ...}]`  
evaluates *expr*, without messages {s1::t1, ...} being displayed.  
`Quiet[expr, All]`  
evaluates *expr*, without any messages being displayed.  
`Quiet[expr, None]`  
evaluates *expr*, without all messages being displayed.  
`Quiet[expr, off, on]`  
evaluates *expr*, with messages *off* being suppressed, but messages *on* being displayed.

```
>> a::b = "Hello";

>> Quiet[x+x, {a::b}]
2x

>> Quiet[Message[a::b]; x+x, {a::b}]
2x

>> Message[a::b]; y=Quiet[Message[a::b]; x+x, {a::b}]; Message[a::b]
2x
Hello
Hello
2x

>> Quiet[expr, All, All]
Arguments2and3ofQuiet[expr, All, All]shouldnotbothbeAll.
Quiet[expr, All, All]

>> Quiet[x + x, {a::b}, {a::b}]
InQuiet[x + x, {a::b}, {a::b}]themessagename(s){a::b}appearinboththeli
Quiet[x + x, {a::b}, {a::b}]
```

## Right

`Right`  
is used with operator formatting constructs to specify a right-associative operator.

## Row

`Row[{expr, ...}]`  
formats several expressions inside a `RowBox`.

## RowBox

`RowBox[{...}]`  
is a box construct that represents a sequence of boxes arranged in a horizontal row.

## StandardForm

`StandardForm[expr]`  
displays *expr* in the default form.

```
>> StandardForm[a + b * c]
a + bc

>> StandardForm["A string"]
A string

StandardForm is used by default:

>> "A string"
A string

>> f'[x]
f'[x]
```

## StringForm

`StringForm[str, expr1, expr2, ...]`  
displays the string *str*, replacing placeholders in *str* with the corresponding expressions. *switchon*.

```
>> StringForm["'1' bla '2' blub "'
bla '2'", a, b, c]
a bla b blub c bla b
```

## Style

### StyleBox

`StyleBox[boxes, options]`  
is a low-level representation of boxes to be shown with the specified option settings.  
`StyleBox[boxes, style]`  
uses the option setting for the specified style in the current notebook.

### Subscript

`Subscript[a, i]`  
displays as  $a_i$ .

```
>> Subscript[x,1,2,3] // TeXForm
x_{1,2,3}
```

### SubscriptBox

### Subsuperscript

`Subsuperscript[a, b, c]`  
displays as  $a_b^c$ .

```
>> Subsuperscript[a, b, c] //
TeXForm
a_b^c
```

### SubsuperscriptBox

### Superscript

`Superscript[x, y]`  
displays as  $x^y$ .

```
>> Superscript[x,3] // TeXForm
x^3
```

## SuperscriptBox

### SympyForm

`SympyForm[expr]`  
returns an Sympy *expr* in Python. Sympy is used internally to implement a number of Mathics functions, like Simplify.

```
>> SympyForm[Pi^2]
pi**2

>> E^2 + 3E // SympyForm
exp(2) + 3*E
```

## Syntax

`Syntax`  
is a symbol to which all syntax messages are assigned.

```
>> 1 +
>> Sin[1)
>> ^ 2
>> 1.5‘‘
```


## TableForm

`TableForm[expr]`  
displays *expr* as a table.

```
>> TableForm[Array[a, {3,2}],
TableDepth->1]
{a [1,1], a [1,2]}
{a [2,1], a [2,2]}
{a [3,1], a [3,2]}
```

A table of Graphics:

```
>> Table[Style[Graphics[{EdgeForm[{
Black}], RGBColor[r,g,b],
Rectangle[]}],
ImageSizeMultipliers->{0.2, 1}],
{r,0,1,1/2}, {g,0,1,1/2}, {b
,0,1,1/2}] // TableForm
```



## TagBox

`TagBox[boxes, tag]`  
is a low-level box construct that displays as boxes but is interpreted on input as `expr`

## TeXForm

`TeXForm[expr]`  
displays `expr` using TeX math mode commands.

```
>> TeXForm[HoldForm[Sqrt[a^3]]]
\sqrt{a^3}
```

## TemplateBox

`TemplateBox[{box_1, box_2,...}, tag]`  
is a low-level box structure that parameterizes the display and evaluation of the boxes `box_i`.

## TextData

`TextData[...]`  
is a low-level representation of the contents of a textual cell.

## ToBoxes

`ToBoxes[expr]`  
evaluates `expr` and converts the result to box form.

Unlike `MakeBoxes`, `ToBoxes` evaluates its argument:

```
>> ToBoxes[a + a]
RowBox[{2, a}]

>> ToBoxes[a + b]
RowBox[{a, +, b}]

>> ToBoxes[a ^ b] // FullForm
SuperscriptBox["a", "b"]
```

## TooltipBox

`TooltipBox[{...}]`  
undocumented...

## **\$UseSansSerif**

**\$UseSansSerif**  
controls whether the Web interfaces use a  
Sans-Serif font.

When set True, the output in MathMLForm uses  
SansSerif fonts instead of the standard fonts.

```
>> $UseSansSerif  
True  
  
>> $UseSansSerif = False  
False
```

# VI. Plotting

## Contents


Axis . . . . .	55	Full . . . . .	58	PieChart . . . . .	61
BarChart . . . . .	56	Histogram . . . . .	58	Plot . . . . .	62
Bottom . . . . .	56	ImageSize . . . . .	58	Plot3D . . . . .	63
ColorData . . . . .	56	Joined . . . . .	58	PlotPoints . . . . .	64
ColorDataFunction . .	56	ListLinePlot . . . . .	59	PlotRange . . . . .	64
DensityPlot . . . . .	57	ListPlot . . . . .	59	PolarPlot . . . . .	64
Filling . . . . .	57	Mesh . . . . .	60	Top . . . . .	64
		ParametricPlot . . . . .	60		

## Axis

Axis  
is a possible value for the Filling option.

```
>> ListLinePlot[Table[Sin[x], {x, -5, 5, 0.5}], Filling->Axis]
```


```
>> BarChart[{1, 4, 2}, ChartStyle -> {Red, Green, Blue}]
```




## BarChart

BarChart[{b1, b2 ...}]  
makes a bar chart with lengths b1, b2, ....


```
>> BarChart[{1, 4, 2}]
```




```
>> BarChart[{{1, 2, 3}, {2, 3, 4}}]
```



```
>> BarChart[{{1, 2, 3}, {2, 3, 4}},
  ChartLabels -> {"a", "b", "c"}]
```



```
>> BarChart[{{1, 5}, {3, 4}},
  ChartStyle -> {{EdgeForm[Thin],
  White}, {EdgeForm[Thick], White
  }}]
```



## Bottom

Bottom  
is a possible value for the Filling option.

```
>> ListLinePlot[Table[Sin[x], {x,
  -5, 5, 0.5}], Filling->Bottom]
```

## ColorData


ColorData["name"]  
returns a color function with the given name.

Define a user-defined color function:

```
>> Unprotect[ColorData]; ColorData
["test"] := ColorDataFunction["
test", "Gradients", {0, 1},
Blend[{Red, Green, Blue}, #1]
&]; Protect[ColorData]
```

Compare it to the default color function, LakeColors:

```
>> {DensityPlot[x + y, {x, -1, 1},
  {y, -1, 1}], DensityPlot[x + y,
  {x, -1, 1}, {y, -1, 1},
  ColorFunction->"test"]}
```




## ColorDataFunction

### DensityPlot


DensityPlot[f, {x, xmin, xmax}, {y, ymin, ymax}]  
plots a density plot of  $f$  with  $x$  ranging from  $xmin$  to  $xmax$  and  $y$  ranging from  $ymin$  to  $ymax$ .





```
>> DensityPlot[x ^ 2 + 1 / y, {x,
-1, 1}, {y, 1, 4}]
```




```
>> DensityPlot[1 / x, {x, 0, 1}, {y
, 0, 1}]
```




```
>> DensityPlot[Sqrt[x * y], {x, -1,
1}, {y, -1, 1}]
```



```
>> DensityPlot[1/(x^2 + y^2 + 1), {
x, -1, 1}, {y, -2,2}, Mesh->Full
]
```



```
>> DensityPlot[x^2 y, {x, -1, 1}, {
y, -1, 1}, Mesh->All]
```



## Filling

Filling Top |Bottom|Axis

is a an option to Plot to specify what filling to add under point, curves, and surfaces

```
>> ListLinePlot[Table[Sin[x], {x,
-5, 5, 0.5}], Filling->Axis]
```

## Full

Full

is a possible value for the Mesh and PlotRange options.

Automatic

determined by location or other dimension (default)


Tiny, Small, Medium, Large  
pre defined absolute sizes

## Histogram


Histogram[{x1, x2 ...}]

plots a histogram using the values x1, x2, ....

```
>> Histogram[{3, 8, 10, 100, 1000,
500, 300, 200, 10, 20, 200, 100,
200, 300, 500}]
```



```
>> Histogram[{{1, 2, 10, 5, 50,
20}, {90, 100, 101, 120, 80}}]
```



## ImageSize

ImageSize

is an option that specifies the overall size of an image to display.


Specifications for both width and height can be any of the following:

## Joined

Joined *boolean*

is an option for Plot that gives whether to join points to make lines.

```
>> ListPlot[Table[n ^ 2, {n, 10}],
Joined->True]
```



## ListLinePlot

ListLinePlot[{y1, y2, ...}]

plots a line through a list of y-values, assuming integer x-values 1, 2, 3, ...

ListLinePlot[{x1, y1}, {x2, y2}, ...]


plots a line through a list of x, y pairs.

ListLinePlot[{list1, list2, ...}]


plots several lines.

ListPlot accepts a superset of the Graphics options.

```
>> ListLinePlot[Table[{n, n ^ 0.5},
  {n, 10}]]
```



```
>> ListLinePlot[{{-2, -1}, {-1,
  -1}}]
```




## ListPlot

`ListPlot[{y1, y2, ...}]`  
 plots a list of y-values, assuming integer  
 x-values 1, 2, 3, ...  
`ListPlot[{{x1, y1}, {x2, y2},  
 ...}]`  
 plots a list of x, y pairs.  
`ListPlot[{list1, list2, ...}]`  
 plots several lists of points.

ListPlot accepts a superset of the Graphics options.

```
>> ListPlot[Table[n ^ 2, {n, 10}]]
```




## Mesh


### Mesh

is an option for Plot that specifies the mesh to be drawn. The default is Mesh->None.


```
>> Plot[Sin[Cos[x^2]], {x, -4, 4}, Mesh
  ->All]
```




```
>> Plot[Sin[x], {x, 0, 4 Pi}, Mesh->
  Full]
```




```
>> DensityPlot[Sin[x y], {x, -2,
  2}, {y, -2, 2}, Mesh->Full]
```




```
>> Plot3D[Sin[x y], {x, -2, 2}, {y, -2, 2}, Mesh->Full]
```



```
>> ParametricPlot[{Cos[u] / u, Sin[u] / u}, {u, 0, 50}, PlotRange -> 0.5]
```



```
>> ParametricPlot[{Sin[u], Cos[u]}, {0.6 Sin[u], 0.6 Cos[u]}, {0.2 Sin[u], 0.2 Cos[u]}, {u, 0, 2 Pi}, PlotRange->1, AspectRatio->1]
```



## ParametricPlot

```
ParametricPlot[{f_x, f_y}, {u, umin, umax}]
```

plots a parametric function  $f$  with the parameter  $u$  ranging from  $umin$  to  $umax$ .

```
ParametricPlot[{f_x, f_y}, {g_x, g_y}, ..., {u, umin, umax}]
```

plots several parametric functions  $f, g, \dots$


```
ParametricPlot[{f_x, f_y}, {u, umin, umax}, {v, vmin, vmax}]
```

plots a parametric area.

```
ParametricPlot[{f_x, f_y}, {g_x, g_y}, ..., {u, umin, umax}, {v, vmin, vmax}]
```

plots several parametric areas.

```
>> ParametricPlot[{Sin[u], Cos[3 u]}, {u, 0, 2 Pi}]
```




## PieChart


```
PieChart[{p1, p2 ...}]
```

draws a pie chart.


```
>> PieChart[{1, 4, 2}]
```




```
>> PieChart[{8, 16, 2},
SectorOrigin -> {Automatic,
1.5}]
```




```
>> PieChart[{{10, 20, 30}, {15, 22,
30}}]
```



```
>> PieChart[{{10, 20, 30}, {15, 22,
30}}, SectorSpacing -> None]
```




```
>> PieChart[{{10, 20, 30}, {15, 22,
30}}, ChartLabels -> {a, b, c}]
```



Negative values are clipped to 0.


```
>> PieChart[{1, -1, 3}]
```




## Plot

`Plot[f, {x, xmin, xmax}]`  
 plots  $f$  with  $x$  ranging from  $xmin$  to  $xmax$ .  
`Plot[{f1, f2, ...}, {x, xmin, xmax}]`  
 plots several functions  $f1, f2, \dots$


```
>> Plot[{Sin[x], Cos[x], x / 3}, {x, -Pi, Pi}]
```




```
>> Plot[Sin[x], {x, 0, 4 Pi},
PlotRange->{{0, 4 Pi}, {0, 1.5}}]
```




```
>> Plot[Tan[x], {x, -6, 6}, Mesh->Full]
```




```
>> Plot[x^2, {x, -1, 1},
MaxRecursion->5, Mesh->All]
```



```
>> Plot[Log[x], {x, 0, 5},
MaxRecursion->0]
```




```
>> Plot[Tan[x], {x, 0, 6}, Mesh->All, PlotRange->{{-1, 5}, {0, 15}},
MaxRecursion->10]
```



A constant function:

```
>> Plot[3, {x, 0, 1}]
```




## Plot3D


`Plot3D[f, {x, xmin, xmax}, {y, ymin, ymax}]`

creates a three-dimensional plot of  $f$  with  $x$  ranging from  $xmin$  to  $xmax$  and  $y$  ranging from  $ymin$  to  $ymax$ .


```
>> Plot3D[x ^ 2 + 1 / y, {x, -1, 1}, {y, 1, 4}]
```




```
>> Plot3D[x y / (x ^ 2 + y ^ 2 + 1), {x, -2, 2}, {y, -2, 2}]
```




```
>> Plot3D[x / (x ^ 2 + y ^ 2 + 1), {x, -2, 2}, {y, -2, 2}, Mesh->None]
```



```
>> Plot3D[Sin[x y] / (x y), {x, -3, 3}, {y, -3, 3}, Mesh->All]
```



```
>> Plot3D[Log[x + y^2], {x, -1, 1}, {y, -1, 1}]
```




## PlotPoints

`PlotPoints` *n*

A number specifies how many initial sample points to use.

```
>> Plot[Sin[Cos[x^2]], {x, -4, 4},
PlotPoints -> 22]
```




## PlotRange

`PlotRange` *n* | All | Automatic

is an option for `Plot` that gives the range of coordinates to include in a plot.

```
>> Plot[Sin[Cos[x^2]], {x, -4, 4},
PlotRange -> All]
```




## PolarPlot


`PolarPlot`[*r*, {*t*, *tmin*, *tmax*}]

creates a polar plot of *r* with angle *t* ranging from *tmin* to *tmax*.

```
>> PolarPlot[Cos[5t], {t, 0, Pi}]
```



```
>> PolarPlot[{1, 1 + Sin[20 t] / 5}, {t, 0, 2 Pi}]
```




## Top

`Top`

is a possible value for the `Filling` option.

```
>> ListLinePlot[Table[Sin[x], {x,
-5, 5, 0.5}], Filling -> Axis | Top |
Bottom]
```





## VII. Logic

### Contents

AllTrue . . . . .	65	False . . . . .	66	Or (  ) . . . . .	66
And (&&) . . . . .	65	Implies (=>) . . . . .	66	True . . . . .	66
AnyTrue . . . . .	65	NoneTrue . . . . .	66	Xor (xor) . . . . .	67
Equivalent (==) . . . . .	66	Not (!) . . . . .	66		

### AllTrue

AllTrue[{*expr1*, *expr2*, ...}, *test*]  
returns True if all applications of *test* to *expr1*, *expr2*, ... evaluate to True.

AllTrue[*list*, *test*, *level*]  
returns True if all applications of *test* to items of *list* at *level* evaluate to True.

AllTrue[*test*]  
gives an operator that may be applied to expressions.

```
>> AllTrue[{2, 4, 6}, EvenQ]
True
>> AllTrue[{2, 4, 7}, EvenQ]
False
```

### And (&&)

And[*expr1*, *expr2*, ...]  
*expr1* && *expr2* && ...  
evaluates each expression in turn, returning False as soon as an expression evaluates to False. If all expressions evaluate to True, And returns True.

```
>> True && True && False
False
```

If an expression does not evaluate to True or False, And returns a result in symbolic form:

```
>> a && b && True && c
a&&b&&c
```

### AnyTrue

AnyTrue[{*expr1*, *expr2*, ...}, *test*]  
returns True if any application of *test* to *expr1*, *expr2*, ... evaluates to True.

AnyTrue[*list*, *test*, *level*]  
returns True if any application of *test* to items of *list* at *level* evaluates to True.

AnyTrue[*test*]  
gives an operator that may be applied to expressions.

```
>> AnyTrue[{1, 3, 5}, EvenQ]
False
>> AnyTrue[{1, 4, 5}, EvenQ]
True
```

### Equivalent (==)

Equivalent[*expr1*, *expr2*, ...]  
*expr1* == *expr2* == ...  
is equivalent to (*expr1* && *expr2* && ...) || (!*expr1* && !*expr2* && ...)

```
>> Equivalent[True, True, False]
False
```

If all expressions do not evaluate to True or False, Equivalent returns a result in symbolic form:

```
>> Equivalent[a, b, c]
abc
```

Otherwise, `Equivalent` returns a result in DNF

```
>> Equivalent[a, b, True, c]
a&&b&&c
```

## False

```
False
  represents the Boolean false value.
```

## Implies (=>)

```
Implies[expr1, expr2]
expr1 => expr2
  evaluates each expression in turn, returning True as soon as the first expression evaluates to False. If the first expression evaluates to True, Implies returns the second expression.
```

```
>> Implies[False, a]
True

>> Implies[True, a]
a
```

If an expression does not evaluate to True or False, `Implies` returns a result in symbolic form:

```
>> Implies[a, Implies[b, Implies[
  True, c]]]
abc
```

## NoneTrue

```
NoneTrue[{expr1, expr2, ...}, test]
  returns True if no application of test to expr1, expr2, ... evaluates to True.
NoneTrue[list, test, level]
  returns True if no application of test to items of list at level evaluates to True.
NoneTrue[test]
  gives an operator that may be applied to expressions.
```

```
>> NoneTrue[{1, 3, 5}, EvenQ]
True
```

```
>> NoneTrue[{1, 4, 5}, EvenQ]
False
```

## Not (!)

```
Not[expr]
!expr
  negates the logical expression expr.
```

```
>> !True
False

>> !False
True

>> !b
!b
```

## Or (||)

```
Or[expr1, expr2, ...]
expr1 || expr2 || ...
  evaluates each expression in turn, returning True as soon as an expression evaluates to True. If all expressions evaluate to False, Or returns False.
```

```
>> False || True
True
```

If an expression does not evaluate to True or False, `Or` returns a result in symbolic form:

```
>> a || False || b
a||b
```

## True

```
True
  represents the Boolean true value.
```

## Xor (xor)

```
Xor[expr1, expr2, ...]  
expr1 xor expr2 xor...  
    evaluates each expression in turn, return-  
    ing True as soon as not all expressions  
    evaluate to the same value. If all expres-  
    sions evaluate to the same value, Xor re-  
    turns False.
```

```
>> Xor[False, True]  
True
```

```
>> Xor[True, True]  
False
```

If an expression does not evaluate to True or False, Xor returns a result in symbolic form:

```
>> Xor[a, False, b]  
ab
```

# VIII. Scoping

## Contents

<b>Begin</b> . . . . .	68	<b>Sys-</b>	<b>EndPackage</b> . . . . .	70
<b>BeginPackage</b> . . . . .	68	<b>tem'Private'\$ContextPathStack</b> 69	<b>Module</b> . . . . .	70
<b>Block</b> . . . . .	69	<b>Sys-</b>	<b>\$ModuleNumber</b> . . . . .	70
<b>Context</b> . . . . .	69	<b>tem'Private'\$ContextStack</b> 69	<b>Unique</b> . . . . .	71
<b>\$ContextPath</b> . . . . .	69	<b>\$Context</b> . . . . .	<b>With</b> . . . . .	71
		<b>Contexts</b> . . . . .		
		<b>End</b> . . . . .		
				69

## Begin

`Begin[context]`  
temporarily sets the current context to *context*.

```
>> Begin["test'"]
test'
>> {$Context, $ContextPath}
{test', {Global', System'}}
>> Context[newsymbol]
test'
>> End[]
test'
>> End[]
Nopreviouscontextdefined.
Global'
```

## BeginPackage

`BeginPackage[context]`  
starts the package given by *context*.

The *context* argument must be a valid context name. `BeginPackage` changes the values of `$Context` and `$ContextPath`, setting the current context to *context*.

```
>> BeginPackage["test'"]
test'
```

## Block

`Block[{x, y, ...}, expr]`  
temporarily removes the definitions of the given variables, evaluates *expr*, and restores the original definitions afterwards.  
`Block[{x=x0, y=y0, ...}, expr]`  
assigns temporary values to the variables during the evaluation of *expr*.

```
>> n = 10
10
>> Block[{n = 5}, n ^ 2]
25
>> n
10
```

Values assigned to block variables are evaluated at the beginning of the block. Keep in mind that the result of `Block` is evaluated again, so a returned block variable will get its original value.

```
>> Block[{x = n+2, n}, {x, n}]
{12, 10}
```

If the variable specification is not of the described form, an error message is raised:

```
>> Block[{x + y}, x]
      Localvariablespecificationcontainsx+y,
      whichisnotasymboloranassignmenttoasymbol.
      x
```

Variable names may not appear more than once:

```
>> Block[{x, x}, x]
      Duplicatelocalvariablexfoundinlocalvariablespecification.
      x
```

## Context

`Context[symbol]`  
yields the name of the context where *symbol* is defined in.

`Context[]`  
returns the value of `$Context`.

```
>> Context[a]
      Global'

>> Context[b'c]
      b'

>> InputForm[Context[]]
      "Global"
```

## \$ContextPath

`$ContextPath`  
is the search path for contexts.

```
>> $ContextPath // InputForm
      {"Global'", "System'"}
```

## System'Private'\$ContextPathStack

`System'Private'$ContextPathStack`  
is an internal variable tracking the values of `$ContextPath` saved by `Begin` and `BeginPackage`.

## System'Private'\$ContextStack

`System'Private'$ContextStack`  
is an internal variable tracking the values of `$Context` saved by `Begin` and `BeginPackage`.

## \$Context

`$Context`  
is the current context.

```
>> $Context
      Global'
```

## Contexts

`Contexts[]`  
yields a list of all contexts.

```
>> x = 5;

>> Contexts[] // InputForm
      {"CombinatoricaOld",
      "Global'", "ImportExport'",
      "Internal'", "Settings'", "System'",
      "System'Convert'B64Dump'",
      "System'Convert'CommonDump'",
      "System'Convert'Image'",
      "System'Convert'JSONDump'",
      "System'Convert'TableDump'",
      "System'Convert'TextDump'",
      "System'ConvertersDump'",
      "System'Private'",
      "XML'", "XML'Parser'"}
```

## End

`End[]`  
ends a context started by `Begin`.

## EndPackage

`EndPackage[]`  
marks the end of a package, undoing a previous `BeginPackage`.

After `EndPackage`, the values of `$Context` and `$ContextPath` at the time of the `BeginPackage` call are restored, with the new package's context prepended to `$ContextPath`.

## Module

`Module[{vars}, expr]`  
localizes variables by giving them a temporary name of the form `name$number`, where `number` is the current value of `$ModuleNumber`. Each time a module is evaluated, `$ModuleNumber` is incremented.

```
>> x = 10;

>> Module[{x=x}, x=x+1; x]
11

>> x
10

>> t === Module[{t}, t]
False
```

Initial values are evaluated immediately:

```
>> Module[{t=x}, x = x + 1; t]
10

>> x
11
```

Variables inside other scoping constructs are not affected by the renaming of `Module`:

```
>> Module[{a}, Block[{a}, a]]
a

>> Module[{a}, Block[{}, a]]
a$5
```

## \$ModuleNumber

`$ModuleNumber`  
is the current “serial number” to be used for local module variables.

```
>> Unprotect[$ModuleNumber]
```

```
>> $ModuleNumber = 20;
```

```
>> Module[{x}, x]
x$20
```

```
>> $ModuleNumber = x;
```

*Cannot set \$ModuleNumber to x; value must be a positive integer.*

## Unique

`Unique[]`  
generates a new symbol and gives a name of the form `$number`.  
`Unique[x]`  
generates a new symbol and gives a name of the form `x$number`.  
`Unique[{x, y, ...}]`  
generates a list of new symbols.  
`Unique['xxx']`  
generates a new symbol and gives a name of the form `xxxnumber`.

Create a unique symbol with no particular name:

```
>> Unique[]
$9

>> Unique[sym]
sym$1
```

Create a unique symbol whose name begins with `x`:

```
>> Unique["x"]
x10
```

Each use of `Unique[symbol]` increments `$ModuleNumber`:

```
>> {$ModuleNumber, Unique[x],
  $ModuleNumber}
{2, x$2, 3}
```

`Unique[symbol]` creates symbols in the same way `Module` does:

```
>> {Module[{x}, x], Unique[x]}
{x$3, x$4}
```

Unique with more arguments

```
>> Unique[{x, "s"}, Flat ^ Listable
      ^ Orderless]
```

*Flat<sup>Listable</sup>Orderless* is not a known attribute.

```
Unique[{x, s}, FlatListableOrderless]
```

Unique call without symbol argument

```
>> Unique[x + y]
```

*x + y* is not a symbol or a valid symbol name.

```
Unique[x + y]
```

## With

`With[{x=x0, y=y0, ...}, expr]`  
 specifies that all occurrences of the symbols *x*, *y*, ... in *expr* should be replaced by *x0*, *y0*, ...

```
>> n = 10
10
```

Evaluate an expression with *x* locally set to 5:  
 With works even without evaluation:

```
>> With[{x = a}, (1 + x^2)&]
1 + a^2&
```

Use With to insert values into held expressions

```
>> With[{x=y}, Hold[x]]
Hold[y]
```

```
>> Table[With[{i=j}, Hold[i]], {j, 1, 4}]
{Hold[1], Hold[2],
 Hold[3], Hold[4]}
```

```
>> x=5; With[{x=x}, Hold[x]]
Hold[5]
```

```
>> {Block[{x = 3}, Hold[x]], With[{x = 3}, Hold[x]]}
{Hold[x], Hold[3]}
```

```
>> x=.; ReleaseHold /@ %
{x, 3}
```

```
>> With[{e = y}, Function[{x,y}, e*x*y]]
Function[{x$,y$}, yx$y$]
```

# IX. Random number generation

Random numbers are generated using the Mersenne Twister.

## Contents

<b>Random</b> . . . . .	72	<b>RandomInteger</b> . . . . .	73	<b>\$RandomState</b> . . . . .	74
<b>RandomChoice</b> . . . . .	72	<b>RandomReal</b> . . . . .	74	<b>SeedRandom</b> . . . . .	75
<b>RandomComplex</b> . . . . .	73	<b>RandomSample</b> . . . . .	74		

## Random

Legacy function. Superseded by RandomReal, RandomInteger and RandomComplex.

## RandomChoice

**RandomChoice[items]**  
randomly picks one item from *items*.

**RandomChoice[items, n]**  
randomly picks *n* items from *items*. Each pick in the *n* picks happens from the given set of *items*, so each item can be picked any number of times.

**RandomChoice[items, {n1, n2, ...}]**  
randomly picks items from *items* and arranges the picked items in the nested list structure described by {*n1*, *n2*, ...}.

**RandomChoice[weights -> items, n]**  
randomly picks *n* items from *items* and uses the corresponding numeric values in *weights* to determine how probable it is for each item in *items* to get picked (in the long run, items with higher weights will get picked more often than ones with lower weight).

**RandomChoice[weights -> items]**  
randomly picks one items from *items* using weights *weights*.

**RandomChoice[weights -> items, {n1, n2, ...}]**  
randomly picks a structured list of items from *items* using weights *weights*.

```
>> RandomChoice[{a, b, c}]
{c}

>> SeedRandom[42]

>> RandomChoice[{a, b, c}, 20]
{c,a,c,c,a,a,c,b,c,c,
 c,c,a,c,b,a,b,b,b}

>> SeedRandom[42]

>> RandomChoice[{"a", {1, 2}, x, {}], 10]
{x, {}, a,x,x, {}, a,a,x, {1,2}}

>> SeedRandom[42]

>> RandomChoice[{a, b, c}, {5, 2}]
{{c,a}, {c,c}, {a,a}, {c,b}, {c,c}}

>> SeedRandom[42]

>> RandomChoice[{1, 100, 5} -> {a, b, c}, 20]
{b,b,b,b,b,b,b,b,b,
 b,c,b,b,b,b,b,b,b}
```

```
>> SeedRandom[42]
```



## RandomComplex

`RandomComplex[{z_min, z_max}]`  
yields a pseudorandom complex number in the rectangle with complex corners `z_min` and `z_max`.

`RandomComplex[z_max]`  
yields a pseudorandom complex number in the rectangle with corners at the origin and at `z_max`.

`RandomComplex[]`  
yields a pseudorandom complex number with real and imaginary parts from 0 to 1.

`RandomComplex[range, n]`  
gives a list of `n` pseudorandom complex numbers.

`RandomComplex[range, {n1, n2, ...}]`  
gives a nested list of pseudorandom complex numbers.

```
>> RandomComplex[]
0.141484 + 0.268766I

>> RandomComplex[{1+I, 5+5I}]
2.29635 + 4.90259I

>> RandomComplex[1+I, 5]
{0.692032 + 0.905688I, 0.826~
~388 + 0.482661I, 0.721135 +
0.703028I, 0.0870583 + 0.036~
~5253I, 0.930318 + 0.0611352I}

>> RandomComplex[{1+I, 2+2I}, {2,
2}]
{{1.0819 + 1.2034I, 1.312~
~06 + 1.90094I}, {1.98909 +
1.95015I, 1.794 + 1.47541I}}
```

## RandomInteger

`RandomInteger[{min, max}]`  
yields a pseudorandom integer in the range from `min` to `max` inclusive.

`RandomInteger[max]`  
yields a pseudorandom integer in the range from 0 to `max` inclusive.

`RandomInteger[]`  
gives 0 or 1.

`RandomInteger[range, n]`  
gives a list of `n` pseudorandom integers.

`RandomInteger[range, {n1, n2, ...}]`  
gives a nested list of pseudorandom integers.

```
>> RandomInteger[{1, 5}]
1

>> RandomInteger[100, {2, 3}] //
TableForm
      81 23 50
      88 11 51
```

Calling `RandomInteger` changes `$RandomState`:

```
>> previousState = $RandomState;

>> RandomInteger[]
0

>> $RandomState != previousState
True
```

## RandomReal

`RandomReal[{min, max}]`  
yields a pseudorandom real number in the range from `min` to `max`.

`RandomReal[max]`  
yields a pseudorandom real number in the range from 0 to `max`.

`RandomReal[]`  
yields a pseudorandom real number in the range from 0 to 1.

`RandomReal[range, n]`  
gives a list of `n` pseudorandom real numbers.

`RandomReal[range, {n1, n2, ...}]`  
gives a nested list of pseudorandom real numbers.

```
>> RandomReal[]
0.464535

>> RandomReal[{1, 5}]
3.41196
```

## RandomSample

`RandomSample[items]`  
randomly picks one item from *items*.

`RandomSample[items, n]`  
randomly picks *n* items from *items*. Each pick in the *n* picks happens after the previous items picked have been removed from *items*, so each item can be picked at most once.

`RandomSample[items, {n1, n2, ...}]`  
randomly picks items from *items* and arranges the picked items in the nested list structure described by {*n1*, *n2*, ...}. Each item gets picked at most once.

`RandomSample[weights -> items, n]`  
randomly picks *n* items from *items* and uses the corresponding numeric values in *weights* to determine how probable it is for each item in *items* to get picked (in the long run, items with higher weights will get picked more often than ones with lower weight). Each item gets picked at most once.

`RandomSample[weights -> items]`  
randomly picks one items from *items* using weights *weights*. Each item gets picked at most once.

`RandomSample[weights -> items, {n1, n2, ...}]`  
randomly picks a structured list of items from *items* using weights *weights*. Each item gets picked at most once.

```
>> SeedRandom[42]

>> RandomSample[{a, b, c}]
{a}

>> SeedRandom[42]

>> RandomSample[{a, b, c, d, e, f, g, h}, 7]
{b, f, a, h, c, e, d}

>> SeedRandom[42]
```

```
>> RandomSample[{"a", {1, 2}, x, {}], 3]
{{1, 2}, {}, a}

>> SeedRandom[42]

>> RandomSample[Range[100], {2, 3}]
{{84, 54, 71}, {46, 45, 40}}

>> SeedRandom[42]

>> RandomSample[Range[100] -> Range[100], 5]
{62, 98, 86, 78, 40}
```

## \$RandomState

`$RandomState`  
is a long number representing the internal state of the pseudorandom number generator.

```
>> Mod[$RandomState, 10^100]
9 242 015 758 456 728 033 095 141 ~
~830 367 451 762 178 300 450 658 ~
~174 374 825 080 602 312 615 849 ~
~733 778 406 020 543 048 770 981 934

>> IntegerLength[$RandomState]
6 466
```

So far, it is not possible to assign values to `$RandomState`.

```
>> $RandomState = 42
It is not possible to change the random state.
42
```

Not even to its own value:

```
>> $RandomState = $RandomState;
It is not possible to change the random state.
```

## SeedRandom

`SeedRandom[n]`  
resets the pseudorandom generator with seed *n*.

`SeedRandom[]`  
uses the current date and time as the seed.

SeedRandom can be used to get reproducible random numbers:

```
>> SeedRandom[42]

>> RandomInteger[100]
51

>> RandomInteger[100]
92

>> SeedRandom[42]

>> RandomInteger[100]
51

>> RandomInteger[100]
92
```

String seeds are supported as well:

```
>> SeedRandom["Mathics"]

>> RandomInteger[100]
27
```

Calling SeedRandom without arguments will seed the random number generator to a random state:

```
>> SeedRandom[]

>> RandomInteger[100]
100
```

# X. Combinatorial Functions

## Contents

Binomial . . . . .	76	Multinomial . . . . .	77	StirlingS1 . . . . .	78
DiceDissimilarity . . .	76	RogersTanimotoDis- similarity . . . . .	77	StirlingS2 . . . . .	78
Fibonacci . . . . .	76	RussellRaoDissimilarity	77	Subsets . . . . .	78
JaccardDissimilarity . .	76	SokalSneathDissimi- larity . . . . .	77	YuleDissimilarity . . .	78
MatchingDissimilarity	77				

## Binomial

`Binomial[n, k]`  
gives the binomial coefficient  $n$  choose  $k$ .

```
>> Binomial[5, 3]
10
```

Binomial supports inexact numbers:

```
>> Binomial[10.5, 3.2]
165.286
```

Some special cases:

```
>> Binomial[10, -2]
0
```

```
>> Binomial[-10.5, -3.5]
0.
```

## DiceDissimilarity

`DiceDissimilarity[u, v]`  
returns the Dice dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(c\_tf + c\_ft) / (2 * c\_tt + c\_ft + c\_tf)$ , where  $n$  is  $\text{len}(u)$  and  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> DiceDissimilarity[{1, 0, 1, 1,
0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
1
2
```

## Fibonacci

`Fibonacci[n]`  
computes the  $n$ th Fibonacci number.

```
>> Fibonacci[0]
0
```

```
>> Fibonacci[1]
1
```

```
>> Fibonacci[10]
55
```

```
>> Fibonacci[200]
280 571 172 992 510 140 037 ~
~611 932 413 038 677 189 525
```

## JaccardDissimilarity

`JaccardDissimilarity[u, v]`  
returns the Jaccard-Needham dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(c\_tf + c\_ft) / (c\_tt + c\_ft + c\_tf)$ , where  $n$  is  $\text{len}(u)$  and  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> JaccardDissimilarity[{1, 0, 1,
1, 0, 1, 1}, {0, 1, 1, 0, 0, 0,
1}]
2
3
```

## MatchingDissimilarity

`MatchingDissimilarity[u, v]`  
returns the Matching dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(c\_tf + c\_ft) / n$ , where  $n$  is  $\text{len}(u)$  and  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> MatchingDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
4
7
```

## Multinomial

`Multinomial[n1, n2, ...]`  
gives the multinomial coefficient  $(n1 + n2 + \dots) / (n1! n2! \dots)$ .

```
>> Multinomial[2, 3, 4, 5]
2522520
```

```
>> Multinomial[]
1
```

Multinomial is expressed in terms of Binomial:

```
>> Multinomial[a, b, c]
Binomial[a, a] Binomial[a + b, b] Binomial[a + b + c, c]
```

`Multinomial[n-k, k]` is equivalent to `Binomial[n, k]`.

```
>> Multinomial[2, 3]
10
```

## RogersTanimotoDissimilarity

`RogersTanimotoDissimilarity[u, v]`  
returns the Rogers-Tanimoto dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $R / (c\_tt + c\_ff + R)$  where  $n$  is  $\text{len}(u)$ ,  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ , and  $R = 2 * (c\_tf + c\_ft)$ .

```
>> RogersTanimotoDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
8
11
```

## RussellRaoDissimilarity

`RussellRaoDissimilarity[u, v]`  
returns the Russell-Rao dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(n - c\_tt) / c\_tt$  where  $n$  is  $\text{len}(u)$  and  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> RussellRaoDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
5
7
```

## SokalSneathDissimilarity

`SokalSneathDissimilarity[u, v]`  
returns the Sokal-Sneath dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $R / (c\_tt + R)$  where  $n$  is  $\text{len}(u)$ ,  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ , and  $R = 2 * (c\_tf + c\_ft)$ .

```
>> SokalSneathDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
4
5
```

## StirlingS1

`StirlingS1[n, m]`  
gives the Stirling number of the first kind  ${}_n S_m$ .

Integer mathematical function, suitable for both symbolic and numerical manipulation. gives the

number of permutations of  $n$  elements that contain exactly  $m$  cycles.

```
>> StirlingS1[50, 1]
-608 281 864 034 267 560 872 ~
~252 163 321 295 376 887 552 ~
~831 379 210 240 000 000 000
```

## StirlingS2

`StirlingS2[n, m]`  
gives the Stirling number of the second kind  $_n^m$ .

returns the number of ways of partitioning a set of  $n$  elements into  $m$  nonempty subsets.

```
>> Table[StirlingS2[10, m], {m, 10}]
{1, 511, 9 330, 34 105, 42 525
, 22 827, 5 880, 750, 45, 1}
```

## Subsets

`Subsets[list]`  
finds a list of all possible subsets of *list*.  
`Subsets[list, n]`  
finds a list of all possible subsets containing at most  $n$  elements.  
`Subsets[list, {n}]`  
finds a list of all possible subsets containing exactly  $n$  elements.  
`Subsets[list, {min, max}]`  
finds a list of all possible subsets containing between *min* and *max* elements.  
`Subsets[list, spec, n]`  
finds a list of the first  $n$  possible subsets.  
`Subsets[list, spec, {n}]`  
finds the  $n$ th possible subset.

All possible subsets (power set):

```
>> Subsets[{a, b, c}]
{{}, {a}, {b}, {c}, {a,
b}, {a, c}, {b, c}, {a, b, c}}
```

All possible subsets containing up to 2 elements:

```
>> Subsets[{a, b, c, d}, 2]
{{}, {a}, {b}, {c}, {d},
{a, b}, {a, c}, {a, d},
{b, c}, {b, d}, {c, d}}
```

Subsets containing exactly 2 elements:

```
>> Subsets[{a, b, c, d}, {2}]
{{a, b}, {a, c}, {a, d},
{b, c}, {b, d}, {c, d}}
```

The first 5 subsets containing 3 elements:

```
>> Subsets[{a, b, c, d, e}, {3}, 5]
{{a, b, c}, {a, b, d}, {a,
b, e}, {a, c, d}, {a, c, e}}
```

All subsets with even length:

```
>> Subsets[{a, b, c, d, e}, {0, 5, 2}]
{{}, {a, b}, {a, c}, {a, d}, {a, e},
{b, c}, {b, d}, {b, e}, {c, d}, {c,
e}, {d, e}, {a, b, c, d}, {a, b, c, e},
{a, b, d, e}, {a, c, d, e}, {b, c, d, e}}
```

The 25th subset:

```
>> Subsets[Range[5], All, {25}]
{{2, 4, 5}}
```

The odd-numbered subsets of {a,b,c,d} in reverse order:

```
>> Subsets[{a, b, c, d}, All, {15, 1, -2}]
{{b, c, d}, {a, b, d}, {c, d},
{b, c}, {a, c}, {d}, {b}, {}}
```

## YuleDissimilarity

`YuleDissimilarity[u, v]`  
returns the Yule dissimilarity between the two boolean 1-D lists *u* and *v*, which is defined as  $R / (c_{tt} * c_{ff} + R / 2)$  where  $n$  is  $\text{len}(u)$ ,  $c_{ij}$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ , and  $R = 2 * c_{tf} * c_{ft}$ .

```
>> YuleDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
6
5
```

# XI. Global System Information

## Contents

<code>\$Aborted</code> . . . . .	79	<code>\$MachineName</code> . . . . .	80	<code>\$ScriptCommandLine</code> . . . . .	81
<code>\$ByteOrdering</code> . . . . .	79	<code>MathicsVersion</code> . . . . .	80	<code>\$SystemID</code> . . . . .	81
<code>\$CommandLine</code> . . . . .	79	<code>Names</code> . . . . .	80	<code>\$SystemWordLength</code> . . . . .	81
<code>Environment</code> . . . . .	79	<code>\$Packages</code> . . . . .	80	<code>\$UserName</code> . . . . .	81
<code>\$Failed</code> . . . . .	79	<code>\$ParentProcessID</code> . . . . .	80	<code>\$Version</code> . . . . .	81
<code>GetEnvironment</code> . . . . .	79	<code>\$ProcessID</code> . . . . .	80	<code>\$VersionNumber</code> . . . . .	81
<code>\$Machine</code> . . . . .	80	<code>\$ProcessorType</code> . . . . .	81		
		<code>Run</code> . . . . .	81		

## `$Aborted`

`$Aborted`  
is returned by a calculation that has been aborted.

## `$ByteOrdering`

`$ByteOrdering`  
returns the native ordering of bytes in binary data on your computer system.

```
>> $ByteOrdering
-1
```

## `$CommandLine`

`$CommandLine`  
is a list of strings passed on the command line to launch the Mathics session.

```
>> $CommandLine
{mathics/test.py, -ot, -k}
```

## Environment

`Environment[var]`  
gives the value of an operating system environment variable.

```
>> Environment["HOME"]
/home/rocky
```

## `$Failed`

`$Failed`  
is returned by some functions in the event of an error.

## GetEnvironment

`GetEnvironment["var"]`  
gives the setting corresponding to the variable “*var*” in the operating system environment.

```
>> GetEnvironment["HOME"]
HOME- > /home/rocky
```

## \$Machine

**\$Machine**  
returns a string describing the type of computer system on which the Mathics is being run.

```
>> $Machine
linux
```

## \$MachineName

**\$MachineName**  
is a string that gives the assigned name of the computer on which Mathics is being run, if such a name is defined.

```
>> $MachineName
muffin
```

## MathicsVersion

**MathicsVersion**  
this string is the version of Mathics we are running.

```
>> MathicsVersion
2.0.0
```

## Names

**Names["pattern"]**  
returns the list of names matching *pattern*.

```
>> Names["List"]
{List}
```

The wildcard \* matches any character:

```
>> Names["List*"]
{List, ListLinePlot,
 ListPlot, ListQ, Listable}
```

The wildcard @ matches only lowercase characters:

```
>> Names["List@"]
{Listable}
```

```
>> x = 5;

>> Names["Global'*"]
{x}
```

The number of built-in symbols:

```
>> Length[Names["System'*"]]
1075
```

## \$Packages

**\$Packages**  
returns a list of the contexts corresponding to all packages which have been loaded into Mathics.

```
>> $Packages
{ImportExport', XML',
 Internal', System', Global'}
```

## \$ParentProcessID

**\$ParentProcessID**  
gives the ID assigned to the process which invokes the *Mathics* by the operating system under which it is run.

```
>> $ParentProcessID
2011145
```

## \$ProcessID

**\$ProcessID**  
gives the ID assigned to the *Mathics* process by the operating system under which it is run.

```
>> $ProcessID
2011147
```



## \$ProcessorType

**\$ProcessorType**

gives a string giving the architecture of the processor on which the *Mathics* is being run.

```
>> $ProcessorType
x86_64
```

## Run

**Run[command]**

runs command as an external operating system command, returning the exit code obtained.

```
>> Run["date"]
0
```

## \$ScriptCommandLine

**\$ScriptCommandLine**

is a list of string arguments when running the kernel in script mode.

```
>> $ScriptCommandLine
{}
```

## \$SystemID

**\$SystemID**

is a short string that identifies the type of computer system on which the *Mathics* is being run.

```
>> $SystemID
linux
```

## \$SystemWordLength

**\$SystemWordLength**

gives the effective number of bits in raw machine words on the computer system where *Mathics* is running.

```
>> $SystemWordLength
64
```

## \$UserName

**\$UserName**

returns a string describing the type of computer system on which *Mathics* is being run.

```
>> $UserName
rocky
```

## \$Version

**\$Version**

returns a string with the current *Mathics* version and the versions of relevant libraries.

```
>> $Version
Mathics 2.0.0 on CPython
3.7.9 (default, Nov 18 2020,
03:45:16) using SymPy 1.7.1,
mpmath 1.1.0, cython 0.29.21
```

## \$VersionNumber

**\$VersionNumber**

is a real number which gives the current Wolfram Language version that *Mathics* tries to be compatible with.

```
>> $VersionNumber
6.
```

## XII. The Main Loop

### Contents

---

<b>\$Post</b> . . . . .	82	<b>\$PrePrint</b> . . . . .	82	<b>\$SyntaxHandler</b> . . . .	82
<b>\$Pre</b> . . . . .	82	<b>\$PreRead</b> . . . . .	82		

---

### \$Post

**\$Post**

is a global variable whose value, if set, is applied to every output expression.

```
>> $Pre = .; $Post = .; $PrePrint =  
    .; $EnlapsedTime = .;  
    [Processinginput...]  
  
>> 2 + 2  
    4
```

### \$Pre

**\$Pre**

is a global variable whose value, if set, is applied to every input expression.

Set *Timing* as the **\$Pre** function, stores the elapsed time in a variable, stores just the result in `Out[$Line]` and print a formatted version showing the elapsed time

```
>> $Pre := (Print["Processing  
input..."];#1)&  
  
>> $Post := (Print["Storing result  
..."]; #1)&  
    [Processinginput...]  
    [Storingresult...]  
  
>> $PrePrint := (Print["The result  
is:"]; {TimeUsed[], #1})&  
    [Processinginput...]  
    [Storingresult...]  
  
>> 2 + 2  
    [Processinginput...]  
    [Storingresult...]  
    Theresultis :  
    {389.407,4}
```

### \$PrePrint

**\$PrePrint**

is a global variable whose value, if set, is applied to every output expression before it is printed.

### \$PreRead

**\$PreRead**

is a global variable whose value, if set, is applied to the text or box form of every input expression before it is fed to the parser. (Not implemented yet)

### \$SyntaxHandler

**\$SyntaxHandler**

is a global variable whose value, if set, is applied to any input string that is found to contain a syntax error. (Not implemented yet)

# XIII. Quantities

## Contents

---

KnownUnitQ . . . . .	83	QuantityMagnitude . . . . .	83	QuantityUnit . . . . .	84
Quantity . . . . .	83	QuantityQ . . . . .	83	UnitConvert . . . . .	84

---

## KnownUnitQ

KnownUnitQ[*unit*]  
returns True if *unit* is a canonical unit,  
and False otherwise.

```
>> KnownUnitQ["Feet"]
True

>> KnownUnitQ["Foo"]
False
```

## Quantity

Quantity[magnitude, *unit*]  
represents a quantity with size *magnitude*  
and unit specified by *unit*.  
Quantity[*unit*]  
assumes the magnitude of the specified  
*unit* to be 1.

```
>> Quantity["Kilogram"]
1kilogram

>> Quantity[10, "Meters"]
10meter

>> Quantity[{10,20}, "Meters"]
{10meter,20meter}
```

## QuantityMagnitude

QuantityMagnitude[*quantity*]  
gives the amount of the specified *quantity*.  
QuantityMagnitude[*quantity*, *unit*]  
gives the value corresponding to *quantity*  
when converted to *unit*.

```
>> QuantityMagnitude[Quantity["Kilogram"]]
1

>> QuantityMagnitude[Quantity[10, "Meters"]]
10

>> QuantityMagnitude[Quantity[{10,20}, "Meters"]]
{10,20}
```

## QuantityQ

QuantityQ[*expr*]  
return True if *expr* is a valid Association  
object, and False otherwise.

```
>> QuantityQ[Quantity[3, "Meters"]]
True

>> QuantityQ[Quantity[3, "Maters"]]
UnabletointerpretunitspecificationMaters.
False
```

## QuantityUnit

`QuantityUnit[quantity]`  
returns the unit associated with the specified *quantity*.

```
>> QuantityUnit[Quantity["Kilogram  
"]]
kilogram

>> QuantityUnit[Quantity[10, "  
Meters"]]
meter

>> QuantityUnit[Quantity[{10,20}, "  
Meters"]]
{meter,meter}
```

## UnitConvert

`UnitConvert[quantity, targetunit]`  
converts the specified *quantity* to the specified *targetunit*.  
`UnitConvert[quantity]`  
converts the specified *quantity* to its "SI Base" units.

Convert from miles to kilometers:

```
>> UnitConvert[Quantity[5.2, "miles  
"], "kilometers"]
8.36859kilometer
```

Convert a Quantity object to the appropriate SI base units:

```
>> UnitConvert[Quantity[3.8, "  
Pounds"]]
1.72365kilogram
```

# XIV. Solving Recurrence Equations

## Contents

---

RSolve . . . . . 85

---

## RSolve

`RSolve[eqn, a[n], n]`  
solves a recurrence equation for the function  $a[n]$ .

Solve a difference equation:

```
>> RSolve[a[n] == a[n+1], a[n], n]
{{a[n] -> C[0]}}
```

No boundary conditions gives two general parameters:

```
>> RSolve[{a[n + 2] == a[n]}, a, n]
{{a -> (Function[{n},
C[0] + C[1] - 1^n])}}
```

Include one boundary condition:

```
>> RSolve[{a[n + 2] == a[n], a[0]
== 1}, a, n]
{{a -> (Function[{n},
1 - C[1] + C[1] - 1^n])}}
```

Get a “pure function” solution for a with two boundary conditions:

```
>> RSolve[{a[n + 2] == a[n], a[0]
== 1, a[1] == 4}, a, n]
{{a -> (Function[{n},
5/2 - (3 - 1^n)/2])}}
```

## XV. Patterns and Rules

Some examples:

```
>> a + b + c /. a + b -> t
c + t

>> a + 2 + b + c + x * y /.
n_Integer + s__Symbol + rest_ ->
{n, s, rest}
{2, a, b + c + xy}

>> f[a, b, c, d] /. f[first_,
rest___] -> {first, {rest}}
{a, {b, c, d}}
```

Tests and Conditions:

```
>> f[4] /. f[x_?(# > 0&)] -> x ^ 2
16

>> f[4] /. f[x_] /; x > 0 -> x ^ 2
16
```

Leaves in the beginning of a pattern rather

match fewer leaves:

```
>> f[a, b, c, d] /. f[start__,
end__] -> {{start}, {end}}
{{a}, {b, c, d}}
```

Optional arguments using Optional:

```
>> f[a] /. f[x_, y_:3] -> {x, y}
{a, 3}
```

Options using OptionsPattern and OptionValue:

```
>> f[y, a->3] /. f[x_,
OptionsPattern[{a->2, b->5}]] ->
{x, OptionValue[a], OptionValue
[b]}
{y, 3, 5}
```

The attributes Flat, Orderless, and OneIdentity affect pattern matching.

### Contents

Alternatives ( ) . . . . .	86	MatchQ . . . . .	88	ReplaceAll (/.) . . . . .	91
Blank . . . . .	87	Optional (:) . . . . .	89	ReplaceList . . . . .	91
BlankNullSequence . . . . .	87	OptionsPattern . . . . .	89	ReplaceRepeated (//.) . . . . .	92
BlankSequence . . . . .	87	PatternTest (?) . . . . .	89	RuleDelayed (:>) . . . . .	92
Condition (/;) . . . . .	88	Pattern . . . . .	90	Rule (->) . . . . .	92
Except . . . . .	88	Repeated (..) . . . . .	90	Shortest . . . . .	92
HoldPattern . . . . .	88	RepeatedNull (...) . . . . .	90	Verbatim . . . . .	92
Longest . . . . .	88	Replace . . . . .	91		

### Alternatives (|)

Alternatives[*p*<sub>1</sub>, *p*<sub>2</sub>, ..., *p*<sub>*i*</sub>]  
*p*<sub>1</sub> | *p*<sub>2</sub> | ... | *p*<sub>*i*</sub>  
 is a pattern that matches any of the patterns '*p*<sub>1</sub>, *p*<sub>2</sub>, ..., *p*<sub>*i*</sub>'.

```
>> a+b+c+d/.(a|b)->t
c + d + 2t
```

Alternatives can also be used for string expressions

```
>> StringReplace["0123 3210", "1" |
"2" -> "X"]
0XX3 3XX0
```

## Blank

```
Blank[]
-
  represents any single expression in a pattern.
Blank[h]
_h
  represents any expression with head h.
```

```
>> MatchQ[a + b, _]
True
```

Patterns of the form `_h` can be used to test the types of objects:

```
>> MatchQ[42, _Integer]
True

>> MatchQ[1.0, _Integer]
False

>> {42, 1.0, x} /. {_Integer -> "integer", _Real -> "real"} //
InputForm
{"integer", "real", x}
```

Blank only matches a single expression:

```
>> MatchQ[f[1, 2], f[_]]
False
```

## BlankNullSequence

```
BlankNullSequence[]
---
  represents any sequence of expression leaves in a pattern, including an empty sequence.
```

BlankNullSequence is like BlankSequence, except it can match an empty sequence:

```
>> MatchQ[f[], f[___]]
True
```

## BlankSequence

```
BlankSequence[]
--
  represents any non-empty sequence of expression leaves in a pattern.
BlankSequence[h]
__h
  represents any sequence of leaves, all of which have head h.
```

Use a BlankSequence pattern to stand for a non-empty sequence of arguments:

```
>> MatchQ[f[1, 2, 3], f[___]]
True

>> MatchQ[f[], f[___]]
False
```

`__h` will match only if all leaves have head *h*:

```
>> MatchQ[f[1, 2, 3], f[__Integer]]
True

>> MatchQ[f[1, 2.0, 3], f[__Integer]]
False
```

The value captured by a named BlankSequence pattern is a Sequence object:

```
>> f[1, 2, 3] /. f[x__] -> x
Sequence[1, 2, 3]
```

## Condition (/;)

```
Condition[pattern, expr]
pattern /; expr
  places an additional constraint on pattern that only allows it to match if expr evaluates to True.
```

The controlling expression of a Condition can use variables from the pattern:

```
>> f[3] /. f[x_] /; x>0 -> t
t

>> f[-3] /. f[x_] /; x>0 -> t
f[-3]
```

Condition can be used in an assignment:

```
>> f[x_] := p[x] /; x>0
```

```
>> f[3]
p[3]

>> f[-3]
f[-3]
```

## Except

`Except[c]`  
represents a pattern object that matches any expression except those matching *c*.

`Except[c, p]`  
represents a pattern object that matches *p* but not *c*.

```
>> Cases[{x, a, b, x, c}, Except[x]]
{a, b, c}

>> Cases[{a, 0, b, 1, c, 2, 3}, Except[1, _Integer]]
{0, 2, 3}
```

Except can also be used for string expressions:

```
>> StringReplace["Hello world!", Except[LetterCharacter] -> ""]
Helloworld
```

## HoldPattern

`HoldPattern[expr]`  
is equivalent to *expr* for pattern matching, but maintains it in an unevaluated form.

```
>> HoldPattern[x + x]
HoldPattern[x + x]

>> x /. HoldPattern[x] -> t
t
```

HoldPattern has attribute HoldAll:

```
>> Attributes[HoldPattern]
{HoldAll, Protected}
```

## Longest

```
>> StringCases["aabaab", Longest["a" ~~__ ~~"b"]]
{aabaab}

>> StringCases["aabaab", Longest[RegularExpression["a+b"]]]
{aab, aab}
```

## MatchQ

`MatchQ[expr, form]`  
tests whether *expr* matches *form*.

```
>> MatchQ[123, _Integer]
True

>> MatchQ[123, _Real]
False

>> MatchQ[_Integer][123]
True
```

## Optional (:)

`Optional[patt, default]`  
*patt* : *default*  
is a pattern which matches *patt*, which if omitted should be replaced by *default*.

```
>> f[x_, y_:1] := {x, y}

>> f[1, 2]
{1, 2}

>> f[a]
{a, 1}
```

Note that *symb* : *patt* represents a Pattern object. However, there is no disambiguity, since *symb* has to be a symbol in this case.

```
>> x:_ // FullForm
Pattern[x, Blank[]]

>> _:d // FullForm
Optional[Blank[], d]
```



```
>> x:_+y_:d // FullForm
Pattern[x, Plus[Blank[],
Optional[Pattern[y, Blank[]], d]]]
```

`s_.` is equivalent to `Optional[s_]` and represents an optional parameter which, if omitted, gets its value from `Default`.

```
>> FullForm[s_.]
Optional[Pattern[s, Blank[]]]

>> Default[h, k_] := k

>> h[a] /. h[x_, y_.] -> {x, y}
{a, 2}
```

## OptionsPattern

`OptionsPattern[f]`  
is a pattern that stands for a sequence of options given to a function, with default values taken from `Options[f]`. The options can be of the form `opt->value` or `opt:>value`, and might be in arbitrarily nested lists.

`OptionsPattern[{opt1->value1, ...}]`  
takes explicit default values from the given list. The list may also contain symbols `f`, for which `Options[f]` is taken into account; it may be arbitrarily nested. `OptionsPattern[{}]` does not use any default values.

The option values can be accessed using `OptionValue`.

```
>> f[x_, OptionsPattern[{n->2}]] :=
  x ^ OptionValue[n]

>> f[x]
x2

>> f[x, n->3]
x3
```

Delayed rules as options:

```
>> e = f[x, n:>a]
xa

>> a = 5;

>> e
x5
```

Options might be given in nested lists:

```
>> f[x, {{{n->4}}}]
x4
```

## PatternTest (?)

`PatternTest[pattern, test]`  
`pattern ? test`  
constrains `pattern` to match `expr` only if the evaluation of `test[expr]` yields `True`.

```
>> MatchQ[3, _Integer?(#>0&)]
True

>> MatchQ[-3, _Integer?(#>0&)]
False
```

## Pattern

`Pattern[symb, patt]`  
`symb : patt`  
assigns the name `symb` to the pattern `patt`.

`symb_head`  
is equivalent to `symb : _head` (accordingly with `_` and `__`).

`symb : patt : default`  
is a pattern with name `symb` and default value `default`, equivalent to `Optional[patt : symb, default]`.

```
>> FullForm[a_b]
Pattern[a, Blank[b]]

>> FullForm[a:_:b]
Optional[Pattern[a, Blank[]], b]
```

`Pattern` has attribute `HoldFirst`, so it does not evaluate its name:

```
>> x = 2
2

>> x_
x_
```

Nested `Pattern` assign multiple names to the same pattern. Still, the last parameter is the default value.

```
>> f[y] /. f[a:b, _:d] -> {a, b}
f[y]
```

This is equivalent to:

```
>> f[a] /. f[a:_:b] -> {a, b}
      {a, b}
```

FullForm:

```
>> FullForm[a:b:c:d:e]
      Optional[Pattern[a, b],
      Optional[Pattern[c, d], e]]

>> f[] /. f[a:_:b] -> {a, b}
      {b, b}
```

## Repeated (..)

`Repeated[pattern]`  
matches one or more occurrences of *pattern*.

```
>> a_Integer.. // FullForm
      Repeated[Pattern[a, Blank[Integer]]]

>> 0..1//FullForm
      Repeated[0]

>> {{}, {a}, {a, b}, {a, a, a}, {a,
      a, a, a}} /. {Repeated[x : a |
      b, 3]} -> x
      {{}, a, {a, b}, a, {a, a, a, a}}

>> f[x, 0, 0, 0] /. f[x, s:0..] ->
      s
      Sequence[0, 0, 0]
```

## RepeatedNull (...)

`RepeatedNull[pattern]`  
matches zero or more occurrences of *pattern*.

```
>> a___Integer...//FullForm
      RepeatedNull[Pattern[a,
      BlankNullSequence[Integer]]]

>> f[x] /. f[x, 0...] -> t
      t
```

## Replace

`Replace[expr, x -> y]`  
yields the result of replacing *expr* with *y* if it matches the pattern *x*.  
`Replace[expr, x -> y, levelspec]`  
replaces only subexpressions at levels specified through *levelspec*.  
`Replace[expr, {x -> y, ...}]`  
performs replacement with multiple rules, yielding a single result expression.  
`Replace[expr, {{a -> b, ...}, {c -> d, ...}, ...}]`  
returns a list containing the result of performing each set of replacements.

```
>> Replace[x, {x -> 2}]
      2
```

By default, only the top level is searched for matches

```
>> Replace[1 + x, {x -> 2}]
      1 + x

>> Replace[x, {{x -> 1}, {x -> 2}}]
      {1, 2}
```

Replace stops after the first replacement

```
>> Replace[x, {x -> {}, _List -> y
      {}
      {}}
```

Replace replaces the deepest levels first

```
>> Replace[x[1], {x[1] -> y, 1 ->
      2}, All]
      x[2]
```

By default, heads are not replaced

```
>> Replace[x[x[y]], x -> z, All]
      x[x[y]]
```

Heads can be replaced using the Heads option

```
>> Replace[x[x[y]], x -> z, All,
      Heads -> True]
      z[z[y]]
```

Note that heads are handled at the level of leaves

```
>> Replace[x[x[y]], x -> z, {1},
      Heads -> True]
      z[x[y]]
```

You can use Replace as an operator

```
>> Replace[{x_ -> x + 1}][10]
11
```

## ReplaceAll (/.)

`ReplaceAll[expr, x -> y]`  
`expr /. x -> y`  
 yields the result of replacing all subexpressions of `expr` matching the pattern `x` with `y`.  
`expr /. {x -> y, ...}`  
 performs replacement with multiple rules, yielding a single result expression.  
`expr /. {{a -> b, ...}, {c -> d, ...}, ...}`  
 returns a list containing the result of performing each set of replacements.

```
>> a+b+c /. c->d
a + b + d

>> g[a+b+c,a] /. g[x_+y_,x_]->{x,y}
{a,b + c}
```

If `rules` is a list of lists, a list of all possible respective replacements is returned:

```
>> {a, b} /. {{a->x, b->y}, {a->u, b->v}}
{{x,y}, {u,v}}
```

The list can be arbitrarily nested:

```
>> {a, b} /. {{a->x, b->y}, {a->w, b->z}}, {a->u, b->v}}
{{{x,y}, {w,z}}, {u,v}}
```

>> {a, b} /. {{a->x, b->y}, a->w, b->z}, {a->u, b->v}}

*Elementsof{{a->x,b->y},a->w,b->z}areamixtureoflistsandnonlists.*

```
{{a,b} /. {{a->x,b->y}, a->w,b->z}, {u,v}}
```

`ReplaceAll` also can be used as an operator:

```
>> ReplaceAll[{a -> 1}][{a, b}]
{1,b}
```

`ReplaceAll` replaces the shallowest levels first:

```
>> ReplaceAll[x[1], {x[1] -> y, 1 -> 2}]
y
```

## ReplaceList

`ReplaceList[expr, rules]`  
 returns a list of all possible results of applying `rules` to `expr`.

Get all subsequences of a list:

```
>> ReplaceList[{a, b, c}, {___, x_, ___} -> {x}]
{{a}, {a,b}, {a,b,c}, {b}, {b,c}, {c}}
```

You can specify the maximum number of items:

```
>> ReplaceList[{a, b, c}, {___, x_, ___} -> {x}, 3]
{{a}, {a,b}, {a,b,c}}
```

```
>> ReplaceList[{a, b, c}, {___, x_, ___} -> {x}, 0]
{}
```

If no rule matches, an empty list is returned:

```
>> ReplaceList[a, b->x]
{}
```

Like in `ReplaceAll`, `rules` can be a nested list:

```
>> ReplaceList[{a, b, c}, {{{___, x_, ___} -> {x}}, {{a, b, c} -> t}}, 2]
{{{a}, {a,b}}, {t}}
```

```
>> ReplaceList[expr, {}, -1]
Non
-negativeintegerorInfinityexpectedatposition3.
ReplaceList[expr, {}, -1]
```

Possible matches for a sum:

```
>> ReplaceList[a + b + c, x_ + y_ -> {x, y}]
{{a,b + c}, {b,a + c}, {c,a + b}, {a + b,c}, {a + c,b}, {b + c,a}}
```

## ReplaceRepeated (//.)

`ReplaceRepeated[expr, x -> y]`  
`expr //. x -> y`  
 repeatedly applies the rule `x -> y` to `expr` until the result no longer changes.

```
>> a+b+c /. c->d
a + b + d
```

Simplification of logarithms:

```
>> logrules = {Log[x_ * y_] :> Log[
  x] + Log[y], Log[x_ ^ y_] :> y *
  Log[x]};

>> Log[a * (b * c)^ d ^ e * f] /.
  logrules

Log[a] + Log[f] + (Log[b] + Log[c]) d^e
```

ReplaceAll just performs a single replacement:

```
>> Log[a * (b * c)^ d ^ e * f] /.
  logrules

Log[a] + Log[f (bc)^d^e]
```

## RuleDelayed (:>)

```
RuleDelayed[x, y]
x :> y
  represents a rule replacing x with y, with
  y held unevaluated.
```

```
>> Attributes[RuleDelayed]
{HoldRest, Protected, SequenceHold}
```

## Rule (->)

```
Rule[x, y]
x -> y
  represents a rule replacing x with y.
```

```
>> a+b+c /. c->d
a + b + d

>> {x, x^2, y} /. x->3
{3, 9, y}
```

## Shortest

## Verbatim

```
Verbatim[expr]
  prevents pattern constructs in expr from
  taking effect, allowing them to match
  themselves.
```

Create a pattern matching Blank:

```
>> _ /. Verbatim[_]->t
t

>> x /. Verbatim[_]->t
x
```

Without Verbatim, Blank has its normal effect:

```
>> x /. _->t
t
```

# XVI. Mathematical Functions

Basic arithmetic functions, including complex number arithmetic.

## Contents

<b>Abs</b> . . . . .	93	<b>I</b> . . . . .	96	<b>Power (^)</b> . . . . .	99
<b>Boole</b> . . . . .	93	<b>Im</b> . . . . .	96	<b>Product</b> . . . . .	99
<b>Complex</b> . . . . .	94	<b>InexactNumberQ</b> . . .	96	<b>Rational</b> . . . . .	100
<b>Conjugate</b> . . . . .	94	<b>IntegerQ</b> . . . . .	96	<b>Re</b> . . . . .	100
<b>CubeRoot</b> . . . . .	94	<b>Integer</b> . . . . .	97	<b>RealNumberQ</b> . . . . .	100
<b>DirectedInfinity</b> . . . .	94	<b>MachineNumberQ</b> . .	97	<b>Real</b> . . . . .	100
<b>Divide (/)</b> . . . . .	95	<b>Minus (-)</b> . . . . .	97	<b>Sign</b> . . . . .	100
<b>ExactNumberQ</b> . . . . .	95	<b>NumberQ</b> . . . . .	97	<b>Sqrt</b> . . . . .	101
<b>Factorial (!)</b> . . . . .	95	<b>Piecewise</b> . . . . .	97	<b>Subtract (-)</b> . . . . .	101
<b>Gamma</b> . . . . .	96	<b>Plus (+)</b> . . . . .	98	<b>Sum</b> . . . . .	102
<b>HarmonicNumber</b> . . .	96	<b>Pochhammer</b> . . . . .	98	<b>Times (*)</b> . . . . .	102
		<b>PossibleZeroQ</b> . . . . .	98		

## Abs

**Abs**[*x*]  
returns the absolute value of *x*.


```
>> Abs[-3]
3
```

Abs returns the magnitude of complex numbers:

```
>> Abs[3 + I]
 $\sqrt{10}$ 
```

```
>> Abs[3.0 + I]
3.16228
```

```
>> Plot[Abs[x], {x, -4, 4}]
```



## Boole

**Boole**[*expr*]  
returns 1 if *expr* is True and 0 if *expr* is False.

```
>> Boole[2 == 2]
1
```

```
>> Boole[7 < 5]
0
```

```
>> Boole[a == 7]
Boole[a==7]
```

## Complex

**Complex**  
is the head of complex numbers.  
**Complex**[*a*, *b*]  
constructs the complex number  $a + I b$ .

```
>> Head[2 + 3*I]
Complex
```

```
>> Complex[1, 2/3]
1 +  $\frac{2I}{3}$ 
>> Abs[Complex[3, 4]]
5
```

## Conjugate

`Conjugate[z]`  
returns the complex conjugate of the complex number  $z$ .

```
>> Conjugate[3 + 4 I]
3 - 4I
>> Conjugate[3]
3
>> Conjugate[a + b * I]
Conjugate[a] - IConjugate[b]
>> Conjugate[{{1, 2 + I 4, a + I b}, {I}}]
{{1, 2 - 4I, Conjugate[a] - IConjugate[b]}, {-I}}
>> Conjugate[1.5 + 2.5 I]
1.5 - 2.5I
```

## CubeRoot

`CubeRoot[n]`  
finds the real-valued cube root of the given  $n$ .

```
>> CubeRoot[16]
 $22^{\frac{1}{3}}$ 
```

## DirectedInfinity

`DirectedInfinity[z]`  
represents an infinite multiple of the complex number  $z$ .  
`DirectedInfinity[]`  
is the same as `ComplexInfinity`.

```
>> DirectedInfinity[1]
 $\infty$ 
>> DirectedInfinity[]
ComplexInfinity
>> DirectedInfinity[1 + I]
 $\left(\frac{1}{2} + \frac{I}{2}\right) \sqrt{2} \infty$ 
>> 1 / DirectedInfinity[1 + I]
0
>> DirectedInfinity[1] + DirectedInfinity[-1]
Indeterminateexpression
- Infinity + Infinityencountered.
Indeterminate
```

## Divide (/)

`Divide[a, b]`  
 $a / b$   
represents the division of  $a$  by  $b$ .

```
>> 30 / 5
6
>> 1 / 8
 $\frac{1}{8}$ 
>> Pi / 4
 $\frac{\text{Pi}}{4}$ 
```

Use `N` or a decimal point to force numeric evaluation:

```
>> Pi / 4.0
0.785398
>> 1 / 8
 $\frac{1}{8}$ 
>> N[%]
0.125
```

Nested divisions:

```
>> a / b / c
 $\frac{a}{bc}$ 
```

```
>> a / (b / c)

$$\frac{ac}{b}$$

>> a / b / (c / (d / e))

$$\frac{ad}{bce}$$

>> a / (b ^ 2 * c ^ 3 / e)

$$\frac{ae}{b^2c^3}$$

```

## ExactNumberQ

`ExactNumberQ[expr]`  
returns True if *expr* is an exact number,  
and False otherwise.

```
>> ExactNumberQ[10]
True
>> ExactNumberQ[4.0]
False
>> ExactNumberQ[n]
False
```

`ExactNumberQ` can be applied to complex numbers:

```
>> ExactNumberQ[1 + I]
True
>> ExactNumberQ[1 + 1. I]
False
```

## Factorial (!)

`Factorial[n]`  
 $n!$   
computes the factorial of *n*.

```
>> 20!
2432902008176640000
```

`Factorial` handles numeric (real and complex) values using the gamma function:

```
>> 10.5!
 $1.18994 \times 10^7$ 
>> (-3.0+1.5*I)!
 $0.0427943 - 0.00461565I$ 
```

However, the value at poles is `ComplexInfinity`:

```
>> (-1.)!
ComplexInfinity
```

`Factorial` has the same operator (!) as `Not`, but with higher precedence:

```
>> !a! //FullForm
Not[Factorial[a]]
```

## Gamma

`Gamma[z]`  
is the gamma function on the complex number *z*.  
`Gamma[z, x]`  
is the upper incomplete gamma function.  
`Gamma[z, x0, x1]`  
is equivalent to `Gamma[z, x0] - Gamma[z, x1]`.

`Gamma[z]` is equivalent to  $(z - 1)!$ :

```
>> Simplify[Gamma[z] - (z - 1)!]
0
```



Exact arguments:

```
>> Gamma[8]
5040
>> Gamma[1/2]
 $\sqrt{\pi}$ 
>> Gamma[1, x]
 $E^{-x}$ 
>> Gamma[0, x]
ExpIntegralE[1, x]
```

Numeric arguments:

```
>> Gamma[123.78]
 $4.21078 \times 10^{204}$ 
>> Gamma[1. + I]
 $0.498016 - 0.15495I$ 
```

Both `Gamma` and `Factorial` functions are continuous:



## HarmonicNumber

`HarmonicNumber[n]`  
returns the  $n$ th harmonic number.

```
>> Table[HarmonicNumber[n], {n, 8}]
{1, 3/2, 11/6, 25/12, 137/60, 49/20, 363/140, 761/280}

>> HarmonicNumber[3.8]
2.03806
```

## I

`I`  
represents the imaginary number  $\sqrt{-1}$ .

```
>> I^2
-1

>> (3+I)*(3-I)
10
```

## Im

`Im[z]`  
returns the imaginary component of the complex number  $z$ .

```
>> Im[3+4I]
4
```

## InexactNumberQ

`InexactNumberQ[expr]`  
returns `True` if  $expr$  is not an exact number, and `False` otherwise.

```
>> InexactNumberQ[a]
False

>> InexactNumberQ[3.0]
True

>> InexactNumberQ[2/3]
False
```

`InexactNumberQ` can be applied to complex numbers:

```
>> InexactNumberQ[4.0+I]
True
```

## IntegerQ

`IntegerQ[expr]`  
returns `True` if  $expr$  is an integer, and `False` otherwise.

```
>> IntegerQ[3]
True

>> IntegerQ[Pi]
False
```

## Integer

`Integer`  
is the head of integers.



```
>> Head[5]
Integer
```

## MachineNumberQ

`MachineNumberQ[expr]`  
returns True if *expr* is a machine-precision real or complex number.

```
= True
>> MachineNumberQ
[3.14159265358979324]
False
>> MachineNumberQ[1.5 + 2.3 I]
True
>> MachineNumberQ
[2.71828182845904524 +
3.14159265358979324 I]
False
```

## Minus (-)

`Minus[expr]`  
is the negation of *expr*.

```
>> -a //FullForm
Times[-1, a]
```

Minus automatically distributes:

```
>> -(x - 2/3)
2/3 - x
```

Minus threads over lists:

```
>> -Range[10]
{-1, -2, -3, -4, -5,
-6, -7, -8, -9, -10}
```

## NumberQ

`NumberQ[expr]`  
returns True if *expr* is an explicit number, and False otherwise.

```
>> NumberQ[3+I]
True
>> NumberQ[5!]
True
>> NumberQ[Pi]
False
```

## Piecewise


`Piecewise[{{expr1, cond1}, ...}]`  
represents a piecewise function.  
`Piecewise[{{expr1, cond1}, ...}, expr]`  
represents a piecewise function with default *expr*.

Heaviside function

```
>> Piecewise[{{0, x <= 0}}, 1]
Piecewise[{{0, x <= 0}}, 1]
>> Integrate[Piecewise[{{1, x <= 0}, {-1, x > 0}}, x]
Piecewise[{{x, x <= 0}, {-x, True}}]
>> Integrate[Piecewise[{{1, x <= 0}, {-1, x > 0}}, {x, -1, 2}]
-1
```

Piecewise defaults to 0 if no other case is matching.

```
>> Piecewise[{{1, False}}]
0
>> Plot[Piecewise[{{Log[x], x > 0}, {x*-0.5, x < 0}}, {x, -1, 1}]
```



```
>> Piecewise[{{0 ^ 0, False}}, -1]
-1
```

## Plus (+)

`Plus[a, b, ...]`  
 $a + b + \dots$   
represents the sum of the terms  $a, b, \dots$

```
>> 1 + 2
3
```

Plus performs basic simplification of terms:

```
>> a + b + a
2a + b

>> a + a + 3 * a
5a

>> a + b + 4.5 + a + b + a + 2 +
1.5 b
6.5 + 3a + 3.5b
```

Apply Plus on a list to sum up its elements:

```
>> Plus @@ {2, 4, 6}
12
```

The sum of the first 1000 integers:

```
>> Plus @@ Range[1000]
500500
```


Plus has default value 0:

```
>> DefaultValues[Plus]
{HoldPattern[Default[Plus]]:>0}

>> a /. n_. + x_ :> {n, x}
{0, a}
```

The sum of 2 red circles and 3 red circles is...

```
>> 2 Graphics[{Red,Disk[]}] + 3
Graphics[{Red,Disk[]}]
```



5

## Pochhammer

`Pochhammer[a, n]`  
is the Pochhammer symbol  $(a)_n$ .

```
>> Pochhammer[4, 8]
6652800
```

## PossibleZeroQ

`PossibleZeroQ[expr]`  
returns True if basic symbolic and numerical methods suggest that `expr` has value zero, and False otherwise.

Test whether a numeric expression is zero:

```
>> PossibleZeroQ[E^(I Pi/4) - (-1)^(1/4)]
True
```

The determination is approximate.

Test whether a symbolic expression is likely to be identically zero:

```
>> PossibleZeroQ[(x + 1)(x - 1) - x^2 + 1]
True

>> PossibleZeroQ[(E + Pi)^2 - E^2 - Pi^2 - 2 E Pi]
True
```

Show that a numeric expression is nonzero:

```
>> PossibleZeroQ[E^Pi - Pi^E]
False

>> PossibleZeroQ[1/x + 1/y - (x + y)/(x y)]
True
```

Decide that a numeric expression is zero, based on approximate computations:

```
>> PossibleZeroQ[2^(2 I) - 2^(-2 I) - 2 I Sin[Log[4]]]
True

>> PossibleZeroQ[Sqrt[x^2] - x]
False
```

## Power (^)

`Power[a, b]`  
 $a \wedge b$   
 represents  $a$  raised to the power of  $b$ .

```
>> 4 ^ (1/2)
2


>> 4 ^ (1/3)
22/3

>> 3^123
48 519 278 097 689 642 681 ~
~155 855 396 759 336 072 ~
~749 841 943 521 979 872 827

>> (y ^ 2) ^ (1/2)
 $\sqrt{y^2}$ 

>> (y ^ 2) ^ 3
 $y^6$ 

>> Plot[Evaluate[Table[x^y, {y, 1,
5}]], {x, -1.5, 1.5},
AspectRatio -> 1]
```



Use a decimal point to force numeric evaluation:

```
>> 4.0 ^ (1/3)
1.5874
```

Power has default value 1 for its second argument:

```
>> DefaultValues[Power]
{HoldPattern[Default[Power, 2]] :> 1}

>> a /. x_ ^ n_. :> {x, n}
{a, 1}
```

Power can be used with complex numbers:

```
>> (1.5 + 1.0 I) ^ 3.5
-3.68294 + 6.95139 I

>> (1.5 + 1.0 I) ^ (3.5 + 1.5 I)
-3.19182 + 0.645659 I
```

## Product

`Product[expr, {i, imin, imax}]`  
 evaluates the discrete product of  $expr$  with  $i$  ranging from  $imin$  to  $imax$ .  
`Product[expr, {i, imax}]`  
 same as `Product[expr, {i, 1, imax}]`.  
`Product[expr, {i, imin, imax, di}]`  
 $i$  ranges from  $imin$  to  $imax$  in steps of  $di$ .  
`Product[expr, {i, imin, imax}, {j, jmin, jmax}, ...]`  
 evaluates  $expr$  as a multiple product, with  $\{i, \dots\}, \{j, \dots\}, \dots$  being in outermost-to-innermost order.

```
>> Product[k, {k, 1, 10}]
3 628 800

>> 10!
3 628 800

>> Product[x^k, {k, 2, 20, 2}]
 $x^{110}$ 

>> Product[2 ^ i, {i, 1, n}]
 $2^{\frac{n}{2} + \frac{n^2}{2}}$ 

>> Product[f[i], {i, 1, 7}]
f[1] f[2] f[3] f[4] f[5] f[6] f[7]
```

Symbolic products involving the factorial are evaluated:

```
>> Product[k, {k, 3, n}]
 $\frac{n!}{2}$ 
```

Evaluate the  $n$ th primorial:

```
>> primorial[0] = 1;

>> primorial[n_Integer] := Product[
Prime[k], {k, 1, n}];

>> primorial[12]
7 420 738 134 810
```

## Rational


**Rational**  
is the head of rational numbers.  
**Rational**[*a*, *b*]  
constructs the rational number  $a / b$ .

```
>> Head[1/2]
Rational
>> Rational[1, 2]
 $\frac{1}{2}$ 
```

## Re

**Re**[*z*]  
returns the real component of the complex number *z*.

```
>> Re[3+4I]
3
>> Plot[{Cos[a], Re[E^(I a)]}, {a,
0, 2 Pi}]
```



## RealNumberQ

**RealNumberQ**[*expr*]  
returns True if *expr* is an explicit number with no imaginary component.

```
>> RealNumberQ[10]
True
>> RealNumberQ[4.0]
True
>> RealNumberQ[1+I]
False
```

```
>> RealNumberQ[0 * I]
True
>> RealNumberQ[0.0 * I]
True
```

## Real

**Real**  
is the head of real (inexact) numbers.

```
>> x = 3. ^ -20;
>> InputForm[x]
2.8679719907924413*^-10
>> Head[x]
Real
```

## Sign

**Sign**[*x*]  
return -1, 0, or 1 depending on whether *x* is negative, zero, or positive.

```
>> Sign[19]
1
>> Sign[-6]
-1
>> Sign[0]
0
>> Sign[{-5, -10, 15, 20, 0}]
{-1, -1, 1, 1, 0}
>> Sign[3 - 4*I]
 $\frac{3}{5} - \frac{4I}{5}$ 
```

## Sqrt


**Sqrt**[*expr*]  
returns the square root of *expr*.

```
>> Sqrt[4]
2
```

```
>> Sqrt[5]
 $\sqrt{5}$ 
>> Sqrt[5] // N
2.23607
>> Sqrt[a]^2
a
```

Complex numbers:

```
>> Sqrt[-4]
2I
>> I == Sqrt[-1]
True
>> Plot[Sqrt[a^2], {a, -2, 2}]
```



## Subtract (-)

`Subtract[a, b]`  
 $a - b$   
 represents the subtraction of  $b$  from  $a$ .

```
>> 5 - 3
2
>> a - b // FullForm
Plus[a, Times[-1, b]]
>> a - b - c
a - b - c
>> a - (b - c)
a - b + c
```

## Sum

`Sum[expr, {i, imin, imax}]`  
 evaluates the discrete sum of  $expr$  with  $i$  ranging from  $imin$  to  $imax$ .  
`Sum[expr, {i, imax}]`  
 same as `Sum[expr, {i, 1, imax}]`.  
`Sum[expr, {i, imin, imax, di}]`  
 $i$  ranges from  $imin$  to  $imax$  in steps of  $di$ .  
`Sum[expr, {i, imin, imax}, {j, jmin, jmax}, ...]`  
 evaluates  $expr$  as a multiple sum, with  $\{i, \dots\}, \{j, \dots\}, \dots$  being in outermost-to-innermost order.

```
>> Sum[k, {k, 1, 10}]
55
```

Double sum:

```
>> Sum[i * j, {i, 1, 10}, {j, 1, 10}]
3025
```

Symbolic sums are evaluated:

```
>> Sum[k, {k, 1, n}]
 $\frac{n(1+n)}{2}$ 
>> Sum[k, {k, n, 2 n}]
 $\frac{3n(1+n)}{2}$ 
>> Sum[k, {k, I, I + 1}]
 $1 + 2I$ 
>> Sum[1 / k ^ 2, {k, 1, n}]
HarmonicNumber[n, 2]
>> Sum[f[i], {i, 1, 7}]
f[1] + f[2] + f[3] + f[4] + f[5] + f[6] + f[7]
```

Verify algebraic identities:

```
>> Sum[x ^ 2, {x, 1, y}] - y * (y + 1) * (2 * y + 1) / 6
0
```

Infinite sums:

```
>> Sum[1 / 2 ^ i, {i, 1, Infinity}]
1
>> Sum[1 / k ^ 2, {k, 1, Infinity}]
 $\frac{\pi^2}{6}$ 
```

## Times (\*)

```
Times[a, b, ...]  
a * b * ...  
a b ...  
    represents the product of the terms a, b, ...
```

```
>> 10 * 2  
    20  
  
>> 10 2  
    20  
  
>> a * a  
    a2  
  
>> x ^ 10 * x ^ -2  
    x8  
  
>> {1, 2, 3} * 4  
    {4, 8, 12}  
  
>> Times @@ {1, 2, 3, 4}  
    24  
  
>> IntegerLength[Times@@Range  
    [5000]]  
    16326
```

Times has default value 1:

```
>> DefaultValues[Times]  
    {HoldPattern[Default[Times]]:>1}  
  
>> a /. n_. * x_ :> {n, x}  
    {1, a}
```

# XVII. Functional Programming

## Contents

---

Composition . . . . .	103	Identity . . . . .	104	SlotSequence . . . . .	104
Function (&) . . . . .	104	Slot . . . . .	104		

---

## Composition

`Composition[f, g]`  
returns the composition of two functions *f* and *g*.

```
>> Composition[f, g][x]
f[g[x]]

>> Composition[f, g, h][x, y, z]
f[g[h[x, y, z]]]

>> Composition[]
Identity

>> Composition[] [x]
x

>> Attributes[Composition]
{Flat, OneIdentity, Protected}

>> Composition[f, Composition[g, h]]
Composition[f, g, h]
```

## Function (&)

`Function[body]`  
*body* &  
represents a pure function with parameters #1, #2, etc.  
`Function[{x1, x2, ...}, body]`  
represents a pure function with parameters *x1*, *x2*, etc.  
`Function[{x1, x2, ...}, body, attr]`  
assume that the function has the attributes *attr*.

```
>> f := # ^ 2 &

>> f[3]
9

>> #^3& /@ {1, 2, 3}
{1, 8, 27}

>> #1+#2&[4, 5]
9
```

You can use `Function` with named parameters:

```
>> Function[{x, y}, x * y][2, 3]
6
```

Parameters are renamed, when necessary, to avoid confusion:

```
>> Function[{x}, Function[{y}, f[x, y]]][y]
Function[{y$}, f[y, y$]]

>> Function[{y}, f[x, y]] /. x->y
Function[{y}, f[y, y]]
```

```
>> Function[y, Function[x, y^x]][x]
      [y]
      xy

>> Function[x, Function[y, x^y]][x]
      [y]
      xy
```

Slots in inner functions are not affected by outer function application:

```
>> g[#] & [h[#]] & [5]
      g[h[5]]
```

## Identity

`Identity[x]`  
is the identity function, which returns  $x$  unchanged.

```
>> Identity[x]
      x

>> Identity[x, y]
      Identity[x, y]
```

## Slot

`#n`  
represents the  $n$ th argument to a pure function.

`#`  
is short-hand for `#1`.

`#0`  
represents the pure function itself.

```
>> #
      #1
```

Unused arguments are simply ignored:

```
>> {#1, #2, #3}&[1, 2, 3, 4, 5]
      {1, 2, 3}
```

Recursive pure functions can be written using `#0`:

```
>> If[#1<=1, 1, #1 #0[#1-1]]& [10]
      3 628 800
```

## SlotSequence

`##`  
is the sequence of arguments supplied to a pure function.

`##n`  
starts with the  $n$ th argument.

```
>> Plus[##]& [1, 2, 3]
      6

>> Plus[##2]& [1, 2, 3]
      5

>> FullForm[##]
      SlotSequence[1]
```



# XVIII. Compilation

## Contents

Compile . . . . .	105	CompiledCodeBox . .	105	CompiledFunction . .	106
-------------------	-----	---------------------	-----	----------------------	-----

## Compile

`Compile[{x1, x2, ...}, expr_]`  
Compiles *expr* assuming each *xi* is a *Real* number.  
`Compile[{x1, t1} {x2, t1} ..., expr_]`  
Compiles assuming each *xi* matches type *ti*.

```
>> cf = Compile[{x, y}, x + 2 y]
CompiledFunction[{x, y},
  x + 2y, - CompiledCode-]

>> cf[2.5, 4.3]
11.1

>> cf = Compile[{x, _Real}, Sin[x]]
CompiledFunction[{x},
  Sin[x], - CompiledCode-]

>> cf[1.4]
0.98545
```

Compile supports basic flow control

```
>> cf = Compile[{x, _Real}, {y,
  _Integer}, If[x == 0.0 && y <=
  0, 0.0, Sin[x ^ y] + 1 / Min[x,
  0.5]] + 0.5]
CompiledFunction[{x,
  y}, 0.5 + If[x == 0.0 && y <= 0,
  0., Sin[x^y] + 1 / Min[x, 0.5]],
  - CompiledCode-]
```

```
>> cf[3.5, 2]
2.18888
```

Loops and variable assignments are not yet supported

```
>> Compile[{a, _Integer}, {b,
  _Integer}, While[b != 0, {a, b}
  = {b, Mod[a, b]}; a] (* GCD of
  a, b *)
```

*ExpressionWhile[b!=0, {a,b} = {b, Mod[a,b]}; a could not be compiled.*

```
Function[{Global'a,
  Global'b}, While[b!=0, {a,
  b} = {b, Mod[a,b]}; a]
```

## CompiledCodeBox

Used internally by `CompileCode[]`.

## CompiledFunction

,

`CompiledFunction[args...]`  
represents compiled code for evaluating a compiled function.

```
>> sqr = Compile[{x}, x x]
CompiledFunction[{x},
  x^2, - CompiledCode-]

>> Head[sqr]
CompiledFunction
```

```
>> sqr[2]  
4.
```

# XIX. Options and Default Arguments

## Contents

---

Default . . . . .	107	NotOptionQ . . . . .	107	OptionValue . . . . .	108
FilterRules . . . . .	107	OptionQ . . . . .	108	Options . . . . .	109

---

## Default

`Default[f]`  
gives the default value for an omitted parameter of *f*.  
`Default[f, k]`  
gives the default value for a parameter on the *k*th position.  
`Default[f, k, n]`  
gives the default value for the *k*th parameter out of *n*.

Assign values to `Default` to specify default values.

```
>> Default[f] = 1
1
>> f[x_.] := x ^ 2
>> f[]
1
```

Default values are stored in `DefaultValues`:

```
>> DefaultValues[f]
{HoldPattern[Default[f]] :> 1}
```

You can use patterns for *k* and *n*:

```
>> Default[h, k_, n_] := {k, n}
```

Note that the position of a parameter is relative to the pattern, not the matching expression:

```
>> h[] /. h[___, ___, x_., y_., ___] -> {x, y}
{{3, 5}, {4, 5}}
```

## FilterRules

`FilterRules[rules, pattern]`  
gives those *rules* that have a left side that matches *pattern*.  
`FilterRules[rules, {pattern1, pattern2, ...}]`  
gives those *rules* that have a left side that match at least one of *pattern1*, *pattern2*, ...

```
>> FilterRules[{x -> 100, y -> 1000}, x]
{x -> 100}
>> FilterRules[{x -> 100, y -> 1000, z -> 10000}, {a, b, x, z}]
{x -> 100, z -> 10000}
```

## NotOptionQ

`NotOptionQ[expr]`  
returns `True` if *expr* does not have the form of a valid option specification.

```
>> NotOptionQ[x]
True
>> NotOptionQ[2]
True
>> NotOptionQ["abc"]
True
>> NotOptionQ[a -> True]
False
```

## OptionQ

`OptionQ[expr]`  
returns True if *expr* has the form of a valid option specification.

Examples of option specifications:

```
>> OptionQ[a -> True]
True

>> OptionQ[a :> True]
True

>> OptionQ[{a -> True}]
True

>> OptionQ[{a :> True}]
True
```

Options lists are flattened when they are applied, so

```
>> OptionQ[{a -> True, {b->1, "c
->2}}]
True

>> OptionQ[{a -> True, {b->1, c}}]
False

>> OptionQ[{a -> True, F[b->1, c
->2}}]
False
```

`OptionQ` returns False if its argument is not a valid option specification:

```
>> OptionQ[x]
False
```

## OptionValue

`OptionValue[name]`  
gives the value of the option *name* as specified in a call to a function with `OptionsPattern`.

`OptionValue[f, name]`  
recover the value of the option *name* associated to the symbol *f*.

`OptionValue[f, optvals, name]`  
recover the value of the option *name* associated to the symbol *f*, extracting the values from *optvals* if available.

`OptionValue[$\ldots$, list]`  
recover the value of the options in *list*.

```
>> f[a->3] /. f[OptionsPattern[{}]]
-> {OptionValue[a]}

{3}
```

Unavailable options generate a message:

```
>> f[a->3] /. f[OptionsPattern[{}]]
-> {OptionValue[b]}

Optionnamebnotfound.

{b}
```

The argument of `OptionValue` must be a symbol:

```
>> f[a->3] /. f[OptionsPattern[{}]]
-> {OptionValue[a+b]}

Argumenta
+ batposition1isexpectedtobeasymbol.

{OptionValue[a + b]}
```

However, it can be evaluated dynamically:

```
>> f[a->5] /. f[OptionsPattern[{}]]
-> {OptionValue[Symbol["a"]]}

{5}
```

## Options

`Options[f]`  
gives a list of optional arguments to *f* and their default values.

You can assign values to `Options` to specify options.

```
>> Options[f] = {n -> 2}
{n -> 2}

>> Options[f]
{n:>2}

>> f[x_, OptionsPattern[f]] := x ^
OptionValue[n]

>> f[x]
x2

>> f[x, n -> 3]
x3
```

Delayed option rules are evaluated just when the corresponding `OptionValue` is called:

```
>> f[a :> Print["value"]] /. f[
OptionsPattern[{}]] :> (
OptionValue[a]; Print["between
"]; OptionValue[a]);

value
between
value
```

In contrast to that, normal option rules are evaluated immediately:

```
>> f[a -> Print["value"]] /. f[
OptionsPattern[{}]] :> (
OptionValue[a]; Print["between
"]; OptionValue[a]);

value
between
```

Options must be rules or delayed rules:

```
>> Options[f] = {a}

{a}isnotavalidlistofoptionrules.
{a}
```

A single rule need not be given inside a list:

```
>> Options[f] = a -> b

a -> b

>> Options[f]

{a->b}
```

Options can only be assigned to symbols:

```
>> Options[a + b] = {a -> b}

Argumenta
+ batposition1isexpectedtobeasymbol.
{a -> b}
```

# XX. Comparison

## Contents

BooleanQ . . . . .	110	LessEqual (<=) . . . . .	111	SameQ (===) . . . . .	113
Equal (==) . . . . .	110	Max . . . . .	111	SympyComparison . . . . .	113
Greater (>) . . . . .	111	Min . . . . .	112	TrueQ . . . . .	113
GreaterEqual (>=) . . . . .	111	Negative . . . . .	112	Unequal (!=) . . . . .	113
Inequality . . . . .	111	NonNegative . . . . .	112	UnsameQ (!==) . . . . .	113
Less (<) . . . . .	111	NonPositive . . . . .	112	ValueQ . . . . .	113
		Positive . . . . .	112		

## BooleanQ

`BooleanQ[expr]`  
returns True if *expr* is either True or False.

```
>> BooleanQ[True]
True

>> BooleanQ[False]
True

>> BooleanQ[a]
False

>> BooleanQ[1 < 2]
True
```

## Equal (==)

`Equal[x, y]`  
`x == y`  
yields True if *x* and *y* are known to be equal, or False if *x* and *y* are known to be unequal.  
`lhs == rhs`  
represents the equation *lhs* = *rhs*.

```
>> a==a
True

>> a==b
a==b
```

```
>> 1==1.
True
```

Strings are allowed: `Equal["11", "11"] = True`  
`Equal["121", "11"] = False`  
Comparison to mismatched types is False:  
`Equal[11, "11"] = False`

Lists are compared based on their elements:

```
>> {{1}, {2}} == {{1}, {2}}
True

>> {1, 2} == {1, 2, 3}
False
```

Real values are considered equal if they only differ in their last digits:

```
>> 0.739085133215160642 ==
0.739085133215160641
True
```

```
>> 0.73908513321516064200000000 ==
0.73908513321516064100000000
False
```

Comparisons are done using the lower precision:

```
>> N[E, 100] == N[E, 150]
True
```

Symbolic constants are compared numerically:

```
>> E > 1
True

>> Pi == 3.14
False
```

## Greater (>)

```
Greater[x, y]
x > y
    yields True if  $x$  is known to be greater
    than  $y$ .
lhs > rhs
    represents the inequality  $lhs > rhs$ .
```

```
>> a > b > c //FullForm
Greater[a, b, c]

>> Greater[3, 2, 1]
True
```

## GreaterEqual (>=)

```
GreaterEqual[x, y]
x >= y
    yields True if  $x$  is known to be greater
    than or equal to  $y$ .
lhs >= rhs
    represents the inequality  $lhs \geq rhs$ .
```

## Inequality

```
Inequality
    is the head of expressions involving dif-
    ferent inequality operators (at least tem-
    porarily). Thus, it is possible to write
    chains of inequalities.
```

```
>> a < b <= c
a < b && b <= c

>> Inequality[a, Greater, b,
LessEqual, c]
a > b && b <= c

>> 1 < 2 <= 3
True

>> 1 < 2 > 0
True

>> 1 < 2 < -1
False
```

## Less (<)

```
Less[x, y]
x < y
    yields True if  $x$  is known to be less than  $y$ .
lhs < rhs
    represents the inequality  $lhs < rhs$ .
```

## LessEqual (<=)

```
LessEqual[x, y]
x <= y
    yields True if  $x$  is known to be less than
    or equal to  $y$ .
lhs <= rhs
    represents the inequality  $lhs \leq rhs$ .
```

## Max

```
Max[e_1, e_2, ..., e_i]
    returns the expression with the greatest
    value among the  $e_i$ .
```

Maximum of a series of values:

```
>> Max[4, -8, 1]
4

>> Max[E - Pi, Pi, E + Pi, 2 E]
E + Pi
```

Max flattens lists in its arguments:

```
>> Max[{1,2},3,{-3,3.5,-Infinity},{{1/2}}]
3.5
```

Max with symbolic arguments remains in sym-  
bolic form:

```
>> Max[x, y]
Max[x, y]

>> Max[5, x, -3, y, 40]
Max[40, x, y]
```

With no arguments, Max gives -Infinity:

```
>> Max[]
-∞
```

## Min

```
Min[e1, e2, ..., ei]  
returns the expression with the lowest  
value among the ei.
```

Minimum of a series of values:

```
>> Min[4, -8, 1]  
-8
```

```
>> Min[E - Pi, Pi, E + Pi, 2 E]  
E - Pi
```

Min flattens lists in its arguments:

```
>> Min[{1,2},3,{-3,3.5,-Infinity}  
      ],{{1/2}}]  
-∞
```

Min with symbolic arguments remains in symbolic form:

```
>> Min[x, y]  
Min[x, y]
```

```
>> Min[5, x, -3, y, 40]  
Min[-3, x, y]
```

With no arguments, Min gives Infinity:

```
>> Min[]  
∞
```

## Negative

```
Negative[x]  
returns True if x is a negative real number.
```

```
>> Negative[0]  
False
```

```
>> Negative[-3]  
True
```

```
>> Negative[10/7]  
False
```

```
>> Negative[1+2I]  
False
```

```
>> Negative[a + b]  
Negative[a + b]
```

## NonNegative

```
NonNegative[x]  
returns True if x is a positive real number  
or zero.
```

```
>> {Positive[0], NonNegative[0]}  
{False, True}
```

## NonPositive

```
NonPositive[x]  
returns True if x is a negative real number  
or zero.
```

```
>> {Negative[0], NonPositive[0]}  
{False, True}
```

## Positive

```
Positive[x]  
returns True if x is a positive real number.
```

```
>> Positive[1]  
True
```

Positive returns False if x is zero or a complex number:

```
>> Positive[0]  
False
```

```
>> Positive[1 + 2 I]  
False
```

## SameQ (===)

```
SameQ[x, y]  
x === y  
returns True if x and y are structurally  
identical.
```

Any object is the same as itself:

```
>> a===a  
True
```

Unlike Equal, SameQ only yields True if x and y have the same type:



```
>> {1==1., 1===1.}
{True, False}
```

## SympyComparison

### TrueQ

```
TrueQ[expr]
returns True if and only if expr is True.
```

```
>> TrueQ[True]
True

>> TrueQ[False]
False

>> TrueQ[a]
False
```

### Unequal (!=)

```
Unequal[x, y]
x != y
yields False if x and y are known to be
equal, or True if x and y are known to be
unequal.
lhs == rhs
represents the inequality lhs rhs.
```

```
>> 1 != 1.
False
```

Strings are allowed: Unequal["11", "11"] = False

Equal["121", "11"] = True

Comparison to mismatched types is True:

Equal[11, "11"] = True

Lists are compared based on their elements:

```
>> {1} != {2}
True

>> {1, 2} != {1, 2}
False

>> {a} != {a}
False

>> "a" != "b"
True

>> "a" != "a"
False
```

### UnsameQ (!=)

```
UnsameQ[x, y]
x != y
returns True if x and y are not structurally
identical.
```

```
>> a!=a
False

>> 1!=1.
True
```

### ValueQ

```
ValueQ[expr]
returns True if and only if expr is defined.
```

```
>> ValueQ[x]
False

>> x = 1;

>> ValueQ[x]
True
```

# XXI. Linear algebra

## Contents

BrayCurtisDistance . . .	114	FittedModel . . . . .	116	NullSpace . . . . .	119
CanberraDistance . . .	114	Inverse . . . . .	116	PseudoInverse . . . . .	119
ChessboardDistance .	114	LeastSquares . . . . .	116	QRDecomposition . .	119
CosineDistance . . . .	115	LinearModelFit . . . .	117	RowReduce . . . . .	119
Cross . . . . .	115	LinearSolve . . . . .	117	SingularValueDecom- position . . . . .	119
DesignMatrix . . . . .	115	ManhattanDistance . .	117	SquaredEuclideanDis- tance . . . . .	120
Det . . . . .	115	MatrixExp . . . . .	118	Tr . . . . .	120
Eigensystem . . . . .	115	MatrixPower . . . . .	118	VectorAngle . . . . .	120
Eigenvalues . . . . .	116	MatrixRank . . . . .	118		
Eigenvectors . . . . .	116	Norm . . . . .	118		
EuclideanDistance . .	116	Normalize . . . . .	118		

## BrayCurtisDistance

`BrayCurtisDistance[u, v]`  
returns the Bray Curtis distance between  $u$  and  $v$ .

```
>> BrayCurtisDistance[-7, 5]
6

>> BrayCurtisDistance[{-1, -1},
{10, 10}]
11
9
```

## CanberraDistance

`CanberraDistance[u, v]`  
returns the canberra distance between  $u$  and  $v$ , which is a weighted version of the Manhattan distance.

```
>> CanberraDistance[-7, 5]
1

>> CanberraDistance[{-1, -1}, {1,
1}]
2
```

## ChessboardDistance

`ChessboardDistance[u, v]`  
returns the chessboard distance (also known as Chebyshev distance) between  $u$  and  $v$ , which is the number of moves a king on a chessboard needs to get from square  $u$  to square  $v$ .

```
>> ChessboardDistance[-7, 5]
12

>> ChessboardDistance[{-1, -1}, {1,
1}]
2
```

## CosineDistance

`CosineDistance[u, v]`  
returns the cosine distance between  $u$  and  $v$ .

```
>> N[CosineDistance[{7, 9}, {71,
89}]]
0.0000759646
```

```
>> CosineDistance[{a, b}, {c, d}]
1
+ 
$$\frac{-ac - bd}{\sqrt{\text{Abs}[a]^2 + \text{Abs}[b]^2} \sqrt{\text{Abs}[c]^2 + \text{Abs}[d]^2}}$$

```

## Cross

`Cross[a, b]`  
computes the vector cross product of  $a$  and  $b$ .

```
>> Cross[{x1, y1, z1}, {x2, y2, z2}]
{y1z2 - y2z1,
 -x1z2 + x2z1, x1y2 - x2y1}
>> Cross[{x, y}]
{-y, x}
>> Cross[{1, 2}, {3, 4, 5}]
The arguments are expected to be vectors of equal length,
and the number of arguments is expected to be less than 10.
Cross[{1, 2}, {3, 4, 5}]
```

## DesignMatrix

`DesignMatrix[m, f, x]`  
returns the design matrix.

```
>> DesignMatrix[{{2, 1}, {3, 4}, {5, 3}, {7, 6}}, x, x]
{{1, 2}, {1, 3}, {1, 5}, {1, 7}}
>> DesignMatrix[{{2, 1}, {3, 4}, {5, 3}, {7, 6}}, f[x], x]
{{1, f[2]}, {1, f[3]}, {1, f[5]}, {1, f[7]}}
```

## Det

`Det[m]`  
computes the determinant of the matrix  $m$ .

```
>> Det[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
-2
```

Symbolic determinant:

```
>> Det[{{a, b, c}, {d, e, f}, {g, h, i}}]
aei - afh - bdi + bfg + cdh - ceg
```

## Eigensystem

`Eigensystem[m]`  
returns the list {Eigenvalues[m], Eigenvectors[m]}.

```
>> Eigensystem[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
{{2, -1, 1}, {{1, 1, 1}, {1, -2, 1}, {-1, 0, 1}}}
```

## Eigenvalues

`Eigenvalues[m]`  
computes the eigenvalues of the matrix  $m$ . By default SymPy's routine is used. Sometimes this is slow and less good than the corresponding mpmath routine. Use option Method->"mpmath" if you want to use mpmath's routine instead.

Numeric eigenvalues are sorted in order of decreasing absolute value:

```
>> Eigenvalues[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
{2, -1, 1}
```

Symbolic eigenvalues:

```
>> Eigenvalues[{{Cos[theta], Sin[theta], 0}, {-Sin[theta], Cos[theta], 0}, {0, 0, 1}}] // Sort
{1, Cos[theta],
 
$$+ \sqrt{(-1 + \text{Cos}[\text{theta}]) (1 + \text{Cos}[\text{theta}])},$$

 Cos[theta],
 
$$- \sqrt{(-1 + \text{Cos}[\text{theta}]) (1 + \text{Cos}[\text{theta}])}}$$

```

```
>> Eigenvalues[{{7, 1}, {-4, 3}}]
{5,5}

>> Eigenvalues[{{7, 1}, {-4, 3}}]
{5,5}
```

## Eigenvectors

```
Eigenvectors[m]
  computes the eigenvectors of the matrix m.

>> Eigenvectors[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
{{1,1,1}, {1, -2,1}, {-1,0,1}}

>> Eigenvectors[{{1, 0, 0}, {0, 1, 0}, {0, 0, 0}}]
{{0,1,0}, {1,0,0}, {0,0,1}}

>> Eigenvectors[{{2, 0, 0}, {0, -1, 0}, {0, 0, 0}}]
{{1,0,0}, {0,1,0}, {0,0,1}}

>> Eigenvectors[{{0.1, 0.2}, {0.8, 0.5}}]
{{-0.355518, -1.15048}, {-0.62896, 0.777438}}
```

## EuclideanDistance

```
EuclideanDistance[u, v]
  returns the euclidean distance between u and v.

>> EuclideanDistance[-7, 5]
12

>> EuclideanDistance[{-1, -1}, {1, 1}]
2√2

>> EuclideanDistance[{a, b}, {c, d}]
√Abs[a - c]2 + Abs[b - d]2
```

## FittedModel

### Inverse

```
Inverse[m]
  computes the inverse of the matrix m.
```

```
>> Inverse[{{1, 2, 0}, {2, 3, 0}, {3, 4, 1}}]
{{-3,2,0}, {2, -1,0}, {1, -2,1}}

>> Inverse[{{1, 0}, {0, 0}}]
The matrix {{1,0}, {0,0}} is singular.
Inverse[{{1,0}, {0,0}}]

>> Inverse[{{1, 0, 0}, {0, Sqrt[3]/2, 1/2}, {0, -1/2, Sqrt[3]/2}}]
{ {1,0,0}, {0, √3/2, -1/2}, {0, 1/2, √3/2} }
```

## LeastSquares

```
LeastSquares[m, b]
  computes the least squares solution to m x = b, finding an x that solves for b optimally.
```

```
>> LeastSquares[{{1, 2}, {2, 3}, {5, 6}}, {1, 5, 3}]
{ -28/13, 31/13 }

>> Simplify[LeastSquares[{{1, 2}, {2, 3}, {5, 6}}, {1, x, 3}]]
{ 12/13 - 8x/13, -4/13 + 7x/13 }

>> LeastSquares[{{1, 1, 1}, {1, 1, 2}}, {1, 3}]
Solving for underdetermined system not implemented.
LeastSquares[{{1, 1, 1}, {1, 1, 2}}, {1, 3}]
```

## LinearModelFit

`LinearModelFit[m, f, x]`  
returns the design matrix.

```
>> m = LinearModelFit[{{2, 1}, {3, 4}, {5, 3}, {7, 6}}, x, x];

>> m["BasisFunctions"]
{1, x}

>> m["BestFit"]
0.186441 + 0.779661x

>> m["BestFitParameters"]
{0.186441, 0.779661}

>> m["DesignMatrix"]
{{1, 2}, {1, 3}, {1, 5}, {1, 7}}

>> m["Function"]
0.186441 + 0.779661#1&

>> m["Response"]
{1, 4, 3, 6}

>> m["FitResiduals"]
{-0.745763, 1.47458, -1.08475, 0.355932}

>> m = LinearModelFit[{{2, 2, 1}, {3, 2, 4}, {5, 6, 3}, {7, 9, 6}}, {Sin[x], Cos[y]}, {x, y}];

>> m["BasisFunctions"]
{1, Sin[x], Cos[y]}

>> m["Function"]
3.33077 - 5.65221Cos[#2] - 5.01042Sin[#1]&

>> m = LinearModelFit[{{1, 4}, {1, 5}, {1, 7}}, {1, 2, 3}];

>> m["BasisFunctions"]
{#1, #2}

>> m["FitResiduals"]
{-0.142857, 0.214286, -0.0714286}
```

## LinearSolve

`LinearSolve[matrix, right]`  
solves the linear equation system  $matrix \cdot x = right$  and returns one corresponding solution  $x$ .

```
>> LinearSolve[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}, {1, 2, 3}]
{0, 1, 2}
```

Test the solution:

```
>> {{1, 1, 0}, {1, 0, 1}, {0, 1, 1}} . {0, 1, 2}
{1, 2, 3}
```

If there are several solutions, one arbitrary solution is returned:

```
>> LinearSolve[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {1, 1, 1}]
{-1, 1, 0}
```

Infeasible systems are reported:

```
>> LinearSolve[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {1, -2, 3}]
```

*Linearequationencounteredthathasnosolution.*

```
LinearSolve[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {1, -2, 3}]
```

## ManhattanDistance

`ManhattanDistance[u, v]`  
returns the Manhattan distance between  $u$  and  $v$ , which is the number of horizontal or vertical moves in the gridlike Manhattan city layout to get from  $u$  to  $v$ .

```
>> ManhattanDistance[-7, 5]
12

>> ManhattanDistance[{-1, -1}, {1, 1}]
4
```

## MatrixExp

`MatrixExp[m]`  
computes the exponential of the matrix *m*.

```
>> MatrixExp[{{0, 2}, {0, 1}}]
{{1, -2 + 2E}, {0, E}}

>> MatrixExp[{{1.5, 0.5}, {0.5, 2.0}}]
{{5.16266, 3.02952},
 {3.02952, 8.19218}}
```

## MatrixPower

`MatrixPower[m, n]`  
computes the *n*th power of a matrix *m*.

```
>> MatrixPower[{{1, 2}, {1, 1}}, 10]
{{3363, 4756}, {2378, 3363}}

>> MatrixPower[{{1, 2}, {2, 5}}, -3]
{{169, -70}, {-70, 29}}
```

## MatrixRank

`MatrixRank[matrix]`  
returns the rank of *matrix*.

```
>> MatrixRank[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}]
2

>> MatrixRank[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
3

>> MatrixRank[{{a, b}, {3 a, 3 b}}]
1
```

## Norm

`Norm[m, l]`  
computes the *l*-norm of matrix *m* (currently only works for vectors!).

`Norm[m]`  
computes the 2-norm of matrix *m* (currently only works for vectors!).

```
>> Norm[{1, 2, 3, 4}, 2]
 $\sqrt{30}$ 

>> Norm[{10, 100, 200}, 1]
310

>> Norm[{a, b, c}]
 $\sqrt{\text{Abs}[a]^2 + \text{Abs}[b]^2 + \text{Abs}[c]^2}$ 

>> Norm[{-100, 2, 3, 4}, Infinity]
100

>> Norm[1 + I]
 $\sqrt{2}$ 
```

## Normalize

`Normalize[v]`  
calculates the normalized vector *v*.

`Normalize[z]`  
calculates the normalized complex number *z*.

```
>> Normalize[{1, 1, 1, 1}]
 $\left\{ \frac{1}{2}, \frac{1}{2}, \frac{1}{2}, \frac{1}{2} \right\}$ 

>> Normalize[1 + I]
 $\left( \frac{1}{2} + \frac{I}{2} \right) \sqrt{2}$ 
```

## NullSpace

`NullSpace[matrix]`  
returns a list of vectors that span the nullspace of *matrix*.

```
>> NullSpace[{{1, 2, 3}, {4, 5, 6},
{7, 8, 9}}]
{{1, -2, 1}}
>> A = {{1, 1, 0}, {1, 0, 1}, {0,
1, 1}};
>> NullSpace[A]
{}
>> MatrixRank[A]
3
```

## PseudoInverse

`PseudoInverse[m]`

computes the Moore-Penrose pseudoinverse of the matrix  $m$ . If  $m$  is invertible, the pseudoinverse equals the inverse.

```
>> PseudoInverse[{{1, 2}, {2, 3},
{3, 4}}]
{{-11/6, -1/3, 7/6}, {4/3, 1/3, -2/3}}
>> PseudoInverse[{{1, 2, 0}, {2, 3,
0}, {3, 4, 1}}]
{{-3, 2, 0}, {2, -1, 0}, {1, -2, 1}}
>> PseudoInverse[{{1.0, 2.5}, {2.5,
1.0}}]
{{-0.190476, 0.47619},
{0.47619, -0.190476}}
```

## QRDecomposition

`QRDecomposition[m]`

computes the QR decomposition of the matrix  $m$ .

```
>> QRDecomposition[{{1, 2}, {3, 4},
{5, 6}}]
{{{{sqrt(35)/35, 3*sqrt(35)/35, sqrt(35)/7},
{{13*sqrt(210)/210, 2*sqrt(210)/105},
{-sqrt(210)/42}}}, {{sqrt(35),
44*sqrt(35)/35}, {0, 2*sqrt(210)/35}}}}
```

## RowReduce

`RowReduce[matrix]`

returns the reduced row-echelon form of  $matrix$ .

```
>> RowReduce[{{1, 0, a}, {1, 1, b
}}]
{{1, 0, a}, {0, 1, -a + b}}
>> RowReduce[{{1, 2, 3}, {4, 5, 6},
{7, 8, 9}}] // MatrixForm
( 1  0  -1
 0  1   2
 0  0   0 )
```

## SingularValueDecomposition

`SingularValueDecomposition[m]`

calculates the singular value decomposition for the matrix  $m$ .

`SingularValueDecomposition` returns  $u$ ,  $s$ ,  $w$  such that  $m=usv$ ,  $uu=1$ ,  $vv=1$ , and  $s$  is diagonal.

```
>> SingularValueDecomposition
[{{1.5, 2.0}, {2.5, 3.0}}]
{{{{0.538954, 0.842335}, {0.842335,
-0.538954}}, {{4.63555, 0},
{0, 0.107862}}, {{0.628678, 0.777~
666}, {-0.777666, 0.628678}}}}
```

## SquaredEuclideanDistance

`SquaredEuclideanDistance[ $u$ ,  $v$ ]`  
returns squared the euclidean distance  
between  $u$  and  $v$ .

```
>> SquaredEuclideanDistance[-7, 5]
144

>> SquaredEuclideanDistance[{-1,
-1}, {1, 1}]
8
```

## Tr

`Tr[ $m$ ]`  
computes the trace of the matrix  $m$ .

```
>> Tr[{{1, 2, 3}, {4, 5, 6}, {7, 8,
9}}]
15
```

Symbolic trace:

```
>> Tr[{{a, b, c}, {d, e, f}, {g, h,
i}}]
 $a + e + i$ 
```

## VectorAngle

`VectorAngle[ $u$ ,  $v$ ]`  
gives the angles between vectors  $u$  and  $v$

```
>> VectorAngle[{1, 0}, {0, 1}]
 $\frac{\text{Pi}}{2}$ 

>> VectorAngle[{1, 2}, {3, 1}]
 $\frac{\text{Pi}}{4}$ 

>> VectorAngle[{1, 1, 0}, {1, 0,
1}]
 $\frac{\text{Pi}}{3}$ 
```



## XXII. Attributes

There are several builtin-attributes which have a predefined meaning in *Mathics*. However, you can set any symbol as an attribute, in contrast to *Mathematica*®.

### Contents

Attributes . . . . .	121	HoldRest . . . . .	122	Protect . . . . .	124
ClearAttributes . . . . .	122	Listable . . . . .	123	Protected . . . . .	124
Constant . . . . .	122	Locked . . . . .	123	ReadProtected . . . . .	125
Flat . . . . .	122	NHoldAll . . . . .	123	SequenceHold . . . . .	125
HoldAll . . . . .	122	NHoldFirst . . . . .	123	SetAttributes . . . . .	125
HoldAllComplete . . . . .	122	NHoldRest . . . . .	123	Unprotect . . . . .	125
HoldFirst . . . . .	122	OneIdentity . . . . .	123		
		Orderless . . . . .	124		

### Attributes

`Attributes[symbol]`  
returns the attributes of *symbol*.  
`Attributes[symbol] = {attr1, attr2}`  
sets the attributes of *symbol*, replacing any existing attributes.

```
>> Attributes[Plus]
{Flat, Listable, NumericFunction,
 OneIdentity, Orderless, Protected}
```

Attributes always considers the head of an expression:

```
>> Attributes[a + b + c]
{Flat, Listable, NumericFunction,
 OneIdentity, Orderless, Protected}
```

You can assign values to Attributes to set attributes:

```
>> Attributes[f] = {Flat, Orderless}
{Flat, Orderless}

>> f[b, f[a, c]]
f[a, b, c]
```

Attributes must be symbols:

```
>> Attributes[f] := {a + b}
Argumenta
+ bat position 1 is expected to be a symbol.
$Failed
```

Use Symbol to convert strings to symbols:

```
>> Attributes[f] = Symbol["Listable"]
Listable

>> Attributes[f]
{Listable}
```

### ClearAttributes

`ClearAttributes[symbol, attrib]`  
removes *attrib* from *symbol*'s attributes.

```
>> SetAttributes[f, Flat]

>> Attributes[f]
{Flat}

>> ClearAttributes[f, Flat]

>> Attributes[f]
{}
```

Attributes that are not even set are simply ig-

nored:

```
>> ClearAttributes[{f}, {Flat}]

>> Attributes[f]
{}
```

## Constant

Constant

is an attribute that indicates that a symbol is a constant.

Mathematical constants like `E` have attribute `Constant`:

```
>> Attributes[E]
{Constant, Protected, ReadProtected}
```

Constant symbols cannot be used as variables in `Solve` and related functions:

```
>> Solve[x + E == 0, E]
Eisnotavalidvariable.
Solve[E + x==0, E]
```

## Flat

Flat

is an attribute that specifies that nested occurrences of a function should be automatically flattened.

A symbol with the `Flat` attribute represents an associative mathematical operation:

```
>> SetAttributes[f, Flat]

>> f[a, f[b, c]]
f[a, b, c]
```

`Flat` is taken into account in pattern matching:

```
>> f[a, b, c] /. f[a, b] -> d
f[d, c]
```

## HoldAll

HoldAll

is an attribute specifying that all arguments of a function should be left unevaluated.

```
>> Attributes[Function]
{HoldAll, Protected}
```

## HoldAllComplete

HoldAllComplete

is an attribute that includes the effects of `HoldAll` and `SequenceHold`, and also protects the function from being affected by the upvalues of any arguments.

`HoldAllComplete` even prevents upvalues from being used, and includes `SequenceHold`.

```
>> SetAttributes[f, HoldAllComplete]

>> f[a] ^= 3;

>> f[a]
f[a]

>> f[Sequence[a, b]]
f[Sequence[a, b]]
```

## HoldFirst

HoldFirst

is an attribute specifying that the first argument of a function should be left unevaluated.

```
>> Attributes[Set]
{HoldFirst, Protected, SequenceHold}
```

## HoldRest

HoldRest

is an attribute specifying that all but the first argument of a function should be left unevaluated.

```
>> Attributes[If]
{HoldRest, Protected}
```

## Listable

### Listable

is an attribute specifying that a function should be automatically applied to each element of a list.

```
>> SetAttributes[f, Listable]

>> f[{1, 2, 3}, {4, 5, 6}]
{f[1,4], f[2,5], f[3,6]}

>> f[{1, 2, 3}, 4]
{f[1,4], f[2,4], f[3,4]}

>> {{1, 2}, {3, 4}} + {5, 6}
{{6,7}, {9,10}}
```

## Locked

### Locked

is an attribute that prevents attributes on a symbol from being modified.

The attributes of Locked symbols cannot be modified:

```
>> Attributes[lock] = {Flat, Locked}
};

>> SetAttributes[lock, {}]
Symbollockislocked.

>> ClearAttributes[lock, Flat]
Symbollockislocked.

>> Attributes[lock] = {}
Symbollockislocked.
{}

>> Attributes[lock]
{Flat, Locked}
```

However, their values might be modified (as long as they are not Protected too):

```
>> lock = 3
3
```

## NHoldAll

### NHoldAll

is an attribute that protects all arguments of a function from numeric evaluation.

```
>> N[f[2, 3]]
f[2.,3.]

>> SetAttributes[f, NHoldAll]

>> N[f[2, 3]]
f[2,3]
```

## NHoldFirst

### NHoldFirst

is an attribute that protects the first argument of a function from numeric evaluation.

## NHoldRest

### NHoldRest

is an attribute that protects all but the first argument of a function from numeric evaluation.

## OneIdentity

### OneIdentity

is an attribute specifying that  $f[x]$  should be treated as equivalent to  $x$  in pattern matching.

OneIdentity affects pattern matching:

```
>> SetAttributes[f, OneIdentity]

>> a /. f[args___] -> {args}
{a}
```

It does not affect evaluation:

```
>> f[a]
f[a]
```

## Orderless

### Orderless

is an attribute that can be assigned to a symbol  $f$  to indicate that the elements  $ei$  in expressions of the form  $f[e1, e2, \dots]$  should automatically be sorted into canonical order. This property is accounted for in pattern matching.

The leaves of an Orderless function are automatically sorted:

```
>> SetAttributes[f, Orderless]
```

```
>> f[c, a, b, a + b, 3, 1.0]
f[1., 3, a, b, c, a + b]
```

A symbol with the Orderless attribute represents a commutative mathematical operation.

```
>> f[a, b] == f[b, a]
True
```

Orderless affects pattern matching:

```
>> SetAttributes[f, Flat]
```

```
>> f[a, b, c] /. f[a, c] -> d
f[b, d]
```

## Protect

### Protect[s1, s2, ...]

sets the attribute Protected for the symbols  $si$ .

### Protect[str1, str2, ...]

protects all symbols whose names textually match  $stri$ .

```
>> A = {1, 2, 3};
```

```
>> Protect[A]
```

```
>> A[[2]] = 4;
Symbol A is Protected.
```

```
>> A
{1, 2, 3}
```

## Protected

### Protected

is an attribute that prevents values on a symbol from being modified.

Values of Protected symbols cannot be modified:

```
>> Attributes[p] = {Protected};
```

```
>> p = 2;
Symbol p is Protected.
```

```
>> f[p] ^= 3;
Tag p in f[p] is Protected.
```

```
>> Format[p] = "text";
Symbol p is Protected.
```

However, attributes might still be set:

```
>> SetAttributes[p, Flat]
```

```
>> Attributes[p]
{Flat, Protected}
```

Thus, you can easily remove the attribute Protected:

```
>> Attributes[p] = {};
```

```
>> p = 2
2
```

You can also use Protect or Unprotect, resp.

```
>> Protect[p]
```

```
>> Attributes[p]
{Protected}
```

```
>> Unprotect[p]
```

If a symbol is Protected and Locked, it can never be changed again:

```
>> SetAttributes[p, {Protected, Locked}]
```

```
>> p = 2
Symbol p is Protected.
2
```

```
>> Unprotect[p]
Symbol p is locked.
```

## ReadProtected

`ReadProtected`  
is an attribute that prevents values on a symbol from being read.

Values associated with `ReadProtected` symbols cannot be seen in `Definition`:

```
>> ClearAll[p]

>> p = 3;

>> Definition[p]
      p = 3

>> SetAttributes[p, ReadProtected]

>> Definition[p]
      Attributes[p] = {ReadProtected}
```

## SequenceHold

`SequenceHold`  
is an attribute that prevents `Sequence` objects from being spliced into a function's arguments.

Normally, `Sequence` will be spliced into a function:

```
>> f[Sequence[a, b]]
      f[a, b]
```

It does not for `SequenceHold` functions:

```
>> SetAttributes[f, SequenceHold]

>> f[Sequence[a, b]]
      f[Sequence[a, b]]
```

E.g., `Set` has attribute `SequenceHold` to allow assignment of sequences to variables:

```
>> s = Sequence[a, b];

>> s
      Sequence[a, b]

>> Plus[s]
      a + b
```

## SetAttributes

`SetAttributes[symbol, attrib]`  
adds *attrib* to the list of *symbol*'s attributes.

```
>> SetAttributes[f, Flat]

>> Attributes[f]
      {Flat}
```

Multiple attributes can be set at the same time using lists:

```
>> SetAttributes[{f, g}, {Flat,
      Orderless}]

>> Attributes[g]
      {Flat, Orderless}
```

## Unprotect

`Unprotect[s1, s2, ...]`  
removes the attribute `Protected` for the symbols *si*.  
`Unprotect[str]`  
unprotects symbols whose names textually match *str*.

# XXIII. Assignment

## Contents

AddTo (+=) . . . . .	126	Information (??) . . . . .	129	SubtractFrom (-=) . . . . .	132
Clear . . . . .	127	LoadModule . . . . .	130	TagSet . . . . .	133
ClearAll . . . . .	127	Messages . . . . .	130	TagSetDelayed . . . . .	133
Decrement (--). . . . .	127	NValues . . . . .	130	TimesBy (*=) . . . . .	133
DefaultValues . . . . .	127	OwnValues . . . . .	130	Unset (=.) . . . . .	133
Definition . . . . .	128	PreDecrement (--). . . . .	131	UpSet (^=) . . . . .	134
DivideBy (/=) . . . . .	129	PreIncrement (++) . . . . .	131	UpSetDelayed (^:=) . . . . .	134
DownValues . . . . .	129	Set (=) . . . . .	131	UpValues . . . . .	134
Increment (++) . . . . .	129	SetDelayed (:=) . . . . .	132		
		SubValues . . . . .	132		

## AddTo (+=)

AddTo[x, dx]  
 $x += dx$   
 is equivalent to  $x = x + dx$ .

```
>> a = 10;

>> a += 2
12

>> a
12
```

## Clear

Clear[symb1, symb2, ...]  
 clears all values of the given symbols.  
 The arguments can also be given as  
 strings containing symbol names.

```
>> x = 2;

>> Clear[x]

>> x
x

>> x = 2;
```

```
>> y = 3;

>> Clear["Global`*"]

>> x
x

>> y
y
```

ClearAll may not be called for Protected symbols.

```
>> Clear[Sin]
SymbolSinisProtected.
```

The values and rules associated with built-in symbols will not get lost when applying Clear (after unprotecting them):

```
>> Unprotect[Sin]

>> Clear[Sin]

>> Sin[Pi]
0
```

Clear does not remove attributes, messages, options, and default values associated with the symbols. Use ClearAll to do so.

```
>> Attributes[r] = {Flat, Orderless};

>> Clear["r"]
```

```
>> Attributes[r]
{Flat, Orderless}
```

## ClearAll

`ClearAll[symb1, symb2, ...]`  
clears all values, attributes, messages and options associated with the given symbols. The arguments can also be given as strings containing symbol names.

```
>> x = 2;

>> ClearAll[x]

>> x
x

>> Attributes[r] = {Flat, Orderless};

>> ClearAll[r]

>> Attributes[r]
{}
```

`ClearAll` may not be called for Protected or Locked symbols.

```
>> Attributes[lock] = {Locked};

>> ClearAll[lock]
Symbollockislocked.
```

## Decrement (--)

`Decrement[x]`  
`x--`  
decrements  $x$  by 1, returning the original value of  $x$ .

```
>> a = 5;

>> a--
5

>> a
4
```

## DefaultValues

`DefaultValues[symbol]`  
gives the list of default values associated with *symbol*.

```
>> Default[f, 1] = 4
4

>> DefaultValues[f]
{HoldPattern[Default[f, 1]] :> 4}
```

You can assign values to `DefaultValues`:

```
>> DefaultValues[g] = {Default[g] -> 3};

>> Default[g, 1]
3

>> g[x_.] := {x}

>> g[a]
{a}

>> g[]
{3}
```

## Definition

`Definition[symbol]`  
prints as the user-defined values and rules associated with *symbol*.

`Definition` does not print information for ReadProtected symbols. `Definition` uses `InputForm` to format values.

```
>> a = 2;

>> Definition[a]
a = 2

>> f[x_] := x ^ 2

>> g[f] ^:= 2

>> Definition[f]
f[x_] = x^2
g[f] ^:= 2
```

`Definition` of a rather evolved (though meaningless) symbol:

```
>> Attributes[r] := {Orderless}

>> Format[r[args___]] := Infix[{
  args}, "~"]

>> N[r] := 3.5

>> Default[r, 1] := 2

>> r::msg := "My message"

>> Options[r] := {Opt -> 3}

>> r[arg_., OptionsPattern[r]] := {
  arg, OptionValue[Opt]}
```

Some usage:

```
>> r[z, x, y]
  x ~ y ~ z

>> N[r]
  3.5

>> r[]
  {2, 3}

>> r[5, Opt->7]
  {5, 7}
```

Its definition:

```
>> Definition[r]
  Attributes[r] = {Orderless}
  arg_ ~ OptionsPattern[r]
    = {arg, OptionValue[Opt]}
  N[r, MachinePrecision] = 3.5
  Format[args___, MathMLForm]
    = Infix[{args}, "~"]
  Format[args___,
  OutputForm] = Infix[{args}, "~"]
  Format[args___, StandardForm]
    = Infix[{args}, "~"]
  Format[args___,
  TeXForm] = Infix[{args}, "~"]
  Format[args___, TraditionalForm]
    = Infix[{args}, "~"]
  Default[r, 1] = 2
  Options[r] = {Opt -> 3}
```

For ReadProtected symbols, Definition just prints attributes, default values and options:

```
>> SetAttributes[r, ReadProtected]
```

```
>> Definition[r]
  Attributes[r] = {Orderless,
    ReadProtected}
  Default[r, 1] = 2
  Options[r] = {Opt -> 3}
```

This is the same for built-in symbols:

```
>> Definition[Plus]
  Attributes[Plus] = {Flat, Listable,
    NumericFunction,
    OneIdentity,
    Orderless, Protected}
  Default[Plus] = 0

>> Definition[Level]
  Attributes[Level] = {Protected}
  Options[Level] = {Heads -> False}
```

ReadProtected can be removed, unless the symbol is locked:

```
>> ClearAttributes[r, ReadProtected]
]
```

Clear clears values:

```
>> Clear[r]

>> Definition[r]
  Attributes[r] = {Orderless}
  Default[r, 1] = 2
  Options[r] = {Opt -> 3}
```

ClearAll clears everything:

```
>> ClearAll[r]

>> Definition[r]
  Null
```

If a symbol is not defined at all, Null is printed:

```
>> Definition[x]
  Null
```

## DivideBy (/=)

```
DivideBy[x, dx]
x /= dx
is equivalent to x = x / dx.
```

```
>> a = 10;

>> a /= 2
  5
```



```
>> a
5
```

## DownValues

`DownValues[symbol]`  
gives the list of downvalues associated with *symbol*.

`DownValues` uses `HoldPattern` and `RuleDelayed` to protect the downvalues from being evaluated. Moreover, it has attribute `HoldAll` to get the specified symbol instead of its value.

```
>> f[x_] := x ^ 2
```

```
>> DownValues[f]
{HoldPattern[f[x_]] :> x^2}
```

Mathics will sort the rules you assign to a symbol according to their specificity. If it cannot decide which rule is more special, the newer one will get higher precedence.

```
>> f[x_Integer] := 2
```

```
>> f[x_Real] := 3
```

```
>> DownValues[f]
{HoldPattern[f[x_Real]] :> 3,
 HoldPattern[f[x_Integer]] :> 2,
 HoldPattern[f[x_]] :> x^2}
```

```
>> f[3]
2
```

```
>> f[3.]
3
```

```
>> f[a]
a^2
```

The default order of patterns can be computed using `Sort` with `PatternsOrderedQ`:

```
>> Sort[{x_, x_Integer},
PatternsOrderedQ]
{x_Integer, x_}
```

By assigning values to `DownValues`, you can override the default ordering:

```
>> DownValues[g] := {g[x_] :> x ^
2, g[x_Integer] :> x}
```

```
>> g[2]
4
```

Fibonacci numbers:

```
>> DownValues[fib] := {fib[0] -> 0,
fib[1] -> 1, fib[n_] :> fib[n -
1] + fib[n - 2]}
```

```
>> fib[5]
5
```

## Increment (++)

`Increment[x]`  
`x++`  
increments *x* by 1, returning the original value of *x*.

```
>> a = 2;
```

```
>> a++
2
```

```
>> a
3
```

Grouping of `Increment`, `PreIncrement` and `Plus`:

```
>> ++++a+++++2//Hold//FullForm
Hold[Plus[PreIncrement[
PreIncrement[Increment[
Increment[a]]]], 2]]
```

## Information (??)

`Information[symbol]`  
Prints information about a *symbol*

`Information` does not print information for

`ReadProtected` symbols. `Information` uses `InputForm` to format values.

## LoadModule

`LoadModule[module]`  
'Load Mathics definitions from the python module *module*

```
>> LoadModule["nomodule"]
      Pythonmodulenomoduledoesnotexist.
      $Failed

>> LoadModule["sys"]
      Pythonmodulesysisnotapymathicsmodule.
      $Failed
```

## Messages

`Messages[symbol]`  
gives the list of messages associated with *symbol*.

```
>> a::b = "foo"
      foo

>> Messages[a]
      {HoldPattern[a::b]:>foo}

>> Messages[a] = {a::c :> "bar"};

>> a::c // InputForm
      "bar"

>> Message[a::c]
      bar
```

## NValues

`NValues[symbol]`  
gives the list of numerical values associated with *symbol*.

```
>> NValues[a]
      {}

>> N[a] = 3;

>> NValues[a]
      {HoldPattern[N[a,
      MachinePrecision]]:>3}
```

You can assign values to `NValues`:

```
>> NValues[b] := {N[b,
      MachinePrecision] :> 2}

>> N[b]
      2.
```

Be sure to use `SetDelayed`, otherwise the left-hand side of the transformation rule will be evaluated immediately, causing the head of `N` to get lost. Furthermore, you have to include the precision in the rules; `MachinePrecision` will not be inserted automatically:

```
>> NValues[c] := {N[c] :> 3}

>> N[c]
      c
```

`Mathics` will gracefully assign any list of rules to `NValues`; however, inappropriate rules will never be used:

```
>> NValues[d] = {foo -> bar};

>> NValues[d]
      {HoldPattern[foo]:>bar}

>> N[d]
      d
```

## OwnValues

`OwnValues[symbol]`  
gives the list of ownvalues associated with *symbol*.

```
>> x = 3;

>> x = 2;

>> OwnValues[x]
      {HoldPattern[x]:>2}

>> x := y

>> OwnValues[x]
      {HoldPattern[x]:>y}

>> y = 5;

>> OwnValues[x]
      {HoldPattern[x]:>y}

>> Hold[x] /. OwnValues[x]
      Hold[y]

>> Hold[x] /. OwnValues[x] //
      ReleaseHold
      5
```

## PreDecrement (--)

**PreDecrement** [*x*]

--*x*  
decrements *x* by 1, returning the new value of *x*.

--*a* is equivalent to  $a = a - 1$ :

```
>> a = 2;
```

```
>> --a
1
```

```
>> a
1
```

## PreIncrement (++)

**PreIncrement** [*x*]

++*x*  
increments *x* by 1, returning the new value of *x*.

++*a* is equivalent to  $a = a + 1$ :

```
>> a = 2;
```

```
>> ++a
3
```

```
>> a
3
```

## Set (=)

**Set** [*expr*, *value*]

*expr* = *value*  
evaluates *value* and assigns it to *expr*.

{*s1*, *s2*, *s3*} = {*v1*, *v2*, *v3*}  
sets multiple symbols (*s1*, *s2*, ...) to the corresponding values (*v1*, *v2*, ...).

Set can be used to give a symbol a value:

```
>> a = 3
3
```

```
>> a
3
```

An assignment like this creates an ownvalue:

```
>> OwnValues[a]
{HoldPattern[a]>3}
```

You can set multiple values at once using lists:

```
>> {a, b, c} = {10, 2, 3}
{10,2,3}
```

```
>> {a, b, {c, {d}}} = {1, 2, {{c1,
c2}, {a}}}
{1,2, {{c1,c2}, {10}}}
```

```
>> d
10
```

Set evaluates its right-hand side immediately and assigns it to the left-hand side:

```
>> a
1
```

```
>> x = a
1
```

```
>> a = 2
2
```

```
>> x
1
```

Set always returns the right-hand side, which you can again use in an assignment:

```
>> a = b = c = 2;
```

```
>> a == b == c == 2
True
```

Set supports assignments to parts:

```
>> A = {{1, 2}, {3, 4}};
```

```
>> A[[1, 2]] = 5
5
```

```
>> A
{{1,5}, {3,4}}
```

```
>> A[1;;, 2] = {6, 7}
{6,7}
```

```
>> A
{{1,6}, {3,7}}
```

Set a submatrix:

```
>> B = {{1, 2, 3}, {4, 5, 6}, {7,
8, 9}};
```

```
>> B[[1;;2, 2;;-1]] = {{t, u}, {y,
z}};
```

```
>> B
{{1,t,u}, {4,y,z}, {7,8,9}}
```

## SetDelayed (:=)

```
SetDelayed[expr, value]
expr := value
    assigns value to expr, without evaluating
    value.
```

SetDelayed is like Set, except it has attribute HoldAll, thus it does not evaluate the right-hand side immediately, but evaluates it when needed.

```
>> Attributes[SetDelayed]
    {HoldAll, Protected, SequenceHold}

>> a = 1
    1

>> x := a

>> x
    1
```

Changing the value of *a* affects *x*:

```
>> a = 2
    2

>> x
    2
```

Condition (/;) can be used with SetDelayed to make an assignment that only holds if a condition is satisfied:

```
>> f[x_] := p[x] /; x>0

>> f[3]
    p[3]

>> f[-3]
    f[-3]
```

## SubValues

```
SubValues[symbol]
    gives the list of subvalues associated with
    symbol.
```

```
>> f[1][x_] := x

>> f[2][x_] := x ^ 2
```

```
>> SubValues[f]
    {HoldPattern[f[2][x_]] :>x^2,
     HoldPattern[f[1][x_]] :>x}

>> Definition[f]
    f[2][x_] = x^2
    f[1][x_] = x
```

## SubtractFrom (==)

```
SubtractFrom[x, dx]
x -= dx
    is equivalent to x = x - dx.
```

```
>> a = 10;

>> a -= 2
    8

>> a
    8
```

## TagSet

```
TagSet[f, expr, value]
f /: expr = value
    assigns value to expr, associating the cor-
    responding rule with the symbol f.
```

Create an upvalue without using UpSet :

```
>> x /: f[x] = 2
    2

>> f[x]
    2

>> DownValues[f]
    {}

>> UpValues[x]
    {HoldPattern[f[x]] :>2}
```

The symbol *f* must appear as the ultimate head of *lhs* or as the head of a leaf in *lhs*:

```
>> x /: f[g[x]] = 3;
    Tagxnotfoundortoodeepforanassignedrule.

>> g /: f[g[x]] = 3;
```

```
>> f[g[x]]
3
```

## TagSetDelayed

`TagSetDelayed[f, expr, value]`  
 $f$   $/:$   $expr := value$   
 is the delayed version of `TagSet`.

## TimesBy (\*=)

`TimesBy[x, dx]`  
 $x *= dx$   
 is equivalent to  $x = x * dx$ .

```
>> a = 10;
>> a *= 2
20
>> a
20
```

## Unset (=.)

`Unset[x]`  
 $x =.$   
 removes any value belonging to  $x$ .

```
>> a = 2
2
>> a =.
>> a
a
```

Unsetting an already unset or never defined variable will not change anything:

```
>> a =.
>> b =.
```

Unset can unset particular function values. It will print a message if no corresponding rule is found.

```
>> f[x_] =.
Assignment on f for f[x_] not found.
$Failed
>> f[x_] := x ^ 2
>> f[3]
9
>> f[x_] =.
>> f[3]
f[3]
```

You can also unset `OwnValues`, `DownValues`, `SubValues`, and `UpValues` directly. This is equivalent to setting them to `{}`.

```
>> f[x_] = x; f[0] = 1;
>> DownValues[f] =.
>> f[2]
f[2]
Unset threads over lists:
>> a = b = 3;
>> {a, {b}} =.
{Null, {Null}}
```

## UpSet (^=)

$f[x] \hat{=} expression$   
 evaluates  $expression$  and assigns it to the value of  $f[x]$ , associating the value with  $x$ .

UpSet creates an upvalue:

```
>> a[b] ^= 3;
>> DownValues[a]
{}
>> UpValues[b]
{HoldPattern[a[b]] :> 3}
>> a ^= 3
Nonatomic expression expected.
3
```

You can use `UpSet` to specify special values like format values. However, these values will not

be saved in UpValues:

```
>> Format[r] ^= "custom";

>> r
custom

>> UpValues[r]
{}
```

## UpSetDelayed (^:=)

`UpSetDelayed[expression, value]`  
*expression* ^= *value*  
assigns *expression* to the value of *f[x]* (without evaluating *expression*), associating the value with *x*.

```
>> a[b] ^= x

>> x = 2;

>> a[b]
2

>> UpValues[b]
{HoldPattern[a[b]]:>x}
```

## UpValues

`UpValues[symbol]`  
gives the list of upvalues associated with *symbol*.

```
>> a + b ^= 2
2

>> UpValues[a]
{HoldPattern[a + b]:>2}

>> UpValues[b]
{HoldPattern[a + b]:>2}
```

You can assign values to UpValues:

```
>> UpValues[pi] := {Sin[pi] :> 0}

>> Sin[pi]
0
```

# XXIV. Tensors

## Contents

ArrayDepth . . . . .	135	Dot (.) . . . . .	136	Outer . . . . .	137
ArrayQ . . . . .	135	IdentityMatrix . . . . .	136	Transpose . . . . .	137
DiagonalMatrix . . . . .	135	Inner . . . . .	136	VectorQ . . . . .	137
Dimensions . . . . .	136	MatrixQ . . . . .	136		

## ArrayDepth

`ArrayDepth[a]`  
returns the depth of the non-ragged array *a*, defined as `Length[Dimensions[a]]`.

```
>> ArrayDepth[{{a,b},{c,d}}]
2
>> ArrayDepth[x]
0
```

## ArrayQ

`ArrayQ[expr]`  
tests whether *expr* is a full array.  
`ArrayQ[expr, pattern]`  
also tests whether the array depth of *expr* matches *pattern*.  
`ArrayQ[expr, pattern, test]`  
furthermore tests whether *test* yields True for all elements of *expr*. `ArrayQ[expr]` is equivalent to `ArrayQ[expr, _, True&]`.

```
>> ArrayQ[a]
False
>> ArrayQ[{a}]
True
>> ArrayQ[{{a}},{{b,c}}]
False
```

```
>> ArrayQ[{{a, b}, {c, d}}, 2,
SymbolQ]
True
```

## DiagonalMatrix

`DiagonalMatrix[list]`  
gives a matrix with the values in *list* on its diagonal and zeroes elsewhere.

```
>> DiagonalMatrix[{1, 2, 3}]
{{1,0,0},{0,2,0},{0,0,3}}
>> MatrixForm[%]

$$\begin{pmatrix} 1 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & 3 \end{pmatrix}$$

```

## Dimensions

`Dimensions[expr]`  
returns a list of the dimensions of the expression *expr*.

A vector of length 3:

```
>> Dimensions[{a, b, c}]
{3}
```

A 3x2 matrix:

```
>> Dimensions[{{a, b}, {c, d}, {e, f}}]
{3,2}
```

Ragged arrays are not taken into account:

```
>> Dimensions[{{a, b}, {b, c}, {c,
    d, e}}]
{3}
```

The expression can have any head:

```
>> Dimensions[f[f[a, b, c]]]
{1,3}
```

## Dot (.)

```
Dot[x, y]
x . y
computes the vector dot product or matrix product  $x \cdot y$ .
```

Scalar product of vectors:

```
>> {a, b, c} . {x, y, z}
 $ax + by + cz$ 
```

Product of matrices and vectors:

```
>> {{a, b}, {c, d}} . {x, y}
 $\{ax + by, cx + dy\}$ 
```

Matrix product:

```
>> {{a, b}, {c, d}} . {{r, s}, {t,
    u}}
 $\{\{ar + bt, as + bu\}, \{cr + dt, cs + du\}\}$ 
```

```
>> a . b
a.b
```

## IdentityMatrix

```
IdentityMatrix[n]
gives the identity matrix with  $n$  rows and columns.
```

```
>> IdentityMatrix[3]
{{1,0,0}, {0,1,0}, {0,0,1}}
```

## Inner

```
Inner[f, x, y, g]
computes a generalised inner product of  $x$  and  $y$ , using a multiplication function  $f$  and an addition function  $g$ .
```

```
>> Inner[f, {a, b}, {x, y}, g]
 $g[f[a, x], f[b, y]]$ 
```

Inner can be used to compute a dot product:

```
>> Inner[Times, {a, b}, {c, d},
    Plus] == {a, b} . {c, d}
True
```

The inner product of two boolean matrices:

```
>> Inner[And, {{False, False}, {
    False, True}}, {{True, False}, {
    True, True}}, Or]
{{False, False}, {True, True}}
```

Inner works with tensors of any depth:

```
>> Inner[f, {{{a, b}}, {{c, d}}},
    {{1}, {2}}, g]
{{{g[f[a, 1], f[b, 2]]}},
    {{g[f[c, 1], f[d, 2]]}}}
```

## MatrixQ

```
MatrixQ[m]
returns True if  $m$  is a list of equal-length lists.
MatrixQ[m, f]
only returns True if  $f[x]$  returns True for each element  $x$  of the matrix  $m$ .
```

```
>> MatrixQ[{{1, 3}, {4.0, 3/2}},
    NumberQ]
True
```

## Outer

```
Outer[f, x, y]
computes a generalised outer product of  $x$  and  $y$ , using the function  $f$  in place of multiplication.
```



```
>> Outer[f, {a, b}, {1, 2, 3}]
{{f[a, 1], f[a, 2], f[a, 3]},
 {f[b, 1], f[b, 2], f[b, 3]}}
```

Outer product of two matrices:

```
>> Outer[Times, {{a, b}, {c, d}},
{{1, 2}, {3, 4}}]
{{{a, 2a}, {3a, 4a}}, {{b,
 2b}, {3b, 4b}}}, {{c, 2c}, {3c,
 4c}}, {{d, 2d}, {3d, 4d}}}]
```

Outer of multiple lists:

```
>> Outer[f, {a, b}, {x, y, z}, {1,
 2}]
{{{f[a, x, 1], f[a, x, 2]}, {f[
  a, y, 1], f[a, y, 2]}, {f[a, z, 1],
  f[a, z, 2]}}, {{f[b, x, 1], f[
  b, x, 2]}, {f[b, y, 1], f[b, y,
  2]}, {f[b, z, 1], f[b, z, 2]}}}]
```

Arrays can be ragged:

```
>> Outer[Times, {{1, 2}}, {{a, b},
{c, d, e}}]
{{{a, b}, {c, d, e}},
 {{2a, 2b}, {2c, 2d, 2e}}}]
```

Word combinations:

```
>> Outer[StringJoin, {"", "re", "un"}, {"cover", "draw", "wind"}, {"", "ing", "s"}] // InputForm
{{{ "cover", "covering", "covers"},
 { "draw", "drawing", "draws"},
 { "wind", "winding", "winds"}},
 {{ "recover", "recovering",
 "recovers"}, {"redraw",
 "redrawing", "redraws"},
 {"rewind", "rewinding",
 "rewinds"}}, {"uncover",
 "uncovering", "uncovers"},
 {"undraw", "undrawing",
 "undraws"}, {"unwind",
 "unwinding", "unwinds"}}]
```

Compositions of trigonometric functions:

```
>> trigs = Outer[Composition, {Sin,
  Cos, Tan}, {ArcSin, ArcCos,
  ArcTan}]
{{Composition[Sin, ArcSin],
  Composition[Sin, ArcCos],
  Composition[Sin, ArcTan]},
 {Composition[Cos, ArcSin],
  Composition[Cos, ArcCos],
  Composition[Cos, ArcTan]},
 {Composition[Tan, ArcSin],
  Composition[Tan, ArcCos],
  Composition[Tan, ArcTan]}}
```

Evaluate at 0:

```
>> Map[# [0] &, trigs, {2}]
{{0, 1, 0}, {1, 0, 1}, {0,
  ComplexInfinity, 0}}
```

## Transpose

**Transpose** $[m]$

transposes rows and columns in the matrix  $m$ .

```
>> Transpose[{{1, 2, 3}, {4, 5,
  6}}]
{{1, 4}, {2, 5}, {3, 6}}
```

```
>> MatrixForm[%]
```

$$\begin{pmatrix} 1 & 4 \\ 2 & 5 \\ 3 & 6 \end{pmatrix}$$

## VectorQ

**VectorQ** $[v]$

returns True if  $v$  is a list of elements which are not themselves lists.

**VectorQ** $[v, f]$

returns True if  $v$  is a vector and  $f[x]$  returns True for each element  $x$  of  $v$ .

```
>> VectorQ[{a, b, c}]
True
```

# XXV. Structure

## Contents

Apply (@@) . . . . .	138	Head . . . . .	140	Scan . . . . .	143
ApplyLevel (@@@) . . . . .	138	Map (/@) . . . . .	140	Sort . . . . .	143
AtomQ . . . . .	139	MapAt . . . . .	141	SortBy . . . . .	143
Combinatori- caOld'BinarySearch	139	MapIndexed . . . . .	142	SymbolName . . . . .	143
ByteCount . . . . .	139	MapThread . . . . .	142	SymbolQ . . . . .	144
Depth . . . . .	139	Null . . . . .	142	Symbol . . . . .	144
Flatten . . . . .	140	Operate . . . . .	142	Thread . . . . .	144
FreeQ . . . . .	140	Order . . . . .	142	Through . . . . .	144
		OrderedQ . . . . .	142		
		PatternsOrderedQ . . . . .	143		

## Apply (@@)

`Apply[f, expr]`  
`f @@ expr`  
 replaces the head of `expr` with `f`.  
`Apply[f, expr, levelspec]`  
 applies `f` on the parts specified by `levelspec`.

```
>> f @@ {1, 2, 3}
f[1,2,3]
```

```
>> Plus @@ {1, 2, 3}
6
```

The head of `expr` need not be `List`:

```
>> f @@ (a + b + c)
f[a,b,c]
```

Apply on level 1:

```
>> Apply[f, {a + b, g[c, d, e * f],
3}, {1}]
{f[a,b],f[c,d,ef],3}
```

The default level is 0:

```
>> Apply[f, {a, b, c}, {0}]
f[a,b,c]
```

Range of levels, including negative level (counting from bottom):

```
>> Apply[f, {{{{a}}}}, {2, -3}]
{{f[f[{a}]]}}
```

Convert all operations to lists:

```
>> Apply[List, a + b * c ^ e * f[g
], {0, Infinity}]
{a, {b, {g}}, {c,e}}
```

## ApplyLevel (@@@)

`ApplyLevel[f, expr]`  
`f @@@ expr`  
 is equivalent to `Apply[f, expr, {1}]`.

```
>> f @@@ {{a, b}, {c, d}}
{f[a,b],f[c,d]}
```

## AtomQ

`AtomQ[x]`  
 is true if `x` is an atom (an object such as a number or string, which cannot be divided into subexpressions using `Part`).

```
>> AtomQ[x]
True
```

```
>> AtomQ[1.2]
True

>> AtomQ[2 + 1]
True

>> AtomQ[2 / 3]
True

>> AtomQ[x + y]
False
```

## CombinatoricaOld'BinarySearch

`CombinatoricaOld'BinarySearch[l, k]` searches the list *l*, which has to be sorted, for key *k* and returns its index in *l*. If *k* does not exist in *l*, `BinarySearch` returns  $(a + b) / 2$ , where *a* and *b* are the indices between which *k* would have to be inserted in order to maintain the sorting order in *l*. Please note that *k* and the elements in *l* need to be comparable under a strict total order (see [https://en.wikipedia.org/wiki/Total\\_order](https://en.wikipedia.org/wiki/Total_order)).

`CombinatoricaOld'BinarySearch[l, k, f]` the index of *k* in the elements of *l* if *f* is applied to the latter prior to comparison. Note that *f* needs to yield a sorted sequence if applied to the elements of *l*.

```
>> CombinatoricaOld'BinarySearch
[{3, 4, 10, 100, 123}, 100]
4

>> CombinatoricaOld'BinarySearch
[{2, 3, 9}, 7] // N
2.5

>> CombinatoricaOld'BinarySearch
[{2, 7, 9, 10}, 3] // N
1.5

>> CombinatoricaOld'BinarySearch
[{-10, 5, 8, 10}, -100] // N
0.5

>> CombinatoricaOld'BinarySearch
[{-10, 5, 8, 10}, 20] // N
4.5
```

```
>> CombinatoricaOld'BinarySearch[{{
a, 1}, {b, 7}}, 7, #[[2]]&]
2
```

## ByteCount

`ByteCount[expr]`  
gives the internal memory space used by *expr*, in bytes.

The results may heavily depend on the Python implementation in use.

## Depth

`Depth[expr]`  
gives the depth of *expr*.

The depth of an expression is defined as one plus the maximum number of Part indices required to reach any part of *expr*, except for heads.

```
>> Depth[x]
1

>> Depth[x + y]
2

>> Depth[{{{x}}}]
5
```

Complex numbers are atomic, and hence have depth 1:

```
>> Depth[1 + 2 I]
1
```

Depth ignores heads:

```
>> Depth[f[a, b][c]]
2
```

## Flatten

`Flatten[expr]`  
flattens out nested lists in *expr*.  
`Flatten[expr, n]`  
stops flattening at level *n*.  
`Flatten[expr, n, h]`  
flattens expressions with head *h* instead of List.

```
>> Flatten[{{a, b}, {c, {d}, e}, {f, {g, h}}}]
{a, b, c, d, e, f, g, h}

>> Flatten[{{a, b}, {c, {e}, e}, {f, {g, h}}}, 1]
{a, b, c, {e}, e, f, {g, h}}

>> Flatten[f[a, f[b, f[c, d]], e], Infinity, f]
f[a, b, c, d, e]

>> Flatten[{{a, b}, {c, d}}, {{2}, {1}}]
{{a, c}, {b, d}}

>> Flatten[{{a, b}, {c, d}}, {{1, 2}}]
{a, b, c, d}
```

Flatten also works in irregularly shaped arrays

```
>> Flatten[{{1, 2, 3}, {4}, {6, 7}, {8, 9, 10}}, {{2}, {1}}]
{{1, 4, 6, 8}, {2, 7, 9}, {3, 10}}
```

## FreeQ

**FreeQ**[*expr*, *x*]  
returns True if *expr* does not contain the expression *x*.

```
>> FreeQ[y, x]
True

>> FreeQ[a+b+c, a+b]
False

>> FreeQ[{1, 2, a^(a+b)}, Plus]
False

>> FreeQ[a+b, x_+y_+z_]
True

>> FreeQ[a+b+c, x_+y_+z_]
False

>> FreeQ[x_+y_+z_] [a+b]
True
```

## Head

**Head**[*expr*]  
returns the head of the expression or atom *expr*.

```
>> Head[a * b]
Times

>> Head[6]
Integer

>> Head[x]
Symbol
```

## Map (/@)

**Map**[*f*, *expr*] or *f* /@ *expr*  
applies *f* to each part on the first level of *expr*.  
**Map**[*f*, *expr*, *levelspec*]  
applies *f* to each level specified by *levelspec* of *expr*.

```
>> f /@ {1, 2, 3}
{f[1], f[2], f[3]}

>> #^2 & /@ {1, 2, 3, 4}
{1, 4, 9, 16}
```

Map *f* on the second level:

```
>> Map[f, {{a, b}, {c, d, e}}, {2}]
{{f[a], f[b]}, {f[c], f[d], f[e]}}
```

Include heads:

```
>> Map[f, a + b + c, Heads->True]
f[Plus] [f[a], f[b], f[c]]
```

## MapAt

`MapAt[f, expr, n]`  
applies *f* to the element at position *n* in *expr*. If *n* is negative, the position is counted from the end.

`MapAt[f, expr, {i, j ...}]`  
applies *f* to the part of *expr* at position {*i*, *j*, ...}.

`MapAt[f, pos]`  
represents an operator form of `MapAt` that can be applied to an expression.

Map *f* onto the part at position 2:

```
>> MapAt[f, {a, b, c, d}, 2]
      {a, f[b], c, d}
```

Map *f* onto multiple parts:

```
>> MapAt[f, {a, b, c, d}, {{1},
      {4}}]
      {f[a], b, c, f[d]}
```

Map *f* onto the at the end:

```
>> MapAt[f, {a, b, c, d}, -1]
      {a, b, c, f[d]}
```

Map *f* onto an association:

```
>> MapAt[f, <|"a" -> 1, "b" -> 2, "
      c" -> 3, "d" -> 4, "e" -> 5|>,
      3]
      {a -> 1, b -> 2, c -> f[
      3], d -> 4, e -> 5}
```

Use negative position in an association:

```
>> MapAt[f, <|"a" -> 1, "b" -> 2, "
      c" -> 3, "d" -> 4|>, -3]
      {a -> 1, b -> f[2], c -> 3, d -> 4}
```

Use the operator form of `MapAt`:

```
>> MapAt[f, 1][{a, b, c, d}]
      {f[a], b, c, d}
```

## MapIndexed

`MapIndexed[f, expr]`  
applies *f* to each part on the first level of *expr*, including the part positions in the call to *f*.

`MapIndexed[f, expr, levelspec]`  
applies *f* to each level specified by *level-spec* of *expr*.

```
>> MapIndexed[f, {a, b, c}]
      {f[a, {1}], f[b, {2}], f[c, {3}]}
```

Include heads (index 0):

```
>> MapIndexed[f, {a, b, c}, Heads->
      True]
      f[List, {0}][f[a, {1}],
      f[b, {2}], f[c, {3}]]
```

Map on levels 0 through 1 (outer expression gets index {}):

```
>> MapIndexed[f, a + b + c * d, {0,
      1}]
      f[f[a, {1}] + f[b,
      {2}] + f[cd, {3}], {}]
```

Get the positions of atoms in an expression (convert operations to `List` first to disable `Listable` functions):

```
>> expr = a + b * f[g] * c ^ e;

>> listified = Apply[List, expr,
      {0, Infinity}];

>> MapIndexed[#2 &, listified,
      {-1}]
      {{1}, {{2, 1}, {{2, 2, 1}},
      {{2, 3, 1}, {2, 3, 2}}}}
```

Replace the heads with their positions, too:

```
>> MapIndexed[#2 &, listified,
      {-1}, Heads -> True]
      {0}[{1}, {2, 0}[{2, 1},
      {2, 2, 0}[{2, 2, 1}], {2, 3,
      0}[{2, 3, 1}, {2, 3, 2}]]]
```

The positions are given in the same format as used by `Extract`. Thus, mapping `Extract` on the indices given by `MapIndexed` re-constructs the original expression:

```
>> MapIndexed[Extract[expr, #2] &,
  listified, {-1}, Heads -> True]
 $a + bf[g]c^e$ 
```

## MapThread

`MapThread[f, {{a1, a2, ...}, {b1, b2, ...}, ...}]`  
 returns `{f[a1, b1, ...], f[a2, b2, ...], ...}`.  
`MapThread[f, {expr1, expr2, ...}, n]`  
 applies `f` at level `n`.

```
>> MapThread[f, {{a, b, c}, {1, 2, 3}}]
{f[a, 1], f[b, 2], f[c, 3]}

>> MapThread[f, {{{a, b}, {c, d}}, {{e, f}, {g, h}}}, 2]
{{f[a, e], f[b, f]}, {f[c, g], f[d, h]}}
```

## Null

`Null`  
 is the implicit result of expressions that do not yield a result.

```
>> FullForm[a:=b]
Null
```

It is not displayed in `StandardForm`,

```
>> a:=b
```

in contrast to the empty string:

```
>> ""
```

## Operate

`Operate[p, expr]`  
 applies `p` to the head of `expr`.  
`Operate[p, expr, n]`  
 applies `p` to the `n`th head of `expr`.

```
>> Operate[p, f[a, b]]
p[f][a, b]
```

The default value of `n` is 1:

```
>> Operate[p, f[a, b], 1]
p[f][a, b]
```

With `n=0`, `Operate` acts like `Apply`:

```
>> Operate[p, f[a][b][c], 0]
p[f[a][b][c]]
```

## Order

`Order[x, y]`  
 returns a number indicating the canonical ordering of `x` and `y`. 1 indicates that `x` is before `y`, -1 that `y` is before `x`. 0 indicates that there is no specific ordering. Uses the same order as `Sort`.

```
>> Order[7, 11]
1

>> Order[100, 10]
-1

>> Order[x, z]
1

>> Order[x, x]
0
```

## OrderedQ

`OrderedQ[a, b]`  
 is True if `a` sorts before `b` according to canonical ordering.

```
>> OrderedQ[a, b]
True

>> OrderedQ[b, a]
False
```

## PatternsOrderedQ

`PatternsOrderedQ[patt1, patt2]`  
 returns True if pattern `patt1` would be applied before `patt2` according to canonical pattern ordering.

```
>> PatternsOrderedQ[x_, x_]
False

>> PatternsOrderedQ[x_, x_]
True

>> PatternsOrderedQ[b, a]
True
```

```
>> Sort[{2+c_, 1+b_},
PatternsOrderedQ]
{2 + c_, 1 + b_}

>> Sort[{x_ + n_*y_, x_ + y_},
PatternsOrderedQ]
{x_ + n_y_, x_ + y_}
```

## Scan

`Scan[f, expr]`  
applies *f* to each element of *expr* and returns Null.

`'Scan[f, expr, levelspec]`  
applies *f* to each level specified by *levelspec* of *expr*.

```
>> Scan[Print, {1, 2, 3}]
1
2
3
```

## Sort

`Sort[list]`  
sorts *list* (or the leaves of any other expression) according to canonical ordering.

`Sort[list, p]`  
sorts using *p* to determine the order of two elements.

```
>> Sort[{4, 1.0, a, 3+I}]
{1., 3 + I, 4, a}
```

Sort uses OrderedQ to determine ordering by default. You can sort patterns according to their precedence using PatternsOrderedQ:

```
>> Sort[{items___, item_,
OptionsPattern[], item_symbol,
item_?test}, PatternsOrderedQ]
{item_symbol, item_?test, item_,
items___, OptionsPattern[]}
```

When sorting patterns, values of atoms do not matter:

```
>> Sort[{a, b;/t}, PatternsOrderedQ]
{b;/t, a}
```

## SortBy

`SortBy[list, f]`  
sorts *list* (or the leaves of any other expression) according to canonical ordering of the keys that are extracted from the *list*'s elements using *f*. Chunks of leaves that appear the same under *f* are sorted according to their natural order (without applying *f*).

`SortBy[f]`  
creates an operator function that, when applied, sorts by *f*.

```
>> SortBy[{{5, 1}, {10, -1}}, Last]
{{10, -1}, {5, 1}}

>> SortBy[Total][{{5, 1}, {10, -9}}]
{{10, -9}, {5, 1}}
```

## SymbolName

`SymbolName[s]`  
returns the name of the symbol *s* (without any leading context name).

```
>> SymbolName[x] // InputForm
"x"
```

## SymbolQ

`SymbolQ[x]`  
is True if *x* is a symbol, or False otherwise.

```
>> SymbolQ[a]
True
```

```
>> SymbolQ[1]
False

>> SymbolQ[a + b]
False
```

```
>> Through[f[g][x]]
f[g[x]]

>> Through[p[f, g][x]]
p[f[x], g[x]]
```

## Symbol

`Symbol`  
is the head of symbols.

```
>> Head[x]
Symbol
```

You can use `Symbol` to create symbols from strings:

```
>> Symbol["x"] + Symbol["x"]
2x
```

## Thread

`Thread[f[args]]`  
threads  $f$  over any lists that appear in  $args$ .  
`Thread[f[args], h]`  
threads over any parts with head  $h$ .

```
>> Thread[f[{a, b, c}]]
{f[a], f[b], f[c]}

>> Thread[f[{a, b, c}, t]]
{f[a, t], f[b, t], f[c, t]}

>> Thread[f[a + b + c], Plus]
f[a] + f[b] + f[c]
```

Functions with attribute `Listable` are automatically threaded over lists:

```
>> {a, b, c} + {d, e, f} + g
{a + d + g, b + e + g, c + f + g}
```

## Through

`Through[p[f][x]]`  
gives  $p[f[x]]$ .



## XXVI. Exponential, Trigonometric and Hyperbolic Functions

*Mathics* basically supports all important trigonometric and hyperbolic functions.

Numerical values and derivatives can be computed; however, most special exact values and simplification rules are not implemented yet.

### Contents

AnglePath . . . . .	146	ArcSinh . . . . .	148	InverseHaversine . . .	149
AngleVector . . . . .	146	ArcTan . . . . .	148	Log . . . . .	149
ArcCos . . . . .	146	ArcTanh . . . . .	148	Log10 . . . . .	150
ArcCosh . . . . .	147	Cos . . . . .	148	Log2 . . . . .	150
ArcCot . . . . .	147	Cosh . . . . .	148	LogisticSigmoid . . .	150
ArcCoth . . . . .	147	Cot . . . . .	148	Sec . . . . .	150
ArcCsc . . . . .	147	Coth . . . . .	148	Sech . . . . .	150
ArcCsch . . . . .	147	Csc . . . . .	149	Sin . . . . .	151
ArcSec . . . . .	147	Csch . . . . .	149	Sinh . . . . .	151
ArcSech . . . . .	147	Exp . . . . .	149	Tan . . . . .	151
ArcSin . . . . .	148	Haversine . . . . .	149	Tanh . . . . .	151

### AnglePath

`AnglePath[{phi1, phi2, ...}]`  
 returns the points formed by a turtle starting at {0, 0} and angled at 0 degrees going through the turns given by angles *phi1*, *phi2*, ... and using distance 1 for each step.

`AnglePath[{r1, phi1}, {r2, phi2}, ...]`  
 instead of using 1 as distance, use *r1*, *r2*, ... as distances for the respective steps.

`AngleVector[phi0, {phi1, phi2, ...}]`  
 returns the points on a path formed by a turtle starting with direction *phi0* instead of 0.

`AngleVector[{x, y}, {phi1, phi2, ...}]`  
 returns the points on a path formed by a turtle starting at {*x*, *y*} instead of {0, 0}.

`AngleVector[{x, y}, phi0, {phi1, phi2, ...}]`  
 specifies initial position {*x*, *y*} and initial direction *phi0*.

`AngleVector[{x, y}, {dx, dy}, {phi1, phi2, ...}]`  
 specifies initial position {*x*, *y*} and a slope {*dx*, *dy*} that is understood to be the initial direction of the turtle.


```
>> AnglePath[{90 Degree, 90 Degree,
  90 Degree, 90 Degree}]
{{0,0}, {0,1}, {-1,
  1}, {-1,0}, {0,0}}

>> AnglePath[{{1, 1}, 90 Degree},
  {{1, 90 Degree}, {2, 90 Degree},
  {1, 90 Degree}, {2, 90 Degree
  }}]
{{1,1}, {0,1}, {0,
  -1}, {1, -1}, {1,1}}


>> AnglePath[{a, b}]
{{0,0}, {Cos[a], Sin[a]}, {Cos[
  a]+Cos[a+b], Sin[a]+Sin[a+b]}}

>> Precision[Part[AnglePath[{N[1/3,
  100], N[2/3, 100]}], 2, 1]]
100.

>> Graphics[Line[AnglePath[Table
  [1.7, {50}]]]]
```



```
>> Graphics[Line[AnglePath[
  RandomReal[{-1, 1}, {100}]]]]
```



## AngleVector

`AngleVector[phi]`  
returns the point at angle  $\phi$  on the unit circle.

`AngleVector[{r, phi}]`  
returns the point at angle  $\phi$  on a circle of radius  $r$ .

`AngleVector[{x, y}, phi]`  
returns the point at angle  $\phi$  on a circle of radius 1 centered at  $\{x, y\}$ .

`AngleVector[{x, y}, {r, phi}]`  
returns point at angle  $\phi$  on a circle of radius  $r$  centered at  $\{x, y\}$ .

```
>> AngleVector[90 Degree]
{0, 1}

>> AngleVector[{1, 10}, a]
{1 + Cos[a], 10 + Sin[a]}
```

## ArcCos

`ArcCos[z]`  
returns the inverse cosine of  $z$ .

```
>> ArcCos[1]
0

>> ArcCos[0]
Pi/2

>> Integrate[ArcCos[x], {x, -1, 1}]
Pi
```

## ArcCosh

`ArcCosh[z]`  
returns the inverse hyperbolic cosine of  $z$ .

```
>> ArcCosh[0]
I/2 Pi

>> ArcCosh[0.]
0. + 1.5708 I
```

## ArcCot

```
>> ArcCot[0]
      Pi
      2

>> ArcCot[1]
      Pi
      4
```

## ArcCoth

```
>> ArcCoth[0]
       $\frac{I}{2}\text{Pi}$ 
>> ArcCoth[1]
       $\infty$ 
>> ArcCoth[0.0]
       $0. + 1.5708I$ 
>> ArcCoth[0.5]
       $0.549306 - 1.5708I$ 
```

## ArcCsc

```
>> ArcCsc[1]
      Pi
      --
      2
```

## ArcCsch

```
>> ArcCsch[0]
ComplexInfinity
>> ArcCsch[1.0]
0.881374
```

## ArcSec

```
>> ArcSec[1]
0
>> ArcSec[-1]
Pi
```

## ArcSech

```
>> ArcSech[0]
      ∞
>> ArcSech[1]
      0
>> ArcSech[0.5]
      1.31696
```

## ArcSin

```
>> ArcSin[0]
0
```

```
>> ArcSin[1]
      Pi
      2
```

## ArcSinh

`ArcSinh[z]`  
returns the inverse hyperbolic sine of z.

```
>> ArcSinh[0]
0

>> ArcSinh[0.]
0.

>> ArcSinh[1.0]
0.881374
```

## ArcTan

`ArcTan[z]`  
returns the inverse tangent of z.

```
>> ArcTan[1]
      Pi
      4

>> ArcTan[1.0]
0.785398

>> ArcTan[-1.0]
-0.785398

>> ArcTan[1, 1]
      Pi
      4
```

## ArcTanh

`ArcTanh[z]`  
returns the inverse hyperbolic tangent of z.

```
>> ArcTanh[0]
0

>> ArcTanh[1]
∞

>> ArcTanh[0]
0
```

```
>> ArcTanh[.5 + 2 I]
0.0964156 + 1.12656 I

>> ArcTanh[2 + I]
ArcTanh[2 + I]
```

## Cos

`Cos[z]`  
returns the cosine of z.

```
>> Cos[3 Pi]
-1
```

## Cosh

`Cosh[z]`  
returns the hyperbolic cosine of z.

```
>> Cosh[0]
1
```

## Cot

`Cot[z]`  
returns the cotangent of z.

```
>> Cot[0]
ComplexInfinity

>> Cot[1.]
0.642093
```

## Coth

`Coth[z]`  
returns the hyperbolic cotangent of z.

```
>> Coth[0]
ComplexInfinity
```

## Csc

**Csc[z]**  
returns the cosecant of z.

```
>> Csc[0]
ComplexInfinity

>> Csc[1] (* Csc[1] in Mathematica *)

$$\frac{1}{\sin[1]}$$


>> Csc[1.]
1.1884
```

## Csch

**Csch[z]**  
returns the hyperbolic cosecant of z.

```
>> Csch[0]
ComplexInfinity
```

## Exp


**Exp[z]**  
returns the exponential function of z.

```
>> Exp[1]
E

>> Exp[10.0]
22026.5

>> Exp[x] //FullForm
Power[E, x]

>> Plot[Exp[x], {x, 0, 3}]
```



## Haversine

**Haversine[z]**  
returns the haversine function of z.

```
>> Haversine[1.5]
0.464631

>> Haversine[0.5 + 2I]
-1.15082 + 0.869405I
```

## InverseHaversine

**InverseHaversine[z]**  
returns the inverse haversine function of z.

```
>> InverseHaversine[0.5]
1.5708

>> InverseHaversine[1 + 2.5 I]
1.76459 + 2.33097I
```


## Log

**Log[z]**  
returns the natural logarithm of z.

```
>> Log[{0, 1, E, E * E, E ^ 3, E ^ x}]
{-∞, 0, 1, 2, 3, Log[E^x]}

>> Log[0.]
Indeterminate

>> Plot[Log[x], {x, 0, 5}]
```



## Log10

`Log10[z]`  
returns the base-10 logarithm of  $z$ .

```
>> Log10[1000]
3
>> Log10[{2., 5.}]
{0.30103, 0.69897}
>> Log10[E ^ 3]
 $\frac{3}{\text{Log}[10]}$ 
```

## Log2

`Log2[z]`  
returns the base-2 logarithm of  $z$ .

```
>> Log2[4 ^ 8]
16
>> Log2[5.6]
2.48543
>> Log2[E ^ 2]
 $\frac{2}{\text{Log}[2]}$ 
```

## LogisticSigmoid

`LogisticSigmoid[z]`  
returns the logistic sigmoid of  $z$ .

```
>> LogisticSigmoid[0.5]
0.622459
>> LogisticSigmoid[0.5 + 2.3 I]
1.06475 + 0.808177I
>> LogisticSigmoid[{-0.2, 0.1, 0.3}]
{0.450166, 0.524979, 0.574443}
```

## Sec

`Sec[z]`  
returns the secant of  $z$ .

```
>> Sec[0]
1
>> Sec[1] (* Sec[1] in Mathematica *)
 $\frac{1}{\text{Cos}[1]}$ 
>> Sec[1.]
1.85082
```

## Sech

`Sech[z]`  
returns the hyperbolic secant of  $z$ .


```
>> Sech[0]
1
```

## Sin

`Sin[z]`  
returns the sine of  $z$ .

```
>> Sin[0]
0
>> Sin[0.5]
0.479426
>> Sin[3 Pi]
0
>> Sin[1.0 + I]
1.29846 + 0.634964I
```

```
>> Plot[Sin[x], {x, -Pi, Pi}]
```



## Sinh

`Sinh[z]`  
returns the hyperbolic sine of z.

```
>> Sinh[0]  
0
```

## Tan

`Tan[z]`  
returns the tangent of z.

```
>> Tan[0]  
0  
  
>> Tan[Pi / 2]  
ComplexInfinity
```

## Tanh

`Tanh[z]`  
returns the hyperbolic tangent of z.

```
>> Tanh[0]  
0
```

# XXVII. Drawing Graphics


## Contents

AbsoluteThickness . . .	152	FilledCurve . . . . .	159	Point . . . . .	165
Arrow . . . . .	153	FilledCurveBox . . . .	159	PointBox . . . . .	165
ArrowBox . . . . .	154	FontColor . . . . .	159	PointSize . . . . .	165
Arrowheads . . . . .	154	Graphics . . . . .	160	Polygon . . . . .	165
Automatic . . . . .	155	GraphicsBox . . . . .	160	PolygonBox . . . . .	165
BernsteinBasis . . . .	155	Gray . . . . .	161	Purple . . . . .	166
BezierCurve . . . . .	155	GrayLevel . . . . .	161	RGBColor . . . . .	166
BezierCurveBox . . . .	155	Green . . . . .	161	Rectangle . . . . .	167
BezierFunction . . . .	155	Hue . . . . .	161	RectangleBox . . . . .	167
Black . . . . .	155	Inset . . . . .	162	Red . . . . .	167
Blend . . . . .	156	InsetBox . . . . .	162	RegularPolygon . . . .	167
Blue . . . . .	156	LABColor . . . . .	162	RegularPolygonBox . .	168
CMYKColor . . . . .	156	LCHColor . . . . .	162	Show . . . . .	168
Circle . . . . .	157	LUVColor . . . . .	162	Small . . . . .	168
CircleBox . . . . .	157	Large . . . . .	162	Text . . . . .	168
ColorDistance . . . . .	157	LightRed . . . . .	162	Thick . . . . .	168
Cyan . . . . .	157	Lighter . . . . .	163	Thickness . . . . .	168
Darker . . . . .	157	Line . . . . .	163	Thin . . . . .	168
Directive . . . . .	158	LineBox . . . . .	163	Tiny . . . . .	168
Disk . . . . .	158	Magenta . . . . .	164	White . . . . .	169
DiskBox . . . . .	159	Medium . . . . .	164	XYZColor . . . . .	169
EdgeForm . . . . .	159	Offset . . . . .	164	Yellow . . . . .	169
FaceForm . . . . .	159	Orange . . . . .	164		

## AbsoluteThickness

`AbsoluteThickness[p]`  
sets the line thickness for subsequent graphics primitives to *p* points.

```
>> Graphics[Table[{
  AbsoluteThickness[t], Line[{{20
t, 10}, {20 t, 80}}], Text[
ToString[t]<"pt", {20 t, 0}],
{t, 0, 10}]]
```






## Arrow

`Arrow[{p1, p2}]`  
 represents a line from  $p1$  to  $p2$  that ends with an arrow at  $p2$ .


`Arrow[{p1, p2}, s]`  
 represents a line with arrow that keeps a distance of  $s$  from  $p1$  and  $p2$ .

`Arrow[{point_1, point_2}, {s1, s2}]`  
 represents a line with arrow that keeps a distance of  $s1$  from  $p1$  and a distance of  $s2$  from  $p2$ .

```
>> Graphics[Arrow[{0,0}, {1,1}]]
```




```
>> Graphics[{Circle[], Arrow[{2,1}, {0,0}, 1]}]
```



Keeping distances may happen across multiple segments:

```
>> Table[Graphics[{Circle[], Arrow[
Table[{Cos[phi], Sin[phi]], {phi
,0,2*Pi,Pi/2}], {d, d}]]], {d
,0,2,0.5}]
```



## ArrowBox

### Arrowheads

`Arrowheads[s]`  
specifies that `Arrow[]` draws one arrow of size  $s$  (relative to width of image, defaults to 0.04).

`Arrowheads[{spec1, spec2, ..., specn}]`  
specifies that `Arrow[]` draws  $n$  arrows as defined by  $spec1, spec2, \dots, specn$ .


`Arrowheads[{s}]`  
specifies that one arrow of size  $s$  should be drawn.

`Arrowheads[{s, pos}]`  
specifies that one arrow of size  $s$  should be drawn at position  $pos$  (for the arrow to be on the line,  $pos$  has to be between 0, i.e. the start for the line, and 1, i.e. the end of the line).

`Arrowheads[{s, pos, g}]`  
specifies that one arrow of size  $s$  should be drawn at position  $pos$  using Graphics  $g$ .


Arrows on both ends can be achieved using negative sizes:

```
>> Graphics[{Circle[], Arrowheads
[{-0.04, 0.04}], Arrow[{0, 0},
{2, 2}], {1, 1}}]
```




You may also specify our own arrow shapes:

```
>> Graphics[{Circle[], Arrowheads
[{{0.04, 1, Graphics[{Red, Disk
[]}]}}], Arrow[{0, 0}, {Cos[Pi
/3], Sin[Pi/3]}]}]
```



```
>> Graphics[{Arrowheads[Table
[{0.04, i/10, Graphics[Disk
[]]], {i, 1, 10}]], Arrow[{0, 0},
{6, 5}, {1, -3}, {-2, 2}]}]
```



## Automatic

`Automatic`  
is used to specify an automatically computed option value.

`Automatic` is the default for `PlotRange`, `ImageSize`, and other graphical options:


```
>> Cases[Options[Plot], HoldPattern
[_ :> Automatic]]
{Background:>Automatic,
 Exclusions:>Automatic,
 ImageSize:>Automatic,
 MaxRecursion:>Automatic,
 PlotRange:>Automatic,
 PlotRangePadding:>Automatic}
```

## BernsteinBasis


## BezierCurve

`BezierCurve[{p1, p2 ...}]`  
represents a bezier curve with  $p1$ ,  $p2$  as control points.

```
>> Graphics[BezierCurve[{{0, 0},{1,
1},{2, -1},{3, 0}}]]
```



```
>> Module[{p={{0, 0},{1, 1},{2,
-1},{4, 0}}}, Graphics[{
BezierCurve[p], Red, Point[Table
[BezierFunction[p][x], {x, 0, 1,
0.1}]]]}]]
```




## BezierCurveBox

## BezierFunction

## Black

`Black`  
represents the color black in graphics.

```
>> Graphics[{EdgeForm[Black], Black
, Disk[]}, ImageSize->Small]
```



```
>> Black // ToBoxes
StyleBox [GraphicsBox [{EdgeForm [■], ■, RectangleBox [
-> Ignore, AspectRatio
-> Automatic, Axes
-> False, AxesStyle
-> {}, Background
-> Automatic, ImageSize
-> 16, LabelStyle-> {}, PlotRange
-> Automatic, PlotRangePadding
-> Automatic, TicksStyle
-> {}], ImageSizeMultipliers
-> {1, 1}]]
```

```
>> Black
```



## Blend

`Blend[{c1, c2}]`  
represents the color between  $c1$  and  $c2$ .  
`Blend[{c1, c2}, x]`  
represents the color formed by blending  $c1$  and  $c2$  with factors  $1 - x$  and  $x$  respectively.  
`Blend[{c1, c2, ..., cn}, x]`  
blends between the colors  $c1$  to  $cn$  according to the factor  $x$ .

```
>> Blend[{Red, Blue}]
```



```
>> Blend[{Red, Blue}, 0.3]
```



```
>> Blend[{Red, Blue, Green}, 0.75]
```



```
>> Graphics[Table[{Blend[{Red,
Green, Blue}, x], Rectangle[{10
x, 0}], {x, 0, 1, 1/10}]]
```




```
>> Graphics[Table[{Blend[{RGBColor
[1, 0.5, 0, 0.5], RGBColor[0, 0,
1, 0.5]}], x], Disk[{5x, 0}], {
x, 0, 1, 1/10}]]
```

## Blue

**Blue**  
represents the color blue in graphics.

```
>> Graphics[{EdgeForm[Black], Blue,
Disk[]}, ImageSize->Small]
```



```
>> Blue // ToBoxes
StyleBox [GraphicsBox [{EdgeForm [■], ■, RectangleBox [{0,0}]}], $OptionSyntax
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}, ImageSizeMultipliers
- > {1,1}]
```

```
>> Blue
■
```

## CMYKColor

**CMYKColor**[*c, m, y, k*]  
represents a color with the specified cyan, magenta, yellow and black components.


```
>> Graphics[MapIndexed[{CMYKColor
@@ #1, Disk[2*#2 ~Join~{0}]} &,
IdentityMatrix[4]], ImageSize->
Small]
```




## Circle

**Circle**[{*cx, cy*}, *r*]  
draws a circle with center (*cx, cy*) and radius *r*.  
**Circle**[{*cx, cy*}, {*rx, ry*}]  
draws an ellipse.  
**Circle**[{*cx, cy*}]  
chooses radius 1.  
**Circle**[]  
chooses center (0, 0) and radius 1.

```
>> Graphics[{Red, Circle[{0, 0},
{2, 1}]]]
```



```
>> Graphics[{Circle[], Disk[{0, 0},
{1, 1}, {0, 2.1}]}]
```



## CircleBox

## ColorDistance

`ColorDistance[c1, c2]`  
returns a measure of color distance between the colors *c1* and *c2*.

`ColorDistance[list, c2]`  
returns a list of color distances between the colors in *list* and *c2*.

The option `DistanceFunction` specifies the method used to measure the color distance. Available options are:

CIE76: euclidean distance in the LABColor space  
CIE94: euclidean distance in the LCH-Color space  
CIE2000 or CIEDE2000: CIE94 distance with corrections  
CMC: Colour Measurement Committee metric (1984)  
DeltaL: difference in the L component of LCHColor  
DeltaC: difference in the C component of LCHColor  
DeltaH: difference in the H component of LCHColor

It is also possible to specify a custom distance


```
>> ColorDistance[Magenta, Green]
2.2507

>> ColorDistance[{Red, Blue}, {
Green, Yellow}, DistanceFunction
-> {"CMC", "Perceptibility"}]
{1.0495, 1.27455}
```

## Cyan

**Cyan**  
represents the color cyan in graphics.

```
>> Graphics[{EdgeForm[Black], Cyan,
Disk[]}, ImageSize->Small]
```



```
>> Cyan // ToBoxes
```

```
StyleBox[GraphicsBox[{EdgeForm[Black], Cyan, RectangleBox[
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle-> {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}], ImageSizeMultipliers
- > {1, 1}]
```

```
>> Cyan
```



## Darker

`Darker[c, f]`  
is equivalent to `Blend[{c, Black}, f]`.

`Darker[c]`  
is equivalent to `Darker[c, 1/3]`.

```
>> Graphics[Table[{Darker[Yellow, x
], Disk[{12x, 0}]}], {x, 0, 1,
1/6}]]
```




## Directive

### Disk


```
Disk[{cx, cy}, r]  
    fills a circle with center (cx, cy) and radius r.  
Disk[{cx, cy}, {rx, ry}]  
    fills an ellipse.  
Disk[{cx, cy}]  
    chooses radius 1.  
Disk[]  
    chooses center (0, 0) and radius 1.  
Disk[{x, y}, ..., {t1, t2}]  
    is a sector from angle t1 to t2.
```

```
>> Graphics[{Blue, Disk[{0, 0}, {2, 1}]}]
```




The outer border can be drawn using EdgeForm:

```
>> Graphics[{EdgeForm[Black], Red, Disk[]}]
```




Disk can also draw sectors of circles and ellipses

```
>> Graphics[Disk[{0, 0}, 1, {Pi / 3, 2 Pi / 3}]]
```




```
>> Graphics[{Blue, Disk[{0, 0}, {1, 2}, {Pi / 3, 5 Pi / 3}]]]
```




## DiskBox

## EdgeForm

```
>> Graphics[{EdgeForm[{Thick, Green}], Disk[]}]
```



```
>> Graphics[{Style[Disk[], EdgeForm[{Thick, Red}]], Circle[{1, 1}]}]
```




## FaceForm

## FilledCurve

```
FilledCurve[{segment1, segment2 ...}]
```

represents a filled curve.

```
>> Graphics[FilledCurve[{Line[{0, 0}, {1, 1}, {2, 0}]}]]
```



```
>> Graphics[FilledCurve[{BezierCurve[{0, 0}, {1, 1}, {2, 0}], Line[{3, 0}, {0, 2}]}]]
```



## FilledCurveBox

## FontColor

FontColor  
is an option for Style to set the font color.

## Graphics

Graphics[primitives, options]  
represents a graphic.


Options include:

- Axes
- TicksStyle
- AxesStyle
- LabelStyle
- AspectRatio
- PlotRange
- PlotRangePadding
- ImageSize
- Background

```

•
>> Graphics[{Blue, Line[{{0,0},
{1,1}}]}]}

```




Graphics supports PlotRange:

```

>> Graphics[{Rectangle[{1, 1}]},
  Axes -> True, PlotRange -> {{-2,
  1.5}, {-1, 1.5}}]

```



```

>> Graphics[{Rectangle[], Red, Disk
[{1,0}], PlotRange
->{{0,1},{0,1}}]

```



Graphics produces GraphicsBox boxes:

```

>> Graphics[Rectangle[]] // ToBoxes
// Head
GraphicsBox

```

In TeXForm, Graphics produces Asymptote figures:

```

>> Graphics[Circle[]] // TeXForm

\begin{asy}
  usepackage("amsmath");
  size(5.8556cm, 5.8333cm);
  draw(ellipse((175,175),175,175),
  rgb(0, 0, 0)+linewidth(0.66667));
  clip(box((-0.33333,0.33333),
  (350.33,349.67)));
\end{asy}

```

## GraphicsBox

### Gray


Gray

represents the color gray in graphics.

```

>> Graphics[{EdgeForm[Black], Gray,
  Disk[]}, ImageSize->Small]

```



```

>> Gray // ToBoxes

```

```

StyleBox [GraphicsBox [{EdgeForm [■], ■, RectangleBox [
  - > Ignore, AspectRatio
  - > Automatic, Axes
  - > False, AxesStyle
  - > {}, Background
  - > Automatic, ImageSize
  - > 16, LabelStyle - > {}, PlotRange
  - > Automatic, PlotRangePadding
  - > Automatic, TicksStyle
  - > {}], ImageSizeMultipliers
  - > {1,1}]

```



```
>> Gray
```



## GrayLevel

```
GrayLevel[g]
```

represents a shade of gray specified by  $g$ , ranging from 0 (black) to 1 (white).

```
GrayLevel[g, a]
```


represents a shade of gray specified by  $g$  with opacity  $a$ .

## Green

```
Green
```

represents the color green in graphics.

```
>> Graphics[{EdgeForm[Black], Green, Disk[]}, ImageSize->Small]
```



```
>> Green // ToBoxes
```

```
StyleBox[GraphicsBox[{EdgeForm[Black], Green, RectangleBox[{0,0}]}], $OptionSyntax
```

```
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}, ImageSizeMultipliers
- > {1,1}]
```

```
>> Green
```



## Hue

```
Hue[h, s, l, a]
```

represents the color with hue  $h$ , saturation  $s$ , lightness  $l$  and opacity  $a$ .

```
Hue[h, s, l]
```

is equivalent to `Hue[h, s, l, 1]`.


```
Hue[h, s]
```

is equivalent to `Hue[h, s, 1, 1]`.

```
Hue[h]
```

is equivalent to `Hue[h, 1, 1, 1]`.

```
>> Graphics[Table[{EdgeForm[Gray], Hue[h, s], Disk[{12h, 8s]}], {h, 0, 1, 1/6}, {s, 0, 1, 1/4}]]
```



```
>> Graphics[Table[{EdgeForm[GrayLevel[0, 0.5]], Hue[(-11+q+10r)/72, 1, 1, 0.6], Disk[(8-r){Cos[2Pi q/12], Sin[2Pi q/12]}], (8-r)/3}], {r, 6}, {q, 12}]]
```

## Inset

## InsetBox

## LABColor

`LABColor[l, a, b]`

represents a color with the specified lightness, red/green and yellow/blue components in the CIE 1976 L\*a\*b\* (CIELAB) color space.

## LCHColor

`LCHColor[l, c, h]`

represents a color with the specified lightness, chroma and hue components in the CIE LCh CIE Lab cube color space.

## LUVColor

`LCHColor[l, u, v]`

represents a color with the specified components in the CIE 1976 L\*u\*v\* (CIELUV) color space.

## Large

`ImageSize -> Large`


produces a large image.

## LightRed

`LightRed`

represents the color light red in graphics.

```
>> Graphics[{EdgeForm[Black],  
LightRed, Disk[]}, ImageSize->  
Small]
```



```
>> LightRed // ToBoxes
```

```
StyleBox [GraphicsBox [{EdgeForm [Black], LightRed, RectangleBox [0, 0, 1, 1]},  
- > Ignore, AspectRatio  
- > Automatic, Axes  
- > False, AxesStyle  
- > {}, Background  
- > Automatic, ImageSize  
- > 16, LabelStyle - > {}, PlotRange  
- > Automatic, PlotRangePadding  
- > Automatic, TicksStyle  
- > {}], ImageSizeMultipliers  
- > {1, 1}]
```

## Lighter

`Lighter[c, f]`

is equivalent to `Blend[{c, White}, f]`.


`Lighter[c]`

is equivalent to `Lighter[c, 1/3]`.

```
>> Lighter[Orange, 1/4]
```



```
>> Graphics[{Lighter[Orange, 1/4],
Disk[]}]
```




```
>> Graphics[Table[{Lighter[Orange,
x], Disk[{12x, 0}]}], {x, 0, 1,
1/6}]]
```




## Line

`Line[{point_1, point_2 ...}]`  
represents the line primitive.  
`Line[{p_11, p_12, ...}, {p_21, p_22,  
...}, ...]`  
represents a number of line primitives.

```
>> Graphics[Line
[{{0,1},{0,0},{1,0},{1,1}}]]
```



```
>> Graphics3D[Line
[{{0,0,0},{0,1,1},{1,0,0}}]]
```




## LineBox

## Magenta

`Magenta`  
represents the color magenta in graphics.

```
>> Graphics[{EdgeForm[Black],
Magenta, Disk[]}, ImageSize->
Small]
```



```
>> Magenta // ToBoxes
```

```
StyleBox [GraphicsBox [{EdgeForm [Black], RectangleBox[{0,0}, {1,1}],
  - > Ignore, AspectRatio
  - > Automatic, Axes
  - > False, AxesStyle
  - > {}, Background
  - > Automatic, ImageSize
  - > 16, LabelStyle- > {}, PlotRange
  - > Automatic, PlotRangePadding
  - > Automatic, TicksStyle
  - > {}], ImageSizeMultipliers
  - > {1,1}]
```

```
>> Magenta
```



## Medium


ImageSize -> Medium  
produces a medium-sized image.

## Offset

## Orange

Orange  
represents the color orange in graphics.

```
>> Graphics[{EdgeForm[Black],
  Orange, Disk[]}, ImageSize->
  Small]
```



```
>> Orange // ToBoxes
```

```
StyleBox [GraphicsBox [{EdgeForm [Black], RectangleBox[{0,0}, {1,1}],
  - > Ignore, AspectRatio
  - > Automatic, Axes
  - > False, AxesStyle
  - > {}, Background
  - > Automatic, ImageSize
  - > 16, LabelStyle- > {}, PlotRange
  - > Automatic, PlotRangePadding
  - > Automatic, TicksStyle
  - > {}], ImageSizeMultipliers
  - > {1,1}]
```


## Point

Point[{*point\_1*, *point\_2* ...}]  
represents the point primitive.  
Point[{{*p\_11*, *p\_12*, ...}, {*p\_21*, *p\_22*,  
...}, ...}]  
represents a number of point primitives.


```
>> Graphics[Point[{0,0}]]
```

```
.
```

```
>> Graphics[Point[Table[{Sin[t],
  Cos[t]}, {t, 0, 2. Pi, Pi /
  15.}]]]
```



```
>> Graphics3D[Point[Table[{Sin[t],  
Cos[t], 0}, {t, 0, 2. Pi, Pi /  
15.}]]]
```



## PointSize


## PointSize

`PointSize[t]`  
sets the diameter of points to  $t$ , which is relative to the overall width.


## Polygon

`Polygon[{point_1, point_2 ...}]`  
represents the filled polygon primitive.  
`Polygon[{{p_11, p_12, ...}, {p_21, p_22, ...}, ...}]`  
represents a number of filled polygon primitives.

```
>> Graphics[Polygon  
[{{1,0},{0,0},{0,1}}]]
```



```
>> Graphics3D[Polygon  
[{{0,0,0},{0,1,1},{1,0,0}}]]
```




## PolygonBox

## Purple

`Purple`  
represents the color purple in graphics.

```
>> Graphics[{EdgeForm[Black],
Purple, Disk[]}, ImageSize->
Small]
```




```
>> Purple // ToBoxes
StyleBox [GraphicsBox [{EdgeForm [■], ■, RectangleBox [
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}], ImageSizeMultipliers
- > {1, 1}]]
```

## RGBColor

`RGBColor[r, g, b]`  
represents a color with the specified red, green and blue components.

```
>> Graphics[MapIndexed[{RGBColor @@
#1, Disk[2*#2 ~Join~{0}]} &,
IdentityMatrix[3]], ImageSize->
Small]
```



```
>> RGBColor[0, 1, 0]
■
```

```
>> RGBColor[0, 1, 0] // ToBoxes
```


```
StyleBox [GraphicsBox [{EdgeForm [■], ■, RectangleBox [
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}], ImageSizeMultipliers
- > {1, 1}]]
```

## Rectangle


`Rectangle[{xmin, ymin}]`  
represents a unit square with bottom-left corner at {xmin, ymin}.

`Rectangle[{xmin, ymin}, {xmax, ymax}]`  
is a rectangle extending from {xmin, ymin} to {xmax, ymax}.

```
>> Graphics[Rectangle[]]
```



```
>> Graphics[{Blue, Rectangle[{0.5, 0}], Orange, Rectangle[{0, 0.5}]}]
```



```
>> Red
```



## RegularPolygon


`RegularPolygon[n]`  
gives the regular polygon with  $n$  edges.

`RegularPolygon[r, n]`  
gives the regular polygon with  $n$  edges and radius  $r$ .

`RegularPolygon[{r, phi}, n]`  
gives the regular polygon with radius  $r$  with one vertex drawn at angle  $phi$ .

`RegularPolygon[{x, y}, r, n]`  
gives the regular polygon centered at the position  $\{x, y\}$ .

```
>> Graphics[RegularPolygon[5]]
```




## RectangleBox


### Red

`Red`  
represents the color red in graphics.

```
>> Graphics[{EdgeForm[Black], Red, Disk[]}, ImageSize->Small]
```



```
>> Graphics[{Yellow, Rectangle[], Orange, RegularPolygon[{1, 1}, {0.25, 0}, 3]}]
```



```
>> Red // ToBoxes
```

```
StyleBox[GraphicsBox[{EdgeForm[Black], Red, RectangleBox[{0, 0}]}], $OptionSyntax]
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle
- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}, ImageSizeMultipliers
- > {1, 1}]
```

## RegularPolygonBox

### Show

```
Show[graphics, options]
```

shows graphics with the specified options added.

### Small

```
ImageSize -> Small
```


produces a small image.

### Text

```
Text["text", {x, y}]
```

draws *text* centered on position {*x*, *y*}.

```
>> Graphics[{Text["First", {0, 0}],  
Text["Second", {1, 1}], Axes->  
True, PlotRange->{{-2, 2}, {-2,  
2}}]
```



### Thick

```
Thick
```


sets the line width for subsequent graphics primitives to 2pt.

## Thickness

```
Thickness[t]
```

sets the line thickness for subsequent graphics primitives to *t* times the size of the plot area.

```
>> Graphics[{Thickness[0.2], Line  
[{{0, 0}, {0, 5}}]}, Axes->True,  
PlotRange->{{-5, 5}, {-5, 5}}]
```



### Thin

```
Thin
```

sets the line width for subsequent graphics primitives to 0.5pt.

### Tiny

```
ImageSize -> Tiny
```

produces a tiny image.


## White

```
White
```


represents the color white in graphics.



```
>> Graphics[{EdgeForm[Black], White
, Disk[]}, ImageSize->Small]
```



```
>> Graphics[{EdgeForm[Black],
Yellow, Disk[]}, ImageSize->
Small]
```



```
>> White // ToBoxes
```

```
StyleBox [GraphicsBox [{EdgeForm [■], □, RectangleBox [{0, 0}],
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}], ImageSizeMultipliers
- > {1, 1}]
```

```
>> White
```



```
>> Yellow // ToBoxes
```

```
StyleBox [GraphicsBox [{EdgeForm [■], ■, RectangleBox [{0, 0}],
- > Ignore, AspectRatio
- > Automatic, Axes
- > False, AxesStyle
- > {}, Background
- > Automatic, ImageSize
- > 16, LabelStyle- > {}, PlotRange
- > Automatic, PlotRangePadding
- > Automatic, TicksStyle
- > {}], ImageSizeMultipliers
- > {1, 1}]
```

```
>> Yellow
```



## XYZColor

```
XYZColor[x, y, z]
```

represents a color with the specified components in the CIE 1931 XYZ color space.

## Yellow

```
Yellow
```

represents the color yellow in graphics.

# XXVIII. Manipulate

## Contents

---

Manipulate . . . . .	170	Sys-	
		tem'Private'ManipulateParameter	170

---

## Manipulate

`Manipulate[expr1, {u, u_min, u_max}]`  
interactively compute and display an expression with different values of  $u$ .

`Manipulate[expr1, {u, u_min, u_max, du}]`  
allows  $u$  to vary between  $u_{min}$  and  $u_{max}$  in steps of  $du$ .

`Manipulate[expr1, {{u, u_init}, u_min, u_max, ...}]`  
starts with initial value of  $u_{init}$ .

`Manipulate[expr1, {{u, u_init, u_lbl}, ...}]`  
labels the  $u$  controll by  $u_{lbl}$ .

`Manipulate[expr1, {u, {u_1, u_2, ...}}]`  
sets  $u$  to take discrete values  $u_1, u_2, \dots$ .

`Manipulate[expr1, {u, ...}, {v, ...}, ...]`  
control each of  $u, v, \dots$ .

```
>> Manipulate[N[Sin[y]], {y, 1, 20, 2}]
Manipulate[N[Sin[y]], {y, 1, 20, 2}]

>> Manipulate[i^3, {i, {2, x^4, a}}]
Manipulate[i^3, {i, {2, x^4, a}}]

>> Manipulate[x^y, {x, 1, 20}, {y, 1, 3}]
Manipulate[x^y, {x, 1, 20}, {y, 1, 3}]
```

```
>> Manipulate[N[1 / x], {{x, 1}, 0, 2}]
Manipulate[N[1 / x], {{x, 1}, 0, 2}]

>> Manipulate[N[1 / x], {{x, 1}, 0, 2, 0.1}]
Manipulate[N[1 / x], {{x, 1}, 0, 2, 0.1}]
```

## System'Private'ManipulateParameter

# XXIX. Number theoretic functions

## Contents

ContinuedFraction . . .	171	GCD . . . . .	172	Prime . . . . .	174
CoprimeQ . . . . .	171	IntegerExponent . . . .	172	PrimePi . . . . .	174
Divisors . . . . .	172	LCM . . . . .	173	PrimePowerQ . . . . .	174
EvenQ . . . . .	172	MantissaExponent . . .	173	PrimeQ . . . . .	174
FactorInteger . . . . .	172	Mod . . . . .	173	Quotient . . . . .	175
FractionalPart . . . . .	172	NextPrime . . . . .	173	QuotientRemainder . .	175
FromContinuedFraction	172	OddQ . . . . .	173	RandomPrime . . . . .	175
		PowerMod . . . . .	174		

## ContinuedFraction

`ContinuedFraction[x, n]`  
generate the first  $n$  terms in the continued fraction representation of  $x$ .

`ContinuedFraction[x]`  
the complete continued fraction representation for a rational or quadratic irrational number.

```
>> ContinuedFraction[Pi, 10]
{3, 7, 15, 1, 292, 1, 1, 1, 2, 1}

>> ContinuedFraction[(1 + 2 Sqrt[3])/5]
{0, 1, {8, 3, 34, 3}}
```

```
>> ContinuedFraction[Sqrt[70]]
{8, {2, 1, 2, 1, 2, 16}}
```

## CoprimeQ

`CoprimeQ[x, y]`  
tests whether  $x$  and  $y$  are coprime by computing their greatest common divisor.

```
>> CoprimeQ[7, 9]
True
```

```
>> CoprimeQ[-4, 9]
True

>> CoprimeQ[12, 15]
False
```

`CoprimeQ` also works for complex numbers

```
>> CoprimeQ[1+2I, 1-I]
True

>> CoprimeQ[4+2I, 6+3I]
True

>> CoprimeQ[2, 3, 5]
True

>> CoprimeQ[2, 4, 5]
False
```

## Divisors

`Divisors[n]`  
returns a list of the integers that divide  $n$ .

```
>> Divisors[96]
{1, 2, 3, 4, 6, 8, 12, 16, 24, 32, 48, 96}

>> Divisors[704]
{1, 2, 4, 8, 11, 16, 22, 32, 44, 64, 88, 176, 352, 704}
```

```
>> Divisors[{87, 106, 202, 305}]
{{1, 3, 29, 87}, {1, 2, 53, 106},
 {1, 2, 101, 202}, {1, 5, 61, 305}}
```

## EvenQ

**EvenQ**[*x*]  
returns True if *x* is even, and False otherwise.

```
>> EvenQ[4]
True

>> EvenQ[-3]
False

>> EvenQ[n]
False
```

## FactorInteger

**FactorInteger**[*n*]  
returns the factorization of *n* as a list of factors and exponents.

```
>> factors = FactorInteger[2010]
{{2, 1}, {3, 1}, {5, 1}, {67, 1}}
```

To get back the original number:

```
>> Times @@ Power @@@ factors
2010
```

**FactorInteger** factors rationals using negative exponents:

```
>> FactorInteger[2010 / 2011]
{{2, 1}, {3, 1}, {5, 1},
 {67, 1}, {2011, -1}}
```

## FractionalPart

**FractionalPart**[*n*]  
finds the fractional part of *n*.

```
>> FractionalPart[4.1]
0.1

>> FractionalPart[-5.25]
-0.25
```

## FromContinuedFraction

**FromContinuedFraction**[*list*]  
reconstructs a number from the list of its continued fraction terms.

```
>> FromContinuedFraction[{3, 7, 15,
 1, 292, 1, 1, 1, 2, 1}]
1 146 408
-----
364 913
```

```
>> FromContinuedFraction[Range[5]]
225
---
157
```

## GCD

**GCD**[*n1*, *n2*, ...]  
computes the greatest common divisor of the given integers.

```
>> GCD[20, 30]
10

>> GCD[10, y]
GCD[10, y]
```

**GCD** is Listable:

```
>> GCD[4, {10, 11, 12, 13, 14}]
{2, 1, 4, 1, 2}
```

**GCD** does not work for rational numbers and Gaussian integers yet.

## IntegerExponent

**IntegerExponent**[*n*, *b*]  
gives the highest exponent of *b* that divides *n*.

```
>> IntegerExponent[16, 2]
4

>> IntegerExponent[-510000]
4

>> IntegerExponent[10, b]
IntegerExponent[10, b]
```

## LCM

`LCM[n1, n2, ...]`  
computes the least common multiple of the given integers.

```
>> LCM[15, 20]
60
>> LCM[20, 30, 40, 50]
600
```

## MantissaExponent

`MantissaExponent[n]`  
finds a list containing the mantissa and exponent of a given number  $n$ .  
`MantissaExponent[n, b]`  
finds the base  $b$  mantissa and exponent of  $n$ .

```
>> MantissaExponent[2.5*10^20]
{0.25, 21}
>> MantissaExponent[125.24]
{0.12524, 3}
>> MantissaExponent[125., 2]
{0.976563, 7}
>> MantissaExponent[10, b]
MantissaExponent[10, b]
```

## Mod

`Mod[x, m]`  
returns  $x$  modulo  $m$ .

```
>> Mod[14, 6]
2
>> Mod[-3, 4]
1
>> Mod[-3, -4]
-3
```

```
>> Mod[5, 0]
The argument 0 should be non zero.
Mod[5, 0]
```

## NextPrime

`NextPrime[n]`  
gives the next prime after  $n$ .  
`NextPrime[n, k]`  
gives the  $k$ th prime after  $n$ .

```
>> NextPrime[10000]
10007
>> NextPrime[100, -5]
73
>> NextPrime[10, -5]
-2
>> NextPrime[100, 5]
113
>> NextPrime[5.5, 100]
563
>> NextPrime[5, 10.5]
NextPrime[5, 10.5]
```

## OddQ

`OddQ[x]`  
returns True if  $x$  is odd, and False otherwise.

```
>> OddQ[-3]
True
>> OddQ[0]
False
```

## PowerMod

`PowerMod[x, y, m]`  
computes  $x^y$  modulo  $m$ .

```
>> PowerMod[2, 10000000, 3]
1
```

```
>> PowerMod[3, -2, 10]
9

>> PowerMod[0, -1, 2]
Oisnotinvertiblemodulo2.
PowerMod[0, -1, 2]

>> PowerMod[5, 2, 0]
Theargument0shouldbenonzero.
PowerMod[5, 2, 0]
```

PowerMod does not support rational coefficients (roots) yet.

## Prime

`Prime[n]`  
returns the  $n$ th prime number.

```
>> Prime[1]
2

>> Prime[167]
991
```

## PrimePi

`PrimePi[x]`  
gives the number of primes less than or equal to  $x$ .

```
>> PrimePi[100]
25

>> PrimePi[-1]
0

>> PrimePi[3.5]
2

>> PrimePi[E]
1
```

## PrimePowerQ

`PrimePowerQ[n]`  
returns True if  $n$  is a power of a prime number.

```
>> PrimePowerQ[9]
True

>> PrimePowerQ[52142]
False

>> PrimePowerQ[-8]
True

>> PrimePowerQ[371293]
True
```

## PrimeQ

`PrimeQ[n]`  
returns True if  $n$  is a prime number.

For very large numbers, PrimeQ uses probabilistic prime testing, so it might be wrong sometimes (a number might be composite even though PrimeQ says it is prime). The algorithm might be changed in the future.

```
>> PrimeQ[2]
True

>> PrimeQ[-3]
True

>> PrimeQ[137]
True

>> PrimeQ[2 ^ 127 - 1]
True
```

All prime numbers between 1 and 100:

```
>> Select[Range[100], PrimeQ]
{2, 3, 5, 7, 11, 13, 17, 19, 23,
 29, 31, 37, 41, 43, 47, 53, 59,
 61, 67, 71, 73, 79, 83, 89, 97}
```

PrimeQ has attribute Listable:

```
>> PrimeQ[Range[20]]
{False, True, True, False, True,
 False, True, False, False, False,
 True, False, True, False, False,
 False, True, False, True, False}
```

## Quotient

`Quotient[m, n]`  
computes the integer quotient of  $m$  and  $n$ .

```
>> Quotient[23, 7]
3
```

## QuotientRemainder

`QuotientRemainder[m, n]`  
computes a list of the quotient and remainder from division of  $m$  by  $n$ .

```
>> QuotientRemainder[23, 7]
{3, 2}
```

## RandomPrime

`RandomPrime[{imin, imax}]`  
gives a random prime between  $imin$  and  $imax$ .  
`RandomPrime[imax]`  
gives a random prime between 2 and  $imax$ .  
`RandomPrime[range, n]`  
gives a list of  $n$  random primes in  $range$ .

```
>> RandomPrime[{14, 17}]
17

>> RandomPrime[{14, 16}, 1]
There are no primes in the specified interval.
RandomPrime[{14, 16}, 1]

>> RandomPrime[{8, 12}, 3]
{11, 11, 11}

>> RandomPrime[{10, 30}, {2, 5}]
{{11, 11, 11, 11, 11},
 {11, 11, 11, 11, 11}}
```

# XXX. XML

## Contents

---

XML'PlaintextImport .	176	XMLElement . . . . .	176	XMLObject . . . . .	176
XML'TagsImport . . .	176	XML'Parser'XMLGet .	176	XML'XMLObjectImport	176
		XML'Parser'XMLGetString	176		

---

## XML'PlaintextImport

```
>> StringReplace[StringTake[Import
["ExampleData/InventionNo1.xml",
"Plaintext"],31],
FromCharacterCode[10]->"/"]
MuseScore 1.2/2012-09-12/5.7/40
```

## XML'TagsImport

```
>> Take[Import["ExampleData/
InventionNo1.xml", "Tags"], 10]
{accidental, alter, arpeggiate,
articulations, attributes, backup,
bar-style, barline, beam, beat-type}
```

## XMLElement

## XML'Parser'XMLGet

## XML'Parser'XMLGetString

```
>> Head[XML'Parser'XMLGetString["<a
></a>"]]
XMLObject[Document]
```

## XMLObject

## XML'XMLObjectImport

```
>> Part[Import["ExampleData/
InventionNo1.xml", "XMLObject"],
2, 3, 1]
XMLElement[identification,
{ }, {XMLElement[encoding,
{ }, {XMLElement[software,
{ }, {MuseScore 1.2}]}],
XMLElement[encoding-date,
{ }, {2012-09-12}]}]}]}
>> Part[Import["ExampleData/
Namespaces.xml"], 2]
XMLElement[book,
{{http://www.w3.org/2000/xmlns/,
xmlns}->urn:loc.gov:books},
{XMLElement[title, { }, {Cheaper
by the Dozen}]}], XMLElement[
{urn:ISBN:0-395-36341-6, number},
{ }, {1568491379}], XMLElement[
notes, { }, {XMLElement[p,
{{http://www.w3.org/2000/xmlns/,
xmlns}->http://www.w3.org/1999/xhtml},
{This is a, XMLElement[i,
{ }, {funny, book!}]}]}]}]}]}]
```



# XXXI. Differential Equations

## Contents

---

C . . . . .	177	DSolve . . . . .	177
-------------	-----	------------------	-----

---

## C

`C[n]`

represents the  $n$ th constant in a solution to a differential equation.

```
>> DSolve[D[y[x, t], t] + 2 D[y[x,
t], x] == 0, y[x, t], {x, t}]
{{y[x, t] -> C[1] [-2t + x]}}
```

## DSolve

`DSolve[eq, y[x], x]`

solves a differential equation for the function  $y[x]$ .

```
>> DSolve[y''[x] == 0, y[x], x]
{{y[x] -> x C[2] + C[1]}}

>> DSolve[y''[x] == y[x], y[x], x]
{{y[x] -> C[1] E^-x + C[2] E^x}}

>> DSolve[y''[x] == y[x], y, x]
{{y -> (Function[{x},
C[1] E^-x + C[2] E^x])}}
```

DSolve can also solve basic PDE

```
>> DSolve[D[f[x, y], x] / f[x, y] +
3 D[f[x, y], y] / f[x, y] == 2,
f, {x, y}]
{{f -> (Function[{x, y},
E^(x/5 + 3y/5) C[1] [3x - y])}]}
```

```
>> DSolve[D[f[x, y], x] x + D[f[x,
y], y] y == 2, f[x, y], {x, y}]
{{f[x, y] -> 2 Log[x] + C[1] [y/x]}}
```

# XXXII. Strings and Characters

## Contents

<code>\$CharacterEncoding</code> . . .	178	<code>NumberString</code> . . . . .	181	<code>StringReplace</code> . . . . .	186
<code>\$CharacterEncodings</code> . .	178	<code>RegularExpression</code> . . .	181	<code>StringRiffle</code> . . . . .	186
<code>CharacterRange</code> . . . . .	178	<code>RemoveDiacritics</code> . . . .	182	<code>StringSplit</code> . . . . .	187
<code>Characters</code> . . . . .	178	<code>StartOfLine</code> . . . . .	182	<code>StringTake</code> . . . . .	187
<code>DamerauLevenshteinDistance</code> . .	179	<code>StartOfString</code> . . . . .	182	<code>StringTrim</code> . . . . .	187
<code>DigitCharacter</code> . . . . .	179	<code>StringCases</code> . . . . .	183	<code>String</code> . . . . .	187
<code>DigitQ</code> . . . . .	179	<code>StringContainsQ</code> . . . . .	183	<code>ToCharacterCode</code> . . . .	188
<code>EditDistance</code> . . . . .	180	<code>StringDrop</code> . . . . .	183	<code>ToExpression</code> . . . . .	188
<code>EndOfLine</code> . . . . .	180	<code>StringExpression (~~)</code> . .	183	<code>ToLowerCase</code> . . . . .	188
<code>EndOfString</code> . . . . .	180	<code>StringFreeQ</code> . . . . .	184	<code>ToString</code> . . . . .	188
<code>FromCharacterCode</code> . . .	180	<code>StringInsert</code> . . . . .	184	<code>ToUpperCase</code> . . . . .	188
<code>HammingDistance</code> . . .	181	<code>StringJoin (&lt;&gt;)</code> . . . . .	185	<code>Transliterate</code> . . . . .	188
<code>HexadecimalCharacter</code> . .	181	<code>StringLength</code> . . . . .	185	<code>UpperCaseQ</code> . . . . .	189
<code>LetterCharacter</code> . . . .	181	<code>StringMatchQ</code> . . . . .	185	<code>Whitespace</code> . . . . .	189
<code>LetterQ</code> . . . . .	181	<code>StringPosition</code> . . . . .	185	<code>WhitespaceCharacter</code> . .	189
<code>LowerCaseQ</code> . . . . .	181	<code>StringQ</code> . . . . .	185	<code>WordBoundary</code> . . . . .	189
		<code>StringRepeat</code> . . . . .	186	<code>WordCharacter</code> . . . . .	189

## \$CharacterEncoding

`CharacterEncoding`  
specifies the default character encoding to use if no other encoding is specified.

## \$CharacterEncodings

### CharacterRange

`CharacterRange["a", "b"]`  
returns a list of the Unicode characters from *a* to *b* inclusive.

```
>> CharacterRange["a", "e"]
{a, b, c, d, e}

>> CharacterRange["b", "a"]
{}
```

## Characters

`Characters["string"]`  
returns a list of the characters in *string*.

```
>> Characters["abc"]
{a, b, c}
```

## DamerauLevenshteinDistance

`DamerauLevenshteinDistance[a, b]`  
returns the Damerau-Levenshtein distance of *a* and *b*, which is defined as the minimum number of transpositions, insertions, deletions and substitutions needed to transform one into the other. In contrast to `EditDistance`, `DamerauLevenshteinDistance` counts transposition of adjacent items (e.g. "ab" into "ba") as one operation of change.



```
>> EditDistance[{1, E, 2, Pi}, {1,
  E, Pi, 2}]
2
```

## EndOfLine

**EndOfString**  
represents the end of a line in a string.

```
>> StringReplace["aba\nbba\na\nab",
  "a" ~~EndOfLine -> "c"]

abc
  bbc
    c
  ab

>> StringSplit["abc\ndef\nhij",
  EndOfLine]

{abc,
  def,
  hij}
```

## EndOfString

**EndOfString**  
represents the end of a string.

Test whether strings end with “e”:

```
>> StringMatchQ[#, __ ~~"e" ~~
  EndOfString] &/@ {"apple", "
  banana", "artichoke"}

{True, False, True}

>> StringReplace["aab\nabb", "b" ~~
  EndOfString -> "c"]

aab
  abc
```

## FromCharCode

**FromCharCode**[*n*]  
returns the character corresponding to  
Unicode codepoint *n*.  
**FromCharCode**[{*n*<sub>1</sub>, *n*<sub>2</sub>, ...}]  
returns a string with characters corre-  
sponding to *n*<sub>*i*</sub>.  
**FromCharCode**[{{*n*<sub>11</sub>, *n*<sub>12</sub>, ...}, {  
*n*<sub>21</sub>, *n*<sub>22</sub>, ...}, ...}]  
returns a list of strings.

```
>> FromCharCode[100]
d

>> FromCharCode[228, "ISO8859
-1"]
ä

>> FromCharCode[{100, 101,
  102}]
def

>> ToCharCode[%]
{100,101,102}

>> FromCharCode[{{97, 98, 99},
  {100, 101, 102}}]
{abc,def}

>> ToCharCode["abc 123"] //
  FromCharCode
abc 123
```

## HammingDistance

**HammingDistance**[*u*, *v*]  
returns the Hamming distance between  
*u* and *v*, i.e. the number of different el-  
ements. *u* and *v* may be lists or strings.

```
>> HammingDistance[{1, 0, 1, 0},
  {1, 0, 0, 1}]
2

>> HammingDistance["time", "dime"]
1

>> HammingDistance["TIME", "dime",
  IgnoreCase -> True]
1
```

## HexidecimalCharacter

HexidecimalCharacter  
represents the characters 0-9, a-f and A-F.

```
>> StringMatchQ[#,  
HexidecimalCharacter] & /@ {"a",  
"1", "A", "x", "H", " ", "."}  
  
{True, True, True, False,  
False, False, False}
```

## LetterCharacter

LetterCharacter  
represents letters.

```
>> StringMatchQ[#, LetterCharacter]  
& /@ {"a", "1", "A", " ", "."}  
  
{True, False, True, False, False}
```

LetterCharacter also matches unicode characters.

```
>> StringMatchQ["\[Lambda]",  
LetterCharacter]  
  
True
```

## LetterQ

LetterQ[*string*] yields True if all the characters in the *string* are letters, and yields False otherwise.

```
>> LetterQ["m"]  
True  
  
>> LetterQ["9"]  
False  
  
>> LetterQ["Mathics"]  
True  
  
>> LetterQ["Welcome to Mathics"]  
False
```

## LowerCaseQ

LowerCaseQ[*s*]  
returns True if *s* consists wholly of lower case characters.

```
>> LowerCaseQ["abc"]  
True
```

An empty string returns True.

```
>> LowerCaseQ[""]  
True
```

## NumberString

NumberString  
represents the characters in a number.

```
>> StringMatchQ["1234",  
NumberString]  
True  
  
>> StringMatchQ["1234.5",  
NumberString]  
True  
  
>> StringMatchQ["1.2'20",  
NumberString]  
False
```

## RegularExpression

RegularExpression[*'regex'*]  
represents the regex specified by the string *'regex'*.

```
>> StringSplit["1.23, 4.56 7.89",  
RegularExpression["(\\s|,)+"]]  
  
{1.23, 4.56, 7.89}
```

## RemoveDiacritics

RemoveDiacritics[*s*]  
returns a version of *s* with all diacritics removed.

```
>> RemoveDiacritics["en prononçant
pêcher et pêcher"]
en prononcant pecher et pecher

>> RemoveDiacritics["piñata"]
pinata
```

## StartOfLine

**StartOfString**  
represents the start of a line in a string.

```
>> StringReplace["aba\nbba\na\nab",
  StartOfLine ~~"a" -> "c"]

cba
  bba
    c
  cb

>> StringSplit["abc\ndef\nhij",
  StartOfLine]

{abc
 ,def
 ,hij}
```

## StartOfString

**StartOfString**  
represents the start of a string.

Test whether strings start with "a":

```
>> StringMatchQ[#, StartOfString ~~
"a" ~~__] &/@ {"apple", "banana", "artichoke"}

{True, False, True}

>> StringReplace["aba\nabb",
  StartOfString ~~"a" -> "c"]

cba
  abb
```

## StringCases

**StringCases**["string", pattern]  
gives all occurrences of pattern in string.  
**StringReplace**["string", pattern -> form]  
gives all instances of form that stem from occurrences of pattern in string.  
**StringCases**["string", {pattern1, pattern2, ...}]  
gives all occurrences of pattern1, pattern2, ....  
**StringReplace**["string", pattern, n]  
gives only the first n occurrences.  
**StringReplace**[{"string1", "string2", ...}, pattern]  
gives occurrences in string1, string2, ...

```
>> StringCases["axbaxxb", "a" ~~x_
~~"b"]

{axb}

>> StringCases["axbaxxb", "a" ~~x_
~~"b"]

{axbaxxb}

>> StringCases["axbaxxb", Shortest
["a" ~~x_ ~~"b"]]

{axb, axxb}

>> StringCases["-abc- def -uvw- xyz", Shortest["-" ~~x_ ~~"-"] ->
x]

{abc, uvw}

>> StringCases["-öhi- -abc- -. -",
  "- " ~~x : WordCharacter .. ~~"- "
-> x]

{öhi, abc}

>> StringCases["abc-abc xyz-uvw",
  Shortest[x : WordCharacter .. ~~
  "- " ~~x_] -> x]

{abc}

>> StringCases["abba", {"a" -> 10,
  "b" -> 20}, 2]

{10, 20}

>> StringCases["a#ä_123",
  WordCharacter]

{a, ä, 1, 2, 3}
```

```
>> StringCases["a#ä_123",
LetterCharacter]

{a,ä}
```

## StringContainsQ

```
StringContainsQ["string", patt]
  returns True if any part of string matches
  patt, and returns False otherwise.
StringContainsQ[{ 's1', "s2", ... },
patt] '
  returns the list of results for each element
  of string list.
StringContainsQ[patt]
  represents an operator form of String-
  ContainsQ that can be applied to an ex-
  pression.
```

```
>> StringContainsQ["mathics", "m" ~
~__ ~~"s"]
True

>> StringContainsQ["mathics", "a" ~
~__ ~~"m"]
False

>> StringContainsQ["Mathics", "MA"
, IgnoreCase -> True]
True

>> StringContainsQ[{"g", "a", "laxy
", "universe", "sun"}, "u"]
{False, False, False, True, True}

>> StringContainsQ["e" ~~__ ~~"u"]
/@ {"The Sun", "Mercury", "
Venus", "Earth", "Mars", "
Jupiter", "Saturn", "Uranus", "
Neptune"}
{True, True, True, False, False,
False, False, False, True}
```

## StringDrop

```
StringDrop["string", n]
  gives string with the first n characters
  dropped.
StringDrop["string", -n]
  gives string with the last n characters
  dropped.
StringDrop["string", {n}]
  gives string with the nth character
  dropped.
StringDrop["string", {m, n}]
  gives string with the characters m through
  n dropped.
```

```
>> StringDrop["abcde", 2]
cde

>> StringDrop["abcde", -2]
abc

>> StringDrop["abcde", {2}]
acde

>> StringDrop["abcde", {2,3}]
ade

>> StringDrop["abcd",{3,2}]
abcd

>> StringDrop["abcd",0]
abcd
```

## StringExpression (~~)

```
StringExpression[s_1, s_2, ...]
  represents a sequence of strings and sym-
  bolic string objects si.
```

```
>> "a" ~~ "b" // FullForm
"ab"
```

## StringFreeQ

`StringFreeQ["string", patt]`  
returns True if no substring in *string* matches the string expression *patt*, and returns False otherwise.

`StringFreeQ[{'s1', "s2", ...}, patt]`  
returns the list of results for each element of string list.

`StringFreeQ['string', {p1, p2, ...}]`  
returns True if no substring matches any of the *pi*.

`StringFreeQ[patt]`  
represents an operator form of `StringFreeQ` that can be applied to an expression.

```
>> StringFreeQ["mathics", "m" ~~__
~~"s"]
False

>> StringFreeQ["mathics", "a" ~~__
~~"m"]
True

>> StringFreeQ["Mathics", "MA" ,
IgnoreCase -> True]
False

>> StringFreeQ[{"g", "a", "laxy", "
universe", "sun"}, "u"]
{True, True, True, False, False}

>> StringFreeQ["e" ~~__ ~~"u"] /@
{"The Sun", "Mercury", "Venus",
"Earth", "Mars", "Jupiter", "
Saturn", "Uranus", "Neptune"}
{False, False, False, True,
True, True, True, True, False}

>> StringFreeQ[{"A", "Galaxy", "Far",
"Far", "Away"}, {"F" ~~__ ~~"
r", "aw" ~~__}, IgnoreCase ->
True]
{True, True, False, False, False}
```

## StringInsert

`StringInsert["string", "snew", n]`  
yields a string with *snew* inserted starting at position *n* in *string*.

`StringInsert["string", "snew", -n]`  
inserts a at position *n* from the end of *string*.

`StringInsert["string", "snew", {n_1, n_2, ...}]`  
inserts a copy of *snew* at each position *n\_i* in *string*; the *n\_i* are taken before any insertion is done.

`StringInsert[{s_1, s_2, ...}, "snew", n]`  
gives the list of results for each of the *s\_i*.

```
>> StringInsert["nothing", "h", 4]
nothing

>> StringInsert["note", "d", -1]
noted

>> StringInsert["here", "t", -5]
there

>> StringInsert["adac", "he", {1, 5}]
headache

>> StringInsert[{"something", "
sometimes"}, " ", 5]
{some thing, some times}

>> StringInsert["1234567890123456",
".", Range[-16, -4, 3]]
1.234.567.890.123.456
```

## StringJoin (<>)

`StringJoin["s1", "s2", ...]`  
returns the concatenation of the strings *s1*, *s2*, .

```
>> StringJoin["a", "b", "c"]
abc

>> "a" <> "b" <> "c" // InputForm
"abc"
```

`StringJoin` flattens lists out:



```
>> StringJoin[{"a", "b"}] //
InputForm
"ab"

>> Print[StringJoin[{"Hello", " ",
{"world"}}, {"!"}]]
Hello world!
```

## StringLength

```
StringLength["string"]
gives the length of string.
```

```
>> StringLength["abc"]
3
```

StringLength is listable:

```
>> StringLength[{"a", "bc"}]
{1, 2}

>> StringLength[x]
String expected.
StringLength[x]
```

## StringMatchQ

```
>> StringMatchQ["abc", "abc"]
True

>> StringMatchQ["abc", "abd"]
False

>> StringMatchQ["15a94xcZ6", (
DigitCharacter | LetterCharacter
)...]
True
```

Use StringMatchQ as an operator

```
>> StringMatchQ[LetterCharacter] ["a"]
True
```

## StringPosition

```
StringPosition["string", patt]
gives a list of starting and ending positions where patt matches "string".
StringPosition["string", patt, n]
returns the first n matches only.
StringPosition["string", {patt1, patt2, ...}, n]
matches multiple patterns.
StringPosition[{s1, s2, ...}, patt]
returns a list of matches for multiple strings.
```

```
>> StringPosition["123
ABCxyABCzzzABCABC", "ABC"]
{{4, 6}, {9, 11}, {15, 17}, {18, 20}}

>> StringPosition["123
ABCxyABCzzzABCABC", "ABC", 2]
{{4, 6}, {9, 11}}
```

StringPosition can be useful for searching through text.

```
>> data = Import["ExampleData/
EinsteinSzilLetter.txt"];

>> StringPosition[data, "uranium"]
{{299, 305}, {870, 876}, {1538, 1~
~544}, {1671, 1677}, {2300, 2306
}, {2784, 2790}, {3093, 3099}}
```

## StringQ

```
StringQ[expr]
returns True if expr is a String, or False otherwise.
```

```
>> StringQ["abc"]
True

>> StringQ[1.5]
False

>> Select[{"12", 1, 3, 5, "yz", x,
y}, StringQ]
{12, yz}
```

## StringRepeat

```
StringRepeat["string", n]
  gives string repeated n times.
StringRepeat["string", n, max]
  gives string repeated n times, but not
  more than max characters.
```

```
>> StringRepeat["abc", 3]
abcabcabc

>> StringRepeat["abc", 10, 7]
abcabca
```

## StringReplace

```
StringReplace["string", "a" -> "b"]
  replaces each occurrence of old with new
  in string.
StringReplace["string", {"s1" -> "sp1", "s2" -> "sp2"}]
  performs multiple replacements of each
  si by the corresponding spi in string.
StringReplace["string", srules, n]
  only performs the first n replacements.
StringReplace[{"string1", "string2", ...}, srules]
  performs the replacements specified by
  srules on a list of strings.
```

StringReplace replaces all occurrences of one substring with another:

```
>> StringReplace["xyxyxyxyxyxyxy",
  "xy" -> "A"]
AAxyxxAyA
```

Multiple replacements can be supplied:

```
>> StringReplace["xyzwxyzwxyzxyzw",
  {"xyz" -> "A", "w" -> "BCD"}]
ABCDABCDxABCD
```

Only replace the first 2 occurrences:

```
>> StringReplace["xyxyxyxyxyxyxy",
  "xy" -> "A", 2]
AAxyxyxyxyxy
```

Also works for multiple rules:

```
>> StringReplace["abba", {"a" -> "A",
  "b" -> "B"}, 2]
ABba
```

StringReplace acts on lists of strings too:

```
>> StringReplace[{"xyxyxy", "
  yxyxyxyxyxy"}, "xy" -> "A"]
{AAxA, yAAxAyA}
```

StringReplace also can be used as an operator:

```
>> StringReplace["y" -> "ies"]["
  city"]
cities
```

## StringRiffle

```
StringRiffle[{s1, s2, s3, ...}]
  returns a new string by concatenating
  all the si, with spaces inserted between
  them.
StringRiffle[list, sep]
  inserts the separator sep between all ele-
  ments in list.
StringRiffle[list, {"left", "sep",
  "right"}]
  use left and right as delimiters after con-
  catenation.
```

```
>> StringRiffle[{"a", "b", "c", "d",
  "e"}]
a b c d e

>> StringRiffle[{"a", "b", "c", "d",
  "e"}, " ", " "]
a, b, c, d, e

>> StringRiffle[{"a", "b", "c", "d",
  "e"}, {"(", " ", ")"}]
(a b c d e)
```

## StringSplit

```
StringSplit["s"]
  splits the string s at whitespace, discard-
  ing the whitespace and returning a list of
  strings.
StringSplit["s", "d"]
  splits s at the delimiter d.
StringSplit[s, {"d1", "d2", ...}]
  splits s using multiple delimiters.
```

```
>> StringSplit["abc,123", ",", " "]
{abc, 123}
```

```
>> StringSplit["abc 123"]
{abc,123}

>> StringSplit["abc,123.456", {"",",",
"."}]
{abc,123,456}

>> StringSplit["a b c",
RegularExpression[" +"]]
{a,b,c}
```

## StringTake

`StringTake["string", n]`  
gives the first *n* characters in *string*.  
`StringTake["string", -n]`  
gives the last *n* characters in *string*.  
`StringTake["string", {n}]`  
gives the *n*th character in *string*.  
`StringTake["string", {m, n}]`  
gives characters *m* through *n* in *string*.  
`StringTake["string", {m, n, s}]`  
gives characters *m* through *n* in steps of *s*.

```
>> StringTake["abcde", 2]
ab

>> StringTake["abcde", 0]

>> StringTake["abcde", -2]
de

>> StringTake["abcde", {2}]
b

>> StringTake["abcd", {2,3}]
bc

>> StringTake["abcdefgh", {1, 5,
2}]
ace
```

`StringTake` also supports standard sequence specifications

```
>> StringTake["abcdef", All]
abcdef
```

## StringTrim

`StringTrim[s]`  
returns a version of *s* with whitespace removed from start and end.

```
>> StringJoin["a", StringTrim[" \tb
\n "], "c"]
abc

>> StringTrim["ababaxababyaabab",
RegularExpression["(ab)+"]]
axababya
```

## String

`String`  
is the head of strings.

```
>> Head["abc"]
String

>> "abc"
abc
```

Use `InputForm` to display quotes around strings:

```
>> InputForm["abc"]
"abc"
```

`FullForm` also displays quotes:

```
>> FullForm["abc" + 2]
Plus[2,"abc"]
```

## ToCharacterCode

`ToCharacterCode["string"]`  
converts the string to a list of character codes (Unicode codepoints).  
`ToCharacterCode[{"string1", "string2", ...}]`  
converts a list of strings to character codes.

```
>> ToCharacterCode["abc"]
{97,98,99}

>> FromCharacterCode[%]
abc
```

```
>> ToCharacterCode["\[Alpha]\[Beta]
\[Gamma]" ]
{945, 946, 947}


>> ToCharacterCode["ä", "UTF8"]
{195, 164}

>> ToCharacterCode["ä", "ISO8859
-1"]
{228}

>> ToCharacterCode[{"ab", "c"}]
{{97, 98}, {99}}

>> ToCharacterCode[{"ab", x}]
Stringorlistofstringsexpectedatposition1inToCharacterCode[{ab,
x}].
ToCharacterCode[{ab,x}]

>> ListPlot[ToCharacterCode["plot
this string"], Filling -> Axis]
```



## ToExpression

`ToExpression[input]`  
interprets a given string as Mathics input.

`ToExpression[input, form]`  
reads the given input in the specified *form*.

`ToExpression[input, form, h]`  
applies the head *h* to the expression before evaluating it.

```
>> ToExpression["1 + 2"]
3

>> ToExpression["{2, 3, 1}",
InputForm, Max]
3
```

## ToLowerCase

`ToLowerCase[s]`  
returns *s* in all lower case.

```
>> ToLowerCase["New York"]
new york
```

## ToString

`ToString[expr]`  
returns a string representation of *expr*.

```
>> ToString[{ab,
2}
2

>> ToString[2] // InputForm
"2"

>> ToString[a+b]
a + b

>> "U" <> 2
Stringexpected.
U<>2

>> "U" <> ToString[2]
U2
```

## ToUpperCase

`ToUpperCase[s]`  
returns *s* in all upper case.

```
>> ToUpperCase["New York"]
NEW YORK
```

## Transliterate

`Transliterate[s]`  
transliterates a text in some script into an ASCII string.

# The following examples were taken from  
# <https://en.wikipedia.org/wiki/Iliad>, #  
[https://en.wikipedia.org/wiki/Russian\\_language](https://en.wikipedia.org/wiki/Russian_language),  
and # <https://en.wikipedia.org/wiki/Hiragana>

## UpperCaseQ

`UpperCaseQ[s]`  
returns True if *s* consists wholly of upper case characters.

```
>> UpperCaseQ["ABC"]
True
```

An empty string returns True.

```
>> UpperCaseQ[""]
True
```

## Whitespace

`Whitespace`  
represents a sequence of whitespace characters.

```
>> StringMatchQ["\r\n", Whitespace]
True
```

```
>> StringSplit["a\nb\r\ncd", Whitespace]
{a,b,c,d}
```

```
>> StringReplace[" this has leading
and trailing whitespace\n", (
  StartOfString ~~Whitespace)| (
  Whitespace ~~EndOfString)-> ""]
<> " removed" // FullForm
"this has leading and trailing
 whitespace removed"
```

## WhitespaceCharacter

`WhitespaceCharacter`  
represents a single whitespace character.

```
>> StringMatchQ["\n", WhitespaceCharacter]
True
```

```
>> StringSplit["a\nb\r\nc\r d", WhitespaceCharacter]
{a,b,c,d}
```

For sequences of whitespace characters use `Whitespace`:

```
>> StringMatchQ["\n", WhitespaceCharacter]
False
>> StringMatchQ["\n", Whitespace]
True
```

## WordBoundary

`WordBoundary`  
represents the boundary between words.

```
>> StringReplace["apple banana
orange artichoke", "e" ~~
  WordBoundary -> "E"]
applE banana orangE artichokE
```

## WordCharacter

`WordCharacter`  
represents a single letter or digit character.

```
>> StringMatchQ[#, WordCharacter]
&/@ {"1", "a", "A", ",", " "}
{True, True, True, False, False}
```

Test whether a string is alphanumeric:

```
>> StringMatchQ["abc123DEF", WordCharacter..]
True
>> StringMatchQ["$b;123", WordCharacter..]
False
```

# XXXIII. Optimization

## Contents

---

Maximize . . . . .	190	Minimize . . . . .	190
--------------------	-----	--------------------	-----

---

## Maximize

`Maximize[f, x]`  
compute the maximum of  $f$  respect  $x$  that  
change between  $a$  and  $b$

```
>> Maximize[-2 x^2 - 3 x + 5, x]

$$\left\{ \left\{ \frac{49}{8}, \left\{ x - > -\frac{3}{4} \right\} \right\} \right\}$$

#» Maximize[1 - (x y - 3)^2, {x, y}] = {{1, {x -> 3, y -> 1}}}
#» Maximize[{x - 2 y, x^2 + y^2 <= 1}, {x, y}] =
{{Sqrt[5], {x -> Sqrt[5] / 5, y -> -2 Sqrt[5] / 5}}}
```

## Minimize

`Minimize[f, x]`  
compute the minimum of  $f$  respect  $x$  that  
change between  $a$  and  $b$

```
>> Minimize[2 x^2 - 3 x + 5, x]

$$\left\{ \left\{ \frac{31}{8}, \left\{ x - > \frac{3}{4} \right\} \right\} \right\}$$

#» Minimize[(x y - 3)^2 + 1, {x, y}] = {{1, {x -> 3, y -> 1}}}
#» Minimize[{x - 2 y, x^2 + y^2 <= 1}, {x, y}] =
{{-Sqrt[5], {x -> -Sqrt[5] / 5, y -> 2 Sqrt[5] / 5}}}
```

## XXXIV. Image[] and image related functions.

Note that you (currently) need scikit-image installed in order for this module to work.

### Contents

---

Binarize . . . . .	191	ImageAdd . . . . .	195	ImageSubtract . . . . .	198
BinaryImageQ . . . . .	191	ImageAdjust . . . . .	195	ImageTake . . . . .	198
Blur . . . . .	192	ImageAspectRatio . . . . .	195	ImageType . . . . .	198
BoxMatrix . . . . .	192	Image . . . . .	195	MaxFilter . . . . .	198
Closing . . . . .	192	ImageBox . . . . .	195	MedianFilter . . . . .	198
ColorCombine . . . . .	192	ImageChannels . . . . .	195	MinFilter . . . . .	198
ColorConvert . . . . .	192	ImageColorSpace . . . . .	195	MorphologicalCompo- nents . . . . .	199
ColorNegate . . . . .	192	ImageConvolve . . . . .	195	Opening . . . . .	199
ColorQuantize . . . . .	192	ImageData . . . . .	196	PillowImageFilter . . . . .	199
ColorSeparate . . . . .	192	ImageDimensions . . . . .	196	PixelValue . . . . .	199
Colorize . . . . .	193	ImageExport . . . . .	196	PixelValuePositions . . . . .	199
DiamondMatrix . . . . .	193	ImageImport . . . . .	196	RandomImage . . . . .	199
Dilation . . . . .	193	ImageMultiply . . . . .	196	Sharpen . . . . .	199
DiskMatrix . . . . .	193	ImagePartition . . . . .	197	TextRecognize . . . . .	200
DominantColors . . . . .	194	ImageQ . . . . .	197	Threshold . . . . .	200
EdgeDetect . . . . .	194	ImageReflect . . . . .	197	WordCloud . . . . .	200
Erosion . . . . .	194	ImageResize . . . . .	197		
GaussianFilter . . . . .	194	ImageRotate . . . . .	198		

---

### Binarize

`Binarize[image]`  
gives a binarized version of *image*, in which each pixel is either 0 or 1.

`Binarize[image, t]`  
map values  $x > t$  to 1, and values  $x \leq t$  to 0.

`Binarize[image, {t1, t2}]`  
map  $t1 < x < t2$  to 1, and all other values to 0.

```
>> img = Import["ExampleData/lena.tif"];
>> Binarize[img]
-Image-
>> Binarize[img, 0.7]
-Image-
```

```
>> Binarize[img, {0.2, 0.6}]
-Image-
```

### BinaryImageQ

`BinaryImageQ[$image]`  
returns True if the pixels of \$image are binary bit values, and False otherwise.

```
>> img = Import["ExampleData/lena.tif"];
>> BinaryImageQ[img]
False
>> BinaryImageQ[Binarize[img]]
True
```

## Blur

`Blur[image]`  
gives a blurred version of *image*.  
`Blur[image, r]`  
blurs *image* with a kernel of size *r*.

```
>> lena = Import["ExampleData/lena.tif"];
>> Blur[lena]
-Image-
>> Blur[lena, 5]
-Image-
```

## BoxMatrix

`BoxMatrix[s]`  
Gives a box shaped kernel of size  $2s + 1$ .

```
>> BoxMatrix[3]
{{1,1,1,1,1,1,1}, {1,1,1,1,1,1,1},
 {1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}}
{{1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}}
```

## Closing

`Closing[image, ker]`  
Gives the morphological closing of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/Einstein.jpg"];
>> Closing[ein, 2.5]
-Image-
```

## ColorCombine

`ColorCombine[channels, colorspace]`  
Gives an image with *colorspace* and the respective components described by the given channels.

```
>> ColorCombine[{{1, 0}, {0, 0.75}}, {{0, 1}, {0, 0.25}},
{{0, 0}, {1, 0.5}}, "RGB"]
-Image-
```

## ColorConvert

`ColorConvert[c, colorspace]`  
returns the representation of *c* in the color space *colorspace*. *c* may be a color or an image.

Valid values for *colorspace* are:

CMYK: convert to CMYKColor Grayscale: convert to GrayLevel HSB: convert to Hue LAB: convert to LABColor LCH: convert to LCHColor LUV: convert to LUVColor RGB: convert to RGBColor XYZ: convert to XYZColor

## ColorNegate

`ColorNegate[image]`  
Gives a version of *image* with all colors negated.

## ColorQuantize

`ColorQuantize[image, n]`  
gives a version of *image* using only *n* colors.

```
>> img = Import["ExampleData/lena.tif"];
>> ColorQuantize[img, 6]
-Image-
```

## ColorSeparate

`ColorSeparate[image]`  
Gives each channel of *image* as a separate grayscale image.



## Colorize

`Colorize[values]`

returns an image where each number in the rectangular matrix *values* is a pixel and each occurrence of the same number is displayed in the same unique color, which is different from the colors of all non-identical numbers.

`Colorize[image]`

gives a colorized version of *image*.

```
>> Colorize[{{1.3, 2.1, 1.5}, {1.3,
  1.3, 2.1}, {1.3, 2.1, 1.5}}]
-Image-

>> Colorize[{{1, 2}, {2, 2}, {2,
  3}}, ColorFunction -> (Blend[{
  White, Blue}, #]&)]
-Image-
```

## DiamondMatrix

`DiamondMatrix[$s]`

Gives a diamond shaped kernel of size  $2s + 1$ .

```
>> DiamondMatrix[3]
{{0,0,0,1,0,0,0}, {0,0,1,1,1,
  0,0}, {0,1,1,1,1,1,0}, {1,1,1,
  1,1,1,1}, {0,1,1,1,1,1,0}, {0,
  0,1,1,1,0,0}, {0,0,0,1,0,0,0}}
```

## Dilation

`Dilation[image, ker]`

Gives the morphological dilation of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/
  Einstein.jpg"];

>> Dilation[ein, 2.5]
-Image-
```

## DiskMatrix

`DiskMatrix[$s]`

Gives a disk shaped kernel of size  $2s + 1$ .

```
>> DiskMatrix[3]
{{0,0,1,1,1,0,0}, {0,1,1,1,1,
  1,0}, {1,1,1,1,1,1,1}, {1,1,1,
  1,1,1,1}, {1,1,1,1,1,1,1}, {0,
  1,1,1,1,1,0}, {0,0,1,1,1,0,0}}
```

## DominantColors

`DominantColors[image]`

gives a list of colors which are dominant in the given image.

`DominantColors[image, n]`

returns at most *n* colors.

`DominantColors[image, n, prop]`

returns the given property *prop*, which may be "Color" (return RGB colors), "LABColor" (return LAB colors), "Count" (return the number of pixels a dominant color covers), "Coverage" (return the fraction of the image a dominant color covers), or "CoverageImage" (return a black and white image indicating with white the parts that are covered by a dominant color).

The option "ColorCoverage" specifies the minimum amount of coverage needed to include a dominant color in the result.

The option "MinColorDistance" specifies the distance (in LAB color space) up to which colors are merged and thus regarded as belonging to the same dominant color.

```
>> img = Import["ExampleData/lena.
  tif"]
-Image-

>> DominantColors[img]
{{Red, Red, Blue, Red, Red, Red}}



>> DominantColors[img, 3]
{{Red, Red, Blue}}
```



```
>> DominantColors[img, 3, "Coverage
"]




$$\left\{ \frac{28\,579}{131\,072}, \frac{751}{4\,096}, \frac{23\,841}{131\,072} \right\}$$


>> DominantColors[img, 3, "
CoverageImage"]
{-Image-, -Image-, -Image-}

>> DominantColors[img, 3, "Count"]
{57 158, 48 064, 47 682}

>> DominantColors[img, 2, "LABColor
"]
{, }

>> DominantColors[img,
MinColorDistance -> 0.5]
{, }

>> DominantColors[img,
ColorCoverage -> 0.15]
{, , }
```

## EdgeDetect

`EdgeDetect[image]`  
returns an image showing the edges in *image*.

```
>> lena = Import["ExampleData/lena.
.tif"];

>> EdgeDetect[lena]
-Image-

>> EdgeDetect[lena, 5]
-Image-

>> EdgeDetect[lena, 4, 0.5]
-Image-
```

## Erosion

`Erosion[image, ker]`  
Gives the morphological erosion of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/
Einstein.jpg"];

>> Erosion[ein, 2.5]
-Image-
```

## GaussianFilter

`GaussianFilter[image, r]`  
blurs *image* using a Gaussian blur filter of radius *r*.

```
>> lena = Import["ExampleData/lena.
.tif"];

>> GaussianFilter[lena, 2.5]
-Image-
```

## ImageAdd

`ImageAdd[image, expr_1, expr_2, ...]`  
adds all *expr\_i* to *image* where each *expr\_i* must be an image or a real number.

```
>> i = Image[{{0, 0.5, 0.2, 0.1,
0.9}, {1.0, 0.1, 0.3, 0.8,
0.6}}];

>> ImageAdd[i, 0.5]
-Image-

>> ImageAdd[i, i]
-Image-

>> ein = Import["ExampleData/
Einstein.jpg"];

>> noise = RandomImage[{-0.1, 0.1},
ImageDimensions[ein]];

>> ImageAdd[noise, ein]
-Image-

>> lena = Import["ExampleData/lena.
.tif"];

>> noise = RandomImage[{-0.2, 0.2},
ImageDimensions[lena],
ColorSpace -> "RGB"];
```

```
>> ImageAdd[noise, lena]
      -Image-
```

## ImageAdjust

`ImageAdjust[image]`  
adjusts the levels in *image*.  
`ImageAdjust[image, c]`  
adjusts the contrast in *image* by *c*.  
`ImageAdjust[image, {c, b}]`  
adjusts the contrast *c*, and brightness *b* in *image*.  
`ImageAdjust[image, {c, b, g}]`  
adjusts the contrast *c*, brightness *b*, and gamma *g* in *image*.

```
>> lena = Import["ExampleData/lena.tif"];

>> ImageAdjust[lena]
      -Image-
```

## ImageAspectRatio

`ImageAspectRatio[image]`  
gives the aspect ratio of *image*.

```
>> img = Import["ExampleData/lena.tif"];

>> ImageAspectRatio[img]
1

>> ImageAspectRatio[Image[{{0, 1}, {1, 0}, {1, 1}}]]
3
2
```

## Image

## ImageBox

## ImageChannels

`ImageChannels[image]`  
gives the number of channels in *image*.

```
>> ImageChannels[Image[{{0, 1}, {1, 0}}]]
1

>> img = Import["ExampleData/lena.tif"];

>> ImageChannels[img]
3
```

## ImageColorSpace

`ImageColorSpace[image]`  
gives *image*'s color space, e.g. "RGB" or "CMYK".

```
>> img = Import["ExampleData/lena.tif"];

>> ImageColorSpace[img]
RGB
```

## ImageConvolve

`ImageConvolve[image, kernel]`  
Computes the convolution of *image* using *kernel*.

```
>> img = Import["ExampleData/lena.tif"];

>> ImageConvolve[img, DiamondMatrix[5] / 61]
      -Image-

>> ImageConvolve[img, DiskMatrix[5] / 97]
      -Image-

>> ImageConvolve[img, BoxMatrix[5] / 121]
      -Image-
```

## ImageData

`ImageData[image]`  
gives a list of all color values of *image* as a matrix.

`ImageData[image, stype]`  
gives a list of color values in type *stype*.

```
>> img = Image[{{0.2, 0.4}, {0.9, 0.6}, {0.5, 0.8}}];
>> ImageData[img]
{{0.2, 0.4}, {0.9, 0.6}, {0.5, 0.8}}
>> ImageData[img, "Byte"]
{{51, 102}, {229, 153}, {127, 204}}
>> ImageData[Image[{{0, 1}, {1, 0}, {1, 1}}], "Bit"]
{{0, 1}, {1, 0}, {1, 1}}
```

## ImageDimensions

`ImageDimensions[image]`  
Returns the dimensions of *image* in pixels.

```
>> lena = Import["ExampleData/lena.tif"];
>> ImageDimensions[lena]
{512, 512}
>> ImageDimensions[RandomImage[1, {50, 70}]]
{50, 70}
```

## ImageExport

### ImageImport

```
>> Import["ExampleData/Einstein.jpg"]
-Image-
>> Import["ExampleData/MadTeaParty.gif"]
-Image-
```

```
>> Import["ExampleData/moon.tif"]
-Image-
```

## ImageMultiply

`ImageMultiply[image, expr_1, expr_2, ...]`  
multiplies all *expr\_i* with *image* where each *expr\_i* must be an image or a real number.

```
>> i = Image[{{0, 0.5, 0.2, 0.1, 0.9}, {1.0, 0.1, 0.3, 0.8, 0.6}}];
>> ImageMultiply[i, 0.2]
-Image-
>> ImageMultiply[i, i]
-Image-
>> ein = Import["ExampleData/Einstein.jpg"];
>> noise = RandomImage[{0.7, 1.3}, ImageDimensions[ein]];
>> ImageMultiply[noise, ein]
-Image-
```

## ImagePartition

`ImagePartition[image, s]`  
Partitions an image into an array of *s* x *s* pixel subimages.

`ImagePartition[image, {w, h}]`  
Partitions an image into an array of *w* x *h* pixel subimages.

```
>> lena = Import["ExampleData/lena.tif"];
>> ImageDimensions[lena]
{512, 512}
>> ImagePartition[lena, 256]
{{-Image-, -Image-},
 {-Image-, -Image-}}
```

```
>> ImagePartition[lena, {512, 128}]
{{{-Image-}}, {-Image-}},
{{{-Image-}}, {-Image-}}}
```

## ImageQ

`ImageQ[Image[$pixels]]`  
returns True if \$pixels has dimensions from which an Image can be constructed, and False otherwise.

```
>> ImageQ[Image[{{0, 1}, {1, 0}}]]
True
>> ImageQ[Image[{{{0, 0, 0}, {0, 1, 0}}, {{0, 1, 0}, {0, 1, 1}}]]]
True
>> ImageQ[Image[{{{0, 0, 0}, {0, 1}}, {{0, 1, 0}, {0, 1, 1}}]]]
False
>> ImageQ[Image[{{1, 0, 1}}]]
False
>> ImageQ["abc"]
False
```

## ImageReflect

`ImageReflect[image]`  
Flips *image* top to bottom.  
`ImageReflect[image, side]`  
Flips *image* so that *side* is interchanged with its opposite.  
`ImageReflect[image, side_1 -> side_2]`  
Flips *image* so that *side\_1* is interchanged with *side\_2*.

```
>> ein = Import["ExampleData/Einstein.jpg"];
>> ImageReflect[ein]
-Image-
>> ImageReflect[ein, Left]
-Image-
>> ImageReflect[ein, Left -> Top]
-Image-
```

## ImageResize

`ImageResize[image, width]`  
`ImageResize[image, {width, height}]`

```
>> ein = Import["ExampleData/Einstein.jpg"];
>> ImageDimensions[ein]
{615, 768}
>> ImageResize[ein, {400, 600}]
-Image-
>> ImageResize[ein, 256]
-Image-
>> ImageDimensions[%]
{256, 320}
```

The default sampling method is Bicubic

```
>> ImageResize[ein, 256, Resampling -> "Bicubic"]
-Image-
>> ImageResize[ein, 256, Resampling -> "Nearest"]
-Image-
>> ImageResize[ein, 256, Resampling -> "Gaussian"]
-Image-
```

## ImageRotate

`ImageRotate[image]`  
Rotates *image* 90 degrees counterclockwise.  
`ImageRotate[image, theta]`  
Rotates *image* by a given angle *theta*

```
>> ein = Import["ExampleData/Einstein.jpg"];
>> ImageRotate[ein]
-Image-
>> ImageRotate[ein, 45 Degree]
-Image-
```

```
>> ImageRotate[ein, Pi / 2]
-Image-
```

## ImageSubtract

`ImageSubtract[image, expr_1, expr_2, ...]`  
 subtracts all *expr\_i* from *image* where each *expr\_i* must be an image or a real number.

```
>> i = Image[{{0, 0.5, 0.2, 0.1, 0.9}, {1.0, 0.1, 0.3, 0.8, 0.6}}];
>> ImageSubtract[i, 0.2]
-Image-
>> ImageSubtract[i, i]
-Image-
```

## ImageTake

`ImageTake[image, n]`  
 gives the first *n* rows of *image*.  
`ImageTake[image, -n]`  
 gives the last *n* rows of *image*.  
`ImageTake[image, {r1, r2}]`  
 gives rows *r1*, ..., *r2* of *image*.  
`ImageTake[image, {r1, r2}, {c1, c2}]`  
 gives a cropped version of *image*.

## ImageType

`ImageType[image]`  
 gives the interval storage type of *image*, e.g. "Real", "Bit32", or "Bit".

```
>> img = Import["ExampleData/lena.tif"];
>> ImageType[img]
Byte
>> ImageType[Image[{{0, 1}, {1, 0}}]]
Real
```

```
>> ImageType[Binarize[img]]
Bit
```

## MaxFilter

`MaxFilter[image, r]`  
 gives *image* with a maximum filter of radius *r* applied on it. This always picks the largest value in the filter's area.

```
>> lena = Import["ExampleData/lena.tif"];
>> MaxFilter[lena, 5]
-Image-
```

## MedianFilter

`MedianFilter[image, r]`  
 gives *image* with a median filter of radius *r* applied on it. This always picks the median value in the filter's area.

```
>> lena = Import["ExampleData/lena.tif"];
>> MedianFilter[lena, 5]
-Image-
```

## MinFilter

`MinFilter[image, r]`  
 gives *image* with a minimum filter of radius *r* applied on it. This always picks the smallest value in the filter's area.

```
>> lena = Import["ExampleData/lena.tif"];
>> MinFilter[lena, 5]
-Image-
```

## MorphologicalComponents

### Opening

`Opening[image, ker]`

Gives the morphological opening of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/  
Einstein.jpg"];
```

```
>> Opening[ein, 2.5]  
—Image—
```

### PillowImageFilter

### PixelValue

`PixelValue[image, {x, y}]`

gives the value of the pixel at position {x, y} in *image*.

```
>> lena = Import["ExampleData/lena.  
tif"];
```

```
>> PixelValue[lena, {1, 1}]  
{0.321569, 0.0862745, 0.223529}
```

### PixelValuePositions

`PixelValuePositions[image, val]`

gives the positions of all pixels in *image* that have value *val*.

```
>> PixelValuePositions[Image[{{0,  
1}, {1, 0}, {1, 1}}, 1]  
{{1,1}, {1,2}, {2,1}, {2,3}}  
  
>> PixelValuePositions[Image[{{0.2,  
0.4}, {0.9, 0.6}, {0.3, 0.8}},  
0.5, 0.15]  
{{2,2}, {2,3}}  
  
>> img = Import["ExampleData/lena.  
tif"];
```

```
>> PixelValuePositions[img, 3 /  
255, 0.5 / 255]  
{{180,192,2}, {181,192,2},  
 {181,193,2}, {188,204,2},  
 {265,314,2}, {364,77,2}, {365,  
72,2}, {365,73,2}, {365,77,  
2}, {366,70,2}, {367,65,2}}  
  
>> PixelValue[img, {180, 192}]  
{0.25098, 0.0117647, 0.215686}
```

### RandomImage

`RandomImage[max]`

creates an image of random pixels with values 0 to *max*.

`RandomImage[{min, max}]`

creates an image of random pixels with values *min* to *max*.

`RandomImage[... , size]`

creates an image of the given *size*.

```
>> RandomImage[1, {100, 100}]  
—Image—
```

### Sharpen

`Sharpen[image]`

gives a sharpened version of *image*.

`Sharpen[image, r]`

sharpens *image* with a kernel of size *r*.

```
>> lena = Import["ExampleData/lena.  
tif"];  
  
>> Sharpen[lena]  
—Image—  
  
>> Sharpen[lena, 5]  
—Image—
```

## TextRecognize

`TextRecognize[{image}]`  
Recognizes text in *image* and returns it as string.

```
>> WordCloud[StringSplit[Import["
ExampleData/EinsteinSzilLetter.
txt"]]]
-Image-

>> WordCloud[Range[50] -> ToString
/@ Range[50]]
-Image-
```

## Threshold

`Threshold[image]`  
gives a value suitable for binarizing *image*.

The option "Method" may be "Cluster" (use Otsu's threshold), "Median", or "Mean".

```
>> img = Import["ExampleData/lena.
tif"];

>> Threshold[img]
0.456739

>> Binarize[img, %]
-Image-

>> Threshold[img, Method -> "Mean"]
0.486458

>> Threshold[img, Method -> "Median"]
0.504726
```

## WordCloud

`WordCloud[{word1, word2, ...}]`  
Gives a word cloud with the given list of words.

`WordCloud[{weight1 -> word1, weight2 -> word2, ...}]`  
Gives a word cloud with the words weighted using the given weights.

`WordCloud[{weight1, weight2, ...} -> {word1, word2, ...}]`  
Also gives a word cloud with the words weighted using the given weights.

`WordCloud[{{word1, weight1}, {word2, weight2}, ...}]`  
Gives a word cloud with the words weighted using the given weights.



# XXXV. Special Functions

## Contents

AiryAi . . . . .	201	ChebyshevU . . . . .	204	KelvinBei . . . . .	206
AiryAiPrime . . . . .	202	Erf . . . . .	204	KelvinBer . . . . .	206
AiryAiZero . . . . .	202	Erfc . . . . .	204	KelvinKei . . . . .	207
AiryBi . . . . .	202	ExpIntegralE . . . . .	204	KelvinKer . . . . .	207
AiryBiPrime . . . . .	202	ExpIntegralEi . . . . .	205	LaguerreL . . . . .	207
AiryBiZero . . . . .	202	FresnelC . . . . .	205	LegendreP . . . . .	208
AngerJ . . . . .	202	FresnelS . . . . .	205	LegendreQ . . . . .	208
BesselI . . . . .	203	GegenbauerC . . . . .	205	LerchPhi . . . . .	208
BesselJ . . . . .	203	HankelH1 . . . . .	205	ProductLog . . . . .	208
BesselJZero . . . . .	203	HankelH2 . . . . .	205	SphericalHarmonicY . . . . .	208
BesselK . . . . .	203	HermiteH . . . . .	205	StruveH . . . . .	209
BesselY . . . . .	203	InverseErf . . . . .	206	StruveL . . . . .	209
BesselYZero . . . . .	203	InverseErfc . . . . .	206	WeberE . . . . .	209
ChebyshevT . . . . .	204	JacobiP . . . . .	206	Zeta . . . . .	209

## AiryAi

`AiryAi[x]`  
returns the Airy function  $\text{Ai}(x)$ .

Exact values:


```
>> AiryAi[0]
      31/3
-----
3Gamma[2/3]
```

AiryAi can be evaluated numerically:

```
>> AiryAi[0.5]
0.231694

>> AiryAi[0.5 + I]
0.157118 - 0.24104I
```

```
>> Plot[AiryAi[x], {x, -10, 10}]
```



## AiryAiPrime

`AiryAiPrime[x]`  
returns the derivative of the Airy function `AiryAi[x]`.

Exact values:

```
>> AiryAiPrime[0]
      32/3
-----
3Gamma[1/3]
```

Numeric evaluation:

```
>> AiryAiPrime[0.5]
-0.224911
```

## AiryAiZero

**AiryAiZero[k]**  
returns the  $k$ th zero of the Airy function  $\text{Ai}(z)$ .

```
>> N[AiryAiZero[1]]
-2.33811
```

## AiryBi

**AiryBi[x]**  
returns the Airy function of the second kind  $\text{Bi}(x)$ .

Exact values:

```
>> AiryBi[0]

$$\frac{3^{\frac{5}{6}}}{3\Gamma\left[\frac{2}{3}\right]}$$


```

Numeric evaluation:

```
>> AiryBi[0.5]
0.854277

>> AiryBi[0.5 + I]
0.688145 + 0.370815I

>> Plot[AiryBi[x], {x, -10, 2}]
```



## AiryBiPrime

**AiryBiPrime[x]**  
returns the derivative of the Airy function of the second kind  $\text{Ai}(x)$ .

Exact values:

```
>> AiryBiPrime[0]

$$\frac{3^{\frac{1}{6}}}{\Gamma\left[\frac{1}{3}\right]}$$

```

Numeric evaluation:

```
>> AiryBiPrime[0.5]
0.544573
```

## AiryBiZero

**AiryBiZero[k]**  
returns the  $k$ th zero of the Airy function  $\text{Bi}(z)$ .


```
>> N[AiryBiZero[1]]
-1.17371
```

## AngerJ

**AngerJ[n, z]**  
returns the Anger function  $J_n(z)$ .

```
>> AngerJ[1.5, 3.5]
0.294479


>> Plot[AngerJ[1, x], {x, -10, 10}]
```



## BesselI

**BesselI**[ $n$ ,  $z$ ]  
returns the modified Bessel function of the first kind  $I_n(z)$ .


```
>> BesselI[1.5, 4]  
8.17263  
  
>> Plot[BesselI[0, x], {x, 0, 5}]
```



## BesselK

**BesselK**[ $n$ ,  $z$ ]  
returns the modified Bessel function of the second kind  $K_n(z)$ .


```
>> BesselK[1.5, 4]  
0.014347  
  
>> Plot[BesselK[0, x], {x, 0, 5}]
```



## BesselJ

**BesselJ**[ $n$ ,  $z$ ]  
returns the Bessel function of the first kind  $J_n(z)$ .


```
>> BesselJ[0, 5.2]  
-0.11029  
  
>> Plot[BesselJ[0, x], {x, 0, 10}]
```



## BesselY

**BesselY**[ $n$ ,  $z$ ]  
returns the Bessel function of the second kind  $Y_n(z)$ .

```
>> BesselY[1.5, 4]  
0.367112  
  
>> Plot[BesselY[0, x], {x, 0, 10}]
```



## BesselJZero

**BesselJZero**[ $n$ ,  $k$ ]  
returns the  $k$ th zero of the Bessel function of the first kind  $J_n(z)$ .

```
>> N[BesselJZero[0, 1]]  
2.40483
```

## BesselYZero

**BesselYZero**[ $n$ ,  $k$ ]  
returns the  $k$ th zero of the Bessel function of the second kind  $Y_n(z)$ .

```
>> N[BesselYZero[0, 1]]  
0.893577
```

## ChebyshevT

**ChebyshevT** $[n, x]$   
returns the Chebyshev polynomial of the first kind  $T_n(x)$ .

```
>> ChebyshevT[8, x]
1 - 32x2 + 160x4 - 256x6 + 128x8

>> ChebyshevT[1 - I, 0.5]
0.800143 + 1.08198I
```

## ChebyshevU

**ChebyshevU** $[n, x]$   
returns the Chebyshev polynomial of the second kind  $U_n(x)$ .

```
>> ChebyshevU[8, x]
1 - 40x2 + 240x4 - 448x6 + 256x8

>> ChebyshevU[1 - I, 0.5]
1.60029 + 0.721322I
```

## Erf

**Erf** $[z]$   
returns the error function of  $z$ .  
**Erf** $[z0, z1]$   
returns the result of  $\text{Erf}[z1] - \text{Erf}[z0]$ .

$\text{Erf}[x]$  is an odd function:


```
>> Erf[-x]
-Erf[x]

>> Erf[1.0]
0.842701

>> Erf[0]
0

>> {Erf[0, x], Erf[x, 0]}
{Erf[x], -Erf[x]}
```

```
>> Plot[Erf[x], {x, -2, 2}]
```



## Erfc


**Erfc** $[z]$   
returns the complementary error function of  $z$ .

```
>> Erfc[-x] / 2
(2 - Erfc[x]) / 2

>> Erfc[1.0]
0.157299

>> Erfc[0]
1

>> Plot[Erfc[x], {x, -2, 2}]
```



## ExpIntegralE

**ExpIntegralE** $[n, z]$   
returns the exponential integral function  $E_n(z)$ .

```
>> ExpIntegralE[2.0, 2.0]
0.0375343
```

## ExpIntegralEi

`ExpIntegralEi[z]`  
returns the exponential integral function  $\text{Ei}(z)$ .

```
>> ExpIntegralEi[2.0]
4.95423
```

## FresnelC

`FresnelC[z]`  
is the Fresnel C integral  $C(z)$ .

```
>> FresnelC[{0, Infinity}]
{0, 1/2}

>> Integrate[Cos[x^2 Pi/2], {x, 0,
z}]
FresnelC[z] Gamma[1/4]
-----
4 Gamma[5/4]
```

## FresnelS

`FresnelS[z]`  
is the Fresnel S integral  $S(z)$ .

```
>> FresnelS[{0, Infinity}]
{0, 1/2}

>> Integrate[Sin[x^2 Pi/2], {x, 0,
z}]
3 FresnelS[z] Gamma[3/4]
-----
4 Gamma[7/4]
```

## GegenbauerC

`GegenbauerC[n, m, x]`  
returns the Gegenbauer polynomial  $C_n^{(m)}(x)$ .

```
>> GegenbauerC[6, 1, x]
-1 + 24x^2 - 80x^4 + 64x^6

>> GegenbauerC[4 - I, 1 + 2 I, 0.7]
-3.2621 - 24.9739 I
```

## HankelH1

`HankelH1[n, z]`  
returns the Hankel function of the first kind  $H_n^{(1)}(z)$ .

```
>> HankelH1[1.5, 4]
0.185286 + 0.367112 I
```

## HankelH2

`HankelH2[n, z]`  
returns the Hankel function of the second kind  $H_n^{(2)}(z)$ .

```
>> HankelH2[1.5, 4]
0.185286 - 0.367112 I
```

## HermiteH

`HermiteH[n, x]`  
returns the Hermite polynomial  $H_n(x)$ .

```
>> HermiteH[8, x]
1 680 - 13 440x^2 + 13 ~
~ 440x^4 - 3 584x^6 + 256x^8

>> HermiteH[3, 1 + I]
-28 + 4 I


>> HermiteH[4.2, 2]
77.5291
```

## InverseErf

`InverseErf[z]`  
returns the inverse error function of  $z$ .

```
>> InverseErf /@ {-1, 0, 1}
{-∞, 0, ∞}
```

```
>> Plot[InverseErf[x], {x, -1, 1}]
```



InverseErf[z] only returns numeric values for  $-1 \leq z \leq 1$ :

```
>> InverseErf /@ {0.9, 1.0, 1.1}
{1.16309, ∞, InverseErf[1.1]}
```

## InverseErfc

InverseErfc[z]  
returns the inverse complementary error function of z.

```
>> InverseErfc /@ {0, 1, 2}
{∞, 0, -∞}
```

## JacobiP

JacobiP[n, a, b, x]  
returns the Jacobi polynomial  $P_n^{(a,b)}(x)$ .

```
>> JacobiP[1, a, b, z]
 $\frac{a}{2} - \frac{b}{2} + z \left( 1 + \frac{a}{2} + \frac{b}{2} \right)$ 

>> JacobiP[3.5 + I, 3, 2, 4 - I]
1410.02 + 5797.3I
```

## KelvinBei


KelvinBei[z]  
returns the Kelvin function bei(z).  
KelvinBei[n, z]  
returns the Kelvin function bei<sub>n</sub>(z).

```
>> KelvinBei[0.5]
0.0624932
```

```
>> KelvinBei[1.5 + I]
0.326323 + 0.755606I
```

```
>> KelvinBei[0.5, 0.25]
0.370153
```

```
>> Plot[KelvinBei[x], {x, 0, 10}]
```



## KelvinBer


KelvinBer[z]  
returns the Kelvin function ber(z).  
KelvinBer[n, z]  
returns the Kelvin function ber<sub>n</sub>(z).

```
>> KelvinBer[0.5]
0.999023
```

```
>> KelvinBer[1.5 + I]
1.1162 - 0.117944I
```

```
>> KelvinBer[0.5, 0.25]
0.148824
```

```
>> Plot[KelvinBer[x], {x, 0, 10}]
```



## KelvinKei


KelvinKei[z]  
returns the Kelvin function kei(z).  
KelvinKei[n, z]  
returns the Kelvin function kei<sub>n</sub>(z).

```
>> KelvinKei[0.5]
-0.671582

>> KelvinKei[1.5 + I]
-0.248994 + 0.303326I

>> KelvinKei[0.5, 0.25]
-2.0517

>> Plot[KelvinKei[x], {x, 0, 10}]
```



## KelvinKer


`KelvinKer[z]`  
returns the Kelvin function  $\ker(z)$ .  
`KelvinKer[n, z]`  
returns the Kelvin function  $\ker_n(z)$ .

```
>> KelvinKer[0.5]
0.855906

>> KelvinKer[1.5 + I]
-0.167162 - 0.184404I

>> KelvinKer[0.5, 0.25]
0.450023

>> Plot[KelvinKer[x], {x, 0, 10}]
```



## LaguerreL

`LaguerreL[n, x]`  
returns the Laguerre polynomial  $L_n(x)$ .  
`LaguerreL[n, a, x]`  
returns the generalised Laguerre polynomial  $L_n^a(x)$ .

```
>> LaguerreL[8, x]
1 - 8x + 14x^2 - 28x^3/3 + 35x^4/12
- 7x^5/15 + 7x^6/180 - x^7/630 + x^8/40320

>> LaguerreL[3/2, 1.7]
-0.947134

>> LaguerreL[5, 2, x]
21 - 35x + 35x^2/2 - 7x^3/2 + 7x^4/24 - x^5/120
```

## LegendreP

`LegendreP[n, x]`  
returns the Legendre polynomial  $P_n(x)$ .  
`LegendreP[n, m, x]`  
returns the associated Legendre polynomial  $P_n^m(x)$ .

```
>> LegendreP[4, x]
3/8 - 15x^2/4 + 35x^4/8


>> LegendreP[5/2, 1.5]
4.17762

>> LegendreP[1.75, 1.4, 0.53]
-1.32619

>> LegendreP[1.6, 3.1, 1.5]
-0.303998 - 1.91937I
```

`LegendreP` can be used to draw generalized Lis-sajous figures:

```
>> ParametricPlot[ {LegendreP[7, x
], LegendreP[5, x]}, {x, -1, 1}]
```



## LegendreQ

**LegendreQ[n, x]**  
returns the Legendre function of the second kind  $Q_n(x)$ .

**LegendreQ[n, m, x]**  
returns the associated Legendre function of the second kind  $Q_n^m(x)$ .

```
>> LegendreQ[5/2, 1.5]
0.036211 - 6.56219I

>> LegendreQ[1.75, 1.4, 0.53]
2.05499

>> LegendreQ[1.6, 3.1, 1.5]
-1.71931 - 7.70273I
```

## LerchPhi

**LerchPhi[z, s, a]**  
gives the Lerch transcendent  $(z, s, a)$ .

```
>> LerchPhi[2, 3, -1.5]
19.3893 - 2.1346I

>> LerchPhi[1, 2, 1/4]
17.1973
```

## ProductLog

**ProductLog[z]**  
returns the value of the Lambert W function at  $z$ .

The defining equation:

```
>> z == ProductLog[z] * E ^
ProductLog[z]
True
```


Some special values:

```
>> ProductLog[0]
0

>> ProductLog[E]
1
```

The graph of ProductLog:

```
>> Plot[ProductLog[x], {x, -1/E, E
}]
```



## SphericalHarmonicY

**SphericalHarmonicY[l, m, theta, phi]**  
returns the spherical harmonic function  $Y_l^m(\theta, \phi)$ .

```
>> SphericalHarmonicY[3/4, 0.5, Pi
/5, Pi/3]
0.254247 + 0.14679I

>> SphericalHarmonicY[3, 1, theta,
phi]

$$\frac{\sqrt{21} (1 - 5 \cos[\theta]^2) E^{I \phi} \sin[\theta]}{8 \sqrt{\pi}}$$

```


## StruveH

**StruveH[n, z]**  
returns the Struve function  $H_n(z)$ .


```
>> StruveH[1.5, 3.5]
1.13192
```



```
>> Plot[StruveH[0, x], {x, 0, 20}]
```



```
>> Plot[WeberE[1, x], {x, -10, 10}]
```




## StruveL

**StruveL[n, z]**  
returns the modified Struve function  $L_n(z)$ .

```
>> StruveL[1.5, 3.5]
4.41126
```

```
>> Plot[StruveL[0, x], {x, 0, 5}]
```



## Zeta

**Zeta[z]**  
returns the Riemann zeta function of  $z$ .

```
>> Zeta[2]
```

$$\frac{\pi^2}{6}$$

```
>> Zeta[-2.5 + I]
```

$$0.0235936 + 0.0014078I$$

## WeberE

**WeberE[n, z]**  
returns the Weber function  $E_n(z)$ .

```
>> WeberE[1.5, 3.5]
-0.397256
```

# XXXVI. Physical and Chemical data

## Contents

---

ElementData . . . . . 211

---

### ElementData

`ElementData["name", "property"]`  
gives the value of the *property* for the chemical specified by *name*.  
`ElementData[n, "property"]`  
gives the value of the *property* for the *n*th chemical element.

```
>> ElementData[74]
Tungsten

>> ElementData["He", "
AbsoluteBoilingPoint"]
4.22

>> ElementData["Carbon", "
IonizationEnergies"]
{1 086.5, 2 352.6, 4 620.5
, 6 222.7, 37 831, 47 277.}

>> ElementData[16, "
ElectronConfigurationString"]
[Ne] 3s2 3p4

>> ElementData[73, "
ElectronConfiguration"]
{{2}, {2, 6}, {2, 6, 10}, {2,
6, 10, 14}, {2, 6, 3}, {2}}
```

The number of known elements:

```
>> Length[ElementData[All]]
118
```

Some properties are not appropriate for certain elements:

```
>> ElementData["He", "
ElectroNegativity"]
Missing[NotApplicable]
```


Some data is missing:

```
>> ElementData["Tc", "SpecificHeat
"]
Missing[NotAvailable]
```

All the known properties:

```
>> ElementData["Properties"]
{Abbreviation,
AbsoluteBoilingPoint,
AbsoluteMeltingPoint,
AtomicNumber, AtomicRadius,
AtomicWeight, Block, BoilingPoint,
BrinellHardness, BulkModulus,
CovalentRadius, CrustAbundance,
Density, DiscoveryYear,
ElectroNegativity, ElectronAffinity,
ElectronConfiguration,
ElectronConfigurationString,
ElectronShellConfiguration,
FusionHeat, Group,
IonizationEnergies, LiquidDensity,
MeltingPoint, MohsHardness,
Name, Period, PoissonRatio,
Series, ShearModulus,
SpecificHeat, StandardName,
ThermalConductivity,
VanDerWaalsRadius,
VaporizationHeat,
VickersHardness, YoungModulus}
```

```
>> ListPlot[Table[ElementData[z, "AtomicWeight"], {z, 118}]]
```



# XXXVII. Calculus

## Contents

Complexes . . . . .	212	FindRoot . . . . .	214	Reals . . . . .	215
D . . . . .	213	Integers . . . . .	214	Root . . . . .	215
Derivative (') . . . . .	213	Integrate . . . . .	215	Solve . . . . .	216
DiscreteLimit . . . . .	213	Limit . . . . .	215		

## Complexes

Complexes  
is the set of complex numbers.

## D

$D[f, x]$   
gives the partial derivative of  $f$  with respect to  $x$ .  
 $D[f, x, y, \dots]$   
differentiates successively with respect to  $x, y$ , etc.  
 $D[f, \{x, n\}]$   
gives the multiple derivative of order  $n$ .  
 $D[f, \{x1, x2, \dots\}]$   
gives the vector derivative of  $f$  with respect to  $x1, x2$ , etc.

First-order derivative of a polynomial:

```
>> D[x^3 + x^2, x]
2x + 3x^2
```

Second-order derivative:

```
>> D[x^3 + x^2, {x, 2}]
2 + 6x
```

Trigonometric derivatives:

```
>> D[Sin[Cos[x]], x]
-Cos[Cos[x]] Sin[x]

>> D[Sin[x], {x, 2}]
-Sin[x]
```

```
>> D[Cos[t], {t, 2}]
-Cos[t]
```

Unknown variables are treated as constant:

```
>> D[y, x]
0
```

```
>> D[x, x]
1
```

```
>> D[x + y, x]
1
```

Derivatives of unknown functions are represented using `Derivative`:

```
>> D[f[x], x]
f'[x]
```

```
>> D[f[x, x], x]
f^(0,1)[x, x] + f^(1,0)[x, x]
```

```
>> D[f[x, x], x] // InputForm
Derivative[0, 1][f][x, x]
+ Derivative[1, 0][f][x, x]
```

Chain rule:

```
>> D[f[2x+1, 2y, x+y], x]
2f^(1,0,0)[1 + 2x, 2y,
x + y] + f^(0,0,1)[1 + 2x, 2y, x + y]
```

```
>> D[f[x^2, x, 2y], {x,2}, y] //
Expand
```

$$8x f^{(1,1,1)}[x^2, x, 2y] + 8x^2 f^{(2,0,1)}[x^2, x, 2y] + 2f^{(0,2,1)}[x^2, x, 2y] + 4f^{(1,0,1)}[x^2, x, 2y]$$

Compute the gradient vector of a function:

```
>> D[x ^ 3 * Cos[y], {{x, y}}]
{3x^2 Cos[y], -x^3 Sin[y]}
```

Hesse matrix:

```
>> D[Sin[x] * Cos[y], {{x,y}, 2}]
{{{-Cos[y] Sin[x], -Cos[x] Sin[y]}, {-Cos[x] Sin[y], -Cos[y] Sin[x]}}
```

## Derivative (')

`Derivative[n][f]`  
represents the  $n$ th derivative of the function  $f$ .  
`Derivative[n1, n2, ...][f]`  
represents a multivariate derivative.

```
>> Derivative[1][Sin]
Cos[#1]&
```

```
>> Derivative[3][Sin]
-Cos[#1]&
```

```
>> Derivative[2][# ^ 3&]
6#1&
```

Derivative can be entered using ':

```
>> Sin'[x]
Cos[x]
```

```
>> (# ^ 4&)'
12#1^2&
```

```
>> f'[x] // InputForm
Derivative[1][f][x]
```

```
>> Derivative[1][#2 Sin[#1]+Cos
[#2]&]
Cos[#1]#2&
```

```
>> Derivative[1,2][#2^3 Sin[#1]+Cos
[#2]&]
6Cos[#1]#2&
```

Deriving with respect to an unknown parameter yields 0:

```
>> Derivative[1,2,1][#2^3 Sin[#1]+
Cos[#2]&]
0&
```

The 0th derivative of any expression is the expression itself:

```
>> Derivative[0,0,0][a+b+c]
a + b + c
```

You can calculate the derivative of custom functions:

```
>> f[x_] := x ^ 2
>> f'[x]
2x
```

Unknown derivatives:

```
>> Derivative[2, 1][h]
h^(2,1)
>> Derivative[2, 0, 1, 0][h[g]]
h[g]^(2,0,1,0)
```

## DiscreteLimit

`DiscreteLimit[f, k->Infinity]`  
gives the limit of the sequence  $f$  as  $k$  tends to infinity.

```
>> DiscreteLimit[n/(n + 1), n ->
Infinity]
1
```

```
>> DiscreteLimit[f[n], n ->
Infinity]
f[∞]
```

## FindRoot

```
FindRoot[f, {x, x0}]
  searches for a numerical root of  $f$ , starting
  from  $x=x0$ .
FindRoot[lhs == rhs, {x, x0}]
  tries to solve the equation  $lhs == rhs$ .
```

FindRoot uses Newton's method, so the function of interest should have a first derivative.

```
>> FindRoot[Cos[x], {x, 1}]
{x -> 1.5708}

>> FindRoot[Sin[x] + Exp[x], {x, 0}]
{x -> -0.588533}

>> FindRoot[Sin[x] + Exp[x] == Pi, {
x, 0}]
{x -> 0.866815}
```

FindRoot has attribute HoldAll and effectively uses Block to localize  $x$ . However, in the result  $x$  will eventually still be replaced by its value.

```
>> x = 3;

>> FindRoot[Tan[x] + Sin[x] == Pi,
{x, 1}]
{3 -> 1.14911}

>> Clear[x]
```

FindRoot stops after 100 iterations:

```
>> FindRoot[x^2 + x + 1, {x, 1}]
The maximum number of iterations was exceeded. The result might be inaccurate.
{x -> -1.}
```

Find complex roots:

```
>> FindRoot[x ^ 2 + x + 1, {x, -I}]
{x -> -0.5 - 0.866025I}
```

The function has to return numerical values:

```
>> FindRoot[f[x] == 0, {x, 0}]
The function value is not a number at x = 0..
FindRoot[f[x] - 0, {x, 0}]
```

The derivative must not be 0:

```
>> FindRoot[Sin[x] == x, {x, 0}]
Encountered a singular derivative at the point x = 0..
FindRoot[Sin[x] - x, {x, 0}]
```

## Integers

```
Integers
  is the set of integer numbers.
```

Limit a solution to integer numbers:

```
>> Solve[-4 - 4 x + x^4 + x^5 == 0,
x, Integers]
{{x -> -1}}

>> Solve[x^4 == 4, x, Integers]
{}
```

## Integrate

```
Integrate[f, x]
  integrates  $f$  with respect to  $x$ . The result
  does not contain the additive integration
  constant.
Integrate[f, {x, a, b}]
  computes the definite integral of  $f$  with
  respect to  $x$  from  $a$  to  $b$ .
```

Integrate a polynomial:

```
>> Integrate[6 x ^ 2 + 3 x ^ 2 - 4
x + 10, x]
10x - 2x^2 + 3x^3
```

Integrate trigonometric functions:

```
>> Integrate[Sin[x] ^ 5, x]
-Cos[x] -  $\frac{\cos[x]^5}{5} + \frac{2\cos[x]^3}{3}$ 
```

Definite integrals:

```
>> Integrate[x ^ 2 + x, {x, 1, 3}]
 $\frac{38}{3}$ 

>> Integrate[Sin[x], {x, 0, Pi/2}]
1
```

Some other integrals:

```
>> Integrate[1 / (1 - 4 x + x^2), x]

$$-\frac{\sqrt{3}\text{Log}\left[-2+\sqrt{3}+x\right]}{6} + \frac{\sqrt{3}\text{Log}\left[-2-\sqrt{3}+x\right]}{6}$$

```

```
>> Integrate[4 Sin[x] Cos[x], x]
2Sin[x]^2
```

Integration in TeX:

```
>> Integrate[f[x], {x, a, b}] //
TeXForm
\int_a^b f(x) dx
```

Sometimes there is a loss of precision during integration. You can check the precision of your result with the following sequence of commands.

```
>> Integrate[Abs[Sin[phi]], {phi,
0, 2Pi}] // N
4.

>> % // Precision
MachinePrecision

>> Integrate[ArcSin[x / 3], x]
x ArcSin[ $\frac{x}{3}$ ] +  $\sqrt{9 - x^2}$ 

>> Integrate[f'[x], {x, a, b}]
f[b] - f[a]
```

## Limit

`Limit[expr, x->x0]`  
gives the limit of *expr* as *x* approaches *x0*.  
`Limit[expr, x->x0, Direction->1]`  
approaches *x0* from smaller values.  
`Limit[expr, x->x0, Direction->-1]`  
approaches *x0* from larger values.

```
>> Limit[x, x->2]
2

>> Limit[Sin[x] / x, x->0]
1

>> Limit[1/x, x->0, Direction->-1]
 $\infty$ 

>> Limit[1/x, x->0, Direction->1]
 $-\infty$ 
```

## Reals

`Reals`  
is the set of real numbers.

Limit a solution to real numbers:

```
>> Solve[x^3 == 1, x, Reals]
{{x -> 1}}
```

## Root

`Root[f, i]`  
represents the *i*-th complex root of the polynomial *f*

```
>> Root[#1 ^ 2 - 1 &, 1]
-1

>> Root[#1 ^ 2 - 1 &, 2]
1
```

Roots that can't be represented by radicals:

```
>> Root[#1 ^ 5 + 2 #1 + 1 &, 2]
Root[#1^5 + 2#1 + 1 &, 2]
```

## Solve

`Solve[equation, vars]`  
attempts to solve *equation* for the variables *vars*.  
`Solve[equation, vars, domain]`  
restricts variables to *domain*, which can be Complexes or Reals or Integers.

```
>> Solve[x ^ 2 - 3 x == 4, x]
{{x -> -1}, {x -> 4}}

>> Solve[4 y - 8 == 0, y]
{{y -> 2}}
```

Apply the solution:

```
>> sol = Solve[2 x^2 - 10 x - 12 ==
0, x]
{{x -> -1}, {x -> 6}}

>> x /. sol
{-1, 6}
```

Contradiction:

```
>> Solve[x + 1 == x, x]
{}
```

Tautology:

```
>> Solve[x ^ 2 == x ^ 2, x]
{{}}
```

Rational equations:

```
>> Solve[x / (x ^ 2 + 1) == 1, x]
{{x -> 1/2 - I/2 Sqrt[3]},
 {x -> 1/2 + I/2 Sqrt[3]}}

>> Solve[(x^2 + 3 x + 2)/(4 x - 2)
 == 0, x]
{{x -> -2}, {x -> -1}}
```

Transcendental equations:

```
>> Solve[Cos[x] == 0, x]
{{x -> Pi/2}, {x -> 3Pi/2}}
```

Solve can only solve equations with respect to symbols or functions:

```
>> Solve[f[x + y] == 3, f[x + y]]
{{f[x + y] -> 3}}

>> Solve[a + b == 2, a + b]
a + b is not a valid variable.
Solve[a + b == 2, a + b]
```

This happens when solving with respect to an assigned symbol:

```
>> x = 3;

>> Solve[x == 2, x]
3 is not a valid variable.
Solve[False, 3]

>> Clear[x]

>> Solve[a < b, a]
a < b is not a well-formed equation.
Solve[a < b, a]
```

Solve a system of equations:

```
>> eqs = {3 x ^ 2 - 3 y == 0, 3 y ^
 2 - 3 x == 0};
```

```
>> sol = Solve[eqs, {x, y}] //
Simplify
```

$$\left\{ \left\{ x -> 0, y -> 0 \right\}, \left\{ x -> 1, y -> 1 \right\}, \left\{ x -> -\frac{1}{2} + \frac{I}{2}\sqrt{3}, y -> -\frac{1}{2} - \frac{I}{2}\sqrt{3} \right\}, \left\{ x -> \frac{(1 - I\sqrt{3})^2}{4}, y -> -\frac{1}{2} + \frac{I}{2}\sqrt{3} \right\} \right\}$$

```
>> eqs /. sol // Simplify
{{True, True}, {True, True},
 {False, False}, {True, True}}
```

An underdetermined system:

```
>> Solve[x^2 == 1 && z^2 == -1, {x,
 y, z}]
```

*Equations may not give solutions for all "solve" variables.*

```
{{x -> -1, z -> -I},
 {x -> -1, z -> I}, {x -> 1,
 z -> -I}, {x -> 1, z -> I}}
```

Domain specification:

```
>> Solve[x^2 == -1, x, Reals]
{}

>> Solve[x^2 == 1, x, Reals]
{{x -> -1}, {x -> 1}}

>> Solve[x^2 == -1, x, Complexes]
{{x -> -I}, {x -> I}}

>> Solve[4 - 4 * x^2 - x^4 + x^6 ==
 0, x, Integers]
{{x -> -1}, {x -> 1}}
```



# XXXVIII. Integer Functions

## Contents

---

BitLength . . . . .	217	Floor . . . . .	218	IntegerLength . . . . .	219
Ceiling . . . . .	217	FromDigits . . . . .	218	IntegerReverse . . . . .	219
DigitCount . . . . .	217	IntegerDigits . . . . .	218	IntegerString . . . . .	219

---

## BitLength

**BitLength** $[x]$   
gives the number of bits needed to represent the integer  $x$ .  $x$ 's sign is ignored.

```
>> BitLength[1023]
10
>> BitLength[100]
7
>> BitLength[-5]
3
>> BitLength[0]
0
```

## Ceiling

**Ceiling** $[x]$   
gives the first integer greater than  $x$ .

```
>> Ceiling[1.2]
2
>> Ceiling[3/2]
2
```

For complex  $x$ , take the ceiling of real and imaginary parts.

```
>> Ceiling[1.3 + 0.7 I]
2 + I
```

## DigitCount

**DigitCount** $[n, b, d]$   
returns the number of times digit  $d$  occurs in the base  $b$  representation of  $n$ .

**DigitCount** $[n, b]$   
returns a list indicating the number of times each digit occurs in the base  $b$  representation of  $n$ .

**DigitCount** $[n]$   
returns a list indicating the number of times each digit occurs in the decimal representation of  $n$ .

```
>> DigitCount[1022]
{1, 2, 0, 0, 0, 0, 0, 0, 1}
>> DigitCount[Floor[Pi * 10^100]]
{8, 12, 12, 10, 8, 9, 8, 12, 14, 8}
>> DigitCount[1022, 2]
{9, 1}
>> DigitCount[1022, 2, 1]
9
```

## Floor

**Floor** $[x]$   
gives the smallest integer less than or equal to  $x$ .

**Floor** $[x, a]$   
gives the smallest multiple of  $a$  less than or equal to  $x$ .

```
>> Floor[10.4]
10
>> Floor[10/3]
3
>> Floor[10]
10
>> Floor[21, 2]
20
>> Floor[2.6, 0.5]
2.5
>> Floor[-10.4]
-11
```

For complex  $x$ , take the floor of real and imaginary parts.

```
>> Floor[1.5 + 2.7 I]
1 + 2I
```

For negative  $a$ , the smallest multiple of  $a$  greater than or equal to  $x$  is returned.

```
>> Floor[10.4, -1]
11
>> Floor[-10.4, -1]
-10
```

## FromDigits

**FromDigits[ $l$ ]**  
returns the integer corresponding to the decimal representation given by  $l$ .  $l$  can be a list of digits or a string.

**FromDigits[ $l, b$ ]**  
returns the integer corresponding to the base  $b$  representation given by  $l$ .  $l$  can be a list of digits or a string.

```
>> FromDigits["123"]
123
>> FromDigits[{1, 2, 3}]
123
>> FromDigits[{1, 0, 1}, 1000]
1 000 001
```

FromDigits can handle symbolic input:

```
>> FromDigits[{a, b, c}, 5]
c + 5 (5a + b)
```

Note that FromDigits does not automatically detect if you are providing a non-decimal representation:

```
>> FromDigits["a0"]
100
>> FromDigits["a0", 16]
160
```

FromDigits on empty lists or strings returns 0:

```
>> FromDigits[{}]
0
>> FromDigits[""]
0
```

## IntegerDigits

**IntegerDigits[ $n$ ]**  
returns the decimal representation of integer  $x$  as list of digits.  $x$ 's sign is ignored.

**IntegerDigits[ $n, b$ ]**  
returns the base  $b$  representation of integer  $x$  as list of digits.  $x$ 's sign is ignored.

**IntegerDigits[ $n, b, length$ ]**  
returns a list of length  $length$ . If the number is too short, the list gets padded with 0 on the left. If the number is too long, the  $length$  least significant digits are returned.

```
>> IntegerDigits[12345]
{1, 2, 3, 4, 5}
>> IntegerDigits[-500]
{5, 0, 0}
>> IntegerDigits[12345, 10, 8]
{0, 0, 0, 1, 2, 3, 4, 5}
>> IntegerDigits[12345, 10, 3]
{3, 4, 5}
>> IntegerDigits[11, 2]
{1, 0, 1, 1}
>> IntegerDigits[123, 8]
{1, 7, 3}
>> IntegerDigits[98765, 20]
{12, 6, 18, 5}
```

## IntegerLength

`IntegerLength[x]`  
gives the number of digits in the base-10 representation of  $x$ .  
`IntegerLength[x, b]`  
gives the number of base- $b$  digits in  $x$ .

```
>> IntegerLength[123456]
6
>> IntegerLength[10^10000]
10001
>> IntegerLength[-10^1000]
1001
```

IntegerLength with base 2:

```
>> IntegerLength[8, 2]
4
```

Check that IntegerLength is correct for the first 100 powers of 10:

```
>> IntegerLength /@ (10 ^ Range
[100]) == Range[2, 101]
True
```

The base must be greater than 1:

```
>> IntegerLength[3, -2]
Base - 2 is not an integer greater than 1.
IntegerLength[3, -2]
```

0 is a special case:

```
>> IntegerLength[0]
0
```

## IntegerReverse

`IntegerReverse[n]`  
returns the integer that has the reverse decimal representation of  $x$  without sign.  
`IntegerReverse[n, b]`  
returns the integer that has the reverse base  $b$  representation of  $x$  without sign.

```
>> IntegerReverse[1234]
4321
>> IntegerReverse[1022, 2]
511
```

```
>> IntegerReverse[-123]
321
```

## IntegerString

`IntegerString[n]`  
returns the decimal representation of integer  $x$  as string.  $x$ 's sign is ignored.  
`IntegerString[n, b]`  
returns the base  $b$  representation of integer  $x$  as string.  $x$ 's sign is ignored.  
`IntegerString[n, b, length]`  
returns a string of length *length*. If the number is too short, the string gets padded with 0 on the left. If the number is too long, the *length* least significant digits are returned.

For bases  $> 10$ , alphabetic characters a, b, ... are used to represent digits 11, 12, ... . Note that base must be an integer in the range from 2 to 36.

```
>> IntegerString[12345]
12345
>> IntegerString[-500]
500
>> IntegerString[12345, 10, 8]
00012345
>> IntegerString[12345, 10, 3]
345
>> IntegerString[11, 2]
1011
>> IntegerString[123, 8]
173
>> IntegerString[32767, 16]
7fff
>> IntegerString[98765, 20]
c6i5
```

# XXXIX. List Functions

## Contents

Accumulate . . . . .	220	Insert . . . . .	228	Quartiles . . . . .	236
All . . . . .	221	IntersectingQ . . . . .	228	Range . . . . .	236
Append . . . . .	221	Intersection . . . . .	228	RankedMax . . . . .	236
AppendTo . . . . .	221	Join . . . . .	228	RankedMin . . . . .	236
Array . . . . .	221	Key . . . . .	228	Reap . . . . .	237
Association . . . . .	222	Keys . . . . .	229	ReplacePart . . . . .	237
AssociationQ . . . . .	222	Kurtosis . . . . .	229	Rest . . . . .	237
Cases . . . . .	222	Last . . . . .	229	Reverse . . . . .	238
Catenate . . . . .	222	LeafCount . . . . .	229	Riffle . . . . .	238
CentralMoment . . . . .	222	Length . . . . .	229	RotateLeft . . . . .	238
ClusteringComponents . . . . .	222	Level . . . . .	230	RotateRight . . . . .	238
Complement . . . . .	223	LevelQ . . . . .	230	Select . . . . .	239
ConstantArray . . . . .	223	List . . . . .	230	Skewness . . . . .	239
ContainsOnly . . . . .	223	ListQ . . . . .	231	Sow . . . . .	239
Correlation . . . . .	223	Lookup . . . . .	231	Span (;) . . . . .	239
Count . . . . .	223	Mean . . . . .	231	Split . . . . .	239
Covariance . . . . .	223	Median . . . . .	231	SplitBy . . . . .	239
Delete . . . . .	224	MemberQ . . . . .	231	StandardDeviation . . . . .	240
DeleteCases . . . . .	224	Most . . . . .	231	SubsetQ . . . . .	240
DeleteDuplicates . . . . .	225	Nearest . . . . .	232	Table . . . . .	240
DisjointQ . . . . .	225	None . . . . .	232	Take . . . . .	241
Drop . . . . .	225	NotListQ . . . . .	232	TakeLargest . . . . .	241
Extract . . . . .	225	PadLeft . . . . .	232	TakeLargestBy . . . . .	241
Failure . . . . .	225	PadRight . . . . .	233	TakeSmallest . . . . .	241
FindClusters . . . . .	226	Part . . . . .	234	TakeSmallestBy . . . . .	241
First . . . . .	226	Partition . . . . .	234	Tally . . . . .	242
FirstCase . . . . .	226	Permutations . . . . .	234	Total . . . . .	242
FirstPosition . . . . .	227	Pick . . . . .	235	Tuples . . . . .	242
Fold . . . . .	227	Position . . . . .	235	Union . . . . .	243
FoldList . . . . .	227	Prepend . . . . .	235	UnitVector . . . . .	243
Gather . . . . .	227	PrependTo . . . . .	235	Values . . . . .	243
GatherBy . . . . .	228	Quantile . . . . .	236	Variance . . . . .	243

## Accumulate

```
>> Accumulate[{1, 2, 3}]
{1,3,6}
```

`Accumulate`[*list*]  
accumulates the values of *list*, returning a new list.

## All

All  
is a possible value for Span and Quiet.

## Append

Append[*expr*, *elem*]  
returns *expr* with *elem* appended.

```
>> Append[{1, 2, 3}, 4]
{1, 2, 3, 4}
```

Append works on expressions with heads other than List:

```
>> Append[f[a, b], c]
f[a, b, c]
```

Unlike Join, Append does not flatten lists in *item*:

```
>> Append[{a, b}, {c, d}]
{a, b, {c, d}}
```

## AppendTo

AppendTo[*s*, *item*]  
append *item* to value of *s* and sets *s* to the result.

```
>> s = {};
>> AppendTo[s, 1]
{1}
>> s
{1}
```

Append works on expressions with heads other than List:

```
>> y = f[];
>> AppendTo[y, x]
f[x]
>> y
f[x]
```

## Array

Array[*f*, *n*]  
returns the *n*-element list {*f*[1], ..., *f*[*n*]}.  
Array[*f*, *n*, *a*]  
returns the *n*-element list {*f*[*a*], ..., *f*[*a* + *n*]}.  
Array[*f*, {*n*, *m*}, {*a*, *b*}]  
returns an *n*-by-*m* matrix created by applying *f* to indices ranging from (*a*, *b*) to (*a* + *n*, *b* + *m*).  
Array[*f*, *dims*, *origins*, *h*]  
returns an expression with the specified dimensions and index origins, with head *h* (instead of List).

```
>> Array[f, 4]
{f[1], f[2], f[3], f[4]}
>> Array[f, {2, 3}]
{{f[1, 1], f[1, 2], f[1, 3]},
 {f[2, 1], f[2, 2], f[2, 3]}}
>> Array[f, {2, 3}, 3]
{{f[3, 3], f[3, 4], f[3, 5]},
 {f[4, 3], f[4, 4], f[4, 5]}}
>> Array[f, {2, 3}, {4, 6}]
{{f[4, 6], f[4, 7], f[4, 8]},
 {f[5, 6], f[5, 7], f[5, 8]}}
>> Array[f, {2, 3}, 1, Plus]
f[1, 1] + f[1, 2] + f[1, 3] + f[2, 1] + f[2, 2] + f[2, 3]
```

## Association

Association[*key1* -> *val1*, *key2* -> *val2*, ...]  
<|*key1* -> *val1*, *key2* -> *val2*, ...|>  
represents an association between keys and values.

Association is the head of associations:

```
>> Head[<|a -> x, b -> y, c -> z|>]
Association
>> <|a -> x, b -> y|>
<|a -> x, b -> y|>
```

```
>> Association[{a -> x, b -> y}]
<|a -> x, b -> y|>
```

Associations can be nested:

```
>> <|a -> x, b -> y, <|a -> z, d ->
t|>|>
<|a -> z, b -> y, d -> t|>
```

## AssociationQ

**AssociationQ**[*expr*]  
return True if *expr* is a valid Association object, and False otherwise.

```
>> AssociationQ[<|a -> 1, b -> 2|>]
True
>> AssociationQ[<|a, b|>]
False
```

## Cases

**Cases**[*list*, *pattern*]  
returns the elements of *list* that match *pattern*.  
**Cases**[*list*, *pattern*, *ls*]  
returns the elements matching at level-spec *ls*.

```
>> Cases[{a, 1, 2.5, "string"},
_Integer|_Real]
{1, 2.5}
>> Cases[_Complex] [{1, 2I, 3, 4-I,
5}]
{2I, 4 - I}
```

## Catenate

**Catenate**[{*l1*, *l2*, ...}]  
concatenates the lists *l1*, *l2*, ...

```
>> Catenate[{ {1, 2, 3}, {4, 5} }]
{1, 2, 3, 4, 5}
```

## CentralMoment

**CentralMoment**[*list*, *r*]  
gives the the *r*th central moment (i.e. the *r*th moment about the mean) of *list*.

```
>> CentralMoment[{1.1, 1.2, 1.4,
2.1, 2.4}, 4]
0.100845
```

## ClusteringComponents

**ClusteringComponents**[*list*]  
forms clusters from *list* and returns a list of cluster indices, in which each element shows the index of the cluster in which the corresponding element in *list* ended up.

**ClusteringComponents**[*list*, *k*]  
forms *k* clusters from *list* and returns a list of cluster indices, in which each element shows the index of the cluster in which the corresponding element in *list* ended up.

For more detailed documentation regarding options and behavior, see **FindClusters**[].

```
>> ClusteringComponents[{1, 2, 3,
1, 2, 10, 100}]
{1, 1, 1, 1, 1, 1, 2}
>> ClusteringComponents[{10, 100,
20}, Method -> "KMeans"]
{1, 0, 1}
```

## Complement

**Complement**[*all*, *e1*, *e2*, ...]  
returns an expression containing the elements in the set *all* that are not in any of *e1*, *e2*, etc.

**Complement**[*all*, *e1*, *e2*, ..., *SameTest* -> *test*]  
applies *test* to the elements in *all* and each of the *ei* to determine equality.

The sets *all*, *e1*, etc can have any head, which must all match. The returned expression has the

same head as the input expressions. The expression will be sorted and each element will only occur once.

```
>> Complement[{a, b, c}, {a, c}]
      {b}

>> Complement[{a, b, c}, {a, c}, {b}]
      {}

>> Complement[f[z, y, x, w], f[x],
      f[x, z]]
      f[w, y]

>> Complement[{c, b, a}]
      {a, b, c}
```

## ConstantArray

`ConstantArray[expr, n]`  
returns a list of  $n$  copies of *expr*.

```
>> ConstantArray[a, 3]
      {a, a, a}

>> ConstantArray[a, {2, 3}]
      {{a, a, a}, {a, a, a}}
```

## ContainsOnly

`ContainsOnly[list1, list2]`  
yields True if *list1* contains only elements that appear in *list2*.

```
>> ContainsOnly[{b, a, a}, {a, b, c}]
      True
```

The first list contains elements not present in the second list:

```
>> ContainsOnly[{b, a, d}, {a, b, c}]
      False

>> ContainsOnly[{}, {a, b, c}]
      True
```

Use `Equal` as the comparison function to have numerical tolerance:

```
>> ContainsOnly[{a, 1.0}, {1, a, b}, {SameTest -> Equal}]
      True
```

## Correlation

`Correlation[a, b]`  
computes Pearson's correlation of two equal-sized vectors *a* and *b*.

An example from Wikipedia:

```
>> Correlation[{10, 8, 13, 9, 11,
      14, 6, 4, 12, 7, 5}, {8.04,
      6.95, 7.58, 8.81, 8.33, 9.96,
      7.24, 4.26, 10.84, 4.82, 5.68}]
      0.816421
```

## Count

`Count[list, pattern]`  
returns the number of times *pattern* appears in *list*.  
`Count[list, pattern, ls]`  
counts the elements matching at level-spec *ls*.

```
>> Count[{3, 7, 10, 7, 5, 3, 7,
      10}, 3]
      2

>> Count[{{a, a}, {a, a, a}, a}, a, {2}]
      5
```

## Covariance

`Covariance[a, b]`  
computes the covariance between the equal-sized vectors *a* and *b*.

```
>> Covariance[{0.2, 0.3, 0.1},
      {0.3, 0.3, -0.2}]
      0.025
```

## Delete

```
Delete[expr, i]
  deletes the element at position i in expr.
  The position is counted from the end if i
  is negative.
Delete[expr, {m, n, ...}]
  deletes the element at position {m, n, ...}.
Delete[expr, {{m1, n1, ...}, {m2,
n2, ...}, ...}]
  deletes the elements at several positions.
```

Delete the element at position 3:

```
>> Delete[{a, b, c, d}, 3]
{a, b, d}
```

Delete at position 2 from the end:

```
>> Delete[{a, b, c, d}, -2]
{a, b, d}
```

Delete at positions 1 and 3:

```
>> Delete[{a, b, c, d}, {{1}, {3}}]
{b, d}
```

Delete in a 2D array:

```
>> Delete[{{a, b}, {c, d}}, {2, 1}]
{{a, b}, {d}}
```

Deleting the head of a whole expression gives a Sequence object:

```
>> Delete[{a, b, c}, 0]
Sequence[a, b, c]
```

Delete in an expression with any head:

```
>> Delete[f[a, b, c, d], 3]
f[a, b, d]
```

Delete a head to splice in its arguments:

```
>> Delete[f[a, b, u + v, c], {3, 0}]
f[a, b, u, v, c]
```

```
>> Delete[{a, b, c}, 0]
Sequence[a, b, c]
```

Delete without the position:

```
>> Delete[{a, b, c, d}]
Delete[{a, b, c, d}]
Delete[{a, b, c, d}]
```

*Delete called with 1 argument; 2 arguments are expected.*

Delete with many arguments:

```
>> Delete[{a, b, c, d}, 1, 2]
Delete called with 3 arguments; 2 arguments are expected.
Delete[{a, b, c, d}, 1, 2]
```

Delete the element out of range:

```
>> Delete[{a, b, c, d}, 5]
Part{5} of {a, b, c, d} does not exist.
Delete[{a, b, c, d}, 5]
```

Delete the position not integer:

```
>> Delete[{a, b, c, d}, {1, n}]
Position specification {a, b, c, d} is not a machine
– sized integer or a list of machine
– sized integers.
Delete[{a, b, c, d}, {1, n}]
```

## DeleteCases

```
DeleteCases[list, pattern]
  returns the elements of list that do not
  match pattern.
DeleteCases[list, pattern, levelspec]
  removes all parts of $list on levels spec-
  ified by levelspec that match pattern (not
  fully implemented).
DeleteCases[list, pattern, levelspec, n]
  removes the first n parts of list that match
  pattern.
```

```
>> DeleteCases[{a, 1, 2.5, "string"}, _Integer | _Real]
{a, string}
```

```
>> DeleteCases[{a, b, 1, c, 2, 3}, _Symbol]
{1, 2, 3}
```



## DeleteDuplicates

`DeleteDuplicates[list]`  
deletes duplicates from *list*.  
`DeleteDuplicates[list, test]`  
deletes elements from *list* based on whether the function *test* yields True on pairs of elements. `DeleteDuplicates` does not change the order of the remaining elements.

```
>> DeleteDuplicates[{1, 7, 8, 4, 3,
  4, 1, 9, 9, 2, 1}]
{1,7,8,4,3,9,2}

>> DeleteDuplicates[{3,2,1,2,3,4},
  Less]
{3,2,1}
```

## DisjointQ

`DisjointQ[a, b]`  
gives True if \$a and \$b are disjoint, or False if \$a and \$b have any common elements.

## Drop

`Drop[expr, n]`  
returns *expr* with the first *n* leaves removed.

```
>> Drop[{a, b, c, d}, 3]
{d}

>> Drop[{a, b, c, d}, -2]
{a,b}

>> Drop[{a, b, c, d, e}, {2, -2}]
{a,e}
```

Drop a submatrix:

```
>> A = Table[i*10 + j, {i, 4}, {j,
  4}]
{{11,12,13,14}, {21,22,23,24},
 {31,32,33,34}, {41,42,43,44}}
```

```
>> Drop[A, {2, 3}, {2, 3}]
{{11,14}, {41,44}}
```

## Extract

`Extract[expr, list]`  
extracts parts of *expr* specified by *list*.  
`Extract[expr, {list1, list2, ...}]`  
extracts a list of parts.

`Extract[expr, i, j, ...]` is equivalent to `Part[expr, {i, j, ...}]`.

```
>> Extract[a + b + c, {2}]
b

>> Extract[{{a, b}, {c, d}}, {{1},
  {2, 2}}]
{{a,b},d}
```

## Failure

`Failure[tag, assoc]`  
represents a failure of a type indicated by *tag*, with details given by the association *assoc*.

## FindClusters

`FindClusters[list]`  
returns a list of clusters formed from the elements of *list*. The number of cluster is determined automatically.  
`FindClusters[list, k]`  
returns a list of *k* clusters formed from the elements of *list*.

```
>> FindClusters[{1, 2, 20, 10, 11,
  40, 19, 42}]
{{1,2,20,10,11,19}, {40,42}}

>> FindClusters[{25, 100, 17, 20}]
{{25,17,20}, {100}}

>> FindClusters[{3, 6, 1, 100, 20,
  5, 25, 17, -10, 2}]
{{3,6,1,5,-10,2},
 {100}, {20,25,17}}
```

```

>> FindClusters[{1, 2, 10, 11, 20,
21}]
{{1,2}, {10,11}, {20,21}}

>> FindClusters[{1, 2, 10, 11, 20,
21}, 2]
{{1,2,10,11}, {20,21}}

>> FindClusters[{1 -> a, 2 -> b, 10
-> c}]
{{a,b}, {c}}

>> FindClusters[{1, 2, 5} -> {a, b,
c}]
{{a,b}, {c}}

>> FindClusters[{1, 2, 3, 1, 2, 10,
100}, Method -> "Agglomerate"]
{{1,2,3,1,2,10}, {100}}

>> FindClusters[{1, 2, 3, 10, 17,
18}, Method -> "Agglomerate"]
{{1,2,3}, {10}, {17,18}}

>> FindClusters[{{1}, {5, 6}, {7},
{2, 4}}, DistanceFunction -> (
Abs[Length[#1] - Length[#2]]&)]
{{{1}, {7}}, {{5,6}, {2,4}}}

>> FindClusters[{"meep", "heap", "
deep", "weep", "sheep", "leap",
"keep"}, 3]
{{meep,deep,weep,keep},
{heap,leap}, {sheep}}

```

FindClusters' automatic distance function detection supports scalars, numeric tensors, boolean vectors and strings.

The Method option must be either "Agglomerate" or "Optimize". If not specified, it defaults to "Optimize". Note that the Agglomerate and Optimize methods usually produce different clusterings.

The runtime of the Agglomerate method is quadratic in the number of clustered points  $n$ , builds the clustering from the bottom up, and is exact (no element of randomness). The Optimize method's runtime is linear in  $n$ , Optimize builds the clustering from top down, and uses random sampling.

## First

`First[expr]`  
returns the first element in *expr*.

`First[expr]` is equivalent to `expr[[1]]`.

```

>> First[{a, b, c}]
a

>> First[a + b + c]
a

>> First[x]
Nonatomicexpressionexpected.
First[x]

```

## FirstCase

`FirstCase[{e1, e2, $ldots$}, pattern]`  
gives the first *ei* to match *pattern*, or `$Missing["NotFound"]` if none matching pattern is found.

`FirstCase[{e1, e2, $ldots$}, pattern -> rhs]`  
gives the value of *rhs* corresponding to the first *ei* to match pattern.

`FirstCase[expr, pattern, default]`  
gives *default* if no element matching *pattern* is found.

`FirstCase[expr, pattern, default, levelspec]`  
finds only objects that appear on levels specified by *levelspec*.

`FirstCase[pattern]`  
represents an operator form of FirstCase that can be applied to an expression.

## FirstPosition

`FirstPosition[expr, pattern]`  
gives the position of the first element in *expr* that matches *pattern*, or `Missing["NotFound"]` if no such element is found.

`FirstPosition[expr, pattern, default]`  
gives default if no element matching *pattern* is found.

`FirstPosition[expr, pattern, default, levelspec]`  
finds only objects that appear on levels specified by *levelspec*.

```
>> FirstPosition[{a, b, a, a, b, c, b}, b]
{2}
```

```
>> FirstPosition[{{a, a, b}, {b, a, a}, {a, b, a}}, b]
{1, 3}
```

```
>> FirstPosition[{x, y, z}, b]
Missing[NotFound]
```

Find the first position at which  $x^2$  to appears:

```
>> FirstPosition[{1 + x^2, 5, x^4, a + (1 + x^2)^2}, x^2]
{1, 2}
```

## Fold

`Fold[f, x, list]`  
returns the result of iteratively applying the binary operator *f* to each element of *list*, starting with *x*.

`Fold[f, list]`  
is equivalent to `Fold[f, First[list], Rest[list]]`.

```
>> Fold[Plus, 5, {1, 1, 1}]
8
```

```
>> Fold[f, 5, {1, 2, 3}]
f[f[f[5, 1], 2], 3]
```

## FoldList

`FoldList[f, x, list]`  
returns a list starting with *x*, where each element is the result of applying the binary operator *f* to the previous result and the next element of *list*.

`FoldList[f, list]`  
is equivalent to `FoldList[f, First[list], Rest[list]]`.

```
>> FoldList[f, x, {1, 2, 3}]
{x, f[x, 1], f[f[x, 1], 2], f[f[f[x, 1], 2], 3]}
```

```
>> FoldList[Times, {1, 2, 3}]
{1, 2, 6}
```

## Gather

`Gather[list, test]`  
gathers leaves of *list* into sub lists of items that are the same according to *test*.

`Gather[list]`  
gathers leaves of *list* into sub lists of items that are the same.

The order of the items inside the sub lists is the same as in the original list.

```
>> Gather[{1, 7, 3, 7, 2, 3, 9}]
{{1}, {7, 7}, {3, 3}, {2}, {9}}
```

```
>> Gather[{1/3, 2/6, 1/9}]
{{1/3, 1/3}, {1/9}}
```

## GatherBy

`GatherBy[list, f]`  
gathers leaves of *list* into sub lists of items whose image under *f* identical.

`GatherBy[list, {f, g, ...}]`  
gathers leaves of *list* into sub lists of items whose image under *f* identical. Then, gathers these sub lists again into sub sub lists, that are identical under *g*.

```
>> GatherBy[{{1, 3}, {2, 2}, {1, 1}}, Total]
{{{1, 3}, {2, 2}}, {{1, 1}}}

>> GatherBy[{"xy", "abc", "ab"}, StringLength]
{{xy, ab}, {abc}}

>> GatherBy[{{2, 0}, {1, 5}, {1, 0}}, Last]
{{{2, 0}, {1, 0}}, {{1, 5}}}

>> GatherBy[{{1, 2}, {2, 1}, {3, 5}, {5, 1}, {2, 2, 2}}, {Total, Length}]
{{{1, 2}, {2, 1}}, {{3, 5}}, {{5, 1}}, {{2, 2, 2}}}
```

## Insert

`Insert[list, elem, n]`  
inserts *elem* at position *n* in *list*. When *n* is negative, the position is counted from the end.

```
>> Insert[{a,b,c,d,e}, x, 3]
{a,b,x,c,d,e}

>> Insert[{a,b,c,d,e}, x, -2]
{a,b,c,d,x,e}
```

## IntersectingQ

`IntersectingQ[a, b]`  
gives True if there are any common elements in *a* and *b*, or False if *a* and *b* are disjoint.

## Intersection

`Intersection[a, b, ...]`  
gives the intersection of the sets. The resulting list will be sorted and each element will only occur once.

```
>> Intersection[{1000, 100, 10, 1}, {1, 5, 10, 15}]
{1, 10}

>> Intersection[{{a, b}, {x, y}}, {{x, x}, {x, y}, {x, z}}]
{{x, y}}

>> Intersection[{c, b, a}]
{a, b, c}

>> Intersection[{1, 2, 3}, {2, 3, 4}, SameTest->Less]
{3}
```

## Join

`Join[l1, l2]`  
concatenates the lists *l1* and *l2*.

Join concatenates lists:

```
>> Join[{a, b}, {c, d, e}]
{a,b,c,d,e}

>> Join[{{a, b}, {c, d}}, {{1, 2}, {3, 4}}]
{{a,b}, {c,d}, {1,2}, {3,4}}
```

The concatenated expressions may have any head:

```
>> Join[a + b, c + d, e + f]
a + b + c + d + e + f
```

However, it must be the same for all expressions:

```
>> Join[a + b, c * d]
HeadsPlusandTimesareexpectedtobethesame.
Join[a + b, cd]
```

## Key

`Key[key]`  
represents a key used to access a value in an association.  
`Key[key][assoc]`

## Keys

```
Keys[<|key1 -> val1, key2 -> val2,
...|>]
  return a list of the keys keyi in an association.
Keys[{key1 -> val1, key2 -> val2, ...}]
  return a list of the keyi in a list of rules.
```

```
>> Keys[<|a -> x, b -> y|>]
{a, b}

>> Keys[{a -> x, b -> y}]
{a, b}
```

Keys automatically threads over lists:

```
>> Keys[{<|a -> x, b -> y|>, {w ->
z, {}}}]
{{a, b}, {w, {}}}
```

Keys are listed in the order of their appearance:

```
>> Keys[{c -> z, b -> y, a -> x}]
{c, b, a}
```

## Kurtosis

```
Kurtosis[list]
  gives the Pearson measure of kurtosis for
  list (a measure of existing outliers).
```

```
>> Kurtosis[{1.1, 1.2, 1.4, 2.1,
2.4}]
1.42098
```

## Last

```
Last[expr]
  returns the last element in expr.
```

Last[*expr*] is equivalent to *expr*[[*-1*]].

```
>> Last[{a, b, c}]
c

>> Last[x]
Nonatomicexpressionexpected.
Last[x]
```

## LeafCount

```
LeafCount[expr]
  returns the total number of indivisible
  subexpressions in expr.
```

```
>> LeafCount[1 + x + y^a]
6

>> LeafCount[f[x, y]]
3

>> LeafCount[{1 / 3, 1 + I}]
7

>> LeafCount[Sqrt[2]]
5

>> LeafCount[100!]
1
```

## Length

```
Length[expr]
  returns the number of leaves in expr.
```

Length of a list:

```
>> Length[{1, 2, 3}]
3
```

Length operates on the FullForm of expressions:

```
>> Length[Exp[x]]
2

>> FullForm[Exp[x]]
Power[E, x]
```

The length of atoms is 0:

```
>> Length[a]
0
```

Note that rational and complex numbers are atoms, although their FullForm might suggest the opposite:

```
>> Length[1/3]
0

>> FullForm[1/3]
Rational[1, 3]
```

## Level

`Level[expr, levelspec]`  
gives a list of all subexpressions of *expr* at the level(s) specified by *levelspec*.

Level uses standard level specifications:

*n*  
levels 1 through *n*  
Infinity  
all levels from level 1  
{*n*}  
level *n* only  
{*m*, *n*}  
levels *m* through *n*

Level 0 corresponds to the whole expression.  
A negative level  $-n$  consists of parts with depth *n*.

Level -1 is the set of atoms in an expression:

```
>> Level[a + b ^ 3 * f[2 x ^ 2], {-1}]
{a, b, 3, 2, x, 2}

>> Level[{{{a}}}, 3]
{{{a}}, {{a}}, {{{a}}}}

>> Level[{{{a}}}, -4]
{{{a}}}

>> Level[{{{a}}}, -5]
{}

>> Level[h0[h1[h2[h3[a]]]], {0, -1}]
{a, h3[a], h2[h3[a]], h1[h2[h3[a]]], h0[h1[h2[h3[a]]]]}
```

Use the option `Heads -> True` to include heads:

```
>> Level[{{{a}}}, 3, Heads -> True]
{List, List, List, {a}, {{a}}, {{{a}}}}

>> Level[x^2 + y^3, 3, Heads -> True]
{Plus, Power, x, 2, x^2, Power, y, 3, y^3}

>> Level[a ^ 2 + 2 * b, {-1}, Heads -> True]
{Plus, Power, a, 2, Times, 2, b}
```

```
>> Level[f[g[h]] [x], {-1}, Heads -> True]
{f, g, h, x}

>> Level[f[g[h]] [x], {-2, -1}, Heads -> True]
{f, g, h, g[h], x, f[g[h]] [x]}
```

## LevelQ

`LevelQ[expr]`  
tests whether *expr* is a valid level specification.

```
>> LevelQ[2]
True

>> LevelQ[{2, 4}]
True

>> LevelQ[Infinity]
True

>> LevelQ[a + b]
False
```

## List

`List[e1, e2, ..., ei]`  
{*e1*, *e2*, ..., *ei*}  
represents a list containing the elements *e1...ei*.

List is the head of lists:

```
>> Head[{1, 2, 3}]
List
```

Lists can be nested:

```
>> {{a, b, {c, d}}}
{{a, b, {c, d}}}
```

## ListQ

`ListQ[expr]`  
tests whether *expr* is a List.

```
>> ListQ[{1, 2, 3}]
True
```

```
>> ListQ[{{1, 2}, {3, 4}}]
True

>> ListQ[x]
False
```

## Lookup

`Lookup[assoc, key]`  
looks up the value associated with *key* in the association *assoc*, or `Missing[KeyAbsent]`.

## Mean

`Mean[list]`  
returns the statistical mean of *list*.

```
>> Mean[{26, 64, 36}]
42

>> Mean[{1, 1, 2, 3, 5, 8}]
 $\frac{10}{3}$ 

>> Mean[{a, b}]
 $\frac{a + b}{2}$ 
```

## Median

`Median[list]`  
returns the median of *list*.

```
>> Median[{26, 64, 36}]
36
```

For lists with an even number of elements, `Median` returns the mean of the two middle values:

```
>> Median[{-11, 38, 501, 1183}]
 $\frac{539}{2}$ 
```

Passing a matrix returns the medians of the respective columns:

```
>> Median[{{100, 1, 10, 50}, {-1, 1, -2, 2}}]
 $\left\{\frac{99}{2}, 1, 4, 26\right\}$ 
```

## MemberQ

`MemberQ[list, pattern]`  
returns `True` if *pattern* matches any element of *list*, or `False` otherwise.

```
>> MemberQ[{a, b, c}, b]
True

>> MemberQ[{a, b, c}, d]
False

>> MemberQ[{"a", b, f[x]}, _?
NumericQ]
False

>> MemberQ[_List][{}]]
True
```

## Most

`Most[expr]`  
returns *expr* with the last element removed.

`Most[expr]` is equivalent to `expr[[;;-2]]`.

```
>> Most[{a, b, c}]
{a, b}

>> Most[a + b + c]
a + b

>> Most[x]
Nonatomicexpressionexpected.
Most[x]
```

## Nearest

```
Nearest[list, x]
  returns the one item in list that is nearest
  to x.
Nearest[list, x, n]
  returns the n nearest items.
Nearest[list, x, {n, r}]
  returns up to n nearest items that are not
  farther from x than r.
Nearest[{p1 -> q1, p2 -> q2, ...}, x]
  returns q1, q2, ... but measures the dis-
  tances using p1, p2, ...
Nearest[{p1, p2, ...} -> {q1, q2,
...}, x]
  returns q1, q2, ... but measures the dis-
  tances using p1, p2, ...
```

```
>> Nearest[{5, 2.5, 10, 11, 15,
8.5, 14}, 12]
{11}
```

Return all items within a distance of 5:

```
>> Nearest[{5, 2.5, 10, 11, 15,
8.5, 14}, 12, {All, 5}]
{11, 10, 14}

>> Nearest[{Blue -> "blue", White
-> "white", Red -> "red", Green
-> "green"}, {Orange, Gray}]
{{red}, {white}}

>> Nearest[{{0, 1}, {1, 2}, {2, 3}}
-> {a, b, c}, {1.1, 2}]
{b}
```

## None

```
None
  is a possible value for Span and Quiet.
```

## NotListQ

```
NotListQ[expr]
  returns true if expr is not a list.
```

## PadLeft

```
PadLeft[list, n]
  pads list to length n by adding 0 on the
  left.
PadLeft[list, n, x]
  pads list to length n by adding x on the
  left.
PadLeft[list, {n1, $n2, ...}, x]
  pads list to lengths n1, n2 at levels 1, 2, ...
  respectively by adding x on the left.
PadLeft[list, n, x, m]
  pads list to length n by adding x on the
  left and adding a margin of m on the
  right.
PadLeft[list, n, x, {m1, m2, ...}]
  pads list to length n by adding x on the
  left and adding margins of m1, m2, ... on
  levels 1, 2, ... on the right.
PadLeft[list]
  turns the ragged list list into a regular list
  by adding 0 on the left.
```

```
>> PadLeft[{1, 2, 3}, 5]
{0, 0, 1, 2, 3}

>> PadLeft[x[a, b, c], 5]
x[0, 0, a, b, c]

>> PadLeft[{1, 2, 3}, 2]
{2, 3}

>> PadLeft[{{}, {1, 2}, {1, 2, 3}}]
{{0, 0, 0}, {0, 1, 2}, {1, 2, 3}}

>> PadLeft[{1, 2, 3}, 10, {a, b, c}, 2]
{b, c, a, b, c, 1, 2, 3, a, b}

>> PadLeft[{{1, 2, 3}}, {5, 2}, x, 1]
{{x, x}, {x, x}, {x,
x}, {3, x}, {x, x}}
```



## PadRight

`PadRight[list, n]`  
pads *list* to length *n* by adding 0 on the right.

`PadRight[list, n, x]`  
pads *list* to length *n* by adding *x* on the right.

`PadRight[list, {n1, $n2, ...}, x]`  
pads *list* to lengths *n1, n2* at levels 1, 2, ... respectively by adding *x* on the right.

`PadRight[list, n, x, m]`  
pads *list* to length *n* by adding *x* on the left and adding a margin of *m* on the left.

`PadRight[list, n, x, {m1, m2, ...}]`  
pads *list* to length *n* by adding *x* on the right and adding margins of *m1, m2, ...* on levels 1, 2, ... on the left.

`PadRight[list]`  
turns the ragged list *list* into a regular list by adding 0 on the right.

```
>> PadRight[{1, 2, 3}, 5]
{1,2,3,0,0}

>> PadRight[x[a, b, c], 5]
x[a,b,c,0,0]

>> PadRight[{1, 2, 3}, 2]
{1,2}

>> PadRight[{{}}, {1, 2}, {1, 2, 3}]
{{0,0,0}, {1,2,0}, {1,2,3}}

>> PadRight[{1, 2, 3}, 10, {a, b, c}, 2]
{b,c,1,2,3,a,b,c,a,b}

>> PadRight[{{1, 2, 3}}, {5, 2}, x, 1]
{{x,x}, {x,1}, {x,x}, {x,x}, {x,x}}
```

## Part

`Part[expr, i]`  
returns part *i* of *expr*.

Extract an element from a list:

```
>> A = {a, b, c, d};

>> A[[3]]
c
```

Negative indices count from the end:

```
>> {a, b, c}][[-2]]
b
```

Part can be applied on any expression, not necessarily lists.

```
>> (a + b + c)[[2]]
b
```

`expr[[0]]` gives the head of *expr*:

```
>> (a + b + c)[[0]]
Plus
```

Parts of nested lists:

```
>> M = {{a, b}, {c, d}};

>> M[[1, 2]]
b
```

You can use Span to specify a range of parts:

```
>> {1, 2, 3, 4}][[2;;4]]
{2,3,4}

>> {1, 2, 3, 4}][[2;;-1]]
{2,3,4}
```

A list of parts extracts elements at certain indices:

```
>> {a, b, c, d}][[{1, 3, 3}]]
{a,c,c}
```

Get a certain column of a matrix:

```
>> B = {{a, b, c}, {d, e, f}, {g, h, i}};

>> B[[:, 2]]
{b,e,h}
```

Extract a submatrix of 1st and 3rd row and the two last columns:

```
>> B = {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}};

>> B[{{1, 3}, -2;;-1]]
{{2,3}, {8,9}}
```

Further examples:

```
>> (a+b+c+d)[[-1;;-2]]
0
```

```
>> x[[2]]
Part specification is longer than depth of object.
x[[2]]
```

Assignments to parts are possible:

```
>> B[;;, 2] = {10, 11, 12}
{10, 11, 12}

>> B
{{1, 10, 3}, {4, 11, 6}, {7, 12, 9}}

>> B[;;, 3] = 13
13

>> B
{{1, 10, 13}, {4, 11, 13}, {7, 12, 13}}

>> B[[1;;-2]] = t;

>> B
{t, t, {7, 12, 13}}

>> F = Table[i*j*k, {i, 1, 3}, {j, 1, 3}, {k, 1, 3}];

>> F[;;, All, 2 ;; 3, 2] = t;

>> F
{{{1, 2, 3}, {2, t, 6}, {3, t, 9}},
 {{2, 4, 6}, {4, t, 12}, {6, t, 18}},
 {{3, 6, 9}, {6, t, 18}, {9, t, 27}}}}

>> F[;;, All, 1 ;; 2, 3 ;; 3] = k;

>> F
{{{1, 2, k}, {2, t, k}, {3, t, 9}},
 {{2, 4, k}, {4, t, k}, {6, t, 18}},
 {{3, 6, k}, {6, t, k}, {9, t, 27}}}}
```

Of course, part specifications have precedence over most arithmetic operations:

```
>> A[[1]] + B[[2]] + C[[3]] // Hold
// FullForm
Hold[Plus[Part[A, 1],
 Part[B, 2], Part[C, 3]]]
```

## Partition

`Partition[list, n]`  
partitions *list* into sublists of length *n*.  
`Partition[list, n, d]`  
partitions *list* into sublists of length *n* which overlap *d* indicies.

```
>> Partition[{a, b, c, d, e, f}, 2]
{{a, b}, {c, d}, {e, f}}

>> Partition[{a, b, c, d, e, f}, 3, 1]
{{a, b, c}, {b, c, d}, {c, d, e}, {d, e, f}}
```

## Permutations

`Permutations[list]`  
gives all possible orderings of the items in *list*.  
`Permutations[list, n]`  
gives permutations up to length *n*.  
`Permutations[list, {n}]`  
gives permutations of length *n*.

```
>> Permutations[{y, 1, x}]
{{y, 1, x}, {y, x, 1}, {1, y, x},
 {1, x, y}, {x, y, 1}, {x, 1, y}}
```

Elements are differentiated by their position in *list*, not their value.

```
>> Permutations[{a, b, b}]
{{a, b, b}, {a, b, b}, {b, a, b},
 {b, b, a}, {b, a, b}, {b, b, a}}

>> Permutations[{1, 2, 3}, 2]
{{}, {1}, {2}, {3}, {1, 2}, {1, 3}, {2, 1}, {2, 3}, {3, 1}, {3, 2}}

>> Permutations[{1, 2, 3}, {2}]
{{1, 2}, {1, 3}, {2, 1},
 {2, 3}, {3, 1}, {3, 2}}
```

## Pick

```
Pick[list, sel]
  returns those items in list that are True in
  sel.
Pick[list, sel, patt]
  returns those items in list that match patt
  in sel.
```

```
>> Pick[{a, b, c}, {False, True,
False}]
{b}

>> Pick[f[g[1, 2], h[3, 4]], {{True
, False}, {False, True}}]
f[g[1], h[4]]

>> Pick[{a, b, c, d, e}, {1, 2,
3.5, 4, 5.5}, _Integer]
{a, b, d}
```

## Position

```
Position[expr, patt]
  returns the list of positions for which expr
  matches patt.
Position[expr, patt, ls]
  returns the positions on levels specified
  by levelspec ls.
```

```
>> Position[{1, 2, 2, 1, 2, 3, 2},
2]
{{2}, {3}, {5}, {7}}
```

Find positions upto 3 levels deep

```
>> Position[{1 + Sin[x], x, (Tan[x]
- y)^2}, x, 3]
{{1, 2, 1}, {2}}
```

Find all powers of x

```
>> Position[{1 + x^2, x y ^ 2, 4 y,
x ^ z}, x^_]
{{1, 2}, {4}}
```

Use Position as an operator

```
>> Position[_Integer][{1.5, 2,
2.5}]
{{2}}
```

## Prepend

```
Prepend[expr, item]
  returns expr with item prepended to its
  leaves.
```

Prepend is similar to Append, but adds *item* to the beginning of *expr*:

```
>> Prepend[{2, 3, 4}, 1]
{1, 2, 3, 4}
```

Prepend works on expressions with heads other than List:

```
>> Prepend[f[b, c], a]
f[a, b, c]
```

Unlike Join, Prepend does not flatten lists in *item*:

```
>> Prepend[{c, d}, {a, b}]
{{a, b}, c, d}
```

## PrependTo

```
PrependTo[s, item]
  prepends item to value of s and sets s to
  the result.
```

Assign *s* to a list

```
>> s = {1, 2, 4, 9}
{1, 2, 4, 9}
```

Add a new value at the beginning of the list:

```
>> PrependTo[s, 0]
{0, 1, 2, 4, 9}
```

The value assigned to *s* has changed:

```
>> s
{0, 1, 2, 4, 9}
```

PrependTo works with a head other than List:

```
>> y = f[a, b, c];
```

```
>> PrependTo[y, x]
f[x, a, b, c]
```

```
>> y
f[x, a, b, c]
```

## Quantile

`Quantile[list, q]`  
returns the  $q$ th quantile of *list*.

```
>> Quantile[Range[11], 1/3]
4
>> Quantile[Range[16], 1/4]
5
```

## Quartiles

`Quartiles[list]`  
returns the 1/4, 1/2, and 3/4 quantiles of *list*.

```
>> Quartiles[Range[25]]
{ 27/4, 13, 77/4 }
```

## Range

`Range[n]`  
returns a list of integers from 1 to  $n$ .  
`Range[a, b]`  
returns a list of integers from  $a$  to  $b$ .

```
>> Range[5]
{1, 2, 3, 4, 5}
>> Range[-3, 2]
{-3, -2, -1, 0, 1, 2}
>> Range[0, 2, 1/3]
{0, 1/3, 2/3, 1, 4/3, 5/3, 2}
```

## RankedMax

`RankedMax[list, n]`  
returns the  $n$ th largest element of *list* (with  $n = 1$  yielding the largest element,  $n = 2$  yielding the second largest element, and so on).

```
>> RankedMax[{482, 17, 181, -12},
2]
181
```

## RankedMin

`RankedMin[list, n]`  
returns the  $n$ th smallest element of *list* (with  $n = 1$  yielding the smallest element,  $n = 2$  yielding the second smallest element, and so on).

```
>> RankedMin[{482, 17, 181, -12},
2]
17
```

## Reap

`Reap[expr]`  
gives the result of evaluating *expr*, together with all values sown during this evaluation. Values sown with different tags are given in different lists.

`Reap[expr, pattern]`  
only yields values sown with a tag matching *pattern*. `Reap[expr]` is equivalent to `Reap[expr, _]`.

`Reap[expr, {pattern1, pattern2, ...}]`  
uses multiple patterns.

`Reap[expr, pattern, f]`  
applies *f* on each tag and the corresponding values sown in the form  $f[\text{tag}, \{e1, e2, \dots\}]$ .

```
>> Reap[Sow[3]; Sow[1]]
{1, {{3, 1}}}
>> Reap[Sow[2, {x, x, x}]; Sow[3, x]
; Sow[4, y]; Sow[4, 1], {
_Symbol, _Integer, x}, f]
{4, {{f[x, {2, 2, 2, 3}], f[
y, {4}]}, {f[1, {4}]},
{f[x, {2, 2, 2, 3}]}}}
```

Find the unique elements of a list, keeping their order:

```
>> Reap[Sow[Null, {a, a, b, d, c, a
}], _, # &][[2]]
{a,b,d,c}
```

Sown values are reaped by the innermost matching Reap:

```
>> Reap[Reap[Sow[a, x]; Sow[b, 1],
_Symbol, Print["Inner: ",
#1]&];, _, f]
Inner: x
{Null, {f[1, {b}]}}
```

When no value is sown, an empty list is returned:

```
>> Reap[x]
{x, {}}
```

## ReplacePart

```
ReplacePart[expr, i -> new]
  replaces part i in expr with new.
ReplacePart[expr, {{i, j} -> e1, {k,
l} -> e2}]
  replaces parts i and j with e1, and parts k
and l with e2.
```

```
>> ReplacePart[{a, b, c}, 1 -> t]
{t,b,c}

>> ReplacePart[{{a, b}, {c, d}},
{2, 1} -> t]
{{a,b}, {t,d}}

>> ReplacePart[{{a, b}, {c, d}},
{{2, 1} -> t, {1, 1} -> t}]
{{t,b}, {t,d}}

>> ReplacePart[{a, b, c}, {{1},
{2}} -> t]
{t,t,c}
```

Delayed rules are evaluated once for each replacement:

```
>> n = 1;

>> ReplacePart[{a, b, c, d}, {{1},
{3}} :> n++]
{1,b,2,d}
```

Non-existing parts are simply ignored:

```
>> ReplacePart[{a, b, c}, 4 -> t]
{a,b,c}
```

You can replace heads by replacing part 0:

```
>> ReplacePart[{a, b, c}, 0 ->
Times]
abc
```

(This is equivalent to Apply.)

Negative part numbers count from the end:

```
>> ReplacePart[{a, b, c}, -1 -> t]
{a,b,t}
```

## Rest

```
Rest[expr]
  returns expr with the first element re-
  moved.
```

Rest[expr] is equivalent to expr[[2;]].

```
>> Rest[{a, b, c}]
{b,c}

>> Rest[a + b + c]
b + c

>> Rest[x]
Nonatomic expression expected.
Rest[x]
```

## Reverse

```
Reverse[expr]
  reverses the order of expr's items (on the
  top level)
Reverse[expr, n]
  reverses the order of items in expr on level
  n
Reverse[expr, {n1, n2, ...}]
  reverses the order of items in expr on lev-
  els n1, n2, ...
```

```
>> Reverse[{1, 2, 3}]
{3,2,1}

>> Reverse[x[a, b, c]]
x[c,b,a]
```

```
>> Reverse[{{1, 2}, {3, 4}}, 1]
{{3,4}, {1,2}}

>> Reverse[{{1, 2}, {3, 4}}, 2]
{{2,1}, {4,3}}

>> Reverse[{{1, 2}, {3, 4}}, {1,
2}]
{{4,3}, {2,1}}
```

## Riffle

**Riffle**[*list*, *x*]  
inserts a copy of *x* between each element of *list*.

**Riffle**[*a1*, *a2*, ..., *b1*, *b2*, ...]  
interleaves the elements of both lists, returning *a1*, *b1*, *a2*, *b2*, ....

```
>> Riffle[{a, b, c}, x]
{a,x,b,x,c}

>> Riffle[{a, b, c}, {x, y, z}]
{a,x,b,y,c,z}

>> Riffle[{a, b, c, d, e, f}, {x, y,
z}]
{a,x,b,y,c,z,d,x,e,y,f}
```

## RotateLeft

**RotateLeft**[*expr*]  
rotates the items of *expr* by one item to the left.

**RotateLeft**[*expr*, *n*]  
rotates the items of *expr* by *n* items to the left.

**RotateLeft**[*expr*, {*n1*, *n2*, ...}]  
rotates the items of *expr* by *n1* items to the left at the first level, by *n2* items to the left at the second level, and so on.

```
>> RotateLeft[{1, 2, 3}]
{2,3,1}

>> RotateLeft[Range[10], 3]
{4,5,6,7,8,9,10,1,2,3}
```

```
>> RotateLeft[x[a, b, c], 2]
x[c,a,b]

>> RotateLeft[{{a, b, c}, {d, e, f
}, {g, h, i}}, {1, 2}]
{{f,d,e}, {i,g,h}, {c,a,b}}
```

## RotateRight

**RotateRight**[*expr*]  
rotates the items of *expr* by one item to the right.

**RotateRight**[*expr*, *n*]  
rotates the items of *expr* by *n* items to the right.

**RotateRight**[*expr*, {*n1*, *n2*, ...}]  
rotates the items of *expr* by *n1* items to the right at the first level, by *n2* items to the right at the second level, and so on.

```
>> RotateRight[{1, 2, 3}]
{3,1,2}

>> RotateRight[Range[10], 3]
{8,9,10,1,2,3,4,5,6,7}

>> RotateRight[x[a, b, c], 2]
x[b,c,a]

>> RotateRight[{{a, b, c}, {d, e, f
}, {g, h, i}}, {1, 2}]
{{h,i,g}, {b,c,a}, {e,f,d}}
```

## Select

**Select**[*e1*, *e2*, ..., *f*]  
returns a list of the elements *ei* for which *f*[*ei*] returns True.

Find numbers greater than zero:

```
>> Select[{-3, 0, 1, 3, a}, #>0&]
{1,3}
```

Select works on an expression with any head:

```
>> Select[f[a, 2, 3], NumberQ]
f[2,3]
```

```
>> Select[a, True]
Nonatomicexpressionexpected.
Select[a, True]
```

## Skewness

**Skewness**[*list*]  
gives Pearson's moment coefficient of skewness for *list* (a measure for estimating the symmetry of a distribution).

```
>> Skewness[{1.1, 1.2, 1.4, 2.1, 2.4}]
0.407041
```

## Sow

**Sow**[*e*]  
sends the value *e* to the innermost Reap.

**Sow**[*e*, *tag*]  
sows *e* using *tag*. Sow[*e*] is equivalent to Sow[*e*, Null].

**Sow**[*e*, {*tag1*, *tag2*, ...}]  
uses multiple tags.

## Span (; ;)

**Span**  
is the head of span ranges like 1 ;; 3.

```
>> ;; // FullForm
Span[1, All]

>> 1 ;; 4 ;; 2 // FullForm
Span[1, 4, 2]

>> 2 ;; -2 // FullForm
Span[2, -2]

>> ;; 3 // FullForm
Span[1, 3]
```

## Split

**Split**[*list*]  
splits *list* into collections of consecutive identical elements.

**Split**[*list*, *test*]  
splits *list* based on whether the function *test* yields True on consecutive elements.

```
>> Split[{x, x, x, y, x, y, y, z}]
{{x, x, x}, {y}, {x}, {y, y}, {z}}
```

Split into increasing or decreasing runs of elements

```
>> Split[{1, 5, 6, 3, 6, 1, 6, 3, 4, 5, 4}, Less]
{{1, 5, 6}, {3, 6}, {1, 6}, {3, 4, 5}, {4}}

>> Split[{1, 5, 6, 3, 6, 1, 6, 3, 4, 5, 4}, Greater]
{{1}, {5}, {6, 3}, {6, 1}, {6, 3}, {4}, {5, 4}}
```

Split based on first element

```
>> Split[{x -> a, x -> y, 2 -> a, z -> c, z -> a}, First[#1] === First[#2] &]
{{x -> a, x -> y}, {2 -> a}, {z -> c, z -> a}}
```

## SplitBy

**SplitBy**[*list*, *f*]  
splits *list* into collections of consecutive elements that give the same result when *f* is applied.

```
>> SplitBy[Range[1, 3, 1/3], Round]
{{1, 4/3}, {5/3, 2, 7/3}, {8/3, 3}}

>> SplitBy[{1, 2, 1, 1.2}, {Round, Identity}]
{{{1}}, {{2}}, {{1}}, {1.2}}}
```

## StandardDeviation

`StandardDeviation[list]`

computes the standard deviation of *list*.  
*list* may consist of numerical values or symbols. Numerical values may be real or complex.

`StandardDeviation[{a1, a2, ...}, {b1, b2, ...}, ...]` will yield `{StandardDeviation[{a1, b1, ...}, StandardDeviation[{a2, b2, ...}], ...}`.

```
>> StandardDeviation[{1, 2, 3}]
1

>> StandardDeviation[{7, -5, 101,
100}]

$$\frac{\sqrt{13297}}{2}$$


>> StandardDeviation[{a, a}]
0

>> StandardDeviation[{{1, 10}, {-1,
20}}]

$$\{\sqrt{2}, 5\sqrt{2}\}$$

```

## SubsetQ

`SubsetQ[list1, list2]`

returns True if *list2* is a subset of *list1*, and False otherwise.

```
>> SubsetQ[{1, 2, 3}, {3, 1}]
True
```

The empty list is a subset of every list:

```
>> SubsetQ[{}, {}]
True
```

```
>> SubsetQ[{1, 2, 3}, {}]
True
```

Every list is a subset of itself:

```
>> SubsetQ[{1, 2, 3}, {1, 2, 3}]
True
```

## Table

`Table[expr, {i, n}]`

evaluates *expr* with *i* ranging from 1 to *n*, returning a list of the results.

`Table[expr, {i, start, stop, step}]`

evaluates *expr* with *i* ranging from *start* to *stop*, incrementing by *step*.

`Table[expr, {i, {e1, e2, ..., ei}}]`

evaluates *expr* with *i* taking on the values *e1, e2, ..., ei*.

```
>> Table[x, {4}]
{x, x, x, x}

>> n = 0;

>> Table[n = n + 1, {5}]
{1, 2, 3, 4, 5}

>> Table[i, {i, 4}]
{1, 2, 3, 4}

>> Table[i, {i, 2, 5}]
{2, 3, 4, 5}

>> Table[i, {i, 2, 6, 2}]
{2, 4, 6}

>> Table[i, {i, Pi, 2 Pi, Pi / 2}]
{Pi,  $\frac{3\text{Pi}}{2}$ , 2Pi}

>> Table[x^2, {x, {a, b, c}}]
{a^2, b^2, c^2}
```

Table supports multi-dimensional tables:

```
>> Table[{i, j}, {i, {a, b}}, {j,
1, 2}]
{{{a, 1}, {a, 2}}, {{b, 1}, {b, 2}}}
```

## Take

`Take[expr, n]`

returns *expr* with all but the first *n* leaves removed.

```
>> Take[{a, b, c, d}, 3]
{a, b, c}
```



```
>> Take[{a, b, c, d}, -2]
      {c, d}

>> Take[{a, b, c, d, e}, {2, -2}]
      {b, c, d}
```

Take a submatrix:

```
>> A = {{a, b, c}, {d, e, f}};

>> Take[A, 2, 2]
      {{a, b}, {d, e}}
```

Take a single column:

```
>> Take[A, All, {2}]
      {{b}, {e}}
```

## TakeLargest

`TakeLargest[list, f, n]`  
returns the a sorted list of the  $n$  largest items in *list*.

```
>> TakeLargest[{100, -1, 50, 10},
               2]
      {100, 50}
```

None, Null, Indeterminate and expressions with head Missing are ignored by default:

```
>> TakeLargest[{-8, 150, Missing[
  abc]}, 2]
      {150, -8}
```

You may specify which items are ignored using the option `ExcludedForms`:

```
>> TakeLargest[{-8, 150, Missing[
  abc]}, 2, ExcludedForms -> {}]
      {Missing[abc], 150}
```

## TakeLargestBy

`TakeLargestBy[list, f, n]`  
returns the a sorted list of the  $n$  largest items in *list* using *f* to retrieve the items' keys to compare them.

For details on how to use the `ExcludedForms` option, see `TakeLargest[]`.

```
>> TakeLargestBy[{{1, -1}, {10,
  100}, {23, 7, 8}, {5, 1}}, Total
, 2]
      {{10, 100}, {23, 7, 8}}

>> TakeLargestBy[{"abc", "ab", "x
  "}, StringLength, 1]
      {abc}
```

## TakeSmallest

`TakeSmallest[list, f, n]`  
returns the a sorted list of the  $n$  smallest items in *list*.

For details on how to use the `ExcludedForms` option, see `TakeLargest[]`.

```
>> TakeSmallest[{100, -1, 50, 10},
               2]
      {-1, 10}
```

## TakeSmallestBy

`TakeSmallestBy[list, f, n]`  
returns the a sorted list of the  $n$  smallest items in *list* using *f* to retrieve the items' keys to compare them.

For details on how to use the `ExcludedForms` option, see `TakeLargest[]`.

```
>> TakeSmallestBy[{{1, -1}, {10,
  100}, {23, 7, 8}, {5, 1}}, Total
, 2]
      {{1, -1}, {5, 1}}

>> TakeSmallestBy[{"abc", "ab", "x
  "}, StringLength, 1]
      {x}
```

## Tally

**Tally**[*list*]  
counts and returns the number of occurrences of objects and returns the result as a list of pairs {object, count}.

**Tally**[*list*, *test*]  
counts the number of occurrences of objects and uses *\$test* to determine if two objects should be counted in the same bin.

```
>> Tally[{a, b, c, b, a}]
{{a,2}, {b,2}, {c,1}}
```

Tally always returns items in the order as they first appear in *list*:

```
>> Tally[{b, b, a, a, a, d, d, d, d, c}]
{{b,2}, {a,3}, {d,4}, {c,1}}
```

## Total

**Total**[*list*]  
adds all values in *list*.

**Total**[*list*, *n*]  
adds all values up to level *n*.

**Total**[*list*, {*n*}]  
totals only the values at level {*n*}.

**Total**[*list*, {*n*<sub>1</sub>, *n*<sub>2</sub>}]  
totals at levels {*n*<sub>1</sub>, *n*<sub>2</sub>}.

```
>> Total[{1, 2, 3}]
6
```

```
>> Total[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}]
{12,15,18}
```

Total over rows and columns

```
>> Total[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, 2]
45
```

Total over rows instead of columns

```
>> Total[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {2}]
{6,15,24}
```

## Tuples

**Tuples**[*list*, *n*]  
returns a list of all *n*-tuples of elements in *list*.

**Tuples**[{*list*<sub>1</sub>, *list*<sub>2</sub>, ...}]  
returns a list of tuples with elements from the given lists.

```
>> Tuples[{a, b, c}, 2]
{{a,a}, {a,b}, {a,c}, {b,a}, {b,b}, {b,c}, {c,a}, {c,b}, {c,c}}
```

```
>> Tuples[{}, 2]
{}
```

```
>> Tuples[{a, b, c}, 0]
{{}}
```

```
>> Tuples[{{a, b}, {1, 2, 3}}]
{{a,1}, {a,2}, {a,3}, {b,1}, {b,2}, {b,3}}
```

The head of *list* need not be List:

```
>> Tuples[f[a, b, c], 2]
{f[a,a], f[a,b], f[a,c], f[b,a], f[b,b], f[b,c], f[c,a], f[c,b], f[c,c]}
```

However, when specifying multiple expressions, List is always used:

```
>> Tuples[{f[a, b], g[c, d]]}
{{a,c}, {a,d}, {b,c}, {b,d}}
```

## Union

**Union**[*a*, *b*, ...]  
gives the union of the given set or sets. The resulting list will be sorted and each element will only occur once.

```
>> Union[{5, 1, 3, 7, 1, 8, 3}]
{1,3,5,7,8}
```

```
>> Union[{a, b, c}, {c, d, e}]
{a,b,c,d,e}
```

```
>> Union[{c, b, a}]
{a,b,c}
```

```
>> Union[{{a, 1}, {b, 2}}, {{c, 1},
      {d, 3}}, SameTest->(SameQ[Last
      [#1], Last[#2]]&)]
      {{b, 2}, {c, 1}, {d, 3}}
>> Union[{1, 2, 3}, {2, 3, 4},
      SameTest->Less]
      {1, 2, 2, 3, 4}
```

## UnitVector

`UnitVector[n, k]`  
 returns the  $n$ -dimensional unit vector  
 with a 1 in position  $k$ .  
`UnitVector[k]`  
 is equivalent to `UnitVector[2, k]`.

```
>> UnitVector[2]
      {0, 1}
>> UnitVector[4, 3]
      {0, 0, 1, 0}
```

## Values

`Values[<|key1 -> val1, key2 -> val2, ...|>]`  
 return a list of the values *vali* in an asso-  
 ciation.  
`Values[{key1 -> val1, key2 -> val2, ...}]`  
 return a list of the *vali* in a list of rules.

```
>> Values[<|a -> x, b -> y|>]
      {x, y}
>> Values[{a -> x, b -> y}]
      {x, y}
```

Values automatically threads over lists:

```
>> Values[{<|a -> x, b -> y|>, {c
      -> z, {}}}]
      {{x, y}, {z, {}}}
```

Values are listed in the order of their appearance:

```
>> Values[{c -> z, b -> y, a -> x}]
      {z, y, x}
```

## Variance

`Variance[list]`  
 computes the variance of \$list. *list* may  
 consist of numerical values or symbols.  
 Numerical values may be real or com-  
 plex.  
`Variance[{a1, a2, ...}, {b1, b2, ...}, ...]` will yield  
`{Variance[{a1, b1, ...}, Variance[{a2, b2, ...}], ...}`.

```
>> Variance[{1, 2, 3}]
      1
>> Variance[{7, -5, 101, 3}]
      7475
      3
>> Variance[{1 + 2I, 3 - 10I}]
      74
>> Variance[{a, a}]
      0
>> Variance[{{1, 3, 5}, {4, 10,
      100}}]
      { 9 49 9025 }
      { 2' 2' 2 }
```

# XL. Mathematical Constants

Numeric, Arithmetic, or Symbolic constants like Pi, E, or Infinity.

## Contents

---

Catalan . . . . .	244	Glaisher . . . . .	245	MPMathConstant . . .	245
ComplexInfinity . . . .	244	GoldenRatio . . . . .	245	NumpyConstant . . . .	245
Degree . . . . .	244	Indeterminate . . . . .	245	Pi . . . . .	246
E . . . . .	244	Infinity . . . . .	245	SympyConstant . . . .	246
EulerGamma . . . . .	245	Khinchin . . . . .	245		

---

## Catalan

Catalan  
is Catalan's constant with numerical value 0.915966.

```
>> Catalan // N
0.915966
>> N[Catalan, 20]
0.91596559417721901505
```

## ComplexInfinity

ComplexInfinity  
represents an infinite complex quantity of undetermined direction.

```
>> 1 / ComplexInfinity
0
>> ComplexInfinity * Infinity
ComplexInfinity
>> FullForm[ComplexInfinity]
DirectedInfinity[]
```

## Degree

Degree  
is the number of radians in one degree. It has a numerical value of  $\pi / 180$ .

```
>> Cos[60 Degree]
1/2
Degree has the value of Pi / 180
>> Degree == Pi / 180
True
```

## E

E  
is the constant with numerical value 2.71828.

```
>> N[E]
2.71828
>> N[E, 50]
2.718281828459045235360287~
~4713526624977572470937000
```

## EulerGamma

EulerGamma  
is Euler's constant with numerical value 0.577216.

```
>> EulerGamma // N
0.577216

>> N[EulerGamma, 40]
0.577215664901532860~
~6065120900824024310422
```

## Glaisher

Glaisher  
is Glaisher's constant, with numerical value 1.28243.

```
>> N[Glaisher]
1.28243

>> N[Glaisher, 50]
1.282427129100621954194139~
~1071304678916931152343750
```

## GoldenRatio

GoldenRatio  
is the golden ratio,  $= (1 + \sqrt{5})/2$ .

```
>> GoldenRatio // N
1.61803

>> N[GoldenRatio, 40]
1.618033988749894848~
~204586834365638117720
```

## Indeterminate

Indeterminate  
represents an indeterminate result.

```
>> 0^0
Indeterminate
Indeterminateexpression 00 encountered.
```

```
>> Tan[Indeterminate]
Indeterminate
```

## Infinity

Infinity  
represents an infinite real quantity.

```
>> 1 / Infinity
0

>> Infinity + 100
∞
```

Use Infinity in sum and limit calculations:

```
>> Sum[1/x^2, {x, 1, Infinity}]

$$\frac{\pi^2}{6}$$

```

## Khinchin

Khinchin  
is Khinchin's constant, with numerical value 2.68545.

```
>> N[Khinchin]
2.68545

>> N[Khinchin, 50]
2.685452001065307570115692~
~2150403261184692382812500
```

## MPMathConstant

Representation of a constant in mpmath, e.g. Pi, E, I, etc.

## NumpyConstant

Representation of a constant in numpy, e.g. Pi, E, etc.

## Pi

Pi  
is the constant  $\pi$ .

```
>> N[Pi]
3.14159

>> N[Pi, 50]
3.141592653589793238462643~
~3832795028841971693993751

>> Attributes[Pi]
{Constant, Protected, ReadProtected}
```

## SympyConstant

Representation of a constant in Sympy, e.g. Pi, E, I, Catalan, etc.

# XLI. Algebraic Manipulation

## Contents

Apart . . . . .	247	ExpandDenominator . . . . .	249	PolynomialQ . . . . .	251
Cancel . . . . .	247	Exponent . . . . .	250	PowerExpand . . . . .	251
Coefficient . . . . .	248	Factor . . . . .	250	Simplify . . . . .	251
CoefficientList . . . . .	248	FactorTermsList . . . . .	250	Together . . . . .	252
Denominator . . . . .	248	MinimalPolynomial . . . . .	251	UpTo . . . . .	252
Expand . . . . .	249	Missing . . . . .	251	Variables . . . . .	252
ExpandAll . . . . .	249	Numerator . . . . .	251		

## Apart

`Apart[expr]`  
writes *expr* as a sum of individual fractions.

`Apart[expr, var]`  
treats *var* as the main variable.

```
>> Apart[1 / (x^2 + 5x + 6)]
      1      1
     ---  -  ---
    2 + x   3 + x
```

When several variables are involved, the results can be different depending on the main variable:

```
>> Apart[1 / (x^2 - y^2), x]
      1      1
     ---  +  ---
    2y (x + y) 2y (x - y)

>> Apart[1 / (x^2 - y^2), y]
      1      1
     ---  +  ---
    2x (x + y) 2x (x - y)
```

`Apart` is `Listable`:

```
>> Apart[{1 / (x^2 + 5x + 6)}]
      { 1      1 }
     { ---  -  --- }
      2 + x   3 + x
```

But it does not touch other expressions:

```
>> Sin[1 / (x^2 - y^2)] //
    Apart
      Sin[ $\frac{1}{x^2 - y^2}$ ]
```

## Cancel

`Cancel[expr]`  
cancels out common factors in numerators and denominators.

```
>> Cancel[x / x^2]
      1
     ---
      x
```

`Cancel` threads over sums:

```
>> Cancel[x / x^2 + y / y^2]
      1      1
     ---  +  ---
      x      y

>> Cancel[f[x] / x + x * f[x] / x^2]
      2f[x]
     -----
        x
```

## Coefficient

`Coefficient[expr, form]`  
returns the coefficient of *form* in the polynomial *expr*.

`Coefficient[expr, form, n]`  
return the coefficient of *form*<sup>*n*</sup> in *expr*.

```
>> Coefficient[(x + y)^4, (x^2)* (y^2)]
      6
```

```
>> Coefficient[a x^2 + b y^3 + c x
+ d y + 5, x]
c

>> Coefficient[(x + 3 y)^5, x]
405 y^4

>> Coefficient[(x + 3 y)^5, x * y
^4]
405

>> Coefficient[(x + 2)/(y - 3) + (x
+ 3)/(y - 2), x]
1
-3 + y + 1
-2 + y

>> Coefficient[x * Cos[x + 3] + 6 * y,
x]
Cos[3 + x]

>> Coefficient[(x + 1)^3, x, 2]
3

>> Coefficient[a x^2 + b y^3 + c x
+ d y + 5, y, 3]
b

>> Coefficient[(x + 2)^3 + (x + 3)
^2, x, 0]
17

>> Coefficient[(x + 2)^3 + (x + 3)
^2, y, 0]
(2 + x)^3 + (3 + x)^2

>> Coefficient[a x^2 + b y^3 + c x
+ d y + 5, x, 0]
5 + b y^3 + d y
```

## CoefficientList

`CoefficientList[poly, var]`  
returns a list of coefficients of powers of *var* in *poly*, starting with power 0.

`CoefficientList[poly, {var1, var2, ...}]`  
returns an array of coefficients of the *vari*.

```
>> CoefficientList[(x + 3)^5, x]
{243, 405, 270, 90, 15, 1}
```

```
>> CoefficientList[(x + y)^4, x]
{y^4, 4 y^3, 6 y^2, 4 y, 1}

>> CoefficientList[a x^2 + b y^3 +
c x + d y + 5, x]
{5 + b y^3 + d y, c, a}

>> CoefficientList[(x + 2)/(y - 3) +
x/(y - 2), x]
{2
-3 + y, 1
-3 + y, 1
-2 + y}

>> CoefficientList[(x + y)^3, z]
{(x + y)^3}

>> CoefficientList[a x^2 + b y^3 +
c x + d y + 5, {x, y}]
{{5, d, 0, b}, {c, 0, 0, 0}, {a, 0, 0, 0}}

>> CoefficientList[(x - 2 y + 3 z)
^3, {x, y, z}]
{{{0, 0, 0, 27}, {0, 0, -54, 0},
{0, 36, 0, 0}, {-8, 0, 0, 0}}, {{0,
0, 27, 0}, {0, -36, 0, 0}, {12,
0, 0, 0}, {0, 0, 0, 0}}, {{0, 9, 0,
0}, {-6, 0, 0, 0}, {0, 0, 0, 0},
{0, 0, 0, 0}}, {{1, 0, 0, 0}, {0, 0,
0, 0}, {0, 0, 0, 0}, {0, 0, 0, 0}}}
```

## Denominator

`Denominator[expr]`  
gives the denominator in *expr*.

```
>> Denominator[a / b]
b

>> Denominator[2 / 3]
3

>> Denominator[a + b]
1
```



## Expand

**Expand[*expr*]**  
expands out positive integer powers and products of sums in *expr*, as well as trigonometric identities.

```
>> Expand[(x + y)^3]
      x^3 + 3x^2y + 3xy^2 + y^3

>> Expand[(a + b)(a + c + d)]
      a^2 + ab + ac + ad + bc + bd

>> Expand[(a + b)(a + c + d)(e + f)
      + e a a]
      2a^2e + a^2f + abe + abf + ace + acf
      + ade + adf + bce + bcf + bde + bdf

>> Expand[(a + b)^2 * (c + d)]
      a^2c + a^2d + 2abc + 2abd + b^2c + b^2d

>> Expand[(x + y)^2 + x y]
      x^2 + 3xy + y^2

>> Expand[((a + b)(c + d))^2 + b
      (1 + a)]
      a^2c^2 + 2a^2cd + a^2d^2 + b + ab + 2abc^2
      + 4abcd + 2abd^2 + b^2c^2 + 2b^2cd + b^2d^2
```

Expand expands items in lists and rules:

```
>> Expand[{4 (x + y), 2 (x + y) -> 4
      (x + y)}]
      {4x + 4y, 2x + 2y -> 4x + 4y}
```

Expand expands trigonometric identities

```
>> Expand[Sin[x + y], Trig -> True]
      Cos[x] Sin[y] + Cos[y] Sin[x]
```

Expand does not change any other expression.

```
>> Expand[Sin[x (1 + y)]]
      Sin[x (1 + y)]
```

Expand also works in Galois fields

```
>> Expand[(1 + a)^12, Modulus -> 3]
      1 + a^3 + a^9 + a^12

>> Expand[(1 + a)^12, Modulus -> 4]
      1 + 2a^2 + 3a^4 + 3a^8 + 2a^10 + a^12
```

## ExpandAll

**ExpandAll[*expr*]**  
expands out negative integer powers and products of sums in *expr*.

```
>> ExpandAll[(a + b)^2 / (c + d)
      ^2]
      a^2
      c^2 + 2cd + d^2 + 2ab
      b^2
      c^2 + 2cd + d^2
```

ExpandAll descends into sub expressions

```
>> ExpandAll[(a + Sin[x (1 + y)])
      ^2]
      2aSin[x + xy] + a^2 + Sin[x + xy]^2
```

ExpandAll also expands heads

```
>> ExpandAll[((1 + x)(1 + y))[x]]
      (1 + x + y + xy)[x]
```

ExpandAll can also work in finite fields

```
>> ExpandAll[(1 + a)^6 / (x + y)
      ^3, Modulus -> 3]
      1 + 2a^3 + a^6
      x^3 + y^3
```

## ExpandDenominator

**ExpandDenominator[*expr*]**  
expands out negative integer powers and products of sums in *expr*.

```
>> ExpandDenominator[(a + b)^2 /
      ((c + d)^2 (e + f))]
      (a + b)^2
      c^2e + c^2f + 2cde + 2cdf + d^2e + d^2f
```

## Exponent

**Exponent[expr, form]**  
returns the maximum power with which *form* appears in the expanded form of *expr*.

**Exponent[expr, form, h]**  
applies *h* to the set of exponents with which *form* appears in *expr*.

```
>> Exponent[5 x^2 - 3 x + 7, x]
2

>> Exponent[(x^3 + 1)^2 + 1, x]
6

>> Exponent[x^(n + 1) + Sqrt[x] + 1, x]
Max  $\left[\frac{1}{2}, 1 + n\right]$ 

>> Exponent[x / y, y]
-1

>> Exponent[(x^2 + 1)^3 - 1, x, Min]
2

>> Exponent[1 - 2 x^2 + a x^3, x, List]
{0, 2, 3}

>> Exponent[0, x]
-∞

>> Exponent[1, x]
0
```

## Factor

**Factor[expr]**  
factors the polynomial expression *expr*.

```
>> Factor[x^2 + 2 x + 1]
(1 + x)^2

>> Factor[1 / (x^2 + 2x + 1) + 1 / (x^4 + 2x^2 + 1)]

$$\frac{2 + 2x + 3x^2 + x^4}{(1 + x)^2 (1 + x^2)^2}$$

```

## FactorTermsList

**FactorTermsList[poly]**  
returns a list of 2 elements. The first element is the numerical factor in *poly*. The second one is the remaining of the polynomial with numerical factor removed

**FactorTermsList[poly, {x1, x2, ...}]**  
returns a list of factors in *poly*. The first element is the numerical factor in *poly*. The next ones are factors that are independent of variables lists which are created by removing each variable *xi* from right to left. The last one is the remaining of polynomial after dividing *poly* to all previous factors

```
>> FactorTermsList[2 x^2 - 2]
{2, -1 + x^2}

>> FactorTermsList[x^2 - 2 x + 1]
{1, 1 - 2x + x^2}

>> f = 3 (-1 + 2 x) (-1 + y) (1 - a)
3 (-1 + 2x) (-1 + y) (1 - a)

>> FactorTermsList[f]
{-3, -1 + a - 2ax - ay + 2x + y - 2xy + 2axy}

>> FactorTermsList[f, x]
{-3, 1 - a - y + ay, -1 + 2x}

>> FactorTermsList[f, {x, y}]
{-3, -1 + a, -1 + y, -1 + 2x}
```

## MinimalPolynomial

**MinimalPolynomial[s, x]**  
gives the minimal polynomial in *x* for which the algebraic number *s* is a root.

```
>> MinimalPolynomial[7, x]
-7 + x

>> MinimalPolynomial[Sqrt[2] + Sqrt[3], x]
1 - 10x^2 + x^4
```

```
>> MinimalPolynomial[Sqrt[1 + Sqrt
[3]], x]
-2 - 2x2 + x4

>> MinimalPolynomial[Sqrt[I + Sqrt
[6]], x]
49 - 10x4 + x8
```

## Missing

## Numerator

`Numerator[expr]`  
gives the numerator in *expr*.

```
>> Numerator[a / b]
a

>> Numerator[2 / 3]
2

>> Numerator[a + b]
a + b
```

## PolynomialQ

`PolynomialQ[expr, var]`  
returns True if *expr* is a polynomial in *var*,  
and returns False otherwise.  
`PolynomialQ[expr, {var1, ...}]`  
tests whether *expr* is a polynomial in the  
*vari*.

```
>> PolynomialQ[x3 - 2 x/y + 3xz, x]
True

>> PolynomialQ[x3 - 2 x/y + 3xz, y]
False

>> PolynomialQ[f[a] + f[a]2, f[a]]
True

>> PolynomialQ[x2 + axy2 - bSin[c], {x, y}]
True
```

```
>> PolynomialQ[x2 + axy2 - bSin[c], {a, b, c}]
False
```

## PowerExpand

`PowerExpand[expr]`  
expands out powers of the form  $(x^y)^z$   
and  $(x*y)^z$  in *expr*.

```
>> PowerExpand[(a ^ b) ^ c]
abc

>> PowerExpand[(a * b) ^ c]
acbc
```

PowerExpand is not correct without certain assumptions:

```
>> PowerExpand[(x ^ 2) ^ (1/2)]
x
```

## Simplify

`Simplify[expr]`  
simplifies *expr*.

```
>> Simplify[2*Sin[x]2 + 2*Cos[x]2]
2

>> Simplify[x]
x

>> Simplify[f[x]]
f[x]
```

## Together

`Together[expr]`  
writes sums of fractions in *expr* together.

```
>> Together[a / c + b / c]

$$\frac{a + b}{c}$$

```

Together operates on lists:

```
>> Together[{x / (y+1)+ x / (y+1)
^2}]
```

$$\left\{ \frac{x (2 + y)}{(1 + y)^2} \right\}$$

But it does not touch other functions:

```
>> Together[f[a / c + b / c]]
```

$$f \left[ \frac{a}{c} + \frac{b}{c} \right]$$

## UpTo

## Variables

`Variables[expr]`

gives a list of the variables that appear in the polynomial *expr*.

```
>> Variables[a x^2 + b x + c]
{a, b, c, x}
```

```
>> Variables[{a + b x, c y^2 + x
/2}]
{a, b, c, x, y}
```

```
>> Variables[x + Sin[y]]
{x, Sin[y]}
```

## XLII. Numeric Evaluation

Support for numeric evaluation with arbitrary precision is just a proof-of-concept. Precision is not “guarded” through the evaluation process. Only integer precision is supported. However, things like  $N[\text{Pi}, 100]$  should work as expected.

### Contents

<b>Chop</b> . . . . .	253	<b>\$MaxPrecision</b> . . . . .	254	<b>RealDigits</b> . . . . .	257
<b>Hash</b> . . . . .	253	<b>\$MinPrecision</b> . . . . .	255	<b>Inter-</b>	
<b>IntegerDigits</b> . . . . .	254	<b>N</b> . . . . .	256	<b>nal'RealValuedNumberQ</b>	257
<b>\$MachineEpsilon</b> . . . . .	254	<b>NumericQ</b> . . . . .	256	<b>Inter-</b>	
<b>MachinePrecision</b> . . . . .	254	<b>Precision</b> . . . . .	256	<b>nal'RealValuedNumericQ</b>	257
<b>\$MachinePrecision</b> . . . . .	254	<b>Rationalize</b> . . . . .	256	<b>Round</b> . . . . .	257

### Chop

**Chop**[*expr*]  
replaces floating point numbers close to 0 by 0.

**Chop**[*expr*, *delta*]  
uses a tolerance of *delta*. The default tolerance is  $10^{-10}$ .

```
>> Chop[10.0 ^ -16]
0

>> Chop[10.0 ^ -9]
1. × 10-9

>> Chop[10 ^ -11 I]

$$\frac{I}{100\,000\,000\,000}$$


>> Chop[0. + 10 ^ -11 I]
0
```

### Hash

**Hash**[*expr*]  
returns an integer hash for the given *expr*.

**Hash**[*expr*, *type*]  
returns an integer hash of the specified *type* for the given *expr*.  
The types supported are “MD5”, “Adler32”, “CRC32”, “SHA”, “SHA224”, “SHA256”, “SHA384”, and “SHA512”.

**Hash**[*expr*, *type*, *format*]  
Returns the hash in the especified format.

```
> Hash["The Adventures of Huckleberry Finn"]
= 213425047836523694663619736686226550816
> Hash["The Adventures of Huckleberry Finn",
"SHA256"] = 950926495945903842880571834086092549189343518
> Hash[1/3] = 56073172797010645108327809727054836008
> Hash[{a, b, {c, {d, e, f}}}] = 135682164776235407777080772547528
> Hash[SomeHead[3.1415]] = 5804231647347187731544201546970
>> Hash[{a, b, c}, "xyzstr"]
Hash[{a, b, c}, xyzstr, Integer]
```

## IntegerDigits

`IntegerDigits[n]`  
returns a list of the base-10 digits in the integer  $n$ .  
`IntegerDigits[n, base]`  
returns a list of the base- $base$  digits in  $n$ .  
`IntegerDigits[n, base, length]`  
returns a list of length  $length$ , truncating or padding with zeroes on the left as necessary.

```
>> IntegerDigits[76543]
{7, 6, 5, 4, 3}
```

The sign of  $n$  is discarded:

```
>> IntegerDigits[-76543]
{7, 6, 5, 4, 3}
```

```
>> IntegerDigits[15, 16]
{15}
```

```
>> IntegerDigits[1234, 16]
{4, 13, 2}
```

```
>> IntegerDigits[1234, 10, 5]
{0, 1, 2, 3, 4}
```

## \$MachineEpsilon

`$MachineEpsilon`  
is the distance between 1.0 and the next nearest representable machine-precision number.

```
>> $MachineEpsilon
2.22045 × 10-16
>> x = 1.0 + {0.4, 0.5, 0.6}
$MachineEpsilon;
>> x - 1
{0., 0., 2.22045 × 10-16}
```

## MachinePrecision

`MachinePrecision`  
represents the precision of machine precision numbers.

```
>> N[MachinePrecision]
15.9546
>> N[MachinePrecision, 30]
15.9545897701910033463281614204
```

## \$MachinePrecision

`$MachinePrecision`  
is the number of decimal digits of precision for machine-precision numbers.

```
>> $MachinePrecision
15.9546
```

## \$MaxPrecision

`$MaxPrecision`  
represents the maximum number of digits of precision permitted in arbitrary-precision numbers.

```
>> $MaxPrecision
∞
>> $MaxPrecision = 10;
>> N[Pi, 11]
Requested precision 11 is larger than $MaxPrecision. Using current
= Infinity specifies that any precision should be allowed.
3.141592654
```

## \$MinPrecision

`$MinPrecision`  
represents the minimum number of digits of precision permitted in arbitrary-precision numbers.

```
>> $MinPrecision
0
```

```
>> $MinPrecision = 10;
```

```
>> N[Pi, 9]
```

*Requested precision 9 is smaller than \$MinPrecision. Using current \$MinPrecision of 10 instead.*

```
3.141592654
```

## N

`N[expr, prec]`  
evaluates *expr* numerically with a precision of *prec* digits.

```
>> N[Pi, 50]
```

```
3.141592653589793238462643~  
~3832795028841971693993751
```

```
>> N[1/7]
```

```
0.142857
```

```
>> N[1/7, 5]
```

```
0.14286
```

You can manually assign numerical values to symbols. When you do not specify a precision, `MachinePrecision` is taken.

```
>> N[a] = 10.9
```

```
10.9
```

```
>> a
```

```
a
```

`N` automatically threads over expressions, except when a symbol has attributes `NHoldAll`, `NHoldFirst`, or `NHoldRest`.

```
>> N[a + b]
```

```
10.9 + b
```

```
>> N[a, 20]
```

```
a
```

```
>> N[a, 20] = 11;
```

```
>> N[a + b, 20]
```

```
11.000000000000000000 + b
```

```
>> N[f[a, b]]
```

```
f[10.9, b]
```

```
>> SetAttributes[f, NHoldAll]
```

```
>> N[f[a, b]]
```

```
f[a, b]
```

The precision can be a pattern:

```
>> N[c, p_?(#>10&)] := p
```

```
>> N[c, 3]
```

```
>> N[c, 11]
```

```
11.000000000
```

You can also use `UpSet` or `TagSet` to specify values for `N`:

```
>> N[d] ^= 5;
```

However, the value will not be stored in `UpValues`, but in `NValues` (as for `Set`):

```
>> UpValues[d]
```

```
{}
```

```
>> NValues[d]
```

```
{HoldPattern[N[d,  
MachinePrecision]]:>5}
```

```
>> e /: N[e] = 6;
```

```
>> N[e]
```

```
6.
```

Values for `N[expr]` must be associated with the head of *expr*:

```
>> f /: N[e[f]] = 7;
```

*Tag f not found or too deep for an assigned rule.*

You can use `Condition`:

```
>> N[g[x_, y_], p_] := x + y * Pi  
/; x + y > 3
```

```
>> SetAttributes[g, NHoldRest]
```

```
>> N[g[1, 1]]
```

```
g[1, 1]
```

```
>> N[g[2, 2]] // InputForm
```

```
8.283185307179586
```

The precision of the result is no higher than the precision of the input

```
>> N[Exp[0.1], 100]
```

```
1.10517
```

```
>> % // Precision
```

```
MachinePrecision
```

```
>> N[Exp[1/10], 100]
1.105170918075647624811707~
~826490246668224547194737~
~518718792863289440967966~
~747654302989143318970748654

>> % // Precision
100.

>> N[Exp[1.0^20], 100]
2.7182818284590452354

>> % // Precision
20.
```

## NumericQ

`NumericQ[expr]`  
tests whether *expr* represents a numeric quantity.

```
>> NumericQ[2]
True

>> NumericQ[Sqrt[Pi]]
True

>> NumericQ[Sqrt[Pi]]
False
```

## Precision

`Precision[expr]`  
examines the number of significant digits of *expr*.

This is rather a proof-of-concept than a full im-

plementation. Precision of compound expression is not supported yet.

```
>> Precision[1]
∞

>> Precision[1/2]
∞

>> Precision[0.5]
MachinePrecision
```

## Rationalize

`Rationalize[x]`  
converts a real number *x* to a nearby rational number.  
`Rationalize[x, dx]`  
finds the rational number within *dx* of *x* with the smallest denominator.

```
>> Rationalize[2.2]

$$\frac{11}{5}$$

```

Not all numbers can be well approximated.

```
>> Rationalize[N[Pi]]
3.14159
```

Find the exact rational representation of `N[Pi]`

```
>> Rationalize[N[Pi], 0]

$$\frac{245850922}{78256779}$$

```

## RealDigits

`RealDigits[n]`  
returns the decimal representation of the real number *n* as list of digits, together with the number of digits that are to the left of the decimal point.  
`RealDigits[n, b]`  
returns a list of base-*b* representation of the real number *n*.  
`RealDigits[n, b, len]`  
returns a list of *len* digits.  
`RealDigits[n, b, len, p]`  
return *len* digits starting with the coefficient of  $b^p$

Return the list of digits and exponent:

```
>> RealDigits[123.55555]
{{1, 2, 3, 5, 5, 5, 5, 5},
 {0, 0, 0, 0, 0, 0, 0, 0}, 3}

>> RealDigits[0.000012355555]
{{1, 2, 3, 5, 5, 5, 5, 5, 0},
 {0, 0, 0, 0, 0, 0, 0, 0}, -4}

>> RealDigits[-123.55555]
{{1, 2, 3, 5, 5, 5, 5, 5},
 {0, 0, 0, 0, 0, 0, 0, 0}, 3}
```



Return 25 digits of in base 10:

```
>> RealDigits[Pi, 10, 25]
{{3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5, 8, 9,
  7, 9, 3, 2, 3, 8, 4, 6, 2, 6, 4, 3}, 1}
```

Return an explicit recurring decimal form:

```
>> RealDigits[19 / 7]
{{2, {7, 1, 4, 2, 8, 5}}, 1}
```

20 digits starting with the coefficient of  $10^{-5}$ :

```
>> RealDigits[Pi, 10, 20, -5]
{{9, 2, 6, 5, 3, 5, 8, 9, 7, 9, 3,
  2, 3, 8, 4, 6, 2, 6, 4, 3}, -4}
```

The 10000th digit of is an 8:

```
>> RealDigits[Pi, 10, 1, -10000]
{{8}, -9999}
```

RealDigits gives Indeterminate if more digits than the precision are requested:

```
>> RealDigits[123.45, 10, 18]
{{1, 2, 3, 4, 5, 0, 0, 0, 0, 0, 0,
  0, 0, 0, 0, 0, Indeterminate,
  Indeterminate}, 3}
```

Round to exact value

```
>> Round[2.6, 1/3]
8
3
```

```
>> Round[10, Pi]
3Pi
```

Round complex numbers

```
>> Round[6/(2 + 3 I)]
1 - I
```

```
>> Round[1 + 2 I, 2 I]
2I
```

Round Negative numbers too

```
>> Round[-1.4]
-1
```

Expressions other than numbers remain unevaluated:

```
>> Round[x]
Round[x]
```

```
>> Round[1.5, k]
Round[1.5, k]
```

## Internal'RealValuedNumberQ

## Internal'RealValuedNumericQ

## Round

`Round[expr]`  
rounds *expr* to the nearest integer.  
`Round[expr, k]`  
rounds *expr* to the closest multiple of *k*.

```
>> Round[10.6]
11
```

```
>> Round[0.06, 0.1]
0.1
```

```
>> Round[0.04, 0.1]
0.
```

Constants can be rounded too

```
>> Round[Pi, .5]
3.
```

```
>> Round[Pi^2]
10
```

# XLIII. File Operations

## Contents

AbsoluteFileName . . .	258	FileHash . . . . .	263	\$Path . . . . .	267
BinaryRead . . . . .	259	FileInformation . . . .	263	\$PathnameSeparator .	267
BinaryWrite . . . . .	260	FileNameDepth . . . .	263	Put (>>) . . . . .	268
Byte . . . . .	260	FileNameJoin . . . . .	263	PutAppend (>>>) . . .	268
Character . . . . .	260	FileNameSplit . . . . .	263	Read . . . . .	269
Close . . . . .	260	FileNameTake . . . . .	264	ReadList . . . . .	269
Compress . . . . .	260	FilePrint . . . . .	264	Record . . . . .	269
CopyDirectory . . . . .	260	FileType . . . . .	264	RenameDirectory . . .	269
CopyFile . . . . .	260	Find . . . . .	264	RenameFile . . . . .	269
CreateDirectory . . . .	260	FindFile . . . . .	265	ResetDirectory . . . .	269
DeleteDirectory . . . .	261	FindList . . . . .	265	\$RootDirectory . . . .	270
DeleteFile . . . . .	261	Get (<<) . . . . .	265	SetDirectory . . . . .	270
Directory . . . . .	261	\$HomeDirectory . . . .	265	SetFileDate . . . . .	270
DirectoryName . . . . .	261	\$InitialDirectory . . . .	265	SetStreamPosition . . .	270
DirectoryQ . . . . .	261	\$Input . . . . .	265	Skip . . . . .	270
DirectoryStack . . . . .	261	\$InputFileName . . . .	265	StreamPosition . . . .	270
EndOfFile . . . . .	261	InputStream . . . . .	266	Streams . . . . .	271
ExpandFileName . . . .	262	\$InstallationDirectory .	266	StringToStream . . . .	272
Expression . . . . .	262	Needs . . . . .	266	\$TemporaryDirectory .	272
File . . . . .	262	Number . . . . .	266	ToFileName . . . . .	272
FileBaseName . . . . .	262	OpenAppend . . . . .	266	Uncompress . . . . .	272
FileByteCount . . . . .	262	OpenRead . . . . .	266	Word . . . . .	272
FileDate . . . . .	262	OpenWrite . . . . .	266	Write . . . . .	272
FileExistsQ . . . . .	262	\$OperatingSystem . . .	266	WriteString . . . . .	273
FileExtension . . . . .	263	OutputStream . . . . .	267		
		ParentDirectory . . . .	267		

## AbsoluteFileName

`AbsoluteFileName["name"]`  
returns the absolute version of the given filename.

```
>> AbsoluteFileName["ExampleData/sunflowers.jpg"]
/src/external-vcs/github/mathics/Mathics/matl
```

## BinaryRead

`BinaryRead[stream]`  
reads one byte from the stream as an integer from 0 to 255.

`BinaryRead[stream, type]`  
reads one object of specified type from the stream.

`BinaryRead[stream, {type1, type2, ...}]`  
reads a sequence of objects of specified types.

```

>> strm = OpenWrite[BinaryFormat ->
    True]
    OutputStream [
        /tmp/tmpb0epk6sw,184]
>> BinaryWrite[strm, {97, 98, 99}]
    OutputStream [
        /tmp/tmpb0epk6sw,184]
>> Close[strm]
    /tmp/tmpb0epk6sw
>> strm = OpenRead[%, BinaryFormat
    -> True]
    InputStream [
        /tmp/tmpb0epk6sw,185]
>> BinaryRead[strm, {"Character8",
    "Character8", "Character8"}]
    {a,b,c}
>> Close[strm];

```

## BinaryWrite

BinaryWrite[channel, b]  
writes a single byte given as an integer from 0 to 255.

BinaryWrite[channel, {b1, b2, ...}]  
writes a sequence of byte.

BinaryWrite[channel, 'string']  
writes the raw characters in a string.

BinaryWrite[channel, x, type]  
writes x as the specified type.

BinaryWrite[channel, {x1, x2, ...}, type]  
writes a sequence of objects as the specified type.

BinaryWrite[channel, {x1, x2, ...}, {type1, type2, ...}]  
writes a sequence of objects using a sequence of specified types.

```

>> strm = OpenWrite[BinaryFormat ->
    True]
    OutputStream [
        /tmp/tmp5t5goyss,310]

```

```

>> BinaryWrite[strm, {39, 4, 122}]
    OutputStream [
        /tmp/tmp5t5goyss,310]
>> Close[strm]
    /tmp/tmp5t5goyss
>> strm = OpenRead[%, BinaryFormat
    -> True]
    InputStream [/tmp/tmp5t5goyss,311]
>> BinaryRead[strm]
    39
>> BinaryRead[strm, "Byte"]
    4
>> BinaryRead[strm, "Character8"]
    z
>> Close[strm];

```

Write a String

```

>> strm = OpenWrite[BinaryFormat ->
    True]
    OutputStream [
        /tmp/tmpcrcz9l83,312]
>> BinaryWrite[strm, "abc123"]
    OutputStream [
        /tmp/tmpcrcz9l83,312]
>> Close[%]
    /tmp/tmpcrcz9l83

```

Read as Bytes

```

>> strm = OpenRead[%, BinaryFormat
    -> True]
    InputStream [/tmp/tmpcrcz9l83,313]
>> BinaryRead[strm, {"Character8",
    "Character8", "Character8", "
    Character8", "Character8", "
    Character8", "Character8"}]
    {a,b,c,1,2,3,EndOfFile}
>> Close[strm]
    /tmp/tmpcrcz9l83

```

Read as Characters

```
>> strm = OpenRead[%, BinaryFormat
-> True]
InputStream [/tmp/tmpcrz9l83,314]

>> BinaryRead[strm, {"Byte", "Byte",
"Byte", "Byte", "Byte", "Byte",
"Byte"}]
{97,98,99,49,50,51,EndOfFile}

>> Close[strm]
/tmp/tmpcrz9l83
```

Write Type

```
>> strm = OpenWrite[BinaryFormat ->
True]
OutputStream [
/tmp/tmpesq8yrv7,315]

>> BinaryWrite[strm, 97, "Byte"]
OutputStream [
/tmp/tmpesq8yrv7,315]

>> BinaryWrite[strm, {97, 98, 99},
{"Byte", "Byte", "Byte"}]
OutputStream [
/tmp/tmpesq8yrv7,315]

>> Close[%]
/tmp/tmpesq8yrv7
```

## Byte

Byte  
is a data type for Read.

## Character

Character  
is a data type for Read.

## Close

Close[*stream*]  
closes an input or output stream.

```
>> Close[StringToStream["123abc"]]
String

>> Close[OpenWrite[]]
/tmp/tmpvdcjie3a
```

## Compress

Compress[*expr*]  
gives a compressed string representation  
of *expr*.

```
>> Compress[N[Pi, 10]]
eJwz1jM0MTS1NDIzNQEADRsCNw==
```

## CopyDirectory

CopyDirectory["*dir1*", "*dir2*"]  
copies directory *dir1* to *dir2*.

## CopyFile

CopyFile["*file1*", "*file2*"]  
copies *file1* to *file2*.

```
>> CopyFile["ExampleData/sunflowers
.jpg", "MathicsSunflowers.jpg"]
MathicsSunflowers.jpg

>> DeleteFile["MathicsSunflowers.
jpg"]
```

## CreateDirectory

CreateDirectory["*dir*"]  
creates a directory called *dir*.  
CreateDirectory[]  
creates a temporary directory.

```
>> dir = CreateDirectory[]
/tmp/m0rtjtkio
```

## DeleteDirectory

```
DeleteDirectory["dir"]  
    deletes a directory called dir.
```

```
>> dir = CreateDirectory[]  
    /tmp/m4ojpleyo  
  
>> DeleteDirectory[dir]  
  
>> DirectoryQ[dir]  
False
```

## DeleteFile

```
Delete["file"]  
    deletes file.  
Delete[{"file1", "file2", ...}]  
    deletes a list of files.
```

```
>> CopyFile["ExampleData/sunflowers  
.jpg", "MathicsSunflowers.jpg"];  
  
>> DeleteFile["MathicsSunflowers.  
jpg"]  
  
>> CopyFile["ExampleData/sunflowers  
.jpg", "MathicsSunflowers1.jpg  
"];  
  
>> CopyFile["ExampleData/sunflowers  
.jpg", "MathicsSunflowers2.jpg  
"];  
  
>> DeleteFile[{"MathicsSunflowers1.  
jpg", "MathicsSunflowers2.jpg"}]
```

## Directory

```
Directory[]  
    returns the current working directory.
```

```
>> Directory[]  
/src/external-vcs/github/mathics/Mathics
```

## DirectoryName

```
DirectoryName["name"]  
    extracts the directory name from a file-  
    name.
```

```
>> DirectoryName["a/b/c"]  
a/b  
  
>> DirectoryName["a/b/c", 2]  
a
```

## DirectoryQ

```
DirectoryQ["name"]  
    returns True if the directory called name  
    exists and False otherwise.
```

```
>> DirectoryQ["ExampleData/"]  
True  
  
>> DirectoryQ["ExampleData/  
MythicalSubdir/"]  
False
```

## DirectoryStack

```
DirectoryStack[]  
    returns the directory stack.
```

```
>> DirectoryStack[]  
{/src/external-vcs/github/mathics/Mathics}
```

## EndOfFile

```
EndOfFile  
    is returned by Read when the end of an  
    input stream is reached.
```

## ExpandFileName

```
ExpandFileName["name"]  
    expands name to an absolute filename for  
    your system.
```

```
>> ExpandFileName["ExampleData/
sunflowers.jpg"]
/src/external-vcs/github/mathics/Mathics/ExampleData/Sunflowers.jpg
```

## Expression

Expression  
is a data type for Read.

## File

### FileName

FileName["file"]  
gives the base name for the specified file name.

```
>> FileName["file.txt"]
file
>> FileName["file.tar.gz"]
file.tar
```

### FileByteCount

FileByteCount[file]  
returns the number of bytes in file.

```
>> FileByteCount["ExampleData/
sunflowers.jpg"]
142286
```

### FileDate

FileDate[file, types]  
returns the time and date at which the file was last modified.

```
>> FileDate["ExampleData/sunflowers
.jpg"]
{2120,9,7,7,16,33.2822}
```

```
>> FileDate["ExampleData/sunflowers
.jpg", "Access"]
{2121,2,15,1,40,43.5443}
```

```
>> FileDate["ExampleData/sunflowers
.jpg", "Creation"]
Missing[NotApplicable]
```

```
>> FileDate["ExampleData/sunflowers
.jpg", "Change"]
{2120,9,7,7,16,33.2822}
```

```
>> FileDate["ExampleData/sunflowers
.jpg", "Modification"]
{2120,9,7,7,16,33.2822}
```

```
>> FileDate["ExampleData/sunflowers
.jpg", "Rules"]
{Access -> {2121,2,15,1,40,
43.5443}, Creation -> Missing[
NotApplicable], Change -> {
2120,9,7,7,16,33.2822~
~2}, Modification -> {
2120,9,7,7,16,33.2822}}
```

### FileExistsQ

FileExistsQ["file"]  
returns True if file exists and False otherwise.

```
>> FileExistsQ["ExampleData/
sunflowers.jpg"]
True
>> FileExistsQ["ExampleData/
sunflowers.png"]
False
```

### FileExtension

FileExtension["file"]  
gives the extension for the specified file name.

```
>> FileExtension["file.txt"]
txt
```

```
>> FileExtension["file.tar.gz"]
gz
```

## FileHash

`FileHash[file]`  
returns an integer hash for the given *file*.

`FileHash[file, type]`  
returns an integer hash of the specified *type* for the given *file*.  
The types supported are “MD5”, “Adler32”, “CRC32”, “SHA”, “SHA224”, “SHA256”, “SHA384”, and “SHA512”.

`FileHash[file, type, format]`  
gives a hash code in the specified format.

```
>> FileHash["ExampleData/sunflowers
.jpg"]
109 937 059 621 979 839 ~
~952 736 809 235 486 742 106

>> FileHash["ExampleData/sunflowers
.jpg", "MD5"]
109 937 059 621 979 839 ~
~952 736 809 235 486 742 106

>> FileHash["ExampleData/sunflowers
.jpg", "Adler32"]
1 607 049 478

>> FileHash["ExampleData/sunflowers
.jpg", "SHA256"]
111 619 807 552 579 450 300 684 600 ~
~241 129 773 909 359 865 098 672 ~
~286 468 229 443 390 003 894 913 065
```

## FileInformation

`FileInformation["file"]`  
returns information about *file*.

This function is totally undocumented in MMA!

```
>> FileInformation["ExampleData/
sunflowers.jpg"]
{File
 - > /src/external-vcs/github/mathics/Mathics/ExampleD
FileType - > File, ByteCount - >
142 286, Date - > 6.96413 × 109}
```

## FileNameDepth

`FileNameDepth["name"]`  
gives the number of path parts in the given filename.

```
>> FileNameDepth["a/b/c"]
3

>> FileNameDepth["a/b/c/"]
3
```

## FileNameJoin

`FileNameJoin[{"dir_1", "dir_2", ...}]`  
joins the *dir\_i* together into one path.

```
>> FileNameJoin[{"dir1", "dir2", "
dir3"}]
dir1/dir2/dir3

>> FileNameJoin[{"dir1", "dir2", "
dir3"}, OperatingSystem -> "Unix
"]
dir1/dir2/dir3
```

## FileNameSplit

`FileNameSplit["filenams"]`  
splits a *filename* into a list of parts.

```
>> FileNameSplit["example/path/file
.txt"]
{example, path, file.txt}
```

## FileNameTake

```
FileNameTake["file"]
  returns the last path element in the file
  name name.
FileNameTake["file", n]
  returns the first n path elements in the file
  name name.
FileNameTake["file",  $\$-n\$$ ]
  returns the last n path elements in the file
  name name.
```

```
>> FileNameTake["/tmp/file.txt"]
file.txt
>> FileNameTake["tmp/file.txt", 1]
tmp
>> FileNameTake["tmp/file.txt", -1]
file.txt
```

## FilePrint

```
FilePrint[file]
  prints the raw contents of file.
```

## FileType

```
FileType["file"]
  gives the type of a file, a string. This is
  typically File, Directory or None.
```

```
>> FileType["ExampleData/sunflowers
.jpg"]
File
>> FileType["ExampleData"]
Directory
>> FileType["ExampleData/
nonexistent"]
None
```

## Find

```
Find[stream, text]
  find the first line in stream that contains
  text.
```

```
>> str = OpenRead["ExampleData/
EinsteinSzilLetter.txt"];
>> Find[str, "uranium"]
in manuscript, leads me
to expect that the element
uranium may be turned into
>> Find[str, "uranium"]
become possible to set up
a nuclear chain reaction in
a large mass of uranium,
>> Close[str]
ExampleData/EinsteinSzilLetter.txt
>> str = OpenRead["ExampleData/
EinsteinSzilLetter.txt"];
>> Find[str, {"energy", "power"} ]
a new and important source
of energy in the immediate
future. Certain aspects
>> Find[str, {"energy", "power"} ]
by which vast amounts of
power and large quantities
of new radium-like
>> Close[str]
ExampleData/EinsteinSzilLetter.txt
```

## FindFile

```
FindFile[name]
  searches $Path for the given filename.
```

```
>> FindFile["ExampleData/sunflowers
.jpg"]
/src/external-vcs/github/mathics/Mathics/mathics/data/
>> FindFile["VectorAnalysis"]
/src/external-vcs/github/mathics/Mathics/mathics/pack
```



```
>> FindFile["VectorAnalysis`
VectorAnalysis`"]
/src/external-vcs/github/mathics/Mathics/mathics/packages/VectorAnalysis/VectorAnalysis.m

>> Get["/tmp/example_file"]
"x"cannotbefollowedby"
packages/VectorAnalysis/VectorAnalysis.m

>> DeleteFile[filename]
```

## FindList

`FindList[file, text]`  
returns a list of all lines in *file* that contain *text*.

`FindList[file, {text1, text2, ...}]`  
returns a list of all lines in *file* that contain any of the specified string.

`FindList[{file1, file2, ...}, ...]`  
returns a list of all lines in any of the *filei* that contain the specified strings.

```
>> str = FindList["ExampleData/
EinsteinSzilLetter.txt", "
uranium"];

>> FindList["ExampleData/
EinsteinSzilLetter.txt", "
uranium", 1]

{in manuscript, leads me
to expect that the element
uranium may be turned into}
```

## Get (<<)

`<<name`  
reads a file and evaluates each expression, returning only the last one.

```
>> filename = $TemporaryDirectory
<> "/example_file";

>> Put[x + y, filename]

>> Get[filename]
"x"cannotbefollowedby"
text{+}y"(line1of"/tmp/example_file").

>> filename = $TemporaryDirectory
<> "/example_file";

>> Put[x + y, 2x^2 + 4z!, Cos[x] +
I Sin[x], filename]
```

## \$HomeDirectory

`$HomeDirectory`  
returns the users HOME directory.

```
>> $HomeDirectory
/home/rocky
```

## \$InitialDirectory

`$InitialDirectory`  
returns the directory from which *Mathics* was started.

```
>> $InitialDirectory
/src/external-vcs/github/mathics/Mathics
```

## \$Input

`$Input`  
is the name of the stream from which input is currently being read.

```
>> $Input
```

## \$InputFileName

`$InputFileName`  
is the name of the file from which input is currently being read.

While in interactive mode, `$InputFileName` is "".

```
>> $InputFileName
/tmp/example_file
```

## InputStream

`InputStream[name, n]`  
represents an input stream.

```
>> str = StringToStream["Mathics is cool!"]
      InputStream[String, 375]
>> Close[str]
      String
```

## \$InstallationDirectory

`$InstallationDirectory`  
returns the directory in which *Mathics* was installed.

```
>> $InstallationDirectory
      /src/external-vcs/github/mathics/Mathics/mathics
```

## Needs

`Needs["context"]`  
loads the specified context if not already in `$Packages`.

```
>> Needs["VectorAnalysis"]
```

## Number

`Number`  
is a data type for `Read`.

## OpenAppend

`OpenAppend['file']`  
opens a file and returns an `OutputStream` to which writes are appended.

```
>> OpenAppend[]
      OutputStream[
        /tmp/tmpejv607h2, 385]
```

## OpenRead

`OpenRead['file']`  
opens a file and returns an `InputStream`.

```
>> OpenRead["ExampleData/
      EinsteinSzilLetter.txt"]
      InputStream[
        ExampleData/EinsteinSzilLetter.txt,
        391]
>> OpenRead["https://raw.
      githubusercontent.com/mathics/
      Mathics/master/README.rst"]
      InputStream[
        https://raw.githubusercontent.com/mathics/Mathics/master/
        README.rst, 392]
>> Close[%];
```

## OpenWrite

`OpenWrite['file']`  
opens a file and returns an `OutputStream`.

```
>> OpenWrite[]
      OutputStream[
        /tmp/tmpwi_jgq0y, 396]
```

## \$OperatingSystem

`$OperatingSystem`  
gives the type of operating system running *Mathics*.

```
>> $OperatingSystem
      Unix
```

## OutputStream

`OutputStream[name, n]`  
represents an output stream.

```
>> OpenWrite[]
      OutputStream [
        /tmp/tmpu_9eznsb, 399]

>> Close[%]
      /tmp/tmpu_9eznsb
```

## ParentDirectory

ParentDirectory[]  
returns the parent of the current working directory.  
ParentDirectory["dir"]  
returns the parent *dir*.

```
>> ParentDirectory[]
      /src/external-vcs/github/mathics
```

## \$Path

\$Path  
returns the list of directories to search when looking for a file.

```
>> $Path
      {., /home/rocky,
       /src/external-vcs/github/mathics/Mathics/mathics/data,
       /src/external-vcs/github/mathics/Mathics/mathics/packages}
```

## \$PathnameSeparator

\$PathnameSeparator  
returns a string for the separator in paths.

```
>> $PathnameSeparator
      /
```

## Put (>>)

*expr* >> *filename*  
write *expr* to a file.  
Put [*expr1*, *expr2*, ..., *filename*]  
write a sequence of expressions to a file.

```
>> Put[40!, fortyfactorial]
      fortyfactorialisnotstring,
      InputStream[], orOutputStream[]
      815 915 283 247 897 734 345 ~
      ~611 269 596 115 894 272 ~
      ~000 000 000»fortyfactorial

>> filename = $TemporaryDirectory
      <> "/fortyfactorial";

>> Put[40!, filename]

>> FilePrint[filename]
      815 915 283 247 897 734 345 611 ~
      ~269 596 115 894 272 000 000 000

>> Get[filename]
      815 915 283 247 897 734 345 611 ~
      ~269 596 115 894 272 000 000 000

>> DeleteFile[filename]

>> filename = $TemporaryDirectory
      <> "/fiftyfactorial";

>> Put[10!, 20!, 30!, filename]

>> FilePrint[filename]
      3 628 800
      2 432 902 008 176 640 000
      265 252 859 812 191 ~
      ~058 636 308 480 000 000

>> DeleteFile[filename]

=

>> filename = $TemporaryDirectory
      <> "/example_file";

>> Put[x + y, 2x^2 + 4z!, Cos[x] +
      I Sin[x], filename]
```

```

>> FilePrint[filename]
x
  text{+}y
2 * x{{
  wedge}2
  text{+}4 * z!

  text{Cos}
  left[x
  right]
  text{+}I *
  text{Sin}
  left[x
  right]

>> DeleteFile[filename]

>> x >> /var/
Cannotopen/var/.
x>/var/

>> x >> /proc/uptime
Cannotopen/proc/uptime.
x>/proc/uptime

>> x >> /dev/full
Nospacelefttondevice.

```

## PutAppend (>>>)

```

expr >>> filename
  append expr to a file.
PutAppend[expr1, expr2, ..., '$'
filename'$']'
  write a sequence of expressions to a file.

```

```

>> Put[50!, "factorials"]

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000

>> PutAppend[10!, 20!, 30!, "
factorials"]

```

```

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000

>> 60! >>> "factorials"

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000
8 320 987 112 741 390 144 ~
~276 341 183 223 364 380 754 ~
~172 606 361 245 952 449 277 ~
~696 409 600 000 000 000 000

>> "string" >>> factorials

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000
8 320 987 112 741 390 144 ~
~276 341 183 223 364 380 754 ~
~172 606 361 245 952 449 277 ~
~696 409 600 000 000 000 000
"string"

```

## Read

```

Read[stream]
  reads the input stream and returns one
  expression.
Read[stream, type]
  reads the input stream and returns an ob-
  ject of the given type.

```

```
>> str = StringToStream["abc123"];

>> Read[str, String]
abc123

>> str = StringToStream["abc 123"];

>> Read[str, Word]
abc

>> Read[str, Word]
123

>> str = StringToStream["123, 4"];

>> Read[str, Number]
123

>> Read[str, Number]
4

>> str = StringToStream["123 abc"];

>> Read[str, {Number, Word}]
{123, abc}
```

## ReadList

```
ReadList["file"]
  Reads all the expressions until the end of
  file.
ReadList["file", type]
  Reads objects of a specified type until the
  end of file.
ReadList["file", {type1, type2, ...}]
  Reads a sequence of specified types until
  the end of file.

>> ReadList[StringToStream["a 1 b
2"], {Word, Number}]
{{a, 1}, {b, 2}}

>> str = StringToStream["abc123"];

>> ReadList[str]
{abc123}

>> InputForm[%]
{"abc123"}
```

## Record

```
Record
  is a data type for Read.
```

## RenameDirectory

```
RenameDirectory["dir1", "dir2"]
  renames directory dir1 to dir2.
```

## RenameFile

```
RenameFile["file1", "file2"]
  renames file1 to file2.
```

```
>> CopyFile["ExampleData/sunflowers
.jpg", "MathicsSunflowers.jpg"]
MathicsSunflowers.jpg

>> RenameFile["MathicsSunflowers.
jpg", "MathicsSunnyFlowers.jpg"]
MathicsSunnyFlowers.jpg

>> DeleteFile["MathicsSunnyFlowers.
jpg"]
```

## ResetDirectory

```
ResetDirectory[]
  pops a directory from the directory stack
  and returns it.
```

```
>> ResetDirectory[]
Directorystackisempty.
/src/external-vcs/github/mathics/Mathics
```

## \$RootDirectory

```
$RootDirectory
  returns the system root directory.
```

```
>> $RootDirectory
/
```

## SetDirectory

```
SetDirectory[dir]  
sets the current working directory to dir.
```

```
>> SetDirectory[]  
/home/rocky
```

## SetFileDate

```
SetFileDate["file"]  
set the file access and modification dates  
of file to the current date.  
SetFileDate["file", date]  
set the file access and modification dates  
of file to the specified date list.  
SetFileDate["file", date, "type"]  
set the file date of file to the specified date  
list. The "type" can be one of "Access",  
"Creation", "Modification", or All.
```

Create a temporary file (for example purposes)

```
>> tmpfilename =  
$TemporaryDirectory <> "/tmp0";  
  
>> Close[OpenWrite[tmpfilename]];  
  
>> SetFileDate[tmpfilename, {2002,  
1, 1, 0, 0, 0.}, "Access"];  
  
>> FileDate[tmpfilename, "Access"]  
{2002, 1, 1, 0, 0, 0.}
```

## SetStreamPosition

```
SetStreamPosition[stream, n]  
sets the current position in a stream.
```

```
>> str = StringToStream["Mathics is  
cool!"]  
InputStream[String, 482]  
  
>> SetStreamPosition[str, 8]  
8  
  
>> Read[str, Word]  
is
```

```
>> SetStreamPosition[str, Infinity]  
16
```

## Skip

```
Skip[stream, type]  
skips ahead in an input stream by one  
object of the specified type.  
Skip[stream, type, n]  
skips ahead in an input stream by n ob-  
jects of the specified type.
```

```
>> str = StringToStream["a b c d"];  
  
>> Read[str, Word]  
a  
  
>> Skip[str, Word]  
  
>> Read[str, Word]  
c  
  
>> str = StringToStream["a b c d"];  
  
>> Read[str, Word]  
a  
  
>> Skip[str, Word, 2]  
  
>> Read[str, Word]  
d
```

## StreamPosition

```
StreamPosition[stream]  
returns the current position in a stream as  
an integer.
```

```
>> str = StringToStream["Mathics is  
cool!"]  
InputStream[String, 491]  
  
>> Read[str, Word]  
Mathics  
  
>> StreamPosition[str]  
7
```

## Streams

`Streams []`

returns a list of all open streams.

```
>> Streams []
{InputStream [<stdin>, 0],
 OutputStream [<stdout>,
 1], OutputStream [<stderr>,
 2], OutputStream [
MathicsNonExampleFile,
 383], OutputStream [
/tmp/tmpmsvbecv1, 384],
 OutputStream [/tmp/tmpejv607h2,
 385], InputStream [
/src/external-vcs/github/mathics/Mathics/mathics/data,
 389], InputStream [
/src/external-vcs/github/mathics/Mathics/mathics/data,
 391], OutputStream [
/tmp/tmp3zujv7ke, 395],
 OutputStream [/tmp/tmpwi_jgq0y,
 396], InputStream [
String, 452], InputStream [
String, 462], InputStream [
String, 463], InputStream [
String, 464], InputStream [
String, 465], InputStream [
String, 466], InputStream [
String, 467], InputStream [
String, 468], InputStream [
String, 469], InputStream [
String, 470], InputStream [
String, 472], InputStream [
String, 473], InputStream [
String, 474], InputStream [
String, 475], InputStream [
String, 476], InputStream [
String, 480], InputStream [
String, 481], InputStream [
String, 482], InputStream [
String, 485], InputStream [
String, 486], InputStream [
String, 487], InputStream [
String, 488], InputStream [
String, 489], InputStream [
String, 490], InputStream [
String, 491], OutputStream [
/tmp/tmpkexkdcrm, 492]}
```

## StringToStream

`StringToStream[string]`  
converts a *string* to an open input stream.

```
>> strm = StringToStream["abc 123"]
      InputStream [String, 495]
```

## \$TemporaryDirectory

`$TemporaryDirectory`  
returns the directory used for temporary files.

```
>> $TemporaryDirectory
      /tmp
```

## ToFileName

`ToFileName[{"dir_1", "dir_2", ...}]`  
joins the *dir\_i* together into one path.

`ToFileName` has been superseded by `FileNameJoin`.

```
>> ToFileName[{"dir1", "dir2"}, "file"]
      dir1/dir2/file
>> ToFileName["dir1", "file"]
      dir1/file
>> ToFileName[{"dir1", "dir2", "dir3"}]
      dir1/dir2/dir3
```

## Uncompress

`Uncompress["string"]`  
recovers an expression from a string generated by `Compress`.

```
>> Compress["Mathics is cool"]
      eJxT8k0sychMLlbILFZlzs/PUQIANFwF1w==
```

```
>> Uncompress[%]
      Mathics is cool
>> a = x ^ 2 + y Sin[x] + 10 Log [15];
>> b = Compress[a];
>> Uncompress[b]
      x2 + ySin[x] + 10Log[15]
```

## Word

`Word`  
is a data type for `Read`.

## Write

`Write[channel, expr1, expr2, ...]`  
writes the expressions to the output channel followed by a newline.

```
>> str = OpenWrite[]
      OutputStream [
        /tmp/tmp4r3ec3av, 500]
>> Write[str, 10 x + 15 y ^ 2]
>> Write[str, 3 Sin[z]]
>> Close[str]
      /tmp/tmp4r3ec3av
>> str = OpenRead[%];
>> ReadList[str]
      {10 x + 15 y ^ 2, 3 Sin[z]}
```

## WriteString

`WriteString[stream, $str1, str2, ...]`  
writes the strings to the output stream.

```
>> str = OpenWrite[];
>> WriteString[str, "This is a test 1"]
```



```
>> WriteString[str, "This is also a  
test 2"]  
  
>> Close[str]  
/tmp/tmpfb3fz1xh  
  
>> FilePrint[%]  
Thisisatest1Thisisalsoatest2  
  
>> str = OpenWrite[];  
  
>> WriteString[str, "This is a test  
1", "This is also a test 2"]  
  
>> Close[str]  
/tmp/tmpkcy1an0j  
  
>> FilePrint[%]  
Thisisatest1Thisisalsoatest2
```

# XLIV. Importing and Exporting

## Contents

Sys-	tem'Convert'B64Dump'B64Decode	274	Sys-	tem'ConvertersDump'\$formatMappings	275	ImportString	277	
Sys-	tem'Convert'B64Dump'B64Encode	274	Sys-	tem'ConvertersDump'\$formatMappings	275	port'RegisterExport	277	
Sys-	tem'Convert'CommonDump'RemoveLinearSyntax	274	Sys-	tem'ConvertersDump'\$formatMappings	275	ImportEx-	port'RegisterImport	278
Sys-	tem'ConvertersDump'\$extensionMappings	276	Sys-	tem'ConvertersDump'\$extensionMappings	276	URLFetch	278	

### System'Convert'B64Dump'B64Decode

System'Convert'B64Dump'B64Decode[  
*string*]  
Decode *string* in Base64 coding to an ex-  
pression.

```
>> System'Convert'B64Dump'B64Decode  
["R!="]  
String"R!  
="isnotavalidb64encodedstring.  
$Failed
```

```
System'Convert'B64Dump'B64Decode  
[%]  
Integrate[f[x], {x, 0, 2}]  
  
>> System'Convert'B64Dump'B64Encode  
["Sf dx"]  
4oirIGYg752MIHg=  
  
>> System'Convert'B64Dump'B64Decode  
[%]  
f dx
```

### System'Convert'CommonDump'RemoveLin

### System'Convert'B64Dump'B64Encode

System'Convert'B64Dump'B64Encode[*expr*]  
Encodes *expr* in Base64 coding

```
>> System'Convert'B64Dump'B64Encode  
["Hello world"]  
SGVsbg8gd29ybGQ=  
  
>> System'Convert'B64Dump'B64Decode  
[%]  
Hello world  
  
>> System'Convert'B64Dump'B64Encode  
[Integrate[f[x], {x, 0, 2}]]  
SW50ZWdyYXRlW2ZbeF0sIHt4LCAwLCAyfV0=
```

System'Convert'CommonDump'  
RemoveLinearSyntax[*something*]  
Keine anung... Undocumented in wma

### System'ConvertersDump'\$extensionMapping

\$extensionMappings  
Returns a list of associations between file  
extensions and file types.

## System 'ConvertersDump'\$formatMappings

**\$formatMappings**  
Returns a list of associations between file extensions and file types.

## Export

**Export**["file.ext", *expr*]  
exports *expr* to a file, using the extension *ext* to determine the format.  
**Export**["file", *expr*, "*format*"]  
exports *expr* to a file in the specified format.  
**Export**["file", *exprs*, *elems*]  
exports *exprs* to a file as elements specified by *elems*.

## \$ExportFormats

**\$ExportFormats**  
returns a list of file formats supported by Export.

```
>> $ExportFormats
{BMP, Base64, CSV, GIF, JPEG,
  JPEG2000, PBM, PCX, PGM,
  PNG, PPM, SVG, TIFF, Text}
```

## ExportString

**ExportString**[*expr*, *form*]  
exports *expr* to a string, in the format *form*.  
**Export**["file", *exprs*, *elems*]  
exports *exprs* to a string as elements specified by *elems*.

```
>> ExportString
[{{1,2,3,4},{3},{2},{4}}, "CSV"]
1,2,3,4
3,
2,
4,
```

```
ExportString[{1,2,3,4}, "CSV"]
1,
2,
3,
4,

>> ExportString[Integrate[f[x],{x
,0,2}], "SVG"]
<svg><mstyle
  mathvariant="sans-serif">
  <mrow><msubsup>
    <mo></mo> <mn>0</mn>
    <mn>2</mn></msubsup>
    <mrow><mi>f</mi>
    <mo>[</mo> <mi>x</mi>
    <mo>]</mo></mrow> <mo
form="prefix" lspace="0"
rspace="0.2em"></mo>
<mrow><mtext></mtext>
<mi>x</mi></mrow>
</mrow></mstyle></svg>
```

## FileFormat

**FileFormat**["*name*"]  
attempts to determine what format Import should use to import specified file.

```
>> FileFormat["ExampleData/
sunflowers.jpg"]
JPEG

>> FileFormat["ExampleData/
EinsteinSzilLetter.txt"]
Text

>> FileFormat["ExampleData/lena.tif
"]
TIFF

>> FileFormat["ExampleData/benzene.
xyz"]
XYZ
```

## Import

```
Import["file"]
  imports data from a file.
Import["file", elements]
  imports the specified elements from a file.
Import["http://url", ...] and Import["ftp://url", ...]
  imports from a URL.
```

```
>> Import["ExampleData/ExampleData.txt", "Elements"]
{Data, Lines, Plaintext, String, Words}

>> Import["ExampleData/ExampleData.txt", "Lines"]
{Example File Format, Created
 by Angus, 0.629452 0.586355,
 0.711009 0.687453, 0.246540
 0.433973, 0.926871 0.887255,
 0.825141 0.940900, 0.847035
 0.127464, 0.054348 0.296494,
 0.838545 0.247025, 0.838697
 0.436220, 0.309496 0.833591}
```

```
>> Import["ExampleData/colors.json"]
{colorsArray
 - > {{colorName- > black,
  rgbValue- > (0, 0, 0),
  hexValue- > #000 000},
 {colorName- > red,
  rgbValue- > (255, 0, 0),
  hexValue- > #FF0 000},
 {colorName- > green,
  rgbValue- > (0, 255, 0),
  hexValue- > #00FF00},
 {colorName- > blue,
  rgbValue- > (0, 0, 255),
  hexValue- > #0 000FF},
 {colorName- > yellow,
  rgbValue- > (255, 255, 0),
  hexValue- > #FFFF00},
 {colorName- > cyan,
  rgbValue- > (0, 255, 255),
  hexValue- > #00FFFF},
 {colorName- > magenta,
  rgbValue- > (255, 0, 255),
  hexValue- > #FF00FF},
 {colorName- > white,
  rgbValue- > (255, 255, 255),
  hexValue- > #FFFFFF}}}
```

## \$ImportFormats

```
$ImportFormats
  returns a list of file formats supported by
  Import.
```

```
>> $ImportFormats
{BMP, Base64, CSV, GIF,
 ICO, JPEG, JPEG2 000, JSON,
 PBM, PCX, PGM, PNG, PPM,
 Package, TGA, TIFF, Text, XML}
```

## ImportString

```
ImportString["data", "format"]
    imports data in the specified format from
    a string.
ImportString["file", elements]
    imports the specified elements from a
    string.
ImportString["data"]
    attempts to determine the format of the
    string from its content.
```

```
>> str = "Hello!\n This is a
testing text\n";

>> ImportString[str, "Elements"]
{Data, Lines, Plaintext, String, Words}

>> ImportString[str, "Lines"]
{Hello!, This is a testing text}
```

## ImportExport‘RegisterExport

```
RegisterExport["format", func]
    register func as the default function used
    when exporting from a file of type "
    format".
```

Simple text exporter

```
>> ExampleExporter1[filename_,
    data_, opts___] := Module[{strm
    = OpenWrite[filename], char =
    data}, WriteString[strm, char];
    Close[strm]]

>> ImportExport‘RegisterExport["
    ExampleFormat1",
    ExampleExporter1]

>> Export["sample.txt", "Encode
    this string!", "ExampleFormat1
    "];

>> FilePrint["sample.txt"]
Encodethisstring!
```

Very basic encrypted text exporter

```
>> ExampleExporter2[filename_,
    data_, opts___] := Module[{strm
    = OpenWrite[filename], char}, (*
    TODO: Check data *)char =
    FromCharacterCode[Mod[
    ToCharacterCode[data] - 84, 26]
    + 97]; WriteString[strm, char];
    Close[strm]]

>> ImportExport‘RegisterExport["
    ExampleFormat2",
    ExampleExporter2]

>> Export["sample.txt", "
    encodethisstring", "
    ExampleFormat2"];

>> FilePrint["sample.txt"]
rapbqrguovffgevat
```

## ImportExport‘RegisterImport

```
RegisterImport["format", defaultFunction]
    register defaultFunction as the default
    function used when importing from a file
    of type "format".
RegisterImport["format", {"elem1" :>
    conditionalFunction1, "elem2" :> conditional-
    Function2, ..., defaultFunction}]
    registers multiple elements (elem1, ...)
    and their corresponding converter func-
    tions (conditionalFunction1, ...) in addition
    to the defaultFunction.
RegisterImport["format", {"
    conditionalFunctions, defaultFunction,
    "elem3" :> postFunction3, "elem4" :>
    postFunction4, ...}]
    also registers additional elements (elem3,
    ...) whose converters (postFunction3, ...)
    act on output from the low-level func-
    tions.
```

First, define the default function used to import the data.

```
>> ExampleFormat1Import[
  filename_String] := Module[{
    stream, head, data}, stream =
    OpenRead[filename]; head =
    ReadList[stream, String, 2];
    data = Partition[ReadList[stream
    , Number], 2]; Close[stream]; {"
    Header" -> head, "Data" -> data
  }]
```

RegisterImport is then used to register the above function to a new data format.

```
>> ImportExport`RegisterImport["
  ExampleFormat1",
  ExampleFormat1Import]

>> FilePrint["ExampleData/
  ExampleData.txt"]

ExampleFileFormat
CreatedbyAngus
0.6294520.586355
0.7110090.687453
0.2465400.433973
0.9268710.887255
0.8251410.940900
0.8470350.127464
0.0543480.296494
0.8385450.247025
0.8386970.436220
0.3094960.833591

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat1", "
  Elements"}]

  {Data,Header}

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat1", "Header
  "}]]

  {Example File Format,
    Created by Angus}
```

Conditional Importer:

```
>> ExampleFormat2DefaultImport[
  filename_String] := Module[{
    stream, head}, stream = OpenRead
    [filename]; head = ReadList[
    stream, String, 2]; Close[stream
    ]; {"Header" -> head}]
```

```
>> ExampleFormat2DataImport[
  filename_String] := Module[{
    stream, data}, stream = OpenRead
    [filename]; Skip[stream, String,
    2]; data = Partition[ReadList[
    stream, Number], 2]; Close[
    stream]; {"Data" -> data}]

>> ImportExport`RegisterImport["
  ExampleFormat2", {"Data" :>
  ExampleFormat2DataImport,
  ExampleFormat2DefaultImport}]

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat2", "
  Elements"}]

  {Data,Header}

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat2", "Header
  "}]]

  {Example File Format,
    Created by Angus}

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat2", "Data
  "}]] // Grid

0.629452 0.586355
0.711009 0.687453
0.24654 0.433973
0.926871 0.887255
0.825141 0.9409
0.847035 0.127464
0.054348 0.296494
0.838545 0.247025
0.838697 0.43622
0.309496 0.833591
```

## URLFetch

URLFetch[URL]

Returns the content of URL as a string.

# **Part III.**

# **License**

# A. GNU General Public License

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program—to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers and authors protection, the GPL clearly explains that there is no warranty for this free software. For both users and authors sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.



# TERMS AND CONDITIONS

## 0. Definitions.

This License refers to version 3 of the GNU General Public License.

Copyright also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

The Program refers to any copyrightable work licensed under this License. Each licensee is addressed as you. Licensees and recipients may be individuals or organizations.

To modify a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a modified version of the earlier work or a work based on the earlier work.

A covered work means either the unmodified Program or a work based on the Program.

To propagate a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To convey a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying. An interactive user interface displays Appropriate Legal Notices to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

## 1. Source Code.

The source code for a work means the preferred form of the work for making modifications to it. Object code means any non-source form of a work.

A Standard Interface means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The System Libraries of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A Major Component, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The Corresponding Source for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

## **2. Basic Permissions.**

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sub-licensing is not allowed; section 10 makes it unnecessary.

## **3. Protecting Users' Legal Rights From Anti-Circumvention Law.**

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the works users, your or third parties legal rights to forbid circumvention of technological measures.

## **4. Conveying Verbatim Copies.**

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

## **5. Conveying Modified Source Versions.**

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to keep intact all notices.
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an aggregate if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

## 6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A User Product is either (1) a consumer product, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, normally used refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

Installation Information for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User

Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

## **7. Additional Terms.**

Additional permissions are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
  - b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
  - c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
  - d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
  - e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
  - f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.
- All other non-permissive additional terms are considered further restrictions within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

## **8. Termination.**

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

## **9. Acceptance Not Required for Having Copies.**

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

## **10. Automatic Licensing of Downstream Recipients.**

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An entity transaction is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

## **11. Patents.**

A contributor is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's contributor version.

A contributor's essential patent claims are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, control includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a patent license is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To grant such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. Knowingly relying means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is discriminatory if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

## **12. No Surrender of Others' Freedom.**

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

## **13. Use with the GNU Affero General Public License.**

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

## **14. Revised Versions of this License.**

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License or any later version applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

## **15. Disclaimer of Warranty.**

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM AS IS WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

## **16. Limitation of Liability.**

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

## **17. Interpretation of Sections 15 and 16.**

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

## **How to Apply These Terms to Your New Programs**

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the copyright line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year>  <name of author>
```

```
This program is free software: you can redistribute it and/or
  modify
it under the terms of the GNU General Public License as published
  by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program.  If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year>  <name of author>
  This program comes with ABSOLUTELY NO WARRANTY; for details type `
    show w`.
  This is free software, and you are welcome to redistribute it
  under certain conditions; type `show c' for details.
```

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an about box.

You should also get your employer (if you work as a programmer) or school, if any, to sign a copyright disclaimer for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.



## B. Included software and data

### Included data

*Mathics* includes data from Wikipedia that is published under the Creative Commons Attribution-Sharealike 3.0 Unported License and the GNU Free Documentation License contributed by the respective authors that are listed on the websites specified in "data/elements.txt".

### scriptaculous

Copyright © 2005-2008 Thomas Fuchs (<http://script.aculo.us>, <http://mir.aculo.us>)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the Software), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### Prototype

Copyright © 2005-2010 Sam Stephenson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### MathJax

Copyright © 2009-2010 Design Science, Inc.

Licensed under the Apache License, Version 2.0 (the “License”); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an “AS IS” BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

## Three.js

Copyright I 2010-2020 Three.js authors.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## pymimemagic

Copyright (c) 2009, Xiaohai Lu All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of the <ORGANIZATION> nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## SciPy

Copyright I 2001, 2002 Enthought, Inc. All rights reserved.

Copyright © 2003-2019 SciPy Developers. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Enthought nor the names of the SciPy Developers may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS AS IS AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

# Index

\$Aborted, 79  
\$ByteOrdering, 79  
\$CharacterEncoding, 178  
\$CharacterEncodings, 178  
\$CommandLine, 79  
\$Context, 69  
\$ContextPath, 69  
\$DateStringFormat, 39  
\$ExportFormats, 275  
\$Failed, 79  
\$HistoryLength, 28  
\$HomeDirectory, 265  
\$ImportFormats, 276  
\$InitialDirectory, 265  
\$Input, 265  
\$InputFileName, 265  
\$InstallationDirectory, 266  
\$IterationLimit, 29  
\$Line, 29  
\$Machine, 80  
\$MachineEpsilon, 254  
\$MachineName, 80  
\$MachinePrecision, 254  
\$MaxPrecision, 254  
\$MinPrecision, 254  
\$ModuleNumber, 70  
\$OperatingSystem, 266  
\$Packages, 80  
\$ParentProcessID, 80  
\$Path, 267  
\$PathnameSeparator, 267  
\$Post, 82  
\$Pre, 82  
\$PrePrint, 82  
\$PreRead, 82  
\$ProcessID, 80  
\$ProcessorType, 81  
\$RandomState, 74  
\$RecursionLimit, 30  
\$RootDirectory, 269  
\$ScriptCommandLine, 81  
\$SyntaxHandler, 82  
\$SystemID, 81  
\$SystemTimeZone, 39  
\$SystemWordLength, 81  
\$TemporaryDirectory, 272  
\$TimeZone, 40  
\$UseSansSerif, 54  
\$UserName, 81  
\$Version, 81  
\$VersionNumber, 81  
  
Abort, 32  
Abs, 93  
AbsoluteFileName, 258  
AbsoluteThickness, 152  
AbsoluteTime, 37  
AbsoluteTiming, 37  
Accumulate, 220  
AddTo, 126  
AiryAi, 201  
AiryAiPrime, 201  
AiryAiZero, 202  
AiryBi, 202  
AiryBiPrime, 202  
AiryBiZero, 202  
All, 221  
AllTrue, 65  
Alternatives, 86  
And, 65  
AngerJ, 202  
AnglePath, 145  
AngleVector, 146  
AnyTrue, 65  
Apart, 247  
Append, 221  
AppendTo, 221  
Apply, 138  
ApplyLevel, 138  
ArcCos, 146  
ArcCosh, 146  
ArcCot, 147  
ArcCoth, 147  
ArcCsc, 147  
ArcCsch, 147  
ArcSec, 147  
ArcSech, 147  
ArcSin, 147  
ArcSinh, 148  
ArcTan, 148  
ArcTanh, 148

Array, 221  
 ArrayDepth, 135  
 ArrayQ, 135  
 Arrow, 153  
 ArrowBox, 154  
 Arrowheads, 154  
 Association, 221  
 AssociationQ, 222  
 AtomQ, 138  
 Attributes, 121  
 Automatic, 154  
 Axis, 55  
  
 BarChart, 55  
 BaseForm, 45  
 Begin, 68  
 BeginPackage, 68  
 BernsteinBasis, 155  
 Bessel, 203  
 BesselJ, 203  
 BesselJZero, 203  
 BesselK, 203  
 BesselY, 203  
 BesselYZero, 203  
 BezierCurve, 155  
 BezierCurveBox, 155  
 BezierFunction, 155  
 Binarize, 191  
 BinaryImageQ, 191  
 BinaryRead, 258  
 BinaryWrite, 259  
 Binomial, 76  
 BitLength, 217  
 Black, 155  
 Blank, 87  
 BlankNullSequence, 87  
 BlankSequence, 87  
 Blend, 155  
 Block, 68  
 Blue, 156  
 Blur, 192  
 Boole, 93  
 BooleanQ, 110  
 Bottom, 56  
 BoxData, 45  
 BoxMatrix, 192  
 BrayCurtisDistance, 114  
 Break, 32  
 ButtonBox, 46  
 Byte, 260  
 ByteCount, 139  
  
 C, 177  
 CanberraDistance, 114  
 Cancel, 247  
  
 Cases, 222  
 Catalan, 244  
 Catch, 32  
 Catenate, 222  
 Ceiling, 217  
 Center, 46  
 CentralMoment, 222  
 Character, 260  
 CharacterRange, 178  
 Characters, 178  
 ChebyshevT, 204  
 ChebyshevU, 204  
 Check, 46  
 ChessboardDistance, 114  
 Chop, 253  
 Circle, 156  
 CircleBox, 157  
 Clear, 126  
 ClearAll, 127  
 ClearAttributes, 121  
 Close, 260  
 Closing, 192  
 ClusteringComponents, 222  
 CMYKColor, 156  
 Coefficient, 247  
 CoefficientList, 248  
 ColorCombine, 192  
 ColorConvert, 192  
 ColorData, 56  
 ColorDataFunction, 56  
 ColorDistance, 157  
 Colorize, 193  
 ColorNegate, 192  
 ColorQuantize, 192  
 ColorSeparate, 192  
 CombinatoricaOld'BinarySearch, 139  
 Compile, 105  
 CompiledCodeBox, 105  
 CompiledFunction, 105  
 Complement, 222  
 Complex, 93  
 Complexes, 212  
 ComplexInfinity, 244  
 Composition, 103  
 CompoundExpression, 32  
 Compress, 260  
 Condition, 87  
 Conjugate, 94  
 Constant, 122  
 ConstantArray, 223  
 ContainsOnly, 223  
 Context, 69  
 Contexts, 69  
 Continue, 33  
 ContinuedFraction, 171

CoprimeQ, 171  
 CopyDirectory, 260  
 CopyFile, 260  
 Correlation, 223  
 Cos, 148  
 Cosh, 148  
 CosineDistance, 114  
 Cot, 148  
 Coth, 148  
 Count, 223  
 Covariance, 223  
 CreateDirectory, 260  
 Cross, 115  
 Csc, 149  
 Csch, 149  
 CubeRoot, 94  
 Cuboid, 41  
 Cyan, 157  
  
 D, 212  
 DamerauLevenshteinDistance, 178  
 Darker, 157  
 DateDifference, 37  
 DateList, 38  
 DatePlus, 38  
 DateString, 39  
 Decrement, 127  
 Default, 107  
 DefaultValues, 127  
 Definition, 127  
 Degree, 244  
 Delete, 224  
 DeleteCases, 224  
 DeleteDirectory, 261  
 DeleteDuplicates, 225  
 DeleteFile, 261  
 Denominator, 248  
 DensityPlot, 56  
 Depth, 139  
 Derivative, 213  
 DesignMatrix, 115  
 Det, 115  
 DiagonalMatrix, 135  
 DiamondMatrix, 193  
 DiceDissimilarity, 76  
 DigitCharacter, 179  
 DigitCount, 217  
 DigitQ, 179  
 Dilation, 193  
 Dimensions, 135  
 DirectedInfinity, 94  
 Directive, 158  
 Directory, 261  
 DirectoryName, 261  
 DirectoryQ, 261  
  
 DirectoryStack, 261  
 DiscreteLimit, 213  
 DisjointQ, 225  
 Disk, 158  
 DiskBox, 159  
 DiskMatrix, 193  
 Divide, 94  
 DivideBy, 128  
 Divisors, 171  
 Do, 33  
 DominantColors, 193  
 Dot, 136  
 DownValues, 129  
 Drop, 225  
 DSolve, 177  
  
 E, 244  
 EasterSunday, 39  
 EdgeDetect, 194  
 EdgeForm, 159  
 EditDistance, 179  
 Eigensystem, 115  
 Eigenvalues, 115  
 Eigenvectors, 116  
 ElementData, 210  
 End, 69  
 EndOfFile, 261  
 EndOfLine, 180  
 EndOfString, 180  
 EndPackage, 70  
 Environment, 79  
 Equal, 110  
 Equivalent, 65  
 Erf, 204  
 Erfc, 204  
 Erosion, 194  
 EuclideanDistance, 116  
 EulerGamma, 245  
 Evaluate, 28  
 EvenQ, 172  
 ExactNumberQ, 95  
 Except, 88  
 Exp, 149  
 Expand, 249  
 ExpandAll, 249  
 ExpandDenominator, 249  
 ExpandFileName, 261  
 ExpIntegralE, 204  
 ExpIntegralEi, 205  
 Exponent, 250  
 Export, 275  
 ExportString, 275  
 Expression, 262  
 Extract, 225

- FaceForm, 159
- Factor, 250
- Factorial, 95
- FactorInteger, 172
- FactorTermsList, 250
- Failure, 225
- False, 66
- Fibonacci, 76
- File, 262
- FileBaseName, 262
- FileByteCount, 262
- FileDate, 262
- FileExistsQ, 262
- FileExtension, 262
- FileFormat, 275
- FileHash, 263
- FileInformation, 263
- FileNameDepth, 263
- FileNameJoin, 263
- FileNameSplit, 263
- FileNameTake, 264
- FilePrint, 264
- FileType, 264
- FilledCurve, 159
- FilledCurveBox, 159
- Filling, 57
- FilterRules, 107
- Find, 264
- FindClusters, 225
- FindFile, 264
- FindList, 265
- FindRoot, 214
- First, 226
- FirstCase, 226
- FirstPosition, 227
- FittedModel, 116
- FixedPoint, 33
- FixedPointList, 33
- Flat, 122
- Flatten, 139
- Floor, 217
- Fold, 227
- FoldList, 227
- FontColor, 159
- For, 34
- Format, 46
- FractionalPart, 172
- FreeQ, 140
- FresnelC, 205
- FresnelS, 205
- FromCharacterCode, 180
- FromContinuedFraction, 172
- FromDigits, 218
- Full, 58
- FullForm, 46

- Function, 103
- Gamma, 95
- Gather, 227
- GatherBy, 227
- GaussianFilter, 194
- GCD, 172
- GegenbauerC, 205
- General, 46
- Get, 265
- GetEnvironment, 79
- Glaisher, 245
- GoldenRatio, 245
- Graphics, 159
- Graphics3D, 42
- Graphics3DBox, 43
- GraphicsBox, 160
- Gray, 160
- GrayLevel, 161
- Greater, 111
- GreaterEqual, 111
- Green, 161
- Grid, 47
- GridBox, 47
- HammingDistance, 180
- HankelH1, 205
- HankelH2, 205
- HarmonicNumber, 96
- Hash, 253
- Haversine, 149
- Head, 140
- HermiteH, 205
- HexadecimalCharacter, 181
- Histogram, 58
- Hold, 28
- HoldAll, 122
- HoldAllComplete, 122
- HoldComplete, 28
- HoldFirst, 122
- HoldForm, 29
- HoldPattern, 88
- HoldRest, 122
- Hue, 161
- I, 96
- Identity, 104
- IdentityMatrix, 136
- If, 34
- Im, 96
- Image, 195
- ImageAdd, 194
- ImageAdjust, 195
- ImageAspectRatio, 195
- ImageBox, 195

- ImageChannels, 195
- ImageColorSpace, 195
- ImageConvolve, 195
- ImageData, 196
- ImageDimensions, 196
- ImageExport, 196
- ImageImport, 196
- ImageMultiply, 196
- ImagePartition, 196
- ImageQ, 197
- ImageReflect, 197
- ImageResize, 197
- ImageRotate, 197
- ImageSize, 58
- ImageSubtract, 198
- ImageTake, 198
- ImageType, 198
- Implies, 66
- Import, 276
- ImportExport'RegisterExport, 277
- ImportExport'RegisterImport, 277
- ImportString, 277
- In, 29
- Increment, 129
- Indeterminate, 245
- Inequality, 111
- InexactNumberQ, 96
- Infinity, 245
- Infix, 47
- Information, 129
- Inner, 136
- InputForm, 47
- InputStream, 266
- Insert, 228
- Inset, 162
- InsetBox, 162
- Integer, 96
- IntegerDigits, 218, 254
- IntegerExponent, 172
- IntegerLength, 219
- IntegerQ, 96
- IntegerReverse, 219
- Integers, 214
- IntegerString, 219
- Integrate, 214
- Internal'RealValuedNumberQ, 257
- Internal'RealValuedNumericQ, 257
- InterpretationBox, 47
- Interrupt, 34
- IntersectingQ, 228
- Intersection, 228
- Inverse, 116
- InverseErf, 205
- InverseErfc, 206
- InverseHaversine, 149

- JaccardDissimilarity, 76
- JacobiP, 206
- Join, 228
- Joined, 58
- KelvinBei, 206
- KelvinBer, 206
- KelvinKei, 206
- KelvinKer, 207
- Key, 228
- Keys, 229
- Khinchin, 245
- KnownUnitQ, 83
- Kurtosis, 229
- LABColor, 162
- LaguerreL, 207
- Large, 162
- Last, 229
- LCHColor, 162
- LCM, 173
- LeafCount, 229
- LeastSquares, 116
- Left, 47
- LegendreP, 207
- LegendreQ, 208
- Length, 229
- LerchPhi, 208
- Less, 111
- LessEqual, 111
- LetterCharacter, 181
- LetterQ, 181
- Level, 230
- LevelQ, 230
- Lighter, 162
- LightRed, 162
- Limit, 215
- Line, 163
- Line3DBox, 43
- LinearModelFit, 117
- LinearSolve, 117
- LineBox, 163
- List, 230
- Listable, 123
- ListLinePlot, 58
- ListPlot, 59
- ListQ, 230
- LoadModule, 129
- Locked, 123
- Log, 149
- Log10, 150
- Log2, 150
- LogisticSigmoid, 150
- Longest, 88
- Lookup, 231



LowerCaseQ, 181  
 LUVColor, 162  
  
 MachineNumberQ, 97  
 MachinePrecision, 254  
 Magenta, 163  
 MakeBoxes, 47  
 ManhattanDistance, 117  
 Manipulate, 170  
 MantissaExponent, 173  
 Map, 140  
 MapAt, 141  
 MapIndexed, 141  
 MapThread, 142  
 MatchingDissimilarity, 77  
 MatchQ, 88  
 MathicsVersion, 80  
 MathMLForm, 48  
 MatrixExp, 118  
 MatrixForm, 48  
 MatrixPower, 118  
 MatrixQ, 136  
 MatrixRank, 118  
 Max, 111  
 MaxFilter, 198  
 Maximize, 190  
 Mean, 231  
 Median, 231  
 MedianFilter, 198  
 Medium, 164  
 MemberQ, 231  
 Mesh, 59  
 Message, 48  
 MessageName, 48  
 Messages, 130  
 Min, 112  
 MinFilter, 198  
 MinimalPolynomial, 250  
 Minimize, 190  
 Minus, 97  
 Missing, 251  
 Mod, 173  
 Module, 70  
 MorphologicalComponents, 199  
 Most, 231  
 MPMathConstant, 245  
 Multinomial, 77  
  
 N, 255  
 Names, 80  
 Nearest, 232  
 Needs, 266  
 Negative, 112  
 Nest, 34  
 NestList, 34  
  
 NestWhile, 35  
 NextPrime, 173  
 NHoldAll, 123  
 NHoldFirst, 123  
 NHoldRest, 123  
 NonAssociative, 48  
 None, 232  
 NoneTrue, 66  
 NonNegative, 112  
 NonPositive, 112  
 Norm, 118  
 Normalize, 118  
 Not, 66  
 NotListQ, 232  
 NotOptionQ, 107  
 Null, 142  
 NullSpace, 118  
 Number, 266  
 NumberForm, 49  
 NumberQ, 97  
 NumberString, 181  
 Numerator, 251  
 NumericQ, 256  
 NumpyConstant, 245  
 NValues, 130  
  
 OddQ, 173  
 Off, 49  
 Offset, 164  
 On, 49  
 OneIdentity, 123  
 OpenAppend, 266  
 Opening, 199  
 OpenRead, 266  
 OpenWrite, 266  
 Operate, 142  
 Optional, 88  
 OptionQ, 108  
 Options, 108  
 OptionsPattern, 89  
 OptionValue, 108  
 Or, 66  
 Orange, 164  
 Order, 142  
 OrderedQ, 142  
 Orderless, 124  
 Out, 29  
 Outer, 136  
 OutputForm, 49  
 OutputStream, 266  
 OwnValues, 130  
  
 PadLeft, 232  
 PadRight, 233  
 ParametricPlot, 60

- ParentDirectory, 267
- Part, 233
- Partition, 234
- Pattern, 89
- PatternsOrderedQ, 142
- PatternTest, 89
- Pause, 39
- Permutations, 234
- Pi, 245
- Pick, 235
- Piecewise, 97
- PieChart, 60
- PillowImageFilter, 199
- PixelValue, 199
- PixelValuePositions, 199
- Plot, 62
- Plot3D, 63
- PlotPoints, 64
- PlotRange, 64
- Plus, 98
- Pochhammer, 98
- Point, 164
- Point3DBox, 43
- PointBox, 165
- PointSize, 165
- PolarPlot, 64
- Polygon, 165
- Polygon3DBox, 43
- PolygonBox, 165
- PolynomialQ, 251
- Position, 235
- Positive, 112
- PossibleZeroQ, 98
- Postfix, 49
- Power, 99
- PowerExpand, 251
- PowerMod, 173
- Precedence, 50
- Precision, 256
- PreDecrement, 131
- Prefix, 50
- PreIncrement, 131
- Prepend, 235
- PrependTo, 235
- Prime, 174
- PrimePi, 174
- PrimePowerQ, 174
- PrimeQ, 174
- Print, 50
- Product, 99
- ProductLog, 208
- Protect, 124
- Protected, 124
- PseudoInverse, 119
- Purple, 165
- Put, 267
- PutAppend, 268
- PythonForm, 50
- QRDecomposition, 119
- Quantile, 236
- Quantity, 83
- QuantityMagnitude, 83
- QuantityQ, 83
- QuantityUnit, 84
- Quartiles, 236
- Quiet, 51
- Quit, 30
- Quotient, 175
- QuotientRemainder, 175
- Random, 72
- RandomChoice, 72
- RandomComplex, 73
- RandomImage, 199
- RandomInteger, 73
- RandomPrime, 175
- RandomReal, 73
- RandomSample, 74
- Range, 236
- RankedMax, 236
- RankedMin, 236
- Rational, 100
- Rationalize, 256
- Re, 100
- Read, 268
- ReadList, 269
- ReadProtected, 125
- Real, 100
- RealDigits, 256
- RealNumberQ, 100
- Reals, 215
- Reap, 236
- Record, 269
- Rectangle, 166
- RectangleBox, 167
- Red, 167
- RegularExpression, 181
- RegularPolygon, 167
- RegularPolygonBox, 168
- ReleaseHold, 30
- RemoveDiacritics, 181
- RenameDirectory, 269
- RenameFile, 269
- Repeated, 90
- RepeatedNull, 90
- Replace, 90
- ReplaceAll, 91
- ReplaceList, 91
- ReplacePart, 237

ReplaceRepeated, 91  
 ResetDirectory, 269  
 Rest, 237  
 Return, 35  
 Reverse, 237  
 RGBColor, 166  
 Riffle, 238  
 Right, 51  
 RogersTanimotoDissimilarity, 77  
 Root, 215  
 RotateLeft, 238  
 RotateRight, 238  
 Round, 257  
 Row, 51  
 RowBox, 51  
 RowReduce, 119  
 RSolve, 85  
 Rule, 92  
 RuleDelayed, 92  
 Run, 81  
 RussellRaoDissimilarity, 77  
  
 SameQ, 112  
 Scan, 143  
 Sec, 150  
 Sech, 150  
 SeedRandom, 74  
 Select, 238  
 Sequence, 30  
 SequenceHold, 125  
 SessionTime, 39  
 Set, 131  
 SetAttributes, 125  
 SetDelayed, 132  
 SetDirectory, 270  
 SetFileDate, 270  
 SetStreamPosition, 270  
 Sharpen, 199  
 Shortest, 92  
 Show, 168  
 Sign, 100  
 Simplify, 251  
 Sin, 150  
 SingularValueDecomposition, 119  
 Sinh, 151  
 Skewness, 239  
 Skip, 270  
 Slot, 104  
 SlotSequence, 104  
 Small, 168  
 SokalSneathDissimilarity, 77  
 Solve, 215  
 Sort, 143  
 SortBy, 143  
 Sow, 239  
  
 Span, 239  
 Sphere, 43  
 Sphere3DBox, 44  
 SphericalHarmonicY, 208  
 Split, 239  
 SplitBy, 239  
 Sqrt, 100  
 SquaredEuclideanDistance, 120  
 StandardDeviation, 240  
 StandardForm, 51  
 StartOfLine, 182  
 StartOfString, 182  
 StirlingS1, 77  
 StirlingS2, 78  
 StreamPosition, 270  
 Streams, 271  
 String, 187  
 StringCases, 182  
 StringContainsQ, 183  
 StringDrop, 183  
 StringExpression, 183  
 StringForm, 51  
 StringFreeQ, 184  
 StringInsert, 184  
 StringJoin, 184  
 StringLength, 185  
 StringMatchQ, 185  
 StringPosition, 185  
 StringQ, 185  
 StringRepeat, 186  
 StringReplace, 186  
 StringRiffle, 186  
 StringSplit, 186  
 StringTake, 187  
 StringToStream, 272  
 StringTrim, 187  
 StruveH, 208  
 StruveL, 209  
 Style, 52  
 StyleBox, 52  
 Subscript, 52  
 SubscriptBox, 52  
 SubsetQ, 240  
 Subsets, 78  
 Subsuperscript, 52  
 SubsuperscriptBox, 52  
 Subtract, 101  
 SubtractFrom, 132  
 SubValues, 132  
 Sum, 101  
 Superscript, 52  
 SuperscriptBox, 52  
 Switch, 35  
 Symbol, 144  
 SymbolName, 143

SymbolQ, 143  
 SympyComparison, 113  
 SympyConstant, 246  
 SympyForm, 52  
 Syntax, 52  
 System'Convert'B64Dump'B64Decode, 274  
 System'Convert'B64Dump'B64Encode, 274  
 System'Convert'CommonDump'RemoveLinearSyntax, 274  
 System'ConvertersDump'\$extensionMappings, 274  
 System'ConvertersDump'\$formatMappings, 275  
 System'Private'\$ContextPathStack, 69  
 System'Private'\$ContextStack, 69  
 System'Private'ManipulateParameter, 170  
  
 Table, 240  
 TableForm, 52  
 TagBox, 53  
 TagSet, 132  
 TagSetDelayed, 133  
 Take, 240  
 TakeLargest, 241  
 TakeLargestBy, 241  
 TakeSmallest, 241  
 TakeSmallestBy, 241  
 Tally, 242  
 Tan, 151  
 Tanh, 151  
 TemplateBox, 53  
 TeXForm, 53  
 Text, 168  
 TextData, 53  
 TextRecognize, 200  
 Thick, 168  
 Thickness, 168  
 Thin, 168  
 Thread, 144  
 Threshold, 200  
 Through, 144  
 Throw, 35  
 TimeConstrained, 40  
 TimeRemaining, 40  
 Times, 102  
 TimesBy, 133  
 TimeUsed, 40  
 Timing, 40  
 Tiny, 168  
 ToBoxes, 53  
 ToCharacterCode, 187  
 ToExpression, 188  
 ToFileName, 272  
 Together, 251  
 ToLowerCase, 188  
 TooltipBox, 53  
  
 Top, 64  
 ToString, 188  
 Total, 242  
 ToUpperCase, 188  
 Tr, 120  
 Transliterate, 188  
 Transpose, 137  
 True, 66  
 TrueQ, 113  
 Tuples, 242  
  
 Uncompress, 272  
 Unequal, 113  
 Unevaluated, 31  
 Union, 242  
 Unique, 70  
 UnitConvert, 84  
 UnitVector, 243  
 Unprotect, 125  
 UnsameQ, 113  
 Unset, 133  
 UpperCaseQ, 189  
 UpSet, 133  
 UpSetDelayed, 134  
 UpTo, 252  
 UpValues, 134  
 URLFetch, 278  
  
 ValueQ, 113  
 Values, 243  
 Variables, 252  
 Variance, 243  
 VectorAngle, 120  
 VectorQ, 137  
 Verbatim, 92  
  
 WeberE, 209  
 Which, 36  
 While, 36  
 White, 168  
 Whitespace, 189  
 WhitespaceCharacter, 189  
 With, 71  
 Word, 272  
 WordBoundary, 189  
 WordCharacter, 189  
 WordCloud, 200  
 Write, 272  
 WriteString, 272  
  
 XML'Parser'XMLGet, 176  
 XML'Parser'XMLGetString, 176  
 XML'PlaintextImport, 176  
 XML'TagsImport, 176  
 XML'XMLObjectImport, 176

XMLElement, 176  
XMLObject, 176  
Xor, 67  
XYZColor, 169  
  
Yellow, 169  
YuleDissimilarity, 78  
  
Zeta, 209