



*A free, open-source alternative to Mathematica*

The Mathics Team

July 3, 2021

# Contents

<b>I. Manual</b>	<b>5</b>
1. Introduction	6
2. Language Tutorials	8
3. Examples	21
4. Django-based Web Interface	24
<b>II. Reference of Built-in Symbols</b>	<b>27</b>
1. Date and Time	28
2. Input and Output	33
3. Procedural Programming	42
4. Global System Information	47
5. SparseArray Functions	51
6. Solving Recurrence Equations	52
7. Patterns and Rules	53
8. Mathematical Functions	60
9. Functional Programming	68
10. Code Compilation	70
11. Options and Default Arguments	72
12. Attributes	75
13. Tensors	80
14. Structural Operations	84
15. Drawing Graphics	91
16. Strings and Characters - Miscellaneous	103
17. Mathematical Optimization	107
18. Drawing Options and Option Values	108
19. Physical and Chemical data	113

20. List Functions - Miscellaneous	115
21. Numeric Evaluation and Precision	130
22. Arithmetic Functions	136
23. Basic Arithmetic	137
24. Sums, Simple Statistics	141
25. Colors	142
26. Color Directives	143
27. Color Operations	146
28. Named Colors	149
29. Distance and Similarity Measures	161
30. String Distances and Similarity Measures	162
31. Graphics, Drawing, and Images	164
32. Three-Dimensional Graphics	165
33. Image[] and image related functions.	168
34. Plotting	177
35. Splines	186
36. Input/Output, Files, and Filesystem	188
37. File and Stream Operations	189
38. Filesystem Operations	198
39. Importing and Exporting	206
40. The Main Loop	211
41. Integer Functions	214
42. Combinatorial Functions	215
43. Division-Related Functions	218
44. Recurrence and Sum Functions	221
45. List Functions	222
46. Constructing Lists	223
47. Elements of Lists	226
48. Integer and Number-Theoretical Functions	233
49. Algebraic Manipulation	234

50. Calculus	241
51. Mathematical Constants	247
52. Differential Equations	249
53. Exponential, Trigonometric and Hyperbolic Functions	250
54. Integer Functions	257
55. Linear algebra	260
56. Number theoretic functions	267
57. Random number generation	270
58. Special Functions	274
59. Bessel and Related Functions	275
60. Error Function and Related Functions	280
61. Exponential Integral and Special Functions	282
62. Gamma and Related Functions	283
63. Orthogonal Polynomials	284
64. Exponential Integral and Special Functions	286
65. Strings and Characters	287
66. Characters in Strings	288
67. Character Codes	290
68. Operations on Strings	292
69. String Patterns	296
70. Regular Expressions	300
71. File Formats	301
72. HTML	302
73. HTML	303
74. XML	304
<b>III. License</b>	<b>305</b>
A. GNU General Public License	306
B. Included software and data	315
Index	320

**Part I.**

**Manual**

# 1. Introduction

*Mathics*—to be pronounced like “Mathematics” without the “emat”—is a general-purpose computer algebra system (CAS). It is meant to be a free, open-source alternative to *Mathematica*®. It is free both as in “free beer” and as in “freedom”. *Mathics* can be run *Mathics* locally, and to facilitate installation of the vast amount of software need to run this, there is a docker image available. See <https://hub.docker.com/r/mathicsorg/mathics>.

The programming language of *Mathics* is meant to resemble *Wolfram*’s famous *Mathematica*® as much as possible. However, *Mathics* is in no way

affiliated or supported by *Wolfram*. *Mathics* will probably never have the power to compete with *Mathematica*® in industrial applications; yet, it is an alternative for educational purposes. It also invites community development at all levels.

See <https://mathics-development-guide.readthedocs.io/en/latest/installing/index.html> for the most recent instructions for installing from PyPI, source, or from *docker*.

For implementation details see <https://mathics-development-guide.readthedocs.io/en/latest/>.

## Contents

Why yet another CAS? . . . . .	6	What does it offer? . . . . .	7	Who is behind it? . . . . .	7
		What is missing? . . . . .	7		

## Why yet another CAS?

*Mathematica*® is great, but it a couple of disadvantages.

- It is not open source.
- Its development is tightly controled and centralized.

The last point some may find and advantage.

Even if you are willing to pay hundreds of dollars for the software, would will not be able to see what’s going on “inside” the program if that is your interest. That’s what free, open-source, and community-supported software is for!

*Mathics* aims at combining the best of both worlds: the beauty of *Mathematica*® backed by a free, extensible Python core which includes a rich set of Python tools including:

- `mpmath` <https://mpmath.org/> for floating-point arithmetic with arbitrary precision,
- `numpy` <https://numpy.org/numpy> for numeric computation,
- `sympy` <https://sympy.org> for symbolic mathematics, and

- optionally `scipy` <https://www.scipy.org/> for Scientific calculations.

Performance of *Mathics* is not, right now, practical in large-scale projects and calculations. However can be used as a tool for quick explorations and to educate people who might later switch to *Mathematica*®.

## What does it offer?

Some of the features of *Mathics* are:

- a powerful functional programming language,
- a system driven by pattern matching and rules application,
- rationals, complex numbers, and arbitrary-precision arithmetic,
- lots of list and structure manipulation routines,
- an interactive graphical user interface right in the Web browser using MathML (apart from a command line interface),
- creation of graphics (e.g. plots) and display in the browser using SVG for 2D

- graphics and three.js for 3D graphics,
- export of results to  $\text{\LaTeX}$  (using Asymptote for graphics),
- an easy way of defining new functions in Python and which hooks into Python libraries
- an integrated documentation and testing system.

## What is missing?

There are lots of ways in which *Mathics* could still be improved.

Most notably, performance is still slow. Although there are various ways to speed up Python, some serious work is needed in *Mathics*, to speed it up. This will be addressed in the future. Apart from performance issues, *Mathics* has about about half of the features and libraries of

*Mathematica*®.

Graphics has always been lagging and in the future we intend to decouple Graphics better so that the rich set of graphics packages that are out there can be more easily used.

## Who is behind it?

*Mathics* was created by Jan Pöschk in 2011. From 2013 to about 2017 it had been maintained mostly by Angus Griffith and Ben Jones. Since then, a number of others have been people involved in *Mathics*; the list can be found in the AUTHORS.txt file, <https://github.com/mathics/Mathics/blob/master/AUTHORS.txt>.

If you have any ideas on how to improve *Mathics* or even want to help out yourself, please contact us!

Welcome to *Mathics*, have fun!

## 2. Language Tutorials

The following sections are introductions to the basic principles of the language of *Mathics*. A few examples and functions are presented. Only their most common usages are listed; for a full description of a Symbols possible arguments, options, etc., see its entry in the Reference of

Built-in Symbols.

However if you google for “Mathematica Tutorials” you will find easily dozens of other tutorials which are applicable. Be warned though that *Mathics* does not yet offer the full range and features and capabilities of *Mathematica*®.

### Contents

---

Basic calculations . . .	9	Lists . . . . .	11	Graphics Introduction	
Symbols and		The Structure of Things	12	Examples . . . . .	19
Assignments . . .	10	Functions and Patterns	14	3D Graphics . . . . .	19
Comparisons and		Control Statements . .	14	Plotting Introduction	
Boolean Logic . .	10	Scoping . . . . .	15	Examples . . . . .	20
Strings . . . . .	10	Formatting Output . .	17		

---

### Basic calculations

*Mathics* can be used to calculate basic stuff:

```
>> 1 + 2
3
```

To submit a command to *Mathics*, press Shift+Return in the Web interface or Return in the console interface. The result will be printed in a new line below your query.

*Mathics* understands all basic arithmetic operators and applies the usual operator precedence. Use parentheses when needed:

```
>> 1 - 2 * (3 + 5) / 4
-3
```

The multiplication can be omitted:

```
>> 1 - 2 (3 + 5) / 4
-3
```

```
>> 2 4
8
```

Powers can be entered using ^:

```
>> 3 ^ 4
81
```

Integer divisions yield rational numbers:

```
>> 6 / 4
3
2
```

To convert the result to a floating point number, apply the function N:

```
>> N[6 / 4]
1.5
```

As you can see, functions are applied using square braces [ and ], in contrast to the common notation of ( and ). At first hand, this might seem strange, but this distinction between function application and precedence change is necessary to allow some general syntax structures, as you will see later.

*Mathics* provides many common mathematical functions and constants, e.g.:

```
>> Log[E]
1
```

```
>> Sin[Pi]
0
```

```
>> Cos[0.5]
0.877583
```

When entering floating point numbers in your query, *Mathics* will perform a numerical evalua-



tion and present a numerical result, pretty much like if you had applied  $N$ .

Of course, *Mathics* has complex numbers:

```
>> Sqrt[-4]
2I
>> I ^ 2
-1
>> (3 + 2 I)^ 4
-119 + 120I
>> (3 + 2 I)^ (2.5 - I)
43.663 + 8.28556I
>> Tan[I + 0.5]
0.195577 + 0.842966I
```

*Abs* calculates absolute values:

```
>> Abs[-3]
3
>> Abs[3 + 4 I]
5
```

*Mathics* can operate with pretty huge numbers:

```
>> 100!
93 326 215 443 944 152 681 699 ~
~238 856 266 700 490 715 968 ~
~264 381 621 468 592 963 895 ~
~217 599 993 229 915 608 941 ~
~463 976 156 518 286 253 697 920 ~
~827 223 758 251 185 210 916 864 ~
~000 000 000 000 000 000 000 000
```

(! denotes the factorial function.) The precision of numerical evaluation can be set:

```
>> N[Pi, 100]
3.141592653589793238462643~
~383279502884197169399375~
~105820974944592307816406~
~286208998628034825342117068
```

Division by zero is forbidden:

```
>> 1 / 0
Indeterminateexpression1/0encountered.
ComplexInfinity
```

Other expressions involving *Infinity* are evaluated:

```
>> Infinity + 2 Infinity
∞
```

In contrast to combinatorial belief,  $0^0$  is undefined:

```
>> 0 ^ 0
Indeterminateexpression0^0encountered.
Indeterminate
```

The result of the previous query to *Mathics* can be accessed by %:

```
>> 3 + 4
7
>> % ^ 2
49
```

## Symbols and Assignments

Symbols need not be declared in *Mathics*, they can just be entered and remain variable:

```
>> x
x
```

Basic simplifications are performed:

```
>> x + 2 x
3x
```

Symbols can have any name that consists of characters and digits:

```
>> iAm1Symbol ^ 2
iAm1Symbol^2
```

You can assign values to symbols:

```
>> a = 2
2
>> a ^ 3
8
>> a = 4
4
>> a ^ 3
64
```

Assigning a value returns that value. If you want to suppress the output of any result, add a ; to the end of your query:

```
>> a = 4;
```

Values can be copied from one variable to another:

```
>> b = a;
```

Now changing *a* does not affect *b*:

```
>> a = 3;
>> b
4
```

Such a dependency can be achieved by using “delayed assignment” with the `:=` operator (which does not return anything, as the right side is not even evaluated):

```
>> b := a ^ 2

>> b
9

>> a = 5;

>> b
25
```

## Comparisons and Boolean Logic

Values can be compared for equality using the operator `==`:

```
>> 3 == 3
True

>> 3 == 4
False
```

The special symbols `True` and `False` are used to denote truth values. Naturally, there are inequality comparisons as well:

```
>> 3 > 4
False
```

Inequalities can be chained:

```
>> 3 < 4 >= 2 != 1
True
```

Truth values can be negated using `!` (logical *not*) and combined using `&&` (logical *and*) and `||` (logical *or*):

```
>> !True
False

>> !False
True

>> 3 < 4 && 6 > 5
True
```

`&&` has higher precedence than `||`, i.e. it binds stronger:

```
>> True && True || False && False
True

>> True && (True || False) && False
False
```

## Strings

Strings can be entered with `"` as delimiters:

```
>> "Hello world!"
Hello world!
```

As you can see, quotation marks are not printed in the output by default. This can be changed by using `InputForm`:

```
>> InputForm["Hello world!"]
"Hello world!"
```

Strings can be joined using `<>`:

```
>> "Hello" <> " " <> "world!"
Hello world!
```

Numbers cannot be joined to strings:

```
>> "Debian" <> 6
Stringexpected.
Debian<>6
```

They have to be converted to strings using `ToString` first:

```
>> "Debian" <> ToString[6]
Debian6
```

## Lists

Lists can be entered in *Mathics* with curly braces `{` and `}`:

```
>> mylist = {a, b, c, d}
{a, b, c, d}
```

There are various functions for constructing lists:

```
>> Range[5]
{1, 2, 3, 4, 5}

>> Array[f, 4]
{f[1], f[2], f[3], f[4]}

>> ConstantArray[x, 4]
{x, x, x, x}

>> Table[n ^ 2, {n, 2, 5}]
{4, 9, 16, 25}
```

The number of elements of a list can be determined with `Length`:

```
>> Length[mylist]
4
```

Elements can be extracted using double square

braces:

```
>> mylist[[3]]  
c
```

Negative indices count from the end:

```
>> mylist[[-3]]  
b
```

Lists can be nested:

```
>> mymatrix = {{1, 2}, {3, 4}, {5,  
6}};
```

There are alternate forms to display lists:

```
>> TableForm[mymatrix]
```

```
1 2  
3 4  
5 6
```

```
>> MatrixForm[mymatrix]
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{pmatrix}$$

There are various ways of extracting elements from a list:

```
>> mymatrix[[2, 1]]  
3
```

```
>> mymatrix[;;, 2]  
{2, 4, 6}
```

```
>> Take[mylist, 3]  
{a, b, c}
```

```
>> Take[mylist, -2]  
{c, d}
```

```
>> Drop[mylist, 2]  
{c, d}
```

```
>> First[mymatrix]  
{1, 2}
```

```
>> Last[mylist]  
d
```

```
>> Most[mylist]  
{a, b, c}
```

```
>> Rest[mylist]  
{b, c, d}
```

Lists can be used to assign values to multiple variables at once:

```
>> {a, b} = {1, 2};
```

```
>> a  
1
```

```
>> b  
2
```

Many operations, like addition and multiplication, “thread” over lists, i.e. lists are combined element-wise:

```
>> {1, 2, 3} + {4, 5, 6}  
{5, 7, 9}
```

```
>> {1, 2, 3} * {4, 5, 6}  
{4, 10, 18}
```

It is an error to combine lists with unequal lengths:

```
>> {1, 2} + {4, 5, 6}
```

*Objectsofunequallengthcannotbecombined.*

```
{1, 2} + {4, 5, 6}
```

## The Structure of Things

Every expression in *Mathics* is built upon the same principle: it consists of a *head* and an arbitrary number of *children*, unless it is an *atom*, i.e. it can not be subdivided any further. To put it another way: everything is a function call. This can be best seen when displaying expressions in their “full form”:

```
>> FullForm[a + b + c]  
Plus[a, b, c]
```

Nested calculations are nested function calls:

```
>> FullForm[a + b * (c + d)]  
Plus[a, Times[b, Plus[c, d]]]
```

Even lists are function calls of the function `List`:

```
>> FullForm[{1, 2, 3}]  
List[1, 2, 3]
```

The head of an expression can be determined with `Head`:

```
>> Head[a + b + c]  
Plus
```

The children of an expression can be accessed like list elements:

```
>> (a + b + c)[[2]]  
b
```

The head is the 0th element:

```
>> (a + b + c)[[0]]
Plus
```

The head of an expression can be exchanged using the function `Apply`:

```
>> Apply[g, f[x, y]]
g[x, y]

>> Apply[Plus, a * b * c]
a + b + c
```

`Apply` can be written using the operator `@@`:

```
>> Times @@ {1, 2, 3, 4}
24
```

(This exchanges the head `List` of `{1, 2, 3, 4}` with `Times`, and then the expression `Times[1, 2, 3, 4]` is evaluated, yielding 24.) `Apply` can also be applied on a certain *level* of an expression:

```
>> Apply[f, {{1, 2}, {3, 4}}, {1}]
{f[1, 2], f[3, 4]}
```

Or even on a range of levels:

```
>> Apply[f, {{1, 2}, {3, 4}}, {0, 2}]
f[f[1, 2], f[3, 4]]
```

`Apply` is similar to `Map (/@)`:

```
>> Map[f, {1, 2, 3, 4}]
{f[1], f[2], f[3], f[4]}

>> f /@ {{1, 2}, {3, 4}}
{f[{1, 2}], f[{3, 4}]}
```

The atoms of *Mathics* are numbers, symbols, and strings. `AtomQ` tests whether an expression is an atom:

```
>> AtomQ[5]
True

>> AtomQ[a + b]
False
```

The full form of rational and complex numbers looks like they were compound expressions:

```
>> FullForm[3 / 5]
Rational[3, 5]

>> FullForm[3 + 4 I]
Complex[3, 4]
```

However, they are still atoms, thus unaffected

by applying functions, for instance:

```
>> f @@ Complex[3, 4]
3 + 4 I
```

Nevertheless, every atom has a head:

```
>> Head /@ {1, 1/2, 2.0, I, "a string", x}
{Integer, Rational, Real,
 Complex, String, Symbol}
```

The operator `===` tests whether two expressions are the same on a structural level:

```
>> 3 === 3
True

>> 3 == 3.0
True
```

But

```
>> 3 === 3.0
False
```

because 3 (an `Integer`) and 3.0 (a `Real`) are structurally different.

## Functions and Patterns

Functions can be defined in the following way:

```
>> f[x_] := x ^ 2
```

This tells *Mathics* to replace every occurrence of `f` with one (arbitrary) parameter `x` with `x ^ 2`.

```
>> f[3]
9

>> f[a]
a2
```

The definition of `f` does not specify anything for two parameters, so any such call will stay unevaluated:

```
>> f[1, 2]
f[1, 2]
```

In fact, *functions* in *Mathics* are just one aspect of *patterns*: `f[x_]` is a pattern that *matches* expressions like `f[3]` and `f[a]`. The following patterns are available:

```

_ or Blank[]
    matches one expression.
Pattern[x, p]
    matches the pattern p and stores the value
    in x.
x_ or Pattern[x, Blank[]]
    matches one expression and stores it in x.
__ or BlankSequence[]
    matches a sequence of one or more ex-
    pressions.
___ or BlankNullSequence[]
    matches a sequence of zero or more ex-
    pressions.
_h or Blank[h]
    matches one expression with head h.
x_h or Pattern[x, Blank[h]]
    matches one expression with head h and
    stores it in x.
p | q or Alternatives[p, q]
    matches either pattern p or q.
p ? t or PatternTest[p, t]
    matches p if the test t[p] yields True.
p /; c or Condition[p, c]
    matches p if condition c holds.
Verbatim[p]
    matches an expression that equals p,
    without regarding patterns inside p.

```

As before, patterns can be used to define func-  
tions:

```

>> g[s___] := Plus[s] ^ 2

>> g[1, 2, 3]
36

```

MatchQ[*e*, *p*] tests whether *e* matches *p*:

```

>> MatchQ[a + b, x_ + y_]
True

>> MatchQ[6, _Integer]
True

```

ReplaceAll (/.) replaces all occurrences of a  
pattern in an expression using a Rule given by  
->:

```

>> {2, "a", 3, 2.5, "b", c} /.
    x_Integer -> x ^ 2
{4, a, 9, 2.5, b, c}

```

You can also specify a list of rules:

```

>> {2, "a", 3, 2.5, "b", c} /. {
    x_Integer -> x ^ 2.0, y_String
    -> 10}
{4., 10, 9., 2.5, 10, c}

```

ReplaceRepeated (//.) applies a set of rules re-  
peatedly, until the expression doesn't change  
anymore:

```

>> {2, "a", 3, 2.5, "b", c} //. {
    x_Integer -> x ^ 2.0, y_String
    -> 10}
{4., 100., 9., 2.5, 100., c}

```

There is a “delayed” version of Rule which can  
be specified by :> (similar to the relation of := to  
=):

```

>> a :> 1 + 2
a:>1 + 2

>> a -> 1 + 2
a- > 3

```

This is useful when the right side of a rule  
should not be evaluated immediately (before  
matching):

```

>> {1, 2} /. x_Integer -> N[x]
{1, 2}

```

Here, N is applied to *x* before the actual match-  
ing, simply yielding *x*. With a delayed rule this  
can be avoided:

```

>> {1, 2} /. x_Integer :> N[x]
{1., 2.}

```

While ReplaceAll and ReplaceRepeated sim-  
ply take the first possible match into ac-  
count, ReplaceList returns a list of all possi-  
ble matches. This can be used to get all subse-  
quences of a list, for instance:

```

>> ReplaceList[{a, b, c}, {___, x__,
    , ___} -> {x}]
{{a}, {a, b}, {a, b,
    c}, {b}, {b, c}, {c}}

```

ReplaceAll would just return the first expres-  
sion:

```

>> ReplaceAll[{a, b, c}, {___, x__,
    ___} -> {x}]
{a}

```

In addition to defining functions as rules for cer-  
tain patterns, there are *pure* functions that can be  
defined using the & postfix operator, where ev-  
erything before it is treated as the function body  
and # can be used as argument placeholder:

```

>> h = # ^ 2 &;

>> h[3]
9

```

Multiple arguments can simply be indexed:

```
>> sum = #1 + #2 &;  
  
>> sum[4, 6]  
10
```

It is also possible to name arguments using Function:

```
>> prod = Function[{x, y}, x * y];  
  
>> prod[4, 6]  
24
```

Pure functions are very handy when functions are used only locally, e.g., when combined with operators like Map:

```
>> # ^ 2 & /@ Range[5]  
{1,4,9,16,25}
```

Sort according to the second part of a list:

```
>> Sort[{{x, 10}, {y, 2}, {z, 5}},  
#1[[2]] < #2[[2]] &]  
{{y,2}, {z,5}, {x,10}}
```

Functions can be applied using prefix or postfix notation, in addition to using []:

```
>> h @ 3  
9  
  
>> 3 // h  
9
```

## Control Statements

Like most programming languages, *Mathics* has common control statements for conditions, loops, etc.:

If[*cond*, *pos*, *neg*]  
returns *pos* if *cond* evaluates to True, and *neg* if it evaluates to False.  
Which[*cond1*, *expr1*, *cond2*, *expr2*, ...]  
yields *expr1* if *cond1* evaluates to True, *expr2* if *cond2* evaluates to True, etc.  
Do[*expr*, {*i*, *max*}]  
evaluates *expr* *max* times, substituting *i* in *expr* with values from 1 to *max*.  
For[*start*, *test*, *incr*, *body*]  
evaluates *start*, and then iteratively *body* and *incr* as long as *test* evaluates to True.  
While[*test*, *body*]  
evaluates *body* as long as *test* evaluates to True.  
Nest[*f*, *expr*, *n*]  
returns an expression with *f* applied *n* times to *expr*.  
NestWhile[*f*, *expr*, *test*]  
applies a function *f* repeatedly on an expression *expr*, until applying *test* on the result no longer yields True.  
FixedPoint[*f*, *expr*]  
starting with *expr*, repeatedly applies *f* until the result no longer changes.

```
>> If[2 < 3, a, b]  
a  
  
>> x = 3; Which[x < 2, a, x > 4, b,  
x < 5, c]  
c
```

Compound statements can be entered with ;. The result of a compound expression is its last part or Null if it ends with a ;.

```
>> 1; 2; 3  
3  
  
>> 1; 2; 3;
```

Inside For, While, and Do loops, Break[] exits the loop and Continue[] continues to the next iteration.

```
>> For[i = 1, i <= 5, i++, If[i ==  
4, Break[]]; Print[i]]  
1  
2  
3
```

## Scoping

By default, all symbols are “global” in *Mathics*, i.e. they can be read and written in any part of your program. However, sometimes “local” variables are needed in order not to disturb the global namespace. *Mathics* provides two ways to support this:

- *lexical scoping* by `Module`, and
- *dynamic scoping* by `Block`.

```
Module[{vars}, expr]
  localizes variables by giving them a temporary name of the form name$number, where number is the current value of $ModuleNumber. Each time a module is evaluated, $ModuleNumber is incremented.

Block[{vars}, expr]
  temporarily stores the definitions of certain variables, evaluates expr with reset values and restores the original definitions afterwards.
```

Both scoping constructs shield inner variables from affecting outer ones:

```
>> t = 3;

>> Module[{t}, t = 2]
2

>> Block[{t}, t = 2]
2

>> t
3
```

`Module` creates new variables:

```
>> y = x ^ 3;

>> Module[{x = 2}, x * y]
2x3
```

`Block` does not:

```
>> Block[{x = 2}, x * y]
16
```

Thus, `Block` can be used to temporarily assign a value to a variable:

```
>> expr = x ^ 2 + x;

>> Block[{x = 3}, expr]
12

>> x
x
```

`Block` can also be used to temporarily change the value of system parameters:

```
>> Block[{$RecursionLimit = 30}, x
= 2 x]
Recursiondepthof30exceeded.
$Aborted

>> f[x_] := f[x + 1]; Block[{
$IterationLimit = 30}, f[1]]
Iterationlimitof30exceeded.
$Aborted
```

It is common to use scoping constructs for function definitions with local variables:

```
>> fac[n_] := Module[{k, p}, p = 1;
  For[k = 1, k <= n, ++k, p *= k
]; p]

>> fac[10]
3 628 800

>> 10!
3 628 800
```

## Formatting Output

The way results are formatted for output in *Mathics* is rather sophisticated, as compatibility to the way *Mathematica*® does things is one of the design goals. It can be summed up in the following procedure:

1. The result of the query is calculated.
2. The result is stored in `Out` (which % is a shortcut for).
3. Any `Format` rules for the desired output form are applied to the result. In the console version of *Mathics*, the result is formatted as `OutputForm`; `MathMLForm` for the `StandardForm` is used in the interactive Web version; and `TeXForm` for the `StandardForm` is used to generate the  $\text{\LaTeX}$  version of this documentation.
4. `MakeBoxes` is applied to the formatted result, again given either `OutputForm`, `MathMLForm`, or `TeXForm` depending on the execution context of *Mathics*. This yields a new expression consisting of “box constructs”.
5. The boxes are turned into an ordinary string and displayed in the console, sent to the browser, or written to the documentation  $\text{\LaTeX}$  file.

As a consequence, there are various ways to implement your own formatting strategy for custom objects.

You can specify how a symbol shall be formatted by assigning values to `Format`:

```
>> Format[x] = "y";

>> x
y
```

This will apply to `MathMLForm`, `OutputForm`, `StandardForm`, `TeXForm`, and `TraditionalForm`.

```
>> x // InputForm
x
```

You can specify a specific form in the assignment to `Format`:

```
>> Format[x, TeXForm] = "z";

>> x // TeXForm
\text{z}
```

Special formats might not be very relevant for individual symbols, but rather for custom functions (objects):

```
>> Format[r[args___]] = "<an r
object>";

>> r[1, 2, 3]
<an r object>
```

You can use several helper functions to format expressions:

```
Infix[expr, op]
  formats the arguments of expr with infix
  operator op.
Prefix[expr, op]
  formats the argument of expr with prefix
  operator op.
Postfix[expr, op]
  formats the argument of expr with postfix
  operator op.
StringForm[form, arg1, arg2, ...]
  formats arguments using a format string.
```

```
>> Format[r[args___]] = Infix[{args
}, "~"];

>> r[1, 2, 3]
1 ~ 2 ~ 3

>> StringForm["'1' and '2'", n, m]
n and m
```

There are several methods to display expressions in 2-D:

```
Row[{...}]
  displays expressions in a row.
Grid[{{...}}]
  displays a matrix in two-dimensional
  form.
Subscript[expr, i1, i2, ...]
  displays expr with subscript indices i1, i2,
  ...
Superscript[expr, exp]
  displays expr with superscript (exponent)
  exp.
```

```
>> Grid[{{a, b}, {c, d}}]
  a  b
  c  d

>> Subscript[a, 1, 2] // TeXForm
a_{1,2}
```

If you want even more low-level control of how expressions are displayed, you can override `MakeBoxes`:

```
>> MakeBoxes[b, StandardForm] = "c
";

>> b
c
```

This will even apply to `TeXForm`, because `TeXForm` implies `StandardForm`:

```
>> b // TeXForm
c
```

Except some other form is applied first:

```
>> b // OutputForm // TeXForm
b
```

`MakeBoxes` for another form:

```
>> MakeBoxes[b, TeXForm] = "d";

>> b // TeXForm
d
```

You can cause a much bigger mess by overriding `MakeBoxes` than by sticking to `Format`, e.g. generate invalid XML:

```
>> MakeBoxes[c, MathMLForm] = "<not
closed";

>> c // MathMLForm
<not closed
```

However, this will not affect formatting of ex-



pressions involving  $c$ :

```
>> c + 1 // MathMLForm
<math display="block"><mrow>
  <mn>1</mn> <mo>+</mo>
  <mi>c</mi></mrow></math>
```

That's because MathMLForm will, when not overridden for a special case, call StandardForm first. Format will produce escaped output:

```
>> Format[d, MathMLForm] = "<not
  closed";

>> d // MathMLForm
<math display="block">
<mtext>&lt;not&nbsp;closed</mtext>
</math>

>> d + 1 // MathMLForm
<math display="block"><mrow>
<mn>1</mn> <mo>+</mo>
<mtext>&lt;not&nbsp;closed</mtext>
</mrow></math>
```

For instance, you can override MakeBoxes to format lists in a different way:

```
>> MakeBoxes[{items___},
  StandardForm] := RowBox[{"[",
  Sequence @@ Riffle[MakeBoxes /@
  {items}, " ", "]" ]}]

>> {1, 2, 3}
[123]
```

However, this will not be accepted as input to *Mathics* anymore:

```
>> [1 2 3]

>> Clear[MakeBoxes]
```

By the way, MakeBoxes is the only built-in symbol that is not protected by default:

```
>> Attributes[MakeBoxes]
[HoldAllComplete]
```

MakeBoxes must return a valid box construct:

```
>> MakeBoxes[squared[args___],
  StandardForm] := squared[args] ^
  2

>> squared[1, 2]
Power[squared[1,2],
  2]isnotavalidboxstructure.
```

```
>> squared[1, 2] // TeXForm
Power[squared[1,2],
  2]isnotavalidboxstructure.
```

= The desired effect can be achieved in the following way:

```
>> MakeBoxes[squared[args___],
  StandardForm] := SuperscriptBox[
  RowBox[{MakeBoxes[squared], "["],
  RowBox[Riffle[MakeBoxes[#] & /@
  {args}, " ", "]" ]], 2]

>> squared[1, 2]
squared[1,2]2
```

You can view the box structure of a formatted expression using ToBoxes:

```
>> ToBoxes[m + n]
RowBox[{m, +, n}]
```

The list elements in this RowBox are strings, though string delimiters are not shown in the default output form:


```
>> InputForm[%]
RowBox[{ "m", "+", "n" ]}
```

## Graphics Introduction Examples


Two-dimensional graphics can be created using the function Graphics and a list of graphics primitives. For three-dimensional graphics see the following section. The following primitives are available:

```
Circle[{x, y}, r]
  draws a circle.
Disk[{x, y}, r]
  draws a filled disk.
Rectangle[{x1, y1}, {x2, y2}]
  draws a filled rectangle.
Polygon[{{x1, y1}, {x2, y2}, ...}]
  draws a filled polygon.
Line[{{x1, y1}, {x2, y2}, ...}]
  draws a line.
Text[text, {x, y}]
  draws text in a graphics.
```

```
>> Graphics[{Circle[{0, 0}, 1]}]
```



```
>> Graphics[{Line[{0, 0}, {0, 1}, {1, 1}, {1, -1}], Rectangle[{0, 0}, {-1, -1}]}]
```



Colors can be added in the list of graphics primitives to change the drawing color. The following ways to specify colors are supported:

`RGBColor[r, g, b]`  
specifies a color using red, green, and blue.

`CMYKColor[c, m, y, k]`  
specifies a color using cyan, magenta, yellow, and black.

`Hue[h, s, b]`  
specifies a color using hue, saturation, and brightness.

`GrayLevel[l]`  
specifies a color using a gray level.

All components range from 0 to 1. Each color

function can be supplied with an additional argument specifying the desired opacity ("alpha") of the color. There are many predefined colors,

such as Black, White, Red, Green, Blue, etc.

```
>> Graphics[{Red, Disk[]}]
```





Table of hues:

```
>> Graphics[Table[{Hue[h, s], Disk[{12h, 8s}]}, {h, 0, 1, 1/6}, {s, 0, 1, 1/4}]]
```




Colors can be mixed and altered using the following functions:

`Blend[{color1, color2}, ratio]`  
mixes *color1* and *color2* with *ratio*, where a ratio of 0 returns *color1* and a ratio of 1 returns *color2*.

`Lighter[color]`  
makes *color* lighter (mixes it with White).

`Darker[color]`  
makes *color* darker (mixes it with Black).

```
>> Graphics[{Lighter[Red], Disk[]}]
```



Graphics produces a GraphicsBox:

```
>> Head[ToBoxes[Graphics[{Circle[]}]]]
```


GraphicsBox

## 3D Graphics

Three-dimensional graphics are created using the function `Graphics3D` and a list of 3D primitives. The following primitives are supported so far:


```
Polygon[{{x1, y1, z1}, {x2, y2, z3}, ...}]
  draws a filled polygon.
Line[{{x1, y1, z1}, {x2, y2, z3}, ...}]
  draws a line.
Point[{x1, y1, z1}]
  draws a point.
```

```
>> Graphics3D[Polygon[{{0,0,0}, {0,1,1}, {1,0,0}}]]
```



Colors can also be added to three-dimensional primitives.

```
>> Graphics3D[{Orange, Polygon
  [{{0,0,0}, {1,1,1}, {1,0,0}}]},
  Axes->True]
```



Graphics3D produces a Graphics3DBox:


```
>> Head[ToBoxes[Graphics3D[{Polygon[]}]]]
```

Graphics3DBox

## Plotting Introduction Examples


*Mathics* can plot functions:

```
>> Plot[Sin[x], {x, 0, 2 Pi}]
```




You can also plot multiple functions at once:

```
>> Plot[{Sin[x], Cos[x], x ^ 2}, {x, -1, 1}]
```




Two-dimensional functions can be plotted using DensityPlot:

```
>> DensityPlot[x ^ 2 + 1 / y, {x, -1, 1}, {y, 1, 4}]
```



You can use a custom coloring function:


```
>> DensityPlot[x ^ 2 + 1 / y, {x, -1, 1}, {y, 1, 4}, ColorFunction -> (Blend[{Red, Green, Blue}, #]&)]
```



One problem with DensityPlot is that it's still very slow, basically due to function evaluation being pretty slow in general—and DensityPlot has to evaluate a lot of functions.

Three-dimensional plots are supported as well:

```
>> Plot3D[Exp[x] Cos[y], {x, -2, 1}, {y, -Pi, 2 Pi}]
```



# 3. Examples

## Contents

Curve sketching . . . .	21	Linear algebra . . . . .	22	Dice . . . . .	23
-------------------------	----	--------------------------	----	----------------	----

## Curve sketching

Let's sketch the function

```
>> f[x_] := 4 x / (x ^ 2 + 3 x + 5)
```

The derivatives are

```
>> {f'[x], f''[x], f'''[x]} //
```

Together

$$\left\{ \begin{array}{l} \frac{-4(-5+x^2)}{(5+3x+x^2)^2}, \\ \frac{8(-15-15x+x^3)}{(5+3x+x^2)^3}, \\ \frac{-24(-20-60x-30x^2+x^4)}{(5+3x+x^2)^4} \end{array} \right\}$$

To get the extreme values of f, compute the zeroes of the first derivatives:

```
>> extremes = Solve[f'[x] == 0, x]
```

$$\left\{ \left\{ x \rightarrow -\sqrt{5} \right\}, \left\{ x \rightarrow \sqrt{5} \right\} \right\}$$

And test the second derivative:

```
>> f''[x] /. extremes // N
```

$$\{1.65086, -0.064079\}$$

Thus, there is a local maximum at  $x = \text{Sqrt}[5]$  and a local minimum at  $x = -\text{Sqrt}[5]$ . Compute the inflection points numerically, chopping imaginary parts close to 0:

```
>> inflections = Solve[f''[x] == 0, x] // N // Chop
```

$$\left\{ \left\{ x \rightarrow -1.0852 \right\}, \left\{ x \rightarrow -3.21463 \right\}, \left\{ x \rightarrow 4.29983 \right\} \right\}$$

Insert into the third derivative:

```
>> f'''[x] /. inflections
```

$$\{-3.67683, 0.694905, 0.00671894\}$$

Being different from 0, all three points are actual inflection points. f is not defined where its denominator is 0:

```
>> Solve[Denominator[f[x]] == 0, x]
```

$$\left\{ \left\{ x \rightarrow -\frac{3}{2} - \frac{I}{2}\sqrt{11} \right\}, \left\{ x \rightarrow -\frac{3}{2} + \frac{I}{2}\sqrt{11} \right\} \right\}$$

These are non-real numbers, consequently f is defined on all real numbers. The behaviour of f at the boundaries of its definition:

```
>> Limit[f[x], x -> Infinity]
```


$$0$$

```
>> Limit[f[x], x -> -Infinity]
```

$$0$$

Finally, let's plot f:

```
>> Plot[f[x], {x, -8, 6}]
```



## Linear algebra

Let's consider the matrix

```
>> A = {{1, 1, 0}, {1, 0, 1}, {0, 1, 1}};
```

```
>> MatrixForm[A]

$$\begin{pmatrix} 1 & 1 & 0 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{pmatrix}$$

```

We can compute its eigenvalues and eigenvectors:

```
>> Eigenvalues[A]
{2, -1, 1}

>> Eigenvectors[A]
{{1, 1, 1}, {1, -2, 1}, {-1, 0, 1}}
```

This yields the diagonalization of A:

```
>> T = Transpose[Eigenvectors[A]];
MatrixForm[T]

$$\begin{pmatrix} 1 & 1 & -1 \\ 1 & -2 & 0 \\ 1 & 1 & 1 \end{pmatrix}$$


>> Inverse[T] . A . T // MatrixForm

$$\begin{pmatrix} 2 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$


>> % == DiagonalMatrix[Eigenvalues[A]]
True
```

We can solve linear systems:

```
>> LinearSolve[A, {1, 2, 3}]
{0, 1, 2}

>> A . %
{1, 2, 3}
```

In this case, the solution is unique:

```
>> NullSpace[A]
{}
```

Let's consider a singular matrix:

```
>> B = {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}};

>> MatrixRank[B]
2

>> s = LinearSolve[B, {1, 2, 3}]
 $\left\{-\frac{1}{3}, \frac{2}{3}, 0\right\}$ 

>> NullSpace[B]
{{1, -2, 1}}
```

```
>> B . (RandomInteger[100] * %[[1]]
+ s)
{1, 2, 3}
```

## Dice

Let's play with dice in this example. A Dice object shall represent the outcome of a series of rolling a dice with six faces, e.g.:

```
>> Dice[1, 6, 4, 4]
Dice[1, 6, 4, 4]
```

Like in most games, the ordering of the individual throws does not matter. We can express this by making Dice Orderless:


```
>> SetAttributes[Dice, Orderless]

>> Dice[1, 6, 4, 4]
Dice[1, 4, 4, 6]
```

A dice object shall be displayed as a rectangle with the given number of points in it, positioned like on a traditional dice:

```
>> Format[Dice[n_Integer?(1 <= # <=
6 &)] := Block[{p = 0.2, r =
0.05}, Graphics[{EdgeForm[Black],
White, Rectangle[], Black,
EdgeForm[], If[OddQ[n], Disk
[{0.5, 0.5}, r]], If[MemberQ[{2,
3, 4, 5, 6}, n], Disk[{p, p}, r]],
If[MemberQ[{2, 3, 4, 5, 6}, n],
Disk[{1 - p, 1 - p}, r]], If[
MemberQ[{4, 5, 6}, n], Disk[{p,
1 - p}, r]], If[MemberQ[{4, 5,
6}, n], Disk[{1 - p, p}, r]], If
[n === 6, {Disk[{p, 0.5}, r],
Disk[{1 - p, 0.5}, r}]}],
ImageSize -> Tiny]]


>> Dice[1]
```



The empty series of dice shall be displayed as an empty dice:

```
>> Format[Dice[]] := Graphics[{
EdgeForm[Black], White,
Rectangle[]}, ImageSize -> Tiny]
```


```
>> Dice[]
```



Any non-empty series of dice shall be displayed as a row of individual dice:

```
>> Format[Dice[d___Integer?(1 <= #
  <= 6 &)] := Row[Dice /@ {d}]
```

```
>> Dice[1, 6, 4, 4]
```



Note that *Mathics* will automatically sort the given format rules according to their “generality”, so the rule for the empty dice does not get overridden by the rule for a series of dice. We can still see the original form by using `InputForm`:

```
>> Dice[1, 6, 4, 4] // InputForm
Dice[1, 4, 4, 6]
```

We want to combine `Dice` objects using the `+` operator:


```
>> Dice[a___] + Dice[b___] ^:= Dice
  [Sequence @@ {a, b}]
```

The `^:=` (`UpSetDelayed`) tells *Mathics* to associate this rule with `Dice` instead of `Plus`, which is protected—we would have to unprotect it first:

```
>> Dice[a___] + Dice[b___] := Dice[
  Sequence @@ {a, b}]
TagPlusinDice[a___]
+ Dice[b___]isProtected.
$Failed
```

We can now combine dice:

```
>> Dice[1, 5] + Dice[3, 2] + Dice
  [4]
```




Let’s write a function that returns the sum of the rolled dice:

```
>> DiceSum[Dice[d___]] := Plus @@ {
  d}

>> DiceSum @ Dice[1, 2, 5]
8
```

And now let’s put some dice into a table:

```
>> Table[{Dice[Sequence @@ d],
  DiceSum @ Dice[Sequence @@ d]},
  {d, {{1, 2}, {2, 2}, {2, 6}}}]
// TableForm
```



It is not very sophisticated from a mathematical point of view, but it’s beautiful.

## 4. Django-based Web Interface

In the future, we plan on providing an interface to Jupyter as a separate package.

However currently as part *Mathics*, we distribute a browser-based interface using long-term-release (LTS) Django 3.2.

Since a Jupyter-based interface seems preferable to the home-grown interface described here, it is doubtful whether there will be future improve-

ments to the this interface.

When you enter Mathics in the top after the Mathics logo and the word “Mathics” you’ll see a *menubar*.

It looks like this:



### Contents

---

URIs . . . . .	24	Persistence of Mathics	Keyboard Commands . . . . .	26
Saving, Loading, and		Definitions in a		
Deleting		Session . . . . .		25
Worksheets . . . . .	25			

---

### URIs

For the most part, the application is a single-page application. Assuming your are running locally or on a host called `localhost` using the default port, 8000, here are some URLs and what they do:

`http://localhost:8000`

The single-page application; the main page.

`http://localhost:8000/about`

A page giving:

- the software versions of this package and version information of important software this uses.
- directory path information for the current setup
- machine information
- system information

`http://localhost:8000/doc`

An on-line formatted version of the documentation, which include this text. You can see this as a right side frame of the main page, when clicking "?" on the right-hand upper corner.



## Saving, Loading, and Deleting Worksheets

<subsection title="Saving Worksheets">


Worksheets exist in the browser window only and are not stored on the server, by default. To save all your queries and results, use the *Save* button which is the middle graphic of the menu bar. It looks like this:



Depending on browser, desktop, and OS-settings, the "Ctrl+S" key combination may do the same thing.

<subsection title="Loading and Deleting Worksheets">

Saved worksheets can be loaded or deleted using the *File Open* button which is the left-most button in the menu bar. It looks like this:



Depending on browser, desktop, and OS-settings, the "Ctrl+O" key combination may do the same thing.

A popup menu should appear with the list of saved worksheets with an option to either load or delete the worksheet.

## Persistence of Mathics Definitions in a Session

When you use the Django-based Web interface of *Mathics*, a browser session is created. Cookies have to be enabled to allow this. Your session holds a key which is used to access your definitions that are stored in a database on the server. As long as you don't clear the cookies in your browser, your definitions will remain even when you close and re-open the browser.

This implies that you should not store sensitive, private information in *Mathics* variables when using the online Web interface. In addition to their values being stored in a database on the server, your queries might be saved for debugging purposes. However, the fact that they are transmitted over plain HTTP should make you aware that you should not transmit any sensitive information. When you want to do calculations with that kind of stuff, simply install *Mathics* locally!

If you are using a public terminal, to erase all

your definitions and close the browser window. When you use *Mathics* in a browser, use the command `Quit []` or its alias, `Exit []`.

Normally, when you reload the current page in a browser using the default url, e.g `http://localhost:8000`, all of the previous input and output disappears, even though definitions as described above do not, unless `Quit []` or `Exit []` is entered as described above.

However if you want a URL that will that records the input entered the *Generate Input Hash* button does this. The button looks like this:



For example, assuming you have a *Mathics* server running at port 8000 on localhost, and you enter the url `http://localhost:8000/#cXVlcm11cz14`, you should see a single line of input containing `x` entered.

Of course, what the value of this is when evaluated depends on whether `x` has been previously defined.

## Keyboard Commands

There are some keyboard commands you can use in the Django-based Web interface of *Mathics*.

### Shift+Return

This evaluates the current cell (the most important one, for sure). On the right-hand side you may also see an "=" button which can be clicked to do the same thing.

### Ctrl+D

This moves the cursor over to the documentation pane on the right-hand side. From here you can preform a search for a pre-defined *Mathics* function, or symbol. Clicking on the "?" symbol on the right-hand side does the same thing.

### Ctrl+C

This moves the cursor back to document code pane area where you type *Mathics* expressions

### Ctrl+S

Save worksheet

### Ctrl+O

Open worksheet

### Right Click on MathML output

Opens MathJax Menu

Of special note is the last item on the list: right-click to open the MathJax menu. Under “Math Setting”/“Zoom Trigger”, if the zoom trigger is set to a value other than “No Zoom”, then when that trigger is applied on MathML formatted output, the MathML formula pop up a window for the formula. The window can show the formula larger. Also, this is a way to see output that is too large to fit on the display since the window allows for scrolling.

Keyboard commands behavior depends the browser used, the operating system, desk-

top settings, and customization. We hook into the desktop “Open the current document” and “Save the current document” functions that many desktops provide. For example see: [https://help.ubuntu.com/community/KeyboardShortcuts#Finding\\_keyboard\\_shortcuts](https://help.ubuntu.com/community/KeyboardShortcuts#Finding_keyboard_shortcuts)

Often, these shortcut keyboard command are only recognized when a text field has focus; otherwise, the browser might do some browser-specific actions, like setting a bookmark etc.

## **Part II.**

# **Reference of Built-in Symbols**

# 1. Date and Time

Dates and times are represented symbolically; computations can be performed on them.

Date object can also input and output dates and times in a wide range of formats, as well as handle calendars.

## Contents

<b>AbsoluteTime</b> . . . . .	28	<b>DateString</b> . . . . .	30	<b>TimeConstrained</b> . . . .	31
<b>AbsoluteTiming</b> . . . .	28	<b>\$DateStringFormat</b> . .	30	<b>TimeRemaining</b> . . . .	31
<b>DateDifference</b> . . . .	29	<b>EasterSunday</b> . . . .	30	<b>TimeUsed</b> . . . . .	32
<b>DateList</b> . . . . .	29	<b>Now</b> . . . . .	31	<b>\$TimeZone</b> . . . . .	32
<b>DateObject</b> . . . . .	29	<b>Pause</b> . . . . .	31	<b>Timing</b> . . . . .	32
<b>DatePlus</b> . . . . .	30	<b>SessionTime</b> . . . . .	31		
		<b>\$SystemTimeZone</b> . .	31		

## AbsoluteTime

```
AbsoluteTime[]
    gives the local time in seconds since
    epoch January 1, 1900, in your time zone.
AbsoluteTime[{y, m, d, h, m, s}]
    gives the absolute time specification cor-
    responding to a date list.
AbsoluteTime["string"]
    gives the absolute time specification for a
    given date string.
AbsoluteTime[{"string", {e1, e2, ...}}]
    takgs the date string to contain the ele-
    ments "ei".
```

```
>> AbsoluteTime[]
3.83429 × 109

>> AbsoluteTime[{2000}]
3 155 673 600

>> AbsoluteTime[{"01/02/03", {"Day",
    "Month", "YearShort"}}]
3 253 046 400

>> AbsoluteTime["6 June 1991"]
2 885 155 200

>> AbsoluteTime[{"6-6-91", {"Day",
    "Month", "YearShort"}}]
2 885 155 200
```

## AbsoluteTiming

```
AbsoluteTiming[expr]
    evaluates expr, returning a list of the ab-
    solute number of seconds in real time that
    have elapsed, together with the result ob-
    tained.
```

```
>> AbsoluteTiming[50!]
{0.000205278, 30 414 093 ~
    ~201 713 378 043 612 608 166 ~
    ~064 768 844 377 641 568 ~
    ~960 512 000 000 000 000}

>> Attributes[AbsoluteTiming]
{HoldAll, Protected}
```

## DateDifference

`DateDifference[date1, date2]`  
returns the difference between *date1* and *date2* in days.  
`DateDifference[date1, date2, unit]`  
returns the difference in the specified *unit*.  
`DateDifference[date1, date2, {unit1, unit2, ...}]`  
represents the difference as a list of integer multiples of each *unit*, with any remainder expressed in the smallest unit.

```
>> DateDifference[{2042, 1, 4}, {2057, 1, 1}]
5476

>> DateDifference[{1936, 8, 14}, {2000, 12, 1}, "Year"]
{64.3425, Year}

>> DateDifference[{2010, 6, 1}, {2015, 1, 1}, "Hour"]
{40200, Hour}

>> DateDifference[{2003, 8, 11}, {2003, 10, 19}, {"Week", "Day"}]
{{9, Week}, {6, Day}}
```

## DateList

`DateList[]`  
returns the current local time in the form {*year*, *month*, *day*, *hour*, *minute*, *second*}.  
`DateList[time]`  
returns a formatted date for the number of seconds *time* since epoch Jan 1 1900.  
`DateList[{y, m, d, h, m, s}]`  
converts an incomplete date list to the standard representation.  
`DateString[string]`  
returns the formatted date list of a date string specification.  
`DateString[string, {e1, e2, ...}]`  
returns the formatted date list of a *string* obtained from elements *ei*.

```
>> DateList[0]
{1900, 1, 1, 0, 0, 0}
```

```
>> DateList[3155673600]
{2000, 1, 1, 0, 0, 0}

>> DateList[{2003, 5, 0.5, 0.1, 0.767}]
{2003, 4, 30, 12, 6, 46.02}

>> DateList[{2012, 1, 300., 10}]
{2012, 10, 26, 10, 0, 0}

>> DateList["31/10/1991"]
{1991, 10, 31, 0, 0, 0}

>> DateList["1/10/1991"]
The interpretation of 1/10/1991 is ambiguous.
{1991, 1, 10, 0, 0, 0}

>> DateList[{"31/10/91", {"Day", "Month", "YearShort"}}]
{1991, 10, 31, 0, 0, 0}

>> DateList[{"31 10/91", {"Day", "Month", "YearShort"}}]
{1991, 10, 31, 0, 0, 0}

If not specified, the current year assumed
>> DateList[{"5/18", {"Month", "Day"}}]
{2021, 5, 18, 0, 0, 0}
```

## DateObject

`DateObject[...]`  
Returns an object codifying DateList...

```
>> DateObject[{2020, 4, 15}]
[Wed 15 Apr 2020 00:00:00 GTM - 5]
```

## DatePlus

```
DatePlus[date, n]  
    finds the date n days after date.  
DatePlus[date, {n, "unit"}]  
    finds the date n units after date.  
DatePlus[date, {{n1, "unit1"}, {n2, "  
unit2"}, ...}]  
    finds the date which is n_i specified units  
    after date.  
DatePlus[n]  
    finds the date n days after the current  
    date.  
DatePlus[offset]  
    finds the date which is offset from the  
    current date.
```

Add 73 days to Feb 5, 2010:

```
>> DatePlus[{2010, 2, 5}, 73]  
      {2010, 4, 19}
```

Add 8 weeks and 1 day to March 16, 1999:

```
>> DatePlus[{2010, 2, 5}, {{8, "  
Week"}, {1, "Day"}}]  
      {2010, 4, 3}
```

## DateString

```
DateString[]  
    returns the current local time and date as  
    a string.  
DateString[elem]  
    returns the time formatted according to  
    elems.  
DateString[{e1, e2, ...}]  
    concatenates the time formatted accord-  
    ing to elements ei.  
DateString[time]  
    returns the date string of an Absolute-  
    Time.  
DateString[{y, m, d, h, m, s}]  
    returns the date string of a date list spec-  
    ification.  
DateString[string]  
    returns the formatted date string of a date  
    string specification.  
DateString[spec, elems]  
    formats the time in turns of elems. Both  
    spec and elems can take any of the above  
    formats.
```

The current date and time:

```
>> DateString[];  
  
>> DateString[{1991, 10, 31, 0, 0},  
      {"Day", " ", "MonthName", " ", "  
Year"}]  
      31 October 1991  
  
>> DateString[{2007, 4, 15, 0}]  
      Sun 15 Apr 2007 00:00:00  
  
>> DateString[{1979, 3, 14}, {"  
DayName", " ", "Month", "-", "  
YearShort"}]  
      Wednesday 03-79
```

Non-integer values are accepted too:

```
>> DateString[{1991, 6, 6.5}]  
      Thu 6 Jun 1991 12:00:00
```

## \$DateStringFormat

```
$DateStringFormat  
    gives the format used for dates generated  
    by DateString.
```

```
>> $DateStringFormat  
      {DateTimeShort}
```

## EasterSunday

```
EasterSunday[year]  
    returns the date of the Gregorian Easter  
    Sunday as {year, month, day}.
```

```
>> EasterSunday[2000]  
      {2000, 4, 23}  
  
>> EasterSunday[2030]  
      {2030, 4, 21}
```

## Now

```
Now  
    gives the current time on the system.
```

```
>> Now
[Sat 3 Jul 2 021 09:35:47 GTM - 5]
```

## Pause

`Pause[n]`  
pauses for  $n$  seconds.

```
>> Pause[0.5]
```

## SessionTime

`SessionTime[]`  
returns the total time in seconds since this session started.

```
>> SessionTime[]
36.9798
```

## \$SystemTimeZone

`$SystemTimeZone`  
gives the current time zone for the computer system on which Mathics is being run.

```
>> $SystemTimeZone
-5.
```

## TimeConstrained

`TimeConstrained[expr, t]`  
evaluates  $expr$ , stopping after  $t$  seconds.  
`TimeConstrained[expr, t, failexpr]`  
returns  $failexpr$  if the time constraint is not met.

```
>> TimeConstrained[Integrate[Sin[x]
^1000000,x],1]
$Aborted
```

```
>> TimeConstrained[Integrate[Sin[x]
^1000000,x], 1, Integrate[Cos[x]
,x]]
Sin[x]
```

```
>> s=TimeConstrained[Integrate[Sin[
x] ^ 3, x], a]
Numberofsecondsaisnotapositivemachine
– sizednumberorInfinity.
```

`TimeConstrained`  $\left[ \int \sin[x]^3 dx, a \right]$

```
>> a=1; s
Cos[x] (-5 + Cos[2x])
6
```

Possible issues: for certain time-consuming functions (like `simplify`) which are based on `sympy` or other libraries, it is possible that the evaluation continues after the timeout. However, at the end of the evaluation, the function will return `$Aborted` and the results will not affect the state of the mathics kernel.

## TimeRemaining

`TimeRemaining[]`  
Gives the number of seconds remaining until the earliest enclosing `TimeConstrained` will request the current computation to stop.  
`TimeConstrained[expr, t, failexpr]`  
returns  $failexpr$  if the time constraint is not met.

If `TimeConstrained` is called out of a `TimeConstrained` expression, returns 'Infinity'

```
>> TimeRemaining[]
∞

>> TimeConstrained[1+2; Print[
TimeRemaining[]], 0.9]
0.89935
```

## TimeUsed

`TimeUsed[]`  
returns the total CPU time used for this session, in seconds.

```
>> TimeUsed[]  
96.4546
```

## \$TimeZone

**\$TimeZone**  
gives the current time zone to assume for dates and times.

```
>> $TimeZone  
-5.
```

## Timing

**Timing[*expr*]**  
measures the processor time taken to evaluate *expr*. It returns a list containing the measured time in seconds and the result of the evaluation.

```
>> Timing[50!]  
{0.00020343, 30 414 093 201 713 378 ~  
~043 612 608 166 064 768 844 377 ~  
~641 568 960 512 000 000 000 000}  
  
>> Attributes[Timing]  
{HoldAll, Protected}
```



## 2. Input and Output

### Contents

BaseForm . . . . .	33	MatrixForm . . . . .	36	Right . . . . .	39
BoxData . . . . .	33	Message . . . . .	36	Row . . . . .	39
Center . . . . .	34	MessageName (::) . . . . .	36	StandardForm . . . . .	39
Check . . . . .	34	NonAssociative . . . . .	36	StringForm . . . . .	39
Format . . . . .	34	NumberForm . . . . .	36	Subscript . . . . .	39
FullForm . . . . .	34	Off . . . . .	37	Subsuperscript . . . . .	39
General . . . . .	34	On . . . . .	37	Superscript . . . . .	39
Grid . . . . .	35	OutputForm . . . . .	37	SympyForm . . . . .	40
Infix . . . . .	35	Postfix (/) . . . . .	37	Syntax . . . . .	40
InputForm . . . . .	35	Precedence . . . . .	38	TableForm . . . . .	40
Left . . . . .	35	Prefix (@) . . . . .	38	TeXForm . . . . .	40
MakeBoxes . . . . .	35	Print . . . . .	38	TextData . . . . .	40
MathMLForm . . . . .	36	PythonForm . . . . .	38	ToBoxes . . . . .	41
		Quiet . . . . .	39		

### BaseForm

`BaseForm[expr, n]`  
prints numbers in *expr* in base *n*.

```
>> BaseForm[33, 2]
100 0012

>> BaseForm[234, 16]
ea16

>> BaseForm[12.3, 2]
1 100.010011001100110012

>> BaseForm[-42, 16]
-2a16

>> BaseForm[x, 2]
x

>> BaseForm[12, 3] // FullForm
BaseForm[12, 3]
```

Bases must be between 2 and 36:

```
>> BaseForm[12, -3]
Positivemachine
— sized integer expected at position 2 in BaseForm[12,
— 3].
MakeBoxes[BaseForm[12, -3],
StandardForm] is not a valid box structure.

>> BaseForm[12, 100]
Requested base 100 must be between 2 and 36.
MakeBoxes[BaseForm[12, 100],
StandardForm] is not a valid box structure.
```

### BoxData

`BoxData[...]`  
is a low-level representation of the contents of a typesetting cell.

## Center

**Center**

is used with the `ColumnAlignments` option to `Grid` or `TableForm` to specify a centered column.

## Check

`Check[expr, failexpr]`

evaluates `expr`, and returns the result, unless messages were generated, in which case it evaluates and `failexpr` will be returned.

`Check[expr, failexpr, {s1::t1, s2::t2, ...}]`

checks only for the specified messages.

Return error when a message is generated:

```
>> Check[1/0, err]
      Infiniteexpression1/0encountered.
      err
```

Check only for specific messages:

```
>> Check[Sin[0^0], err, Sin::argx]
      Indeterminateexpression0^0encountered.
      Indeterminate

>> Check[1/0, err, Power::infy]
      Infiniteexpression1/0encountered.
      err
```

## Format

`Format[expr]`

holds values specifying how `expr` should be printed.

Assign values to `Format` to control how particular expressions should be formatted when printed to the user.

```
>> Format[f[x_]] := Infix[{x}, "~"]

>> f[1, 2, 3]
      1 ~ 2 ~ 3

>> f[1]
      1
```

Raw objects cannot be formatted:

```
>> Format[3] = "three";
      Cannotassigntorawobject3.
```

Format types must be symbols:

```
>> Format[r, a + b] = "r";
      Formattypea + bisnotasymbol.
```

Formats must be attached to the head of an expression:

```
>> f /: Format[g[f]] = "my f";
      Tagnotfoundortoodeepforanassignedrule.
```

## FullForm

`FullForm[expr]`

displays the underlying form of `expr`.

```
>> FullForm[a + b * c]
      Plus[a, Times[b, c]]

>> FullForm[2/3]
      Rational[2, 3]

>> FullForm["A string"]
      "A string"
```

## General

**General**

is a symbol to which all general-purpose messages are assigned.

```
>> General::argr
      '1' called with 1 argument;
      '2' arguments are expected.

>> Message[Rule::argr, Rule, 2]
      Rulecalledwith1argument;2argumentsareexpected.
```

## Grid

`Grid[{{a1, a2, ...}, {b1, b2, ...}, ...}]`

formats several expressions inside a `GridBox`.

```
>> Grid[{{a, b}, {c, d}}]
      a  b
      c  d
```

## Infix

`Infix[expr, oper, prec, assoc]`  
displays *expr* with the infix operator *oper*,  
with precedence *prec* and associativity *assoc*.

`Infix` can be used with `Format` to display certain forms with user-defined infix notation:

```
>> Format[g[x_, y_]] := Infix[{x, y
  }, "#", 350, Left]

>> g[a, g[b, c]]
      a#(b#c)

>> g[g[a, b], c]
      a#b#c

>> g[a + b, c]
      (a + b)#c

>> g[a * b, c]
      ab#c

>> g[a, b] + c
      c + a#b

>> g[a, b] * c
      c(a#b)

>> Infix[{a, b, c}, {"+", "-"}]
      a + b - c
```

## InputForm

`InputForm[expr]`  
displays *expr* in an unambiguous form  
suitable for input.

```
>> InputForm[a + b * c]
      a + b * c

>> InputForm["A string"]
      "A string"
```

```
>> InputForm[f' [x]]
      Derivative[1] [f] [x]

>> InputForm[Derivative[1, 0] [f] [x
  ]]
      Derivative[1, 0] [f] [x]
```

## Left

`Left`

is used with operator formatting constructs to specify a left-associative operator.

## MakeBoxes

`MakeBoxes[expr]`  
is a low-level formatting primitive that  
converts *expr* to box form, without evaluating it.  
`\( ... \)`  
directly inputs box objects.

String representation of boxes

```
>> \(\mathbf{x}^2\)
      SuperscriptBox[x, 2]

>> \(\mathbf{x}_2\)
      SubscriptBox[x, 2]

>> \(\mathbf{a}^b \mathbf{c}\)
      UnderoverscriptBox[a, b, c]

>> \(\mathbf{a} \mathbf{b}^c \mathbf{c}\)
      UnderoverscriptBox[a, c, b]

>> \(\mathbf{x} \mathbf{y}\)
      OverscriptBox[x, y]

>> \(\mathbf{x} \mathbf{y}\)
      UnderscriptBox[x, y]
```

## MathMLForm

`MathMLForm[expr]`  
displays *expr* as a MathML expression.

```
>> MathMLForm[HoldForm[Sqrt[a^3]]]
<math display="block">
  <msqrt><msup><mi>a</mi>
  <mn>3</mn></msup>
</msqrt></math>

>> MathMLForm[\[Mu]]
<math display="block">
  <mi></mi></math>

# This can causes the TeX to fail # »
MathMLForm[Graphics[Text["μ"]]] # = ...
= ...
```

## MatrixForm

`MatrixForm[m]`  
displays a matrix  $m$ , hiding the underlying list structure.

```
>> Array[a,{4,3}]/MatrixForm
( a[1,1] a[1,2] a[1,3]
  a[2,1] a[2,2] a[2,3]
  a[3,1] a[3,2] a[3,3]
  a[4,1] a[4,2] a[4,3] )
```

## Message

`Message[symbol::msg, expr1, expr2, ...]`  
displays the specified message, replacing placeholders in the message text with the corresponding expressions.

```
>> a::b = "Hello world!"
Hello world!

>> Message[a::b]
Helloyou!

>> a::c := "Hello '1', Mr 00'2'!"

>> Message[a::c, "you", 3 + 4]
Helloyou, Mr007!
```

## MessageName (::)

`MessageName[symbol, tag]`  
*symbol::tag*  
identifies a message.

`MessageName` is the head of message IDs of the form `symbol::tag`.

```
>> FullForm[a::b]
MessageName[a,"b"]
```

The second parameter `tag` is interpreted as a string.

```
>> FullForm[a::"b"]
MessageName[a,"b"]
```

## NonAssociative

`NonAssociative`  
is used with operator formatting constructs to specify a non-associative operator.

## NumberForm

`NumberForm[expr, n]`  
prints a real number  $expr$  with  $n$ -digits of precision.  
`NumberForm[expr, {n, f}]`  
prints with  $n$ -digits and  $f$  digits to the right of the decimal point.

```
>> NumberForm[N[Pi], 10]
3.141592654

>> NumberForm[N[Pi], {10, 5}]
3.14159
```

## Off

`Off[symbol::tag]`  
turns a message off so it is no longer printed.

```
>> Off[Power::infy]
```

```
>> 1 / 0
ComplexInfinity

>> Off[Power::indet, Syntax::com]

>> {0 ^ 0,}
{Indeterminate, Null}
```

## On

`On[symbol::tag]`  
turns a message on for printing.

```
>> Off[Power::infy]

>> 1 / 0
ComplexInfinity

>> On[Power::infy]

>> 1 / 0
Infiniteexpression1/0encountered.
ComplexInfinity
```

## OutputForm


`OutputForm[expr]`  
displays *expr* in a plain-text form.

```
>> OutputForm[f' [x]]
f' [x]

>> OutputForm[Derivative[1, 0] [f] [x]]
Derivative[1,0] [f] [x]

>> OutputForm["A string"]
A string
```

```
>> OutputForm[Graphics[Rectangle
[]]]
```



## Postfix (//)

$x // f$   
is equivalent to  $f[x]$ .

```
>> b // a
a[b]

>> c // b // a
a[b[c]]
```

The postfix operator `//` is parsed to an expression before evaluation:

```
>> Hold[x // a // b // c // d // e
// f]
Hold[f[e[d[c[b[a[x]]]]]]]
```

## Precedence

`Precedence[op]`  
returns the precedence of the built-in operator *op*.

```
>> Precedence[Plus]
310.

>> Precedence[Plus] < Precedence[
Times]
True
```

Unknown symbols have precedence 670:

```
>> Precedence[f]
670.
```

Other expressions have precedence 1000:

```
>> Precedence[a + b]
1000.
```

## Prefix (@)

$f @ x$   
is equivalent to  $f[x]$ .

```
>> a @ b
a[b]

>> a @ b @ c
a[b[c]]

>> Format[p[x_]] := Prefix[{x},
" * "]

>> p[3]
*3

>> Format[q[x_]] := Prefix[{x}, "~
", 350]

>> q[a+b]
~ (a + b)

>> q[a*b]
~ ab

>> q[a]+b
b+ ~ a
```

The prefix operator @ is parsed to an expression before evaluation:

```
>> Hold[a @ b @ c @ d @ e @ f @ x]
Hold[a[b[c[d[e[f[x]]]]]]]
```

## Print

`Print[expr, ...]`  
prints each *expr* in string form.

```
>> Print["Hello world!"]
Hello world!
```

```
>> Print["The answer is ", 7 * 6,
"."]
```

*The answer is 42.*

## PythonForm

`PythonForm[expr]`  
returns an approximate equivalent of *expr* in Python, when that is possible. We assume that Python has sympy imported. No explicit import will be include in the result.

```
>> PythonForm[Infinity]
math.inf

>> PythonForm[Pi]
sympy.pi

>> E // PythonForm
sympy.E

>> {1, 2, 3} // PythonForm
[1, 2, 3]
```

## Quiet

`Quiet[expr, {s1::t1, ...}]`  
evaluates *expr*, without messages {s1::t1, ...} being displayed.  
`Quiet[expr, All]`  
evaluates *expr*, without any messages being displayed.  
`Quiet[expr, None]`  
evaluates *expr*, without all messages being displayed.  
`Quiet[expr, off, on]`  
evaluates *expr*, with messages *off* being suppressed, but messages *on* being displayed.

Evaluate without generating messages:

```
>> Quiet[1/0]
ComplexInfinity
```

Same as above:

```
>> Quiet[1/0, All]
ComplexInfinity
```

```
>> a::b = "Hello";

>> Quiet[x+x, {a::b}]
2x

>> Quiet[Message[a::b]; x+x, {a::b
}]
2x

>> Message[a::b]; y=Quiet[Message[a
::b]; x+x, {a::b}]; Message[a::b
]; y
Hello
Hello
2x

>> Quiet[x + x, {a::b}, {a::b}]
InQuiet[x + x, {a :: b},
{a :: b}]the messagename(s){a :: b} appear in both the list of messages to be displayed and the list of messages to switch on.
Quiet [x + x, {a::b}, {a::b}]
```

## Right

`Right`  
is used with operator formatting constructs to specify a right-associative operator.

## Row

`Row[{expr, ...}]`  
formats several expressions inside a `RowBox`.

## StandardForm

`StandardForm[expr]`  
displays `expr` in the default form.

```
>> StandardForm[a + b * c]
a + bc

>> StandardForm["A string"]
A string
```

`StandardForm` is used by default:

```
>> "A string"
A string

>> f'[x]
f'[x]
```

## StringForm

`StringForm[str, expr1, expr2, ...]`  
displays the string *str*, replacing placeholders in *str* with the corresponding expressions.

```
>> StringForm["'1' bla '2' blub '"
bla '2'", a, b, c]
'1' bla blub '2' bla blub '2'
```

## Subscript

`Subscript[a, i]`  
displays as  $a_i$ .

```
>> Subscript[x,1,2,3] // TeXForm
x_{1,2,3}
```

## Subsuperscript

`Subsuperscript[a, b, c]`  
displays as  $a_b^c$ .

```
>> Subsuperscript[a, b, c] //
TeXForm
a_b^c
```

## Superscript

`Superscript[x, y]`  
displays as  $x^y$ .

```
>> Superscript[x,3] // TeXForm
x^3
```

## SympyForm

`SympyForm[expr]`  
returns an Sympy *expr* in Python. Sympy is used internally to implement a number of Mathics functions, like Simplify.

```
>> SympyForm[Pi^2]
pi**2
>> E^2 + 3E // SympyForm
exp(2) + 3*E
```

## Syntax

`Syntax`  
is a symbol to which all syntax messages are assigned.

```
>> 1 +
>> Sin[1]
>> ^ 2
>> 1.5‘‘
```


## TableForm

`TableForm[expr]`  
displays *expr* as a table.

```
>> TableForm[Array[a, {3,2}],
TableDepth->1]
{a[1,1], a[1,2]}
{a[2,1], a[2,2]}
{a[3,1], a[3,2]}
```

A table of Graphics:

```
>> Table[Style[Graphics[{EdgeForm[{
Black}], RGBColor[r,g,b],
Rectangle[]}],
ImageSizeMultipliers->{0.2, 1}],
{r,0,1,1/2}, {g,0,1,1/2}, {b
,0,1,1/2}] // TableForm
```



## TeXForm

`TeXForm[expr]`  
displays *expr* using TeX math mode commands.

```
>> TeXForm[HoldForm[Sqrt[a^3]]]
\sqrt{a^3}
```

## TextData

`TextData[...]`  
is a low-level representation of the contents of a textual cell.



## ToBoxes

`ToBoxes[expr]`  
evaluates *expr* and converts the result to box form.

Unlike `MakeBoxes`, `ToBoxes` evaluates its argument:

```
>> ToBoxes[a + a]
RowBox[{2, a}]

>> ToBoxes[a + b]
RowBox[{a, +, b}]

>> ToBoxes[a ^ b] // FullForm
SuperscriptBox["a", "b"]
```

## 3. Procedural Programming

Procedural programming is a programming paradigm, derived from imperative programming, based on the concept of the procedure call. This term is sometimes compared and contrasted with Functional Programming.

Procedures (a type of routine or subroutine) sim-

ply contain a series of computational steps to be carried out. Any given procedure might be called at any point during a program's execution, including by other procedures or itself.

Procedural functions are integrated into Mathics symbolic programming environment.

### Contents

---

Abort . . . . .	42	FixedPoint . . . . .	43	NestWhile . . . . .	45
Break . . . . .	42	FixedPointList . . . . .	44	Return . . . . .	45
Catch . . . . .	43	For . . . . .	44	Switch . . . . .	45
CompoundExpression (;) . . . . .	43	If . . . . .	44	Throw . . . . .	46
Continue . . . . .	43	Interrupt . . . . .	44	Which . . . . .	46
Do . . . . .	43	Nest . . . . .	44	While . . . . .	46
		NestList . . . . .	45		

---

### Abort

**Abort[]**  
aborts an evaluation completely and returns `$Aborted`.

```
>> Print["a"]; Abort[]; Print["b"]
a
$Aborted
```

### Break

**Break[]**  
exits a For, While, or Do loop.

```
>> n = 0;

>> While[True, If[n>10, Break[]]; n
    =n+1]

>> n
11
```

### Catch

**Catch[*expr*]**  
returns the argument of the first `Throw` generated in the evaluation of *expr*.  
**Catch[*expr*, *form*]**  
returns value from the first `Throw[value, tag]` for which *form* matches *tag*.  
**Catch[*expr*, *form*, *f*]**  
returns *f[*value*, *tag*]*.

Exit to the enclosing `Catch` as soon as `Throw` is evaluated:

```
>> Catch[r; s; Throw[t]; u; v]
t
```

Define a function that can “throw an exception”:

```
>> f[x_] := If[x > 12, Throw[
    overflow], x!]
```

The result of `Catch` is just what is thrown by `Throw`:

```
>> Catch[f[1] + f[15]]
overflow

>> Catch[f[1] + f[4]]
25
```

## CompoundExpression (;)

`CompoundExpression[e1, e2, ...]`  
`e1; e2; ...`  
evaluates its arguments in turn, returning the last result.

```
>> a; b; c; d
d
```

If the last argument is omitted, `Null` is taken:

```
>> a;
```

## Continue

`Continue[]`  
continues with the next iteration in a `For`, `While`, or `Do` loop.

```
>> For[i=1, i<=8, i=i+1, If[Mod[i,2] == 0, Continue[]]; Print[i]]
1
3
5
7
```

## Do

`Do[expr, {max}]`  
evaluates *expr* *max* times.  
`Do[expr, {i, max}]`  
evaluates *expr* *max* times, substituting *i* in *expr* with values from 1 to *max*.  
`Do[expr, {i, min, max}]`  
starts with *i* = *max*.  
`Do[expr, {i, min, max, step}]`  
uses a step size of *step*.  
`Do[expr, {i, {i1, i2, ...}}]`  
uses values *i1*, *i2*, ... for *i*.  
`Do[expr, {i, imin, imax}, {j, jmin, jmax}, ...]`  
evaluates *expr* for each *j* from *jmin* to *jmax*, for each *i* from *imin* to *imax*, etc.

```
>> Do[Print[i], {i, 2, 4}]
2
3
4
```

```
>> Do[Print[{i, j}], {i,1,2}, {j,3,5}]
{1,3}
{1,4}
{1,5}
{2,3}
{2,4}
{2,5}
```

You can use `Break[]` and `Continue[]` inside `Do`:

```
>> Do[If[i > 10, Break[], If[Mod[i,2] == 0, Continue[]]; Print[i]], {i, 5, 20}]
5
7
9
```

## FixedPoint

`FixedPoint[f, expr]`  
starting with *expr*, iteratively applies *f* until the result no longer changes.  
`FixedPoint[f, expr, n]`  
performs at most *n* iterations. The same that using `$MaxIterations->n`

```
>> FixedPoint[Cos, 1.0]
0.739085

>> FixedPoint[#+1 &, 1, 20]
21
```

## FixedPointList

`FixedPointList[f, expr]`  
starting with *expr*, iteratively applies *f* until the result no longer changes, and returns a list of all intermediate results.  
`FixedPointList[f, expr, n]`  
performs at most *n* iterations.

```
>> FixedPointList[Cos, 1.0, 4]
{1., 0.540302, 0.857~
~553, 0.65429, 0.79348}
```

Observe the convergence of Newton's method for approximating square roots:

```
>> newton[n_] := FixedPointList
    [.5(# + n/#)&, 1.];

>> newton[9]
{1., 5., 3.4, 3.02353, 3.00009, 3., 3., 3.}
```

Plot the “hailstone” sequence of a number:


```
>> collatz[1] := 1;

>> collatz[x_ ? EvenQ] := x / 2;

>> collatz[x_] := 3 x + 1;

>> list = FixedPointList[collatz,
    14]
{14, 7, 22, 11, 34, 17, 52, 26, 13,
    40, 20, 10, 5, 16, 8, 4, 2, 1, 1}

>> ListLinePlot[list]
```



## For

```
For[start, test, incr, body]
    evaluates start, and then iteratively body
    and incr as long as test evaluates to True.
For[start, test, incr]
    evaluates only incr and no body.
For[start, test]
    runs the loop without any body.
```

Compute the factorial of 10 using For:

```
>> n := 1

>> For[i=1, i<=10, i=i+1, n = n * i]

>> n
3 628 800

>> n == 10!
True
```

## If

```
If[cond, pos, neg]
    returns pos if cond evaluates to True, and
    neg if it evaluates to False.
If[cond, pos, neg, other]
    returns other if cond evaluates to neither
    True nor False.
If[cond, pos]
    returns Null if cond evaluates to False.
```

```
>> If[1<2, a, b]
a
```

If the second branch is not specified, Null is taken:

```
>> If[1<2, a]
a

>> If[False, a] //FullForm
Null
```

You might use comments (inside (\* and \*)) to make the branches of If more readable:

```
>> If[a, (*then*)b, (*else*)c];
```

## Interrupt

```
Interrupt[]
    Interrupt an evaluation and returns
    $Aborted.
```

```
>> Print["a"]; Interrupt[]; Print["
b"]
a
$Aborted
```

## Nest

```
Nest[f, expr, n]
    starting with expr, iteratively applies f n
    times and returns the final result.
```

```
>> Nest[f, x, 3]
f[f[f[x]]]

>> Nest[(1+#)^2 &, x, 2]
(1 + (1 + x)2)2
```

## NestList

`NestList[f, expr, n]`  
starting with *expr*, iteratively applies *f* *n* times and returns a list of all intermediate results.

```
>> NestList[f, x, 3]
{x, f[x], f[f[x]], f[f[f[x]]]}


>> NestList[2 # &, 1, 8]
{1, 2, 4, 8, 16, 32, 64, 128, 256}
```

Chaos game rendition of the Sierpinski triangle:

```
>> vertices = {{0,0}, {1,0}, {.5,
.5 Sqrt[3]}};

>> points = NestList[.5(vertices[[
RandomInteger[{1,3}] ] + #)&,
{0.,0.}, 2000];

>> Graphics[Point[points],
ImageSize->Small]
```



## NestWhile

`NestWhile[f, expr, test]`  
applies a function *f* repeatedly on an expression *expr*, until applying *test* on the result no longer yields True.

`NestWhile[f, expr, test, m]`  
supplies the last *m* results to *test* (default value: 1).

`NestWhile[f, expr, test, All]`  
supplies all results gained so far to *test*.

Divide by 2 until the result is no longer an integer:

```
>> NestWhile[#/2&, 10000, IntegerQ]
625
 2
```

## Return

`Return[expr]`  
aborts a function call and returns *expr*.

```
>> f[x_] := (If[x < 0, Return[0]];
x)

>> f[-1]
0

>> Do[If[i > 3, Return[]]; Print[i], {i, 10}]
1
2
3
```

Return only exits from the innermost control flow construct.

```
>> g[x_] := (Do[If[x < 0, Return
[0]], {i, {2, 1, 0, -1}}]; x)

>> g[-1]
-1
```

## Switch

`Switch[expr, pattern1, value1, pattern2, value2, ...]`  
yields the first *value* for which *expr* matches the corresponding *pattern*.

```
>> Switch[2, 1, x, 2, y, 3, z]
y

>> Switch[5, 1, x, 2, y]
Switch[5, 1, x, 2, y]

>> Switch[5, 1, x, 2, a, _, b]
b

>> Switch[2, 1]
Switch called with 2 arguments. Switch must be called with an odd number of arguments.
```

## Throw

```
Throw['value']
  stops evaluation and returns 'value' as
  the value of the nearest enclosing Catch.
Catch['value', 'tag']
  is caught only by 'Catch[expr,form]',
  where tag matches form.
```

Using Throw can affect the structure of what is returned by a function:

```
>> NestList[#^2 + 1 &, 1, 7]
{1, 2, 5, 26, 677, 458 330,
 210 066 388 901, 44 127 ~
~887 745 906 175 987 802}

>> Catch[NestList[If[# > 1000,
  Throw[#], #^2 + 1] &, 1, 7]]
458 330

>> Throw[1]
UncaughtHold[Throw[1]]returnedtotoplevel.
Hold[Throw[1]]
```

## Which

```
Which[cond1, expr1, cond2, expr2, ...]
  yields expr1 if cond1 evaluates to True,
  expr2 if cond2 evaluates to True, etc.
```

```
>> n = 5;

>> Which[n == 3, x, n == 5, y]
y

>> f[x_] := Which[x < 0, -x, x ==
  0, 0, x > 0, x]

>> f[-3]
3
```

If no test yields True, Which returns Null:

```
>> Which[False, a]
```

If a test does not evaluate to True or False, evaluation stops and a Which expression containing the remaining cases is returned:

```
>> Which[False, a, x, b, True, c]
Which[x, b, True, c]
```

Which must be called with an even number of

arguments:

```
>> Which[a, b, c]
Whichcalledwith3arguments.
Which[a, b, c]
```

## While

```
While[test, body]
  evaluates body as long as test evaluates to
  True.
While[test]
  runs the loop without any body.
```

Compute the GCD of two numbers:

```
>> {a, b} = {27, 6};

>> While[b != 0, {a, b} = {b, Mod[a
  , b]};

>> a
3
```

## 4. Global System Information

### Contents

---

<code>\$Aborted</code> . . . . .	47	<code>MathicsVersion</code> . . . . .	48	<code>\$ScriptCommandLine</code> .	49
<code>\$ByteOrdering</code> . . . . .	47	<code>MemoryAvailable</code> . . . .	48	<code>Share</code> . . . . .	49
<code>\$CommandLine</code> . . . . .	47	<code>MemoryInUse</code> . . . . .	48	<code>\$SystemID</code> . . . . .	49
<code>Environment</code> . . . . .	47	<code>Names</code> . . . . .	48	<code>\$SystemMemory</code> . . . .	49
<code>\$Failed</code> . . . . .	47	<code>\$Packages</code> . . . . .	48	<code>\$SystemWordLength</code> .	50
<code>GetEnvironment</code> . . . .	47	<code>\$ParentProcessID</code> . . . .	49	<code>\$UserName</code> . . . . .	50
<code>\$Machine</code> . . . . .	48	<code>\$ProcessID</code> . . . . .	49	<code>\$Version</code> . . . . .	50
<code>\$MachineName</code> . . . . .	48	<code>\$ProcessorType</code> . . . . .	49	<code>\$VersionNumber</code> . . . .	50
		<code>Run</code> . . . . .	49		

---

### `$Aborted`

`$Aborted`  
is returned by a calculation that has been aborted.

### `$ByteOrdering`

`$ByteOrdering`  
returns the native ordering of bytes in binary data on your computer system.

```
>> $ByteOrdering
-1
```

### `$CommandLine`

`$CommandLine`  
is a list of strings passed on the command line to launch the Mathics session.

```
>> $CommandLine
{mathics/docpipeline.py, -ot, -k}
```

### `Environment`

`Environment[var]`  
gives the value of an operating system environment variable.

```
>> Environment["HOME"]
/home/rocky
```

### `$Failed`

`$Failed`  
is returned by some functions in the event of an error.

### `GetEnvironment`

`GetEnvironment["var"]`  
gives the setting corresponding to the variable “*var*” in the operating system environment.

```
>> GetEnvironment["HOME"]
HOME -> /home/rocky
```

## \$Machine

**\$Machine**  
returns a string describing the type of computer system on which the Mathics is being run.

```
>> $Machine  
linux
```

## \$MachineName

**\$MachineName**  
is a string that gives the assigned name of the computer on which Mathics is being run, if such a name is defined.

```
>> $MachineName  
muffin
```

## MathicsVersion

**MathicsVersion**  
this string is the version of Mathics we are running.

```
>> MathicsVersion  
3.1.0
```

## MemoryAvailable

**MemoryAvailable**  
Returns the amount of the available physical memory.

```
>> MemoryAvailable[]  
4667019264
```

The relationship between `$SystemMemory`, `MemoryAvailable`, and `MemoryInUse`:

```
>> $SystemMemory > MemoryAvailable  
[] > MemoryInUse[]  
True
```

## MemoryInUse

**MemoryInUse[]**  
Returns the amount of memory used by the definitions object.

```
>> MemoryInUse[]  
56
```

## Names

**Names["pattern"]**  
returns the list of names matching *pattern*.

```
>> Names["List"]  
{List}
```

The wildcard `*` matches any character:

```
>> Names["List*"]  
{List, ListLinePlot,  
ListPlot, ListQ, Listable}
```

The wildcard `@` matches only lowercase characters:

```
>> Names["List@"]  
{Listable}
```

```
>> x = 5;
```

```
>> Names["Global'"]  
{x}
```

The number of built-in symbols:

```
>> Length[Names["System'"]]  
1109
```

## \$Packages

**\$Packages**  
returns a list of the contexts corresponding to all packages which have been loaded into Mathics.

```
>> $Packages  
{ImportExport', XML',  
Internal', System', Global'}
```



## \$ParentProcessID

**\$ParentProcessID**

gives the ID assigned to the process which invokes the *Mathics* by the operating system under which it is run.

```
>> $ParentProcessID
3883171
```

## \$ProcessID

**\$ProcessID**

gives the ID assigned to the *Mathics* process by the operating system under which it is run.

```
>> $ProcessID
3883173
```

## \$ProcessorType

**\$ProcessorType**

gives a string giving the architecture of the processor on which the *Mathics* is being run.

```
>> $ProcessorType
x86_64
```

## Run

**Run[command]**

runs command as an external operating system command, returning the exit code obtained.

```
>> Run["date"]
0
```

## \$ScriptCommandLine

**\$ScriptCommandLine**

is a list of string arguments when running the kernel in script mode.

```
>> $ScriptCommandLine
{}
```

## Share

**Share[]**

Tries to reduce the amount of memory required to store definitions, by reducing duplicated definitions. Now it just does nothing.

**Share[Symbol]**

Tries to reduce the amount of memory required to store definitions associated to *Symbol*.

```
>> Share[]
0
```

## \$SystemID

**\$SystemID**

is a short string that identifies the type of computer system on which the *Mathics* is being run.

```
>> $SystemID
linux
```

## \$SystemMemory

**\$SystemMemory**

Returns the total amount of physical memory.

```
>> $SystemMemory
33691602944
```

## \$SystemWordLength

**\$SystemWordLength**

gives the effective number of bits in raw machine words on the computer system where *Mathics* is running.

```
>> $SystemWordLength
64
```

## **\$UserName**

**\$UserName**  
returns a string describing the type of computer system on which *Mathics* is being run.

```
>> $UserName
rocky
```

## **\$Version**

**\$Version**  
returns a string with the current *Mathics* version and the versions of relevant libraries.

```
>> $Version
Mathics 3.1.0 on CPython 3.6.13
(default, Feb 23 2021, 10:08:17)
using SymPy 1.8, mpmath 1.2.1,
numpy 1.19.5, cython 0.29.22
```

## **\$VersionNumber**

**\$VersionNumber**  
is a real number which gives the current Wolfram Language version that *Mathics* tries to be compatible with.

```
>> $VersionNumber
10.
```

## 5. SparseArray Functions

### Contents

---

SparseArray . . . . . 51

---

### SparseArray

`SparseArray[rules]`  
Builds a sparse array according to the list of *rules*.  
`SparseArray[rules, dims]`  
Builds a sparse array of dimensions *dims* according to the *rules*.  
`SparseArray[list]`  
Builds a sparse representation of *list*.

```
>> SparseArray[{{1, 2} -> 1, {2, 1} -> 1}]  
  
SparseArray[Automatic, {2, 2},  
0, {{1, 2} -> 1, {2, 1} -> 1}]  
  
>> SparseArray[{{1, 2} -> 1, {2, 1} -> 1}, {3, 3}]  
  
SparseArray[Automatic, {3, 3},  
0, {{1, 2} -> 1, {2, 1} -> 1}]  
  
>> M=SparseArray[{{0, a}, {b, 0}}]  
  
SparseArray[Automatic, {2, 2},  
0, {{1, 2} -> a, {2, 1} -> b}]  
  
>> M //Normal  
{{0, a}, {b, 0}}
```

## 6. Solving Recurrence Equations

### Contents

---

RSolve . . . . . 52

---

### RSolve

`RSolve[eqn, a[n], n]`  
solves a recurrence equation for the function  $a[n]$ .

Solve a difference equation:

```
>> RSolve[a[n] == a[n+1], a[n], n]
{{a[n] -> C[0]}}
```

No boundary conditions gives two general parameters:

```
>> RSolve[{a[n + 2] == a[n]}, a, n]
{{a -> (Function[{n}, C[0] + C[1] - 1^n])}}
```

Include one boundary condition:

```
>> RSolve[{a[n + 2] == a[n], a[0] == 1}, a, n]
{{a -> (Function[{n}, C[0] + (1 - C[0]) - 1^n])}}
```

Get a “pure function” solution for a with two boundary conditions:

```
>> RSolve[{a[n + 2] == a[n], a[0] == 1, a[1] == 4}, a, n]
{{a -> (Function[{n}, 5/2 - (3 - 1^n)/2])}}
```

## 7. Patterns and Rules

Some examples:

```
>> a + b + c /. a + b -> t
c + t

>> a + 2 + b + c + x * y /.
n_Integer + s__Symbol + rest_ ->
{n, s, rest}
{2, a, b + c + xy}

>> f[a, b, c, d] /. f[first_,
rest___] -> {first, {rest}}
{a, {b, c, d}}
```

Tests and Conditions:

```
>> f[4] /. f[x_?(# > 0&)] -> x ^ 2
16

>> f[4] /. f[x_] /; x > 0 -> x ^ 2
16
```

Leaves in the beginning of a pattern rather

match fewer leaves:

```
>> f[a, b, c, d] /. f[start__,
end__] -> {{start}, {end}}
{{a}, {b, c, d}}
```

Optional arguments using Optional:

```
>> f[a] /. f[x_, y_:3] -> {x, y}
{a, 3}
```

Options using OptionsPattern and OptionValue:

```
>> f[y, a->3] /. f[x_,
OptionsPattern[{a->2, b->5}]] ->
{x, OptionValue[a], OptionValue
[b]}
{y, 3, 5}
```

The attributes Flat, Orderless, and OneIdentity affect pattern matching.

### Contents

Alternatives ( ) . . . . .	53	Longest . . . . .	55	Replace . . . . .	58
Blank . . . . .	54	MatchQ . . . . .	55	ReplaceAll (/.) . . . . .	58
BlankNullSequence . . . . .	54	Optional (:) . . . . .	56	ReplaceList . . . . .	59
BlankSequence . . . . .	54	OptionsPattern . . . . .	56	ReplaceRepeated (//.) . . . . .	59
Condition (/;) . . . . .	55	PatternTest (?) . . . . .	56	RuleDelayed (:>) . . . . .	59
Dispatch . . . . .	55	Pattern . . . . .	57	Rule (->) . . . . .	59
Except . . . . .	55	Repeated (..) . . . . .	57	Verbatim . . . . .	59
HoldPattern . . . . .	55	RepeatedNull (...) . . . . .	57		

### Alternatives (|)

Alternatives[*p*<sub>1</sub>, *p*<sub>2</sub>, ..., *p*<sub>*i*</sub>]  
*p*<sub>1</sub> | *p*<sub>2</sub> | ... | *p*<sub>*i*</sub>  
 is a pattern that matches any of the patterns '*p*<sub>1</sub>, *p*<sub>2</sub>, ..., *p*<sub>*i*</sub>'.

```
>> a+b+c+d/.(a|b)->t
c + d + 2t
```

Alternatives can also be used for string expressions

```
>> StringReplace["0123 3210", "1" |
"2" -> "X"]
0XX3 3XX0
```

## Blank

```
Blank[]
-
  represents any single expression in a pattern.
Blank[h]
_h
  represents any expression with head h.
```

```
>> MatchQ[a + b, _]
True
```

Patterns of the form `_h` can be used to test the types of objects:

```
>> MatchQ[42, _Integer]
True

>> MatchQ[1.0, _Integer]
False

>> {42, 1.0, x} /. {_Integer -> "integer", _Real -> "real"} //
InputForm
{"integer", "real", x}
```

Blank only matches a single expression:

```
>> MatchQ[f[1, 2], f[_]]
False
```

## BlankNullSequence

```
BlankNullSequence[]
---
  represents any sequence of expression
  leaves in a pattern, including an empty
  sequence.
```

BlankNullSequence is like BlankSequence, except it can match an empty sequence:

```
>> MatchQ[f[], f[___]]
True
```

## BlankSequence

```
BlankSequence[]
--
  represents any non-empty sequence of
  expression leaves in a pattern.
BlankSequence[h]
__h
  represents any sequence of leaves, all of
  which have head h.
```

Use a BlankSequence pattern to stand for a non-empty sequence of arguments:

```
>> MatchQ[f[1, 2, 3], f[___]]
True

>> MatchQ[f[], f[___]]
False
```

`__h` will match only if all leaves have head *h*:

```
>> MatchQ[f[1, 2, 3], f[__Integer]]
True

>> MatchQ[f[1, 2.0, 3], f[__Integer]]
False
```

The value captured by a named BlankSequence pattern is a Sequence object:

```
>> f[1, 2, 3] /. f[x__] -> x
Sequence[1, 2, 3]
```

## Condition (/;)

```
Condition[pattern, expr]
pattern /; expr
  places an additional constraint on pattern
  that only allows it to match if expr evaluates to True.
```

The controlling expression of a Condition can use variables from the pattern:

```
>> f[3] /. f[x_] /; x>0 -> t
t

>> f[-3] /. f[x_] /; x>0 -> t
f[-3]
```

Condition can be used in an assignment:

```
>> f[x_] := p[x] /; x>0
```

```
>> f[3]
p[3]

>> f[-3]
f[-3]
```

## Dispatch

`Dispatch[rulelist]`  
Introduced for compatibility. Currently, it just return *rulelist*. In the future, it should return an optimized `DispatchRules` atom, containing an optimized set of rules.

## Except

`Except[c]`  
represents a pattern object that matches any expression except those matching *c*.  
`Except[c, p]`  
represents a pattern object that matches *p* but not *c*.

```
>> Cases[{x, a, b, x, c}, Except[x]]
{a, b, c}

>> Cases[{a, 0, b, 1, c, 2, 3}, Except[1, _Integer]]
{0, 2, 3}
```

Except can also be used for string expressions:

```
>> StringReplace["Hello world!", Except[LetterCharacter] -> ""]
Helloworld
```

## HoldPattern

`HoldPattern[expr]`  
is equivalent to *expr* for pattern matching, but maintains it in an unevaluated form.

```
>> HoldPattern[x + x]
HoldPattern[x + x]
```

```
>> x /. HoldPattern[x] -> t
t
```

`HoldPattern` has attribute `HoldAll`:

```
>> Attributes[HoldPattern]
{HoldAll, Protected}
```

## Longest

```
>> StringCases["aabaab", Longest["a" ~~__ ~~"b"]]
{aabaab}

>> StringCases["aabaab", Longest[RegularExpression["a+b"]]]
{aab, aab}
```

## MatchQ

`MatchQ[expr, form]`  
tests whether *expr* matches *form*.

```
>> MatchQ[123, _Integer]
True

>> MatchQ[123, _Real]
False

>> MatchQ[_Integer][123]
True

>> MatchQ[3, Pattern[3]]
FirstelementinpatternPattern[3]isnotavalidpatternname.
False
```

## Optional (:)

`Optional[patt, default]`  
*patt* : *default*  
is a pattern which matches *patt*, which if omitted should be replaced by *default*.

```
>> f[x_, y_:1] := {x, y}

>> f[1, 2]
{1, 2}
```

```
>> f[a]
{a, 1}
```

Note that *symb* : *patt* represents a Pattern object. However, there is no disambiguity, since *symb* has to be a symbol in this case.

```
>> x:_ // FullForm
Pattern[x, Blank[]]

>> _:d // FullForm
Optional[Blank[], d]

>> x:+y_:d // FullForm
Pattern[x, Plus[Blank[],
Optional[Pattern[y, Blank[]], d]]]
```

*s\_.* is equivalent to *Optional[s\_]* and represents an optional parameter which, if omitted, gets its value from *Default*.

```
>> FullForm[s_.]
Optional[Pattern[s, Blank[]]]

>> Default[h, k_] := k

>> h[a] /. h[x_, y_.] -> {x, y}
{a, 2}
```

## OptionsPattern

**OptionsPattern[f]**  
is a pattern that stands for a sequence of options given to a function, with default values taken from *Options[f]*. The options can be of the form *opt->value* or *opt:>value*, and might be in arbitrarily nested lists.

**OptionsPattern[{opt1->value1, ...}]**  
takes explicit default values from the given list. The list may also contain symbols *f*, for which *Options[f]* is taken into account; it may be arbitrarily nested. *OptionsPattern[{}]* does not use any default values.

The option values can be accessed using *OptionValue*.

```
>> f[x_, OptionsPattern[{n->2}]] :=
x ^ OptionValue[n]

>> f[x]
x2
```

```
>> f[x, n->3]
x3
```

Delayed rules as options:

```
>> e = f[x, n:>a]
xa

>> a = 5;

>> e
x5
```

Options might be given in nested lists:

```
>> f[x, {{n->4}}]
x4
```

## PatternTest (?)

**PatternTest[pattern, test]**  
*pattern* ? *test*  
constrains *pattern* to match *expr* only if the evaluation of *test[expr]* yields *True*.

```
>> MatchQ[3, _Integer?(#>0&)]
True

>> MatchQ[-3, _Integer?(#>0&)]
False

>> MatchQ[3, Pattern[3]]
FirstelementinpatternPattern[3]isnotavalidpatternname.
False
```

## Pattern

**Pattern[symb, patt]**  
*symb* : *patt*  
assigns the name *symb* to the pattern *patt*.

*symb\_head*  
is equivalent to *symb* : *\_head* (accordingly with *\_* and *\_\_*).

*symb* : *patt* : *default*  
is a pattern with name *symb* and default value *default*, equivalent to *Optional[patt : symb, default]*.

```
>> FullForm[a_b]
Pattern[a, Blank[b]]
```



```
>> FullForm[a:_:b]
Optional[Pattern[a,Blank[]],b]
```

Pattern has attribute HoldFirst, so it does not evaluate its name:

```
>> x = 2
2
>> x_
x_
```

Nested Pattern assign multiple names to the same pattern. Still, the last parameter is the default value.

```
>> f[y] /. f[a:b,_:d] -> {a, b}
f[y]
```

This is equivalent to:

```
>> f[a] /. f[a:_:b] -> {a, b}
{a,b}
```

FullForm:

```
>> FullForm[a:b:c:d:e]
Optional[Pattern[a,b],
Optional[Pattern[c,d],e]]
>> f[] /. f[a:_:b] -> {a, b}
{b,b}
```

## Repeated (..)

**Repeated[*pattern*]**  
matches one or more occurrences of *pattern*.

```
>> a_Integer.. // FullForm
Repeated[Pattern[a,Blank[Integer]]]
>> 0..1//FullForm
Repeated[0]
>> {{}, {a}, {a, b}, {a, a, a}, {a,
a, a, a}} /. {Repeated[x : a |
b, 3]} -> x
{{}, a, {a,b}, a, {a,a,a,a}}
>> f[x, 0, 0, 0] /. f[x, s:0..] ->
s
Sequence[0,0,0]
```

## RepeatedNull (...)

**RepeatedNull[*pattern*]**  
matches zero or more occurrences of *pattern*.

```
>> a___Integer...//FullForm
RepeatedNull[Pattern[a,
BlankNullSequence[Integer]]]
>> f[x] /. f[x, 0...] -> t
t
```

## Replace

**Replace[*expr*, *x* -> *y*]**  
yields the result of replacing *expr* with *y* if it matches the pattern *x*.  
**Replace[*expr*, *x* -> *y*, *levelspec*]**  
replaces only subexpressions at levels specified through *levelspec*.  
**Replace[*expr*, {*x* -> *y*, ...}]**  
performs replacement with multiple rules, yielding a single result expression.  
**Replace[*expr*, {{*a* -> *b*, ...}, {*c* -> *d*, ...}, ...}]**  
returns a list containing the result of performing each set of replacements.

```
>> Replace[x, {x -> 2}]
2
```

By default, only the top level is searched for matches

```
>> Replace[1 + x, {x -> 2}]
1 + x
>> Replace[x, {{x -> 1}, {x -> 2}}]
{1,2}
```

Replace stops after the first replacement

```
>> Replace[x, {x -> {}, _List -> y
}]
{}
```

Replace replaces the deepest levels first

```
>> Replace[x[1], {x[1] -> y, 1 ->
2}, All]
x[2]
```

By default, heads are not replaced

```
>> Replace[x[x[y]], x -> z, All]
x[x[y]]
```

Heads can be replaced using the Heads option

```
>> Replace[x[x[y]], x -> z, All,
Heads -> True]
z[z[y]]
```

Note that heads are handled at the level of leaves

```
>> Replace[x[x[y]], x -> z, {1},
Heads -> True]
z[x[y]]
```

You can use Replace as an operator

```
>> Replace[{x_ -> x + 1}] [10]
11
```

## ReplaceAll (/.)

`ReplaceAll[expr, x -> y]`  
`expr /. x -> y`  
yields the result of replacing all subexpressions of `expr` matching the pattern `x` with `y`.  
`expr /. {x -> y, ...}`  
performs replacement with multiple rules, yielding a single result expression.  
`expr /. {{a -> b, ...}, {c -> d, ...}, ...}`  
returns a list containing the result of performing each set of replacements.

```
>> a+b+c /. c->d
a + b + d
>> g[a+b+c,a]/.g[x_+y_,x_]->{x,y}
{a,b+c}
```

If `rules` is a list of lists, a list of all possible respective replacements is returned:

```
>> {a, b} /. {{a->x, b->y}, {a->u,
b->v}}
{{x,y}, {u,v}}
```

The list can be arbitrarily nested:

```
>> {a, b} /. {{{a->x, b->y}, {a->w,
b->z}}, {a->u, b->v}}
{{{x,y}, {w,z}}, {u,v}}
```

```
>> {a, b} /. {{a->x, b->y}, a->w,
b->z}, {a->u, b->v}}
Elementsof{{a->x,b->y},a->w,
b->z}areamixtureoflistsandnonlists.
{{a,b} /. {a->x,b->y},
a->w,b->z}, {u,v}}
```

ReplaceAll also can be used as an operator:

```
>> ReplaceAll[{a -> 1}][{a, b}]
{1,b}
```

ReplaceAll replaces the shallowest levels first:

```
>> ReplaceAll[x[1], {x[1] -> y, 1
-> 2}]
y
```

## ReplaceList

`ReplaceList[expr, rules]`  
returns a list of all possible results of applying `rules` to `expr`.

Get all subsequences of a list:

```
>> ReplaceList[{a, b, c}, {___, x__,
___} -> {x}]
{{a}, {a,b}, {a,b,
c}, {b}, {b,c}, {c}}
```

You can specify the maximum number of items:

```
>> ReplaceList[{a, b, c}, {___, x__,
___} -> {x}, 3]
{{a}, {a,b}, {a,b,c}}
>> ReplaceList[{a, b, c}, {___, x__,
___} -> {x}, 0]
{}
```

If no rule matches, an empty list is returned:

```
>> ReplaceList[a, b->x]
{}
```

Like in `ReplaceAll`, `rules` can be a nested list:

```
>> ReplaceList[{a, b, c}, {{{___,
x__, ___} -> {x}}, {{a, b, c} ->
t}}, 2]
{{{a}, {a,b}}, {t}}
```

```
>> ReplaceList[expr, {}, -1]
Non
—negativeintegerorInfinityexpectedatposition3.
ReplaceList[expr, {}, -1]
```

Possible matches for a sum:

```
>> ReplaceList[a + b + c, x_ + y_
-> {x, y}]
{{a, b + c}, {b, a + c}, {c, a + b},
{a + b, c}, {a + c, b}, {b + c, a}}
```

## ReplaceRepeated (//.)

```
ReplaceRepeated[expr, x -> y]
expr //. x -> y
repeatedly applies the rule x -> y to expr
until the result no longer changes.
```

```
>> a+b+c //. c->d
a + b + d

>> f = ReplaceRepeated[c->d];

>> f[a+b+c]
a + b + d

>> Clear[f];
```

Simplification of logarithms:

```
>> logrules = {Log[x_ * y_] :> Log[
x] + Log[y], Log[x_ ^ y_] :> y *
Log[x]};

>> Log[a * (b * c)^ d ^ e * f] //.
logrules
Log[a] + Log[f] + (Log[b] + Log[c]) d^e
```

ReplaceAll just performs a single replacement:

```
>> Log[a * (b * c)^ d ^ e * f] /.
logrules
Log[a] + Log[f (bc)^d^e]
```

## RuleDelayed (:>)

```
RuleDelayed[x, y]
x :> y
represents a rule replacing x with y, with
y held unevaluated.
```

```
>> Attributes[RuleDelayed]
{HoldRest, Protected, SequenceHold}
```

## Rule (->)

```
Rule[x, y]
x -> y
represents a rule replacing x with y.
```

```
>> a+b+c /. c->d
a + b + d

>> {x,x^2,y} /. x->3
{3,9,y}
```

## Verbatim

```
Verbatim[expr]
prevents pattern constructs in expr from
taking effect, allowing them to match
themselves.
```

Create a pattern matching Blank:

```
>> _ /. Verbatim[_]->t
t

>> x /. Verbatim[_]->t
x
```

Without Verbatim, Blank has its normal effect:

```
>> x /. _->t
t
```

## 8. Mathematical Functions

Basic arithmetic functions, including complex number arithmetic.

### Contents

<b>Abs</b> . . . . .	60	<b>ExactNumberQ</b> . . . . .	62	<b>Piecewise</b> . . . . .	65
<b>Arg</b> . . . . .	61	<b>Factorial (!)</b> . . . . .	63	<b>PossibleZeroQ</b> . . . . .	65
<b>Assuming</b> . . . . .	61	<b>Factorial2 (!!)</b> . . . . .	63	<b>Product</b> . . . . .	65
<b>\$Assumptions</b> . . . . .	61	<b>I</b> . . . . .	63	<b>Rational</b> . . . . .	66
<b>Boole</b> . . . . .	61	<b>Im</b> . . . . .	63	<b>Re</b> . . . . .	66
<b>Complex</b> . . . . .	61	<b>InexactNumberQ</b> . . . . .	64	<b>RealNumberQ</b> . . . . .	66
<b>ConditionalExpression</b> . . . . .	62	<b>IntegerQ</b> . . . . .	64	<b>Real</b> . . . . .	66
<b>Conjugate</b> . . . . .	62	<b>Integer</b> . . . . .	64	<b>Sign</b> . . . . .	66
<b>DirectedInfinity</b> . . . . .	62	<b>MachineNumberQ</b> . . . . .	64	<b>Sum</b> . . . . .	67
		<b>NumberQ</b> . . . . .	64		

### Abs

**Abs**[*x*]  
returns the absolute value of *x*.


```
>> Abs[-3]
3
```

Abs returns the magnitude of complex numbers:

```
>> Abs[3 + I]
 $\sqrt{10}$ 
```

```
>> Abs[3.0 + I]
3.16228
```

```
>> Plot[Abs[x], {x, -4, 4}]
```



### Arg

**Arg**[*z*, *method\_option*]  
returns the argument of a complex value *z*.

- Arg[*z*] is left unevaluated if *z* is not a numeric quantity.
- Arg[*z*] gives the phase angle of *z* in radians.
- The result from Arg[*z*] is always between -Pi and +Pi.
- Arg[*z*] has a branch cut discontinuity in the complex *z* plane running from -Infinity to 0.
- Arg[0] is 0.

```
>> Arg[-3]
Pi
```

Same as above using sympy's method:

```
>> Arg[-3, Method->"sympy"]
Pi
```

```
>> Arg[1-I]
 $-\frac{\text{Pi}}{4}$ 
```

Arg evaluate the direction of DirectedInfinity quantities by the Arg of they arguments:

```
>> Arg[DirectedInfinity[1+I]]
      Pi
      4
```

```
>> Arg[DirectedInfinity[]]
      1
```

Arg for 0 is assumed to be 0:

```
>> Arg[0]
      0
```

## Assuming

**Assuming[*cond*, *expr*]**  
Evaluates *expr* assuming the conditions *cond*.

```
>> $Assumptions = { x > 0 }
      {x > 0}

>> Assuming[y>0,
      ConditionalExpression[y x^2, y
      >0]//Simplify]
      x^2 y

>> Assuming[Not[y>0],
      ConditionalExpression[y x^2, y
      >0]//Simplify]
      Undefined

>> ConditionalExpression[y x ^ 2, y
      > 0]//Simplify
      ConditionalExpression[x^2 y, y > 0]
```

## \$Assumptions

**\$Assumptions**  
is the default setting for the Assumptions option used in such functions as Simplify, Refine, and Integrate.

## Boole

**Boole[*expr*]**  
returns 1 if *expr* is True and 0 if *expr* is False.

```
>> Boole[2 == 2]
      1

>> Boole[7 < 5]
      0

>> Boole[a == 7]
      Boole[a==7]
```

## Complex

**Complex**  
is the head of complex numbers.  
**Complex[*a*, *b*]**  
constructs the complex number  $a + I b$ .

```
>> Head[2 + 3*I]
      Complex

>> Complex[1, 2/3]
      1 +  $\frac{2I}{3}$ 

>> Abs[Complex[3, 4]]
      5
```

## ConditionalExpression

**ConditionalExpression[*expr*, *cond*]**  
returns *expr* if *cond* evaluates to True, Undefined if *cond* evaluates to False.

```
>> ConditionalExpression[x^2, True]
      x^2

>> ConditionalExpression[x^2, False]
      Undefined

>> f = ConditionalExpression[x^2, x
      >0]
      ConditionalExpression[x^2, x > 0]
```

```
>> f /. x -> 2
4
>> f /. x -> -2
Undefined
```

ConditionalExpression uses assumptions to evaluate the condition:

```
>> $Assumptions = x > 0;

>> ConditionalExpression[x ^ 2, x
>0]//Simplify
x^2

>> $Assumptions = True;
```

```
#» ConditionalExpression[ConditionalExpression[s,x>a],
x<b] # = ConditionalExpression[s, And[x>a,
x<b]]
```

## Conjugate

Conjugate[z]  
returns the complex conjugate of the complex number z.

```
>> Conjugate[3 + 4 I]
3 - 4I
>> Conjugate[3]
3
>> Conjugate[a + b * I]
Conjugate[a] - IConjugate[b]
>> Conjugate[{{1, 2 + I 4, a + I b}, {I}}]
{{1, 2 - 4I, Conjugate[a] - IConjugate[b]}, {-I}}
>> Conjugate[1.5 + 2.5 I]
1.5 - 2.5I
```

## DirectedInfinity

DirectedInfinity[z]  
represents an infinite multiple of the complex number z.  
DirectedInfinity[]  
is the same as ComplexInfinity.

```
>> DirectedInfinity[1]
∞
>> DirectedInfinity[]
ComplexInfinity
>> DirectedInfinity[1 + I]
 $\left(\frac{1}{2} + \frac{I}{2}\right) \sqrt{2} \infty$ 
>> 1 / DirectedInfinity[1 + I]
0
>> DirectedInfinity[1] + DirectedInfinity[-1]
Indeterminateexpression
- Infinity + Infinityencountered.
Indeterminate
>> DirectedInfinity[0]
Indeterminateexpression0Infinityencountered.
Indeterminate
```

## ExactNumberQ

ExactNumberQ[expr]  
returns True if expr is an exact number, and False otherwise.

```
>> ExactNumberQ[10]
True
>> ExactNumberQ[4.0]
False
>> ExactNumberQ[n]
False
ExactNumberQ can be applied to complex numbers:
>> ExactNumberQ[1 + I]
True
>> ExactNumberQ[1 + 1. I]
False
```

## Factorial (!)

`Factorial[n]`  
 $n!$   
computes the factorial of  $n$ .

```
>> 20!  
2432 902 008 176 640 000
```

`Factorial` handles numeric (real and complex) values using the gamma function:

```
>> 10.5!  
1.18994  $\times 10^7$   
  
>> (-3.0+1.5*I)!  
0.0427943 - 0.00461565I
```

However, the value at poles is `ComplexInfinity`:

```
>> (-1.)!  
ComplexInfinity
```

`Factorial` has the same operator (!) as `Not`, but with higher precedence:

```
>> !a! //FullForm  
Not[Factorial[a]]
```

## Factorial2 (!!)

`Factorial2[n]`  
 $n!!$   
computes the double factorial of  $n$ .

The double factorial or semifactorial of a num-

ber  $n$ , is the product of all the integers from 1 up to  $n$  that have the same parity (odd or even) as  $n$ .

```
>> 5!!  
15.  
  
>> Factorial2[-3]  
-1.
```

`Factorial2` accepts Integers, Rationals, Reals, or Complex Numbers:

```
>> I!! + 1  
3.71713 + 0.279527I
```

Irrationals can be handled by using numeric approximation:

```
>> N[Pi!!, 6]  
3.35237
```

## I


`I`  
represents the imaginary number  $\text{Sqrt}[-1]$ .

```
>> I^2  
-1  
  
>> (3+I)*(3-I)  
10
```

## Im

`Im[z]`  
returns the imaginary component of the complex number  $z$ .

```
>> Im[3+4I]  
4  
  
>> Plot[{Sin[a], Im[E^(I a)]}, {a,  
0, 2 Pi}]
```



## InexactNumberQ

`InexactNumberQ[expr]`  
returns `True` if `expr` is not an exact number, and `False` otherwise.

```
>> InexactNumberQ[a]  
False  
  
>> InexactNumberQ[3.0]  
True  
  
>> InexactNumberQ[2/3]  
False
```

`InexactNumberQ` can be applied to complex numbers:

```
>> InexactNumberQ[4.0+I]
True
```

## IntegerQ

`IntegerQ[expr]`  
returns True if *expr* is an integer, and False otherwise.

```
>> IntegerQ[3]
True
>> IntegerQ[Pi]
False
```

## Integer

`Integer`  
is the head of integers.

```
>> Head[5]
Integer
```

## MachineNumberQ

`MachineNumberQ[expr]`  
returns True if *expr* is a machine-precision real or complex number.

```
= True
>> MachineNumberQ
[3.14159265358979324]
False
>> MachineNumberQ[1.5 + 2.3 I]
True
>> MachineNumberQ
[2.71828182845904524 +
3.14159265358979324 I]
False
```

## NumberQ

`NumberQ[expr]`  
returns True if *expr* is an explicit number, and False otherwise.

```
>> NumberQ[3+I]
True
>> NumberQ[5!]
True
>> NumberQ[Pi]
False
```

## Piecewise


`Piecewise[{{expr1, cond1}, ...}]`  
represents a piecewise function.  
`Piecewise[{{expr1, cond1}, ...}, expr]`  
represents a piecewise function with default *expr*.

Heaviside function

```
>> Piecewise[{{0, x <= 0}}, 1]
Piecewise[{{0, x <= 0}}, 1]
>> Integrate[Piecewise[{{1, x <= 0}, {-1, x > 0}}, x]
Piecewise[{{x, x <= 0}}, -x]
>> Integrate[Piecewise[{{1, x <= 0}, {-1, x > 0}}, {x, -1, 2}]
-1
```

Piecewise defaults to 0 if no other case is matching.

```
>> Piecewise[{{1, False}}]
0
>> Plot[Piecewise[{{Log[x], x > 0}, {x*-0.5, x < 0}}, {x, -1, 1}]
```





```
>> Piecewise[{{0 ^ 0, False}}, -1]
-1
```

## PossibleZeroQ

**PossibleZeroQ[expr]**  
returns True if basic symbolic and numerical methods suggest that expr has value zero, and False otherwise.

Test whether a numeric expression is zero:

```
>> PossibleZeroQ[E^(I Pi/4) - (-1)^(1/4)]
True
```

The determination is approximate.

Test whether a symbolic expression is likely to be identically zero:

```
>> PossibleZeroQ[(x + 1)(x - 1) - x^2 + 1]
True

>> PossibleZeroQ[(E + Pi)^2 - E^2 - Pi^2 - 2 E Pi]
True
```

Show that a numeric expression is nonzero:

```
>> PossibleZeroQ[E^Pi - Pi^E]
False

>> PossibleZeroQ[1/x + 1/y - (x + y)/(x y)]
True
```

Decide that a numeric expression is zero, based on approximate computations:

```
>> PossibleZeroQ[2^(2 I) - 2^(-2 I) - 2 I Sin[Log[4]]]
True

>> PossibleZeroQ[Sqrt[x^2] - x]
False
```

## Product

**Product[expr, {i, imin, imax}]**  
evaluates the discrete product of *expr* with *i* ranging from *imin* to *imax*.  
**Product[expr, {i, imax}]**  
same as **Product[expr, {i, 1, imax}]**.  
**Product[expr, {i, imin, imax, di}]**  
*i* ranges from *imin* to *imax* in steps of *di*.  
**Product[expr, {i, imin, imax}, {j, jmin, jmax}, ...]**  
evaluates *expr* as a multiple product, with {i, ...}, {j, ...}, ... being in outermost-to-innermost order.

```
>> Product[k, {k, 1, 10}]
3 628 800

>> 10!
3 628 800

>> Product[x^k, {k, 2, 20, 2}]
x^110

>> Product[2 ^ i, {i, 1, n}]
2^(n/2 + n^2/2)

>> Product[f[i], {i, 1, 7}]
f[1] f[2] f[3] f[4] f[5] f[6] f[7]
```

Symbolic products involving the factorial are evaluated:

```
>> Product[k, {k, 3, n}]
n! / 2
```

Evaluate the *n*th primorial:

```
>> primorial[0] = 1;

>> primorial[n_Integer] := Product[
Prime[k], {k, 1, n}];

>> primorial[12]
7 420 738 134 810
```

## Rational

**Rational**  
is the head of rational numbers.  
**Rational[a, b]**  
constructs the rational number *a* / *b*.

```
>> Head[1/2]
Rational


>> Rational[1, 2]
 $\frac{1}{2}$ 
```

## Re

**Re[z]**  
returns the real component of the complex number *z*.

```
>> Re[3+4I]
3

>> Plot[{Cos[a], Re[E^(I a)]}, {a,
0, 2 Pi}]
```



## RealNumberQ

**RealNumberQ[expr]**  
returns True if *expr* is an explicit number with no imaginary component.

```
>> RealNumberQ[10]
True

>> RealNumberQ[4.0]
True

>> RealNumberQ[1+I]
False

>> RealNumberQ[0 * I]
True

>> RealNumberQ[0.0 * I]
True
```

## Real

**Real**  
is the head of real (inexact) numbers.

```
>> x = 3. ^ -20;

>> InputForm[x]
2.8679719907924413*^-10

>> Head[x]
Real
```

## Sign

**Sign[x]**  
return -1, 0, or 1 depending on whether *x* is negative, zero, or positive.

```
>> Sign[19]
1

>> Sign[-6]
-1

>> Sign[0]
0

>> Sign[{-5, -10, 15, 20, 0}]
{-1, -1, 1, 1, 0}

>> Sign[3 - 4*I]
 $\frac{3}{5} - \frac{4I}{5}$ 
```

## Sum

**Sum[expr, {i, imin, imax}]**  
evaluates the discrete sum of *expr* with *i* ranging from *imin* to *imax*.  
**Sum[expr, {i, imax}]**  
same as **Sum[expr, {i, 1, imax}]**.  
**Sum[expr, {i, imin, imax, di}]**  
*i* ranges from *imin* to *imax* in steps of *di*.  
**Sum[expr, {i, imin, imax}, {j, jmin, jmax}, ...]**  
evaluates *expr* as a multiple sum, with {i, ...}, {j, ...}, ... being in outermost-to-innermost order.

A sum that Gauss in elementary school was asked to do to kill time:

```
>> Sum[k, {k, 1, 10}]
55
```

The symbolic form he used:

```
>> Sum[k, {k, 1, n}]

$$\frac{n(1+n)}{2}$$

```

A Geometric series with a finite limit:

```
>> Sum[1 / 2 ^ i, {i, 1, k}]

$$1 - 2^{-k}$$

```

A Geometric series using Infinity:

```
>> Sum[1 / 2 ^ i, {i, 1, Infinity}]
1
```

Leibniz formula used in computing Pi:

```
>> Sum[1 / ((-1)^k (2k + 1)), {k,
0, Infinity}]

$$\frac{\pi}{4}$$

```

A table of double sums to compute squares:

```
>> Table[ Sum[i * j, {i, 0, n}, {j,
0, n}], {n, 0, 4} ]
{0,1,9,36,100}
```

Computing Harmonic using a sum

```
>> Sum[1 / k ^ 2, {k, 1, n}]
HarmonicNumber[n,2]
```

Other symbolic sums:

```
>> Sum[k, {k, n, 2 n}]

$$\frac{3n(1+n)}{2}$$

```

A sum with Complex-number iteration values

```
>> Sum[k, {k, I, I + 1}]
1 + 2I
```

```
>> Sum[f[i], {i, 1, 7}]
f[1] + f[2] + f[3] + f[
4] + f[5] + f[6] + f[7]
```

Verify algebraic identities:

```
>> Sum[x ^ 2, {x, 1, y}] - y * (y +
1) * (2 * y + 1) / 6
0
```

## 9. Functional Programming

Functional programming is a programming paradigm where programs are constructed by applying and composing functions. This is term is often used in contrast to Procedural programming. It is made richer by expressions like  $f[x]$  being treating as symbolic data.

### Contents

Composition . . . . .	68	Identity . . . . .	69	SlotSequence . . . . .	69
Function (&) . . . . .	69	Slot . . . . .	69		

### Composition

`Composition[f, g]`  
returns the composition of two functions  $f$  and  $g$ .

```
>> Composition[f, g][x]
f[g[x]]

>> Composition[f, g, h][x, y, z]
f[g[h[x, y, z]]]

>> Composition[]
Identity

>> Composition[][x]
x

>> Attributes[Composition]
{Flat, OneIdentity, Protected}

>> Composition[f, Composition[g, h]]
Composition[f, g, h]
```

### Function (&)

`Function[body]`  
*body* &  
represents a pure function with parameters #1, #2, etc.  
`Function[{x1, x2, ...}, body]`  
represents a pure function with parameters  $x_1, x_2$ , etc.  
`Function[{x1, x2, ...}, body, attr]`  
assume that the function has the attributes *attr*.

```
>> f := # ^ 2 &

>> f[3]
9

>> #^3& /@ {1, 2, 3}
{1, 8, 27}

>> #1+#2&[4, 5]
9
```

You can use Function with named parameters:

```
>> Function[{x, y}, x * y][2, 3]
6
```

Parameters are renamed, when necessary, to avoid confusion:

```
>> Function[{x}, Function[{y}, f[x, y]]][y]
Function[{y$}, f[y, y$]]

>> Function[{y}, f[x, y]] /. x->y
Function[{y}, f[y, y]]
```

```
>> Function[y, Function[x, y^x]][x]
      [y]
      xy

>> Function[x, Function[y, x^y]][x]
      [y]
      xy
```

Slots in inner functions are not affected by outer function application:

```
>> g[#] & [h[#]] & [5]
      g[h[5]]
```

## Identity

`Identity[x]`  
is the identity function, which returns  $x$  unchanged.

```
>> Identity[x]
      x

>> Identity[x, y]
      Identity[x, y]
```

## Slot

`#n`  
represents the  $n$ th argument to a pure function.

`#`  
is short-hand for `#1`.

`#0`  
represents the pure function itself.

```
>> #
      #1
```

Unused arguments are simply ignored:

```
>> {#1, #2, #3}&[1, 2, 3, 4, 5]
      {1, 2, 3}
```

Recursive pure functions can be written using `#0`:

```
>> If[#1<=1, 1, #1 #0[#1-1]]& [10]
      3 628 800
```

## SlotSequence

`##`  
is the sequence of arguments supplied to a pure function.

`##n`  
starts with the  $n$ th argument.

```
>> Plus[##]& [1, 2, 3]
      6

>> Plus[##2]& [1, 2, 3]
      5

>> FullForm[##]
      SlotSequence[1]
```

# 10. Code Compilation

Code compilation allows Mathics functions to be run faster.

When LLVM and Python libraries are available, compilation produces LLVM code.

## Contents

<b>Compile . . . . .</b>	<b>70</b>	<b>CompiledFunction . . . . .</b>	<b>71</b>
--------------------------	-----------	-----------------------------------	-----------

## Compile

`Compile[{x1, x2, ...}, expr]`  
Compiles *expr* assuming each *xi* is a *Real* number.  
`Compile[{x1, t1} {x2, t1} ...}, expr]`  
Compiles assuming each *xi* matches type *ti*.

Compilation is performed using `llvmlite`, or Python's builtin "compile" function.

```
>> cf = Compile[{x, y}, x + 2 y]
CompiledFunction[{x, y},
  x + 2y, - CompiledCode-]

>> cf[2.5, 4.3]
11.1

>> cf = Compile[{x, _Real}}, Sin[x]]
CompiledFunction[{x},
  Sin[x], - CompiledCode-]

>> cf[1.4]
0.98545
```

Compile supports basic flow control:

```
>> cf = Compile[{x, _Real}, {y,
  _Integer}}, If[x == 0.0 && y <=
0, 0.0, Sin[x ^ y] + 1 / Min[x,
0.5]] + 0.5]
```

`CompiledFunction`  $\left[ \left\{ x, y \right\}, 0.5 + \text{If} \left[ x == 0. \& \& y <= 0, 0., \text{Sin} \left[ x^y \right] + \frac{1}{\text{Min} \left[ x, 0.5 \right]} \right], - \text{CompiledCode} - \right]$

```
>> cf[3.5, 2]
2.18888
```

Loops and variable assignments are supported using Python builtin "compile" function:

```
>> Compile[{a, _Integer}, {b,
  _Integer}}, While[b != 0, {a, b}
= {b, Mod[a, b]}; a] (* GCD of
a, b *)

CompiledFunction[{a,
  b}, a, - PythonizedCode-]
```

## CompiledFunction

`CompiledFunction[args...]`  
represents compiled code for evaluating a compiled function.

```
>> sqr = Compile[{x}, x x]  
CompiledFunction[{x},  
   $x^2$ , - CompiledCode-]  
  
>> Head[sqr]  
CompiledFunction  
  
>> sqr[2]  
4.
```

# 11. Options and Default Arguments

## Contents

Default . . . . .	72	NotOptionQ . . . . .	72	OptionValue . . . . .	73
FilterRules . . . . .	72	OptionQ . . . . .	73	Options . . . . .	74

## Default

`Default[f]`  
gives the default value for an omitted parameter of *f*.

`Default[f, k]`  
gives the default value for a parameter on the *k*th position.

`Default[f, k, n]`  
gives the default value for the *k*th parameter out of *n*.

Assign values to `Default` to specify default values.

```
>> Default[f] = 1
1

>> f[x_.] := x ^ 2

>> f[]
1
```

Default values are stored in `DefaultValues`:

```
>> DefaultValues[f]
{HoldPattern[Default[f]] :> 1}
```

You can use patterns for *k* and *n*:

```
>> Default[h, k_, n_] := {k, n}
```

Note that the position of a parameter is relative to the pattern, not the matching expression:

```
>> h[] /. h[___, ___, x_., y_., ___] -> {x, y}
{{3, 5}, {4, 5}}
```

## FilterRules

`FilterRules[rules, pattern]`  
gives those *rules* that have a left side that matches *pattern*.

`FilterRules[rules, {pattern1, pattern2, ...}]`  
gives those *rules* that have a left side that match at least one of *pattern1*, *pattern2*, ...

```
>> FilterRules[{x -> 100, y -> 1000}, x]
{x -> 100}

>> FilterRules[{x -> 100, y -> 1000, z -> 10000}, {a, b, x, z}]
{x -> 100, z -> 10000}
```

## NotOptionQ

`NotOptionQ[expr]`  
returns `True` if *expr* does not have the form of a valid option specification.

```
>> NotOptionQ[x]
True

>> NotOptionQ[2]
True

>> NotOptionQ["abc"]
True

>> NotOptionQ[a -> True]
False
```



## OptionQ

`OptionQ[expr]`  
returns True if *expr* has the form of a valid option specification.

Examples of option specifications:

```
>> OptionQ[a -> True]
True

>> OptionQ[a :> True]
True

>> OptionQ[{a -> True}]
True

>> OptionQ[{a :> True}]
True
```

Options lists are flattened when they are applied, so

```
>> OptionQ[{a -> True, {b->1, "c
->2}}]
True

>> OptionQ[{a -> True, {b->1, c}}]
False

>> OptionQ[{a -> True, F[b->1, c
->2}}]
False
```

`OptionQ` returns False if its argument is not a valid option specification:

```
>> OptionQ[x]
False
```

## OptionValue

`OptionValue[name]`  
gives the value of the option *name* as specified in a call to a function with `OptionsPattern`.

`OptionValue[f, name]`  
recover the value of the option *name* associated to the symbol *f*.

`OptionValue[f, optvals, name]`  
recover the value of the option *name* associated to the symbol *f*, extracting the values from *optvals* if available.

`OptionValue[... , list]`  
recover the value of the options in *list*.

```
>> f[a->3] /. f[OptionsPattern[{}]]
-> {OptionValue[a]}

{3}
```

Unavailable options generate a message:

```
>> f[a->3] /. f[OptionsPattern[{}]]
-> {OptionValue[b]}

Optionnamebnotfound.

{b}
```

The argument of `OptionValue` must be a symbol:

```
>> f[a->3] /. f[OptionsPattern[{}]]
-> {OptionValue[a+b]}

Argumenta
+ batposition1isexpectedtobeasymbol.

{OptionValue[a + b]}
```

However, it can be evaluated dynamically:

```
>> f[a->5] /. f[OptionsPattern[{}]]
-> {OptionValue[Symbol["a"]]}

{5}
```

## Options

`Options[f]`  
gives a list of optional arguments to *f* and their default values.

You can assign values to `Options` to specify options.

```
>> Options[f] = {n -> 2}
{n -> 2}

>> Options[f]
{n:>2}

>> f[x_, OptionsPattern[f]] := x ^
OptionValue[n]

>> f[x]
x2

>> f[x, n -> 3]
x3
```

Delayed option rules are evaluated just when the corresponding `OptionValue` is called:

```
>> f[a :> Print["value"]] /. f[
OptionsPattern[{}]] :> (
OptionValue[a]; Print["between
"]; OptionValue[a]);

value
between
value
```

In contrast to that, normal option rules are evaluated immediately:

```
>> f[a -> Print["value"]] /. f[
OptionsPattern[{}]] :> (
OptionValue[a]; Print["between
"]; OptionValue[a]);

value
between
```

Options must be rules or delayed rules:

```
>> Options[f] = {a}
{a}isnotavalidlistofoptionrules.
{a}
```

A single rule need not be given inside a list:

```
>> Options[f] = a -> b
a -> b

>> Options[f]
{a->b}
```

Options can only be assigned to symbols:

```
>> Options[a + b] = {a -> b}
Argumenta
+ batposition1isexpectedtobeasymbol.
{a -> b}
```

## 12. Attributes

There are several builtin-attributes which have a predefined meaning in *Mathics*. However, you can set any symbol as an attribute, in contrast to *Mathematica*®.

### Contents

Attributes . . . . .	75	HoldRest . . . . .	77	Protect . . . . .	78
ClearAttributes . . . . .	76	Listable . . . . .	77	Protected . . . . .	78
Constant . . . . .	76	Locked . . . . .	77	ReadProtected . . . . .	79
Flat . . . . .	76	NHoldAll . . . . .	77	SequenceHold . . . . .	79
HoldAll . . . . .	76	NHoldFirst . . . . .	77	SetAttributes . . . . .	79
HoldAllComplete . . . . .	76	NHoldRest . . . . .	77	Unprotect . . . . .	79
HoldFirst . . . . .	76	OneIdentity . . . . .	77		
		Orderless . . . . .	78		

### Attributes

`Attributes[symbol]`  
returns the attributes of *symbol*.  
`Attributes["string"]`  
returns the attributes of `Symbol["string"]`.  
`Attributes[symbol] = {attr1, attr2}`  
sets the attributes of *symbol*, replacing any existing attributes.

```
>> Attributes[Plus]
{Flat, Listable, NumericFunction,
 OneIdentity, Orderless, Protected}

>> Attributes["Plus"]
{Flat, Listable, NumericFunction,
 OneIdentity, Orderless, Protected}
```

Attributes always considers the head of an expression:

```
>> Attributes[a + b + c]
{Flat, Listable, NumericFunction,
 OneIdentity, Orderless, Protected}
```

You can assign values to Attributes to set attributes:

```
>> Attributes[f] = {Flat, Orderless}
{Flat, Orderless}
```

```
>> f[b, f[a, c]]
f[a, b, c]
```

Attributes must be symbols:

```
>> Attributes[f] := {a + b}
Argumenta
+ batposition1isexpectedtobeasymbol.
$Failed
```

Use Symbol to convert strings to symbols:

```
>> Attributes[f] = Symbol["Listable"]
Listable

>> Attributes[f]
{Listable}
```

### ClearAttributes

`ClearAttributes[symbol, attrib]`  
removes *attrib* from *symbol*'s attributes.

```
>> SetAttributes[f, Flat]

>> Attributes[f]
{Flat}

>> ClearAttributes[f, Flat]
```

```
>> Attributes[f]
{}

```

Attributes that are not even set are simply ignored:

```
>> ClearAttributes[{f}, {Flat}]

>> Attributes[f]
{}

```

## Constant

**Constant**  
is an attribute that indicates that a symbol is a constant.

Mathematical constants like  $E$  have attribute **Constant**:

```
>> Attributes[E]
{Constant, Protected, ReadProtected}

```

Constant symbols cannot be used as variables in **Solve** and related functions:

```
>> Solve[x + E == 0, E]
Eisnotavalidvariable.
Solve[E + x == 0, E]

```

## Flat

**Flat**  
is an attribute that specifies that nested occurrences of a function should be automatically flattened.

A symbol with the **Flat** attribute represents an associative mathematical operation:

```
>> SetAttributes[f, Flat]

>> f[a, f[b, c]]
f[a, b, c]

```

**Flat** is taken into account in pattern matching:

```
>> f[a, b, c] /. f[a, b] -> d
f[d, c]

```

## HoldAll

**HoldAll**  
is an attribute specifying that all arguments of a function should be left unevaluated.

```
>> Attributes[Function]
{HoldAll, Protected}

```

## HoldAllComplete

**HoldAllComplete**  
is an attribute that includes the effects of **HoldAll** and **SequenceHold**, and also protects the function from being affected by the upvalues of any arguments.

**HoldAllComplete** even prevents upvalues from being used, and includes **SequenceHold**.

```
>> SetAttributes[f, HoldAllComplete]

>> f[a] ^= 3;

>> f[a]
f[a]

>> f[Sequence[a, b]]
f[Sequence[a, b]]

```

## HoldFirst

**HoldFirst**  
is an attribute specifying that the first argument of a function should be left unevaluated.

```
>> Attributes[Set]
{HoldFirst, Protected, SequenceHold}

```

## HoldRest

**HoldRest**  
is an attribute specifying that all but the first argument of a function should be left unevaluated.

```
>> Attributes[If]
{HoldRest, Protected}
```

## Listable

**Listable**  
is an attribute specifying that a function should be automatically applied to each element of a list.

```
>> SetAttributes[f, Listable]

>> f[{1, 2, 3}, {4, 5, 6}]
{f[1,4], f[2,5], f[3,6]}

>> f[{1, 2, 3}, 4]
{f[1,4], f[2,4], f[3,4]}

>> {{1, 2}, {3, 4}} + {5, 6}
{{6,7}, {9,10}}
```

## Locked

**Locked**  
is an attribute that prevents attributes on a symbol from being modified.

The attributes of Locked symbols cannot be modified:

```
>> Attributes[lock] = {Flat, Locked}
};

>> SetAttributes[lock, {}]
Symbollockislocked.

>> ClearAttributes[lock, Flat]
Symbollockislocked.

>> Attributes[lock] = {}
Symbollockislocked.
{}

>> Attributes[lock]
{Flat, Locked}
```

However, their values might be modified (as long as they are not Protected too):

```
>> lock = 3
3
```

## NHoldAll

**NHoldAll**  
is an attribute that protects all arguments of a function from numeric evaluation.

```
>> N[f[2, 3]]
f[2.,3.]

>> SetAttributes[f, NHoldAll]

>> N[f[2, 3]]
f[2,3]
```

## NHoldFirst

**NHoldFirst**  
is an attribute that protects the first argument of a function from numeric evaluation.

## NHoldRest

**NHoldRest**  
is an attribute that protects all but the first argument of a function from numeric evaluation.

## OneIdentity

**OneIdentity**  
is an attribute specifying that  $f[x]$  should be treated as equivalent to  $x$  in pattern matching.

OneIdentity affects pattern matching:

```
>> SetAttributes[f, OneIdentity]

>> a /. f[args___] -> {args}
{a}
```

It does not affect evaluation:

```
>> f[a]
f[a]
```

## Orderless

### Orderless

is an attribute that can be assigned to a symbol  $f$  to indicate that the elements  $ei$  in expressions of the form  $f[e1, e2, \dots]$  should automatically be sorted into canonical order. This property is accounted for in pattern matching.

The leaves of an Orderless function are automatically sorted:

```
>> SetAttributes[f, Orderless]
```

```
>> f[c, a, b, a + b, 3, 1.0]
f[1., 3, a, b, c, a + b]
```

A symbol with the Orderless attribute represents a commutative mathematical operation.

```
>> f[a, b] == f[b, a]
True
```

Orderless affects pattern matching:

```
>> SetAttributes[f, Flat]
```

```
>> f[a, b, c] /. f[a, c] -> d
f[b, d]
```

## Protect

### Protect[s1, s2, ...]

sets the attribute Protected for the symbols  $si$ .

### Protect[str1, str2, ...]

protects all symbols whose names textually match  $stri$ .

```
>> A = {1, 2, 3};
```

```
>> Protect[A]
```

```
>> A[[2]] = 4;
Symbol A is Protected.
```

```
>> A
{1, 2, 3}
```

## Protected

### Protected

is an attribute that prevents values on a symbol from being modified.

Values of Protected symbols cannot be modified:

```
>> Attributes[p] = {Protected};
```

```
>> p = 2;
Symbol p is Protected.
```

```
>> f[p] ^= 3;
Tag p in f[p] is Protected.
```

```
>> Format[p] = "text";
Symbol p is Protected.
```

However, attributes might still be set:

```
>> SetAttributes[p, Flat]
```

```
>> Attributes[p]
{Flat, Protected}
```

Thus, you can easily remove the attribute Protected:

```
>> Attributes[p] = {};
```

```
>> p = 2
2
```

You can also use Protect or Unprotect, resp.

```
>> Protect[p]
```

```
>> Attributes[p]
{Protected}
```

```
>> Unprotect[p]
```

If a symbol is Protected and Locked, it can never be changed again:

```
>> SetAttributes[p, {Protected, Locked}]
```

```
>> p = 2
Symbol p is Protected.
2
```

```
>> Unprotect[p]
Symbol p is locked.
```

## ReadProtected

`ReadProtected`  
is an attribute that prevents values on a symbol from being read.

Values associated with `ReadProtected` symbols cannot be seen in `Definition`:

```
>> ClearAll[p]

>> p = 3;

>> Definition[p]
      p = 3

>> SetAttributes[p, ReadProtected]

>> Definition[p]
      Attributes[p] = {ReadProtected}
```

## SequenceHold

`SequenceHold`  
is an attribute that prevents `Sequence` objects from being spliced into a function's arguments.

Normally, `Sequence` will be spliced into a function:

```
>> f[Sequence[a, b]]
      f[a, b]
```

It does not for `SequenceHold` functions:

```
>> SetAttributes[f, SequenceHold]

>> f[Sequence[a, b]]
      f[Sequence[a, b]]
```

E.g., `Set` has attribute `SequenceHold` to allow assignment of sequences to variables:

```
>> s = Sequence[a, b];

>> s
      Sequence[a, b]

>> Plus[s]
      a + b
```

## SetAttributes

`SetAttributes[symbol, attrib]`  
adds *attrib* to the list of *symbol*'s attributes.

```
>> SetAttributes[f, Flat]

>> Attributes[f]
      {Flat}
```

Multiple attributes can be set at the same time using lists:

```
>> SetAttributes[{f, g}, {Flat,
      Orderless}]

>> Attributes[g]
      {Flat, Orderless}
```

## Unprotect

`Unprotect[s1, s2, ...]`  
removes the attribute `Protected` for the symbols *si*.  
`Unprotect[str]`  
unprotects symbols whose names textually match *str*.

# 13. Tensors

In mathematics, a tensor is an algebraic object that describes a (multilinear) relationship between sets of algebraic objects related to a vector space. Objects that tensors may map between include vectors and scalars, and even other tensors.

There are many types of tensors, including scalars and vectors (which are the simplest ten-

sors), dual vectors, multilinear maps between vector spaces, and even some operations such as the dot product. Tensors are defined independent of any basis, although they are often referred to by their components in a basis related to a particular coordinate system.

Mathics represents tensors of vectors and matrices as lists; tensors of any rank can be handled.

## Contents

<b>ArrayDepth</b> . . . . .	80	<b>Dot (.)</b> . . . . .	81	<b>Outer</b> . . . . .	82
<b>ArrayQ</b> . . . . .	80	<b>IdentityMatrix</b> . . . . .	81	<b>Transpose</b> . . . . .	83
<b>DiagonalMatrix</b> . . . . .	81	<b>Inner</b> . . . . .	81	<b>VectorQ</b> . . . . .	83
<b>Dimensions</b> . . . . .	81	<b>MatrixQ</b> . . . . .	82		

## ArrayDepth

**ArrayDepth**[*a*]  
returns the depth of the non-ragged array *a*, defined as **Length**[**Dimensions**[*a*]].

```
>> ArrayDepth[{{a,b},{c,d}}]
2
>> ArrayDepth[x]
0
```

```
>> ArrayQ[a]
False
>> ArrayQ[{a}]
True
>> ArrayQ[{{a}},{b,c}]
False
>> ArrayQ[{{a,b},{c,d}},2,SymbolQ]
True
```

## ArrayQ

**ArrayQ**[*expr*]  
tests whether *expr* is a full array.  
**ArrayQ**[*expr*, *pattern*]  
also tests whether the array depth of *expr* matches *pattern*.  
**ArrayQ**[*expr*, *pattern*, *test*]  
furthermore tests whether *test* yields True for all elements of *expr*. **ArrayQ**[*expr*] is equivalent to **ArrayQ**[*expr*, \_, True&].

## DiagonalMatrix

**DiagonalMatrix**[*list*]  
gives a matrix with the values in *list* on its diagonal and zeroes elsewhere.

```
>> DiagonalMatrix[{1, 2, 3}]
{{1,0,0},{0,2,0},{0,0,3}}
```



```
>> MatrixForm[%]

$$\begin{pmatrix} 1 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & 3 \end{pmatrix}$$

```

## Dimensions

`Dimensions[expr]`  
returns a list of the dimensions of the expression *expr*.

A vector of length 3:

```
>> Dimensions[{a, b, c}]
{3}
```

A 3x2 matrix:

```
>> Dimensions[{a, b}, {c, d}, {e, f}]
{3, 2}
```

Ragged arrays are not taken into account:

```
>> Dimensions[{a, b}, {b, c}, {c, d, e}]
{3}
```

The expression can have any head:

```
>> Dimensions[f[f[a, b, c]]]
{1, 3}
```

## Dot (.)

`Dot[x, y]`  
 $x \cdot y$   
computes the vector dot product or matrix product  $x \cdot y$ .

Scalar product of vectors:

```
>> {a, b, c} . {x, y, z}
ax + by + cz
```

Product of matrices and vectors:

```
>> {{a, b}, {c, d}} . {x, y}
{ax + by, cx + dy}
```

Matrix product:

```
>> {{a, b}, {c, d}} . {{r, s}, {t, u}}
{{ar + bt, as + bu}, {cr + dt, cs + du}}

>> a . b
a.b
```

## IdentityMatrix

`IdentityMatrix[n]`  
gives the identity matrix with  $n$  rows and columns.

```
>> IdentityMatrix[3]
{{1, 0, 0}, {0, 1, 0}, {0, 0, 1}}
```

## Inner

`Inner[f, x, y, g]`  
computes a generalised inner product of  $x$  and  $y$ , using a multiplication function  $f$  and an addition function  $g$ .

```
>> Inner[f, {a, b}, {x, y}, g]
g[f[a, x], f[b, y]]
```

Inner can be used to compute a dot product:

```
>> Inner[Times, {a, b}, {c, d}, Plus] == {a, b} . {c, d}
True
```

The inner product of two boolean matrices:

```
>> Inner[And, {{False, False}, {False, True}}, {{True, False}, {True, True}}, Or]
{{False, False}, {True, True}}
```

Inner works with tensors of any depth:

```
>> Inner[f, {{{a, b}}, {{c, d}}}, {{1}, {2}}, g]
{{{g[f[a, 1], f[b, 2]]}}, {{g[f[c, 1], f[d, 2]]}}}
```

## MatrixQ

```
MatrixQ[m]
  returns True if m is a list of equal-length
  lists.
MatrixQ[m, f]
  only returns True if f[x] returns True for
  each element x of the matrix m.
```

```
>> MatrixQ[{{1, 3}, {4.0, 3/2}},
NumberQ]
True
```

## Outer

```
Outer[f, x, y]
  computes a generalised outer product of
  x and y, using the function f in place of
  multiplication.
```

```
>> Outer[f, {a, b}, {1, 2, 3}]
{{f[a, 1], f[a, 2], f[a, 3]},
 {f[b, 1], f[b, 2], f[b, 3]}}
```

Outer product of two matrices:

```
>> Outer[Times, {{a, b}, {c, d}},
{{1, 2}, {3, 4}}]
{{{a, 2a}, {3a, 4a}}, {{b,
 2b}, {3b, 4b}}}, {{c, 2c}, {3c,
 4c}}, {{d, 2d}, {3d, 4d}}}
```

Outer of multiple lists:

```
>> Outer[f, {a, b}, {x, y, z}, {1,
2}]
{{{f[a, x, 1], f[a, x, 2]}, {f[
a, y, 1], f[a, y, 2]}, {f[a, z, 1],
f[a, z, 2]}}, {{f[b, x, 1], f[
b, x, 2]}, {f[b, y, 1], f[b, y,
2]}, {f[b, z, 1], f[b, z, 2]}}}
```

Arrays can be ragged:

```
>> Outer[Times, {{1, 2}}, {{a, b},
{c, d, e}}]
{{{a, b}, {c, d, e}},
 {{2a, 2b}, {2c, 2d, 2e}}}
```

Word combinations:

```
>> Outer[StringJoin, {"", "re", "un"}, {"cover", "draw", "wind"}, {"", "ing", "s"}] // InputForm
{{{{"cover", "covering", "covers"}, {"draw", "drawing", "draws"}, {"wind", "winding", "winds"}}, {"recover", "recovering", "recovers"}, {"redraw", "redrawing", "redraws"}, {"rewind", "rewinding", "rewinds"}}, {"uncover", "uncovering", "uncovers"}, {"undraw", "undrawing", "undraws"}, {"unwind", "unwinding", "unwinds"}}}
```

Compositions of trigonometric functions:

```
>> trigs = Outer[Composition, {Sin, Cos, Tan}, {ArcSin, ArcCos, ArcTan}]
{{Composition[Sin, ArcSin], Composition[Sin, ArcCos], Composition[Sin, ArcTan]}, {Composition[Cos, ArcSin], Composition[Cos, ArcCos], Composition[Cos, ArcTan]}, {Composition[Tan, ArcSin], Composition[Tan, ArcCos], Composition[Tan, ArcTan]}}
```

Evaluate at 0:

```
>> Map[# [0] &, trigs, {2}]
{{0, 1, 0}, {1, 0, 1}, {0, ComplexInfinity, 0}}
```

## Transpose

```
Transpose[m]
  transposes rows and columns in the matrix m.
```

```
>> Transpose[{{1, 2, 3}, {4, 5, 6}}]
{{1, 4}, {2, 5}, {3, 6}}
```

```
>> MatrixForm[%]
```

$$\begin{pmatrix} 1 & 4 \\ 2 & 5 \\ 3 & 6 \end{pmatrix}$$

## VectorQ

`VectorQ[v]`

returns True if  $v$  is a list of elements which are not themselves lists.

`VectorQ[v, f]`

returns True if  $v$  is a vector and  $f[x]$  returns True for each element  $x$  of  $v$ .

```
>> VectorQ[{a, b, c}]
```

```
True
```

# 14. Structural Operations

## Contents

Apply (@@) . . . . .	84	Head . . . . .	86	Scan . . . . .	89
ApplyLevel (@@@) . . . . .	84	Map (/@) . . . . .	86	Sort . . . . .	89
AtomQ . . . . .	85	MapAt . . . . .	87	SortBy . . . . .	89
Combinatori- caOld'BinarySearch	85	MapIndexed . . . . .	88	SymbolName . . . . .	89
ByteCount . . . . .	85	MapThread . . . . .	88	SymbolQ . . . . .	90
Depth . . . . .	85	Null . . . . .	88	Symbol . . . . .	90
Flatten . . . . .	86	Operate . . . . .	88	Thread . . . . .	90
FreeQ . . . . .	86	Order . . . . .	88	Through . . . . .	90
		OrderedQ . . . . .	88		
		PatternsOrderedQ . . . . .	89		

## Apply (@@)

`Apply[f, expr]`  
`f @@ expr`  
 replaces the head of `expr` with `f`.  
`Apply[f, expr, levelspec]`  
 applies `f` on the parts specified by `levelspec`.

```
>> f @@ {1, 2, 3}
f[1,2,3]

>> Plus @@ {1, 2, 3}
6
```

The head of `expr` need not be `List`:

```
>> f @@ (a + b + c)
f[a,b,c]
```

Apply on level 1:

```
>> Apply[f, {a + b, g[c, d, e * f],
3}, {1}]
{f[a,b],f[c,d,ef],3}
```

The default level is 0:

```
>> Apply[f, {a, b, c}, {0}]
f[a,b,c]
```

Range of levels, including negative level (counting from bottom):

```
>> Apply[f, {{{{a}}}}, {2, -3}]
{{f[f[{a}]]}}
```

Convert all operations to lists:

```
>> Apply[List, a + b * c ^ e * f[g
], {0, Infinity}]
{a, {b, {g}}, {c,e}}
```

## ApplyLevel (@@@)

`ApplyLevel[f, expr]`  
`f @@@ expr`  
 is equivalent to `Apply[f, expr, {1}]`.

```
>> f @@@ {{a, b}, {c, d}}
{f[a,b],f[c,d]}
```

## AtomQ

`AtomQ[x]`  
 is true if `x` is an atom (an object such as a number or string, which cannot be divided into subexpressions using `Part`).

```
>> AtomQ[x]
True
```

```
>> AtomQ[1.2]
True

>> AtomQ[2 + 1]
True

>> AtomQ[2 / 3]
True

>> AtomQ[x + y]
False
```

## CombinatoricaOld'BinarySearch

`CombinatoricaOld'BinarySearch[l, k]`  
searches the list *l*, which has to be sorted, for key *k* and returns its index in *l*. If *k* does not exist in *l*, `BinarySearch` returns  $(a + b) / 2$ , where *a* and *b* are the indices between which *k* would have to be inserted in order to maintain the sorting order in *l*. Please note that *k* and the elements in *l* need to be comparable under a strict total order (see [https://en.wikipedia.org/wiki/Total\\_order](https://en.wikipedia.org/wiki/Total_order)).

`CombinatoricaOld'BinarySearch[l, k, f]`  
the index of *k* in the elements of *l* if *f* is applied to the latter prior to comparison. Note that *f* needs to yield a sorted sequence if applied to the elements of *l*.

```
>> CombinatoricaOld'BinarySearch
    [{3, 4, 10, 100, 123}, 100]
4

>> CombinatoricaOld'BinarySearch
    [{2, 3, 9}, 7] // N
2.5

>> CombinatoricaOld'BinarySearch
    [{2, 7, 9, 10}, 3] // N
1.5

>> CombinatoricaOld'BinarySearch
    [{-10, 5, 8, 10}, -100] // N
0.5

>> CombinatoricaOld'BinarySearch
    [{-10, 5, 8, 10}, 20] // N
4.5
```

```
>> CombinatoricaOld'BinarySearch[{{
    a, 1}, {b, 7}}, 7, #[[2]]&]
2
```

## ByteCount

`ByteCount[expr]`  
gives the internal memory space used by *expr*, in bytes.

The results may heavily depend on the Python implementation in use.

## Depth

`Depth[expr]`  
gives the depth of *expr*.

The depth of an expression is defined as one plus the maximum number of Part indices required to reach any part of *expr*, except for heads.

```
>> Depth[x]
1

>> Depth[x + y]
2

>> Depth[{{{x}}}]
5
```

Complex numbers are atomic, and hence have depth 1:

```
>> Depth[1 + 2 I]
1
```

Depth ignores heads:

```
>> Depth[f[a, b][c]]
2
```

## Flatten

`Flatten[expr]`  
flattens out nested lists in *expr*.  
`Flatten[expr, n]`  
stops flattening at level *n*.  
`Flatten[expr, n, h]`  
flattens expressions with head *h* instead of List.

```
>> Flatten[{{a, b}, {c, {d}, e}, {f, {g, h}}}]
{a, b, c, d, e, f, g, h}

>> Flatten[{{a, b}, {c, {e}, e}, {f, {g, h}}}, 1]
{a, b, c, {e}, e, f, {g, h}}

>> Flatten[f[a, f[b, f[c, d]], e], Infinity, f]
f[a, b, c, d, e]

>> Flatten[{{a, b}, {c, d}}, {{2}, {1}}]
{{a, c}, {b, d}}

>> Flatten[{{a, b}, {c, d}}, {{1, 2}}]
{a, b, c, d}
```

Flatten also works in irregularly shaped arrays

```
>> Flatten[{{1, 2, 3}, {4}, {6, 7}, {8, 9, 10}}, {{2}, {1}}]
{{1, 4, 6, 8}, {2, 7, 9}, {3, 10}}
```

## FreeQ

**FreeQ[expr, x]**  
returns True if *expr* does not contain the expression *x*.

```
>> FreeQ[y, x]
True

>> FreeQ[a+b+c, a+b]
False

>> FreeQ[{1, 2, a^(a+b)}, Plus]
False

>> FreeQ[a+b, x_+y_+z_]
True

>> FreeQ[a+b+c, x_+y_+z_]
False

>> FreeQ[x_+y_+z_] [a+b]
True
```

## Head

**Head[expr]**  
returns the head of the expression or atom *expr*.

```
>> Head[a * b]
Times

>> Head[6]
Integer

>> Head[x]
Symbol
```

## Map (/@)

**Map[f, expr]** or **f /@ expr**  
applies *f* to each part on the first level of *expr*.  
**Map[f, expr, levelspec]**  
applies *f* to each level specified by *levelspec* of *expr*.

```
>> f /@ {1, 2, 3}
{f[1], f[2], f[3]}

>> #^2 & /@ {1, 2, 3, 4}
{1, 4, 9, 16}
```

Map *f* on the second level:

```
>> Map[f, {{a, b}, {c, d, e}}, {2}]
{{f[a], f[b]}, {f[c], f[d], f[e]}}
```

Include heads:

```
>> Map[f, a + b + c, Heads->True]
f[Plus] [f[a], f[b], f[c]]
```

## MapAt

`MapAt[f, expr, n]`  
applies *f* to the element at position *n* in *expr*. If *n* is negative, the position is counted from the end.

`MapAt[f, expr, {i, j ...}]`  
applies *f* to the part of *expr* at position {*i*, *j*, ...}.

`MapAt[f, pos]`  
represents an operator form of `MapAt` that can be applied to an expression.

Map *f* onto the part at position 2:

```
>> MapAt[f, {a, b, c, d}, 2]
      {a, f[b], c, d}
```

Map *f* onto multiple parts:

```
>> MapAt[f, {a, b, c, d}, {{1},
      {4}}]
      {f[a], b, c, f[d]}
```

Map *f* onto the at the end:

```
>> MapAt[f, {a, b, c, d}, -1]
      {a, b, c, f[d]}
```

Map *f* onto an association:

```
>> MapAt[f, <|"a" -> 1, "b" -> 2, "
      c" -> 3, "d" -> 4, "e" -> 5|>,
      3]
      {a -> 1, b -> 2, c -> f[
      3], d -> 4, e -> 5}
```

Use negative position in an association:

```
>> MapAt[f, <|"a" -> 1, "b" -> 2, "
      c" -> 3, "d" -> 4|>, -3]
      {a -> 1, b -> f[2], c -> 3, d -> 4}
```

Use the operator form of `MapAt`:

```
>> MapAt[f, 1][{a, b, c, d}]
      {f[a], b, c, d}
```

## MapIndexed

`MapIndexed[f, expr]`  
applies *f* to each part on the first level of *expr*, including the part positions in the call to *f*.

`MapIndexed[f, expr, levelspec]`  
applies *f* to each level specified by *levelspec* of *expr*.

```
>> MapIndexed[f, {a, b, c}]
      {f[a, {1}], f[b, {2}], f[c, {3}]}
```

Include heads (index 0):

```
>> MapIndexed[f, {a, b, c}, Heads->
      True]
      f[List, {0}][f[a, {1}],
      f[b, {2}], f[c, {3}]]
```

Map on levels 0 through 1 (outer expression gets index {}):

```
>> MapIndexed[f, a + b + c * d, {0,
      1}]
      f[f[a, {1}] + f[b,
      {2}] + f[cd, {3}], {}]
```

Get the positions of atoms in an expression (convert operations to `List` first to disable `Listable` functions):

```
>> expr = a + b * f[g] * c ^ e;

>> listified = Apply[List, expr,
      {0, Infinity}];

>> MapIndexed[#2 &, listified,
      {-1}]
      {{1}, {{2, 1}, {{2, 2, 1}}},
      {{2, 3, 1}, {2, 3, 2}}}]
```

Replace the heads with their positions, too:

```
>> MapIndexed[#2 &, listified,
      {-1}, Heads -> True]
      {0}[{1}, {2, 0}][{2, 1},
      {2, 2, 0}][{2, 2, 1}], {2, 3,
      0}[{2, 3, 1}, {2, 3, 2}]]]
```

The positions are given in the same format as used by `Extract`. Thus, mapping `Extract` on the indices given by `MapIndexed` re-constructs the original expression:

```
>> MapIndexed[Extract[expr, #2] &,
  listified, {-1}, Heads -> True]
 $a + bf[g]c^e$ 
```

## MapThread

`MapThread[f, {{a1, a2, ...}, {b1, b2, ...}, ...}]`  
 returns `{f[a1, b1, ...], f[a2, b2, ...], ...}`.  
`MapThread[f, {expr1, expr2, ...}, n]`  
 applies `f` at level `n`.

```
>> MapThread[f, {{a, b, c}, {1, 2, 3}}]
{f[a, 1], f[b, 2], f[c, 3]}

>> MapThread[f, {{{a, b}, {c, d}}, {{e, f}, {g, h}}}, 2]
{{f[a, e], f[b, f]}, {f[c, g], f[d, h]}}
```

## Null

`Null`  
 is the implicit result of expressions that do not yield a result.

```
>> FullForm[a:=b]
Null
```

It is not displayed in `StandardForm`,

```
>> a:=b
```

in contrast to the empty string:

```
>> ""
```

## Operate

`Operate[p, expr]`  
 applies `p` to the head of `expr`.  
`Operate[p, expr, n]`  
 applies `p` to the `n`th head of `expr`.

```
>> Operate[p, f[a, b]]
p[f][a, b]
```

The default value of `n` is 1:

```
>> Operate[p, f[a, b], 1]
p[f][a, b]
```

With `n=0`, `Operate` acts like `Apply`:

```
>> Operate[p, f[a][b][c], 0]
p[f[a][b][c]]
```

## Order

`Order[x, y]`  
 returns a number indicating the canonical ordering of `x` and `y`. 1 indicates that `x` is before `y`, -1 that `y` is before `x`. 0 indicates that there is no specific ordering. Uses the same order as `Sort`.

```
>> Order[7, 11]
1

>> Order[100, 10]
-1

>> Order[x, z]
1

>> Order[x, x]
0
```

## OrderedQ

`OrderedQ[a, b]`  
 is True if `a` sorts before `b` according to canonical ordering.

```
>> OrderedQ[a, b]
True

>> OrderedQ[b, a]
False
```

## PatternsOrderedQ

`PatternsOrderedQ[patt1, patt2]`  
 returns True if pattern `patt1` would be applied before `patt2` according to canonical pattern ordering.



```
>> PatternsOrderedQ[x_, x_]
False

>> PatternsOrderedQ[x_, x_]
True

>> PatternsOrderedQ[b, a]
True
```

## Scan

`Scan[f, expr]`  
applies *f* to each element of *expr* and returns `Null`.

`'Scan[f, expr, levelspec]`  
applies *f* to each level specified by *levelspec* of *expr*.

```
>> Scan[Print, {1, 2, 3}]
1
2
3
```

## Sort

`Sort[list]`  
sorts *list* (or the leaves of any other expression) according to canonical ordering.

`Sort[list, p]`  
sorts using *p* to determine the order of two elements.

```
>> Sort[{4, 1.0, a, 3+I}]
{1., 3 + I, 4, a}
```

`Sort` uses `OrderedQ` to determine ordering by default. You can sort patterns according to their precedence using `PatternsOrderedQ`:

```
>> Sort[{items___, item_,
OptionsPattern[], item_symbol,
item_?test}, PatternsOrderedQ]
{item_symbol, item_?test, item_,
items___, OptionsPattern[]}
```

When sorting patterns, values of atoms do not matter:

```
>> Sort[{a, b;/t}, PatternsOrderedQ]
{b;/t, a}
```

```
>> Sort[{2+c_, 1+b___},
PatternsOrderedQ]
{2 + c_, 1 + b___}

>> Sort[{x_ + n_*y_, x_ + y_},
PatternsOrderedQ]
{x_ + n_y_, x_ + y_}
```

## SortBy

`SortBy[list, f]`  
sorts *list* (or the leaves of any other expression) according to canonical ordering of the keys that are extracted from the *list*'s elements using *f*. Chunks of leaves that appear the same under *f* are sorted according to their natural order (without applying *f*).

`SortBy[f]`  
creates an operator function that, when applied, sorts by *f*.

```
>> SortBy[{{5, 1}, {10, -1}}, Last]
{{10, -1}, {5, 1}}

>> SortBy[Total][{{5, 1}, {10, -9}}]
{{10, -9}, {5, 1}}
```

## SymbolName

`SymbolName[s]`  
returns the name of the symbol *s* (without any leading context name).

```
>> SymbolName[x] // InputForm
"x"
```

## SymbolQ

`SymbolQ[x]`  
is `True` if *x* is a symbol, or `False` otherwise.

```
>> SymbolQ[a]
True
```

```
>> SymbolQ[1]
False

>> SymbolQ[a + b]
False
```

```
>> Through[f[g][x]]
f[g[x]]

>> Through[p[f, g][x]]
p[f[x], g[x]]
```

## Symbol

**Symbol**  
is the head of symbols.

```
>> Head[x]
Symbol
```

You can use **Symbol** to create symbols from strings:

```
>> Symbol["x"] + Symbol["x"]
2x
```

## Thread

**Thread**[*f*[*args*]]  
threads *f* over any lists that appear in *args*.  
**Thread**[*f*[*args*], *h*]  
threads over any parts with head *h*.

```
>> Thread[f[{a, b, c}]]
{f[a], f[b], f[c]}

>> Thread[f[{a, b, c}, t]]
{f[a, t], f[b, t], f[c, t]}

>> Thread[f[a + b + c], Plus]
f[a] + f[b] + f[c]
```

Functions with attribute **Listable** are automatically threaded over lists:

```
>> {a, b, c} + {d, e, f} + g
{a + d + g, b + e + g, c + f + g}
```

## Through

**Through**[*p*[*f*][*x*]]  
gives *p*[*f*[*x*]].

# 15. Drawing Graphics


## Contents

AbsoluteThickness . . .	91	Graphics . . . . .	96	Show . . . . .	101
Arrow . . . . .	92	Large . . . . .	97	Small . . . . .	101
Arrowheads . . . . .	93	Line . . . . .	97	Text . . . . .	101
Circle . . . . .	94	Medium . . . . .	97	Thick . . . . .	101
Disk . . . . .	95	Point . . . . .	98	Thickness . . . . .	102
EdgeForm . . . . .	95	PointSize . . . . .	98	Thin . . . . .	102
FilledCurve . . . . .	95	Polygon . . . . .	99	Tiny . . . . .	102
FontColor . . . . .	96	Rectangle . . . . .	100		
		RegularPolygon . . . .	100		

## AbsoluteThickness

`AbsoluteThickness[p]`  
sets the line thickness for subsequent graphics primitives to  $p$  points.

```
>> Graphics[Table[{
  AbsoluteThickness[t], Line[{{20
t, 10}, {20 t, 80}}], Text[
ToString[t]<>"pt", {20 t, 0}],
{t, 0, 10}]]
```



## Arrow


`Arrow[{p1, p2}]`  
represents a line from  $p1$  to  $p2$  that ends with an arrow at  $p2$ .

`Arrow[{p1, p2}, s]`  
represents a line with arrow that keeps a distance of  $s$  from  $p1$  and  $p2$ .


`Arrow[{point_1, point_2}, {s1, s2}]`  
represents a line with arrow that keeps a distance of  $s1$  from  $p1$  and a distance of  $s2$  from  $p2$ .

`Arrow[{point_1, point_2}, {s1, s2}]`  
represents a line with arrow that keeps a distance of  $s1$  from  $p1$  and a distance of  $s2$  from  $p2$ .

```
>> Graphics[Arrow[{{0,0}, {1,1}}]]
```




```
>> Graphics[{Circle[], Arrow[{2, 1}, {0, 0}], 1]}]
```




Arrows can also be drawn in 3D by giving points in three dimensions:

```
>> Graphics3D[Arrow[{1, 1, -1}, {2, 2, 0}, {3, 3, -1}, {4, 4, 0}]]]
```



Keeping distances may happen across multiple segments:

```
>> Table[Graphics[{Circle[], Arrow[Table[{Cos[phi], Sin[phi]], {phi, 0, 2*Pi, Pi/2}], {d, d}]]], {d, 0, 2, 0.5}]
```



## Arrowheads

`Arrowheads[s]`  
specifies that `Arrow[]` draws one arrow of size  $s$  (relative to width of image, defaults to 0.04).

`Arrowheads[{spec1, spec2, ..., specn}]`  
specifies that `Arrow[]` draws  $n$  arrows as defined by  $spec1, spec2, \dots, specn$ .


`Arrowheads[{s}]`  
specifies that one arrow of size  $s$  should be drawn.

`Arrowheads[{s, pos}]`  
specifies that one arrow of size  $s$  should be drawn at position  $pos$  (for the arrow to be on the line,  $pos$  has to be between 0, i.e. the start for the line, and 1, i.e. the end of the line).

`Arrowheads[{s, pos, g}]`  
specifies that one arrow of size  $s$  should be drawn at position  $pos$  using Graphics  $g$ .


Arrows on both ends can be achieved using negative sizes:

```
>> Graphics[{Circle[], Arrowheads
[{-0.04, 0.04}], Arrow[{0, 0},
{2, 2}], {1, 1}}]
```




You may also specify our own arrow shapes:

```
>> Graphics[{Circle[], Arrowheads
[{{0.04, 1, Graphics[{Red, Disk
[]}]}}], Arrow[{0, 0}, {Cos[Pi
/3], Sin[Pi/3]}]}]
```



```
>> Graphics[{Arrowheads[Table
[{0.04, i/10, Graphics[Disk
[]]], {i, 1, 10}]], Arrow[{0, 0},
{6, 5}, {1, -3}, {-2, 2}]}]
```



## Circle


`Circle[{cx, cy}, r]`  
draws a circle with center  $(cx, cy)$  and radius  $r$ .

`Circle[{cx, cy}, {rx, ry}]`  
draws an ellipse.


`Circle[{cx, cy}]`  
chooses radius 1.

`Circle[]`  
chooses center  $(0, 0)$  and radius 1.

```
>> Graphics[{Red, Circle[{0, 0}, {2, 1}]}]
```




```
>> Graphics[{Circle[], Disk[{0, 0}, {1, 1}, {0, 2.1}]}]
```



Target practice:

```
>> Graphics[Circle[], Axes-> True]
```



## Disk

`Disk[{cx, cy}, r]`  
fills a circle with center  $(cx, cy)$  and radius  $r$ .


`Disk[{cx, cy}, {rx, ry}]`  
fills an ellipse.

`Disk[{cx, cy}]`  
chooses radius 1.

`Disk[]`  
chooses center  $(0, 0)$  and radius 1.


`Disk[{x, y}, ..., {t1, t2}]`  
is a sector from angle  $t1$  to  $t2$ .

```
>> Graphics[{Blue, Disk[{0, 0}, {2, 1}]}]
```




The outer border can be drawn using `EdgeForm`:

```
>> Graphics[{EdgeForm[Black], Red, Disk[]}]
```




Disk can also draw sectors of circles and ellipses

```
>> Graphics[Disk[{0, 0}, 1, {Pi / 3, 2 Pi / 3}]]
```




```
>> Graphics[{Blue, Disk[{0, 0}, {1, 2}, {Pi / 3, 5 Pi / 3}]]]
```




## EdgeForm

```
>> Graphics[{EdgeForm[{Thick, Green}], Disk[]}]
```




```
>> Graphics[{Style[Disk[], EdgeForm[{Thick, Red}]], Circle[{1, 1}]}]
```



## FilledCurve

`FilledCurve[{segment1, segment2 ...}]` represents a filled curve.

```
>> Graphics[FilledCurve[{Line[{0, 0}, {1, 1}, {2, 0}]}]]]
```



```
>> Graphics[FilledCurve[{BezierCurve[{0, 0}, {1, 1}, {2, 0}], Line[{3, 0}, {0, 2}]}]]]
```



## FontColor

FontColor

is an option for Style to set the font color.


## Graphics

`Graphics[primitives, options]`  
represents a graphic.

Options include:


- Axes
- TicksStyle
- AxesStyle
- LabelStyle
- AspectRatio
- PlotRange
- PlotRangePadding
- ImageSize
- Background

```
>> Graphics[{Blue, Line[{{0,0},  
{1,1}]}]}
```




Graphics supports PlotRange:

```
>> Graphics[{Rectangle[{1, 1}]},  
Axes -> True, PlotRange -> {{-2,  
1.5}, {-1, 1.5}}]
```



```
>> Graphics[{Rectangle[], Red, Disk  
[{1,0}], PlotRange  
->{{0,1},{0,1}}]
```



Graphics produces GraphicsBox boxes:

```
>> Graphics[Rectangle[]] // ToBoxes  
// Head  
GraphicsBox
```

In TeXForm, Graphics produces Asymptote figures:

```
>> Graphics[Circle[]] // TeXForm  
  
\begin{asy}  
usepackage("amsmath");  
size(5.8556cm, 5.8333cm);  
draw(ellipse((175,175),175,175),  
rgb(0, 0, 0)+linewidth(0.66667));  
clip(box((-0.33333,0.33333),  
(350.33,349.67)));  
\end{asy}
```



## Large

ImageSize -> Large  
produces a large image.


## Line

Line[{*point\_1*, *point\_2* ...}]  
represents the line primitive.  
Line[{{*p\_11*, *p\_12*, ...}, {*p\_21*, *p\_22*,  
...}, ...}]  
represents a number of line primitives.

```
>> Graphics[Line  
[{{0,1},{0,0},{1,0},{1,1}}]]
```



```
>> Graphics3D[Line  
[{{0,0,0},{0,1,1},{1,0,0}}]]
```



## Medium

ImageSize -> Medium  
produces a medium-sized image.

## Point

Point[{*point\_1*, *point\_2* ...}]  
represents the point primitive.  
Point[{{*p\_11*, *p\_12*, ...}, {*p\_21*, *p\_22*,  
...}, ...}]  
represents a number of point primitives.


Points are rendered if possible as circular regions. Their diameters can be specified using PointSize.

Points can be specified as {*x*, *y*}:

```
>> Graphics[Point[{0, 0}]]
```


.

```
>> Graphics[Point[Table[{Sin[t],  
Cos[t]}, {t, 0, 2. Pi, Pi /  
15.}]]]
```



or as {*x*, *y*, *z*}:

```
>> Graphics3D[{Orange, PointSize
[0.05], Point[Table[{Sin[t], Cos
[t], 0}], {t, 0, 2 Pi, Pi /
15.}]]}]
```




## PointSize


`PointSize[t]`  
sets the diameter of points to  $t$ , which is relative to the overall width.

`PointSize` can be used for both two- and three-dimensional graphics. The initial default point-size is 0.008 for two-dimensional graphics and 0.01 for three-dimensional graphics.

```
>> Table[Graphics[{PointSize[r],
Point[{0, 0}]}], {r, {0.02,
0.05, 0.1, 0.3}}]
```



```
>> Table[Graphics3D[{PointSize[r],
Point[{0, 0, 0}]}], {r, {0.05,
0.1, 0.8}}]
```



## Polygon

`Polygon[{point_1, point_2 ...}]`  
represents the filled polygon primitive.  
`Polygon[{{p_11, p_12, ...}, {p_21, p_22, ...}, ...}]`  
represents a number of filled polygon primitives.

A Right Triangle:


```
>> Graphics[Polygon
[{{1,0},{0,0},{0,1}}]]
```




Notice that there is a line connecting from the last point to the first one.

A point is an element of the polygon if a ray from the point in any direction in the plane crosses the boundary line segments an odd number of times.

```
>> Graphics[Polygon
[{{150,0},{121,90},{198,35},{102,35},{179,
```




```
>> Graphics3D[Polygon
[{{0,0,0},{0,1,1},{1,0,0}}]]
```



## Rectangle

`Rectangle[{xmin, ymin}]`  
represents a unit square with bottom-left corner at  $\{x_{min}, y_{min}\}$ .  
`Rectangle[{xmin, ymin}, {xmax, yymax}]`  
is a rectangle extending from  $\{x_{min}, y_{min}\}$  to  $\{x_{max}, y_{ymax}\}$ .


```
>> Graphics[Rectangle[]]
```



```
>> Graphics[{Blue, Rectangle[{0.5, 0}], Orange, Rectangle[{0, 0.5}]}]
```



```
>> Graphics[{Yellow, Rectangle[], Orange, RegularPolygon[{1, 1}, {0.25, 0}, 3]}]
```



## RegularPolygon


`RegularPolygon[ $n$ ]`  
gives the regular polygon with  $n$  edges.

`RegularPolygon[ $r$ ,  $n$ ]`  
gives the regular polygon with  $n$  edges and radius  $r$ .

`RegularPolygon[{ $r$ ,  $\phi$ },  $n$ ]`  
gives the regular polygon with radius  $r$  with one vertex drawn at angle  $\phi$ .

`RegularPolygon[{ $x$ ,  $y$ },  $r$ ,  $n$ ]`  
gives the regular polygon centered at the position  $\{x, y\}$ .


```
>> Graphics[RegularPolygon[5]]
```



## Show

`Show[graphics, options]`  
shows a list of graphics with the specified options added.

```
>> Show[{Plot[x, {x, 0, 10}],
ListPlot[{1,2,3}]}]
```



- > Ignore, AspectRatio  
 - > Automatic, Axes  
 - > False, AxesStyle  
 - > {}, Background  
 - > Automatic, ImageSize  
 - > Automatic, LabelStyle  
 - > {}, PlotRange  
 - > Automatic, PlotRangePadding

- > Automatic, TicksStyle - > {}

## Small


ImageSize -> Small  
produces a small image.

Text

Text["text", {x, y}]  
draws *text* centered on position {x, y}.

Syntax

```
>> Graphics[{Text["First", {0, 0}],
Text["Second", {1, 1}], Axes->
True, PlotRange->{{-2, 2}, {-2,
2}}]
```




## Thick

Thick  
sets the line width for subsequent graphics primitives to 2pt.

## Thickness

Thickness[t]  
sets the line thickness for subsequent graphics primitives to  $t$  times the size of the plot area.

```
>> Graphics[{Thickness[0.2], Line
[{{0, 0}, {0, 5}}]}, Axes->True,
PlotRange->{{-5, 5}, {-5, 5}}]
```



## Thin

**Thin**  
sets the line width for subsequent graphics primitives to 0.5pt.

## Tiny

**ImageSize -> Tiny**  
produces a tiny image.

## 16. Strings and Characters - Miscellaneous

### Contents

---

Alphabet . . . . .	103	StringContainsQ . . . . .	104	ToExpression . . . . .	105
\$CharacterEncoding . . . . .	103	StringQ . . . . .	105	ToString . . . . .	106
HexidecimalCharacter . . . . .	103	StringRepeat . . . . .	105	Transliterate . . . . .	106
LetterNumber . . . . .	104	String . . . . .	105	Whitespace . . . . .	106
NumberString . . . . .	104	\$SystemCharacterEn-			
RemoveDiacritics . . . . .	104	coding . . . . .	105		

---

### Alphabet

`Alphabet[]`  
gives the list of lowercase letters a-z in the English alphabet .  
`Alphabet[type]`  
gives the alphabet for the language or class *type*.

```
>> Alphabet[]
{a,b,c,d,e,f,g,h,i,j,k,l,m,
 n,o,p,q,r,s,t,u,v,w,x,y,z}

>> Alphabet["German"]
{a,b,c,d,e,f,g,h,i,j,k,l,m,
 n,o,p,q,r,s,t,u,v,w,x,y,z}
```

### \$CharacterEncoding

`CharacterEncoding`  
specifies the default character encoding to use if no other encoding is specified.

### HexidecimalCharacter

`HexidecimalCharacter`  
represents the characters 0-9, a-f and A-F.

```
>> StringMatchQ[#,
HexidecimalCharacter] & /@ {"a",
 "1", "A", "x", "H", " ", "."}

{True,True,True,False,
 False,False,False}
```

### LetterNumber

`LetterNumber[c]`  
returns the position of the character *c* in the English alphabet.  
`LetterNumber['string']`  
returns a list of the positions of characters in string.  
`LetterNumber['string', alpha]`  
returns a list of the positions of characters in string, regarding the alphabet *alpha*.

```
>> LetterNumber["b"]
2
```

LetterNumber also works with uppercase characters

```
>> LetterNumber["B"]
2
```

```
>> LetterNumber["ss2!"]
{19,19,0,0}
```

Get positions of each of the letters in a string:

```
>> LetterNumber[Characters["Peccary"]]
{16,5,3,3,1,18,25}
```

```
>> LetterNumber[{"P", "Pe", "P1", "eck"}]
{16, {16, 5}, {16, 0}, {5, 3, 11}}
>> LetterNumber["\[Beta]", "Greek"]
2
```

## NumberString

**NumberString**  
represents the characters in a number.

```
>> StringMatchQ["1234",
NumberString]
True
>> StringMatchQ["1234.5",
NumberString]
True
>> StringMatchQ["1.2'20",
NumberString]
False
```

## RemoveDiacritics

**RemoveDiacritics[s]**  
returns a version of *s* with all diacritics removed.

```
>> RemoveDiacritics["en prononçant
pêcher et pêcher"]
en prononcant pecher et pecher
>> RemoveDiacritics["piñata"]
pinata
```

## StringContainsQ

**StringContainsQ[*string*, *patt*]**  
returns True if any part of *string* matches *patt*, and returns False otherwise.  
**StringContainsQ[{*s1*, *s2*, ...}, *patt*]**  
returns the list of results for each element of string list.  
**StringContainsQ[*patt*]**  
represents an operator form of StringContainsQ that can be applied to an expression.

```
>> StringContainsQ["mathics", "m" ~
~__ ~~"s"]
True
>> StringContainsQ["mathics", "a" ~
~__ ~~"m"]
False
>> StringContainsQ["Mathics", "MA"
, IgnoreCase -> True]
True
>> StringContainsQ[{"g", "a", "laxy",
"universe", "sun"}, "u"]
{False, False, False, True, True}
>> StringContainsQ["e" ~~__ ~~"u"]
/ @ {"The Sun", "Mercury", "Venus", "Earth", "Mars", "Jupiter", "Saturn", "Uranus", "Neptune"}
{True, True, True, False, False, False, False, False, True}
```

## StringQ

**StringQ[*expr*]**  
returns True if *expr* is a String, or False otherwise.

```
>> StringQ["abc"]
True
>> StringQ[1.5]
False
```



```
>> Select[{"12", 1, 3, 5, "yz", x,
y}, StringQ]
{12, yz}
```

## StringRepeat

```
StringRepeat["string", n]
  gives string repeated n times.
StringRepeat["string", n, max]
  gives string repeated n times, but not
  more than max characters.
```

```
>> StringRepeat["abc", 3]
abcabcabc
>> StringRepeat["abc", 10, 7]
abcabca
```

## String

```
String
  is the head of strings.
```

```
>> Head["abc"]
String
>> "abc"
abc
```

Use `InputForm` to display quotes around strings:

```
>> InputForm["abc"]
"abc"
```

`FullForm` also displays quotes:

```
>> FullForm["abc" + 2]
Plus[2, "abc"]
```

## \$SystemCharacterEncoding

```
$SystemCharacterEncoding
```

## ToExpression

```
ToExpression[input]
  interprets a given string as Mathics input.
ToExpression[input, form]
  reads the given input in the specified
  form.
ToExpression[input, form, h]
  applies the head h to the expression be-
  fore evaluating it.
```

```
>> ToExpression["1 + 2"]
3
>> ToExpression["{2, 3, 1}",
InputForm, Max]
3
>> ToExpression["2 3", InputForm]
6
```

Note that newlines are like semicolons, not blanks. So the return value is the second-line value.

```
>> ToExpression["2\[NewLine]3"]
3
```

## ToString

```
ToString[expr]
  returns a string representation of expr.
ToString[expr, form]
  returns a string representation of expr in
  the form form.
```

```
>> ToString[2]
2
>> ToString[2] // InputForm
"2"
>> ToString[a+b]
a + b
>> "U" <> 2
Stringexpected.
U<>2
>> "U" <> ToString[2]
U2
```

```
>> ToString[Integrate[f[x],x],
TeXForm]
\int f\left[x\right] \, dx
```

## Transliterate

```
Transliterate[s]
  transliterates a text in some script into an
  ASCII string.
```

# The following examples were taken from  
# <https://en.wikipedia.org/wiki/Iliad>, #  
[https://en.wikipedia.org/wiki/Russian\\_language](https://en.wikipedia.org/wiki/Russian_language),  
and # <https://en.wikipedia.org/wiki/Hiragana>

## Whitespace

```
Whitespace
  represents a sequence of whitespace char-
  acters.
```

```
>> StringMatchQ["\r \n", Whitespace
]
True

>> StringSplit["a \n b \r\n c d",
Whitespace]
{a,b,c,d}

>> StringReplace[" this has leading
  and trailing whitespace \n ", (
  StartOfString ~~Whitespace)| (
  Whitespace ~~EndOfString)-> ""]
<> " removed" // FullForm
"this has leading and trailing
  whitespace removed"
```

# 17. Mathematical Optimization

Mathematical optimization is the selection of a best element, with regard to some criterion, from some set of available alternatives.

Optimization problems of sorts arise in all quantitative disciplines from computer science and engineering to operations research and eco-

nomics, and the development of solution methods has been of interest in mathematics for centuries.

We intend to provide local and global optimization techniques, both numeric and symbolic.

## Contents

---

<b>Maximize</b> . . . . .	<b>107</b>	<b>Minimize</b> . . . . .	<b>107</b>
---------------------------	------------	---------------------------	------------

---

## Maximize

`Maximize[f, x]`  
compute the maximum of  $f$  respect  $x$  that change between  $a$  and  $b$

```
>> Maximize[-2 x^2 - 3 x + 5, x]
      { { 49/8, { x -> -3/4 } } }

#> Maximize[1 - (x y - 3)^2, {x, y}] = {{1, {x -> 3, y -> 1}}}
#> Maximize[{x - 2 y, x^2 + y^2 <= 1}, {x, y}] =
{{Sqrt[5], {x -> Sqrt[5] / 5, y -> -2 Sqrt[5] / 5}}}
```

## Minimize

`Minimize[f, x]`  
compute the minimum of  $f$  respect  $x$  that change between  $a$  and  $b$

```
>> Minimize[2 x^2 - 3 x + 5, x]
      { { 31/8, { x -> 3/4 } } }

#> Minimize[(x y - 3)^2 + 1, {x, y}] = {{1, {x -> 3, y -> 1}}}
#> Minimize[{x - 2 y, x^2 + y^2 <= 1}, {x, y}] =
{{-Sqrt[5], {x -> -Sqrt[5] / 5, y -> 2 Sqrt[5] / 5}}}
```

# 18. Drawing Options and Option Values

The various common Plot and Graphics options, along with the meaning of specific option values are described here.

## Contents

Automatic . . . . .	108	ChartLegends . . . . .	109	Mesh . . . . .	111
Axes . . . . .	108	Filling . . . . .	109	PlotPoints . . . . .	111
Axis . . . . .	109	Full . . . . .	109	PlotRange . . . . .	111
Bottom . . . . .	109	ImageSize . . . . .	110	TicksStyle . . . . .	112
ChartLabels . . . . .	109	Joined . . . . .	110	Top . . . . .	112
		MaxRecursion . . . . .	110		


## Automatic

**Automatic**  
is used to specify an automatically computed option value.

Automatic is the default for PlotRange, ImageSize, and other graphical options:

```
>> Cases[Options[Plot], HoldPattern
[_ :> Automatic]]
{Background:>Automatic,
 Exclusions:>Automatic,
 ImageSize:>Automatic,
 MaxRecursion:>Automatic,
 PlotRange:>Automatic,
 PlotRangePadding:>Automatic}
```

```
>> Graphics[Circle[], Axes -> True]
```



## Axes


**Axes**  
is an option for charting and graphics functions that specifies whether axes should be drawn.

- Axes->True draws all axes.
- Axes->False draws no axes.
- Axes->{False,True} draws an axis *y* but no *x* axis in two dimensions.

## Axis

**Axis**  
is a possible value for the Filling option.

```
>> ListLinePlot[Table[Sin[x], {x,
-5, 5, 0.5}], Filling->Axis]
```



## Bottom


**Bottom**  
is a possible value for the **Filling** option.

```
>> ListLinePlot[Table[Sin[x], {x,
-5, 5, 0.5}], Filling->Bottom]
```

## ChartLabels

**ChartLabels**  
is a charting option that specifies what labels should be used for chart elements.

```
>> PieChart[{30, 20, 10},
ChartLabels -> {Dogs, Cats, Fish
}]
```




## ChartLegends

**ChartLegends**  
is a charting option.

## Filling

**Filling** **Top** | **Bottom** | **Axis**  
is an option to **Plot** to specify what filling to add under point, curves, and surfaces

```
>> ListLinePlot[Table[Sin[x], {x,
-5, 5, 0.5}], Filling->Axis]
```



## Full

**Full**  
is a possible value for the **Mesh** and **PlotRange** options.

## ImageSize

**ImageSize**  
is an option that specifies the overall size of an image to display.


Specifications for both width and height can be any of the following:

Automatic

determined by location or other dimension (default)

Tiny, Small, Medium, Large  
pre defined absolute sizes

```
>> Plot[Sin[x], {x, 0, 10},  
ImageSize -> Small]
```




## Joined

Joined *boolean*

is an option for Plot that gives whether to join points to make lines.

```
>> ListPlot[Table[n ^ 2, {n, 10}],  
Joined->True]
```



## MaxRecursion

MaxRecursion

is an option for functions like NIntegrate and Plot that specifies how many recursive subdivisions can be made.

```
>> NIntegrate[Exp[-10^8 x^2], {x,  
-1, 1}, MaxRecursion -> 10]
```


$1.97519 \times 10^{-207}$

## Mesh


Mesh

is a charting option, such as for Plot, BarChart, PieChart, etc. that specifies the mesh to be drawn. The default is Mesh->None.


```
>> Plot[Sin[Cos[x^2]], {x, -4, 4}, Mesh  
->All]
```




```
>> Plot[Sin[x], {x, 0, 4 Pi}, Mesh->  
Full]
```




```
>> DensityPlot[Sin[x y], {x, -2,  
2}, {y, -2, 2}, Mesh->Full]
```




```
>> Plot3D[Sin[x y], {x, -2, 2}, {y, -2, 2}, Mesh->Full]
```



```
>> Plot[Sin[Cos[x^2]], {x, -4, 4}, PlotRange -> All]
```



```
>> Graphics[Disk[], PlotRange -> {{-.5, .5}, {0, 1.5}}]
```




## PlotPoints

**PlotPoints** *n*

A number specifies how many initial sample points to use.

```
>> Plot[Sin[Cos[x^2]], {x, -4, 4}, PlotPoints->22]
```



## PlotRange

**PlotRange**

is a charting option, such as for Plot, BarChart, PieChart, etc. that gives the range of coordinates to include in a plot.

- All all points are included.
- Automatic - outlying points are dropped.
- *max* - explicit limit for each function.
- *{min, max}* - explicit limits for *y* (2D), *z* (3D), or array values.
- *{{x\_min, x\_max}, {{y\_min}, {y\_max}}}* - explicit limits for *x* and *y*.


## TicksStyle

**TicksStyle**

is an option for graphics functions which specifies how ticks should be rendered.

- TicksStyle gives styles for both tick marks and tick labels.
- TicksStyle can be used in both two and three-dimensional graphics.
- TicksStyle->*list* specifies the colors of each of the axes.


```
>> Graphics[Circle[], Axes-> True,
  TicksStyle -> {Blue, Red}]
```



## Top

Top  
is a possible value for the Filling option.

```
>> ListLinePlot[Table[Sin[x], {x,
  -5, 5, 0.5}], Filling->Axis|Top|
  Bottom]
```





# 19. Physical and Chemical data

## Contents

---

ElementData . . . . . 114

---

## ElementData

`ElementData["name", "property"]`  
gives the value of the *property* for the chemical specified by *name*.  
`ElementData[n, "property"]`  
gives the value of the *property* for the *n*th chemical element.

```
>> ElementData[74]
Tungsten

>> ElementData["He", "
AbsoluteBoilingPoint"]
4.22

>> ElementData["Carbon", "
IonizationEnergies"]
{1 086.5, 2 352.6, 4 620.5
, 6 222.7, 37 831, 47 277.}

>> ElementData[16, "
ElectronConfigurationString"]
[Ne] 3s2 3p4

>> ElementData[73, "
ElectronConfiguration"]
{{2}, {2, 6}, {2, 6, 10}, {2,
6, 10, 14}, {2, 6, 3}, {2}}
```

The number of known elements:

```
>> Length[ElementData[All]]
118
```

Some properties are not appropriate for certain elements:

```
>> ElementData["He", "
ElectroNegativity"]
Missing[NotApplicable]
```


Some data is missing:

```
>> ElementData["Tc", "SpecificHeat
"]
Missing[NotAvailable]
```

All the known properties:

```
>> ElementData["Properties"]
{Abbreviation,
AbsoluteBoilingPoint,
AbsoluteMeltingPoint,
AtomicNumber, AtomicRadius,
AtomicWeight, Block, BoilingPoint,
BrinellHardness, BulkModulus,
CovalentRadius, CrustAbundance,
Density, DiscoveryYear,
ElectroNegativity, ElectronAffinity,
ElectronConfiguration,
ElectronConfigurationString,
ElectronShellConfiguration,
FusionHeat, Group,
IonizationEnergies, LiquidDensity,
MeltingPoint, MohsHardness,
Name, Period, PoissonRatio,
Series, ShearModulus,
SpecificHeat, StandardName,
ThermalConductivity,
VanDerWaalsRadius,
VaporizationHeat,
VickersHardness, YoungModulus}
```

```
>> ListPlot[Table[ElementData[z, "AtomicWeight"], {z, 118}]]
```



## 20. List Functions - Miscellaneous

### Contents

All . . . . .	115	IntersectingQ . . . . .	120	Quartiles . . . . .	125
Association . . . . .	115	Intersection . . . . .	120	RankedMax . . . . .	125
AssociationQ . . . . .	116	Join . . . . .	121	RankedMin . . . . .	125
ByteArray . . . . .	116	Key . . . . .	121	Reverse . . . . .	125
Catenate . . . . .	116	Keys . . . . .	121	Riffle . . . . .	125
CentralMoment . . . . .	116	Kurtosis . . . . .	121	RotateLeft . . . . .	126
ClusteringComponents . . . . .	116	LeafCount . . . . .	121	RotateRight . . . . .	126
Complement . . . . .	117	Level . . . . .	122	Skewness . . . . .	126
ContainsOnly . . . . .	117	LevelQ . . . . .	122	Split . . . . .	126
Correlation . . . . .	117	List . . . . .	122	SplitBy . . . . .	127
Covariance . . . . .	117	ListQ . . . . .	122	StandardDeviation . . . . .	127
Delete . . . . .	118	Lookup . . . . .	122	SubsetQ . . . . .	127
DeleteDuplicates . . . . .	118	Median . . . . .	123	TakeLargest . . . . .	127
DisjointQ . . . . .	118	Nearest . . . . .	123	TakeLargestBy . . . . .	128
Failure . . . . .	118	None . . . . .	123	TakeSmallest . . . . .	128
FindClusters . . . . .	119	NotListQ . . . . .	123	TakeSmallestBy . . . . .	128
Fold . . . . .	119	PadLeft . . . . .	124	Tally . . . . .	128
FoldList . . . . .	119	PadRight . . . . .	124	Union . . . . .	128
Gather . . . . .	120	Partition . . . . .	124	UnitVector . . . . .	128
GatherBy . . . . .	120	Position . . . . .	124	Values . . . . .	129
Insert . . . . .	120	Quantile . . . . .	125	Variance . . . . .	129

### All

All

is a possible option value for Span, Quiet, Part and related functions. All specifies all parts at a particular level.

### Association

```
Association[key1 -> val1, key2 -> val2, ...]
<|key1 -> val1, key2 -> val2, ...|>
  represents an association between keys
  and values.
```

Association is the head of associations:

```
>> Head[<|a -> x, b -> y, c -> z|>]
Association
>> <|a -> x, b -> y|>
<|a -> x, b -> y|>
>> Association[{a -> x, b -> y}]
<|a -> x, b -> y|>
```

Associations can be nested:

```
>> <|a -> x, b -> y, <|a -> z, d ->
  t|>|>
<|a -> z, b -> y, d -> t|>
```

## AssociationQ

`AssociationQ[expr]`  
return True if *expr* is a valid Association object, and False otherwise.

```
>> AssociationQ[<|a -> 1, b :> 2|>]
True
>> AssociationQ[<|a, b|>]
False
```

## ByteArray

`ByteArray[{b1, b2, ...}]`  
Represents a sequence of Bytes *b<sub>1</sub>*, *b<sub>2</sub>*, ...  
`ByteArray['string']`  
Constructs a byte array where bytes comes from decode a b64 encoded String

```
>> A=ByteArray[{1, 25, 3}]
ByteArray["ARkD"]
>> A[[2]]
25
>> Normal[A]
{1,25,3}
>> ToString[A]
ByteArray["ARkD"]
>> ByteArray["ARkD"]
ByteArray["ARkD"]
>> B=ByteArray["asy"]
The first argument in ByteArray[asy] should be a B64 encoded string.
$Failed
```

## Catenate

`Catenate[{l1, l2, ...}]`  
concatenates the lists *l<sub>1</sub>*, *l<sub>2</sub>*, ...

```
>> Catenate[{{1, 2, 3}, {4, 5}}]
{1,2,3,4,5}
```

## CentralMoment

`CentralMoment[list, r]`  
gives the the *r*th central moment (i.e. the *r*th moment about the mean) of *list*.

```
>> CentralMoment[{1.1, 1.2, 1.4, 2.1, 2.4}, 4]
0.100845
```

## ClusteringComponents

`ClusteringComponents[list]`  
forms clusters from *list* and returns a list of cluster indices, in which each element shows the index of the cluster in which the corresponding element in *list* ended up.

`ClusteringComponents[list, k]`  
forms *k* clusters from *list* and returns a list of cluster indices, in which each element shows the index of the cluster in which the corresponding element in *list* ended up.

For more detailed documentation regarding options and behavior, see `FindClusters[]`.

```
>> ClusteringComponents[{1, 2, 3, 1, 2, 10, 100}]
{1,1,1,1,1,1,2}
>> ClusteringComponents[{10, 100, 20}, Method -> "KMeans"]
{1,0,1}
```

## Complement

`Complement[all, e1, e2, ...]`  
returns an expression containing the elements in the set *all* that are not in any of *e<sub>1</sub>*, *e<sub>2</sub>*, etc.

`Complement[all, e1, e2, ..., SameTest->test]`  
applies *test* to the elements in *all* and each of the *e<sub>i</sub>* to determine equality.

The sets *all*, *e<sub>1</sub>*, etc can have any head, which must all match. The returned expression has the

same head as the input expressions. The expression will be sorted and each element will only occur once.

```
>> Complement[{a, b, c}, {a, c}]
      {b}

>> Complement[{a, b, c}, {a, c}, {b}]
      {}

>> Complement[f[z, y, x, w], f[x],
      f[x, z]]
      f[w, y]

>> Complement[{c, b, a}]
      {a, b, c}
```

## ContainsOnly

`ContainsOnly[list1, list2]`  
yields True if *list1* contains only elements that appear in *list2*.

```
>> ContainsOnly[{b, a, a}, {a, b, c}]
      True
```

The first list contains elements not present in the second list:

```
>> ContainsOnly[{b, a, d}, {a, b, c}]
      False

>> ContainsOnly[{}, {a, b, c}]
      True
```

Use `Equal` as the comparison function to have numerical tolerance:

```
>> ContainsOnly[{a, 1.0}, {1, a, b}, {SameTest -> Equal}]
      True
```

## Correlation

`Correlation[a, b]`  
computes Pearson's correlation of two equal-sized vectors *a* and *b*.

An example from Wikipedia:

```
>> Correlation[{10, 8, 13, 9, 11,
      14, 6, 4, 12, 7, 5}, {8.04,
      6.95, 7.58, 8.81, 8.33, 9.96,
      7.24, 4.26, 10.84, 4.82, 5.68}]
      0.816421
```

## Covariance

`Covariance[a, b]`  
computes the covariance between the equal-sized vectors *a* and *b*.

```
>> Covariance[{0.2, 0.3, 0.1},
      {0.3, 0.3, -0.2}]
      0.025
```

## Delete

`Delete[expr, i]`  
deletes the element at position *i* in *expr*. The position is counted from the end if *i* is negative.  
`Delete[expr, {m, n, ...}]`  
deletes the element at position *{m, n, ...}*.  
`Delete[expr, {{m1, n1, ...}, {m2, n2, ...}, ...}]`  
deletes the elements at several positions.

Delete the element at position 3:

```
>> Delete[{a, b, c, d}, 3]
      {a, b, d}
```

Delete at position 2 from the end:

```
>> Delete[{a, b, c, d}, -2]
      {a, b, d}
```

Delete at positions 1 and 3:

```
>> Delete[{a, b, c, d}, {{1}, {3}}]
      {b, d}
```

Delete in a 2D array:

```
>> Delete[{{a, b}, {c, d}}, {2, 1}]
      {{a, b}, {d}}
```

Deleting the head of a whole expression gives a Sequence object:

```
>> Delete[{a, b, c}, 0]
      Sequence[a, b, c]
```

Delete in an expression with any head:

```
>> Delete[f[a, b, c, d], 3]
      f[a, b, d]
```

Delete a head to splice in its arguments:

```
>> Delete[f[a, b, u + v, c], {3, 0}]
      f[a, b, u, v, c]

>> Delete[{a, b, c}, 0]
      Sequence[a, b, c]
```

Delete without the position:

```
>> Delete[{a, b, c, d}]
      Delete[{a, b, c, d}]
Delete called with 1 argument; 2 arguments are expected.
```

Delete with many arguments:

```
>> Delete[{a, b, c, d}, 1, 2]
      Delete[{a, b, c, d}, 1, 2]
Delete called with 3 arguments; 2 arguments are expected.
```

Delete the element out of range:

```
>> Delete[{a, b, c, d}, 5]
      Delete[{a, b, c, d}, 5]
Part{5} of {a, b, c, d} does not exist.
```

Delete the position not integer:

```
>> Delete[{a, b, c, d}, {1, n}]
      Delete[{a, b, c, d}, {1, n}]
Position specification {a, b, c, d} is not a machine
  – sized integer or a list of machine
  – sized integers.
```

## DeleteDuplicates

```
DeleteDuplicates[list]
  deletes duplicates from list.
DeleteDuplicates[list, test]
  deletes elements from list based on
  whether the function test yields True on
  pairs of elements. DeleteDuplicates does
  not change the order of the remaining el-
  ements.
```

```
>> DeleteDuplicates[{1, 7, 8, 4, 3,
      4, 1, 9, 9, 2, 1}]
      {1, 7, 8, 4, 3, 9, 2}
```

```
>> DeleteDuplicates[{3, 2, 1, 2, 3, 4},
      Less]
      {3, 2, 1}
```

## DisjointQ

```
DisjointQ[a, b]
  gives True if $a and $b are disjoint, or
  False if $a and $b have any common el-
  ements.
```

## Failure

```
Failure[tag, assoc]
  represents a failure of a type indicated by
  tag, with details given by the association
  assoc.
```

## FindClusters

```
FindClusters[list]
  returns a list of clusters formed from the
  elements of list. The number of cluster is
  determined automatically.
FindClusters[list, k]
  returns a list of k clusters formed from the
  elements of list.
```

```
>> FindClusters[{1, 2, 20, 10, 11,
      40, 19, 42}]
      {{1, 2, 20, 10, 11, 19}, {40, 42}}

>> FindClusters[{25, 100, 17, 20}]
      {{25, 17, 20}, {100}}

>> FindClusters[{3, 6, 1, 100, 20,
      5, 25, 17, -10, 2}]
      {{3, 6, 1, 5, -10, 2},
      {100}, {20, 25, 17}}
```

```

>> FindClusters[{1, 2, 10, 11, 20,
21}]
{{1,2}, {10,11}, {20,21}}

>> FindClusters[{1, 2, 10, 11, 20,
21}, 2]
{{1,2,10,11}, {20,21}}

>> FindClusters[{1 -> a, 2 -> b, 10
-> c}]
{{a,b}, {c}}

>> FindClusters[{1, 2, 5} -> {a, b,
c}]
{{a,b}, {c}}

>> FindClusters[{1, 2, 3, 1, 2, 10,
100}, Method -> "Agglomerate"]
{{1,2,3,1,2,10}, {100}}

>> FindClusters[{1, 2, 3, 10, 17,
18}, Method -> "Agglomerate"]
{{1,2,3}, {10}, {17,18}}

>> FindClusters[{{1}, {5, 6}, {7},
{2, 4}}, DistanceFunction -> (
Abs[Length[#1] - Length[#2]]&)]
{{{1}, {7}}, {{5,6}, {2,4}}}

>> FindClusters[{"meep", "heap", "
deep", "weep", "sheep", "leap",
"keep"}, 3]
{{meep,deep,weep,keep},
{heap,leap}, {sheep}}

```

FindClusters' automatic distance function detection supports scalars, numeric tensors, boolean vectors and strings.

The Method option must be either "Agglomerate" or "Optimize". If not specified, it defaults to "Optimize". Note that the Agglomerate and Optimize methods usually produce different clusterings.

The runtime of the Agglomerate method is quadratic in the number of clustered points  $n$ , builds the clustering from the bottom up, and is exact (no element of randomness). The Optimize method's runtime is linear in  $n$ , Optimize builds the clustering from top down, and uses random sampling.

## Fold

**Fold** $[f, x, list]$   
returns the result of iteratively applying the binary operator  $f$  to each element of  $list$ , starting with  $x$ .  
**Fold** $[f, list]$   
is equivalent to **Fold** $[f, \text{First}[list], \text{Rest}[list]]$ .

```

>> Fold[Plus, 5, {1, 1, 1}]
8

>> Fold[f, 5, {1, 2, 3}]
f[f[f[5,1],2],3]

```

## FoldList

**FoldList** $[f, x, list]$   
returns a list starting with  $x$ , where each element is the result of applying the binary operator  $f$  to the previous result and the next element of  $list$ .  
**FoldList** $[f, list]$   
is equivalent to **FoldList** $[f, \text{First}[list], \text{Rest}[list]]$ .

```

>> FoldList[f, x, {1, 2, 3}]
{x, f[x,1], f[f[x,1],
2], f[f[f[x,1],2],3]}

>> FoldList[Times, {1, 2, 3}]
{1,2,6}

```

## Gather

**Gather** $[list, test]$   
gathers leaves of  $list$  into sub lists of items that are the same according to  $test$ .  
**Gather** $[list]$   
gathers leaves of  $list$  into sub lists of items that are the same.

The order of the items inside the sub lists is the same as in the original list.

```

>> Gather[{1, 7, 3, 7, 2, 3, 9}]
{{1}, {7,7}, {3,3}, {2}, {9}}

```

```
>> Gather[{1/3, 2/6, 1/9}]
{{ {1 1}, {1 1} }, { {1 1} }, { {1 1} } }
```

## GatherBy

`GatherBy[list, f]`  
gathers leaves of *list* into sub lists of items whose image under *f* identical.

`GatherBy[list, {f, g, ...}]`  
gathers leaves of *list* into sub lists of items whose image under *f* identical. Then, gathers these sub lists again into sub sub lists, that are identical under *g*.

```
>> GatherBy[{{1, 3}, {2, 2}, {1, 1}}, Total]
{{{1,3}, {2,2}}, {{1,1}}}
```

```
>> GatherBy[{"xy", "abc", "ab"}, StringLength]
{{xy,ab}, {abc}}
```

```
>> GatherBy[{{2, 0}, {1, 5}, {1, 0}}, Last]
{{{2,0}, {1,0}}, {{1,5}}}
```

```
>> GatherBy[{{1, 2}, {2, 1}, {3, 5}, {5, 1}, {2, 2, 2}}, {Total, Length}]
{{{1,2}, {2,1}}, {{3, 5}}, {{5,1}}, {{2,2,2}}}
```

## Insert

`Insert[list, elem, n]`  
inserts *elem* at position *n* in *list*. When *n* is negative, the position is counted from the end.

```
>> Insert[{a,b,c,d,e}, x, 3]
{a,b,x,c,d,e}
```

```
>> Insert[{a,b,c,d,e}, x, -2]
{a,b,c,d,x,e}
```

## IntersectingQ

`IntersectingQ[a, b]`  
gives True if there are any common elements in *a* and *b*, or False if *a* and *b* are disjoint.

## Intersection

`Intersection[a, b, ...]`  
gives the intersection of the sets. The resulting list will be sorted and each element will only occur once.

```
>> Intersection[{1000, 100, 10, 1}, {1, 5, 10, 15}]
{1,10}
```

```
>> Intersection[{{a, b}, {x, y}}, {{x, x}, {x, y}, {x, z}}]
{{x,y}}
```

```
>> Intersection[{c, b, a}]
{a,b,c}
```

```
>> Intersection[{1, 2, 3}, {2, 3, 4}, SameTest->Less]
{3}
```

## Join

`Join[l1, l2]`  
concatenates the lists *l1* and *l2*.

Join concatenates lists:

```
>> Join[{a, b}, {c, d, e}]
{a,b,c,d,e}
```

```
>> Join[{{a, b}, {c, d}}, {{1, 2}, {3, 4}}]
{{a,b}, {c,d}, {1,2}, {3,4}}
```

The concatenated expressions may have any head:

```
>> Join[a + b, c + d, e + f]
a + b + c + d + e + f
```



However, it must be the same for all expressions:

```
>> Join[a + b, c * d]
      HeadsPlusandTimesareexpectedtobethesame.
Join[a + b, cd]
```

## Key

`Key[key]`  
represents a key used to access a value in an association.  
`Key[key][assoc]`

## Keys

`Keys[<|key1 -> val1, key2 -> val2, ...|>]`  
return a list of the keys *keyi* in an association.  
`Keys[{key1 -> val1, key2 -> val2, ...}]`  
return a list of the *keyi* in a list of rules.

```
>> Keys[<|a -> x, b -> y|>]
      {a, b}
```

```
>> Keys[{a -> x, b -> y}]
      {a, b}
```

Keys automatically threads over lists:

```
>> Keys[{<|a -> x, b -> y|>, {w -> z, {}}}]
      {{a, b}, {w, {}}}
```

Keys are listed in the order of their appearance:

```
>> Keys[{c -> z, b -> y, a -> x}]
      {c, b, a}
```

## Kurtosis

`Kurtosis[list]`  
gives the Pearson measure of kurtosis for *list* (a measure of existing outliers).

```
>> Kurtosis[{1.1, 1.2, 1.4, 2.1, 2.4}]
      1.42098
```

## LeafCount

`LeafCount[expr]`  
returns the total number of indivisible subexpressions in *expr*.

```
>> LeafCount[1 + x + y^a]
      6
>> LeafCount[f[x, y]]
      3
>> LeafCount[{1 / 3, 1 + I}]
      7
>> LeafCount[Sqrt[2]]
      5
>> LeafCount[100!]
      1
```

## Level

`Level[expr, levelspec]`  
gives a list of all subexpressions of *expr* at the level(s) specified by *levelspect*.

Level uses standard level specifications:

*n*  
levels 1 through *n*  
Infinity  
all levels from level 1  
{*n*}  
level *n* only  
{*m*, *n*}  
levels *m* through *n*

Level 0 corresponds to the whole expression.  
A negative level *-n* consists of parts with depth *n*.

Level -1 is the set of atoms in an expression:

```
>> Level[a + b ^ 3 * f[2 x ^ 2], {-1}]
      {a, b, 3, 2, x, 2}
>> Level[{{{a}}}, 3]
      {{a}, {{a}}, {{{a}}}}
>> Level[{{{a}}}, -4]
      {{{{a}}}}
```

```
>> Level[{{{a}}}, -5]
{}

>> Level[h0[h1[h2[h3[a]]]], {0, -1}]
{a, h3[a], h2[h3[a]], h1[h2[h3[a]]], h0[h1[h2[h3[a]]]]}

Use the option Heads -> True to include heads:

>> Level[{{{a}}}, 3, Heads -> True]
{List, List, List, {a}, {{a}}, {{{a}}}}

>> Level[x^2 + y^3, 3, Heads -> True]
{Plus, Power, x, 2, x^2, Power, y, 3, y^3}

>> Level[a ^ 2 + 2 * b, {-1}, Heads -> True]
{Plus, Power, a, 2, Times, 2, b}

>> Level[f[g[h]] [x], {-1}, Heads -> True]
{f, g, h, x}

>> Level[f[g[h]] [x], {-2, -1}, Heads -> True]
{f, g, h, g[h], x, f[g[h]] [x]}
```

## LevelQ

**LevelQ[*expr*]**  
tests whether *expr* is a valid level specification.

```
>> LevelQ[2]
True

>> LevelQ[{2, 4}]
True

>> LevelQ[Infinity]
True

>> LevelQ[a + b]
False
```

## List

**List[*e1, e2, ..., ei*]**  
**{*e1, e2, ..., ei*}**  
represents a list containing the elements *e1...ei*.

List is the head of lists:

```
>> Head[{1, 2, 3}]
List
```

Lists can be nested:

```
>> {{a, b, {c, d}}}
{{a, b, {c, d}}}
```

## ListQ

**ListQ[*expr*]**  
tests whether *expr* is a List.

```
>> ListQ[{1, 2, 3}]
True

>> ListQ[{{1, 2}, {3, 4}}]
True

>> ListQ[x]
False
```

## Lookup

**Lookup[*assoc, key*]**  
looks up the value associated with *key* in the association *assoc*, or Missing[*KeyAbsent*].

## Median

**Median[*list*]**  
returns the median of *list*.

```
>> Median[{26, 64, 36}]
36
```

For lists with an even number of elements, Median returns the mean of the two middle values:

```
>> Median[{-11, 38, 501, 1183}]
      539
      2
```

Passing a matrix returns the medians of the respective columns:

```
>> Median[{{100, 1, 10, 50}, {-1,
      1, -2, 2}}]
      { 99
      2, 1, 4, 26 }
```

## Nearest

```
Nearest[list, x]
  returns the one item in list that is nearest
  to x.
Nearest[list, x, n]
  returns the n nearest items.
Nearest[list, x, {n, r}]
  returns up to n nearest items that are not
  farther from x than r.
Nearest[{p1 -> q1, p2 -> q2, ...}, x]
  returns q1, q2, ... but measures the dis-
  tances using p1, p2, ...
Nearest[{p1, p2, ...} -> {q1, q2,
  ...}, x]
  returns q1, q2, ... but measures the dis-
  tances using p1, p2, ...
```

```
>> Nearest[{5, 2.5, 10, 11, 15,
      8.5, 14}, 12]
      {11}
```

Return all items within a distance of 5:

```
>> Nearest[{5, 2.5, 10, 11, 15,
      8.5, 14}, 12, {All, 5}]
      {11, 10, 14}

>> Nearest[{Blue -> "blue", White
-> "white", Red -> "red", Green
-> "green"}, {Orange, Gray}]
      {{red}, {white}}

>> Nearest[{{0, 1}, {1, 2}, {2, 3}}
-> {a, b, c}, {1.1, 2}]
      {b}
```

## None

```
None
  is a possible value for Span and Quiet.
```

## NotListQ

```
NotListQ[expr]
  returns true if expr is not a list.
```

## PadLeft

```
PadLeft[list, n]
  pads list to length n by adding 0 on the
  left.
PadLeft[list, n, x]
  pads list to length n by adding x on the
  left.
PadLeft[list, {n1, $n2, ...}, x]
  pads list to lengths n1, n2 at levels 1, 2, ...
  respectively by adding x on the left.
PadLeft[list, n, x, m]
  pads list to length n by adding x on the
  left and adding a margin of m on the
  right.
PadLeft[list, n, x, {m1, m2, ...}]
  pads list to length n by adding x on the
  left and adding margins of m1, m2, ... on
  levels 1, 2, ... on the right.
PadLeft[list]
  turns the ragged list list into a regular list
  by adding 0 on the left.
```

```
>> PadLeft[{1, 2, 3}, 5]
      {0, 0, 1, 2, 3}

>> PadLeft[x[a, b, c], 5]
      x[0, 0, a, b, c]

>> PadLeft[{1, 2, 3}, 2]
      {2, 3}

>> PadLeft[{{}, {1, 2}, {1, 2, 3}}]
      {{0, 0, 0}, {0, 1, 2}, {1, 2, 3}}

>> PadLeft[{1, 2, 3}, 10, {a, b, c
}, 2]
      {b, c, a, b, c, 1, 2, 3, a, b}
```

```
>> PadLeft[{{1, 2, 3}}, {5, 2}, x,
1]
{{x, x}, {x, x}, {x,
x}, {3, x}, {x, x}}
```

## PadRight

```
PadRight[list, n]
  pads list to length n by adding 0 on the
  right.
PadRight[list, n, x]
  pads list to length n by adding x on the
  right.
PadRight[list, {n1, $n2, ...}, x]
  pads list to lengths n1, n2 at levels 1, 2, ...
  respectively by adding x on the right.
PadRight[list, n, x, m]
  pads list to length n by adding x on the
  left and adding a margin of m on the left.
PadRight[list, n, x, {m1, m2, ...}]
  pads list to length n by adding x on the
  right and adding margins of m1, m2, ...
  on levels 1, 2, ... on the left.
PadRight[list]
  turns the ragged list list into a regular list
  by adding 0 on the right.
```

```
>> PadRight[{1, 2, 3}, 5]
{1, 2, 3, 0, 0}

>> PadRight[x[a, b, c], 5]
x[a, b, c, 0, 0]

>> PadRight[{1, 2, 3}, 2]
{1, 2}

>> PadRight[{{}}, {1, 2}, {1, 2,
3}]
{{0, 0, 0}, {1, 2, 0}, {1, 2, 3}}

>> PadRight[{1, 2, 3}, 10, {a, b, c
}, 2]
{b, c, 1, 2, 3, a, b, c, a, b}

>> PadRight[{{1, 2, 3}}, {5, 2}, x,
1]
{{x, x}, {x, 1}, {x,
x}, {x, x}, {x, x}}
```

## Partition

```
Partition[list, n]
  partitions list into sublists of length n.
Partition[list, n, d]
  partitions list into sublists of length n
  which overlap d indicies.
```

```
>> Partition[{a, b, c, d, e, f}, 2]
{{a, b}, {c, d}, {e, f}}

>> Partition[{a, b, c, d, e, f}, 3,
1]
{{a, b, c}, {b, c, d}, {c, d, e}, {d, e, f}}
```

## Position

```
Position[expr, patt]
  returns the list of positions for which expr
  matches patt.
Position[expr, patt, ls]
  returns the positions on levels specified
  by levelspec ls.
```

```
>> Position[{1, 2, 2, 1, 2, 3, 2},
2]
{{2}, {3}, {5}, {7}}
```

Find positions upto 3 levels deep

```
>> Position[{1 + Sin[x], x, (Tan[x]
- y)^2}, x, 3]
{{1, 2, 1}, {2}}
```

Find all powers of x

```
>> Position[{1 + x^2, x y ^ 2, 4 y,
x ^ z}, x^_]
{{1, 2}, {4}}
```

Use Position as an operator

```
>> Position[_Integer][{1.5, 2,
2.5}]
{{2}}
```

## Quantile

```
Quantile[list, q]
  returns the qth quantile of list.
```

```
>> Quantile[Range[11], 1/3]
4
>> Quantile[Range[16], 1/4]
5
```

## Quartiles

**Quartiles**[*list*]  
returns the 1/4, 1/2, and 3/4 quantiles of *list*.

```
>> Quartiles[Range[25]]
{ 27/4, 13, 77/4 }
```

## RankedMax

**RankedMax**[*list*, *n*]  
returns the *n*th largest element of *list* (with *n* = 1 yielding the largest element, *n* = 2 yielding the second largest element, and so on).

```
>> RankedMax[{482, 17, 181, -12},
2]
181
```

## RankedMin

**RankedMin**[*list*, *n*]  
returns the *n*th smallest element of *list* (with *n* = 1 yielding the smallest element, *n* = 2 yielding the second smallest element, and so on).

```
>> RankedMin[{482, 17, 181, -12},
2]
17
```

## Reverse

**Reverse**[*expr*]  
reverses the order of *expr*'s items (on the top level)  
**Reverse**[*expr*, *n*]  
reverses the order of items in *expr* on level *n*  
**Reverse**[*expr*, {*n1*, *n2*, ...}]  
reverses the order of items in *expr* on levels *n1*, *n2*, ...

```
>> Reverse[{1, 2, 3}]
{3, 2, 1}
>> Reverse[x[a, b, c]]
x[c, b, a]
>> Reverse[{{1, 2}, {3, 4}}, 1]
{{3, 4}, {1, 2}}
>> Reverse[{{1, 2}, {3, 4}}, 2]
{{2, 1}, {4, 3}}
>> Reverse[{{1, 2}, {3, 4}}, {1, 2}]
{{4, 3}, {2, 1}}
```

## Riffle

**Riffle**[*list*, *x*]  
inserts a copy of *x* between each element of *list*.  
**Riffle**[{*a1*, *a2*, ...}, {*b1*, *b2*, ...}]  
interleaves the elements of both lists, returning {*a1*, *b1*, *a2*, *b2*, ...}.

```
>> Riffle[{a, b, c}, x]
{a, x, b, x, c}
>> Riffle[{a, b, c}, {x, y, z}]
{a, x, b, y, c, z}
>> Riffle[{a, b, c, d, e, f}, {x, y, z}]
{a, x, b, y, c, z, d, x, e, y, f}
```

## RotateLeft

`RotateLeft[expr]`  
rotates the items of *expr* by one item to the left.

`RotateLeft[expr, n]`  
rotates the items of *expr* by *n* items to the left.

`RotateLeft[expr, {n1, n2, ...}]`  
rotates the items of *expr* by *n1* items to the left at the first level, by *n2* items to the left at the second level, and so on.

```
>> RotateLeft[{1, 2, 3}]
{2, 3, 1}

>> RotateLeft[Range[10], 3]
{4, 5, 6, 7, 8, 9, 10, 1, 2, 3}

>> RotateLeft[x[a, b, c], 2]
x[c, a, b]

>> RotateLeft[{{a, b, c}, {d, e, f}, {g, h, i}}, {1, 2}]
{{f, d, e}, {i, g, h}, {c, a, b}}
```

## RotateRight

`RotateRight[expr]`  
rotates the items of *expr* by one item to the right.

`RotateRight[expr, n]`  
rotates the items of *expr* by *n* items to the right.

`RotateRight[expr, {n1, n2, ...}]`  
rotates the items of *expr* by *n1* items to the right at the first level, by *n2* items to the right at the second level, and so on.

```
>> RotateRight[{1, 2, 3}]
{3, 1, 2}

>> RotateRight[Range[10], 3]
{8, 9, 10, 1, 2, 3, 4, 5, 6, 7}

>> RotateRight[x[a, b, c], 2]
x[b, c, a]
```

```
>> RotateRight[{{a, b, c}, {d, e, f}, {g, h, i}}, {1, 2}]
{{h, i, g}, {b, c, a}, {e, f, d}}
```

## Skewness

`Skewness[list]`  
gives Pearson's moment coefficient of skewness for *list* (a measure for estimating the symmetry of a distribution).

```
>> Skewness[{1.1, 1.2, 1.4, 2.1, 2.4}]
0.407041
```

## Split

`Split[list]`  
splits *list* into collections of consecutive identical elements.

`Split[list, test]`  
splits *list* based on whether the function *test* yields True on consecutive elements.

```
>> Split[{x, x, x, y, x, y, y, z}]
{{x, x, x}, {y}, {x}, {y, y}, {z}}
```

Split into increasing or decreasing runs of elements

```
>> Split[{1, 5, 6, 3, 6, 1, 6, 3, 4, 5, 4}, Less]
{{1, 5, 6}, {3, 6}, {1, 6}, {3, 4, 5}, {4}}

>> Split[{1, 5, 6, 3, 6, 1, 6, 3, 4, 5, 4}, Greater]
{{1}, {5}, {6, 3}, {6, 1}, {6, 3}, {4}, {5, 4}}
```

Split based on first element

```
>> Split[{x -> a, x -> y, 2 -> a, z -> c, z -> a}, First[#1] == First[#2] &]
{{x -> a, x -> y}, {2 -> a}, {z -> c, z -> a}}
```

## SplitBy

`SplitBy[list, f]`  
splits *list* into collections of consecutive elements that give the same result when *f* is applied.

```
>> SplitBy[Range[1, 3, 1/3], Round]
{{1, 4/3}, {5/3, 2, 7/3}, {8/3, 3}}
```

```
>> SplitBy[{1, 2, 1, 1.2}, {Round, Identity}]
{{{1}}, {{2}}, {{1}}, {1.2}}}
```

## StandardDeviation

`StandardDeviation[list]`  
computes the standard deviation of *list*. *list* may consist of numerical values or symbols. Numerical values may be real or complex.

`StandardDeviation[{a1, a2, ...}, {b1, b2, ...}, ...]` will yield `{StandardDeviation[{a1, b1, ...}, StandardDeviation[{a2, b2, ...}], ...}`.

```
>> StandardDeviation[{1, 2, 3}]
1
```

```
>> StandardDeviation[{7, -5, 101, 100}]

$$\frac{\sqrt{13297}}{2}$$

```

```
>> StandardDeviation[{a, a}]
0
```

```
>> StandardDeviation[{{1, 10}, {-1, 20}}]
{ $\sqrt{2}$ ,  $5\sqrt{2}$ }
```

## SubsetQ

`SubsetQ[list1, list2]`  
returns True if *list2* is a subset of *list1*, and False otherwise.

```
>> SubsetQ[{1, 2, 3}, {3, 1}]
True
```

The empty list is a subset of every list:

```
>> SubsetQ[{}, {}]
True
```

```
>> SubsetQ[{1, 2, 3}, {}]
True
```

Every list is a subset of itself:

```
>> SubsetQ[{1, 2, 3}, {1, 2, 3}]
True
```

## TakeLargest

`TakeLargest[list, f, n]`  
returns the a sorted list of the *n* largest items in *list*.

```
>> TakeLargest[{100, -1, 50, 10}, 2]
{100, 50}
```

None, Null, Indeterminate and expressions with head Missing are ignored by default:

```
>> TakeLargest[{-8, 150, Missing[abc]}, 2]
{150, -8}
```

You may specify which items are ignored using the option `ExcludedForms`:

```
>> TakeLargest[{-8, 150, Missing[abc]}, 2, ExcludedForms -> {}]
{Missing[abc], 150}
```

## TakeLargestBy

`TakeLargestBy[list, f, n]`  
returns the a sorted list of the *n* largest items in *list* using *f* to retrieve the items' keys to compare them.

For details on how to use the `ExcludedForms` option, see `TakeLargest[]`.

```
>> TakeLargestBy[{{1, -1}, {10, 100}, {23, 7, 8}, {5, 1}}, Total, 2]
{{10, 100}, {23, 7, 8}}
```

```
>> TakeLargestBy[{"abc", "ab", "x"}, StringLength, 1]
{abc}
```

## TakeSmallest

`TakeSmallest[list, f, n]`  
returns the a sorted list of the  $n$  smallest items in *list*.

For details on how to use the ExcludedForms option, see `TakeLargest[]`.

```
>> TakeSmallest[{{100, -1, 50, 10}, 2]
{-1, 10}
```

## TakeSmallestBy

`TakeSmallestBy[list, f, n]`  
returns the a sorted list of the  $n$  smallest items in *list* using *f* to retrieve the items' keys to compare them.

For details on how to use the ExcludedForms option, see `TakeLargest[]`.

```
>> TakeSmallestBy[{{1, -1}, {10, 100}, {23, 7, 8}, {5, 1}}, Total, 2]
{{1, -1}, {5, 1}}

>> TakeSmallestBy[{"abc", "ab", "x"}, StringLength, 1]
{x}
```

## Tally

`Tally[list]`  
counts and returns the number of occurrences of objects and returns the result as a list of pairs {object, count}.

`Tally[list, test]`  
counts the number of occurrences of objects and uses *\$test* to determine if two objects should be counted in the same bin.

```
>> Tally[{a, b, c, b, a}]
{{a, 2}, {b, 2}, {c, 1}}
```

Tally always returns items in the order as they first appear in *list*:

```
>> Tally[{b, b, a, a, a, d, d, d, d, c}]
{{b, 2}, {a, 3}, {d, 4}, {c, 1}}
```

## Union

`Union[a, b, ...]`  
gives the union of the given set or sets. The resulting list will be sorted and each element will only occur once.

```
>> Union[{5, 1, 3, 7, 1, 8, 3}]
{1, 3, 5, 7, 8}

>> Union[{a, b, c}, {c, d, e}]
{a, b, c, d, e}

>> Union[{c, b, a}]
{a, b, c}

>> Union[{{a, 1}, {b, 2}}, {{c, 1}, {d, 3}}, SameTest->(SameQ[Last[#1], Last[#2]]&)]
{{b, 2}, {c, 1}, {d, 3}}

>> Union[{1, 2, 3}, {2, 3, 4}, SameTest->Less]
{1, 2, 2, 3, 4}
```

## UnitVector

`UnitVector[n, k]`  
returns the  $n$ -dimensional unit vector with a 1 in position  $k$ .  
`UnitVector[k]`  
is equivalent to `UnitVector[2, k]`.

```
>> UnitVector[2]
{0, 1}

>> UnitVector[4, 3]
{0, 0, 1, 0}
```



## Values

```
Values[<|key1 -> val1, key2 -> val2,
...|>]
    return a list of the values vali in an asso-
    ciation.
Values[{key1 -> val1, key2 -> val2,
...}]
    return a list of the vali in a list of rules.
```

```
>> Values[<|a -> x, b -> y|>]
{x, y}
```

```
>> Values[{a -> x, b -> y}]
{x, y}
```

Values automatically threads over lists:

```
>> Values[{<|a -> x, b -> y|>, {c
-> z, {}}}]
{{x, y}, {z, {}}}
```

Values are listed in the order of their appearance:

```
>> Values[{c -> z, b -> y, a -> x}]
{z, y, x}
```

## Variance

```
Variance[list]
    computes the variance of $list. list may
    consist of numerical values or symbols.
    Numerical values may be real or com-
    plex.
Variance[{a1, a2, ...}, {b1, b2, ...}, ...] will yield
{Variance[{a1, b1, ...}, Variance[{a2, b2, ...}], ...}.
```

```
>> Variance[{1, 2, 3}]
1
```

```
>> Variance[{7, -5, 101, 3}]

$$\frac{7475}{3}$$

```

```
>> Variance[{1 + 2I, 3 - 10I}]
74
```

```
>> Variance[{a, a}]
0
```

```
>> Variance[{{1, 3, 5}, {4, 10,
100}}]
```

$$\left\{ \frac{9}{2}, \frac{49}{2}, \frac{9025}{2} \right\}$$

## 21. Numeric Evaluation and Precision

Support for numeric evaluation with arbitrary precision is just a proof-of-concept.

Precision is not “guarded” through the evaluation process. Only integer precision is supported. However, things like  $N[\text{Pi}, 100]$  should work as expected.

### Contents

<b>Chop</b> . . . . .	130	<b>\$MachinePrecision</b> . .	131	<b>NumericQ</b> . . . . .	133
<b>Hash</b> . . . . .	130	<b>\$MaxPrecision</b> . . . .	131	<b>Precision</b> . . . . .	134
<b>IntegerDigits</b> . . . . .	131	<b>\$MinPrecision</b> . . . .	132	<b>Rationalize</b> . . . . .	134
<b>\$MachineEpsilon</b> . . .	131	<b>N</b> . . . . .	133	<b>RealDigits</b> . . . . .	134
<b>MachinePrecision</b> . . .	131	<b>NIntegrate</b> . . . . .	133	<b>Round</b> . . . . .	135

### Chop

**Chop[*expr*]**  
replaces floating point numbers close to 0 by 0.  
**Chop[*expr*, *delta*]**  
uses a tolerance of *delta*. The default tolerance is  $10^{-10}$ .

```
>> Chop[10.0 ^ -16]
0
>> Chop[10.0 ^ -9]
1. × 10-9
>> Chop[10 ^ -11 I]

$$\frac{I}{100\,000\,000\,000}$$

>> Chop[0. + 10 ^ -11 I]
0
```

### Hash

**Hash[*expr*]**  
returns an integer hash for the given *expr*.  
**Hash[*expr*, *type*]**  
returns an integer hash of the specified *type* for the given *expr*.  
The types supported are “MD5”, “Adler32”, “CRC32”, “SHA”, “SHA224”, “SHA256”, “SHA384”, and “SHA512”.  
**Hash[*expr*, *type*, *format*]**  
Returns the hash in the specified format.

```
> Hash["The Adventures of Huckleberry Finn"]
= 213425047836523694663619736686226550816
> Hash["The Adventures of Huckleberry Finn",
"SHA256"] = 950926495945903842880571834086092549189343518
> Hash[1/3] = 56073172797010645108327809727054836008
> Hash[{a,b,{c,{d,e,f}}}] = 135682164776235407777080772547528
> Hash[SomeHead[3.1415]] = 5804231647347187731544201546970
>> Hash[{a, b, c}, "xyzstr"]
Hash[{a,b,c},xyzstr,Integer]
```

## IntegerDigits

`IntegerDigits[n]`  
returns a list of the base-10 digits in the integer  $n$ .  
`IntegerDigits[n, base]`  
returns a list of the base- $base$  digits in  $n$ .  
`IntegerDigits[n, base, length]`  
returns a list of length  $length$ , truncating or padding with zeroes on the left as necessary.

```
>> IntegerDigits[76543]
{7, 6, 5, 4, 3}
```

The sign of  $n$  is discarded:

```
>> IntegerDigits[-76543]
{7, 6, 5, 4, 3}
```

```
>> IntegerDigits[15, 16]
{15}
```

```
>> IntegerDigits[1234, 16]
{4, 13, 2}
```

```
>> IntegerDigits[1234, 10, 5]
{0, 1, 2, 3, 4}
```

## \$MachineEpsilon

`$MachineEpsilon`  
is the distance between 1.0 and the next nearest representable machine-precision number.

```
>> $MachineEpsilon
2.22045 × 10-16
>> x = 1.0 + {0.4, 0.5, 0.6}
$MachineEpsilon;
>> x - 1
{0., 0., 2.22045 × 10-16}
```

## MachinePrecision

`MachinePrecision`  
represents the precision of machine precision numbers.

```
>> N[MachinePrecision]
15.9546
>> N[MachinePrecision, 30]
15.9545897701910033463281614204
```

## \$MachinePrecision

`$MachinePrecision`  
is the number of decimal digits of precision for machine-precision numbers.

```
>> $MachinePrecision
15.9546
```

## \$MaxPrecision

`$MaxPrecision`  
represents the maximum number of digits of precision permitted in arbitrary-precision numbers.

```
>> $MaxPrecision
∞
>> $MaxPrecision = 10;
>> N[Pi, 11]
Requested precision 11 is larger than $MaxPrecision. Using current
= Infinity specifies that any precision should be allowed.
3.141592654
```

## \$MinPrecision

`$MinPrecision`  
represents the minimum number of digits of precision permitted in arbitrary-precision numbers.

```
>> $MinPrecision
0
```

```
>> $MinPrecision = 10;
```

```
>> N[Pi, 9]
```

*Requested precision 9 is smaller than \$MinPrecision. Using current \$MinPrecision of 10 instead.*

```
3.141592654
```

## N

`N[expr, prec]`  
evaluates *expr* numerically with a precision of *prec* digits.

```
>> N[Pi, 50]
```

```
3.141592653589793238462643~  
~3832795028841971693993751
```

```
>> N[1/7]
```

```
0.142857
```

```
>> N[1/7, 5]
```

```
0.14286
```

You can manually assign numerical values to symbols. When you do not specify a precision, `MachinePrecision` is taken.

```
>> N[a] = 10.9
```

```
10.9
```

```
>> a
```

```
a
```

`N` automatically threads over expressions, except when a symbol has attributes `NHoldAll`, `NHoldFirst`, or `NHoldRest`.

```
>> N[a + b]
```

```
10.9 + b
```

```
>> N[a, 20]
```

```
a
```

```
>> N[a, 20] = 11;
```

```
>> N[a + b, 20]
```

```
11.000000000000000000 + b
```

```
>> N[f[a, b]]
```

```
f[10.9, b]
```

```
>> SetAttributes[f, NHoldAll]
```

```
>> N[f[a, b]]
```

```
f[a, b]
```

The precision can be a pattern:

```
>> N[c, p_?(#>10&)] := p
```

```
>> N[c, 3]
```

```
>> N[c, 11]
```

```
11.000000000
```

You can also use `UpSet` or `TagSet` to specify values for `N`:

```
>> N[d] ^= 5;
```

However, the value will not be stored in `UpValues`, but in `NValues` (as for `Set`):

```
>> UpValues[d]
```

```
{}
```

```
>> NValues[d]
```

```
{HoldPattern[N[d,  
MachinePrecision]]:>5}
```

```
>> e /: N[e] = 6;
```

```
>> N[e]
```

```
6.
```

Values for `N[expr]` must be associated with the head of *expr*:

```
>> f /: N[e[f]] = 7;
```

*Tag f not found or too deep for an assigned rule.*

You can use `Condition`:

```
>> N[g[x_, y_], p_] := x + y * Pi  
/; x + y > 3
```

```
>> SetAttributes[g, NHoldRest]
```

```
>> N[g[1, 1]]
```

```
g[1, 1]
```

```
>> N[g[2, 2]] // InputForm
```

```
8.283185307179586
```

The precision of the result is no higher than the precision of the input

```
>> N[Exp[0.1], 100]
```

```
1.10517
```

```
>> % // Precision
```

```
MachinePrecision
```

```
>> N[Exp[1/10], 100]
1.105170918075647624811707~
~826490246668224547194737~
~518718792863289440967966~
~747654302989143318970748654

>> % // Precision
100.

>> N[Exp[1.0^20], 100]
2.7182818284590452354

>> % // Precision
20.
```

## NIntegrate

`NIntegrate[expr, interval]`  
returns a numeric approximation to the definite integral of *expr* with limits *interval* and with a precision of *prec* digits.

`NIntegrate[expr, interval1, interval2, ...]`  
returns a numeric approximation to the multiple integral of *expr* with limits *interval1*, *interval2* and with a precision of *prec* digits.

```
>> NIntegrate[Exp[-x], {x, 0, Infinity}, Tolerance->1*^-6]
1.

>> NIntegrate[Exp[x], {x, -Infinity, 0}, Tolerance->1*^-6]
1.

>> NIntegrate[Exp[-x^2/2.], {x, -Infinity, Infinity}, Tolerance->1*^-6]
2.50663

>> Table[1./NIntegrate[x^k, {x, 0, 1}, Tolerance->1*^-6], {k, 0, 6}]
{1., 2., 3., 4., 5., 6., 7.}
```

*This specified method failed to return a number. Falling*

```
>> NIntegrate[1 / z, {z, -1 - I, 1 - I, 1 + I, -1 + I, -1 - I}, Tolerance->1.*^-4]
Integration over a complex domain is not implemented yet

NIntegrate[1/z, {z, -1 - I, 1 - I, 1 + I, -1 + I, -1 - I}, Tolerance->0.0001]
```

Integrate singularities with weak divergences:

```
>> Table[NIntegrate[x^(1./k-1.), {x, 0, 1.}, Tolerance->1*^-6], {k, 1, 7.}]
{1., 2., 3., 4., 5., 6., 7.}
```

Multiple Integrals :

```
>> NIntegrate[x * y, {x, 0, 1}, {y, 0, 1}]
0.25
```

## NumericQ

`NumericQ[expr]`  
tests whether *expr* represents a numeric quantity.

```
>> NumericQ[2]
True

>> NumericQ[Sqrt[Pi]]
True

>> NumberQ[Sqrt[Pi]]
False
```

## Precision

`Precision[expr]`  
examines the number of significant digits of *expr*.

This is rather a proof-of-concept than a full implementation. Precision of compound expression is not supported yet.

```
>> Precision[1]
∞
```

```
>> Precision[1/2]
 $\infty$ 

>> Precision[0.5]
MachinePrecision
```

## Rationalize

**Rationalize**[*x*]  
converts a real number *x* to a nearby rational number.

**Rationalize**[*x*, *dx*]  
finds the rational number within *dx* of *x* with the smallest denominator.

```
>> Rationalize[2.2]
 $\frac{11}{5}$ 
```

Not all numbers can be well approximated.

```
>> Rationalize[N[Pi]]
3.14159
```

Find the exact rational representation of N[Pi]

```
>> Rationalize[N[Pi], 0]
 $\frac{245850922}{78256779}$ 
```

## RealDigits

**RealDigits**[*n*]  
returns the decimal representation of the real number *n* as list of digits, together with the number of digits that are to the left of the decimal point.

**RealDigits**[*n*, *b*]  
returns a list of base-*b* representation of the real number *n*.

**RealDigits**[*n*, *b*, *len*]  
returns a list of *len* digits.

**RealDigits**[*n*, *b*, *len*, *p*]  
return *len* digits starting with the coefficient of  $b^p$

Return the list of digits and exponent:

```
>> RealDigits[123.55555]
{{1, 2, 3, 5, 5, 5, 5, 5}, 3}
```

Return an explicit recurring decimal form:

```
>> RealDigits[19 / 7]
{{2, {7, 1, 4, 2, 8, 5}}, 1}
```

The 10000th digit of is an 8:

```
>> RealDigits[Pi, 10, 1, -10000]
{{8}, -9999}
```

20 digits starting with the coefficient of  $10^{-5}$ :

```
>> RealDigits[Pi, 10, 20, -5]
{{9, 2, 6, 5, 3, 5, 8, 9, 7, 9, 3, 2, 3, 8, 4, 6, 2, 6, 4, 3}, -4}
```

RealDigits gives Indeterminate if more digits than the precision are requested:

```
>> RealDigits[123.45, 10, 18]
{{1, 2, 3, 4, 5, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, Indeterminate}, 3}
```

Return 25 digits of in base 10:

```
>> RealDigits[Pi, 10, 25]
{{3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5, 8, 9, 7, 9, 3, 2, 3, 8, 4, 6, 2, 6, 4, 3}, 1}
```

## Round

**Round**[*expr*]  
rounds *expr* to the nearest integer.

**Round**[*expr*, *k*]  
rounds *expr* to the closest multiple of *k*.

```
>> Round[10.6]
11

>> Round[0.06, 0.1]
0.1

>> Round[0.04, 0.1]
0.
```

Constants can be rounded too

```
>> Round[Pi, .5]
3.

>> Round[Pi^2]
10
```

Round to exact value

```
>> Round[2.6, 1/3]
 $\frac{8}{3}$ 
```

```
>> Round[10, Pi]
3Pi
```

Round complex numbers

```
>> Round[6/(2 + 3 I)]
1 - I
```

```
>> Round[1 + 2 I, 2 I]
2I
```

Round Negative numbers too

```
>> Round[-1.4]
-1
```

Expressions other than numbers remain unevaluated:

```
>> Round[x]
Round[x]
```

```
>> Round[1.5, k]
Round[1.5, k]
```

## 22. Arithmetic Functions

Arithmetic Functions are functions that work on individual numbers, lists, and arrays: in either symbolic or algebraic forms.



## 23. Basic Arithmetic

The functions here are the basic arithmetic operations that you might find on a calculator.

### Contents

<b>CubeRoot</b> . . . . .	137	<b>Plus (+)</b> . . . . .	138	<b>Subtract (-)</b> . . . . .	139
<b>Divide (/)</b> . . . . .	137	<b>Power (^)</b> . . . . .	139	<b>Times (*)</b> . . . . .	140
<b>Minus (-)</b> . . . . .	138	<b>Sqrt</b> . . . . .	139		

### CubeRoot

**CubeRoot** [*n*]  
finds the real-valued cube root of the given *n*.

```
>> CubeRoot[16]
      221/3
```

### Divide (/)

**Divide** [*a*, *b*]  
*a* / *b*  
represents the division of *a* by *b*.

```
>> 30 / 5
      6
>> 1 / 8
      1
      8
>> Pi / 4
      Pi
      4
```

Use **N** or a decimal point to force numeric evaluation:

```
>> Pi / 4.0
      0.785398
>> 1 / 8
      1
      8
```

```
>> N[%]
      0.125
```

Nested divisions:

```
>> a / b / c
      a
      bc
>> a / (b / c)
      ac
      b
>> a / b / (c / (d / e))
      ad
      bce
>> a / (b ^ 2 * c ^ 3 / e)
      ae
      b2c3
```

### Minus (-)

**Minus** [*expr*]  
is the negation of *expr*.

```
>> -a //FullForm
      Times[-1, a]
```

Minus automatically distributes:

```
>> -(x - 2/3)
      2
      3 - x
```

Minus threads over lists:

```
>> -Range[10]
{-1, -2, -3, -4, -5,
 -6, -7, -8, -9, -10}
```

## Plus (+)

`Plus[a, b, ...]`  
 $a + b + \dots$   
 represents the sum of the terms  $a, b, \dots$

```
>> 1 + 2
3
```

Plus performs basic simplification of terms:

```
>> a + b + a
2a + b
```

```
>> a + a + 3 * a
5a
```

```
>> a + b + 4.5 + a + b + a + 2 +
1.5 b
6.5 + 3a + 3.5b
```

Apply Plus on a list to sum up its elements:

```
>> Plus @@ {2, 4, 6}
12
```

The sum of the first 1000 integers:

```
>> Plus @@ Range[1000]
500500
```


Plus has default value 0:

```
>> DefaultValues[Plus]
{HoldPattern[Default[Plus]]:>0}
```

```
>> a /. n_. + x_ :> {n, x}
{0, a}
```

The sum of 2 red circles and 3 red circles is...

```
>> 2 Graphics[{Red,Disk[]}] + 3
Graphics[{Red,Disk[]}]
```



5

## Power (^)

`Power[a, b]`  
 $a ^ b$   
 represents  $a$  raised to the power of  $b$ .

```
>> 4 ^ (1/2)
2
```


```
>> 4 ^ (1/3)
22/3
```

```
>> 3^123
48519278097689642681~
~155855396759336072~
~749841943521979872827
```

```
>> (y ^ 2) ^ (1/2)
 $\sqrt{y^2}$ 
```

```
>> (y ^ 2) ^ 3
 $y^6$ 
```

```
>> Plot[Evaluate[Table[x^y, {y, 1, 5}]], {x, -1.5, 1.5},
AspectRatio -> 1]
```



Use a decimal point to force numeric evaluation:

```
>> 4.0 ^ (1/3)
1.5874
```

Power has default value 1 for its second argument:

```
>> DefaultValues[Power]
{HoldPattern[Default[Power, 2]] :> 1}

>> a /. x_ ^ n_. :> {x, n}
{a, 1}
```

Power can be used with complex numbers:

```
>> (1.5 + 1.0 I)^ 3.5
-3.68294 + 6.95139I

>> (1.5 + 1.0 I)^ (3.5 + 1.5 I)
-3.19182 + 0.645659I
```

## Sqrt

`Sqrt[expr]`  
returns the square root of *expr*.

```
>> Sqrt[4]
2

>> Sqrt[5]
 $\sqrt{5}$ 

>> Sqrt[5] // N
2.23607


>> Sqrt[a]^2
a
```

Complex numbers:

```
>> Sqrt[-4]
2I

>> I == Sqrt[-1]
True

>> Plot[Sqrt[a^2], {a, -2, 2}]
```



## Subtract (-)

`Subtract[a, b]`  
 $a - b$   
represents the subtraction of *b* from *a*.

```
>> 5 - 3
2

>> a - b // FullForm
Plus[a, Times[-1, b]]

>> a - b - c
a - b - c

>> a - (b - c)
a - b + c
```

## Times (\*)

`Times[a, b, ...]`  
 $a * b * \dots$   
 $a \ b \ \dots$   
represents the product of the terms *a*, *b*, ...

```
>> 10 * 2
20

>> 10 2
20
```

```

>> a * a
 $a^2$ 

>> x ^ 10 * x ^ -2
 $x^8$ 

>> {1, 2, 3} * 4
{4, 8, 12}

>> Times @@ {1, 2, 3, 4}
24

>> IntegerLength[Times@@Range
[5000]]
16326

```

Times has default value 1:

```

>> DefaultValues[Times]
{HoldPattern[Default[Times]]:>1}

>> a /. n_. * x_ :> {n, x}
{1, a}

```

## 24. Sums, Simple Statistics

These functions perform a simple arithmetic computation over a list.

### Contents

---

Accumulate . . . . .	141	Mean . . . . .	141	Total . . . . .	141
----------------------	-----	----------------	-----	-----------------	-----

---

### Accumulate

`Accumulate[list]`  
accumulates the values of *list*, returning a new list.

```
>> Accumulate[{1, 2, 3}]
{1,3,6}
```

```
>> Total[{1, 2, 3}]
6
>> Total[{{1, 2, 3}, {4, 5, 6}, {7,
8 ,9}}]
{12,15,18}
```

Total over rows and columns

```
>> Total[{{1, 2, 3}, {4, 5, 6}, {7,
8 ,9}}, 2]
45
```

### Mean

`Mean[list]`  
returns the statistical mean of *list*.

```
>> Mean[{26, 64, 36}]
42
>> Mean[{1, 1, 2, 3, 5, 8}]
10
3
>> Mean[{a, b}]
a + b
2
```

Total over rows instead of columns

```
>> Total[{{1, 2, 3}, {4, 5, 6}, {7,
8 ,9}}, {2}]
{6,15,24}
```

### Total

`Total[list]`  
adds all values in *list*.  
`Total[list, n]`  
adds all values up to level *n*.  
`Total[list, {n}]`  
totals only the values at level *{n}*.  
`Total[list, {n_1, n_2}]`  
totals at levels *{n\_1, n\_2}*.

## 25. Colors

Programmatic support for symbolic colors.

## 26. Color Directives

There are many different way to specify color; we support all of the color formats below and will convert between the different color formats.

### Contents

CMYKColor . . . . .	143	Hue . . . . .	144	LUVColor . . . . .	144
ColorDistance . . . . .	143	LABColor . . . . .	144	RGBColor . . . . .	145
GrayLevel . . . . .	143	LCHColor . . . . .	144	XYZColor . . . . .	145

### CMYKColor

`CMYKColor[c, m, y, k]`  
represents a color with the specified cyan, magenta, yellow and black components.

```
>> Graphics[MapIndexed[{{CMYKColor
@@ #1, Disk[2*#2 ~Join~{0}]} &,
IdentityMatrix[4]], ImageSize->
Small]
```



- DeltaL: difference in the L component of LCHColor
- DeltaC: difference in the C component of LCHColor
- DeltaH: difference in the H component of LCHColor

It is also possible to specify a custom distance.

```
>> ColorDistance[Magenta, Green]
2.2507

>> ColorDistance[{Red, Blue}, {
Green, Yellow}, DistanceFunction
-> {"CMC", "Perceptibility"}]
{1.0495, 1.27455}
```

### ColorDistance

`ColorDistance[c1, c2]`  
returns a measure of color distance between the colors *c1* and *c2*.  
`ColorDistance[list, c2]`  
returns a list of color distances between the colors in *list* and *c2*.

The option `DistanceFunction` specifies the method used to measure the color distance. Available options are:

- CIE76: Euclidean distance in the LAB-Color space
- CIE94: Euclidean distance in the LCH-Color space
- CIE2000 or CIEDE2000: CIE94 distance with corrections
- CMC: Color Measurement Committee metric (1984)


### GrayLevel

`GrayLevel[g]`  
represents a shade of gray specified by *g*, ranging from 0 (black) to 1 (white).  
`GrayLevel[g, a]`  
represents a shade of gray specified by *g* with opacity *a*.

## Hue

`Hue[h, s, l, a]`  
represents the color with hue  $h$ , saturation  $s$ , lightness  $l$  and opacity  $a$ .  
`Hue[h, s, l]`  
is equivalent to `Hue[h, s, l, 1]`.  
`Hue[h, s]`  
is equivalent to `Hue[h, s, 1, 1]`.  
`Hue[h]`  
is equivalent to `Hue[h, 1, 1, 1]`.

```
>> Graphics[Table[{EdgeForm[Gray],  
Hue[h, s], Disk[{12h, 8s}]}], {h,  
0, 1, 1/6}, {s, 0, 1, 1/4}]]
```



```
>> Graphics[Table[{EdgeForm[{  
GrayLevel[0, 0.5]}], Hue[(-11+q  
+10r)/72, 1, 1, 0.6], Disk[(8-r)  
{Cos[2Pi q/12], Sin[2Pi q/12]}],  
(8-r)/3}], {r, 6}, {q, 12}]]
```

## LABColor

`LABColor[l, a, b]`  
represents a color with the specified lightness, red/green and yellow/blue components in the CIE 1976 L\*a\*b\* (CIELAB) color space.

## LCHColor

`LCHColor[l, c, h]`  
represents a color with the specified lightness, chroma and hue components in the CIELCh CIELab cube color space.


## LUVColor

`LCHColor[l, u, v]`  
represents a color with the specified components in the CIE 1976 L\*u\*v\* (CIELUV) color space.

## RGBColor

`RGBColor[r, g, b]`  
represents a color with the specified red, green and blue components.

```
>> Graphics[MapIndexed[{RGBColor @@  
#1, Disk[2*#2 ~Join~{0}]} &,  
IdentityMatrix[3]], ImageSize->  
Small]
```



```
>> RGBColor[0, 1, 0]  
■
```



```
>> RGBColor[0, 1, 0] // ToBoxes
StyleBox[GraphicsBox[
  {EdgeForm[RGBColor[
    0, 0, 0]], RGBColor[0, 1, 0],
  RectangleBox[{0, 0}]}],
$OptionSyntax -> Ignore,
AspectRatio -> Automatic,
Axes -> False, AxesStyle -> {},
Background -> Automatic,
ImageSize -> 16,
LabelStyle -> {},
PlotRange -> Automatic,
PlotRangePadding -> Automatic,
TicksStyle -> {}],
ImageSizeMultipliers -> {1, 1}]
```

## XYZColor

`XYZColor[x, y, z]`  
 represents a color with the specified components in the CIE 1931 XYZ color space.

## 27. Color Operations


Functions for manipulating colors and color images.


### Contents


Blend . . . . .	146	ColorNegate . . . . .	146	DominantColors . . . .	148
ColorConvert . . . . .	146	Darker . . . . .	147	Lighter . . . . .	148


### Blend

`Blend[{c1, c2}]`  
represents the color between *c1* and *c2*.  
`Blend[{c1, c2}, x]`  
represents the color formed by blending *c1* and *c2* with factors  $1 - x$  and  $x$  respectively.  
`Blend[{c1, c2, ..., cn}, x]`  
blends between the colors *c1* to *cn* according to the factor  $x$ .

```
>> Blend[{Red, Blue}]


>> Blend[{Red, Blue}, 0.3]


>> Blend[{Red, Blue, Green}, 0.75]


>> Graphics[Table[{Blend[{Red, Green, Blue}, x], Rectangle[{10 x, 0}], {x, 0, 1, 1/10}}], {x, 0, 1, 1/10}]]


>> Graphics[Table[{Blend[{RGBColor[1, 0.5, 0, 0.5], RGBColor[0, 0, 1, 0.5]}], x], Disk[{5x, 0}], {x, 0, 1, 1/10}]]
```

### ColorConvert

`ColorConvert[c, colspace]`  
returns the representation of *c* in the color space *colspace*. *c* may be a color or an image.

Valid values for *colspace* are:

CMYK: convert to CMYKColor Grayscale: convert to GrayLevel HSB: convert to Hue LAB: convert to LabColor LCH: convert to LCHColor LUV: convert to LUVColor RGB: convert to RGBColor XYZ: convert to XYZColor

### ColorNegate

`<dl><dt>ColorNegate[image] <dd>returns the negative of image in which colors have been negated.`

`<dt>ColorNegate[color] <dd>returns the negative of a color.`

Yellow is RGBColor[1.0, 1.0, 0.0]

```
>> ColorNegate[Yellow]
```




`</dl>`


### Darker

`Darker[c, f]`  
is equivalent to `Blend[{c, Black}, f]`.  
`Darker[c]`  
is equivalent to `Darker[c, 1/3]`.

```
>> Graphics[{Darker[Red], Disk[]}]
```



```
>> Graphics3D[{Darker[Green], Sphere[]}]
```



```
>> Graphics[Table[{Darker[Yellow, x], Disk[{12x, 0}]}], {x, 0, 1, 1/6}]]
```



## DominantColors

`DominantColors[image]`

gives a list of colors which are dominant in the given image.

`DominantColors[image, n]`

returns at most  $n$  colors.

`DominantColors[image, n, prop]`

returns the given property *prop*, which may be "Color" (return RGB colors), "LABColor" (return LAB colors), "Count" (return the number of pixels a dominant color covers), "Coverage" (return the fraction of the image a dominant color covers), or "CoverageImage" (return a black and white image indicating with white the parts that are covered by a dominant color).

The option "ColorCoverage" specifies the minimum amount of coverage needed to include a dominant color in the result.

The option "MinColorDistance" specifies the distance (in LAB color space) up to which colors are merged and thus regarded as belonging to the same dominant color.

```
>> img = Import["ExampleData/lena.tif"]
```

—Image—

```
>> DominantColors[img]
```

```
{Red, Red, Purple, Red, Red, Red}
```

```
>> DominantColors[img, 3]
```

```
{Red, Red, Purple}
```

```
>> DominantColors[img, 3, "Coverage"]
```

```
{ 28 579 751 23 841 }
{ 131 072' 4 096' 131 072 }
```

```
>> DominantColors[img, 3, "CoverageImage"]
```



```
{—Image—, —Image—, —Image—}
```




```
>> DominantColors[img, 3, "Count"]
```

```
{57 158, 48 064, 47 682}
```

```
>> DominantColors[img, 2, "LABColor"]
```


```
{Red, Red}
```

```
>> DominantColors[img,
    MinColorDistance -> 0.5]
{, }


>> DominantColors[img,
    ColorCoverage -> 0.15]
{, , }
```

## Lighter

```
Lighter[c, f]
    is equivalent to Blend[{c, White}, f].
Lighter[c]
    is equivalent to Lighter[c, 1/3].
```

```
>> Lighter[Orange, 1/4]


>> Graphics[{Lighter[Orange, 1/4],
    Disk[]}]
```



```
>> Graphics[Table[{Lighter[Orange,
    x], Disk[{12x, 0}]}, {x, 0, 1,
    1/6}]]
```



## 28. Named Colors

Mathics has definitions for the most common color names which can be used in a graphics or style specification.

### Contents

---


<b>Black</b> . . . . .	149	<b>LightCyan</b> . . . . .	153	<b>LightYellow</b> . . . . .	157
<b>Blue</b> . . . . .	150	<b>LightGray</b> . . . . .	154	<b>Magenta</b> . . . . .	158
<b>Brown</b> . . . . .	150	<b>LightGreen</b> . . . . .	154	<b>Orange</b> . . . . .	158
<b>Cyan</b> . . . . .	151	<b>LightMagenta</b> . . . . .	155	<b>Pink</b> . . . . .	159
<b>Gray</b> . . . . .	151	<b>LightOrange</b> . . . . .	155	<b>Purple</b> . . . . .	159
<b>Green</b> . . . . .	152	<b>LightPink</b> . . . . .	156	<b>Red</b> . . . . .	159
<b>LightBlue</b> . . . . .	152	<b>LightPurple</b> . . . . .	156	<b>White</b> . . . . .	160
<b>LightBrown</b> . . . . .	153	<b>LightRed</b> . . . . .	157	<b>Yellow</b> . . . . .	160

---

### Black

**Black**  
represents the color black in graphics.

```
>> Graphics[{EdgeForm[Black], Black
, Disk[]}, ImageSize->Small]
```



```
>> Black // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0, 0, 0]], RGBColor [0, 0, 0],
  RectangleBox [ {0, 0} ] } ,
  $OptionSyntax-> Ignore,
  AspectRatio-> Automatic,
  Axes-> False, AxesStyle-> {},
  Background-> Automatic,
  ImageSize-> 16,
  LabelStyle-> {},
  PlotRange-> Automatic,
  PlotRangePadding-> Automatic,
  TicksStyle-> {}],
  ImageSizeMultipliers-> {1, 1}]
```


```
>> Black
```



### Blue

**Blue**  
represents the color blue in graphics.

```
>> Graphics[{EdgeForm[Black], Blue,
  Disk[]}, ImageSize->Small]
```




```
>> Blue // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0,0,0]], RGBColor [0,0,1],
  RectangleBox [ {0,0}]}],
$OptionSyntax-> Ignore,
AspectRatio-> Automatic,
Axes-> False, AxesStyle-> {},
Background-> Automatic,
ImageSize-> 16,
LabelStyle-> {},
PlotRange-> Automatic,
PlotRangePadding-> Automatic,
TicksStyle-> {},
ImageSizeMultipliers-> {1,1}]
```

```
>> Blue
■
```

## Brown

Brown  
represents the color brown in graphics.

```
>> Graphics[{EdgeForm[Black], Brown,
  Disk[]}, ImageSize->Small]
```




```
>> Brown // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0,0,0]], RGBColor [0.6,0.4,
    0.2], RectangleBox [ {0,0}]}],
$OptionSyntax-> Ignore,
AspectRatio-> Automatic,
Axes-> False, AxesStyle-> {},
Background-> Automatic,
ImageSize-> 16,
LabelStyle-> {},
PlotRange-> Automatic,
PlotRangePadding-> Automatic,
TicksStyle-> {},
ImageSizeMultipliers-> {1,1}]
```

```
>> Brown
■
```

## Cyan

Cyan  
represents the color cyan in graphics.

```
>> Graphics[{EdgeForm[Black], Cyan,
  Disk[]}, ImageSize->Small]
```



```
>> Cyan // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0, 0, 0]], RGBColor [0, 1, 1],
  RectangleBox [ {0, 0}]}],
$OptionSyntax -> Ignore,
AspectRatio -> Automatic,
Axes -> False, AxesStyle -> {},
Background -> Automatic,
ImageSize -> 16,
LabelStyle -> {},
PlotRange -> Automatic,
PlotRangePadding -> Automatic,
TicksStyle -> {},
ImageSizeMultipliers -> {1, 1}]
```


```
>> Cyan

```


## Gray

Gray  
represents the color gray in graphics.

```
>> Graphics[{EdgeForm[Black], Gray,
  Disk[]}, ImageSize->Small]
```




```
>> Gray // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0, 0]],
  GrayLevel [0.5], RectangleBox [ {0,
    0}]}], $OptionSyntax -> Ignore,
AspectRatio -> Automatic,
Axes -> False, AxesStyle -> {},
Background -> Automatic,
ImageSize -> 16,
LabelStyle -> {},
PlotRange -> Automatic,
PlotRangePadding -> Automatic,
TicksStyle -> {},
ImageSizeMultipliers -> {1, 1}]
```

```
>> Gray

```

## Green

Green  
represents the color green in graphics.

```
>> Graphics[{EdgeForm[Black], Green,
  Disk[]}, ImageSize->Small]
```



```
>> Green // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0,0,0]], RGBColor [0,1,0],
  RectangleBox [ {0,0} ] } ,
  $OptionSyntax-> Ignore,
  AspectRatio-> Automatic,
  Axes-> False, AxesStyle-> { } ,
  Background-> Automatic,
  ImageSize-> 16,
  LabelStyle-> { } ,
  PlotRange-> Automatic,
  PlotRangePadding-> Automatic,
  TicksStyle-> { } ] ,
  ImageSizeMultipliers-> {1,1}]
```


```
>> Green

```

## LightBlue


LightBlue  
represents the color light blue in graphics.

```
>> Graphics[{EdgeForm[Black],
  LightBlue, Disk[]}, ImageSize->
  Small]
```




```
>> LightBlue // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0,
    0,0]], RGBColor [0.87,0.94,
    1], RectangleBox [ {0,0} ] } ,
  $OptionSyntax-> Ignore,
  AspectRatio-> Automatic,
  Axes-> False, AxesStyle-> { } ,
  Background-> Automatic,
  ImageSize-> 16,
  LabelStyle-> { } ,
  PlotRange-> Automatic,
  PlotRangePadding-> Automatic,
  TicksStyle-> { } ] ,
  ImageSizeMultipliers-> {1,1}]
```

```
>> Graphics[{LightBlue, EdgeForm[
  Black], Disk[]}]
```



```
>> Plot[Sin[x], {x, 0, 2 Pi},
  Background -> LightBlue]
```






## LightBrown

LightBrown

represents the color light brown in graphics.

```
>> Graphics[{EdgeForm[Black],  
LightBrown, Disk[]}, ImageSize->  
Small]
```




```
>> LightBrown // ToBoxes  
StyleBox [GraphicsBox [  
  {EdgeForm [RGBColor [0, 0,  
0]], RGBColor [0.94, 0.91, 0.88  
], RectangleBox [ {0, 0} ] },  
$OptionSyntax-> Ignore,  
AspectRatio-> Automatic,  
Axes-> False, AxesStyle-> { } ,  
Background-> Automatic,  
ImageSize-> 16,  
LabelStyle-> { } ,  
PlotRange-> Automatic,  
PlotRangePadding-> Automatic,  
TicksStyle-> { } ],  
ImageSizeMultipliers-> {1, 1}]
```

## LightCyan

LightCyan

represents the color light cyan in graphics.

```
>> Graphics[{EdgeForm[Black],  
LightCyan, Disk[]}, ImageSize->  
Small]
```




```
>> LightCyan // ToBoxes  
StyleBox [GraphicsBox [  
  {EdgeForm [RGBColor [  
0, 0, 0]], RGBColor [0.9, 1.,  
1.], RectangleBox [ {0, 0} ] },  
$OptionSyntax-> Ignore,  
AspectRatio-> Automatic,  
Axes-> False, AxesStyle-> { } ,  
Background-> Automatic,  
ImageSize-> 16,  
LabelStyle-> { } ,  
PlotRange-> Automatic,  
PlotRangePadding-> Automatic,  
TicksStyle-> { } ],  
ImageSizeMultipliers-> {1, 1}]
```

## LightGray

LightGray

represents the color light gray in graphics.

```
>> Graphics[{EdgeForm[Black],  
LightGray, Disk[]}, ImageSize->  
Small]
```




```
>> LightGray // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0,
0,0]], GrayLevel [0.666667,
1.], RectangleBox [ {0,0} ] } ,
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1,1}]
```

```
>> LightGreen // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0,0,
0]], RGBColor [0.88,1.,0.88
], RectangleBox [ {0,0} ] } ,
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1,1}]
```

## LightGreen

**LightGreen**  
represents the color light green in graphics.


```
>> Graphics[{EdgeForm[Black],
LightGreen, Disk[]}, ImageSize->
Small]
```



## LightMagenta

**LightMagenta**  
represents the color light magenta in graphics.

```
>> Graphics[{EdgeForm[Black],
LightMagenta, Disk[]}, ImageSize-
->Small]
```




```
>> LightMagenta // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0,
0]], RGBColor [1., 0.333333,
1.], RectangleBox [ {0, 0} ] },
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1, 1}]
```

```
>> LightOrange // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0,
0, 0]], RGBColor [1, 0.9, 0.8] ,
RectangleBox [ {0, 0} ] } ,
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1, 1}]
```

## LightOrange

LightOrange  
represents the color light orange in graphics.


```
>> Graphics[{EdgeForm[Black],
LightOrange, Disk[]}, ImageSize
->Small]
```



## LightPink

LightPink  
represents the color light pink in graphics.

```
>> Graphics[{EdgeForm[Black],
LightPink, Disk[]}, ImageSize->
Small]
```




```
>> LightPink // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0,
0]], RGBColor [1., 0.925, 0.925
], RectangleBox [ {0, 0} ] },
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1, 1}]
```

```
>> LightPurple // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0,
0]], RGBColor [0.94, 0.88, 0.94
], RectangleBox [ {0, 0} ] },
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1, 1}]
```

## LightPurple

**LightPurple**  
represents the color light purple in graphics.


```
>> Graphics[{EdgeForm[Black],
LightPurple, Disk[]}, ImageSize
->Small]
```



## LightRed

**LightRed**  
represents the color light red in graphics.

```
>> Graphics[{EdgeForm[Black],
LightRed, Disk[]}, ImageSize->
Small]
```




```
>> LightRed // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0,
0]], RGBColor [1., 0.85, 0.85
], RectangleBox [ {0, 0} ] },
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1, 1}]
```

```
>> LightYellow // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0,
0]], RGBColor [1., 1., 0.333333
], RectangleBox [ {0, 0} ] },
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1, 1}]
```

## Light Yellow

LightYellow  
represents the color light yellow in graphics.


```
>> Graphics[{EdgeForm[Black],
LightYellow, Disk[]}, ImageSize
->Small]
```



## Magenta

Magenta  
represents the color magenta in graphics.

```
>> Graphics[{EdgeForm[Black],
Magenta, Disk[]}, ImageSize->
Small]
```



```
>> Magenta // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0,0,0]], RGBColor [1,0,1],
  RectangleBox [ {0,0} ] } ,
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1,1}]
```


```
>> Magenta
```



## Orange

Orange  
represents the color orange in graphics.

```
>> Graphics[{EdgeForm[Black],
Orange, Disk[]}, ImageSize->
Small]
```




```
>> Orange // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0,0,0]], RGBColor [1,0.5,
    0], RectangleBox [ {0,0} ] } ,
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1,1}]
```

## Pink

Pink  
represents the color pink in graphics.

```
>> Graphics[{EdgeForm[Black], Pink,
Disk[]}, ImageSize->Small]
```




```
>> Pink // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
    0,0,0]], RGBColor [1.,0.5,
    0.5], RectangleBox [ {0,0} ] } ,
$OptionSyntax- > Ignore,
AspectRatio- > Automatic,
Axes- > False, AxesStyle- > {} ,
Background- > Automatic,
ImageSize- > 16,
LabelStyle- > {} ,
PlotRange- > Automatic,
PlotRangePadding- > Automatic,
TicksStyle- > {} ] ,
ImageSizeMultipliers- > {1,1}]
```

## Purple

Purple  
represents the color purple in graphics.

```
>> Graphics[{EdgeForm[Black],  
Purple, Disk[]}, ImageSize->  
Small]
```




```
>> Purple // ToBoxes  
StyleBox [GraphicsBox [  
  {EdgeForm [RGBColor [0,  
0,0]], RGBColor [0.5,0,0.5],  
RectangleBox [ {0,0} ] },  
$OptionSyntax-> Ignore,  
AspectRatio-> Automatic,  
Axes-> False, AxesStyle-> { } ,  
Background-> Automatic,  
ImageSize-> 16,  
LabelStyle-> { } ,  
PlotRange-> Automatic,  
PlotRangePadding-> Automatic,  
TicksStyle-> { } ] ,  
ImageSizeMultipliers-> {1,1}]
```

## Red

Red  
represents the color red in graphics.

```
>> Graphics[{EdgeForm[Black], Red,  
Disk[]}, ImageSize->Small]
```




```
>> Red // ToBoxes  
StyleBox [GraphicsBox [  
  {EdgeForm [RGBColor [  
0,0,0]], RGBColor [1,0,0],  
RectangleBox [ {0,0} ] },  
$OptionSyntax-> Ignore,  
AspectRatio-> Automatic,  
Axes-> False, AxesStyle-> { } ,  
Background-> Automatic,  
ImageSize-> 16,  
LabelStyle-> { } ,  
PlotRange-> Automatic,  
PlotRangePadding-> Automatic,  
TicksStyle-> { } ] ,  
ImageSizeMultipliers-> {1,1}]
```

```
>> Red  
■
```

## White

White  
represents the color white in graphics.

```
>> Graphics[{EdgeForm[Black], White  
, Disk[]}, ImageSize->Small]
```



```
>> White // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [0, 0, 0]],
  GrayLevel [1], RectangleBox [ {0,
0}]]}, $OptionSyntax -> Ignore,
AspectRatio -> Automatic,
Axes -> False, AxesStyle -> {},
Background -> Automatic,
ImageSize -> 16,
LabelStyle -> {},
PlotRange -> Automatic,
PlotRangePadding -> Automatic,
TicksStyle -> {}],
ImageSizeMultipliers -> {1, 1}]

>> White
□
```


```
>> Yellow // ToBoxes
StyleBox [GraphicsBox [
  {EdgeForm [RGBColor [
0, 0, 0]], RGBColor [1, 1, 0],
RectangleBox [ {0, 0}]]},
$OptionSyntax -> Ignore,
AspectRatio -> Automatic,
Axes -> False, AxesStyle -> {},
Background -> Automatic,
ImageSize -> 16,
LabelStyle -> {},
PlotRange -> Automatic,
PlotRangePadding -> Automatic,
TicksStyle -> {}],
ImageSizeMultipliers -> {1, 1}]

>> Yellow
■
```

## Yellow

Yellow  
represents the color yellow in graphics.

```
>> Graphics[{EdgeForm[Black],
Yellow, Disk[]}, ImageSize->
Small]
```





## 29. Distance and Similarity Measures

Different measures of distance or similarity for different types of analysis.

## 30. String Distances and Similarity Measures

### Contents

---

DamerauLevenshteinDistance . . 162

EditDistance . . . . . 163

HammingDistance . . 163

---

### DamerauLevenshteinDistance

`DamerauLevenshteinDistance[a, b]`  
returns the Damerau-Levenshtein distance of  $a$  and  $b$ , which is defined as the minimum number of transpositions, insertions, deletions and substitutions needed to transform one into the other. In contrast to `EditDistance`, `DamerauLevenshteinDistance` counts transposition of adjacent items (e.g. “ab” into “ba”) as one operation of change.

```
>> DamerauLevenshteinDistance["kitten", "kitchen"]
2
>> DamerauLevenshteinDistance["abc", "ac"]
1
>> DamerauLevenshteinDistance["abc", "acb"]
1
>> DamerauLevenshteinDistance["azbc", "abxyc"]
3
```

The `IgnoreCase` option makes `DamerauLevenshteinDistance` ignore the case of letters:

```
>> DamerauLevenshteinDistance["time", "Thyme"]
3
>> DamerauLevenshteinDistance["time", "Thyme", IgnoreCase -> True]
2
```

`DamerauLevenshteinDistance` also works on lists:

```
>> DamerauLevenshteinDistance[{1, E, 2, Pi}, {1, E, Pi, 2}]
1
```

### EditDistance

`EditDistance[a, b]`  
returns the Levenshtein distance of  $a$  and  $b$ , which is defined as the minimum number of insertions, deletions and substitutions on the constituents of  $a$  and  $b$  needed to transform one into the other.

```
>> EditDistance["kitten", "kitchen"]
2
>> EditDistance["abc", "ac"]
1
>> EditDistance["abc", "acb"]
2
>> EditDistance["azbc", "abxyc"]
3
```

The `IgnoreCase` option makes `EditDistance` ignore the case of letters:

```
>> EditDistance["time", "Thyme"]
3
>> EditDistance["time", "Thyme", IgnoreCase -> True]
2
```

`EditDistance` also works on lists:

```
>> EditDistance[{1, E, 2, Pi}, {1,
  E, Pi, 2}]
2
```

## HammingDistance

`HammingDistance[ $u$ ,  $v$ ]`  
returns the Hamming distance between  $u$  and  $v$ , i.e. the number of different elements.  $u$  and  $v$  may be lists or strings.

```
>> HammingDistance[{1, 0, 1, 0},
  {1, 0, 0, 1}]
2

>> HammingDistance["time", "dime"]
1

>> HammingDistance["TIME", "dime",
  IgnoreCase -> True]
1
```

## 31. Graphics, Drawing, and Images


Functions like `Plot` and `ListPlot` can be used to draw graphs of functions and data.

Graphics is implemented as a collection of *graphics primitives*. Primitives are objects like `Point`, `Line`, and `Polygon` and become elements of a *graphics object*.

A graphics object can have directives as well such as `RGBColor`, and `Thickness`.


There are several kinds of graphics objects; each kind has a head which identifies its type.

```
>> ListPlot[ Table[Prime[n], {n, 20} ]]
```



```
>> Head[%]  
Graphics
```

```
>> Graphics3D[Sphere[]]
```



```
>> Head[%]  
Graphics3D
```

```
>>
```

## 32. Three-Dimensional Graphics

### Contents

---


Cuboid . . . . .	165	Cylinder . . . . .	166	Sphere . . . . .	167
		Graphics3D . . . . .	167		

---


### Cuboid

`Cuboid[{xmin, ymin, zmin}]`  
is a unit cube.  
`Cuboid[{xmin, ymin, zmin}, {xmax,  
ymax, zmax}]`  
represents a cuboid extending from  
{*xmin*, *ymin*, *zmin*} to {*xmax*, *ymax*, *zmax*}.

```
>> Graphics3D[Cuboid[{0, 0, 1}]]
```




```
>> Graphics3D[{Red, Cuboid[{0, 0,  
0}, {1, 1, 0.5}], Blue, Cuboid  
[{0.25, 0.25, 0.5}, {0.75, 0.75,  
1}]]}
```




### Cylinder

`Cylinder[{{x1, y1, z1}, {x2, y2, z2}}]`  
represents a cylinder of radius 1.  
`Cylinder[{{x1, y1, z1}, {x2, y2, z2}},  
r]`  
is a cylinder of radius *r* starting at (*x1*, *y1*,  
*z1*) and ending at (*x2*, *y2*, *z2*).  
`Cylinder[{{x1, y1, z1}, {x2, y2, z2},  
... }, r]`  
is a collection cylinders of radius *r*


```
>> Graphics3D[Cylinder[{{0, 0, 0},
{1, 1, 1}}, 1]]
```



```
>> Graphics3D[Polygon[{{0,0,0},
{0,1,1}, {1,0,0}}]]
```



```
>> Graphics3D[{Yellow, Cylinder
[{{-1, 0, 0}, {1, 0, 0}, {0, 0,
Sqrt[3]}, {1, 1, Sqrt[3]}}, 1]]]
```



In TeXForm, Graphics3D creates Asymptote figures:

## Graphics3D

`Graphics3D[primitives, options]`  
 represents a three-dimensional graphic.  
 See also the Section “Plotting” for a list of Plot options.

```
>> Graphics3D[Sphere[]] // TeXForm

\begin{asy}
import three;
import solids;
size(6.6667cm, 6.6667cm);
currentprojection=perspective(2.6,-4.8,4.0);
currentlight=light(rgb(0.5,0.5,1),
specular=red, (2,0,2), (2,2,2), (0,2,2));
draw(surface(sphere((0, 0, 0), 1)),
rgb(1,1,1));
draw((( -1,-1,-1)-(1,-1,-1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( -1,-1,-1)-(1,1,-1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( -1,-1,1)-(1,-1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( -1,1,1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( -1,-1,-1)-(-1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( 1,-1,-1)-(1,1,-1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( -1,-1,1)-(-1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( 1,-1,1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( -1,1,1)-(-1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
draw((( 1,1,1)-(1,1,1)), rgb(0.4, 0.4,
0.4)+linewidth(1));
\end{asy}
```


## Sphere

`Sphere[{x, y, z}]`  
is a sphere of radius 1 centered at the point {x, y, z}.


`Sphere[{x, y, z}, r]`  
is a sphere of radius  $r$  centered at the point {x, y, z}.

`Sphere[{ {x1, y1, z1}, {x2, y2, z2}, ... }, r]`  
is a collection spheres of radius  $r$  centered at the points {x1, y2, z2}, {x2, y2, z2}, ...

```
>> Graphics3D[Sphere[{0, 0, 0}, 1]]
```



```
>> Graphics3D[{Yellow, Sphere[{ {-1, 0, 0}, {1, 0, 0}, {0, 0, Sqrt[3.]}}, 1]]}
```



## 33. Image[] and image related functions.

Note that you (currently) need scikit-image installed in order for this module to work.

### Contents

---

Binarize . . . . .	168	ImageAdd . . . . .	171	ImageRotate . . . . .	174
BinaryImageQ . . . . .	168	ImageAdjust . . . . .	171	ImageSubtract . . . . .	174
Blur . . . . .	169	ImageAspectRatio . . . . .	171	ImageTake . . . . .	174
BoxMatrix . . . . .	169	Image . . . . .	171	ImageType . . . . .	174
Closing . . . . .	169	ImageChannels . . . . .	171	MaxFilter . . . . .	174
ColorCombine . . . . .	169	ImageColorSpace . . . . .	171	MedianFilter . . . . .	174
ColorQuantize . . . . .	169	ImageConvolve . . . . .	172	MinFilter . . . . .	175
ColorSeparate . . . . .	169	ImageData . . . . .	172	Opening . . . . .	175
Colorize . . . . .	169	ImageDimensions . . . . .	172	PixelValue . . . . .	175
DiamondMatrix . . . . .	170	ImageImport . . . . .	172	PixelValuePositions . . . . .	175
Dilation . . . . .	170	ImageMultiply . . . . .	172	RandomImage . . . . .	175
DiskMatrix . . . . .	170	ImagePartition . . . . .	173	Sharpen . . . . .	175
EdgeDetect . . . . .	170	ImageQ . . . . .	173	TextRecognize . . . . .	176
Erosion . . . . .	170	ImageReflect . . . . .	173	Threshold . . . . .	176
GaussianFilter . . . . .	170	ImageResize . . . . .	173	WordCloud . . . . .	176

---

### Binarize

```
Binarize[image]
    gives a binarized version of image, in
    which each pixel is either 0 or 1.
Binarize[image, t]
    map values  $x > t$  to 1, and values  $x \leq t$  to
    0.
Binarize[image, {t1, t2}]
    map  $t1 < x < t2$  to 1, and all other values
    to 0.

>> img = Import["ExampleData/lena.
tif"];

>> Binarize[img]
-Image-

>> Binarize[img, 0.7]
-Image-

>> Binarize[img, {0.2, 0.6}]
-Image-
```

### BinaryImageQ

```
BinaryImageQ[$image]
    returns True if the pixels of $image are bi-
    nary bit values, and False otherwise.

>> img = Import["ExampleData/lena.
tif"];

>> BinaryImageQ[img]
False

>> BinaryImageQ[Binarize[img]]
True
```

### Blur

```
Blur[image]
    gives a blurred version of image.
Blur[image, r]
    blurs image with a kernel of size r.
```



```
>> lena = Import["ExampleData/lena.tif"];
```

```
>> Blur[lena]
-Image-
```

```
>> Blur[lena, 5]
-Image-
```

## BoxMatrix

**BoxMatrix**[\$s]  
Gives a box shaped kernel of size  $2s + 1$ .

```
>> BoxMatrix[3]
{{1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}, {1,1,1,1,1,1,1}}
```

## Closing

**Closing**[*image*, *ker*]  
Gives the morphological closing of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/Einstein.jpg"];
```

```
>> Closing[ein, 2.5]
-Image-
```

## ColorCombine

**ColorCombine**[*channels*, *colorspace*]  
Gives an image with *colorspace* and the respective components described by the given channels.

```
>> ColorCombine[{{1, 0}, {0, 0.75}}, {{0, 1}, {0, 0.25}}, {{0, 0}, {1, 0.5}}, "RGB"]
-Image-
```

## ColorQuantize

**ColorQuantize**[*image*, *n*]  
gives a version of *image* using only *n* colors.

```
>> img = Import["ExampleData/lena.tif"];
```

```
>> ColorQuantize[img, 6]
-Image-
```

## ColorSeparate

**ColorSeparate**[*image*]  
Gives each channel of *image* as a separate grayscale image.

## Colorize

**Colorize**[*values*]  
returns an image where each number in the rectangular matrix *values* is a pixel and each occurrence of the same number is displayed in the same unique color, which is different from the colors of all non-identical numbers.

**Colorize**[*image*]  
gives a colorized version of *image*.

```
>> Colorize[{{1.3, 2.1, 1.5}, {1.3, 1.3, 2.1}, {1.3, 2.1, 1.5}}]
-Image-
```

```
>> Colorize[{{1, 2}, {2, 2}, {2, 3}}, ColorFunction -> (Blend[{White, Blue}, #]&)]
-Image-
```

## DiamondMatrix

**DiamondMatrix**[\$s]  
Gives a diamond shaped kernel of size  $2s + 1$ .

```
>> DiamondMatrix[3]
{{0,0,0,1,0,0,0}, {0,0,1,1,1,
 0,0}, {0,1,1,1,1,0}, {1,1,1,
 1,1,1,1}, {0,1,1,1,1,0}, {0,
 0,1,1,1,0,0}, {0,0,0,1,0,0,0}}
```

## Dilation

`Dilation[image, ker]`  
Gives the morphological dilation of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/
Einstein.jpg"];

>> Dilation[ein, 2.5]
-Image-
```

## DiskMatrix

`DiskMatrix[$s]`  
Gives a disk shaped kernel of size  $2s + 1$ .

```
>> DiskMatrix[3]
{{0,0,1,1,1,0,0}, {0,1,1,1,1,
 1,0}, {1,1,1,1,1,1}, {1,1,1,
 1,1,1,1}, {1,1,1,1,1,1}, {0,
 1,1,1,1,0}, {0,0,1,1,1,0,0}}
```

## EdgeDetect

`EdgeDetect[image]`  
returns an image showing the edges in *image*.

```
>> lena = Import["ExampleData/lena.
tif"];

>> EdgeDetect[lena]
-Image-

>> EdgeDetect[lena, 5]
-Image-

>> EdgeDetect[lena, 4, 0.5]
-Image-
```

## Erosion

`Erosion[image, ker]`  
Gives the morphological erosion of *image* with respect to structuring element *ker*.

```
>> ein = Import["ExampleData/
Einstein.jpg"];

>> Erosion[ein, 2.5]
-Image-
```

## GaussianFilter

`GaussianFilter[image, r]`  
blurs *image* using a Gaussian blur filter of radius *r*.

```
>> lena = Import["ExampleData/lena.
tif"];

>> GaussianFilter[lena, 2.5]
-Image-
```

## ImageAdd

`ImageAdd[image, expr_1, expr_2, ...]`  
adds all *expr\_i* to *image* where each *expr\_i* must be an image or a real number.

```
>> i = Image[{{0, 0.5, 0.2, 0.1,
 0.9}, {1.0, 0.1, 0.3, 0.8,
 0.6}}];

>> ImageAdd[i, 0.5]
-Image-

>> ImageAdd[i, i]
-Image-

>> ein = Import["ExampleData/
Einstein.jpg"];

>> noise = RandomImage[{-0.1, 0.1},
  ImageDimensions[ein]];

>> ImageAdd[noise, ein]
-Image-
```

```
>> lena = Import["ExampleData/lena.
tif"];

>> noise = RandomImage[{-0.2, 0.2},
  ImageDimensions[lena],
  ColorSpace -> "RGB"];

>> ImageAdd[noise, lena]
-Image-
```

## ImageAdjust

`ImageAdjust[image]`  
adjusts the levels in *image*.

`ImageAdjust[image, c]`  
adjusts the contrast in *image* by *c*.

`ImageAdjust[image, {c, b}]`  
adjusts the contrast *c*, and brightness *b* in *image*.

`ImageAdjust[image, {c, b, g}]`  
adjusts the contrast *c*, brightness *b*, and gamma *g* in *image*.

```
>> lena = Import["ExampleData/lena.
tif"];

>> ImageAdjust[lena]
-Image-
```

## ImageAspectRatio

`ImageAspectRatio[image]`  
gives the aspect ratio of *image*.

```
>> img = Import["ExampleData/lena.
tif"];

>> ImageAspectRatio[img]
1

>> ImageAspectRatio[Image[{{0, 1},
{1, 0}, {1, 1}}]]
 $\frac{3}{2}$ 
```

## Image

### ImageChannels

`ImageChannels[image]`  
gives the number of channels in *image*.

```
>> ImageChannels[Image[{{0, 1}, {1,
0}}]]
1

>> img = Import["ExampleData/lena.
tif"];

>> ImageChannels[img]
3
```

### ImageColorSpace

`ImageColorSpace[image]`  
gives *image*'s color space, e.g. "RGB" or "CMYK".

```
>> img = Import["ExampleData/lena.
tif"];

>> ImageColorSpace[img]
RGB
```

### ImageConvolve

`ImageConvolve[image, kernel]`  
Computes the convolution of *image* using *kernel*.

```
>> img = Import["ExampleData/lena.
tif"];

>> ImageConvolve[img, DiamondMatrix
[5] / 61]
-Image-

>> ImageConvolve[img, DiskMatrix[5]
/ 97]
-Image-
```

```
>> ImageConvolve[img, BoxMatrix[5]
/ 121]
-Image-
```

## ImageData

`ImageData[image]`  
gives a list of all color values of *image* as a matrix.

`ImageData[image, stype]`  
gives a list of color values in type *stype*.

```
>> img = Image[{{0.2, 0.4}, {0.9,
0.6}, {0.5, 0.8}}];

>> ImageData[img]
{{0.2, 0.4}, {0.9, 0.6}, {0.5, 0.8}}

>> ImageData[img, "Byte"]
{{51, 102}, {229, 153}, {127, 204}}

>> ImageData[Image[{{0, 1}, {1, 0},
{1, 1}}], "Bit"]
{{0, 1}, {1, 0}, {1, 1}}
```

## ImageDimensions

`ImageDimensions[image]`  
Returns the dimensions of *image* in pixels.

```
>> lena = Import["ExampleData/lena.
tif"];

>> ImageDimensions[lena]
{512, 512}

>> ImageDimensions[RandomImage[1,
{50, 70}]]
{50, 70}
```

## ImageImport

```
>> Import["ExampleData/Einstein.jpg"]
-Image-
```

```
>> Import["ExampleData/MadTeaParty.
gif"]
-Image-

>> Import["ExampleData/moon.tif"]
-Image-
```

## ImageMultiply

`ImageMultiply[image, expr_1, expr_2, ...]`  
multiplies all *expr\_i* with *image* where each *expr\_i* must be an image or a real number.

```
>> i = Image[{{0, 0.5, 0.2, 0.1,
0.9}, {1.0, 0.1, 0.3, 0.8,
0.6}}];

>> ImageMultiply[i, 0.2]
-Image-

>> ImageMultiply[i, i]
-Image-

>> ein = Import["ExampleData/
Einstein.jpg"];

>> noise = RandomImage[{0.7, 1.3},
ImageDimensions[ein]];

>> ImageMultiply[noise, ein]
-Image-
```

## ImagePartition

`ImagePartition[image, s]`  
Partitions an image into an array of *s* x *s* pixel subimages.

`ImagePartition[image, {w, h}]`  
Partitions an image into an array of *w* x *h* pixel subimages.

```
>> lena = Import["ExampleData/lena.
tif"];

>> ImageDimensions[lena]
{512, 512}
```

```
>> ImagePartition[lena, 256]
{{-Image-, -Image-},
 {-Image-, -Image-}}
>> ImagePartition[lena, {512, 128}]
{{-Image-}, {-Image-},
 {-Image-}, {-Image-}}
```

## ImageQ

ImageQ[Image[\$pixels]]  
returns True if \$pixels has dimensions from which an Image can be constructed, and False otherwise.

```
>> ImageQ[Image[{{0, 1}, {1, 0}}]]
True
>> ImageQ[Image[{{{0, 0, 0}, {0, 1, 0}}, {{0, 1, 0}, {0, 1, 1}}]]
True
>> ImageQ[Image[{{{0, 0, 0}, {0, 1}}, {{0, 1, 0}, {0, 1, 1}}]]
False
>> ImageQ[Image[{1, 0, 1}]]
False
>> ImageQ["abc"]
False
```

## ImageReflect

ImageReflect[image]  
Flips image top to bottom.  
ImageReflect[image, side]  
Flips image so that side is interchanged with its opposite.  
ImageReflect[image, side\_1 -> side\_2]  
Flips image so that side\_1 is interchanged with side\_2.

```
>> ein = Import["ExampleData/Einstein.jpg"];
>> ImageReflect[ein]
-Image-
```

```
>> ImageReflect[ein, Left]
-Image-
>> ImageReflect[ein, Left -> Top]
-Image-
```

## ImageResize

ImageResize[image, width]  
ImageResize[image, {width, height}]

```
>> ein = Import["ExampleData/Einstein.jpg"];
>> ImageDimensions[ein]
{615, 768}
>> ImageResize[ein, {400, 600}]
-Image-
>> ImageResize[ein, 256]
-Image-
>> ImageDimensions[%]
{256, 320}
The default sampling method is Bicubic
>> ImageResize[ein, 256, Resampling -> "Bicubic"]
-Image-
>> ImageResize[ein, 256, Resampling -> "Nearest"]
-Image-
>> ImageResize[ein, 256, Resampling -> "Gaussian"]
-Image-
```

## ImageRotate

ImageRotate[image]  
Rotates image 90 degrees counterclockwise.  
ImageRotate[image, theta]  
Rotates image by a given angle theta

```
>> ein = Import["ExampleData/
Einstein.jpg"];

>> ImageRotate[ein]
–Image–

>> ImageRotate[ein, 45 Degree]
–Image–

>> ImageRotate[ein, Pi / 2]
–Image–
```

## ImageSubtract

`ImageSubtract[image, expr_1, expr_2, ...]`  
 subtracts all *expr\_i* from *image* where each *expr\_i* must be an image or a real number.

```
>> i = Image[{{0, 0.5, 0.2, 0.1,
0.9}, {1.0, 0.1, 0.3, 0.8,
0.6}}];

>> ImageSubtract[i, 0.2]
–Image–

>> ImageSubtract[i, i]
–Image–
```

## ImageTake

`ImageTake[image, n]`  
 gives the first *n* rows of *image*.  
`ImageTake[image, -n]`  
 gives the last *n* rows of *image*.  
`ImageTake[image, {r1, r2}]`  
 gives rows *r1*, ..., *r2* of *image*.  
`ImageTake[image, {r1, r2}, {c1, c2}]`  
 gives a cropped version of *image*.

## ImageType

`ImageType[image]`  
 gives the interval storage type of *image*,  
 e.g. "Real", "Bit32", or "Bit".

```
>> img = Import["ExampleData/lena.
tif"];

>> ImageType[img]
Byte

>> ImageType[Image[{{0, 1}, {1,
0}}]]
Real

>> ImageType[Binarize[img]]
Bit
```

## MaxFilter

`MaxFilter[image, r]`  
 gives *image* with a maximum filter of radius *r* applied on it. This always picks the largest value in the filter's area.

```
>> lena = Import["ExampleData/lena.
tif"];

>> MaxFilter[lena, 5]
–Image–
```

## MedianFilter

`MedianFilter[image, r]`  
 gives *image* with a median filter of radius *r* applied on it. This always picks the median value in the filter's area.

```
>> lena = Import["ExampleData/lena.
tif"];

>> MedianFilter[lena, 5]
–Image–
```

## MinFilter

`MinFilter[image, r]`  
 gives *image* with a minimum filter of radius *r* applied on it. This always picks the smallest value in the filter's area.

```
>> lena = Import["ExampleData/lena.
tif"];
```

```
>> MinFilter[lena, 5]
      -Image-
```

## Opening

```
Opening[image, ker]
  Gives the morphological opening of image with respect to structuring element ker.
```

```
>> ein = Import["ExampleData/
      Einstein.jpg"];

>> Opening[ein, 2.5]
      -Image-
```

## PixelValue

```
PixelValue[image, {x, y}]
  gives the value of the pixel at position {x, y} in image.
```

```
>> lena = Import["ExampleData/lena.
      tif"];

>> PixelValue[lena, {1, 1}]
      {0.321569, 0.0862745, 0.223529}
```

## PixelValuePositions

```
PixelValuePositions[image, val]
  gives the positions of all pixels in image that have value val.
```

```
>> PixelValuePositions[Image[{{0,
      1}, {1, 0}, {1, 1}}, 1]
      {{1,1}, {1,2}, {2,1}, {2,3}}

>> PixelValuePositions[Image[{{0.2,
      0.4}, {0.9, 0.6}, {0.3, 0.8}},
      0.5, 0.15]
      {{2,2}, {2,3}}

>> img = Import["ExampleData/lena.
      tif"];
```

```
>> PixelValuePositions[img, 3 /
      255, 0.5 / 255]
      {{180,192,2}, {181,192,2},
      {181,193,2}, {188,204,2},
      {265,314,2}, {364,77,2}, {365,
      72,2}, {365,73,2}, {365,77,
      2}, {366,70,2}, {367,65,2}}

>> PixelValue[img, {180, 192}]
      {0.25098, 0.0117647, 0.215686}
```

## RandomImage

```
RandomImage[max]
  creates an image of random pixels with
  values 0 to max.
RandomImage[{min, max}]
  creates an image of random pixels with
  values min to max.
RandomImage[... , size]
  creates an image of the given size.
```

```
>> RandomImage[1, {100, 100}]
      -Image-
```

## Sharpen

```
Sharpen[image]
  gives a sharpened version of image.
Sharpen[image, r]
  sharpens image with a kernel of size r.
```

```
>> lena = Import["ExampleData/lena.
      tif"];

>> Sharpen[lena]
      -Image-

>> Sharpen[lena, 5]
      -Image-
```

## TextRecognize

`TextRecognize[{image}]`  
Recognizes text in *image* and returns it as string.

## Threshold

`Threshold[image]`  
gives a value suitable for binarizing *image*.

The option "Method" may be "Cluster" (use Otsu's threshold), "Median", or "Mean".

```
>> img = Import["ExampleData/lena.tif"];

>> Threshold[img]
0.456739

>> Binarize[img, %]
-Image-

>> Threshold[img, Method -> "Mean"]
0.486458

>> Threshold[img, Method -> "Median"]
0.504726
```

## WordCloud

`WordCloud[{word1, word2, ...}]`  
Gives a word cloud with the given list of words.

`WordCloud[{weight1 -> word1, weight2 -> word2, ...}]`  
Gives a word cloud with the words weighted using the given weights.

`WordCloud[{weight1, weight2, ...} -> {word1, word2, ...}]`  
Also gives a word cloud with the words weighted using the given weights.

`WordCloud[{word1, weight1}, {word2, weight2}, ...}]`  
Gives a word cloud with the words weighted using the given weights.

```
>> WordCloud[StringSplit[Import["ExampleData/EinsteinSzilLetter.txt"]]]
-Image-

>> WordCloud[Range[50] -> ToString /@ Range[50]]
-Image-
```



## 34. Plotting

### Contents

BarChart . . . . .	178	ListLinePlot . . . . .	180	Plot . . . . .	184
ColorData . . . . .	178	ListPlot . . . . .	180	Plot3D . . . . .	185
DensityPlot . . . . .	179	ParametricPlot . . . . .	181	PolarPlot . . . . .	185
Histogram . . . . .	180	PieChart . . . . .	183		

### BarChart

`BarChart[{b1, b2 ...}]`  
makes a bar chart with lengths *b1*, *b2*, ....

Drawing options include - Charting:


- Mesh
- PlotRange
- ChartLabels
- ChartLegends
- ChartStyle

BarChart specific:


- Axes (default {False, True})
- AspectRatio: (default 1 / GoldenRatio)

A bar chart of a list of heights:

>> `BarChart[{1, 4, 2}]`



>> `BarChart[{1, 4, 2}, ChartStyle -> {Red, Green, Blue}]`



>> `BarChart[{{1, 2, 3}, {2, 3, 4}}]`






Chart several datasets with categorical labels:

```
>> BarChart[{{1, 2, 3}, {2, 3, 4}},
  ChartLabels -> {"a", "b", "c"}]
```



```
>> BarChart[{{1, 5}, {3, 4}},
  ChartStyle -> {{EdgeForm[Thin],
  White}, {EdgeForm[Thick], White
  }}]
```



## ColorData


`ColorData["name"]`  
returns a color function with the given *name*.

Define a user-defined color function:

```
>> Unprotect[ColorData]; ColorData
["test"] := ColorDataFunction["
test", "Gradients", {0, 1},
Blend[{Red, Green, Blue}, #1
&]; Protect[ColorData]
```

Compare it to the default color function,  
`LakeColors`:


```
>> {DensityPlot[x + y, {x, -1, 1},
{y, -1, 1}], DensityPlot[x + y,
{x, -1, 1}, {y, -1, 1},
ColorFunction->"test"]}
```




## DensityPlot

`DensityPlot[f, {x, xmin, xmax}, {y, ymin, ymax}]`  
plots a density plot of  $f$  with  $x$  ranging from  $xmin$  to  $xmax$  and  $y$  ranging from  $ymin$  to  $ymax$ .



```
>> DensityPlot[x ^ 2 + 1 / y, {x,
-1, 1}, {y, 1, 4}]
```




```
>> DensityPlot[1 / x, {x, 0, 1}, {y
, 0, 1}]
```




```
>> DensityPlot[Sqrt[x * y], {x, -1,
1}, {y, -1, 1}]
```



```
>> DensityPlot[1/(x^2 + y^2 + 1), {
x, -1, 1}, {y, -2,2}, Mesh->Full
]
```




```
>> DensityPlot[x^2 y, {x, -1, 1}, {
y, -1, 1}, Mesh->All]
```




## Histogram

```
Histogram[{x1, x2 ...}]
plots a histogram using the values x1, x2,
....
```

```
>> Histogram[{3, 8, 10, 100, 1000,
500, 300, 200, 10, 20, 200, 100,
200, 300, 500}]
```



```
>> Histogram[{{1, 2, 10, 5, 50,
20}, {90, 100, 101, 120, 80}}]
```




## ListLinePlot


```
ListLinePlot[{y_1, y_2, ...}]
plots a line through a list of y-values, as-
suming integer x-values 1, 2, 3, ...
ListLinePlot[{x_1, y_1}, {x_2, y_2},
...}]
plots a line through a list of x, y pairs.
ListLinePlot[{list_1, list_2, ...}]
plots several lines.
```

ListPlot accepts a superset of the Graphics options.

```
>> ListLinePlot[Table[{n, n ^ 0.5},
{n, 10}]]
```



```
>> ListLinePlot[{{-2, -1}, {-1,
-1}}]
```




## ListPlot

```
ListPlot[{y_1, y_2, ...}]
plots a list of y-values, assuming integer
x-values 1, 2, 3, ...
ListPlot[{x_1, y_1}, {x_2, y_2},
...}]
plots a list of x, y pairs.
ListPlot[{list_1, list_2, ...}]
plots several lists of points.
```

ListPlot accepts a superset of the Graphics options.


```
>> ListPlot[Table[n ^ 2, {n, 10}]]
```




## ParametricPlot

`ParametricPlot[{f_x, f_y}, {u, u_min, u_max}]`  
 plots a parametric function  $f$  with the parameter  $u$  ranging from  $u_{min}$  to  $u_{max}$ .  
`ParametricPlot[{f_x, f_y}, {g_x, g_y}, ..., {u, u_min, u_max}]`  
 plots several parametric functions  $f, g, \dots$   
`ParametricPlot[{f_x, f_y}, {u, u_min, u_max}, {v, v_min, v_max}]`  
 plots a parametric area.  
`ParametricPlot[{f_x, f_y}, {g_x, g_y}, ..., {u, u_min, u_max}, {v, v_min, v_max}]`  
 plots several parametric areas.


```
>> ParametricPlot[{Sin[u], Cos[3 u]}, {u, 0, 2 Pi}]
```



```
>> ParametricPlot[{Cos[u] / u, Sin[u] / u}, {u, 0, 50}, PlotRange -> 0.5]
```



```
>> ParametricPlot[{Sin[u], Cos[u]}, {0.6 Sin[u], 0.6 Cos[u]}, {0.2 Sin[u], 0.2 Cos[u]}, {u, 0, 2 Pi}, PlotRange -> 1, AspectRatio -> 1]
```



## PieChart

`PieChart[{a1, a2, ...}]`  
 draws a pie chart with sector angles proportional to  $a1, a2, \dots$

Drawing options include - Charting:


- Mesh
- PlotRange
- ChartLabels
- ChartLegends
- ChartStyle

PieChart specific:

- Axes (default: False, False)
- AspectRatio (default 1)
- SectorOrigin: (default {Automatic, 0})
- SectorSpacing" (default Automatic)


A hypothetical comparison between types of pets owned:

```
>> PieChart[{30, 20, 10},
ChartLabels -> {Dogs, Cats, Fish
}]
```




A doughnut chart for a list of values:

```
>> PieChart[{8, 16, 2},
SectorOrigin -> {Automatic,
1.5}]
```




A Pie chart with multiple datasets:

```
>> PieChart[{{10, 20, 30}, {15, 22,
30}}]
```




Same as the above, but without gaps between the groups of data:

```
>> PieChart[{{10, 20, 30}, {15, 22,
30}}, SectorSpacing -> None]
```




The doughnut chart above with labels on each of the 3 pieces:

```
>> PieChart[{{10, 20, 30}, {15, 22,
30}}, ChartLabels -> {A, B, C}]
```



Negative values are removed, the data below is the same as {1, 3}:


```
>> PieChart[{1, -1, 3}]
```




## Plot

`Plot[f, {x, xmin, xmax}]`  
plots  $f$  with  $x$  ranging from  $xmin$  to  $xmax$ .  
`Plot[{f1, f2, ...}, {x, xmin, xmax}]`  
plots several functions  $f1, f2, \dots$


```
>> Plot[{Sin[x], Cos[x], x / 3}, {x, -Pi, Pi}]
```




```
>> Plot[Sin[x], {x, 0, 4 Pi},  
PlotRange->{{0, 4 Pi}, {0, 1.5}}]
```




```
>> Plot[Tan[x], {x, -6, 6}, Mesh->  
Full]
```




```
>> Plot[x^2, {x, -1, 1},  
MaxRecursion->5, Mesh->All]
```



```
>> Plot[Log[x], {x, 0, 5},  
MaxRecursion->0]
```




```
>> Plot[Tan[x], {x, 0, 6}, Mesh->  
All, PlotRange->{{-1, 5}, {0, 15}},  
MaxRecursion->10]
```



A constant function:

```
>> Plot[3, {x, 0, 1}]
```



## Plot3D


`Plot3D[f, {x, xmin, xmax}, {y, ymin, ymax}]`

creates a three-dimensional plot of  $f$  with  $x$  ranging from  $xmin$  to  $xmax$  and  $y$  ranging from  $ymin$  to  $ymax$ .


Plot3D has the same options as Graphics3D, in particular:

- Mesh
- PlotPoints
- MaxRecursion


```
>> Plot3D[x ^ 2 + 1 / y, {x, -1, 1}, {y, 1, 4}]
```




```
>> Plot3D[Sin[y + Sin[3 x]], {x, -2, 2}, {y, -2, 2}, PlotPoints -> 20]
```



```
>> Plot3D[x / (x ^ 2 + y ^ 2 + 1), {x, -2, 2}, {y, -2, 2}, Mesh->None]
```




```
>> Plot3D[Sin[x y] / (x y), {x, -3, 3}, {y, -3, 3}, Mesh->All]
```






```
>> Plot3D[Log[x + y^2], {x, -1, 1},
  {y, -1, 1}]
```



```
>> PolarPlot[Abs[Cos[5t]], {t, 0,
  Pi}]
```




## PolarPlot

`PolarPlot[r, {t, t_min, t_max}]`  
creates a polar plot of curve with radius  $r$  as a function of angle  $t$  ranging from  $t_{min}$  to  $t_{max}$ .

In a Polar Plot, a polar coordinate system is used. A polar coordinate system is a two-dimensional coordinate system in which each point on a plane is determined by a distance from a reference point and an angle from a reference direction.

Here is a 5-blade propeller, or maybe a flower, using `PolarPlot`:

```
>> PolarPlot[Cos[5t], {t, 0, Pi}]
```




The number of blades and be change by adjusting the  $t$  multiplier.

A slight change adding `Abs` turns this a clump of grass:


Coils around a ring:

```
>> PolarPlot[{1, 1 + Sin[20 t] /
  5}, {t, 0, 2 Pi}]
```



A spring having 16 turns:

```
>> PolarPlot[Sqrt[t], {t, 0, 16 Pi
  }]
```



# 35. Splines

Splines are used both in graphics and computations.

## Contents

BernsteinBasis . . . . .	186	BezierCurve . . . . .	186	BezierFunction . . . . .	187
--------------------------	-----	-----------------------	-----	--------------------------	-----

## BernsteinBasis

`BernsteinBasis[d,n,x]`  
returns the  $n$ th Bernstein basis of degree  $d$  at  $x$ .

A Bernstein polynomial is a polynomial that is a linear combination of Bernstein basis polynomials.

With the advent of computer graphics, Bernstein polynomials, restricted to the interval  $[0, 1]$ , became important in the form of Bézier curves.

`BernsteinBasis[d,n,x]` equals `Binomial[d, n] x^n (1-x)^(d-n)` in the interval  $[0, 1]$  and zero elsewhere.

```
>> BernsteinBasis[4, 3, 0.5]
0.25
```

## BezierCurve

`BezierCurve[{pt_1, pt_2 ...}]`  
represents a Bézier curve with control points  $p_i$ .

Option:

- `SplineDegree->d` specifies that the underlying polynomial basis should have maximal degree  $d$ .


Set up some points...

```
>> pts = {{0, 0}, {1, 1}, {2, -1},
{3, 0}, {5, 2}, {6, -1}, {7,
3}};
```

=

A composite Bézier curve and its control points:

```
>> Graphics[{BezierCurve[pts],
Green, Line[pts], Red, Point[pts
]}]
```



=

## BezierFunction

`BezierFunction[{pt_1, pt_2, ...}]`  
returns a Bézier function for the curve defined by points  $pt_i$ . The embedding dimension for the curve represented by `BezierFunction[{pt_1, pt_2, ...}]` is given by the length of the lists  $pt_i$ .

```
>> f = BezierFunction[{{0, 0}, {1,
1}, {2, 0}, {3, 2}}];
```


=

```
>> f[.5]
{1.5, 0.625}
```

=

Plotting the Bézier Function across a Bézier curve:

```
>> Module[{p={{0, 0},{1, 1},{2,
-1},{4, 0}}}, Graphics[{
BezierCurve[p], Red, Point[Table
[BezierFunction[p][x], {x, 0, 1,
0.1}]]}]}
```



## **36. Input/Output, Files, and Filesystem**

## 37. File and Stream Operations

### Contents

BinaryRead . . . . .	189	\$Input . . . . .	192	ReadList . . . . .	195
BinaryWrite . . . . .	190	\$InputFileName . . . . .	192	Record . . . . .	195
Byte . . . . .	190	InputStream . . . . .	192	SetStreamPosition . . . . .	195
Character . . . . .	190	Number . . . . .	192	Skip . . . . .	196
Close . . . . .	191	OpenAppend . . . . .	192	StreamPosition . . . . .	196
EndOfFile . . . . .	191	OpenRead . . . . .	192	Streams . . . . .	196
Expression . . . . .	191	OpenWrite . . . . .	192	StringToStream . . . . .	196
FilePrint . . . . .	191	OutputStream . . . . .	193	Word . . . . .	196
Find . . . . .	191	Put (>>) . . . . .	193	Write . . . . .	197
Get (<<) . . . . .	192	PutAppend (>>>) . . . . .	194	WriteString . . . . .	197
		Read . . . . .	195		

### BinaryRead

`BinaryRead[stream]`  
reads one byte from the stream as an integer from 0 to 255.

`BinaryRead[stream, type]`  
reads one object of specified type from the stream.

`BinaryRead[stream, {type1, type2, ...}]`  
reads a sequence of objects of specified types.

```
>> strm = OpenWrite[BinaryFormat ->
    True]
    OutputStream [
        /tmp/tmpncbldyy2,153]
>> BinaryWrite[strm, {97, 98, 99}]
    OutputStream [
        /tmp/tmpncbldyy2,153]
>> Close[strm]
    /tmp/tmpncbldyy2
>> strm = OpenRead[%, BinaryFormat
    -> True]
    InputStream [
        /tmp/tmpncbldyy2,154]
```

```
>> BinaryRead[strm, {"Character8",
    "Character8", "Character8"}]
    {a,b,c}
>> Close[strm];
```

### BinaryWrite

`BinaryWrite[channel, b]`  
writes a single byte given as an integer from 0 to 255.

`BinaryWrite[channel, {b1, b2, ...}]`  
writes a sequence of byte.

`BinaryWrite[channel, 'string']`  
writes the raw characters in a string.

`BinaryWrite[channel, x, type]`  
writes *x* as the specified type.

`BinaryWrite[channel, {x1, x2, ...}, type]`  
writes a sequence of objects as the specified type.

`BinaryWrite[channel, {x1, x2, ...}, {type1, type2, ...}]`  
writes a sequence of objects using a sequence of specified types.

```
>> strm = OpenWrite[BinaryFormat ->
  True]
  OutputStream [
    /tmp/tmp8q476,273]
>> BinaryWrite[strm, {39, 4, 122}]
  OutputStream [
    /tmp/tmp8q476,273]
>> Close[strm]
  /tmp/tmp8q476
>> strm = OpenRead[%, BinaryFormat
-> True]
  InputStream [
    /tmp/tmp8q476,274]
>> BinaryRead[strm]
39
>> BinaryRead[strm, "Byte"]
4
>> BinaryRead[strm, "Character8"]
z
>> Close[strm];
```

Write a String

```
>> strm = OpenWrite[BinaryFormat ->
  True]
  OutputStream [
    /tmp/tmp5vfbqkb,275]
>> BinaryWrite[strm, "abc123"]
  OutputStream [
    /tmp/tmp5vfbqkb,275]
>> Close[%]
  /tmp/tmp5vfbqkb
```

Read as Bytes

```
>> strm = OpenRead[%, BinaryFormat
-> True]
  InputStream [/tmp/tmp5vfbqkb,276]
>> BinaryRead[strm, {"Character8",
  "Character8", "Character8", "
  Character8", "Character8", "
  Character8", "Character8"}]
{a,b,c,1,2,3,EndOfFile}
```

```
>> Close[strm]
  /tmp/tmp5vfbqkb
```

Read as Characters

```
>> strm = OpenRead[%, BinaryFormat
-> True]
  InputStream [/tmp/tmp5vfbqkb,277]
>> BinaryRead[strm, {"Byte", "Byte
", "Byte", "Byte", "Byte", "Byte
", "Byte"}]
{97,98,99,49,50,51,EndOfFile}
>> Close[strm]
  /tmp/tmp5vfbqkb
```

Write Type

```
>> strm = OpenWrite[BinaryFormat ->
  True]
  OutputStream [
    /tmp/tmp5s9as,278]
>> BinaryWrite[strm, 97, "Byte"]
  OutputStream [
    /tmp/tmp5s9as,278]
>> BinaryWrite[strm, {97, 98, 99},
  {"Byte", "Byte", "Byte"}]
  OutputStream [
    /tmp/tmp5s9as,278]
>> Close[%]
  /tmp/tmp5s9as
```

## Byte

Byte  
is a data type for Read.

## Character

Character  
is a data type for Read.

## Close

`Close[stream]`  
closes an input or output stream.

```
>> Close[StringToStream["123abc"]]
String

>> Close[OpenWrite[]]
/tmp/tmpj1y_j14q
```

## EndOfFile

`EndOfFile`  
is returned by `Read` when the end of an input stream is reached.

## Expression

`Expression`  
is a data type for `Read`.

## FilePrint

`FilePrint[file]`  
prints the raw contents of *file*.

## Find

`Find[stream, text]`  
find the first line in *stream* that contains *text*.

```
>> stream = OpenRead["ExampleData/
EinsteinSzilLetter.txt"];

>> Find[stream, "uranium"]
in manuscript, leads me
to expect that the element
uranium may be turned into
```

```
>> Find[stream, "uranium"]
become possible to set up
a nuclear chain reaction in
a large mass of uranium,

>> Close[stream]
ExampleData/EinsteinSzilLetter.txt

>> stream = OpenRead["ExampleData/
EinsteinSzilLetter.txt"];

>> Find[stream, {"energy", "power"}
]
a new and important source
of energy in the immediate
future. Certain aspects

>> Find[stream, {"energy", "power"}
]
by which vast amounts of
power and large quantities
of new radium-like

>> Close[stream]
ExampleData/EinsteinSzilLetter.txt
```

## Get (<<)

`<<name`  
reads a file and evaluates each expression, returning only the last one.  
`Get[name, Trace->True]`  
Runs `Get` tracing each line before it is evaluated.

```
>> filename = $TemporaryDirectory
<> "/example_file";

>> Put[x + y, filename]

>> Get[filename]
"x"cannotbefollowedby"
text{+}y"(line1of"/tmp/example_file").

>> filename = $TemporaryDirectory
<> "/example_file";

>> Put[x + y, 2x^2 + 4z!, Cos[x] +
I Sin[x], filename]
```

```
>> Get[filename]
      "x"cannotbe followedby"
      text{+}y"(line1of"/tmp/example_file").
>> DeleteFile[filename]
```

## \$Input

`$Input`  
is the name of the stream from which input is currently being read.

```
>> $Input
```

## \$InputFileName

`$InputFileName`  
is the name of the file from which input is currently being read.

While in interactive mode, `$InputFileName` is "".

```
>> $InputFileName
```

## InputStream

`InputStream[name, n]`  
represents an input stream.

```
>> stream = StringToStream["Mathics
      is cool!"]
      InputStream[String, 294]
>> Close[stream]
      String
```

## Number

`Number`  
is a data type for Read.

## OpenAppend

`OpenAppend['file']`  
opens a file and returns an `OutputStream` to which writes are appended.

```
>> OpenAppend[]
      OutputStream[
        /tmp/tmp5n8nnl9n, 297]
```

## OpenRead

`OpenRead['file']`  
opens a file and returns an `InputStream`.

```
>> OpenRead["ExampleData/
      EinsteinSzilLetter.txt"]
      InputStream[
        ExampleData/EinsteinSzilLetter.txt,
        301]
>> OpenRead["https://raw.
      githubusercontent.com/mathics/
      Mathics/master/README.rst"]
      InputStream[
        https://raw.githubusercontent.com/mathics/Mathics/master/
        README.rst, 302]
>> Close[%];
```

## OpenWrite

`OpenWrite['file']`  
opens a file and returns an `OutputStream`.

```
>> OpenWrite[]
      OutputStream[
        /tmp/tmp9wbwt_kr, 305]
```



## OutputStream

```
OutputStream[name, n]
  represents an output stream.
```

```
>> OpenWrite[]
OutputStream[
  /tmp/tmp0vk_2azf, 307]
>> Close[%]
/tmp/tmp0vk_2azf
```

## Put (>>)

```
expr >> filename
  write expr to a file.
Put[expr1, expr2, ..., filename]
  write a sequence of expressions to a file.
```

```
>> Put[40!, fortyfactorial]
      fortyfactorialisnotstring,
      InputStream[], or OutputStream[]
815 915 283 247 897 734 345 ~
~611 269 596 115 894 272 ~
~000 000 000»fortyfactorial

>> filename = $TemporaryDirectory
<> "/fortyfactorial";

>> Put[40!, filename]

>> FilePrint[filename]
815 915 283 247 897 734 345 611 ~
~269 596 115 894 272 000 000 000

>> Get[filename]
815 915 283 247 897 734 345 611 ~
~269 596 115 894 272 000 000 000

>> DeleteFile[filename]

>> filename = $TemporaryDirectory
<> "/fiftyfactorial";

>> Put[10!, 20!, 30!, filename]
```

```
>> FilePrint[filename]
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000

>> DeleteFile[filename]

=

>> filename = $TemporaryDirectory
<> "/example_file";

>> Put[x + y, 2x^2 + 4z!, Cos[x] +
I Sin[x], filename]

>> FilePrint[filename]
x
text{+}y
2 * x{ }{
wedge}2
text{+}4 * z!

text{Cos}
left[x
right]
text{+}I *
text{Sin}
left[x
right]

>> DeleteFile[filename]
```

## PutAppend (>>>)

```
expr >>> filename
  append expr to a file.
PutAppend[expr1, expr2, ..., '$'
filename'$']
  write a sequence of expressions to a file.
```

```
>> Put[50!, "factorials"]

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000

>> PutAppend[10!, 20!, 30!, "
factorials"]
```

```

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000

>> 60! >>> "factorials"

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000
8 320 987 112 741 390 144 ~
~276 341 183 223 364 380 754 ~
~172 606 361 245 952 449 277 ~
~696 409 600 000 000 000 000

>> "string" >>> factorials

>> FilePrint["factorials"]
30 414 093 201 713 378 043 612 ~
~608 166 064 768 844 377 641 ~
~568 960 512 000 000 000 000
3 628 800
2 432 902 008 176 640 000
265 252 859 812 191 ~
~058 636 308 480 000 000
8 320 987 112 741 390 144 ~
~276 341 183 223 364 380 754 ~
~172 606 361 245 952 449 277 ~
~696 409 600 000 000 000 000
"string"

```

## Read

```

Read[stream]
    reads the input stream and returns one
    expression.
Read[stream, type]
    reads the input stream and returns an ob-
    ject of the given type.
Read[stream, type]
    reads the input stream and returns an ob-
    ject of the given type.
Read[stream, Hold[Expression]]
    reads the input stream for an Expression
    and puts it inside Hold.

```

*type* is one of:

- Byte
- Character
- Expression
- HoldExpression
- Number
- Real
- Record
- String
- Word

```

>> stream = StringToStream["abc123
"];

>> Read[stream, String]
abc123

>> stream = StringToStream["abc
123"];

>> Read[stream, Word]
abc

>> Read[stream, Word]
123

>> stream = StringToStream["123,
4"];

>> Read[stream, Number]
123

>> Read[stream, Number]
4

>> stream = StringToStream["2+2\n2
+3"];

```

Read with a Hold[Expression] returns the expression it reads unevaluated so it can be later

inspected and evaluated:

```
>> Read[stream, Hold[Expression]]
      Hold[2 + 2]

>> Read[stream, Expression]
      5

>> Close[stream];
```

Reading a comment however will return the empty list:

```
>> stream = StringToStream["(* ::
      Package:: *)"];

>> Read[stream, Hold[Expression]]
      {}

>> Close[stream];

>> stream = StringToStream["123 abc
      "];

>> Read[stream, {Number, Word}]
      {123, abc}
```

Multiple lines:

```
>> stream = StringToStream["\Tengo
      una\nvaca lechera.\"]; Read[
      stream]

      Tengo una
      vaca lechera.
```

## ReadList

```
ReadList["file"]
  Reads all the expressions until the end of
  file.
ReadList["file", type]
  Reads objects of a specified type until the
  end of file.
ReadList["file", {type1, type2, ...}]
  Reads a sequence of specified types until
  the end of file.
```

```
>> ReadList[StringToStream["a 1 b
      2"], {Word, Number}]
      {{a, 1}, {b, 2}}

>> stream = StringToStream["\
      abc123\"]; 
```

```
>> ReadList[stream]
      {abc123}

>> InputForm[%]
      {"abc123"}
```

## Record

```
Record
  is a data type for Read.
```

## SetStreamPosition

```
SetStreamPosition[stream, n]
  sets the current position in a stream.
```

```
>> stream = StringToStream["Mathics
      is cool!"]

      InputStream[String, 352]

>> SetStreamPosition[stream, 8]
      8

>> Read[stream, Word]
      is

>> SetStreamPosition[stream,
      Infinity]

      16
```

## Skip

```
Skip[stream, type]
  skips ahead in an input stream by one
  object of the specified type.
Skip[stream, type, n]
  skips ahead in an input stream by n ob-
  jects of the specified type.
```

```
>> stream = StringToStream["a b c d
      "];

>> Read[stream, Word]
      a

>> Skip[stream, Word]
```

```
>> Read[stream, Word]
c

>> stream = StringToStream["a b c d
"];

>> Read[stream, Word]
a

>> Skip[stream, Word, 2]

>> Read[stream, Word]
d
```

## StreamPosition

`StreamPosition[stream]`  
returns the current position in a stream as an integer.

```
>> stream = StringToStream["Mathics
is cool!"]

InputStream[String, 358]

>> Read[stream, Word]
Mathics

>> StreamPosition[stream]
7
```

## Streams

`Streams[]`  
returns a list of all open streams.

```
>> Streams[]
{InputStream[stdin, 0],
 OutputStream[stdout, 1],
 OutputStream[stderr, 2],
 OutputStream[/tmp/tmp5n8nnl9n,
 297], InputStream[
 /src/external-vcs/github/mathics/Mathics/mathics/data,
 301], OutputStream[
 /tmp/tmp9wbwt_kr,
 305], InputStream[
 String, 326], InputStream[
 String, 338], InputStream[
 String, 339], InputStream[
 String, 340], InputStream[
 String, 341], InputStream[
 String, 344], InputStream[
 String, 345], InputStream[
 String, 346], InputStream[
 String, 348], InputStream[
 String, 349], InputStream[
 String, 350], InputStream[
 String, 351], InputStream[
 String, 352], InputStream[
 String, 355], InputStream[
 String, 356], InputStream[
 String, 357], InputStream[
 String, 358], OutputStream[
 /tmp/tmp3ci5nb6a, 359]}

>> Streams["stdout"]
{OutputStream[stdout, 1]}
```

## StringToStream

`StringToStream[string]`  
converts a *string* to an open input stream.

```
>> strm = StringToStream["abc 123"]
InputStream[String, 361]
```

## Word

`Word`  
is a data type for `Read`.

## Write

`Write[channel, expr1, expr2, ...]`  
writes the expressions to the output channel followed by a newline.

```
>> stream = OpenWrite[]
      OutputStream[
        /tmp/tmpwb5ie82h, 364]
>> Write[stream, 10 x + 15 y ^ 2]
>> Write[stream, 3 Sin[z]]
>> Close[stream]
      /tmp/tmpwb5ie82h
>> stream = OpenRead[%];
>> ReadList[stream]
      {10x + 15y2, 3Sin[z]}
```

```
>> FilePrint[%]
      Thisisatest1Thisisalsoatest2
```

## WriteString

`WriteString[stream, $str1, str2, ...]`  
writes the strings to the output stream.

```
>> stream = OpenWrite[];
>> WriteString[stream, "This is a
      test 1"]
>> WriteString[stream, "This is
      also a test 2"]
>> Close[stream]
      /tmp/tmpdqy9ujjn
>> FilePrint[%]
      Thisisatest1Thisisalsoatest2
>> stream = OpenWrite[];
>> WriteString[stream, "This is a
      test 1", "This is also a test
      2"]
>> Close[stream]
      /tmp/tmpnyw8ymb8
```

## 38. Filesystem Operations

### Contents

---

AbsoluteFileName . . .	198	FileDate . . . . .	200	Needs . . . . .	203
\$BaseDirectory . . . .	198	FileExistsQ . . . . .	200	\$OperatingSystem . . .	203
CopyDirectory . . . . .	198	FileExtension . . . . .	201	ParentDirectory . . . .	203
CopyFile . . . . .	198	FileHash . . . . .	201	\$Path . . . . .	203
CreateDirectory . . . .	199	FileInformation . . . .	201	\$PathnameSeparator .	204
CreateFile . . . . .	199	FileNameDepth . . . .	201	RenameDirectory . . .	204
CreateTemporary . . .	199	FileNameJoin . . . . .	201	RenameFile . . . . .	204
DeleteDirectory . . . .	199	FileNameSplit . . . . .	202	ResetDirectory . . . .	204
DeleteFile . . . . .	199	FileNameTake . . . . .	202	\$RootDirectory . . . .	204
Directory . . . . .	199	FileNames . . . . .	202	SetDirectory . . . . .	204
DirectoryName . . . .	199	FileType . . . . .	202	SetFileDate . . . . .	204
DirectoryQ . . . . .	200	FindFile . . . . .	202	\$TemporaryDirectory .	204
DirectoryStack . . . .	200	FindList . . . . .	203	ToFileName . . . . .	205
ExpandFileName . . .	200	\$HomeDirectory . . . .	203	URLSave . . . . .	205
FileBaseName . . . . .	200	\$InitialDirectory . . .	203	\$UserBaseDirectory . .	205
FileByteCount . . . .	200	\$InstallationDirectory .	203		

---

### AbsoluteFileName

`AbsoluteFileName["name"]`  
returns the absolute version of the given filename.

```
>> AbsoluteFileName["ExampleData/  
sunflowers.jpg"]  
/src/external-vcs/github/mathics/Mathics/mathics/data/ExampleData/sunflowers.jpg
```

### \$BaseDirectory

`$UserBaseDirectory`  
returns the folder where user configurations are stored.

```
>> $RootDirectory  
/
```

### CopyDirectory

`CopyDirectory["dir1" , "dir2"]`  
copies directory *dir1* to *dir2*.

### CopyFile

`CopyFile["file1" , "file2"]`  
copies *file1* to *file2*.

```
>> CopyFile["ExampleData/sunflowers  
.jpg", "MathicsSunflowers.jpg"]  
MathicsSunflowers.jpg  
  
>> DeleteFile["MathicsSunflowers.  
jpg"]
```

## CreateDirectory

```
CreateDirectory["dir"]  
  creates a directory called dir.  
CreateDirectory[]  
  creates a temporary directory.
```

```
>> dir = CreateDirectory[]  
      /tmp/mub92ii5k
```

## CreateFile

```
CreateFile['filename']  
  Creates a file named "filename" temporary file, but do not open it.  
CreateFile[]  
  Creates a temporary file, but do not open it.
```

## CreateTemporary

```
CreateTemporary[]  
  Creates a temporary file, but do not open it.
```

## DeleteDirectory

```
DeleteDirectory["dir"]  
  deletes a directory called dir.
```

```
>> dir = CreateDirectory[]  
      /tmp/mf1ofp352  
  
>> DeleteDirectory[dir]  
  
>> DirectoryQ[dir]  
      False
```

## DeleteFile

```
Delete["file"]  
  deletes file.  
Delete[{file1, file2, ...}]  
  deletes a list of files.
```

```
>> CopyFile["ExampleData/sunflowers.jpg", "MathicsSunflowers.jpg"];  
  
>> DeleteFile["MathicsSunflowers.jpg"]  
  
>> CopyFile["ExampleData/sunflowers.jpg", "MathicsSunflowers1.jpg"];  
  
>> CopyFile["ExampleData/sunflowers.jpg", "MathicsSunflowers2.jpg"];  
  
>> DeleteFile[{"MathicsSunflowers1.jpg", "MathicsSunflowers2.jpg"}]
```

## Directory

```
Directory[]  
  returns the current working directory.
```

```
>> Directory[]  
      /src/external-vcs/github/mathics/Mathics
```

## DirectoryName

```
DirectoryName["name"]  
  extracts the directory name from a filename.
```

```
>> DirectoryName["a/b/c"]  
      a/b  
  
>> DirectoryName["a/b/c", 2]  
      a
```

## DirectoryQ

```
DirectoryQ["name"]  
  returns True if the directory called name exists and False otherwise.
```

```
>> DirectoryQ["ExampleData/"]  
      True
```

```
>> DirectoryQ["ExampleData/
MythicalSubdir/"]
False
```

## DirectoryStack

```
DirectoryStack[]
returns the directory stack.
```

```
>> DirectoryStack[]
{ /src/external-vcs/github/mathics/Mathics }
```

## ExpandFileName

```
ExpandFileName["name"]
expands name to an absolute filename for
your system.
```

```
>> ExpandFileName["ExampleData/
sunflowers.jpg"]
/src/external-vcs/github/mathics/Mathics/ExampleData/sunflowers.jpg
```

## FileNameBase

```
FileNameBase["file"]
gives the base name for the specified file
name.
```

```
>> FileNameBase["file.txt"]
file
>> FileNameBase["file.tar.gz"]
file.tar
```

## FileByteCount

```
FileByteCount[file]
returns the number of bytes in file.
```

```
>> FileByteCount["ExampleData/
sunflowers.jpg"]
142286
```

## FileDate

```
FileDate[file, types]
returns the time and date at which the file
was last modified.
```

```
>> FileDate["ExampleData/sunflowers
.jpg"]
{ 2120, 9, 7, 7, 16, 33.2822 }
>> FileDate["ExampleData/sunflowers
.jpg", "Access"]
{ 2121, 7, 3, 17, 18, 41.2356 }
>> FileDate["ExampleData/sunflowers
.jpg", "Creation"]
Missing[NotApplicable]
>> FileDate["ExampleData/sunflowers
.jpg", "Change"]
{ 2120, 9, 7, 7, 16, 33.2822 }
>> FileDate["ExampleData/sunflowers
.jpg", "Modification"]
{ 2120, 9, 7, 7, 16, 33.2822 }
>> FileDate["ExampleData/sunflowers
.jpg", "Rules"]
{ Access -> { 2121, 7, 3, 17, 18,
41.2356 }, Creation -> Missing[
NotApplicable], Change -> {
2120, 9, 7, 7, 16, 33.2822 }
~2}, Modification -> {
2120, 9, 7, 7, 16, 33.2822 } }
```

## FileExistsQ

```
FileExistsQ["file"]
returns True if file exists and False other-
wise.
```

```
>> FileExistsQ["ExampleData/
sunflowers.jpg"]
True
>> FileExistsQ["ExampleData/
sunflowers.png"]
False
```



## FileExtension

`FileExtension["file"]`  
gives the extension for the specified file name.

```
>> FileExtension["file.txt"]
txt
>> FileExtension["file.tar.gz"]
gz
```

## FileHash

`FileHash[file]`  
returns an integer hash for the given *file*.  
`FileHash[file, type]`  
returns an integer hash of the specified *type* for the given *file*.  
The types supported are "MD5", "Adler32", "CRC32", "SHA", "SHA224", "SHA256", "SHA384", and "SHA512".  
`FileHash[file, type, format]`  
gives a hash code in the specified format.

```
>> FileHash["ExampleData/sunflowers.jpg"]
109 937 059 621 979 839 ~
~952 736 809 235 486 742 106
>> FileHash["ExampleData/sunflowers.jpg", "MD5"]
109 937 059 621 979 839 ~
~952 736 809 235 486 742 106
>> FileHash["ExampleData/sunflowers.jpg", "Adler32"]
1 607 049 478
>> FileHash["ExampleData/sunflowers.jpg", "SHA256"]
111 619 807 552 579 450 300 684 600 ~
~241 129 773 909 359 865 098 672 ~
~286 468 229 443 390 003 894 913 065
```

## FileInformation

`FileInformation["file"]`  
returns information about *file*.

This function is totally undocumented in MMA!

```
>> FileInformation["ExampleData/sunflowers.jpg"]
{
  File
  - > /src/external-vcs/github/mathics/Mathics/ExampleData/
  FileType - > File, ByteCount - >
  142 286, Date - > 6.96413 × 109
}
```

## FileNameDepth

`FileNameDepth["name"]`  
gives the number of path parts in the given filename.

```
>> FileNameDepth["a/b/c"]
3
>> FileNameDepth["a/b/c/"]
3
```

## FileNameJoin

`FileNameJoin[{dir_1..., dir_2, ...}]`  
joins the *dir\_i* together into one path.  
`FileNameJoin[..., OperatingSystem->'os']`  
yields a file name in the format for the specified operating system. Possible choices are "Windows", "MacOSX", and "Unix".

```
>> FileNameJoin[{"dir1", "dir2", "dir3"}]
dir1/dir2/dir3
>> FileNameJoin[{"dir1", "dir2", "dir3"}, OperatingSystem -> "Unix"]
dir1/dir2/dir3
>> FileNameJoin[{"dir1", "dir2", "dir3"}, OperatingSystem -> "Windows"]
dir1\dir2\dir3
```

## FileNameSplit

`FileNameSplit["filenams"]`  
splits a *filename* into a list of parts.

```
>> FileNameSplit["example/path/file
.txt"]
{example,path,file.txt}
```

## FileNameTake

`FileNameTake["file"]`  
returns the last path element in the file name *name*.  
`FileNameTake["file", n]`  
returns the first *n* path elements in the file name *name*.  
`FileNameTake["file", $-n]`  
returns the last *n* path elements in the file name *name*.

## FileNames

`FileNames[]`  
Returns a list with the filenames in the current working folder.  
`FileNames[form]`  
Returns a list with the filenames in the current working folder that matches with *form*.  
`FileNames[{form_1, form_2, ...}]`  
Returns a list with the filenames in the current working folder that matches with one of *form\_1*, *form\_2*, ....  
`FileNames[{form_1, form_2, ...},{dir_1, dir_2, ...}]`  
Looks into the directories *dir\_1*, *dir\_2*, ....  
`FileNames[{form_1, form_2, ...},{dir_1, dir_2, ...}]`  
Looks into the directories *dir\_1*, *dir\_2*, ....  
`FileNames[{forms, dirs, n}]`  
Look for files up to the level *n*.

```
>> SetDirectory[
$InstallationDirectory <> "/"
autoload];
```

```
>> FileNames["*.m", "formats"]//
Length
0
>> FileNames["*.m", "formats", 3]//
Length
14
>> FileNames["*.m", "formats",
Infinity]//Length
14
```

## FileType

`FileType["file"]`  
gives the type of a file, a string. This is typically File, Directory or None.

```
>> FileType["ExampleData/sunflowers
.jpg"]
File
>> FileType["ExampleData"]
Directory
>> FileType["ExampleData/
nonexistant"]
None
```

## FindFile

`FindFile[name]`  
searches \$Path for the given filename.

```
>> FindFile["ExampleData/sunflowers
.jpg"]
/src/external-vcs/github/mathics/Mathics/mathics/data/
>> FindFile["VectorAnalysis'"]
/src/external-vcs/github/mathics/Mathics/mathics/pack
>> FindFile["VectorAnalysis'
VectorAnalysis'"]
/src/external-vcs/github/mathics/Mathics/mathics/pack
```

## FindList

```
FindList[file, text]
    returns a list of all lines in file that contain
    text.
FindList[file, {text1, text2, ...}]
    returns a list of all lines in file that contain
    any of the specified string.
FindList[{file1, file2, ...}, ...]
    returns a list of all lines in any of the filei
    that contain the specified strings.
```

```
>> stream = FindList["ExampleData/
EinsteinSzilLetter.txt", "
uranium"];

>> FindList["ExampleData/
EinsteinSzilLetter.txt", "
uranium", 1]

{in manuscript, leads me
 to expect that the element
 uranium may be turned into}
```

## \$HomeDirectory

```
$HomeDirectory
    returns the users HOME directory.
```

```
>> $HomeDirectory
/home/rocky
```

## \$InitialDirectory

```
$InitialDirectory
    returns the directory from which Mathics
    was started.
```

```
>> $InitialDirectory
/src/external-vcs/github/mathics/Mathics
```

## \$InstallationDirectory

```
$InstallationDirectory
    returns the top-level directory in which
    Mathics was installed.
```

```
>> $InstallationDirectory
/src/external-vcs/github/mathics/Mathics/mathics
```

## Needs

```
Needs["context'"]
    loads the specified context if not already
    in $Packages.
```

```
>> Needs["VectorAnalysis'"]
```

## \$OperatingSystem

```
$OperatingSystem
    gives the type of operating system run-
    ning Mathics.
```

```
>> $OperatingSystem
Unix
```

## ParentDirectory

```
ParentDirectory[]
    returns the parent of the current working
    directory.
ParentDirectory["dir"]
    returns the parent dir.
```

```
>> ParentDirectory[]
/src/external-vcs/github/mathics/Mathics/mathics
```

## \$Path

```
$Path
    returns the list of directories to search
    when looking for a file.
```

```
>> $Path
{., /home/rocky,
 /src/external-vcs/github/mathics/Mathics/mathics/data,
 /src/external-vcs/github/mathics/Mathics/mathics/pack
```

## \$PathnameSeparator

`$PathnameSeparator`  
returns a string for the separator in paths.

```
>> $PathnameSeparator
/
```

## RenameDirectory

`RenameDirectory["dir1" ' ', "dir2"]`  
renames directory *dir1* to *dir2*.

## RenameFile

`RenameFile["file1" ' ', "file2"]`  
renames *file1* to *file2*.

```
>> CopyFile["ExampleData/sunflowers
.jpg", "MathicsSunflowers.jpg"]
MathicsSunflowers.jpg

>> RenameFile["MathicsSunflowers.
.jpg", "MathicsSunnyFlowers.jpg"]
MathicsSunnyFlowers.jpg

>> DeleteFile["MathicsSunnyFlowers.
.jpg"]
```

## ResetDirectory

`ResetDirectory[]`  
pops a directory from the directory stack and returns it.

```
>> ResetDirectory[]
/src/external-vcs/github/mathics/Mathics/math
```

## \$RootDirectory

`$RootDirectory`  
returns the system root directory.

```
>> $RootDirectory
/
```

## SetDirectory

`SetDirectory[dir]`  
sets the current working directory to *dir*.

```
>> SetDirectory[]
/home/rocky
```

## SetFileDate

`SetFileDate["file"]`  
set the file access and modification dates of *file* to the current date.  
`SetFileDate["file", date]`  
set the file access and modification dates of *file* to the specified date list.  
`SetFileDate["file", date, "type"]`  
set the file date of *file* to the specified date list. The "*type*" can be one of "Access", "Creation", "Modification", or All.

Create a temporary file (for example purposes)

```
>> tmpfilename =
    $TemporaryDirectory <> "/tmp0";

>> Close[OpenWrite[tmpfilename]];

>> SetFileDate[tmpfilename, {2002,
    1, 1, 0, 0, 0.}, "Access"];

>> FileDate[tmpfilename, "Access"]
{2002, 1, 1, 0, 0, 0.}
```

## \$TemporaryDirectory

`$TemporaryDirectory`  
returns the directory used for temporary files.

```
>> $TemporaryDirectory
/tmp
```

## ToFileName

```
ToFileName[{"dir_1", "dir_2", ...}]
```

joins the *dir<sub>i</sub>* together into one path.

ToFileName has been superseded by FileNameJoin.

```
>> ToFileName[{"dir1", "dir2"}, "file"]
dir1/dir2/file

>> ToFileName["dir1", "file"]
dir1/file

>> ToFileName[{"dir1", "dir2", "dir3"}]
dir1/dir2/dir3
```

## URLSave

```
URLSave['url']
Save "url" in a temporary file.
URLSave['url', filename]
Save "url" in filename.
```

## \$UserBaseDirectory

```
$UserBaseDirectory
```

returns the folder where user configurations are stored.

```
>> $RootDirectory
/
```

## 39. Importing and Exporting

## Contents

	Sys-	Sys-	ImportString	. . . . .	208
	tem'Convert'B64Dump'B64Decode	tem'ConvertersDump'\$formatMappings	ImportEx-		
	Export		port'RegisterExport		209
	\$ExportFormats		ImportEx-		
	ExportString		port'RegisterImport		210
	FileFormat		URLFetch		210
	Import				208
	\$extensionMappings				208

## System'Convert'B64Dump'B64Decode

System'Convert'Base64Dump'Base64Decode[  
*string*]  
Decode *string* in Base64 coding to an ex-  
pression.

```
>> System.Convert<B64Dump,B64Decode>
["R!="]
String"R!
= "isnotavalidb64encodedstring.
$Failed
```

```
System.Convert.FromBase64(B64Dump, B64Decode
[%]
```

$$\text{Integrate}[f[x], \{x, 0, 2\}]$$

## System'Convert'CommonDump'RemoveLin

```
System.Convert.CommonDump`
RemoveLinearSyntax[something]
Keine anung... Undocumented in wma
```

## System'ConvertersDump'\$extensionMapping

## System'Convert'B64Dump'B64Encode

System' Convert' B64Dump' B64Encode[*expr*]  
Encodes *expr* in Base64 coding

```
>> System'Convert'B64Dump'B64Encode  
["Hello world"]  
SGVsbG8gd29ybGQ=  
  
>> System'Convert'B64Dump'B64Decode  
[%]  
Hello world  
  
>> System'Convert'B64Dump'B64Encode  
[Integrate[f[x],{x,0,2}]]  
SW50ZWdyYXRiW2ZbeF0sIHt4LCAwLCAyfV0=
```

**\$extensionMappings**  
Returns a list of associations between file extensions and file types.

## System'ConvertersDump'\$formatMappings

**\$formatMappings**  
Returns a list of associations between file extensions and file types.

## Export

```
Export["file.ext", expr]
  exports expr to a file, using the extension
  ext to determine the format.
Export["file", expr, "format"]
  exports expr to a file in the specified for-
  mat.
Export["file", exprs, elems]
  exports exprs to a file as elements speci-
  fied by elems.
```

## \$ExportFormats

```
$ExportFormats
  returns a list of file formats supported by
  Export.
```

```
>> $ExportFormats
{BMP, Base64, CSV, GIF, JPEG,
 JPEG2000, PBM, PCX, PGM,
 PNG, PPM, SVG, TIFF, Text, asy}
```

## ExportString

```
ExportString[expr, form]
  exports expr to a string, in the format
  form.
Export["file", exprs, elems]
  exports exprs to a string as elements speci-
  fied by elems.
```

```
>> ExportString
[{{1,2,3,4},{3},{2},{4}}, "CSV"]
1,2,3,4
3,
2,
4,
>> ExportString[{1,2,3,4}, "CSV"]
1,
2,
3,
4,
```

```
>> ExportString[Integrate[f[x],{x
,0,2}], "SVG"]//Head
String
```

## FileFormat

```
FileFormat["name"]
  attempts to determine what format
  Import should use to import specified
  file.
```

```
>> FileFormat["ExampleData/
sunflowers.jpg"]
JPEG
>> FileFormat["ExampleData/
EinsteinSzilLetter.txt"]
Text
>> FileFormat["ExampleData/lena.tif
"]
TIFF
```

## Import

```
Import["file"]
  imports data from a file.
Import["file", elements]
  imports the specified elements from a file.
Import["http://url", ...] and Import["
ftp://url", ...]
  imports from a URL.
```

```
>> Import["ExampleData/ExampleData.
txt", "Elements"]
{Data, Lines, Plaintext, String, Words}
>> Import["ExampleData/ExampleData.
txt", "Lines"]
{Example File Format, Created
by Angus,0.629452 0.586355,
0.711009 0.687453,0.246540
0.433973,0.926871 0.887255,
0.825141 0.940900,0.847035
0.127464,0.054348 0.296494,
0.838545 0.247025,0.838697
0.436220,0.309496 0.833591}
```

```
>> Import["ExampleData/colors.json"]

{colorsArray
  - > {{colorName- > black,
    rgbValue- > (0, 0, 0),
    hexValue- > #000 000} ,
    {colorName- > red,
    rgbValue- > (255, 0, 0),
    hexValue- > #FF0 000} ,
    {colorName- > green,
    rgbValue- > (0, 255, 0),
    hexValue- > #00FF00} ,
    {colorName- > blue,
    rgbValue- > (0, 0, 255),
    hexValue- > #0 000FF} ,
    {colorName- > yellow,
    rgbValue- > (255, 255, 0),
    hexValue- > #FFFF00} ,
    {colorName- > cyan,
    rgbValue- > (0, 255, 255),
    hexValue- > #00FFFF} ,
    {colorName- > magenta,
    rgbValue- > (255, 0, 255),
    hexValue- > #FF00FF} ,
    {colorName- > white,
    rgbValue- > (255, 255, 255),
    hexValue- > #FFFFFF}}}
```

## \$ImportFormats

`$ImportFormats`  
returns a list of file formats supported by Import.

```
>> $ImportFormats

{BMP, Base64, CSV, GIF, HTML,
 ICO, JPEG, JPEG2 000, JSON,
 PBM, PCX, PGM, PNG, PPM,
 Package, TGA, TIFF, Text, XML}
```

## ImportString

`ImportString["data" , "format"]`  
imports data in the specified format from a string.

`ImportString["file" , elements]`  
imports the specified elements from a string.

`ImportString["data"]`  
attempts to determine the format of the string from its content.

```
>> str = "Hello!\n This is a
testing text\n";

>> ImportString[str, "Elements"]
{Data, Lines, Plaintext, String, Words}

>> ImportString[str, "Lines"]
{Hello!, This is a testing text}
```

## ImportExport‘RegisterExport

`RegisterExport["format" , func]`  
register *func* as the default function used when exporting from a file of type "format".

Simple text exporter

```
>> ExampleExporter1[filename_,
  data_, opts___] := Module[{strm
  = OpenWrite[filename], char =
  data}, WriteString[strm, char];
  Close[strm]]

>> ImportExport‘RegisterExport["
ExampleFormat1",
ExampleExporter1]

>> Export["sample.txt", "Encode
this string!", "ExampleFormat1
"];

>> FilePrint["sample.txt"]
Encodethisstring!
```

Very basic encrypted text exporter



```
>> ExampleExporter2[filename_,
  data_, opts___] := Module[{strm
= OpenWrite[filename], char}, (*
  TODO: Check data *)char =
  FromCharacterCode[Mod[
  ToCharacterCode[data] - 84, 26]
+ 97]; WriteString[strm, char];
  Close[strm]]

>> ImportExport`RegisterExport["
ExampleFormat2",
ExampleExporter2]

>> Export["sample.txt", "
encodethisstring", "
ExampleFormat2"];

>> FilePrint["sample.txt"]
  rapbqrguvffgevat
```

## ImportExport`RegisterImport

```
RegisterImport["format", defaultFunction]
  register defaultFunction as the default
  function used when importing from a file
  of type "format".
RegisterImport["format", {"elem1" :>
conditionalFunction1, "elem2" :> conditional-
Function2, ..., defaultFunction}]
  registers multiple elements (elem1, ...)
  and their corresponding converter func-
  tions (conditionalFunction1, ...) in addition
  to the defaultFunction.
RegisterImport["format", {"
conditionalFunctions, defaultFunction,
"elem3" :> postFunction3, "elem4" :>
postFunction4, ...}]
  also registers additional elements (elem3,
  ...) whose converters (postFunction3, ...)
  act on output from the low-level func-
  tions.
```

First, define the default function used to import the data.

```
>> ExampleFormat1Import[
  filename_String] := Module[{
  stream, head, data}, stream =
  OpenRead[filename]; head =
  ReadList[stream, String, 2];
  data = Partition[ReadList[stream
  , Number], 2]; Close[stream]; {"
Header" -> head, "Data" -> data
}]
```

RegisterImport is then used to register the above function to a new data format.

```
>> ImportExport`RegisterImport["
ExampleFormat1",
ExampleFormat1Import]
```

```
>> FilePrint["ExampleData/
ExampleData.txt"]
```

*ExampleFileFormat*

*CreatedbyAngus*

0.6294520.586355

0.7110090.687453

0.2465400.433973

0.9268710.887255

0.8251410.940900

0.8470350.127464

0.0543480.296494

0.8385450.247025

0.8386970.436220

0.3094960.833591

```
>> Import["ExampleData/ExampleData.
txt", {"ExampleFormat1", "
Elements"}]
```

{Data, Header}

```
>> Import["ExampleData/ExampleData.
txt", {"ExampleFormat1", "Header
"}]
```

{Example File Format,  
Created by Angus}

Conditional Importer:

```
>> ExampleFormat2DefaultImport[
  filename_String] := Module[{
  stream, head}, stream = OpenRead
[filename]; head = ReadList[
stream, String, 2]; Close[stream
]; {"Header" -> head}]
```

```

>> ExampleFormat2DataImport[
  filename_String] := Module[{
    stream, data}, stream = OpenRead
    [filename]; Skip[stream, String,
    2]; data = Partition[ReadList[
    stream, Number], 2]; Close[
    stream]; {"Data" -> data}]

>> ImportExport`RegisterImport["
  ExampleFormat2", {"Data" :>
  ExampleFormat2DataImport,
  ExampleFormat2DefaultImport}]

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat2", "
  Elements"}]

  {Data, Header}

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat2", "Header
  "}

  {Example File Format,
   Created by Angus}

>> Import["ExampleData/ExampleData.
  txt", {"ExampleFormat2", "Data
  "} // Grid

0.629452 0.586355
0.711009 0.687453
0.24654 0.433973
0.926871 0.887255
0.825141 0.9409
0.847035 0.127464
0.054348 0.296494
0.838545 0.247025
0.838697 0.43622
0.309496 0.833591

```

## URLFetch

```

URLFetch[URL]
  Returns the content of URL as a string.
# = ...

```

## 40. The Main Loop

An interactive session operates a loop, called the “main loop” in this way:

- read input
- process input
- format and print results
- repeat

As part of this loop, various global objects in this section are consulted.

There are a variety of “hooks” that allow you to

insert functions to be applied to the expressions at various stages in the main loop.

If you assign a function to the global variable `$PreRead` it will be applied with the input that is read in the first step listed above.

Similarly, if you assign a function to global variable `$Pre`, it will be applied with the input before processing the input, the second step listed above.

### Contents

---

<code>\$HistoryLength</code> . . . . .	211	<code>\$PrePrint</code> . . . . .	212	<code>In</code> . . . . .	212
<code>\$Post</code> . . . . .	211	<code>\$PreRead</code> . . . . .	212	<code>\$Line</code> . . . . .	212
<code>\$Pre</code> . . . . .	212	<code>\$SyntaxHandler</code> . . . . .	212	<code>Out</code> . . . . .	213

---

### `$HistoryLength`

`$HistoryLength`  
specifies the maximum number of `In` and `Out` entries.

```
>> $HistoryLength
100
>> $HistoryLength = 1;
>> 42
42
>> %
42
>> %%
%3
>> $HistoryLength = 0;
>> 42
42
>> %
%7
```

### `$Post`

`$Post`  
is a global variable whose value, if set, is applied to every output expression.

### `$Pre`

`$Pre`  
is a global variable whose value, if set, is applied to every input expression.

Set *Timing* as the `$Pre` function, stores the elapsed time in a variable, stores just the result in `Out[$Line]` and print a formatted version showing the elapsed time

```
>> $Pre := (Print["[Processing
input...]"];#1)&
>> $Post := (Print["[Storing result
...]"]; #1)&
[Processinginput...]
[Storingresult...]
```

```
>> $PrePrint := (Print["The result
is:"]; {TimeUsed[], #1})&
[Processinginput...]
[Storingresult...]

>> 2 + 2
[Processinginput...]
[Storingresult...]
Theresultis :
{341.557,4}

>> $Pre = .; $Post = .; $PrePrint =
.; $EnlapsedTime = .;
[Processinginput...]

>> 2 + 2
4
```

## \$PrePrint

**\$PrePrint**  
is a global variable whose value, if set, is applied to every output expression before it is printed.

## \$PreRead

**\$PreRead**  
is a global variable whose value, if set, is applied to the text or box form of every input expression before it is fed to the parser. (Not implemented yet)

## \$SyntaxHandler

**\$SyntaxHandler**  
is a global variable whose value, if set, is applied to any input string that is found to contain a syntax error. (Not implemented yet)

## In

**In[k]**  
gives the *k*th line of input.

```
>> x = 1
1

>> x = x + 1
2

>> Do[In[2], {3}]

>> x
5

>> In[-1]
5

>> Definition[In]
Attributes[In] = {Listable, Protected}
In[6] = Definition[In]
In[5] = In[-1]
In[4] = x
In[3] = Do[In[2], {3}]
In[2] = x = x + 1
In[1] = x = 1
```

## \$Line

**\$Line**  
holds the current input line number.

```
>> $Line
1

>> $Line
2

>> $Line = 12;

>> 2 * 5
10

>> Out[13]
10

>> $Line = -1;
Non-negative integer expected.
```

## Out

```
Out[k]
%k
    gives the result of the kth input line.
%, %% , etc.
    gives the result of the previous input line,
    of the line before the previous input line,
    etc.

>> 42
    42

>> %
    42

>> 43;

>> %
    43

>> 44
    44

>> %1
    42

>> %%
    44

>> Hold[Out[-1]]
    Hold[%]

>> Hold[%4]
    Hold[%4]

>> Out[0]
    Out[0]
```

## 41. Integer Functions

Integer Functions can work on integers of any size.

## 42. Combinatorial Functions

Combinatorics is an area of mathematics primarily concerned with counting, both as a means and an end in obtaining results, and certain properties of finite structures.

It is closely related to many other areas of mathematics and has many applications ranging from logic to statistical physics, from evolutionary biology to computer science, etc.

### Contents

<b>Binomial</b> . . . . .	215	<b>Multinomial</b> . . . . .	216	<b>SokalSneathDissimilarity</b> . . . . .	216
<b>DiceDissimilarity</b> . . .	215	<b>RogersTanimotoDissimilarity</b> . . . . .	216	<b>Subsets</b> . . . . .	217
<b>JaccardDissimilarity</b> . .	215	<b>RussellRaoDissimilarity</b>	216	<b>YuleDissimilarity</b> . . .	217
<b>MatchingDissimilarity</b>	216				

### Binomial

`Binomial[n, k]`  
gives the binomial coefficient  $n$  choose  $k$ .

```
>> Binomial[5, 3]
10
```

Binomial supports inexact numbers:

```
>> Binomial[10.5, 3.2]
165.286
```

Some special cases:

```
>> Binomial[10, -2]
0
>> Binomial[-10.5, -3.5]
0.
```

### DiceDissimilarity

`DiceDissimilarity[u, v]`  
returns the Dice dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(c_{tf} + c_{ft}) / (2 * c_{tt} + c_{ft} + c_{tf})$ , where  $n$  is  $\text{len}(u)$  and  $c_{ij}$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> DiceDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
1/2
```

### JaccardDissimilarity

`JaccardDissimilarity[u, v]`  
returns the Jaccard-Needham dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(c_{tf} + c_{ft}) / (c_{tt} + c_{ft} + c_{tf})$ , where  $n$  is  $\text{len}(u)$  and  $c_{ij}$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> JaccardDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
2/3
```

## MatchingDissimilarity

`MatchingDissimilarity[u, v]`  
returns the Matching dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(c\_tf + c\_ft) / n$ , where  $n$  is  $\text{len}(u)$  and  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> MatchingDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
4
7
```

## Multinomial

`Multinomial[n1, n2, ...]`  
gives the multinomial coefficient  $(n1 + n2 + \dots) / (n1! n2! \dots)$ .

```
>> Multinomial[2, 3, 4, 5]
2522520
```

```
>> Multinomial[]
1
```

Multinomial is expressed in terms of Binomial:

```
>> Multinomial[a, b, c]
Binomial[a, a] Binomial[a + b, b] Binomial[a + b + c, c]
```

`Multinomial[n-k, k]` is equivalent to `Binomial[n, k]`.

```
>> Multinomial[2, 3]
10
```

## RogersTanimotoDissimilarity

`RogersTanimotoDissimilarity[u, v]`  
returns the Rogers-Tanimoto dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $R / (c\_tt + c\_ff + R)$  where  $n$  is  $\text{len}(u)$ ,  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ , and  $R = 2 * (c\_tf + c\_ft)$ .

```
>> RogersTanimotoDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
8
11
```

## RussellRaoDissimilarity

`RussellRaoDissimilarity[u, v]`  
returns the Russell-Rao dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $(n - c\_tt) / c\_tt$  where  $n$  is  $\text{len}(u)$  and  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ .

```
>> RussellRaoDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
5
7
```

## SokalSneathDissimilarity

`SokalSneathDissimilarity[u, v]`  
returns the Sokal-Sneath dissimilarity between the two boolean 1-D lists  $u$  and  $v$ , which is defined as  $R / (c\_tt + R)$  where  $n$  is  $\text{len}(u)$ ,  $c\_ij$  is the number of occurrences of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ , and  $R = 2 * (c\_tf + c\_ft)$ .

```
>> SokalSneathDissimilarity[{1, 0, 1, 1, 0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
4
5
```



## Subsets

```
Subsets[list]
    finds a list of all possible subsets of list.
Subsets[list, n]
    finds a list of all possible subsets contain-
    ing at most n elements.
Subsets[list, {n}]
    finds a list of all possible subsets contain-
    ing exactly n elements.
Subsets[list, {min, max}]
    finds a list of all possible subsets contain-
    ing between min and max elements.
Subsets[list, spec, n]
    finds a list of the first n possible subsets.
Subsets[list, spec, {n}]
    finds the nth possible subset.
```

All possible subsets (power set):

```
>> Subsets[{a, b, c}]
{{}, {a}, {b}, {c}, {a,
  b}, {a, c}, {b, c}, {a, b, c}}
```

All possible subsets containing up to 2 elements:

```
>> Subsets[{a, b, c, d}, 2]
{{}, {a}, {b}, {c}, {d},
 {a, b}, {a, c}, {a, d},
 {b, c}, {b, d}, {c, d}}
```

Subsets containing exactly 2 elements:

```
>> Subsets[{a, b, c, d}, {2}]
{{a, b}, {a, c}, {a, d},
 {b, c}, {b, d}, {c, d}}
```

The first 5 subsets containing 3 elements:

```
>> Subsets[{a, b, c, d, e}, {3}, 5]
{{a, b, c}, {a, b, d}, {a,
  b, e}, {a, c, d}, {a, c, e}}
```

All subsets with even length:

```
>> Subsets[{a, b, c, d, e}, {0, 5,
  2}]
{{}, {a, b}, {a, c}, {a, d}, {a, e},
 {b, c}, {b, d}, {b, e}, {c, d}, {c,
  e}, {d, e}, {a, b, c, d}, {a, b, c, e},
 {a, b, d, e}, {a, c, d, e}, {b, c, d, e}}
```

The 25th subset:

```
>> Subsets[Range[5], All, {25}]
{{2, 4, 5}}
```

The odd-numbered subsets of {a,b,c,d} in reverse order:

```
>> Subsets[{a, b, c, d}, All, {15,
  1, -2}]
{{b, c, d}, {a, b, d}, {c, d},
 {b, c}, {a, c}, {d}, {b}, {}}
```

## YuleDissimilarity

```
YuleDissimilarity[u, v]
    returns the Yule dissimilarity between
    the two boolean 1-D lists u and v, which is
    defined as  $R / (c_{tt} * c_{ff} + R / 2)$  where n
    is  $\text{len}(u)$ ,  $c_{ij}$  is the number of occurrences
    of  $u[k]=i$  and  $v[k]=j$  for  $k < n$ , and  $R = 2 *
    c_{tf} * c_{ft}$ .
```

```
>> YuleDissimilarity[{1, 0, 1, 1,
  0, 1, 1}, {0, 1, 1, 0, 0, 0, 1}]
6
5
```

## 43. Division-Related Functions

### Contents

---

CoprimeQ . . . . .	218	LCM . . . . .	219	PrimeQ . . . . .	219
EvenQ . . . . .	218	Mod . . . . .	219	Quotient . . . . .	220
GCD . . . . .	218	OddQ . . . . .	219	QuotientRemainder . .	220
		PowerMod . . . . .	219		

---

### CoprimeQ

`CoprimeQ[x, y]`  
tests whether  $x$  and  $y$  are coprime by computing their greatest common divisor.

```
>> CoprimeQ[7, 9]
True
>> CoprimeQ[-4, 9]
True
>> CoprimeQ[12, 15]
False
```

CoprimeQ also works for complex numbers

```
>> CoprimeQ[1+2I, 1-I]
True
>> CoprimeQ[4+2I, 6+3I]
True
>> CoprimeQ[2, 3, 5]
True
>> CoprimeQ[2, 4, 5]
False
```

### EvenQ

`EvenQ[x]`  
returns True if  $x$  is even, and False otherwise.

```
>> EvenQ[4]
True
>> EvenQ[-3]
False
>> EvenQ[n]
False
```

### GCD

`GCD[n1, n2, ...]`  
computes the greatest common divisor of the given integers.

```
>> GCD[20, 30]
10
>> GCD[10, y]
GCD[10, y]
GCD is Listable:
>> GCD[4, {10, 11, 12, 13, 14}]
{2, 1, 4, 1, 2}
```

GCD does not work for rational numbers and Gaussian integers yet.

### LCM

`LCM[n1, n2, ...]`  
computes the least common multiple of the given integers.

```
>> LCM[15, 20]
60
>> LCM[20, 30, 40, 50]
600
```

## Mod

```
Mod[x, m]
returns x modulo m.
```

```
>> Mod[14, 6]
2
>> Mod[-3, 4]
1
>> Mod[-3, -4]
-3
>> Mod[5, 0]
The argument 0 should be non zero.
Mod[5, 0]
```

## OddQ

```
OddQ[x]
returns True if x is odd, and False otherwise.
```

```
>> OddQ[-3]
True
>> OddQ[0]
False
```

## PowerMod

```
PowerMod[x, y, m]
computes  $x^y$  modulo m.
```

```
>> PowerMod[2, 10000000, 3]
1
>> PowerMod[3, -2, 10]
9
```

```
>> PowerMod[0, -1, 2]
0 is not invertible modulo 2.
PowerMod[0, -1, 2]
>> PowerMod[5, 2, 0]
The argument 0 should be non zero.
PowerMod[5, 2, 0]
```

PowerMod does not support rational coefficients (roots) yet.

## PrimeQ

```
PrimeQ[n]
returns True if n is a prime number.
```

For very large numbers, PrimeQ uses probabilistic prime testing, so it might be wrong sometimes (a number might be composite even though PrimeQ says it is prime). The algorithm might be changed in the future.

```
>> PrimeQ[2]
True
>> PrimeQ[-3]
True
>> PrimeQ[137]
True
>> PrimeQ[2 ^ 127 - 1]
True
```

All prime numbers between 1 and 100:

```
>> Select[Range[100], PrimeQ]
{2, 3, 5, 7, 11, 13, 17, 19, 23,
 29, 31, 37, 41, 43, 47, 53, 59,
 61, 67, 71, 73, 79, 83, 89, 97}
```

PrimeQ has attribute Listable:

```
>> PrimeQ[Range[20]]
{False, True, True, False, True,
 False, True, False, False, False,
 True, False, True, False, False,
 False, True, False, True, False}
```

## Quotient

`Quotient[m, n]`  
computes the integer quotient of  $m$  and  $n$ .

```
>> Quotient[23, 7]  
3
```

## QuotientRemainder

`QuotientRemainder[m, n]`  
computes a list of the quotient and remainder from division of  $m$  by  $n$ .

```
>> QuotientRemainder[23, 7]  
{3, 2}
```

## 44. Recurrence and Sum Functions

A recurrence relation is an equation that recursively defines a sequence or multidimensional array of values, once one or more initial terms are given; each further term of the sequence or array is defined as a function of the preceding terms.

### Contents

<b>Fibonacci</b> . . . . .	<b>221</b>	<b>HarmonicNumber</b> . . .	<b>221</b>	<b>StirlingS2</b> . . . . .	<b>221</b>
		<b>StirlingS1</b> . . . . .	<b>221</b>		

### Fibonacci

**Fibonacci** $[n]$   
computes the  $n$ th Fibonacci number.

```
>> Fibonacci[0]
0
>> Fibonacci[1]
1
>> Fibonacci[10]
55
>> Fibonacci[200]
280 571 172 992 510 140 037 ~
~611 932 413 038 677 189 525
```

### HarmonicNumber

**HarmonicNumber** $[n]$   
returns the  $n$ th harmonic number.

```
>> Table[HarmonicNumber[n], {n, 8}]
{1, 3/2, 11/6, 25/12, 137/60, 49/20, 363/140, 761/280}
>> HarmonicNumber[3.8]
2.03806
```

### StirlingS1

**StirlingS1** $[n, m]$   
gives the Stirling number of the first kind  
 ${}_n^m$ .

Integer mathematical function, suitable for both symbolic and numerical manipulation. gives the number of permutations of  $n$  elements that contain exactly  $m$  cycles.

```
>> StirlingS1[50, 1]
-608 281 864 034 267 560 872 ~
~252 163 321 295 376 887 552 ~
~831 379 210 240 000 000 000
```

### StirlingS2

**StirlingS2** $[n, m]$   
gives the Stirling number of the second kind  ${}_n^m$ .

returns the number of ways of partitioning a set of  $n$  elements into  $m$  non empty subsets.

```
>> Table[StirlingS2[10, m], {m, 10}]
{1, 511, 9 330, 34 105, 42 525,
22 827, 5 880, 750, 45, 1}
```

## 45. List Functions

S-Expressions make up a core part of Mathics. The parsed and internal representation of an S-Expression is nothing more than a list with possibly nested elements. As a result, there are about a hundred list functions.

## 46. Constructing Lists

Functions for constructing lists of various sizes and structure.

### Contents

<b>Array</b> . . . . .	223	<b>Permutations</b> . . . . .	224	<b>Sow</b> . . . . .	224
<b>ConstantArray</b> . . . . .	223	<b>Range</b> . . . . .	224	<b>Table</b> . . . . .	225
<b>Normal</b> . . . . .	223	<b>Reap</b> . . . . .	224	<b>Tuples</b> . . . . .	225

### Array

**Array**[*f*, *n*]  
returns the *n*-element list {*f*[1], ..., *f*[*n*]}.  
**Array**[*f*, *n*, *a*]  
returns the *n*-element list {*f*[*a*], ..., *f*[*a* + *n*]}.  
**Array**[*f*, {*n*, *m*}, {*a*, *b*}]  
returns an *n*-by-*m* matrix created by applying *f* to indices ranging from (*a*, *b*) to (*a* + *n*, *b* + *m*).  
**Array**[*f*, *dims*, *origins*, *h*]  
returns an expression with the specified dimensions and index origins, with head *h* (instead of List).

```
>> Array[f, 4]
{f[1], f[2], f[3], f[4]}

>> Array[f, {2, 3}]
{{f[1, 1], f[1, 2], f[1, 3]},
 {f[2, 1], f[2, 2], f[2, 3]}}

>> Array[f, {2, 3}, 3]
{{f[3, 3], f[3, 4], f[3, 5]},
 {f[4, 3], f[4, 4], f[4, 5]}}

>> Array[f, {2, 3}, {4, 6}]
{{f[4, 6], f[4, 7], f[4, 8]},
 {f[5, 6], f[5, 7], f[5, 8]}}

>> Array[f, {2, 3}, 1, Plus]
f[1, 1] + f[1, 2] + f[1, 3] + f[2, 1] + f[2, 2] + f[2, 3]
```

### ConstantArray

**ConstantArray**[*expr*, *n*]  
returns a list of *n* copies of *expr*.

```
>> ConstantArray[a, 3]
{a, a, a}

>> ConstantArray[a, {2, 3}]
{{a, a, a}, {a, a, a}}
```

### Normal

**Normal**[*expr*]  
Brings especial expressions to a normal expression from different especial forms.

### Permutations

**Permutations**[*list*]  
gives all possible orderings of the items in *list*.  
**Permutations**[*list*, *n*]  
gives permutations up to length *n*.  
**Permutations**[*list*, {*n*}]  
gives permutations of length *n*.

```
>> Permutations[{y, 1, x}]
{{y, 1, x}, {y, x, 1}, {1, y, x},
 {1, x, y}, {x, y, 1}, {x, 1, y}}
```

Elements are differentiated by their position in *list*, not their value.

```
>> Permutations[{a, b, b}]
{{a,b,b},{a,b,b},{b,a,b},
 {b,b,a},{b,a,b},{b,b,a}}

>> Permutations[{1, 2, 3}, 2]
{{},{1},{2},{3},{1,2},{1,3},
 {2,1},{2,3},{3,1},{3,2}}

>> Permutations[{1, 2, 3}, {2}]
{{1,2},{1,3},{2,1},
 {2,3},{3,1},{3,2}}
```

## Range

`Range[n]`  
returns a list of integers from 1 to  $n$ .  
`Range[a, b]`  
returns a list of integers from  $a$  to  $b$ .

```
>> Range[5]
{1,2,3,4,5}

>> Range[-3, 2]
{-3,-2,-1,0,1,2}

>> Range[0, 2, 1/3]
{0, 1/3, 2/3, 1, 4/3, 5/3, 2}
```

## Reap

`Reap[expr]`  
gives the result of evaluating *expr*, together with all values sown during this evaluation. Values sown with different tags are given in different lists.  
`Reap[expr, pattern]`  
only yields values sown with a tag matching *pattern*. `Reap[expr]` is equivalent to `Reap[expr, _]`.  
`Reap[expr, {pattern1, pattern2, ...}]`  
uses multiple patterns.  
`Reap[expr, pattern, f]`  
applies  $f$  on each tag and the corresponding values sown in the form  $f[\text{tag}, \{e1, e2, \dots\}]$ .

```
>> Reap[Sow[3]; Sow[1]]
{1, {{3,1}}}

>> Reap[Sow[2, {x, x, x}]; Sow[3, x]; Sow[4, y]; Sow[4, 1], {_Symbol, _Integer, x}, f]
{4, {{f[x, {2,2,2,3}], f[y, {4}]}}, {f[1, {4}]}}, {f[x, {2,2,2,3}]}}
```

Find the unique elements of a list, keeping their order:

```
>> Reap[Sow[Null, {a, a, b, d, c, a}], _, # &][[2]]
{a,b,d,c}
```

Sown values are reaped by the innermost matching `Reap`:

```
>> Reap[Reap[Sow[a, x]; Sow[b, 1], _Symbol, Print["Inner: ", #1]&];, _, f]
Inner: x
{Null, {f[1, {b}]}}
```

When no value is sown, an empty list is returned:

```
>> Reap[x]
{x, {}}
```

## Sow

`Sow[e]`  
sends the value  $e$  to the innermost `Reap`.  
`Sow[e, tag]`  
sows  $e$  using *tag*. `Sow[e]` is equivalent to `Sow[e, Null]`.  
`Sow[e, {tag1, tag2, ...}]`  
uses multiple tags.



## Table

`Table[expr, n]`  
generates a list of  $n$  copies of *expr*.  
`Table[expr, {i, n}]`  
generates a list of the values of *expr* when *i* runs from 1 to  $n$ .  
`Table[expr, {i, start, stop, step}]`  
evaluates *expr* with *i* ranging from *start* to *stop*, incrementing by *step*.  
`Table[expr, {i, {e1, e2, ..., ei}}]`  
evaluates *expr* with *i* taking on the values *e1, e2, ..., ei*.

```
>> Table[x, 3]
{x, x, x}

>> n = 0; Table[n = n + 1, {5}]
{1, 2, 3, 4, 5}

>> Table[i, {i, 4}]
{1, 2, 3, 4}

>> Table[i, {i, 2, 5}]
{2, 3, 4, 5}

>> Table[i, {i, 2, 6, 2}]
{2, 4, 6}

>> Table[i, {i, Pi, 2 Pi, Pi / 2}]
{Pi, 3Pi/2, 2Pi}

>> Table[x^2, {x, {a, b, c}}]
{a^2, b^2, c^2}
```

Table supports multi-dimensional tables:

```
>> Table[{i, j}, {i, {a, b}}, {j, 1, 2}]
{{{a, 1}, {a, 2}}, {{b, 1}, {b, 2}}}
```

## Tuples

`Tuples[list, n]`  
returns a list of all  $n$ -tuples of elements in *list*.  
`Tuples[{list1, list2, ...}]`  
returns a list of tuples with elements from the given lists.

```
>> Tuples[{a, b, c}, 2]
{{a, a}, {a, b}, {a, c}, {b, a}, {b, b}, {b, c}, {c, a}, {c, b}, {c, c}}

>> Tuples[{}, 2]
{}

>> Tuples[{a, b, c}, 0]
{{}}

>> Tuples[{{a, b}, {1, 2, 3}}]
{{a, 1}, {a, 2}, {a, 3}, {b, 1}, {b, 2}, {b, 3}}
```

The head of *list* need not be List:

```
>> Tuples[f[a, b, c], 2]
{f[a, a], f[a, b], f[a, c], f[b, a], f[b, b], f[b, c], f[c, a], f[c, b], f[c, c]}
```

However, when specifying multiple expressions, List is always used:

```
>> Tuples[{f[a, b], g[c, d]]}
{{a, c}, {a, d}, {b, c}, {b, d}}
```

## 47. Elements of Lists

Functions for accessing elements of lists using either indices, positions, or patterns of criteria.

### Contents

<b>Append</b> . . . . .	226	<b>FirstCase</b> . . . . .	228	<b>Prepend</b> . . . . .	231
<b>AppendTo</b> . . . . .	226	<b>FirstPosition</b> . . . . .	228	<b>PrependTo</b> . . . . .	231
<b>Cases</b> . . . . .	227	<b>Last</b> . . . . .	228	<b>ReplacePart</b> . . . . .	231
<b>Count</b> . . . . .	227	<b>Length</b> . . . . .	229	<b>Rest</b> . . . . .	231
<b>DeleteCases</b> . . . . .	227	<b>MemberQ</b> . . . . .	229	<b>Select</b> . . . . .	232
<b>Drop</b> . . . . .	227	<b>Most</b> . . . . .	229	<b>Span (;)</b> . . . . .	232
<b>Extract</b> . . . . .	227	<b>Part</b> . . . . .	230	<b>Take</b> . . . . .	232
<b>First</b> . . . . .	228	<b>Pick</b> . . . . .	230		

### Append

`Append[expr, elem]`  
returns *expr* with *elem* appended.

```
>> Append[{1, 2, 3}, 4]
{1, 2, 3, 4}
```

Append works on expressions with heads other than `List`:

```
>> Append[f[a, b], c]
f[a, b, c]
```

Unlike `Join`, `Append` does not flatten lists in *item*:

```
>> Append[{a, b}, {c, d}]
{a, b, {c, d}}
```

### AppendTo

`AppendTo[s, item]`  
append *item* to value of *s* and sets *s* to the result.

```
>> s = {};
>> AppendTo[s, 1]
{1}
```

```
>> s
{1}
```

Append works on expressions with heads other than `List`:

```
>> y = f[];
>> AppendTo[y, x]
f[x]
>> y
f[x]
```

### Cases

`Cases[list, pattern]`  
returns the elements of *list* that match *pattern*.

`Cases[list, pattern, ls]`  
returns the elements matching at level-spec *ls*.

`Cases[list, pattern, Heads->bool]`  
Match including the head of the expression in the search.

```
>> Cases[{a, 1, 2.5, "string"},
_Integer|_Real]
{1, 2.5}
```

```
>> Cases[_Complex][{1, 2I, 3, 4-I,
5}]
{2I, 4 - I}
```

Find symbols among the elements of an expression:

```
>> Cases[{b, 6, \[Pi]}, _Symbol]
{b, Pi}
```

Also include the head of the expression in the previous search:

```
>> Cases[{b, 6, \[Pi]}, _Symbol,
Heads -> True]
{List, b, Pi}
```

## Count

`Count[list, pattern]`  
returns the number of times *pattern* appears in *list*.  
`Count[list, pattern, ls]`  
counts the elements matching at level-spec *ls*.

```
>> Count[{3, 7, 10, 7, 5, 3, 7,
10}, 3]
2
>> Count[{{a, a}, {a, a, a}, a}, a,
{2}]
5
```

## DeleteCases

`DeleteCases[list, pattern]`  
returns the elements of *list* that do not match *pattern*.  
`DeleteCases[list, pattern, levelspec]`  
removes all parts of *list* on levels specified by *levelspec* that match *pattern* (not fully implemented).  
`DeleteCases[list, pattern, levelspec, n]`  
removes the first *n* parts of *list* that match *pattern*.

```
>> DeleteCases[{a, 1, 2.5, "string"}, _Integer|_Real]
{a, string}
```

```
>> DeleteCases[{a, b, 1, c, 2, 3},
_Symbol]
{1, 2, 3}
```

## Drop

`Drop[expr, n]`  
returns *expr* with the first *n* leaves removed.

```
>> Drop[{a, b, c, d}, 3]
{d}
>> Drop[{a, b, c, d}, -2]
{a, b}
>> Drop[{a, b, c, d, e}, {2, -2}]
{a, e}
```

Drop a submatrix:

```
>> A = Table[i*10 + j, {i, 4}, {j, 4}]
{{11, 12, 13, 14}, {21, 22, 23, 24},
{31, 32, 33, 34}, {41, 42, 43, 44}}
>> Drop[A, {2, 3}, {2, 3}]
{{11, 14}, {41, 44}}
```

## Extract

`Extract[expr, list]`  
extracts parts of *expr* specified by *list*.  
`Extract[expr, {list1, list2, ...}]`  
extracts a list of parts.

`Extract[expr, i, j, ...]` is equivalent to `Part[expr, {i, j, ...}]`.

```
>> Extract[a + b + c, {2}]
b
>> Extract[{{a, b}, {c, d}}, {{1},
{2, 2}}]
{{a, b}, d}
```

## First

`First[expr]`  
returns the first element in *expr*.

`First[expr]` is equivalent to `expr[[1]]`.

```
>> First[{a, b, c}]
a
>> First[a + b + c]
a
>> First[x]
Nonatomicexpressionexpected.
First[x]
```

## FirstCase

`FirstCase[{e1, e2, ...}, pattern]`  
gives the first *ei* to match *pattern*, or `$Missing["NotFound"]` if none matching *pattern* is found.

`FirstCase[{e1, e2, ...}, pattern -> rhs]`  
gives the value of *rhs* corresponding to the first *ei* to match *pattern*.

`FirstCase[expr, pattern, default]`  
gives *default* if no element matching *pattern* is found.

`FirstCase[expr, pattern, default, levelspec]`  
finds only objects that appear on levels specified by *levelspec*.

`FirstCase[pattern]`  
represents an operator form of `FirstCase` that can be applied to an expression.

## FirstPosition

`FirstPosition[expr, pattern]`  
gives the position of the first element in *expr* that matches *pattern*, or `Missing["NotFound"]` if no such element is found.

`FirstPosition[expr, pattern, default]`  
gives *default* if no element matching *pattern* is found.

`FirstPosition[expr, pattern, default, levelspec]`  
finds only objects that appear on levels specified by *levelspec*.

```
>> FirstPosition[{a, b, a, a, b, c, b}, b]
{2}
>> FirstPosition[{{a, a, b}, {b, a, a}, {a, b, a}}, b]
{1, 3}
>> FirstPosition[{x, y, z}, b]
Missing[NotFound]
```

Find the first position at which  $x^2$  appears:

```
>> FirstPosition[{1 + x^2, 5, x^4, a + (1 + x^2)^2}, x^2]
{1, 2}
```

## Last

`Last[expr]`  
returns the last element in *expr*.

`Last[expr]` is equivalent to `expr[[-1]]`.

```
>> Last[{a, b, c}]
c
>> Last[x]
Nonatomicexpressionexpected.
Last[x]
```

## Length

`Length[expr]`  
returns the number of leaves in *expr*.

Length of a list:

```
>> Length[{1, 2, 3}]
3
```

`Length` operates on the `FullForm` of expressions:

```
>> Length[Exp[x]]
2
>> FullForm[Exp[x]]
Power[E, x]
```

The length of atoms is 0:

```
>> Length[a]
0
```

Note that rational and complex numbers are atoms, although their `FullForm` might suggest the opposite:

```
>> Length[1/3]
0

>> FullForm[1/3]
Rational[1,3]
```

## MemberQ

`MemberQ[list, pattern]`  
returns `True` if *pattern* matches any element of *list*, or `False` otherwise.

```
>> MemberQ[{a, b, c}, b]
True

>> MemberQ[{a, b, c}, d]
False

>> MemberQ[{"a", b, f[x]}, _?
NumericQ]
False

>> MemberQ[_List][{}]]
True
```

## Most

`Most[expr]`  
returns *expr* with the last element removed.

`Most[expr]` is equivalent to `expr[[;;-2]]`.

```
>> Most[{a, b, c}]
{a,b}

>> Most[a + b + c]
a + b

>> Most[x]
Nonatomicexpressionexpected.
Most[x]
```

## Part

`Part[expr, i]`  
returns part *i* of *expr*.

Extract an element from a list:

```
>> A = {a, b, c, d};

>> A[[3]]
c
```

Negative indices count from the end:

```
>> {a, b, c}][[-2]]
b
```

`Part` can be applied on any expression, not necessarily lists.

```
>> (a + b + c)[[2]]
b
```

`expr[[0]]` gives the head of *expr*:

```
>> (a + b + c)[[0]]
Plus
```

Parts of nested lists:

```
>> M = {{a, b}, {c, d}};

>> M[[1, 2]]
b
```

You can use `Span` to specify a range of parts:

```
>> {1, 2, 3, 4}][[2;;4]]
{2,3,4}

>> {1, 2, 3, 4}][[2;;-1]]
{2,3,4}
```

A list of parts extracts elements at certain indices:

```
>> {a, b, c, d}][[{1, 3, 3}]]
{a,c,c}
```

Get a certain column of a matrix:

```
>> B = {{a, b, c}, {d, e, f}, {g, h, i}};

>> B[[;;, 2]]
{b,e,h}
```

Extract a submatrix of 1st and 3rd row and the two last columns:

```
>> B = {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}};

>> B[[1, 3, -2, -1]]
{{2, 3}, {5, 6}, {8, 9}}
```

```
>> B[{1, 3}, -2;;-1]
{{2,3}, {8,9}}
```

The 3d column of a matrix:

```
>> {{a, b, c}, {d, e, f}, {g, h, i}
    }[[All, 3]]
{c, f, i}
```

Further examples:

```
>> (a+b+c+d)[[-1;;-2]]
0
>> x[[2]]
Partspecificationislongerthandepthofobject.
x[[2]]
```

Assignments to parts are possible:

```
>> B[;;, 2] = {10, 11, 12}
{10,11,12}

>> B
{{1,10,3}, {4,11,6}, {7,12,9}}

>> B[;;, 3] = 13
13

>> B
{{1,10,13}, {4,11,13}, {7,12,13}}

>> B[[1;;-2]] = t;

>> B
{t,t, {7,12,13}}

>> F = Table[i*j*k, {i, 1, 3}, {j,
1, 3}, {k, 1, 3}];

>> F[[;; All, 2 ;; 3, 2]] = t;

>> F
{{{1,2,3}, {2,t,6}, {3,t,9}},
 {{2,4,6}, {4,t,12}, {6,t,18}},
 {{3,6,9}, {6,t,18}, {9,t,27}}}

>> F[[;; All, 1 ;; 2, 3 ;; 3]] = k;

>> F
{{{1,2,k}, {2,t,k}, {3,t,9}},
 {{2,4,k}, {4,t,k}, {6,t,18}},
 {{3,6,k}, {6,t,k}, {9,t,27}}}
```

Of course, part specifications have precedence over most arithmetic operations:

```
>> A[[1]] + B[[2]] + C[[3]] // Hold
// FullForm
Hold[Plus[Part[A,1],
Part[B,2],Part[C,3]]]
```

## Pick

```
Pick[list, sel]
returns those items in list that are True in
sel.
Pick[list, sel, patt]
returns those items in list that match patt
in sel.
```

```
>> Pick[{a, b, c}, {False, True,
False}]
{b}

>> Pick[f[g[1, 2], h[3, 4]], {{True
, False}, {False, True}}]
f[g[1],h[4]]

>> Pick[{a, b, c, d, e}, {1, 2,
3.5, 4, 5.5}, _Integer]
{a,b,d}
```

## Prepend

```
Prepend[expr, item]
returns expr with item prepended to its
leaves.
Prepend[expr]
Prepend[elem][expr] is equivalent to
Prepend[expr,elem].
```

Prepend is similar to Append, but adds *item* to the beginning of *expr*:

```
>> Prepend[{2, 3, 4}, 1]
{1,2,3,4}
```

Prepend works on expressions with heads other than List:

```
>> Prepend[f[b, c], a]
f[a,b,c]
```

Unlike Join, Prepend does not flatten lists in *item*:

```
>> Prepend[{c, d}, {a, b}]
{{a, b}, c, d}
```

## PrependTo

`PrependTo[s, item]`  
prepends *item* to value of *s* and sets *s* to the result.

Assign *s* to a list

```
>> s = {1, 2, 4, 9}
{1, 2, 4, 9}
```

Add a new value at the beginning of the list:

```
>> PrependTo[s, 0]
{0, 1, 2, 4, 9}
```

The value assigned to *s* has changed:

```
>> s
{0, 1, 2, 4, 9}
```

`PrependTo` works with a head other than `List`:

```
>> y = f[a, b, c];

>> PrependTo[y, x]
f[x, a, b, c]

>> y
f[x, a, b, c]
```

## ReplacePart

`ReplacePart[expr, i -> new]`  
replaces part *i* in *expr* with *new*.  
`ReplacePart[expr, {{i, j} -> e1, {k, l} -> e2}]`  
replaces parts *i* and *j* with *e1*, and parts *k* and *l* with *e2*.

```
>> ReplacePart[{a, b, c}, 1 -> t]
{t, b, c}

>> ReplacePart[{{a, b}, {c, d}},
{2, 1} -> t]
{{a, b}, {t, d}}
```

```
>> ReplacePart[{{a, b}, {c, d}},
{{2, 1} -> t, {1, 1} -> t}]
{{t, b}, {t, d}}
```

```
>> ReplacePart[{a, b, c}, {{1},
{2}} -> t]
{t, t, c}
```

Delayed rules are evaluated once for each replacement:

```
>> n = 1;

>> ReplacePart[{a, b, c, d}, {{1},
{3}} :> n++]
{1, b, 2, d}
```

Non-existing parts are simply ignored:

```
>> ReplacePart[{a, b, c}, 4 -> t]
{a, b, c}
```

You can replace heads by replacing part 0:

```
>> ReplacePart[{a, b, c}, 0 ->
Times]
abc
```

(This is equivalent to `Apply`.)

Negative part numbers count from the end:

```
>> ReplacePart[{a, b, c}, -1 -> t]
{a, b, t}
```

## Rest

`Rest[expr]`  
returns *expr* with the first element removed.

`Rest[expr]` is equivalent to `expr[[2; ;]]`.

```
>> Rest[{a, b, c}]
{b, c}

>> Rest[a + b + c]
b + c

>> Rest[x]
Nonatomicexpressionexpected.
Rest[x]
```

## Select

```
Select[{e1, e2, ...}, f]
  returns a list of the elements ei for which
  f[ei] returns True.
```

Find numbers greater than zero:

```
>> Select[{-3, 0, 1, 3, a}, #>0&]
      {1,3}
```

Select works on an expression with any head:

```
>> Select[f[a, 2, 3], NumberQ]
      f[2,3]
```

```
>> Select[a, True]
      Nonatomicexpressionexpected.
      Select[a, True]
```

```
>> Take[{a, b, c, d, e}, {2, -2}]
      {b,c,d}
```

Take a submatrix:

```
>> A = {{a, b, c}, {d, e, f}};
```

```
>> Take[A, 2, 2]
      {{a,b}, {d,e}}
```

Take a single column:

```
>> Take[A, All, {2}]
      {{b}, {e}}
```

## Span (;;)

```
Span
  is the head of span ranges like 1;;3.
```

```
>> ;; // FullForm
      Span[1,All]

>> 1;;4;;2 // FullForm
      Span[1,4,2]

>> 2;;-2 // FullForm
      Span[2, - 2]

>> ;;3 // FullForm
      Span[1,3]
```

## Take

```
Take[expr, n]
  returns expr with all but the first n leaves
  removed.
```

```
>> Take[{a, b, c, d}, 3]
      {a,b,c}
```

```
>> Take[{a, b, c, d}, -2]
      {c,d}
```



## **48. Integer and Number-Theoretical Functions**

# 49. Algebraic Manipulation

## Contents

Apart . . . . .	234	Expand . . . . .	237	MinimalPolynomial . .	239
Cancel . . . . .	234	ExpandAll . . . . .	237	Numerator . . . . .	239
Coefficient . . . . .	235	ExpandDenominator .	237	PolynomialQ . . . . .	239
CoefficientArrays . .	235	Exponent . . . . .	238	PowerExpand . . . . .	239
CoefficientList . . . .	236	Factor . . . . .	238	Simplify . . . . .	240
Collect . . . . .	236	FactorTermsList . . .	238	Together . . . . .	240
Denominator . . . . .	236	FullSimplify . . . . .	238	Variables . . . . .	240

## Apart

`Apart[expr]`  
writes *expr* as a sum of individual fractions.  
`Apart[expr, var]`  
treats *var* as the main variable.

```
>> Apart[1 / (x^2 + 5x + 6)]
```

$$\frac{1}{2+x} - \frac{1}{3+x}$$

When several variables are involved, the results can be different depending on the main variable:

```
>> Apart[1 / (x^2 - y^2), x]
```

$$-\frac{1}{2y(x+y)} + \frac{1}{2y(x-y)}$$

```
>> Apart[1 / (x^2 - y^2), y]
```

$$\frac{1}{2x(x+y)} + \frac{1}{2x(x-y)}$$

`Apart` is Listable:

```
>> Apart[{1 / (x^2 + 5x + 6)}]
```

$$\left\{ \frac{1}{2+x} - \frac{1}{3+x} \right\}$$

But it does not touch other expressions:

```
>> Sin[1 / (x^2 - y^2)] //
Apart
```

$$\text{Sin} \left[ \frac{1}{x^2 - y^2} \right]$$

## Cancel

`Cancel[expr]`  
cancels out common factors in numerators and denominators.

```
>> Cancel[x / x^2]
```

$$\frac{1}{x}$$

`Cancel` threads over sums:

```
>> Cancel[x / x^2 + y / y^2]
```

$$\frac{1}{x} + \frac{1}{y}$$

```
>> Cancel[f[x] / x + x * f[x] / x^2]
```

$$\frac{2f[x]}{x}$$

## Coefficient

`Coefficient[expr, form]`  
returns the coefficient of *form* in the polynomial *expr*.

`Coefficient[expr, form, n]`  
return the coefficient of *form*<sup>*n*</sup> in *expr*.

```
>> Coefficient[(x + y)^4, (x^2)*(y
^2)]
6
>> Coefficient[a x^2 + b y^3 + c x
+ d y + 5, x]
c
>> Coefficient[(x + 3 y)^5, x]
405y^4
>> Coefficient[(x + 3 y)^5, x * y
^4]
405
>> Coefficient[(x + 2)/(y - 3)+ (x
+ 3)/(y - 2), x]
1
-3 + y + 1
-2 + y
>> Coefficient[x*Cos[x + 3] + 6*y,
x]
Cos[3 + x]
>> Coefficient[(x + 1)^3, x, 2]
3
>> Coefficient[a x^2 + b y^3 + c x
+ d y + 5, y, 3]
b
```

Find the free term in a polynomial:

```
>> Coefficient[(x + 2)^3 + (x + 3)
^2, x, 0]
17
>> Coefficient[(x + 2)^3 + (x + 3)
^2, y, 0]
(2 + x)^3 + (3 + x)^2
>> Coefficient[a x^2 + b y^3 + c x
+ d y + 5, x, 0]
5 + by^3 + dy
```

## CoefficientArrays

`CoefficientArrays[polys, vars]`  
returns a list of arrays of coefficients of the variables *vars* in the polynomial *poly*.

```
>> CoefficientArrays[1 + x^3, x]
{1, {0}, {{0}}, {{{1}}}}
>> CoefficientArrays[1 + x y + x^3,
{x, y}]
{1, {0,0}, {{0,1}, {0,0}}, {{{1,
0}, {0,0}}, {{0,0}, {0,0}}}}
>> CoefficientArrays[{1 + x^2, x y
}, {x, y}]
{{1,0}, {{0,0}, {0,0}}, {{{1,
0}, {0,0}}, {{0,1}, {0,0}}}}
>> CoefficientArrays[(x+y+Sin[z])
^3, {x,y}]
{Sin[z]^3, {3Sin[z]^2, 3Sin[
z]^2}, {{3Sin[z], 6Sin[z]},
{0, 3Sin[z]}}, {{{1,3},
{0,3}}, {{0,0}, {0,1}}}}
>> CoefficientArrays[(x + y + Sin[z]
)^3, {x, z}]
(x+y+Sin[z])^3 is not a polynomial in {x,z}
CoefficientArrays[
(x + y + Sin[z])^3, {x,z}]
```

## CoefficientList

`CoefficientList[poly, var]`  
returns a list of coefficients of powers of *var* in *poly*, starting with power 0.  
`CoefficientList[poly, {var1, var2, ...}]`  
returns an array of coefficients of the *vari*.

```
>> CoefficientList[(x + 3)^5, x]
{243, 405, 270, 90, 15, 1}
>> CoefficientList[(x + y)^4, x]
{y^4, 4y^3, 6y^2, 4y, 1}
>> CoefficientList[a x^2 + b y^3 +
c x + d y + 5, x]
{5 + by^3 + dy, c, a}
```

```
>> CoefficientList[(x + 2)/(y - 3) +
  x/(y - 2), x]

$$\left\{ \frac{2}{-3+y}, \frac{1}{-3+y}, \frac{1}{-2+y} \right\}$$

>> CoefficientList[(x + y)^3, z]

$$\{(x+y)^3\}$$

>> CoefficientList[a x^2 + b y^3 +
  c x + d y + 5, {x, y}]

$$\{\{5, d, 0, b\}, \{c, 0, 0, 0\}, \{a, 0, 0, 0\}\}$$

>> CoefficientList[(x - 2 y + 3 z)^
  ^3, {x, y, z}]

$$\{\{0, 0, 0, 27\}, \{0, 0, -54, 0\}, \{0, 36, 0, 0\}, \{-8, 0, 0, 0\}, \{0, 0, 27, 0\}, \{0, -36, 0, 0\}, \{12, 0, 0, 0\}, \{0, 0, 0, 0\}, \{0, 0, 0, 0\}, \{0, 9, 0, 0\}, \{-6, 0, 0, 0\}, \{0, 0, 0, 0\}, \{0, 0, 0, 0\}, \{1, 0, 0, 0\}, \{0, 0, 0, 0\}, \{0, 0, 0, 0\}, \{0, 0, 0, 0\}\}$$

```

## Collect

`Collect[expr, x]`  
 Expands *expr* and collect together terms having the same power of *x*.  
`Collect[expr, {x_1, x_2, ...}]`  
 Expands *expr* and collect together terms having the same powers of *x\_1, x\_2, ...*.  
`Collect[expr, {x_1, x_2, ...}, filter]`  
 After collect the terms, applies *filter* to each coefficient.

```
>> Collect[(x+y)^3, y]

$$x^3 + 3x^2y + 3xy^2 + y^3$$

>> Collect[2 Sin[x z] (x+2 y^2 +
  Sin[y] x), y]

$$2x\sin[xz] + 2x\sin[xz]\sin[y] + 4y^2\sin[xz]$$

>> Collect[3 x y+2 Sin[x z] (x+2 y
  ^2 + x)+ (x+y)^3, y]

$$4x\sin[xz] + x^3 + y(3x + 3x^2) + y^2(3x + 4\sin[xz]) + y^3$$

```

```
>> Collect[3 x y+2 Sin[x z] (x+2 y
  ^2 + x)+ (x+y)^3, {x,y}]

$$4x\sin[xz] + x^3 + 3xy + 3x^2y + 4y^2\sin[xz] + 3xy^2 + y^3$$

>> Collect[3 x y+2 Sin[x z] (x+2 y
  ^2 + x)+ (x+y)^3, {x,y}, h]

$$xh[4\sin[xz]] + x^3h[1] + xyh[3] + x^2yh[3] + y^2h[4\sin[xz]] + xy^2h[3] + y^3h[1]$$

```

## Denominator

`Denominator[expr]`  
 gives the denominator in *expr*.

```
>> Denominator[a / b]
b
>> Denominator[2 / 3]
3
>> Denominator[a + b]
1
```

## Expand

`Expand[expr]`  
 expands out positive integer powers and products of sums in *expr*, as well as trigonometric identities.  
`Expand[expr, target]`  
 just expands those parts involving *target*.

```
>> Expand[(x + y)^ 3]

$$x^3 + 3x^2y + 3xy^2 + y^3$$

>> Expand[(a + b)(a + c + d)]

$$a^2 + ab + ac + ad + bc + bd$$

>> Expand[(a + b)(a + c + d)(e + f)
  + e a a]

$$2a^2e + a^2f + abe + abf + ace + acf + ade + adf + bce + bcf + bde + bdf$$

>> Expand[(a + b)^ 2 * (c + d)]

$$a^2c + a^2d + 2abc + 2abd + b^2c + b^2d$$

```

```
>> Expand[(x + y)^2 + x y]
x^2 + 3xy + y^2

>> Expand[((a + b)(c + d))^2 + b
(1 + a)]
a^2c^2 + 2a^2cd + a^2d^2 + b + ab + 2abc^2
+ 4abcd + 2abd^2 + b^2c^2 + 2b^2cd + b^2d^2

Expand expands items in lists and rules:
>> Expand[{4 (x + y), 2 (x + y) -> 4
(x + y)}]
{4x + 4y, 2x + 2y -> 4x + 4y}
```

Expand expands trigonometric identities

```
>> Expand[Sin[x + y], Trig -> True]
Cos[x] Sin[y] + Cos[y] Sin[x]

>> Expand[Tanh[x + y], Trig -> True]

```

$$\frac{\cosh[x] \sinh[y]}{\cosh[x] \cosh[y] + \sinh[x] \sinh[y]} + \frac{\cosh[y] \sinh[x]}{\cosh[x] \cosh[y] + \sinh[x] \sinh[y]}$$

Expand does not change any other expression.

```
>> Expand[Sin[x (1 + y)]]
Sin[x (1 + y)]
```

Using the second argument, the expression only expands those subexpressions containing *pat*:

```
>> Expand[(x+a)^2+(y+a)^2+(x+y)(x+a), y]
a^2 + 2ay + x(a+x) + y(a+x) + y^2 + (a+x)^2
```

Expand also works in Galois fields

```
>> Expand[(1 + a)^12, Modulus -> 3]
1 + a^3 + a^9 + a^12

>> Expand[(1 + a)^12, Modulus -> 4]
1 + 2a^2 + 3a^4 + 3a^8 + 2a^10 + a^12
```

## ExpandAll

**ExpandAll[*expr*]**  
expands out negative integer powers and products of sums in *expr*.

**ExpandAll[*expr*, *target*]**  
just expands those parts involving *target*.

```
>> ExpandAll[(a + b)^2 / (c + d)^2]
a^2 / (c^2 + 2cd + d^2) + 2ab / (c^2 + 2cd + d^2)
+ b^2 / (c^2 + 2cd + d^2)
```

ExpandAll descends into sub expressions

```
>> ExpandAll[(a + Sin[x (1 + y)])^2]
2a Sin[x + xy] + a^2 + Sin[x + xy]^2

>> ExpandAll[Sin[(x+y)^2]]
Sin[x^2 + 2xy + y^2]

>> ExpandAll[Sin[(x+y)^2], Trig -> True]
-Sin[x^2] Sin[2xy] Sin[y^2] + Cos[x^2] Cos[2xy] Sin[y^2]
+ Cos[x^2] Cos[y^2] Sin[2xy] + Cos[2xy] Cos[y^2] Sin[x^2]
```

ExpandAll also expands heads

```
>> ExpandAll[((1 + x)(1 + y))[x]]
(1 + x + y + xy)[x]
```

ExpandAll can also work in finite fields

```
>> ExpandAll[(1 + a)^6 / (x + y)^3, Modulus -> 3]
(1 + 2a^3 + a^6) / (x^3 + y^3)
```

## ExpandDenominator

**ExpandDenominator[*expr*]**  
expands out negative integer powers and products of sums in *expr*.

```
>> ExpandDenominator[(a + b)^2 / ((c + d)^2 (e + f))]
(a + b)^2 / (c^2e + c^2f + 2cde + 2cdf + d^2e + d^2f)
```

## Exponent

`Exponent[expr, form]`  
returns the maximum power with which *form* appears in the expanded form of *expr*.

`Exponent[expr, form, h]`  
applies *h* to the set of exponents with which *form* appears in *expr*.

```
>> Exponent[5 x^2 - 3 x + 7, x]
2

>> Exponent[(x^3 + 1)^2 + 1, x]
6

>> Exponent[x^(n + 1) + Sqrt[x] + 1, x]
Max  $\left[\frac{1}{2}, 1 + n\right]$ 

>> Exponent[x / y, y]
-1

>> Exponent[(x^2 + 1)^3 - 1, x, Min]
2

>> Exponent[0, x]
-∞

>> Exponent[1, x]
0
```

## Factor

`Factor[expr]`  
factors the polynomial expression *expr*.

```
>> Factor[x^2 + 2 x + 1]
(1 + x)^2

>> Factor[1 / (x^2 + 2x + 1) + 1 / (x^4 + 2x^2 + 1)]

$$\frac{2 + 2x + 3x^2 + x^4}{(1 + x)^2 (1 + x^2)^2}$$

```

## FactorTermsList

`FactorTermsList[poly]`  
returns a list of 2 elements. The first element is the numerical factor in *poly*. The second one is the remaining of the polynomial with numerical factor removed

`FactorTermsList[poly, {x1, x2, ...}]`  
returns a list of factors in *poly*. The first element is the numerical factor in *poly*. The next ones are factors that are independent of variables lists which are created by removing each variable *xi* from right to left. The last one is the remaining of polynomial after dividing *poly* to all previous factors

```
>> FactorTermsList[2 x^2 - 2]
{2, -1 + x^2}

>> FactorTermsList[x^2 - 2 x + 1]
{1, 1 - 2x + x^2}

>> f = 3 (-1 + 2 x) (-1 + y) (1 - a)
3 (-1 + 2x) (-1 + y) (1 - a)

>> FactorTermsList[f]
{-3, -1 + a - 2ax - ay + 2x + y - 2xy + 2axy}

>> FactorTermsList[f, x]
{-3, 1 - a - y + ay, -1 + 2x}
```

## FullSimplify

`FullSimplify[expr]`  
simplifies *expr* using an extended set of simplification rules.

`FullSimplify[expr, assump]`  
simplifies *expr* assuming *assump* instead of *Assumptions*.

TODO: implement the extension. By now, this

does the same than Simplify...

```
>> FullSimplify[2*Sin[x]^2 + 2*Cos[x]^2]
2
```

## MinimalPolynomial

`MinimalPolynomial[s, x]`  
gives the minimal polynomial in  $x$  for which the algebraic number  $s$  is a root.

```
>> MinimalPolynomial[7, x]
-7 + x

>> MinimalPolynomial[Sqrt[2] + Sqrt[3], x]
1 - 10x2 + x4

>> MinimalPolynomial[Sqrt[1 + Sqrt[3]], x]
-2 - 2x2 + x4

>> MinimalPolynomial[Sqrt[I + Sqrt[6]], x]
49 - 10x4 + x8
```

## Numerator

`Numerator[expr]`  
gives the numerator in  $expr$ .

```
>> Numerator[a / b]
a

>> Numerator[2 / 3]
2

>> Numerator[a + b]
a + b
```

## PolynomialQ

`PolynomialQ[expr, var]`  
returns True if  $expr$  is a polynomial in  $var$ , and returns False otherwise.  
`PolynomialQ[expr, {var1, ...}]`  
tests whether  $expr$  is a polynomial in the  $vari$ .

```
>> PolynomialQ[x3 - 2 x/y + 3xz, x]
True
```

```
>> PolynomialQ[x3 - 2 x/y + 3xz, y]
False

>> PolynomialQ[f[a] + f[a]2, f[a]]
True

>> PolynomialQ[x2 + axy2 - bSin[c], {x, y}]
True

>> PolynomialQ[x2 + axy2 - bSin[c], {a, b, c}]
False
```

## PowerExpand

`PowerExpand[expr]`  
expands out powers of the form  $(x^y)^z$  and  $(x*y)^z$  in  $expr$ .

```
>> PowerExpand[(a ^ b) ^ c]
abc

>> PowerExpand[(a * b) ^ c]
acbc
```

`PowerExpand` is not correct without certain assumptions:

```
>> PowerExpand[(x ^ 2) ^ (1/2)]
x
```

## Simplify

`Simplify[expr]`  
simplifies  $expr$ .  
`Simplify[expr, assump]`  
simplifies  $expr$  assuming  $assump$  instead of *Assumptions*.

```
>> Simplify[2*Sin[x]2 + 2*Cos[x]2]
2

>> Simplify[x]
x

>> Simplify[f[x]]
f[x]
```

Simplify over conditional expressions uses `$Assumptions`, or *assump* to evaluate the condition: # TODO: enable this once the logic for conditional expression # be restored. # » `$Assumptions={a <= 0};` # » `Simplify[ConditionalExpression[1, a > 0]]` # = Undefined # » `Simplify[ConditionalExpression[1, a > 0], {a > 0}]` # = 1

## Together

`Together[expr]`  
writes sums of fractions in *expr* together.

```
>> Together[a / c + b / c]
```

$$\frac{a + b}{c}$$

Together operates on lists:

```
>> Together[{x / (y+1)+ x / (y+1)^2}]
```

$$\left\{ \frac{x(2+y)}{(1+y)^2} \right\}$$

But it does not touch other functions:

```
>> Together[f[a / c + b / c]]
```

$$f\left[\frac{a}{c} + \frac{b}{c}\right]$$

## Variables

`Variables[expr]`  
gives a list of the variables that appear in the polynomial *expr*.

```
>> Variables[a x^2 + b x + c]
```

$$\{a, b, c, x\}$$

```
>> Variables[{a + b x, c y^2 + x / 2}]
```

$$\{a, b, c, x, y\}$$

```
>> Variables[x + Sin[y]]
```

$$\{x, \text{Sin}[y]\}$$



# 50. Calculus

## Contents

Complexes . . . . .	241	Integers . . . . .	243	Root . . . . .	244
D . . . . .	242	Integrate . . . . .	244	Series . . . . .	245
Derivative (') . . . . .	242	Limit . . . . .	244	SeriesData . . . . .	245
DiscreteLimit . . . . .	242	O . . . . .	244	Solve . . . . .	246
FindRoot . . . . .	243	Reals . . . . .	244		

## Complexes

Complexes  
is the set of complex numbers.

## D

$D[f, x]$   
gives the partial derivative of  $f$  with respect to  $x$ .  
 $D[f, x, y, \dots]$   
differentiates successively with respect to  $x, y$ , etc.  
 $D[f, \{x, n\}]$   
gives the multiple derivative of order  $n$ .  
 $D[f, \{x1, x2, \dots\}]$   
gives the vector derivative of  $f$  with respect to  $x1, x2$ , etc.

First-order derivative of a polynomial:

```
>> D[x^3 + x^2, x]
2x + 3x^2
```

Second-order derivative:

```
>> D[x^3 + x^2, {x, 2}]
2 + 6x
```

Trigonometric derivatives:

```
>> D[Sin[Cos[x]], x]
-Cos[Cos[x]] Sin[x]

>> D[Sin[x], {x, 2}]
-Sin[x]
```

```
>> D[Cos[t], {t, 2}]
-Cos[t]
```

Unknown variables are treated as constant:

```
>> D[y, x]
0
```

```
>> D[x, x]
1
```

```
>> D[x + y, x]
1
```

Derivatives of unknown functions are represented using Derivative:

```
>> D[f[x], x]
f'[x]
```

```
>> D[f[x, x], x]
f^(0,1)[x, x] + f^(1,0)[x, x]
```

```
>> D[f[x, x], x] // InputForm
Derivative[0, 1][f][x, x]
+ Derivative[1, 0][f][x, x]
```

Chain rule:

```
>> D[f[2x+1, 2y, x+y], x]
2f^(1,0,0)[1 + 2x, 2y,
x + y] + f^(0,0,1)[1 + 2x, 2y, x + y]
```

```
>> D[f[x^2, x, 2y], {x,2}, y] //
Expand
```

$$8x f^{(1,1,1)}[x^2, x, 2y] + 8x^2 f^{(2,0,1)}[x^2, x, 2y] + 2f^{(0,2,1)}[x^2, x, 2y] + 4f^{(1,0,1)}[x^2, x, 2y]$$

Compute the gradient vector of a function:

```
>> D[x ^ 3 * Cos[y], {{x, y}}]
{3x^2 Cos[y], -x^3 Sin[y]}
```

Hesse matrix:

```
>> D[Sin[x] * Cos[y], {{x,y}, 2}]
{{{-Cos[y] Sin[x], -Cos[x] Sin[y]}, {-Cos[x] Sin[y], -Cos[y] Sin[x]}}
```

## Derivative (')

`Derivative[n][f]`  
represents the  $n$ th derivative of the function  $f$ .  
`Derivative[n1, n2, ...][f]`  
represents a multivariate derivative.

```
>> Derivative[1][Sin]
Cos[#1]&
```

```
>> Derivative[3][Sin]
-Cos[#1]&
```

```
>> Derivative[2][# ^ 3&]
6#1&
```

Derivative can be entered using ':

```
>> Sin'[x]
Cos[x]
```

```
>> (# ^ 4&)'
12#1^2&
```

```
>> f'[x] // InputForm
Derivative[1][f][x]
```

```
>> Derivative[1][#2 Sin[#1]+Cos
[#2]&]
Cos[#1]#2&
```

```
>> Derivative[1,2][#2^3 Sin[#1]+Cos
[#2]&]
6Cos[#1]#2&
```

Deriving with respect to an unknown parameter yields 0:

```
>> Derivative[1,2,1][#2^3 Sin[#1]+
Cos[#2]&]
0&
```

The 0th derivative of any expression is the expression itself:

```
>> Derivative[0,0,0][a+b+c]
a + b + c
```

You can calculate the derivative of custom functions:

```
>> f[x_] := x ^ 2
f'[x]
2x
```

Unknown derivatives:

```
>> Derivative[2, 1][h]
h^(2,1)
>> Derivative[2, 0, 1, 0][h[g]]
h[g]^(2,0,1,0)
```

## DiscreteLimit

`DiscreteLimit[f, k->Infinity]`  
gives the limit of the sequence  $f$  as  $k$  tends to infinity.

```
>> DiscreteLimit[n/(n + 1), n ->
Infinity]
1
```

```
>> DiscreteLimit[f[n], n ->
Infinity]
f[∞]
```

## FindRoot

`FindRoot[f, {x, x0}]`  
 searches for a numerical root of  $f$ , starting from  $x=x0$ .  
`FindRoot[lhs == rhs, {x, x0}]`  
 tries to solve the equation  $lhs == rhs$ .

`FindRoot` by default uses Newton's method, so the function of interest should have a first derivative.

```
>> FindRoot[Cos[x], {x, 1}]
{x -> 1.5708}

>> FindRoot[Sin[x] + Exp[x], {x, 0}]
{x -> -0.588533}

>> FindRoot[Sin[x] + Exp[x] == Pi, {x, 0}]
{x -> 0.866815}
```

`FindRoot` has attribute `HoldAll` and effectively uses `Block` to localize  $x$ . However, in the result  $x$  will eventually still be replaced by its value.

```
>> x = "I am the result!";

>> FindRoot[Tan[x] + Sin[x] == Pi, {x, 1}]
{I am the result! -> 1.14911}

>> Clear[x]
```

`FindRoot` stops after 100 iterations:

```
>> FindRoot[x^2 + x + 1, {x, 1}]
The maximum number of iterations was exceeded. The result might be inaccurate.
{x -> -1.}
```

Find complex roots:

```
>> FindRoot[x^2 + x + 1, {x, -I}]
{x -> -0.5 - 0.866025I}
```

The function has to return numerical values:

```
>> FindRoot[f[x] == 0, {x, 0}]
The function value is not a number at x = 0..
FindRoot[f[x] - 0, {x, 0}]
```

The derivative must not be 0:

```
>> FindRoot[Sin[x] == x, {x, 0}]
Encountered a singular derivative at the point x = 0..
FindRoot[Sin[x] - x, {x, 0}]
```

```
>> FindRoot[x^2 - 2, {x, 1.3},
Method->"Secant"]
{x -> 1.41421}
```

## Integers

`Integers`  
 is the set of integer numbers.

Limit a solution to integer numbers:

```
>> Solve[-4 - 4 x + x^4 + x^5 == 0,
x, Integers]
{{x -> -1}}

>> Solve[x^4 == 4, x, Integers]
{}
```

## Integrate

`Integrate[f, x]`  
 integrates  $f$  with respect to  $x$ . The result does not contain the additive integration constant.  
`Integrate[f, {x, a, b}]`  
 computes the definite integral of  $f$  with respect to  $x$  from  $a$  to  $b$ .

Integrate a polynomial:

```
>> Integrate[6 x^2 + 3 x^2 - 4
x + 10, x]
x (10 - 2x + 3x^2)
```

Integrate trigonometric functions:

```
>> Integrate[Sin[x]^5, x]
-Cos[x] - Cos[x]^5/5 + 2Cos[x]^3/3
```

Definite integrals:

```
>> Integrate[x^2 + x, {x, 1, 3}]
38/3

>> Integrate[Sin[x], {x, 0, Pi/2}]
1
```

Some other integrals:

```
>> Integrate[1 / (1 - 4 x + x^2), x]
```

$$\frac{\sqrt{3} \left( \log \left[ -2 - \sqrt{3} + x \right] - \log \left[ -2 + \sqrt{3} + x \right] \right)}{6}$$

```
>> Integrate[4 Sin[x] Cos[x], x]
2Sin[x]^2
```

Integration in TeX:

```
>> Integrate[f[x], {x, a, b}] //
TeXForm
\int_a^b f\left[x\right] \, dx
```

Sometimes there is a loss of precision during integration. You can check the precision of your result with the following sequence of commands.

```
>> Integrate[Abs[Sin[phi]], {phi,
0, 2Pi}] // N
4.
% // Precision
MachinePrecision
>> Integrate[ArcSin[x / 3], x]
xArcSin[x/3] + sqrt(9 - x^2)
>> Integrate[f'[x], {x, a, b}]
f[b] - f[a]
```

## Limit

`Limit[expr, x->x0]`  
gives the limit of *expr* as *x* approaches *x0*.  
`Limit[expr, x->x0, Direction->1]`  
approaches *x0* from smaller values.  
`Limit[expr, x->x0, Direction->-1]`  
approaches *x0* from larger values.

```
>> Limit[x, x->2]
2
>> Limit[Sin[x] / x, x->0]
1
>> Limit[1/x, x->0, Direction->-1]
∞
>> Limit[1/x, x->0, Direction->1]
-∞
```

## O

`O[x]^n`  
Represents a term of order  $x^n$ .  
`O[x]^n` is generated to represent omitted higher order terms in power series.

```
>> Series[1/(1-x), {x, 0, 2}]
1 + x + x^2 + O[x]^3
```

## Reals

`Reals`  
is the set of real numbers.

Limit a solution to real numbers:

```
>> Solve[x^3 == 1, x, Reals]
{{x -> 1}}
```

## Root

`Root[f, i]`  
represents the *i*-th complex root of the polynomial *f*

```
>> Root[#1^2 - 1&, 1]
-1
>> Root[#1^2 - 1&, 2]
1
```

Roots that can't be represented by radicals:

```
>> Root[#1^5 + 2 #1 + 1&, 2]
Root[#1^5 + 2 #1 + 1&, 2]
```

## Series

`Series[f, {x, x0, n}]`  
Represents the series expansion around  $x=x0$  up to order *n*.

```
>> Series[Exp[x], {x, 0, 2}]
1 + x + 1/2 x^2 + O[x]^3
```

```
>> Series[Exp[x^2], {x, 0, 2}]
1 + x^2 + O[x]^3
```

## SeriesData

```
SeriesData[...]
```

Represents a series expansion

TODO: - Implement sum, product and composition of series

## Solve

```
Solve[equation, vars]
  attempts to solve equation for the variables vars.
Solve[equation, vars, domain]
  restricts variables to domain, which can be Complexes or Reals or Integers.
```

```
>> Solve[x^2 - 3 x == 4, x]
{{x -> -1}, {x -> 4}}
```

```
>> Solve[4 y - 8 == 0, y]
{{y -> 2}}
```

Apply the solution:

```
>> sol = Solve[2 x^2 - 10 x - 12 == 0, x]
{{x -> -1}, {x -> 6}}
>> x /. sol
{-1, 6}
```

Contradiction:

```
>> Solve[x + 1 == x, x]
{}
```

Tautology:

```
>> Solve[x^2 == x^2, x]
{{}}
```

Rational equations:

```
>> Solve[x / (x^2 + 1) == 1, x]
{{x -> 1/2 - I/2 Sqrt[3]},
 {x -> 1/2 + I/2 Sqrt[3]}}
```

```
>> Solve[(x^2 + 3 x + 2)/(4 x - 2) == 0, x]
{{x -> -2}, {x -> -1}}
```

Transcendental equations:

```
>> Solve[Cos[x] == 0, x]
{{x -> Pi/2}, {x -> 3Pi/2}}
```

Solve can only solve equations with respect to symbols or functions:

```
>> Solve[f[x + y] == 3, f[x + y]]
{{f[x + y] -> 3}}
```

```
>> Solve[a + b == 2, a + b]
a + b is not a valid variable.
Solve[a + b == 2, a + b]
```

This happens when solving with respect to an assigned symbol:

```
>> x = 3;
>> Solve[x == 2, x]
3 is not a valid variable.
Solve[False, 3]
```

```
>> Clear[x]
```

```
>> Solve[a < b, a]
a < b is not a well-formed equation.
Solve[a < b, a]
```

Solve a system of equations:

```
>> eqs = {3 x^2 - 3 y == 0, 3 y^2 - 3 x == 0};
```

```
>> sol = Solve[eqs, {x, y}] //
Simplify
```

$$\left\{ \left\{ x - > 0, y - > 0 \right\}, \left\{ x - > 1, \right. \right. \\ \left. \left. y - > 1 \right\}, \left\{ x - > -\frac{1}{2} + \frac{I}{2}\sqrt{3}, \right. \right. \\ \left. \left. y - > -\frac{1}{2} - \frac{I}{2}\sqrt{3} \right\}, \right. \\ \left. \left\{ x - > \frac{(1 - I\sqrt{3})^2}{4}, \right. \right. \\ \left. \left. y - > -\frac{1}{2} + \frac{I}{2}\sqrt{3} \right\} \right\}$$

```
>> eqs /. sol // Simplify
{{True, True}, {True, True},
 {True, True}, {True, True}}
```

An underdetermined system:

```
>> Solve[x^2 == 1 && z^2 == -1, {x,
y, z}]
```

*Equations may not give solutions for all "solve" variables.*

$$\{\{x - > -1, z - > -I\}, \\ \{x - > -1, z - > I\}, \{x - > 1, \\ z - > -I\}, \{x - > 1, z - > I\}\}$$

Domain specification:

```
>> Solve[x^2 == -1, x, Reals]
{}
```

```
>> Solve[x^2 == 1, x, Reals]
{{x - > -1}, {x - > 1}}
```

```
>> Solve[x^2 == -1, x, Complexes]
{{x - > -I}, {x - > I}}
```

```
>> Solve[4 - 4 * x^2 - x^4 + x^6 ==
0, x, Integers]
{{x - > -1}, {x - > 1}}
```

# 51. Mathematical Constants

Numeric, Arithmetic, or Symbolic constants like Pi, E, or Infinity.

## Contents

Catalan . . . . .	247	EulerGamma . . . . .	248	Infinity . . . . .	248
ComplexInfinity . . . . .	247	Glaisher . . . . .	248	Khinchin . . . . .	248
Degree . . . . .	247	GoldenRatio . . . . .	248	Pi . . . . .	248
E . . . . .	247	Indeterminate . . . . .	248		

## Catalan

Catalan  
is Catalan's constant with numerical value  $\simeq 0.915966$ .

```
>> Catalan // N
0.915965594177219
>> N[Catalan, 20]
0.91596559417721901505
```

## ComplexInfinity

ComplexInfinity  
represents an infinite complex quantity of undetermined direction.

```
>> 1 / ComplexInfinity
0
>> ComplexInfinity * Infinity
ComplexInfinity
>> FullForm[ComplexInfinity]
DirectedInfinity[]
```

## Degree

Degree  
is the number of radians in one degree. It has a numerical value of  $\pi / 180$ .

```
>> Cos[60 Degree]
1/2
Degree has the value of Pi / 180
>> Degree == Pi / 180
True
>> N[\[Degree]] == N[Degree]
True
```

## E

E  
is the constant e with numerical value  $\simeq 2.71828$ .

```
>> N[E]
2.71828
>> N[E, 50]
2.718281828459045235360287~
~4713526624977572470937000
```

## EulerGamma

EulerGamma  
is Euler's constant  $\gamma$  with numerical value  $\simeq 0.577216$ .

```
>> EulerGamma // N
0.577216
```

```
>> N[EulerGamma, 40]
0.577215664901532860~
~6065120900824024310422
```

## Glaisher

Glaisher  
is Glaisher's constant, with numerical  
value  $\simeq 1.28243$ .

```
>> N[Glaisher]
1.28242712910062

>> N[Glaisher, 50]
1.282427129100622636875342~
~5688697917277676889273250
```

```
# 1.2824271291006219541941391071304678916931152343750
```

## GoldenRatio

GoldenRatio  
is the golden ratio,  $= (1+\text{Sqrt}[5])/2$ .

```
>> GoldenRatio // N
1.61803398874989

>> N[GoldenRatio, 40]
1.618033988749894848~
~204586834365638117720
```

## Indeterminate

Indeterminate  
represents an indeterminate result.

```
>> 0^0
Indeterminateexpression00encountered.
Indeterminate

>> Tan[Indeterminate]
Indeterminate
```

## Infinity

Infinity  
represents an infinite real quantity.

```
>> 1 / Infinity
0

>> Infinity + 100
∞
```

Use Infinity in sum and limit calculations:

```
>> Sum[1/x^2, {x, 1, Infinity}]

$$\frac{\text{Pi}^2}{6}$$

```

## Khinchin

Khinchin  
is Khinchin's constant, with numerical  
value  $\simeq 2.68545$ .

```
>> N[Khinchin]
2.68545200106531

>> N[Khinchin, 50]
2.685452001065306445309714~
~8354817956938203822939945

# = 2.6854520010653075701156922150403261184692382812500
```

## Pi

Pi  
is the constant  $\pi$ .

```
>> N[Pi]
3.14159
```

Pi to a numeric precision of 20 digits:

```
>> N[Pi, 20]
3.1415926535897932385
```

Note that the above is not the same thing as the number of digits *after* the decimal point. This may differ from similar concepts from other mathematical libraries, including those which Mathics uses!

Use numpy to compute Pi to 20 digits:

```
>> N[Pi, 20, Method->"numpy"]
3.1415926535897930000
```

"sympy" is the default method.

```
>> Attributes[Pi]
{Constant, Protected, ReadProtected}
```



## 52. Differential Equations

### Contents

---

C . . . . .	249	DSolve . . . . .	249
-------------	-----	------------------	-----

---

### C

`C[n]`

represents the  $n$ th constant in a solution to a differential equation.

```
>> DSolve[D[y[x, t], t] + 2 D[y[x,
t], x] == 0, y[x, t], {x, t}]
{{y[x, t] -> C[1][x - 2t]}}
```

### DSolve

`DSolve[eq, y[x], x]`

solves a differential equation for the function  $y[x]$ .

```
>> DSolve[y''[x] == 0, y[x], x]
{{y[x] -> x C[2] + C[1]}}

>> DSolve[y''[x] == y[x], y[x], x]
{{y[x] -> C[1] E^-x + C[2] E^x}}

>> DSolve[y''[x] == y[x], y, x]
{{y -> (Function[{x},
C[1] E^-x + C[2] E^x])}}
```

DSolve can also solve basic PDE

```
>> DSolve[D[f[x, y], x] / f[x, y] +
3 D[f[x, y], y] / f[x, y] == 2,
f, {x, y}]
{{f -> (Function[{x, y},
E^(x/5 + 3y/5) C[1][3x - y])}]}
```

```
>> DSolve[D[f[x, y], x] x + D[f[x,
y], y] y == 2, f[x, y], {x, y}]
{{f[x, y] -> 2 Log[x] + C[1][y/x]}}
```

## 53. Exponential, Trigonometric and Hyperbolic Functions

*Mathics* basically supports all important trigonometric and hyperbolic functions.

Numerical values and derivatives can be computed; however, most special exact values and simplification rules are not implemented yet.

### Contents

---

<b>AnglePath</b> . . . . .	251	<b>ArcSinh</b> . . . . .	253	<b>InverseHaversine</b> . . .	254
<b>AngleVector</b> . . . . .	251	<b>ArcTan</b> . . . . .	253	<b>Log</b> . . . . .	254
<b>ArcCos</b> . . . . .	251	<b>ArcTanh</b> . . . . .	253	<b>Log10</b> . . . . .	255
<b>ArcCosh</b> . . . . .	252	<b>Cos</b> . . . . .	253	<b>Log2</b> . . . . .	255
<b>ArcCot</b> . . . . .	252	<b>Cosh</b> . . . . .	253	<b>LogisticSigmoid</b> . . .	255
<b>ArcCoth</b> . . . . .	252	<b>Cot</b> . . . . .	253	<b>Sec</b> . . . . .	255
<b>ArcCsc</b> . . . . .	252	<b>Coth</b> . . . . .	253	<b>Sech</b> . . . . .	255
<b>ArcCsch</b> . . . . .	252	<b>Csc</b> . . . . .	254	<b>Sin</b> . . . . .	256
<b>ArcSec</b> . . . . .	252	<b>Csch</b> . . . . .	254	<b>Sinh</b> . . . . .	256
<b>ArcSech</b> . . . . .	252	<b>Exp</b> . . . . .	254	<b>Tan</b> . . . . .	256
<b>ArcSin</b> . . . . .	253	<b>Haversine</b> . . . . .	254	<b>Tanh</b> . . . . .	256

---

### AnglePath

**AnglePath**[*{phi1, phi2, ...}*]  
 returns the points formed by a turtle starting at {0, 0} and angled at 0 degrees going through the turns given by angles *phi1, phi2, ...* and using distance 1 for each step.

**AnglePath**[*{{r1, phi1}, {r2, phi2}, ...}*]  
 instead of using 1 as distance, use *r1, r2, ...* as distances for the respective steps.

**AngleVector**[*phi0, {phi1, phi2, ...}*]  
 returns the points on a path formed by a turtle starting with direction *phi0* instead of 0.

**AngleVector**[*{x, y}, {phi1, phi2, ...}*]  
 returns the points on a path formed by a turtle starting at {*x, y*} instead of {0, 0}.

**AngleVector**[*{{x, y}, phi0}, {phi1, phi2, ...}*]  
 specifies initial position {*x, y*} and initial direction *phi0*.

**AngleVector**[*{{x, y}, {dx, dy}}, {phi1, phi2, ...}*]  
 specifies initial position {*x, y*} and a slope {*dx, dy*} that is understood to be the initial direction of the turtle.


```
>> AnglePath[{90 Degree, 90 Degree,
  90 Degree, 90 Degree}]
{{0,0}, {0,1}, {-1,
  1}, {-1,0}, {0,0}}

>> AnglePath[{{1, 1}, 90 Degree},
  {{1, 90 Degree}, {2, 90 Degree},
  {1, 90 Degree}, {2, 90 Degree
  }}]
{{1,1}, {0,1}, {0,
  -1}, {1, -1}, {1,1}}

>> AnglePath[{a, b}]
{{0,0}, {Cos[a], Sin[a]}, {Cos[
  a]+Cos[a+b], Sin[a]+Sin[a+b]}}

>> Precision[Part[AnglePath[{N[1/3,
  100], N[2/3, 100]}], 2, 1]]
100.

>> Graphics[Line[AnglePath[Table
  [1.7, {50}]]]]
```



```
>> Graphics[Line[AnglePath[
  RandomReal[{-1, 1}, {100}]]]]
```



## AngleVector

`AngleVector[phi]`  
returns the point at angle  $\phi$  on the unit circle.

`AngleVector[{r, phi}]`  
returns the point at angle  $\phi$  on a circle of radius  $r$ .

`AngleVector[{x, y}, phi]`  
returns the point at angle  $\phi$  on a circle of radius 1 centered at  $\{x, y\}$ .

`AngleVector[{x, y}, {r, phi}]`  
returns point at angle  $\phi$  on a circle of radius  $r$  centered at  $\{x, y\}$ .

```
>> AngleVector[90 Degree]
{0, 1}

>> AngleVector[{1, 10}, a]
{1 + Cos[a], 10 + Sin[a]}
```

## ArcCos

`ArcCos[z]`  
returns the inverse cosine of  $z$ .

```
>> ArcCos[1]
0

>> ArcCos[0]
Pi/2

>> Integrate[ArcCos[x], {x, -1, 1}]
Pi
```

## ArcCosh

`ArcCosh[z]`  
returns the inverse hyperbolic cosine of  $z$ .

```
>> ArcCosh[0]
I/2 Pi

>> ArcCosh[0.]
0. + 1.5708 I
```

## ArcCot

## ArcCoth

## ArcCsc

## ArcCsch

## ArcSec

## ArcSech

## ArcSin

```
>> ArcSin[1]
      Pi
      2
```

## ArcSinh

`ArcSinh[z]`  
returns the inverse hyperbolic sine of z.

```
>> ArcSinh[0]
0

>> ArcSinh[0.]
0.

>> ArcSinh[1.0]
0.881374
```

## ArcTan

`ArcTan[z]`  
returns the inverse tangent of z.

```
>> ArcTan[1]
      Pi
      4

>> ArcTan[1.0]
0.785398

>> ArcTan[-1.0]
-0.785398

>> ArcTan[1, 1]
      Pi
      4
```

## ArcTanh

`ArcTanh[z]`  
returns the inverse hyperbolic tangent of z.

```
>> ArcTanh[0]
0

>> ArcTanh[1]
∞

>> ArcTanh[0]
0
```

```
>> ArcTanh[.5 + 2 I]
0.0964156 + 1.12656 I

>> ArcTanh[2 + I]
ArcTanh[2 + I]
```

## Cos

`Cos[z]`  
returns the cosine of z.

```
>> Cos[3 Pi]
-1
```

## Cosh

`Cosh[z]`  
returns the hyperbolic cosine of z.

```
>> Cosh[0]
1
```

## Cot

`Cot[z]`  
returns the cotangent of z.

```
>> Cot[0]
ComplexInfinity

>> Cot[1.]
0.642093
```

## Coth

`Coth[z]`  
returns the hyperbolic cotangent of z.

```
>> Coth[0]
ComplexInfinity
```

## Csc

**Csc[z]**  
returns the cosecant of z.

```
>> Csc[0]
ComplexInfinity

>> Csc[1] (* Csc[1] in Mathematica *)

$$\frac{1}{\sin[1]}$$


>> Csc[1.]
1.1884
```

## Csch

**Csch[z]**  
returns the hyperbolic cosecant of z.

```
>> Csch[0]
ComplexInfinity
```

## Exp


**Exp[z]**  
returns the exponential function of z.

```
>> Exp[1]
E

>> Exp[10.0]
22026.5

>> Exp[x] //FullForm
Power[E, x]

>> Plot[Exp[x], {x, 0, 3}]
```



## Haversine

**Haversine[z]**  
returns the haversine function of z.

```
>> Haversine[1.5]
0.464631

>> Haversine[0.5 + 2I]
-1.15082 + 0.869405I
```

## InverseHaversine

**InverseHaversine[z]**  
returns the inverse haversine function of z.

```
>> InverseHaversine[0.5]
1.5708

>> InverseHaversine[1 + 2.5 I]
1.76459 + 2.33097I
```


## Log

**Log[z]**  
returns the natural logarithm of z.

```
>> Log[{0, 1, E, E * E, E ^ 3, E ^ x}]
{-∞, 0, 1, 2, 3, Log[E^x]}

>> Log[0.]
Indeterminate

>> Plot[Log[x], {x, 0, 5}]
```



## Log10

`Log10[z]`  
returns the base-10 logarithm of  $z$ .

```
>> Log10[1000]
3
>> Log10[{2., 5.}]
{0.30103, 0.69897}
>> Log10[E ^ 3]
 $\frac{3}{\text{Log}[10]}$ 
```

## Log2

`Log2[z]`  
returns the base-2 logarithm of  $z$ .

```
>> Log2[4 ^ 8]
16
>> Log2[5.6]
2.48543
>> Log2[E ^ 2]
 $\frac{2}{\text{Log}[2]}$ 
```

## LogisticSigmoid

`LogisticSigmoid[z]`  
returns the logistic sigmoid of  $z$ .

```
>> LogisticSigmoid[0.5]
0.622459
>> LogisticSigmoid[0.5 + 2.3 I]
1.06475 + 0.808177I
>> LogisticSigmoid[{-0.2, 0.1, 0.3}]
{0.450166, 0.524979, 0.574443}
```

## Sec

`Sec[z]`  
returns the secant of  $z$ .

```
>> Sec[0]
1
>> Sec[1] (* Sec[1] in Mathematica *)
 $\frac{1}{\text{Cos}[1]}$ 
>> Sec[1.]
1.85082
```

## Sech

`Sech[z]`  
returns the hyperbolic secant of  $z$ .


```
>> Sech[0]
1
```

## Sin

`Sin[z]`  
returns the sine of  $z$ .

```
>> Sin[0]
0
>> Sin[0.5]
0.479426
>> Sin[3 Pi]
0
>> Sin[1.0 + I]
1.29846 + 0.634964I
```

```
>> Plot[Sin[x], {x, -Pi, Pi}]
```



## Sinh

`Sinh[z]`  
returns the hyperbolic sine of  $z$ .

```
>> Sinh[0]  
0
```

## Tan

`Tan[z]`  
returns the tangent of  $z$ .

```
>> Tan[0]  
0  
  
>> Tan[Pi / 2]  
ComplexInfinity
```

## Tanh

`Tanh[z]`  
returns the hyperbolic tangent of  $z$ .

```
>> Tanh[0]  
0
```



# 54. Integer Functions

## Contents

BitLength . . . . .	257	Floor . . . . .	258	IntegerLength . . . . .	259
Ceiling . . . . .	257	FromDigits . . . . .	258	IntegerReverse . . . . .	259
DigitCount . . . . .	257	IntegerDigits . . . . .	258	IntegerString . . . . .	259

## BitLength

**BitLength** $[x]$   
gives the number of bits needed to represent the integer  $x$ .  $x$ 's sign is ignored.

```
>> BitLength[1023]
10
>> BitLength[100]
7
>> BitLength[-5]
3
>> BitLength[0]
0
```

## Ceiling

**Ceiling** $[x]$   
gives the first integer greater than  $x$ .

```
>> Ceiling[1.2]
2
>> Ceiling[3/2]
2
```

For complex  $x$ , take the ceiling of real and imaginary parts.

```
>> Ceiling[1.3 + 0.7 I]
2 + I
```

## DigitCount

**DigitCount** $[n, b, d]$   
returns the number of times digit  $d$  occurs in the base  $b$  representation of  $n$ .

**DigitCount** $[n, b]$   
returns a list indicating the number of times each digit occurs in the base  $b$  representation of  $n$ .

**DigitCount** $[n]$   
returns a list indicating the number of times each digit occurs in the decimal representation of  $n$ .

```
>> DigitCount[1022]
{1, 2, 0, 0, 0, 0, 0, 0, 1}
>> DigitCount[Floor[Pi * 10^100]]
{8, 12, 12, 10, 8, 9, 8, 12, 14, 8}
>> DigitCount[1022, 2]
{9, 1}
>> DigitCount[1022, 2, 1]
9
```

## Floor

**Floor** $[x]$   
gives the smallest integer less than or equal to  $x$ .

**Floor** $[x, a]$   
gives the smallest multiple of  $a$  less than or equal to  $x$ .

```
>> Floor[10.4]
10
>> Floor[10/3]
3
>> Floor[10]
10
>> Floor[21, 2]
20
>> Floor[2.6, 0.5]
2.5
>> Floor[-10.4]
-11
```

For complex  $x$ , take the floor of real and imaginary parts.

```
>> Floor[1.5 + 2.7 I]
1 + 2I
```

For negative  $a$ , the smallest multiple of  $a$  greater than or equal to  $x$  is returned.

```
>> Floor[10.4, -1]
11
>> Floor[-10.4, -1]
-10
```

## FromDigits

**FromDigits[ $l$ ]**  
returns the integer corresponding to the decimal representation given by  $l$ .  $l$  can be a list of digits or a string.

**FromDigits[ $l, b$ ]**  
returns the integer corresponding to the base  $b$  representation given by  $l$ .  $l$  can be a list of digits or a string.

```
>> FromDigits["123"]
123
>> FromDigits[{1, 2, 3}]
123
>> FromDigits[{1, 0, 1}, 1000]
1 000 001
```

FromDigits can handle symbolic input:

```
>> FromDigits[{a, b, c}, 5]
c + 5 (5a + b)
```

Note that FromDigits does not automatically detect if you are providing a non-decimal representation:

```
>> FromDigits["a0"]
100
>> FromDigits["a0", 16]
160
```

FromDigits on empty lists or strings returns 0:

```
>> FromDigits[{}]
0
>> FromDigits[""]
0
```

## IntegerDigits

**IntegerDigits[ $n$ ]**  
returns the decimal representation of integer  $x$  as list of digits.  $x$ 's sign is ignored.

**IntegerDigits[ $n, b$ ]**  
returns the base  $b$  representation of integer  $x$  as list of digits.  $x$ 's sign is ignored.

**IntegerDigits[ $n, b, length$ ]**  
returns a list of length  $length$ . If the number is too short, the list gets padded with 0 on the left. If the number is too long, the  $length$  least significant digits are returned.

```
>> IntegerDigits[12345]
{1, 2, 3, 4, 5}
>> IntegerDigits[-500]
{5, 0, 0}
>> IntegerDigits[12345, 10, 8]
{0, 0, 0, 1, 2, 3, 4, 5}
>> IntegerDigits[12345, 10, 3]
{3, 4, 5}
>> IntegerDigits[11, 2]
{1, 0, 1, 1}
>> IntegerDigits[123, 8]
{1, 7, 3}
>> IntegerDigits[98765, 20]
{12, 6, 18, 5}
```

## IntegerLength

`IntegerLength[x]`  
gives the number of digits in the base-10 representation of  $x$ .  
`IntegerLength[x, b]`  
gives the number of base- $b$  digits in  $x$ .

```
>> IntegerLength[123456]
6
>> IntegerLength[10^10000]
10001
>> IntegerLength[-10^1000]
1001
```

IntegerLength with base 2:

```
>> IntegerLength[8, 2]
4
```

Check that IntegerLength is correct for the first 100 powers of 10:

```
>> IntegerLength /@ (10 ^ Range
[100]) == Range[2, 101]
True
```

The base must be greater than 1:

```
>> IntegerLength[3, -2]
Base - 2 is not an integer greater than 1.
IntegerLength[3, -2]
```

0 is a special case:

```
>> IntegerLength[0]
0
```

## IntegerReverse

`IntegerReverse[n]`  
returns the integer that has the reverse decimal representation of  $x$  without sign.  
`IntegerReverse[n, b]`  
returns the integer that has the reverse base  $b$  representation of  $x$  without sign.

```
>> IntegerReverse[1234]
4321
>> IntegerReverse[1022, 2]
511
```

```
>> IntegerReverse[-123]
321
```

## IntegerString

`IntegerString[n]`  
returns the decimal representation of integer  $x$  as string.  $x$ 's sign is ignored.  
`IntegerString[n, b]`  
returns the base  $b$  representation of integer  $x$  as string.  $x$ 's sign is ignored.  
`IntegerString[n, b, length]`  
returns a string of length  $length$ . If the number is too short, the string gets padded with 0 on the left. If the number is too long, the  $length$  least significant digits are returned.

For bases  $> 10$ , alphabetic characters a, b, ... are used to represent digits 11, 12, ... . Note that base must be an integer in the range from 2 to 36.

```
>> IntegerString[12345]
12345
>> IntegerString[-500]
500
>> IntegerString[12345, 10, 8]
00012345
>> IntegerString[12345, 10, 3]
345
>> IntegerString[11, 2]
1011
>> IntegerString[123, 8]
173
>> IntegerString[32767, 16]
7fff
>> IntegerString[98765, 20]
c6i5
```

# 55. Linear algebra

## Contents

BrayCurtisDistance . . .	260	EuclideanDistance . . .	263	NullSpace . . . . .	265
CanberraDistance . . .	260	Inverse . . . . .	263	PseudoInverse . . . . .	265
ChessboardDistance . .	260	LeastSquares . . . . .	263	QRDecomposition . . .	266
CosineDistance . . . .	261	LinearModelFit . . . . .	264	RowReduce . . . . .	266
Cross . . . . .	261	LinearSolve . . . . .	264	SingularValueDecom-	
DesignMatrix . . . . .	261	ManhattanDistance . .	264	position . . . . .	266
Det . . . . .	261	MatrixExp . . . . .	264	SquaredEuclideanDis-	
Eigensystem . . . . .	261	MatrixPower . . . . .	264	tance . . . . .	266
Eigenvalues . . . . .	262	MatrixRank . . . . .	264	Tr . . . . .	266
Eigenvectors . . . . .	262	Norm . . . . .	265	VectorAngle . . . . .	266
		Normalize . . . . .	265		

## BrayCurtisDistance

`BrayCurtisDistance[u, v]`  
returns the Bray Curtis distance between  $u$  and  $v$ .

```
>> BrayCurtisDistance[-7, 5]
6

>> BrayCurtisDistance[{-1, -1},
{10, 10}]
11
9
```

## CanberraDistance

`CanberraDistance[u, v]`  
returns the canberra distance between  $u$  and  $v$ , which is a weighted version of the Manhattan distance.

```
>> CanberraDistance[-7, 5]
1

>> CanberraDistance[{-1, -1}, {1,
1}]
2
```

## ChessboardDistance

`ChessboardDistance[u, v]`  
returns the chessboard distance (also known as Chebyshev distance) between  $u$  and  $v$ , which is the number of moves a king on a chessboard needs to get from square  $u$  to square  $v$ .

```
>> ChessboardDistance[-7, 5]
12

>> ChessboardDistance[{-1, -1}, {1,
1}]
2
```

## CosineDistance

`CosineDistance[u, v]`  
returns the cosine distance between  $u$  and  $v$ .

```
>> N[CosineDistance[{7, 9}, {71,
89}]]
0.0000759646
```

```
>> CosineDistance[{a, b}, {c, d}]
1
+ 
$$\frac{-ac - bd}{\sqrt{\text{Abs}[a]^2 + \text{Abs}[b]^2} \sqrt{\text{Abs}[c]^2 + \text{Abs}[d]^2}}$$

```

## Cross

`Cross[a, b]`  
computes the vector cross product of  $a$  and  $b$ .

```
>> Cross[{x1, y1, z1}, {x2, y2, z2}]
{y1z2 - y2z1,
 -x1z2 + x2z1, x1y2 - x2y1}
>> Cross[{x, y}]
{-y, x}
>> Cross[{1, 2}, {3, 4, 5}]
The arguments are expected to be vectors of equal length,
and the number of arguments is expected to be less than 10.
Cross[{1, 2}, {3, 4, 5}]
```

## DesignMatrix

`DesignMatrix[m, f, x]`  
returns the design matrix.

```
>> DesignMatrix[{{2, 1}, {3, 4}, {5, 3}, {7, 6}}, x, x]
{{1, 2}, {1, 3}, {1, 5}, {1, 7}}
>> DesignMatrix[{{2, 1}, {3, 4}, {5, 3}, {7, 6}}, f[x], x]
{{1, f[2]}, {1, f[3]}, {1, f[5]}, {1, f[7]}}
```

## Det

`Det[m]`  
computes the determinant of the matrix  $m$ .

```
>> Det[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
-2
```

Symbolic determinant:

```
>> Det[{{a, b, c}, {d, e, f}, {g, h, i}}]
aei - afh - bdi + bfg + cdh - ceg
```

## Eigensystem

`Eigensystem[m]`  
returns the list `{Eigenvalues[m], Eigenvectors[m]}`.

```
>> Eigensystem[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
{{2, -1, 1}, {{1, 1, 1}, {1, -2, 1}, {-1, 0, 1}}}
```

## Eigenvalues

`Eigenvalues[m]`  
computes the eigenvalues of the matrix  $m$ . By default SymPy's routine is used. Sometimes this is slow and less good than the corresponding mpmath routine. Use option `Method->"mpmath"` if you want to use mpmath's routine instead.

Numeric eigenvalues are sorted in order of decreasing absolute value:

```
>> Eigenvalues[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
{2, -1, 1}
```

Symbolic eigenvalues:

```
>> Eigenvalues[{{Cos[theta], Sin[theta], 0}, {-Sin[theta], Cos[theta], 0}, {0, 0, 1}}] // Sort
{1, Cos[theta],
 
$$+ \sqrt{(-1 + \text{Cos}[\text{theta}]) (1 + \text{Cos}[\text{theta}])},$$

 Cos[theta],
 
$$- \sqrt{(-1 + \text{Cos}[\text{theta}]) (1 + \text{Cos}[\text{theta}])}}$$

```

```
>> Eigenvalues[{{7, 1}, {-4, 3}}]
{5, 5}

>> Eigenvalues[{{7, 1}, {-4, 3}}]
{5, 5}
```

## Eigenvectors

`Eigenvectors[m]`  
computes the eigenvectors of the matrix  $m$ .

```
>> Eigenvectors[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
{{1, 1, 1}, {1, -2, 1}, {-1, 0, 1}}

>> Eigenvectors[{{1, 0, 0}, {0, 1, 0}, {0, 0, 0}}]
{{0, 1, 0}, {1, 0, 0}, {0, 0, 1}}

>> Eigenvectors[{{2, 0, 0}, {0, -1, 0}, {0, 0, 0}}]
{{1, 0, 0}, {0, 1, 0}, {0, 0, 1}}
```

```
>> Eigenvectors[{{0.1, 0.2}, {0.8, 0.5}}]
{{-0.355518216481267016676297~
~559501705929896062805897153~
~500209120909839738411406528~
~939551208168268203735351562~
~50000000000000000000000000~
~00000000000000000000000000~
~00000000000000000000000000~
~000000000000, -1.150481115~
~772866118834236549972506478~
~611688789589714534394707980~
~136107750013252370990812778~
~47290039062500000000000000~
~00000000000000000000000000~
~00000000000000000000000000~
~00000000000000000000000000},
{-0.628960169645094045731745~
~684302104224901929314653543~
~850901708147770746704097177~
~826042752712965011596679687~
~50000000000000000000000000~
~00000000000000000000000000~
~00000000000000000000000000~
~000000000000, 0.777437524821~
~136041447958386087174831147~
~822934682708885214954348721~
~189125726027668861206620931~
~62536621093750000000000000~
~00000000000000000000000000~
~00000000000000000000000000~
~000000000000000000000000}}
```

## EuclideanDistance

`EuclideanDistance[u, v]`  
returns the euclidean distance between  $u$  and  $v$ .

```
>> EuclideanDistance[-7, 5]
12

>> EuclideanDistance[{-1, -1}, {1, 1}]
 $2\sqrt{2}$ 
```

```
>> EuclideanDistance[{a, b}, {c, d
}]
```

$$\sqrt{\text{Abs}[a - c]^2 + \text{Abs}[b - d]^2}$$

## Inverse

`Inverse[m]`  
computes the inverse of the matrix  $m$ .

```
>> Inverse[{{1, 2, 0}, {2, 3, 0},
{3, 4, 1}}]
{{-3, 2, 0}, {2, -1, 0}, {1, -2, 1}}
```

```
>> Inverse[{{1, 0}, {0, 0}}]
Thematrix{{1, 0}, {0, 0}} is singular.
Inverse[{{1, 0}, {0, 0}}]
```

```
>> Inverse[{{1, 0, 0}, {0, Sqrt
[3]/2, 1/2}, {0, -1 / 2, Sqrt
[3]/2}}]
```

$$\left\{ \begin{matrix} 1, 0, 0 \\ 0, \frac{\sqrt{3}}{2}, \\ -\frac{1}{2} \end{matrix} \right\}, \left\{ \begin{matrix} 0, \frac{1}{2}, \frac{\sqrt{3}}{2} \\ 0, \frac{1}{2}, \frac{\sqrt{3}}{2} \end{matrix} \right\}$$

## LeastSquares

`LeastSquares[m, b]`  
computes the least squares solution to  $m$   
 $x = b$ , finding an  $x$  that solves for  $b$  opti-  
mally.

```
>> LeastSquares[{{1, 2}, {2, 3},
{5, 6}}, {1, 5, 3}]
```

$$\left\{ -\frac{28}{13}, \frac{31}{13} \right\}$$

```
>> Simplify[LeastSquares[{{1, 2},
{2, 3}, {5, 6}}, {1, x, 3}]]
```

$$\left\{ \frac{12}{13} - \frac{8x}{13}, -\frac{4}{13} + \frac{7x}{13} \right\}$$

```
>> LeastSquares[{{1, 1, 1}, {1, 1,
2}}, {1, 3}]
```

*Solving for underdetermined system not implemented.*

```
LeastSquares[{{1, 1,
1}, {1, 1, 2}}, {1, 3}]
```

## LinearModelFit

`LinearModelFit[m, f, x]`  
returns the design matrix.

```
>> m = LinearModelFit[{{2, 1}, {3,
4}, {5, 3}, {7, 6}}, x, x];
```

```
>> m["BasisFunctions"]
{1, x}
```

```
>> m["BestFit"]
0.186441 + 0.779661x
```

```
>> m["BestFitParameters"]
{0.186441, 0.779661}
```

```
>> m["DesignMatrix"]
{{1, 2}, {1, 3}, {1, 5}, {1, 7}}
```

```
>> m["Function"]
0.186441 + 0.779661#1 &
```

```
>> m["Response"]
{1, 4, 3, 6}
```

```
>> m["FitResiduals"]
{-0.745763, 1.47458
, -1.08475, 0.355932}
```

```
>> m = LinearModelFit[{{2, 2, 1},
{3, 2, 4}, {5, 6, 3}, {7, 9,
6}}, {Sin[x], Cos[y]}, {x, y}];
```

```
>> m["BasisFunctions"]
{1, Sin[x], Cos[y]}
```

```
>> m["Function"]
3.33077 - 5.65221 Cos[
#2] - 5.01042 Sin[#1] &
```

```
>> m = LinearModelFit[{{1, 4}, {1,
5}, {1, 7}}, {1, 2, 3}];
```

```
>> m["BasisFunctions"]
{#1, #2}
```

```
>> m["FitResiduals"]
{-0.142857, 0.214286, - 0.0714286}
```

## LinearSolve

`LinearSolve[matrix, right]`  
solves the linear equation system *matrix* . *x* = *right* and returns one corresponding solution *x*.

```
>> LinearSolve[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}, {1, 2, 3}]
{0, 1, 2}
```

Test the solution:

```
>> {{1, 1, 0}, {1, 0, 1}, {0, 1, 1}} . {0, 1, 2}
{1, 2, 3}
```

If there are several solutions, one arbitrary solution is returned:

```
>> LinearSolve[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {1, 1, 1}]
{-1, 1, 0}
```

Infeasible systems are reported:

```
>> LinearSolve[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {1, -2, 3}]
```

*Linearequationencounteredthathasnosolution.*

```
LinearSolve[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}, {1, -2, 3}]
```

## ManhattanDistance

`ManhattanDistance[u, v]`  
returns the Manhattan distance between *u* and *v*, which is the number of horizontal or vertical moves in the gridlike Manhattan city layout to get from *u* to *v*.

```
>> ManhattanDistance[-7, 5]
12

>> ManhattanDistance[{-1, -1}, {1, 1}]
4
```

## MatrixExp

`MatrixExp[m]`  
computes the exponential of the matrix *m*.

```
>> MatrixExp[{{0, 2}, {0, 1}}]
{{1, -2 + 2E}, {0, E}}

>> MatrixExp[{{1.5, 0.5}, {0.5, 2.0}}]
{{5.16266, 3.02952}, {3.02952, 8.19218}}
```

## MatrixPower

`MatrixPower[m, n]`  
computes the *n*th power of a matrix *m*.

```
>> MatrixPower[{{1, 2}, {1, 1}}, 10]
{{3363, 4756}, {2378, 3363}}

>> MatrixPower[{{1, 2}, {2, 5}}, -3]
{{169, -70}, {-70, 29}}
```

## MatrixRank

`MatrixRank[matrix]`  
returns the rank of *matrix*.

```
>> MatrixRank[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}]
2

>> MatrixRank[{{1, 1, 0}, {1, 0, 1}, {0, 1, 1}}]
3

>> MatrixRank[{{a, b}, {3 a, 3 b}}]
1
```



## Norm

`Norm[m, l]`  
computes the l-norm of matrix *m* (currently only works for vectors!).  
`Norm[m]`  
computes the 2-norm of matrix *m* (currently only works for vectors!).

```
>> Norm[{1, 2, 3, 4}, 2]
 $\sqrt{30}$ 

>> Norm[{10, 100, 200}, 1]
310

>> Norm[{a, b, c}]
 $\sqrt{\text{Abs}[a]^2 + \text{Abs}[b]^2 + \text{Abs}[c]^2}$ 

>> Norm[{-100, 2, 3, 4}, Infinity]
100

>> Norm[1 + I]
 $\sqrt{2}$ 
```

## Normalize

`Normalize[v]`  
calculates the normalized vector *v*.  
`Normalize[z]`  
calculates the normalized complex number *z*.

```
>> Normalize[{1, 1, 1, 1}]
 $\left\{ \frac{1}{2}, \frac{1}{2}, \frac{1}{2}, \frac{1}{2} \right\}$ 

>> Normalize[1 + I]
 $\left( \frac{1}{2} + \frac{I}{2} \right) \sqrt{2}$ 
```

## NullSpace

`NullSpace[matrix]`  
returns a list of vectors that span the nullspace of *matrix*.

```
>> NullSpace[{{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}]
{{1, -2, 1}}

>> A = {{1, 1, 0}, {1, 0, 1}, {0, 1, 1}};

>> NullSpace[A]
{}

>> MatrixRank[A]
3
```

## PseudoInverse

`PseudoInverse[m]`  
computes the Moore-Penrose pseudoinverse of the matrix *m*. If *m* is invertible, the pseudoinverse equals the inverse.

```
>> PseudoInverse[{{1, 2}, {2, 3}, {3, 4}}]
 $\left\{ \left\{ -\frac{11}{6}, -\frac{1}{3}, \frac{7}{6} \right\}, \left\{ \frac{4}{3}, \frac{1}{3}, -\frac{2}{3} \right\} \right\}$ 

>> PseudoInverse[{{1, 2, 0}, {2, 3, 0}, {3, 4, 1}}]
{{-3, 2, 0}, {2, -1, 0}, {1, -2, 1}}

>> PseudoInverse[{{1.0, 2.5}, {2.5, 1.0}}]
{{-0.190476, 0.47619}, {0.47619, -0.190476}}
```

## QRDecomposition

`QRDecomposition[m]`  
computes the QR decomposition of the matrix *m*.

```
>> QRDecomposition[{{1, 2}, {3, 4},
{5, 6}}]
```

$$\left\{ \left\{ \left\{ \frac{\sqrt{35}}{35}, \frac{3\sqrt{35}}{35}, \frac{\sqrt{35}}{7} \right\}, \right. \right. \\ \left. \left\{ \frac{13\sqrt{210}}{210}, \frac{2\sqrt{210}}{105}, \right. \right. \\ \left. \left. -\frac{\sqrt{210}}{42} \right\} \right\}, \left\{ \left\{ \sqrt{35}, \right. \right. \\ \left. \left. \frac{44\sqrt{35}}{35} \right\}, \left\{ 0, \frac{2\sqrt{210}}{35} \right\} \right\} \right\}$$

## RowReduce

`RowReduce[matrix]`  
returns the reduced row-echelon form of *matrix*.

```
>> RowReduce[{{1, 0, a}, {1, 1, b
}}]
{{1, 0, a}, {0, 1, -a + b}}

>> RowReduce[{{1, 2, 3}, {4, 5, 6},
{7, 8, 9}}] // MatrixForm

$$\begin{pmatrix} 1 & 0 & -1 \\ 0 & 1 & 2 \\ 0 & 0 & 0 \end{pmatrix}$$

```

## SingularValueDecomposition

`SingularValueDecomposition[m]`  
calculates the singular value decomposition for the matrix *m*.

`SingularValueDecomposition` returns *u*, *s*, *w* such that  $m=usv$ ,  $uu=1$ ,  $vv=1$ , and *s* is diagonal.

```
>> SingularValueDecomposition
[{{1.5, 2.0}, {2.5, 3.0}}]
{{{0.538954, 0.842335}, {0.842335
, -0.538954}}, {{4.63555, 0.},
{0., 0.107862}}, {{0.628678, 0.777~
666}, {-0.777666, 0.628678}}}
```

## SquaredEuclideanDistance

`SquaredEuclideanDistance[u, v]`  
returns squared the euclidean distance between *u* and *v*.

```
>> SquaredEuclideanDistance[-7, 5]
144

>> SquaredEuclideanDistance[{-1,
-1}, {1, 1}]
8
```

## Tr

`Tr[m]`  
computes the trace of the matrix *m*.

```
>> Tr[{{1, 2, 3}, {4, 5, 6}, {7, 8,
9}}]
15
```

Symbolic trace:

```
>> Tr[{{a, b, c}, {d, e, f}, {g, h,
i}}]
a + e + i
```

## VectorAngle

`VectorAngle[u, v]`  
gives the angles between vectors *u* and *v*

```
>> VectorAngle[{1, 0}, {0, 1}]
 $\frac{\text{Pi}}{2}$ 

>> VectorAngle[{1, 2}, {3, 1}]
 $\frac{\text{Pi}}{4}$ 

>> VectorAngle[{1, 1, 0}, {1, 0,
1}]
 $\frac{\text{Pi}}{3}$ 
```

## 56. Number theoretic functions

### Contents

ContinuedFraction . . .	267	FromContinuedFraction	268	Prime . . . . .	269
Divisors . . . . .	267	IntegerExponent . . . .	268	PrimePi . . . . .	269
FactorInteger . . . . .	267	MantissaExponent . . .	268	PrimePowerQ . . . . .	269
FractionalPart . . . . .	268	NextPrime . . . . .	268	RandomPrime . . . . .	269
		PartitionsP . . . . .	268		

### ContinuedFraction

`ContinuedFraction[x, n]`  
generate the first  $n$  terms in the continued fraction representation of  $x$ .

`ContinuedFraction[x]`  
the complete continued fraction representation for a rational or quadratic irrational number.

```
>> ContinuedFraction[Pi, 10]
{3, 7, 15, 1, 292, 1, 1, 1, 2, 1}

>> ContinuedFraction[(1 + 2 Sqrt[3])/5]
{0, 1, {8, 3, 34, 3}}

>> ContinuedFraction[Sqrt[70]]
{8, {2, 1, 2, 1, 2, 16}}
```

### Divisors

`Divisors[n]`  
returns a list of the integers that divide  $n$ .

```
>> Divisors[96]
{1, 2, 3, 4, 6, 8, 12, 16, 24, 32, 48, 96}

>> Divisors[704]
{1, 2, 4, 8, 11, 16, 22, 32, 44, 64, 88, 176, 352, 704}
```

```
>> Divisors[{87, 106, 202, 305}]
{{1, 3, 29, 87}, {1, 2, 53, 106},
 {1, 2, 101, 202}, {1, 5, 61, 305}}
```

### FactorInteger

`FactorInteger[n]`  
returns the factorization of  $n$  as a list of factors and exponents.

```
>> factors = FactorInteger[2010]
{{2, 1}, {3, 1}, {5, 1}, {67, 1}}
```

To get back the original number:

```
>> Times @@ Power @@@ factors
2010
```

`FactorInteger` factors rationals using negative exponents:

```
>> FactorInteger[2010 / 2011]
{{2, 1}, {3, 1}, {5, 1},
 {67, 1}, {2011, -1}}
```

### FractionalPart

`FractionalPart[n]`  
finds the fractional part of  $n$ .

```
>> FractionalPart[4.1]
0.1
```

```
>> FractionalPart[-5.25]
-0.25
```

## FromContinuedFraction

`FromContinuedFraction[list]`  
reconstructs a number from the list of its continued fraction terms.

```
>> FromContinuedFraction[{3, 7, 15,
1, 292, 1, 1, 1, 2, 1}]
1 146 408
-----
364 913

>> FromContinuedFraction[Range[5]]
225
-----
157
```

## IntegerExponent

`IntegerExponent[n, b]`  
gives the highest exponent of  $b$  that divides  $n$ .

```
>> IntegerExponent[16, 2]
4

>> IntegerExponent[-510000]
4

>> IntegerExponent[10, b]
IntegerExponent[10, b]
```

## MantissaExponent

`MantissaExponent[n]`  
finds a list containing the mantissa and exponent of a given number  $n$ .  
`MantissaExponent[n, b]`  
finds the base  $b$  mantissa and exponent of  $n$ .

```
>> MantissaExponent[2.5*10^20]
{0.25, 21}

>> MantissaExponent[125.24]
{0.12524, 3}
```

```
>> MantissaExponent[125., 2]
{0.976563, 7}
```

```
>> MantissaExponent[10, b]
MantissaExponent[10, b]
```

## NextPrime

`NextPrime[n]`  
gives the next prime after  $n$ .  
`NextPrime[n, k]`  
gives the  $k$ th prime after  $n$ .

```
>> NextPrime[10000]
10007

>> NextPrime[100, -5]
73

>> NextPrime[10, -5]
-2

>> NextPrime[100, 5]
113

>> NextPrime[5.5, 100]
563

>> NextPrime[5, 10.5]
NextPrime[5, 10.5]
```

## PartitionsP

`PartitionsP[n]`  
return the number  $p(n)$  of unrestricted partitions of the integer  $n$ .

```
>> Table[PartitionsP[k], {k, -2, 12}]
{0, 0, 1, 1, 2, 3, 5, 7, 11,
15, 22, 30, 42, 56, 77}
```

## Prime

```
Prime[n]
Prime[{n0, n1, ...}]
    returns the nth prime number where n is
    an positive Integer. If given a list of inte-
    gers, the return value is a list with Prime
    applied to each.
```

Note that the first prime is 2, not 1:

```
>> Prime[1]
2

>> Prime[167]
991
```

When given a list of integers, a list is returned:

```
>> Prime[{5, 10, 15}]
{11, 29, 47}
```

1.2 isn't an integer

```
>> Prime[1.2]
Prime[1.2]
```

Since 0 is less than 1, like 1.2 it is invalid.

```
>> Prime[{0, 1, 1.2, 3}]
{Prime[0], 2, Prime[1.2], 5}
```

## PrimePi

```
PrimePi[x]
    gives the number of primes less than or
    equal to x.
```

PrimePi is the inverse of Prime:

```
>> PrimePi[2]
1

>> PrimePi[100]
25

>> PrimePi[-1]
0

>> PrimePi[3.5]
2

>> PrimePi[E]
1
```

## PrimePowerQ

```
PrimePowerQ[n]
    returns True if n is a power of a prime
    number.
```

```
>> PrimePowerQ[9]
True

>> PrimePowerQ[52142]
False

>> PrimePowerQ[-8]
True

>> PrimePowerQ[371293]
True
```

## RandomPrime

```
RandomPrime[{imin, $imax}]
    gives a random prime between imin and
    imax.
```

```
RandomPrime[imax]
    gives a random prime between 2 and
    imax.
```

```
RandomPrime[range, n]
    gives a list of n random primes in range.
```

```
>> RandomPrime[{14, 17}]
17

>> RandomPrime[{14, 16}, 1]
There are no primes in the specified interval.
RandomPrime[{14, 16}, 1]

>> RandomPrime[{8, 12}, 3]
{11, 11, 11}

>> RandomPrime[{10, 30}, {2, 5}]
{{19, 19, 19, 19, 19},
 {19, 19, 19, 19, 19}}
```

# 57. Random number generation

Random numbers are generated using the Mersenne Twister.

## Contents

<b>Random</b> . . . . .	270	<b>RandomInteger</b> . . . . .	271	<b>\$RandomState</b> . . . . .	272
<b>RandomChoice</b> . . . . .	270	<b>RandomReal</b> . . . . .	272	<b>SeedRandom</b> . . . . .	273
<b>RandomComplex</b> . . . . .	271	<b>RandomSample</b> . . . . .	272		

## Random

Legacy function. Superseded by RandomReal, RandomInteger and RandomComplex.

## RandomChoice

**RandomChoice[items]**  
randomly picks one item from *items*.

**RandomChoice[items, n]**  
randomly picks *n* items from *items*. Each pick in the *n* picks happens from the given set of *items*, so each item can be picked any number of times.

**RandomChoice[items, {n1, n2, ...}]**  
randomly picks items from *items* and arranges the picked items in the nested list structure described by {*n1*, *n2*, ...}.

**RandomChoice[weights -> items, n]**  
randomly picks *n* items from *items* and uses the corresponding numeric values in *weights* to determine how probable it is for each item in *items* to get picked (in the long run, items with higher weights will get picked more often than ones with lower weight).

**RandomChoice[weights -> items]**  
randomly picks one items from *items* using weights *weights*.

**RandomChoice[weights -> items, {n1, n2, ...}]**  
randomly picks a structured list of items from *items* using weights *weights*.

```
>> RandomChoice[{a, b, c}]
{c}

>> SeedRandom[42]

>> RandomChoice[{a, b, c}, 20]
{c,a,c,c,a,a,c,b,c,c,
 c,c,a,c,b,a,b,b,b}

>> SeedRandom[42]

>> RandomChoice[{"a", {1, 2}, x, {}}, 10]
{x, {}, a,x,x, {}, a,a,x, {1,2}}

>> SeedRandom[42]

>> RandomChoice[{a, b, c}, {5, 2}]
{{c,a}, {c,c}, {a,a}, {c,b}, {c,c}}

>> SeedRandom[42]

>> RandomChoice[{1, 100, 5} -> {a, b, c}, 20]
{b,b,b,b,b,b,b,b,b,
 b,c,b,b,b,b,b,b,b}
```

```
>> SeedRandom[42]
```

## RandomComplex

`RandomComplex[{z_min, z_max}]`  
yields a pseudorandom complex number in the rectangle with complex corners `z_min` and `z_max`.

`RandomComplex[z_max]`  
yields a pseudorandom complex number in the rectangle with corners at the origin and at `z_max`.

`RandomComplex[]`  
yields a pseudorandom complex number with real and imaginary parts from 0 to 1.

`RandomComplex[range, n]`  
gives a list of `n` pseudorandom complex numbers.

`RandomComplex[range, {n1, n2, ...}]`  
gives a nested list of pseudorandom complex numbers.

```
>> RandomComplex[]
0.223828 + 0.430861I

>> RandomComplex[{1+I, 5+5I}]
2.15219 + 2.5964I

>> RandomComplex[1+I, 5]
{0.651258 + 0.113927I, 0.480~
~653 + 0.190907I, 0.351188 +
0.0222305I, 0.850087 + 0.817~
~387I, 0.796483 + 0.351061I}

>> RandomComplex[{1+I, 2+2I}, {2,
2}]
{{1.47823 + 1.16764I, 1.536~
~9 + 1.44804I}, {1.37622 +
1.3907I, 1.04106 + 1.25756I}}
```

## RandomInteger

`RandomInteger[{min, max}]`  
yields a pseudorandom integer in the range from `min` to `max` inclusive.

`RandomInteger[max]`  
yields a pseudorandom integer in the range from 0 to `max` inclusive.

`RandomInteger[]`  
gives 0 or 1.

`RandomInteger[range, n]`  
gives a list of `n` pseudorandom integers.

`RandomInteger[range, {n1, n2, ...}]`  
gives a nested list of pseudorandom integers.

```
>> RandomInteger[{1, 5}]
1

>> RandomInteger[100, {2, 3}] //
TableForm
      32  85  5
      25  33  75
```

Calling `RandomInteger` changes `$RandomState`:

```
>> previousState = $RandomState;

>> RandomInteger[]
0

>> $RandomState != previousState
True
```

## RandomReal

`RandomReal[{min, max}]`  
yields a pseudorandom real number in the range from `min` to `max`.

`RandomReal[max]`  
yields a pseudorandom real number in the range from 0 to `max`.

`RandomReal[]`  
yields a pseudorandom real number in the range from 0 to 1.

`RandomReal[range, n]`  
gives a list of `n` pseudorandom real numbers.

`RandomReal[range, {n1, n2, ...}]`  
gives a nested list of pseudorandom real numbers.

```
>> RandomReal[]
0.133018

>> RandomReal[{1, 5}]
4.29275
```

## RandomSample

`RandomSample[items]`  
randomly picks one item from *items*.

`RandomSample[items, n]`  
randomly picks *n* items from *items*. Each pick in the *n* picks happens after the previous items picked have been removed from *items*, so each item can be picked at most once.

`RandomSample[items, {n1, n2, ...}]`  
randomly picks items from *items* and arranges the picked items in the nested list structure described by {*n1*, *n2*, ...}. Each item gets picked at most once.

`RandomSample[weights -> items, n]`  
randomly picks *n* items from *items* and uses the corresponding numeric values in *weights* to determine how probable it is for each item in *items* to get picked (in the long run, items with higher weights will get picked more often than ones with lower weight). Each item gets picked at most once.

`RandomSample[weights -> items]`  
randomly picks one items from *items* using weights *weights*. Each item gets picked at most once.

`RandomSample[weights -> items, {n1, n2, ...}]`  
randomly picks a structured list of items from *items* using weights *weights*. Each item gets picked at most once.

```
>> SeedRandom[42]

>> RandomSample[{a, b, c}]
{a}

>> SeedRandom[42]

>> RandomSample[{a, b, c, d, e, f, g, h}, 7]
{b, f, a, h, c, e, d}

>> SeedRandom[42]
```

```
>> RandomSample[{"a", {1, 2}, x, {}], 3]
{{1, 2}, {}, a}

>> SeedRandom[42]

>> RandomSample[Range[100], {2, 3}]
{{84, 54, 71}, {46, 45, 40}}

>> SeedRandom[42]

>> RandomSample[Range[100] -> Range[100], 5]
{62, 98, 86, 78, 40}
```

## \$RandomState

`$RandomState`  
is a long number representing the internal state of the pseudorandom number generator.

```
>> Mod[$RandomState, 10^100]
1 922 741 579 711 707 052 868 202 ~
~168 987 310 452 796 849 361 011 ~
~441 840 662 726 639 187 953 358 ~
~001 669 151 583 460 868 769 255 470

>> IntegerLength[$RandomState]
6 466
```

So far, it is not possible to assign values to `$RandomState`.

```
>> $RandomState = 42
It is not possible to change the random state.
42
```

Not even to its own value:

```
>> $RandomState = $RandomState;
It is not possible to change the random state.
```

## SeedRandom

`SeedRandom[n]`  
resets the pseudorandom generator with seed *n*.

`SeedRandom[]`  
uses the current date and time as the seed.



SeedRandom can be used to get reproducible random numbers:

```
>> SeedRandom[42]

>> RandomInteger[100]
51

>> RandomInteger[100]
92

>> SeedRandom[42]

>> RandomInteger[100]
51

>> RandomInteger[100]
92
```

String seeds are supported as well:

```
>> SeedRandom["Mathics"]

>> RandomInteger[100]
27
```

Calling SeedRandom without arguments will seed the random number generator to a random state:

```
>> SeedRandom[]

>> RandomInteger[100]
86
```

## 58. Special Functions

There are a number of functions found in mathematical physics and found in standard handbooks.

One thing to note is that the technical literature often contains several conflicting definitions. So beware and check for conformance with the Mathics documentation.

A number of special functions can be evaluated

for arbitrary complex values of their arguments. However defining relations may apply only for some special choices of arguments. Here, the full function corresponds to an extension or “analytic continuation” of the defining relation.

For example, integral representations of functions are only valid when the integral exists, but the functions can usually be defined by analytic continuation.

# 59. Bessel and Related Functions

## Contents

AiryAi . . . . .	275	BesselI . . . . .	277	KelvinBei . . . . .	278
AiryAiPrime . . . . .	275	BesselJ . . . . .	277	KelvinBer . . . . .	278
AiryAiZero . . . . .	275	BesselJZero . . . . .	277	KelvinKei . . . . .	278
AiryBi . . . . .	276	BesselK . . . . .	277	KelvinKer . . . . .	279
AiryBiPrime . . . . .	276	BesselY . . . . .	277	StruveH . . . . .	279
AiryBiZero . . . . .	276	BesselYZero . . . . .	277	StruveL . . . . .	279
AngerJ . . . . .	276	HankelH1 . . . . .	278	WeberE . . . . .	279
		HankelH2 . . . . .	278		

## AiryAi

`AiryAi[x]`  
returns the Airy function  $\text{Ai}(x)$ .

Exact values:


```
>> AiryAi[0]
      31/3
-----
3Gamma[2/3]
```

AiryAi can be evaluated numerically:

```
>> AiryAi[0.5]
0.231694

>> AiryAi[0.5 + I]
0.157118 - 0.24104I

>> Plot[AiryAi[x], {x, -10, 10}]
```



## AiryAiPrime

`AiryAiPrime[x]`  
returns the derivative of the Airy function `AiryAi[x]`.

Exact values:

```
>> AiryAiPrime[0]
      32/3
-----
3Gamma[1/3]
```

Numeric evaluation:

```
>> AiryAiPrime[0.5]
-0.224911
```

## AiryAiZero

`AiryAiZero[k]`  
returns the  $k$ th zero of the Airy function  $\text{Ai}(z)$ .

```
>> N[AiryAiZero[1]]
-2.33811
```

## AiryBi

**AiryBi[x]**  
returns the Airy function of the second kind  $\text{Bi}(x)$ .

Exact values:

```
>> AiryBi[0]

$$\frac{3^{\frac{5}{6}}}{3\Gamma\left[\frac{2}{3}\right]}$$


```

Numeric evaluation:

```
>> AiryBi[0.5]
0.854277
```

```
>> AiryBi[0.5 + I]
0.688145 + 0.370815I
```

```
>> Plot[AiryBi[x], {x, -10, 2}]
```



## AiryBiPrime

**AiryBiPrime[x]**  
returns the derivative of the Airy function of the second kind  $\text{AiryBi}[x]$ .

Exact values:

```
>> AiryBiPrime[0]

$$\frac{3^{\frac{1}{6}}}{\Gamma\left[\frac{1}{3}\right]}$$

```

Numeric evaluation:

```
>> AiryBiPrime[0.5]
0.544573
```

## AiryBiZero

**AiryBiZero[k]**  
returns the  $k$ th zero of the Airy function  $\text{Bi}(z)$ .


```
>> N[AiryBiZero[1]]
-1.17371
```

## AngerJ

**AngerJ[n, z]**  
returns the Anger function  $J_n(z)$ .

```
>> AngerJ[1.5, 3.5]
0.294479
```

```
>> Plot[AngerJ[1, x], {x, -10, 10}]
```




## BesselI

**BesselI[n, z]**  
returns the modified Bessel function of the first kind  $I_n(z)$ .

```
>> BesselI[1.5, 4]
8.17263
```

```
>> Plot[BesselI[0, x], {x, 0, 5}]
```




## BesselJ

**BesselJ** $[n, z]$   
returns the Bessel function of the first kind  $J_n(z)$ .

```
>> BesselJ[0, 5.2]  
-0.11029
```

```
>> D[BesselJ[n, z], z]  
-  $\frac{\text{BesselJ}[1 + n, z]}{2}$  +  $\frac{\text{BesselJ}[-1 + n, z]}{2}$ 
```

```
>> Plot[BesselJ[0, x], {x, 0, 10}]
```



## BesselJZero

**BesselJZero** $[n, k]$   
returns the  $k$ th zero of the Bessel function of the first kind  $J_n(z)$ .


```
>> N[BesselJZero[0, 1]]  
2.40483
```

## BesselK

**BesselK** $[n, z]$   
returns the modified Bessel function of the second kind  $K_n(z)$ .

```
>> BesselK[1.5, 4]  
0.014347
```

```
>> Plot[BesselK[0, x], {x, 0, 5}]
```




## BesselY

**BesselY** $[n, z]$   
returns the Bessel function of the second kind  $Y_n(z)$ .

```
>> BesselY[1.5, 4]  
0.367112
```

```
>> Plot[BesselY[0, x], {x, 0, 10}]
```



## BesselYZero

**BesselYZero** $[n, k]$   
returns the  $k$ th zero of the Bessel function of the second kind  $Y_n(z)$ .

```
>> N[BesselYZero[0, 1]]  
0.893577
```

## HankelH1

**HankelH1** $[n, z]$   
returns the Hankel function of the first kind  $H_n^{(1)}(z)$ .

```
>> HankelH1[1.5, 4]
0.185286 + 0.367112I
```

## HankelH2

`HankelH2[n, z]`  
returns the Hankel function of the second kind  $H_n^{(2)}(z)$ .

```
>> HankelH2[1.5, 4]
0.185286 - 0.367112I
```

## KelvinBei


`KelvinBei[z]`  
returns the Kelvin function  $\text{bei}(z)$ .  
`KelvinBei[n, z]`  
returns the Kelvin function  $\text{bei}_n(z)$ .

```
>> KelvinBei[0.5]
0.0624932

>> KelvinBei[1.5 + I]
0.326323 + 0.755606I

>> KelvinBei[0.5, 0.25]
0.370153

>> Plot[KelvinBei[x], {x, 0, 10}]
```



## KelvinBer


`KelvinBer[z]`  
returns the Kelvin function  $\text{ber}(z)$ .  
`KelvinBer[n, z]`  
returns the Kelvin function  $\text{ber}_n(z)$ .

```
>> KelvinBer[0.5]
0.999023
```

```
>> KelvinBer[1.5 + I]
1.1162 - 0.117944I
```

```
>> KelvinBer[0.5, 0.25]
0.148824
```

```
>> Plot[KelvinBer[x], {x, 0, 10}]
```



## KelvinKei


`KelvinKei[z]`  
returns the Kelvin function  $\text{kei}(z)$ .  
`KelvinKei[n, z]`  
returns the Kelvin function  $\text{kei}_n(z)$ .

```
>> KelvinKei[0.5]
-0.671582

>> KelvinKei[1.5 + I]
-0.248994 + 0.303326I

>> KelvinKei[0.5, 0.25]
-2.0517

>> Plot[KelvinKei[x], {x, 0, 10}]
```



## KelvinKer


`KelvinKer[z]`  
returns the Kelvin function  $\text{ker}(z)$ .  
`KelvinKer[n, z]`  
returns the Kelvin function  $\text{ker}_n(z)$ .

```
>> KelvinKer[0.5]
0.855906

>> KelvinKer[1.5 + I]
-0.167162 - 0.184404I

>> KelvinKer[0.5, 0.25]
0.450023

>> Plot[KelvinKer[x], {x, 0, 10}]
```




## StruveH

**StruveH[n, z]**  
returns the Struve function  $H_n(z)$ .

```
>> StruveH[1.5, 3.5]
1.13192

>> Plot[StruveH[0, x], {x, 0, 20}]
```




## StruveL

**StruveL[n, z]**  
returns the modified Struve function  $L_n(z)$ .

```
>> StruveL[1.5, 3.5]
4.41126
```

```
>> Plot[StruveL[0, x], {x, 0, 5}]
```




## WeberE

**WeberE[n, z]**  
returns the Weber function  $E_n(z)$ .

```
>> WeberE[1.5, 3.5]
-0.397256

>> Plot[WeberE[1, x], {x, -10, 10}]
```



# 60. Error Function and Related Functions

## Contents

Erf . . . . .	280	FresnelC . . . . .	280	InverseErf . . . . .	281
Erfc . . . . .	280	FresnelS . . . . .	281	InverseErfc . . . . .	281

## Erf

**Erf[z]**  
returns the error function of z.  
**Erf[z0, z1]**  
returns the result of Erf[z1] - Erf[z0].

Erf[x] is an odd function:


```
>> Erf[-x]
      -Erf[x]

>> Erf[1.0]
      0.842701

>> Erf[0]
      0

>> {Erf[0, x], Erf[x, 0]}
      {Erf[x], -Erf[x]}

>> Plot[Erf[x], {x, -2, 2}]
```



## Erfc


**Erfc[z]**  
returns the complementary error function of z.

```
>> Erfc[-x] / 2
      (2 - Erfc[x]) / 2

>> Erfc[1.0]
      0.157299

>> Erfc[0]
      1

>> Plot[Erfc[x], {x, -2, 2}]
```



## FresnelC

**FresnelC[z]**  
is the Fresnel C integral C(z).

```
>> FresnelC[{0, Infinity}]
      {0, 1/2}

>> Integrate[Cos[x^2 Pi/2], {x, 0, z}]
      FresnelC[z]
```



## FresnelS


`FresnelS[z]`  
is the Fresnel S integral  $S(z)$ .

```
>> FresnelS[{0, Infinity}]  
       $\left\{0, \frac{1}{2}\right\}$   
  
>> Integrate[Sin[x^2 Pi/2], {x, 0,  
      z}]  
      FresnelS[z]
```

## InverseErf

`InverseErf[z]`  
returns the inverse error function of  $z$ .

```
>> InverseErf /@ {-1, 0, 1}  
       $\{-\infty, 0, \infty\}$   
  
>> Plot[InverseErf[x], {x, -1, 1}]
```



`InverseErf[z]` only returns numeric values for  
 $-1 \leq z \leq 1$ :

```
>> InverseErf /@ {0.9, 1.0, 1.1}  
      {1.16309,  $\infty$ , InverseErf[1.1]}
```

## InverseErfc

`InverseErfc[z]`  
returns the inverse complementary error function of  $z$ .

```
>> InverseErfc /@ {0, 1, 2}  
       $\{\infty, 0, -\infty\}$ 
```

# 61. Exponential Integral and Special Functions

## Contents

---

ExpIntegralE . . . . . 282

ExpIntegralEi . . . . . 282

ProductLog . . . . . 282

---

## ExpIntegralE

ExpIntegralE[n, z]  
returns the exponential integral function  
 $E_n(z)$ .

```
>> ExpIntegralE[2.0, 2.0]  
0.0375343
```

## ExpIntegralEi

ExpIntegralEi[z]  
returns the exponential integral function  
 $Ei(z)$ .

```
>> ExpIntegralEi[2.0]  
4.95423
```

## ProductLog

ProductLog[z]  
returns the value of the Lambert W function  
at z.

The defining equation:


```
>> z == ProductLog[z] * E ^  
ProductLog[z]  
True
```

Some special values:

```
>> ProductLog[0]  
0  
  
>> ProductLog[E]  
1
```

The graph of ProductLog:

```
>> Plot[ProductLog[x], {x, -1/E, E  
}]
```



## 62. Gamma and Related Functions

### Contents

---

Gamma . . . . .	283	Pochhammer . . . . .	283
-----------------	-----	----------------------	-----

---

### Gamma

In number theory the logarithm of the gamma function often appears. For positive real numbers, this can be evaluated as  $\text{Log}[\text{Gamma}[z]]$ .

`Gamma[z]`  
is the gamma function on the complex number  $z$ .  
`Gamma[z, x]`  
is the upper incomplete gamma function.  
`Gamma[z, x0, x1]`  
is equivalent to  $\text{Gamma}[z, x0] - \text{Gamma}[z, x1]$ .

`Gamma[z]` is equivalent to  $(z - 1)!$ :

```
>> Simplify[Gamma[z] - (z - 1)!]
0
```

Exact arguments:


```
>> Gamma[8]
5040
>> Gamma[1/2]
 $\sqrt{\pi}$ 
>> Gamma[1, x]
 $E^{-x}$ 
>> Gamma[0, x]
ExpIntegralE[1, x]
```

Numeric arguments:

```
>> Gamma[123.78]
 $4.21078 \times 10^{204}$ 
>> Gamma[1. + I]
 $0.498016 - 0.15495I$ 
```

Both Gamma and Factorial functions are continuous:

```
>> Plot[{Gamma[x], x!}, {x, 0, 4}]
```



### Pochhammer

The Pochhammer symbol or rising factorial often appears in series expansions for hypergeometric functions. The Pochhammer symbol has a definite value even when the gamma functions which appear in its definition are infinite.

`Pochhammer[a, n]`  
is the Pochhammer symbol  $(a)_n$ .

```
>> Pochhammer[4, 8]
6652800
```

## 63. Orthogonal Polynomials

### Contents

ChebyshevT . . . . .	284	HermiteH . . . . .	284	LegendreP . . . . .	285
ChebyshevU . . . . .	284	JacobiP . . . . .	284	LegendreQ . . . . .	285
GegenbauerC . . . . .	284	LaguerreL . . . . .	285	SphericalHarmonicY . . . . .	285

### ChebyshevT

**ChebyshevT**[*n*, *x*]  
returns the Chebyshev polynomial of the first kind  $T_n(x)$ .

```
>> ChebyshevT[8, x]
1 - 32x^2 + 160x^4 - 256x^6 + 128x^8

>> ChebyshevT[1 - I, 0.5]
0.800143 + 1.08198I
```

### ChebyshevU

**ChebyshevU**[*n*, *x*]  
returns the Chebyshev polynomial of the second kind  $U_n(x)$ .

```
>> ChebyshevU[8, x]
1 - 40x^2 + 240x^4 - 448x^6 + 256x^8

>> ChebyshevU[1 - I, 0.5]
1.60029 + 0.721322I
```

### GegenbauerC

**GegenbauerC**[*n*, *m*, *x*]  
returns the Gegenbauer polynomial  $C_n^{(m)}(x)$ .

```
>> GegenbauerC[6, 1, x]
-1 + 24x^2 - 80x^4 + 64x^6
```

```
>> GegenbauerC[4 - I, 1 + 2 I, 0.7]
-3.2621 - 24.9739I
```

### HermiteH

**HermiteH**[*n*, *x*]  
returns the Hermite polynomial  $H_n(x)$ .

```
>> HermiteH[8, x]
1 680 - 13 440x^2 + 13 ~
~ 440x^4 - 3 584x^6 + 256x^8

>> HermiteH[3, 1 + I]
-28 + 4I

>> HermiteH[4.2, 2]
77.5291
```

### JacobiP

**JacobiP**[*n*, *a*, *b*, *x*]  
returns the Jacobi polynomial  $P_n^{(a,b)}(x)$ .

```
>> JacobiP[1, a, b, z]
a/2 - b/2 + z (1 + a/2 + b/2)

>> JacobiP[3.5 + I, 3, 2, 4 - I]
1 410.02 + 5 797.3I
```

## LaguerreL

**LaguerreL**[*n*, *x*]  
returns the Laguerre polynomial  $L_n(x)$ .  
**LaguerreL**[*n*, *a*, *x*]  
returns the generalised Laguerre polynomial  $L^a_n(x)$ .

>> **LaguerreL**[8, *x*]

$$1 - 8x + 14x^2 - \frac{28x^3}{3} + \frac{35x^4}{12} - \frac{7x^5}{15} + \frac{7x^6}{180} - \frac{x^7}{630} + \frac{x^8}{40320}$$

>> **LaguerreL**[3/2, 1.7]  
-0.947134

>> **LaguerreL**[5, 2, *x*]

$$21 - 35x + \frac{35x^2}{2} - \frac{7x^3}{2} + \frac{7x^4}{24} - \frac{x^5}{120}$$

## LegendreP

**LegendreP**[*n*, *x*]  
returns the Legendre polynomial  $P_n(x)$ .  
**LegendreP**[*n*, *m*, *x*]  
returns the associated Legendre polynomial  $P^m_n(x)$ .

>> **LegendreP**[4, *x*]

$$\frac{3}{8} - \frac{15x^2}{4} + \frac{35x^4}{8}$$


>> **LegendreP**[5/2, 1.5]  
4.17762

>> **LegendreP**[1.75, 1.4, 0.53]  
-1.32619

>> **LegendreP**[1.6, 3.1, 1.5]  
-0.303998 - 1.91937I

LegendreP can be used to draw generalized Lissajous figures:

>> **ParametricPlot**[ {**LegendreP**[7, *x*], **LegendreP**[5, *x*]}, {*x*, -1, 1}]



## LegendreQ

**LegendreQ**[*n*, *x*]  
returns the Legendre function of the second kind  $Q_n(x)$ .  
**LegendreQ**[*n*, *m*, *x*]  
returns the associated Legendre function of the second  $Q^m_n(x)$ .

>> **LegendreQ**[5/2, 1.5]  
0.036211 - 6.56219I

>> **LegendreQ**[1.75, 1.4, 0.53]  
2.05499

>> **LegendreQ**[1.6, 3.1, 1.5]  
-1.71931 - 7.70273I

## SphericalHarmonicY

**SphericalHarmonicY**[*l*, *m*, *theta*, *phi*]  
returns the spherical harmonic function  $Y_l^m(\theta, \phi)$ .

>> **SphericalHarmonicY**[3/4, 0.5, Pi/5, Pi/3]  
0.254247 + 0.14679I

>> **SphericalHarmonicY**[3, 1, *theta*, *phi*]

$$\frac{\sqrt{21} (1 - 5\cos[\theta])^2}{8\sqrt{\pi}} E^{l\phi} \sin[\theta]$$

## 64. Exponential Integral and Special Functions

### Contents

---

LerchPhi . . . . .	286	Zeta . . . . .	286
--------------------	-----	----------------	-----

---

### LerchPhi

`LerchPhi[z,s,a]`  
gives the Lerch transcendent (z,s,a).

```
>> LerchPhi[2, 3, -1.5]
19.3893 - 2.1346I

>> LerchPhi[1, 2, 1/4]
17.1973
```

### Zeta

`Zeta[z]`  
returns the Riemann zeta function of z.

```
>> Zeta[2]

$$\frac{\pi^2}{6}$$


>> Zeta[-2.5 + I]
0.0235936 + 0.0014078I
```

## **65. Strings and Characters**

## 66. Characters in Strings

## Contents

CharacterRange . . . . .	288	LetterQ . . . . .	288	ToUpperCase . . . . .	289
Characters . . . . .	288	LowerCaseQ . . . . .	289	UpperCaseQ . . . . .	289
DigitO . . . . .	288	ToLowerCase . . . . .	289		

## CharacterRange

`CharacterRange["a", "b"]`  
returns a list of the Unicode characters  
from *a* to *b* inclusive.

```
>> CharacterRange["a", "e"]
{a,b,c,d,e}

>> CharacterRange["b", "a"]
{}

```

## Characters

`Characters["string"]`  
returns a list of the characters in *string*.

```
>> Characters["abc"]
{a, b, c}
```

## DigitQ

`DigitQ[string]` yields `True` if all the characters in the *string* are digits, and yields `False` otherwise.

```
>> DigitQ["9"]
True

>> DigitQ["a"]
False
```

```
>> DigitQ  
["010011010110000101110100011010000110100101100011"]  
  
True  
  
>> DigitQ["-123456789"]  
False
```

## LetterQ

`LetterQ[string]` yields `True` if all the characters in the *string* are letters, and yields `False` otherwise.

```
>> LetterQ["m"]
True

>> LetterQ["9"]
False

>> LetterQ["Mathics"]
True

>> LetterQ["Welcome to Mathics"]
False
```

## LowerCaseQ

`LowerCaseQ[s]`  
returns True if *s* consists wholly of lower case characters.

```
>> LowerCaseQ["abc"]
True
```



An empty string returns True.

```
>> LowerCaseQ[""]  
True
```

## ToLowerCase

`ToLowerCase[s]`  
returns *s* in all lower case.

```
>> ToLowerCase["New York"]  
new york
```

## ToUpperCase

`ToUpperCase[s]`  
returns *s* in all upper case.

```
>> ToUpperCase["New York"]  
NEW YORK
```

## UpperCaseQ

`UpperCaseQ[s]`  
returns True if *s* consists wholly of upper case characters.

```
>> UpperCaseQ["ABC"]  
True
```

An empty string returns True.

```
>> UpperCaseQ[""]  
True
```

# 67. Character Codes

## Contents

---

FromCharCode . . . 290

ToCharCode . . . 291

---

### FromCharCode

`FromCharCode[n]`  
returns the character corresponding to Unicode codepoint *n*.  
`FromCharCode[{n1, n2, ...}]`  
returns a string with characters corresponding to *n<sub>i</sub>*.  
`FromCharCode[{{n11, n12, ...}, {n21, n22, ...}, ...}]`  
returns a list of strings.


```
>> FromCharCode[100]
d
>> FromCharCode[228, "ISO8859
-1"]
ä
>> FromCharCode[{100, 101,
102}]
def
>> ToCharCode[%]
{100,101,102}
>> FromCharCode[{{97, 98, 99},
{100, 101, 102}}]
{abc,def}
>> ToCharCode["abc 123"] //
FromCharCode
abc 123
```

### ToCharCode

`ToCharCode["string"]`  
converts the string to a list of character codes (Unicode codepoints).  
`ToCharCode[{"string1", "string2", ...}]`  
converts a list of strings to character codes.

```
>> ToCharCode["abc"]
{97,98,99}
>> FromCharCode[%]
abc
>> ToCharCode["\[Alpha]\[Beta]\[Gamma]"]
{945,946,947}
>> ToCharCode["ä", "UTF8"]
{195,164}
>> ToCharCode["ä", "ISO8859
-1"]
{228}
>> ToCharCode[{"ab", "c"}]
{{97,98}, {99}}
>> ToCharCode[{"ab", x}]
Stringorlistofstringsexpectedatposition1inToCharCode[
x]].
ToCharCode [ {ab,x}]
```

```
>> ListPlot[ToCharacterCode["plot  
this string"], Filling -> Axis]
```



## 68. Operations on Strings

### Contents

---

<code>StringDrop</code> . . . . .	292	<code>StringPosition</code> . . . . .	293	<code>StringSplit</code> . . . . .	295
<code>StringInsert</code> . . . . .	293	<code>StringReplace</code> . . . . .	294	<code>StringTake</code> . . . . .	295
<code>StringJoin (&lt;&gt;)</code> . . . . .	293	<code>StringReverse</code> . . . . .	294	<code>StringTrim</code> . . . . .	295
<code>StringLength</code> . . . . .	293	<code>StringRiffle</code> . . . . .	294		

---

### StringDrop

```
StringDrop["string", n]
  gives string with the first n characters
  dropped.
StringDrop["string", -n]
  gives string with the last n characters
  dropped.
StringDrop["string", {n}]
  gives string with the nth character
  dropped.
StringDrop["string", {m, n}]
  gives string with the characters m through
  n dropped.
```

```
>> StringDrop["abcde", 2]
cde
>> StringDrop["abcde", -2]
abc
>> StringDrop["abcde", {2}]
acde
>> StringDrop["abcde", {2,3}]
ade
>> StringDrop["abcd", {3,2}]
abcd
>> StringDrop["abcd", 0]
abcd
```

### StringInsert

```
StringInsert["string", "snew", n]
  yields a string with snew inserted starting
  at position n in string.
StringInsert["string", "snew", -n]
  inserts a at position n from the end of
  "string".
StringInsert["string", "snew", {n_1,
n_2, ...}]
  inserts a copy of snew at each position n_i
  in string; the n_i are taken before any in-
  sersion is done.
StringInsert[{s_1, s_2, ...}, "snew",
n]
  gives the list of results for each of the s_i.
```

```
>> StringInsert["noting", "h", 4]
nothing
>> StringInsert["note", "d", -1]
noted
>> StringInsert["here", "t", -5]
there
>> StringInsert["adac", "he", {1,
5}]
headache
>> StringInsert[{"something", "
sometimes"}, " ", 5]
{some thing,some times}
>> StringInsert["1234567890123456",
".", Range[-16, -4, 3]]
1.234.567.890.123.456
```

## StringJoin (<>)

```
StringJoin["s1'", "s2", ...]  
returns the concatenation of the strings  
s1, s2, .
```

```
>> StringJoin["a", "b", "c"]  
abc  
  
>> "a" <> "b" <> "c" // InputForm  
"abc"
```

StringJoin flattens lists out:

```
>> StringJoin[{"a", "b"}] //  
InputForm  
"ab"  
  
>> Print[StringJoin[{"Hello", " ",  
{"world"}}, {"!"}]]  
  
Helloworld!
```

## StringLength

```
StringLength["string"]  
gives the length of string.
```

```
>> StringLength["abc"]  
3
```

StringLength is listable:

```
>> StringLength[{"a", "bc"}]  
{1, 2}  
  
>> StringLength[x]  
String expected.  
StringLength[x]
```

## StringPosition

```
StringPosition["string", patt]  
gives a list of starting and ending posi-  
tions where patt matches "string".  
StringPosition["string", patt, n]  
returns the first n matches only.  
StringPosition["string", {patt1, patt2,  
...}, n]  
matches multiple patterns.  
StringPosition[{s1, s2, ...}, patt]  
returns a list of matches for multiple  
strings.
```

```
>> StringPosition["123  
ABCxyABCzzzABCABC", "ABC"]  
{ {4, 6}, {9, 11}, {15, 17}, {18, 20} }  
  
>> StringPosition["123  
ABCxyABCzzzABCABC", "ABC", 2]  
{ {4, 6}, {9, 11} }
```

StringPosition can be useful for searching through text.

```
>> data = Import["ExampleData/  
EinsteinSzilLetter.txt"];  
  
>> StringPosition[data, "uranium"]  
{ {299, 305}, {870, 876}, {1538, 1~  
~544}, {1671, 1677}, {2300, 2306  
}, {2784, 2790}, {3093, 3099} }
```

## StringReplace

```
StringReplace["string'", "a"-"b"]  
replaces each occurrence of old with new  
in string.  
StringReplace["string", {"s1"-"sp1'",  
"s2"-"sp2"}]  
performs multiple replacements of each  
si by the corresponding spi in string.  
StringReplace["string", srules, n]  
only performs the first n replacements.  
StringReplace[{"string1'", "string2",  
...}, srules]  
performs the replacements specified by  
srules on a list of strings.
```

StringReplace replaces all occurrences of one substring with another:

```
>> StringReplace["xyxyxyxyxyxyxy",
  "xy" -> "A"]
AAxyxxAyA
```

Multiple replacements can be supplied:

```
>> StringReplace["xyzwxyzwxyzxyzw", {"xyz" -> "A", "w" -> "BCD"}]
ABCDABCDxABCD
```

Only replace the first 2 occurrences:

```
>> StringReplace["xyxyxyxyxyxyxy",
  "xy" -> "A", 2]
AAxyxyxyxyxy
```

Also works for multiple rules:

```
>> StringReplace["abba", {"a" -> "A",
  "b" -> "B"}, 2]
ABba
```

StringReplace acts on lists of strings too:

```
>> StringReplace[{"xyxyxy", "xyxyxyxyxyxy"}, "xy" -> "A"]
{AAxA, yAAxxAyA}
```

StringReplace also can be used as an operator:

```
>> StringReplace["y" -> "ies"]["city"]
cities
```

## StringReverse

```
StringReverse["string"]
  reverses the order of the characters in "string".
```

```
>> StringReverse["live"]
evil
```

## StringRiffle

```
StringRiffle[{s1, s2, s3, ...}]
  returns a new string by concatenating all the si, with spaces inserted between them.
StringRiffle[list, sep]
  inserts the separator sep between all elements in list.
StringRiffle[list, {'left', "sep", "right"}]
  use left and right as delimiters after concatenation.
```

```
>> StringRiffle[{"a", "b", "c", "d", "e"}]
a b c d e
>> StringRiffle[{"a", "b", "c", "d", "e"}, " "]
a, b, c, d, e
>> StringRiffle[{"a", "b", "c", "d", "e"}, {"(", " ", ")"}]
(a b c d e)
```

## StringSplit

```
StringSplit["s"]
  splits the string s at whitespace, discarding the whitespace and returning a list of strings.
StringSplit["s", d]
  splits s at the delimiter d.
StringSplit[s, {"d1", "d2", ...}]
  splits s using multiple delimiters.
StringSplit[{s_1, s_2, ...}, {"d1", "d2", ...}]
  returns a list with the result of applying the function to each element.
```

```
>> StringSplit["abc,123", ","]
{abc, 123}
>> StringSplit["abc 123"]
{abc, 123}
>> StringSplit["abc,123.456", {",", "."}]
{abc, 123, 456}
```

```
>> StringSplit["a b c",
  RegularExpression[" +"]]
{a,b,c}

>> StringSplit[{"a b", "c d"},
  RegularExpression[" +"]]
{{a,b},{c,d}}
```

## StringTake

```
StringTake["string", n]
  gives the first n characters in string.
StringTake["string", -n]
  gives the last n characters in string.
StringTake["string", {n}]
  gives the nth character in string.
StringTake["string", {m, n}]
  gives characters m through n in string.
StringTake["string", {m, n, s}]
  gives characters m through n in steps of s.
StringTake[{s1, s2, ...} spec]
  gives the list of results for each of the si.
```

```
>> StringTake["abcde", 2]
ab

>> StringTake["abcde", 0]

>> StringTake["abcde", -2]
de

>> StringTake["abcde", {2}]
b

>> StringTake["abcd", {2,3}]
bc

>> StringTake["abcdefgh", {1, 5,
  2}]
ace
```

Take the last 2 characters from several strings:

```
>> StringTake[{"abcdef", "stuv", "
  xyzw"}, -2]
{ef,uv,zw}
```

StringTake also supports standard sequence specifications

```
>> StringTake["abcdef", All]
abcdef
```

## StringTrim

```
StringTrim[s]
  returns a version of s with whitespace re-
  moved from start and end.
```

```
>> StringJoin["a", StringTrim[" \tb
  \n "], "c"]
abc

>> StringTrim["ababaxababyaabab",
  RegularExpression["(ab)+"]]
axababya
```

# 69. String Patterns

## Contents

DigitCharacter . . . . .	296	StartOfLine . . . . .	297	StringMatchQ . . . . .	298
EndOfLine . . . . .	296	StartOfString . . . . .	297	WhitespaceCharacter . . . . .	299
EndOfString . . . . .	296	StringCases . . . . .	298	WordBoundary . . . . .	299
LetterCharacter . . . . .	297	StringExpression (~~) . . . . .	298	WordCharacter . . . . .	299
		StringFreeQ . . . . .	298		

## DigitCharacter

DigitCharacter  
represents the digits 0-9.

```
>> StringMatchQ["1", DigitCharacter  
  ]  
True  
  
>> StringMatchQ["a", DigitCharacter  
  ]  
False  
  
>> StringMatchQ["12",  
  DigitCharacter]  
False  
  
>> StringMatchQ["123245",  
  DigitCharacter..]  
True
```

## EndOfLine

EndOfString  
represents the end of a line in a string.

```
>> StringReplace["aba\nbba\na\nab",  
  "a" ~~EndOfLine -> "c"]  
abc  
  bbc  
  c  
  ab
```

```
>> StringSplit["abc\ndef\nhij",  
  EndOfLine]  
{abc,  
  def,  
  hij}
```

## EndOfString

EndOfString  
represents the end of a string.

Test whether strings end with "e":

```
>> StringMatchQ[#, __ ~~ "e" ~~  
  EndOfString] &/@ {"apple", "  
  banana", "artichoke"}  
{True, False, True}  
  
>> StringReplace["aab\nabb", "b" ~~  
  EndOfString -> "c"]  
aab  
  abc
```

## LetterCharacter

LetterCharacter  
represents letters.

```
>> StringMatchQ[#, LetterCharacter]  
  & /@ {"a", "1", "A", " ", "."}  
{True, False, True, False, False}
```



LetterCharacter also matches unicode characters.

```
>> StringMatchQ["\[Lambda]",  
LetterCharacter]  
True
```

## StartOfLine

StartOfString  
represents the start of a line in a string.

```
>> StringReplace["aba\nbba\na\nab",  
StartOfLine ~~ "a" -> "c"]  
  
cba  
bba  
c  
cb  
  
>> StringSplit["abc\ndef\nhij",  
StartOfLine]  
  
{abc  
,def  
,hij}
```

## StartOfString

StartOfString  
represents the start of a string.

Test whether strings start with "a":

```
>> StringMatchQ[#, StartOfString ~~  
"a" ~~__] &/@ {"apple", "banana",  
"artichoke"}  
  
{True, False, True}  
  
>> StringReplace["aba\nabb",  
StartOfString ~~ "a" -> "c"]  
  
cba  
abb
```

## StringCases

StringCases["string", pattern]  
gives all occurrences of pattern in string.  
StringReplace["string", pattern -> form]  
gives all instances of form that stem from  
occurrences of pattern in string.  
StringCases["string", {pattern1, pattern2,  
...}]  
gives all occurrences of pattern1, pattern2,  
....  
StringReplace["string", pattern, n]  
gives only the first n occurrences.  
StringReplace[{ "string1", "string2",  
... }, pattern]  
gives occurrences in string1, string2, ...

```
>> StringCases["axbaxxb", "a" ~~x_  
~~"b"]  
  
{axb}  
  
>> StringCases["axbaxxb", "a" ~~x_  
~~"b"]  
  
{axbaxxb}  
  
>> StringCases["axbaxxb", Shortest  
["a" ~~x_ ~~"b"]]  
  
{axb, axxb}  
  
>> StringCases["-abc- def -uvw- xyz",  
Shortest["-" ~~x_ ~~"-"] ->  
x]  
  
{abc, uvw}  
  
>> StringCases["-öhi- -abc- .-.",  
"- " ~~x : WordCharacter .. ~~"-"]  
-> x]  
  
{öhi, abc}  
  
>> StringCases["abc-abc xyz-uvw",  
Shortest[x : WordCharacter .. ~~  
"- " ~~x_] -> x]  
  
{abc}  
  
>> StringCases["abba", {"a" -> 10,  
"b" -> 20}, 2]  
  
{10, 20}  
  
>> StringCases["a#ä_123",  
WordCharacter]  
  
{a, ä, 1, 2, 3}
```

```
>> StringCases["a#ä_123",
LetterCharacter]
{a,ä}
```

## StringExpression (~~)

`StringExpression[s_1, s_2, ...]`  
represents a sequence of strings and symbolic string objects *s<sub>i</sub>*.

```
>> "a" ~~ "b" // FullForm
"ab"
```

## StringFreeQ

`StringFreeQ["string", patt]`  
returns True if no substring in *string* matches the string expression *patt*, and returns False otherwise.  
`StringFreeQ[{‘s1’, “s2”, ...}, patt]’`  
returns the list of results for each element of string list.  
`StringFreeQ[‘string’, {p1, p2, ...}]’`  
returns True if no substring matches any of the *pi*.  
`StringFreeQ[patt]`  
represents an operator form of `StringFreeQ` that can be applied to an expression.

```
>> StringFreeQ["mathics", "m" ~~__
~~"s"]
False
>> StringFreeQ["mathics", "a" ~~__
~~"m"]
True
>> StringFreeQ["Mathics", "MA" ,
IgnoreCase -> True]
False
>> StringFreeQ[{"g", "a", "laxy", "
universe", "sun"}, "u"]
{True, True, True, False, False}
```

```
>> StringFreeQ["e" ~~__ ~~"u"] /@
{"The Sun", "Mercury", "Venus",
"Earth", "Mars", "Jupiter", "
Saturn", "Uranus", "Neptune"}
{False, False, False, True,
True, True, True, True, False}
>> StringFreeQ[{"A", "Galaxy", "Far",
"Far", "Away"}, {"F" ~~__ ~~"
r", "aw" ~~__}], IgnoreCase ->
True]
{True, True, False, False, False}
```

## StringMatchQ

```
>> StringMatchQ["abc", "abc"]
True
>> StringMatchQ["abc", "abd"]
False
>> StringMatchQ["15a94xcZ6", (
DigitCharacter | LetterCharacter
)..]
True
Use StringMatchQ as an operator
>> StringMatchQ[LetterCharacter] ["a"]
True
```

## WhitespaceCharacter

`WhitespaceCharacter`  
represents a single whitespace character.

```
>> StringMatchQ["\n",
WhitespaceCharacter]
True
>> StringSplit["a\nb\r\nc\r\n",
WhitespaceCharacter]
{a,b,c,d}
```

For sequences of whitespace characters use `Whitespace`:

```
>> StringMatchQ[" \n",
WhitespaceCharacter]
False
```

```
>> StringMatchQ[" \n", Whitespace]
True
```

## WordBoundary

WordBoundary  
represents the boundary between words.

```
>> StringReplace["apple banana
orange artichoke", "e" ~~
WordBoundary -> "E"]
appleE banana orangeE artichokeE
```

## WordCharacter

WordCharacter  
represents a single letter or digit character.

```
>> StringMatchQ[#, WordCharacter]
&/@ {"1", "a", "A", ",", " "}
{True, True, True, False, False}
```

Test whether a string is alphanumeric:

```
>> StringMatchQ["abc123DEF",
WordCharacter..]
True

>> StringMatchQ["$b;123",
WordCharacter..]
False
```

# 70. Regular Expressions

## Contents

---

RegularExpression . . . 300

---

## RegularExpression

`RegularExpression['regex']`  
represents the regex specified by the  
string `"regex"`.

```
>> StringSplit["1.23, 4.56 7.89",  
  RegularExpression["(\\s|,)+"]]  
{1.23,4.56,7.89}
```

# 71. File Formats

Built-in Importers.

# 72. HTML

Basic implementation for a HTML importer

## Contents

HTML'DataImport . . 302	HTML'ImageLinksImport 302	HTML'TitleImport . . 302
HTML'Parser'HTMLGetString 302	HTML'PlaintextImport 302	HTML'XMLObjectImport 303
HTML'HyperlinksImport 302	HTML'SourceImport . 302	

### HTML'DataImport

```
>> Import["ExampleData/
PrimeMeridian.html", "Data"][[1,
1, 2, 3]]

{Washington, D.C., 77°03'56.07 W
(1 897) or 77°04'02.24 W (NAD 27)
or 77°04'01.16 W (NAD 83), New
Naval Observatory meridian}
```

### HTML'PlaintextImport

```
>> DeleteDuplicates[StringCases[
Import["ExampleData/
PrimeMeridian.html"],
RegularExpression["Wiki[a-z
]+"]]

{Wikipedia, Wikidata,
Wikibase, Wikimedia}
```

### HTML'Parser'HTMLGetString

### HTML'HyperlinksImport

```
>> Import["ExampleData/
PrimeMeridian.html", "Hyperlinks
"][[1]]

/wiki/Prime_meridian_(Greenwich)
```

### HTML'SourceImport

```
>> DeleteDuplicates[StringCases[
Import["ExampleData/
PrimeMeridian.html", "Source"],
RegularExpression["<t[a-z]+>"]]

{<title>, <tr>, <th>, <td>}
```

### HTML'ImageLinksImport

```
>> Import["ExampleData/
PrimeMeridian.html", "ImageLinks
"][[6]]

//upload.wikimedia.org/wikipedia/commons/thumb/d/d5/Prime_meridian.jpg/180px-Prime_meridian.jpg
```

### HTML'TitleImport

```
>> Import["ExampleData/
PrimeMeridian.html", "Title"]

Prime meridian - Wikipedia
```

### HTML'XMLObjectImport

```
>> Part[Import["ExampleData/
PrimeMeridian.html", "XMLObject
"], 2, 3, 1, 3, 2]

XMLElement[title, {}, {Prime
meridian - Wikipedia}]
```

# 73. HTML

Basic implementation for a HTML importer

## Contents

---

HTML'DataImport . . . 303	HTML'ImageLinksImport 303	HTML'TitleImport . . . 303
HTML'Parser'HTMLGetString 303	HTML'PlaintextImport 303	HTML'XMLObjectImport 304
HTML'HyperlinksImport 303	HTML'SourceImport . . . 303	

---

### HTML'DataImport

```
>> Import["ExampleData/  
PrimeMeridian.html", "Data"][[1,  
1, 2, 3]]  
  
{Washington, D.C., 77°03'56.07 W  
(1 897) or 77°04'02.24 W (NAD 27)  
or 77°04'01.16 W (NAD 83), New  
Naval Observatory meridian}
```

### HTML'PlaintextImport

```
>> DeleteDuplicates[StringCases[  
Import["ExampleData/  
PrimeMeridian.html"],  
RegularExpression["Wiki[a-z  
]+"]] ]  
  
{Wikipedia, Wikidata,  
Wikibase, Wikimedia}
```

### HTML'Parser'HTMLGetString

### HTML'HyperlinksImport

```
>> Import["ExampleData/  
PrimeMeridian.html", "Hyperlinks  
"][[1]]  
  
/wiki/Prime_meridian_(Greenwich)
```

### HTML'SourceImport

```
>> DeleteDuplicates[StringCases[  
Import["ExampleData/  
PrimeMeridian.html", "Source"],  
RegularExpression["<t[a-z]+>"]] ]  
  
{<title>, <tr>, <th>, <td>}
```

### HTML'ImageLinksImport

```
>> Import["ExampleData/  
PrimeMeridian.html", "ImageLinks  
"][[6]]  
  
/upload.wikimedia.org/wikipedia/commons/thumb/d/d5/Prime_meridian.jpg/180px-Prime_meridian.jpg
```

### HTML'TitleImport

```
>> Import["ExampleData/  
PrimeMeridian.html", "Title"]  
  
Prime meridian - Wikipedia
```

### HTML'XMLObjectImport

```
>> Part[Import["ExampleData/  
PrimeMeridian.html", "XMLObject  
"], 2, 3, 1, 3, 2]  
  
XMLElement[title, {}, {Prime  
meridian - Wikipedia}]
```

# 74. XML

## Contents

---

XML'PlaintextImport . 304

XML'TagsImport . . . 304  
XML'Parser'XMLGetString 304

XML'XMLObjectImport 304

---

### XML'PlaintextImport

```
>> StringReplace[StringTake[Import
["ExampleData/InventionNo1.xml",
"Plaintext"],31],
FromCharacterCode[10]->"/"]
MuseScore 1.2/2012-09-12/5.7/40
```

### XML'TagsImport

```
>> Take[Import["ExampleData/
InventionNo1.xml", "Tags"], 10]
{accidental, alter, arpeggiate,
articulations, attributes, backup,
bar-style, barline, beam, beat-type}
```

### XML'Parser'XMLGetString

```
>> Head[XML'Parser'XMLGetString["<a
></a>"]]
XMLObject[Document]
```

### XML'XMLObjectImport

```
>> Part[Import["ExampleData/
InventionNo1.xml", "XMLObject"],
2, 3, 1]
XMLElement[identification,
{ }, {XMLElement[encoding,
{ }, {XMLElement[software,
{ }, {MuseScore 1.2}],
XMLElement[encoding-date,
{ }, {2012-09-12}]]]]]
```

```
>> Part[Import["ExampleData/
Namespaces.xml"], 2]
XMLElement[book,
{{http://www.w3.org/2000/xmlns/,
xmlns}->urn:loc.gov:books},
{XMLElement[title, { }, {Cheaper
by the Dozen}],XMLElement[
{urn:ISBN:0-395-36341-6, number},
{ }, {1568491379}],XMLElement[
notes, { }, {XMLElement[p,
{{http://www.w3.org/2000/xmlns/,
xmlns}->http://www.w3.org/1999/xhtml},
{This is a, XMLElement[i,
{ }, {funny, book!}]]]]]]]
```



# **Part III.**

# **License**

# A. GNU General Public License

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program—to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers and authors protection, the GPL clearly explains that there is no warranty for this free software. For both users and authors sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

# TERMS AND CONDITIONS

## 0. Definitions.

This License refers to version 3 of the GNU General Public License.

Copyright also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

The Program refers to any copyrightable work licensed under this License. Each licensee is addressed as you. Licensees and recipients may be individuals or organizations.

To modify a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a modified version of the earlier work or a work based on the earlier work.

A covered work means either the unmodified Program or a work based on the Program.

To propagate a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To convey a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying. An interactive user interface displays Appropriate Legal Notices to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

## 1. Source Code.

The source code for a work means the preferred form of the work for making modifications to it. Object code means any non-source form of a work.

A Standard Interface means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The System Libraries of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A Major Component, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The Corresponding Source for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

## **2. Basic Permissions.**

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sub-licensing is not allowed; section 10 makes it unnecessary.

## **3. Protecting Users' Legal Rights From Anti-Circumvention Law.**

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the works users, your or third parties legal rights to forbid circumvention of technological measures.

## **4. Conveying Verbatim Copies.**

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

## **5. Conveying Modified Source Versions.**

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to keep intact all notices.
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an aggregate if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

## 6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A User Product is either (1) a consumer product, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, normally used refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

Installation Information for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User

Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

## **7. Additional Terms.**

Additional permissions are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
  - b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
  - c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
  - d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
  - e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
  - f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.
- All other non-permissive additional terms are considered further restrictions within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

## **8. Termination.**

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

## **9. Acceptance Not Required for Having Copies.**

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

## **10. Automatic Licensing of Downstream Recipients.**

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An entity transaction is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

## **11. Patents.**

A contributor is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's contributor version.

A contributor's essential patent claims are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, control includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a patent license is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To grant such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. Knowingly relying means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is discriminatory if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

## **12. No Surrender of Others' Freedom.**

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

## **13. Use with the GNU Affero General Public License.**

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.



## **14. Revised Versions of this License.**

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License or any later version applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

## **15. Disclaimer of Warranty.**

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM AS IS WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

## **16. Limitation of Liability.**

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

## **17. Interpretation of Sections 15 and 16.**

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

## **How to Apply These Terms to Your New Programs**

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the copyright line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>
```

```
This program is free software: you can redistribute it and/or
modify it under the terms of the GNU General Public License as
published by the Free Software Foundation, either version 3 of
the License, or (at your option) any later version.
```

```
This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `
show w`.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an about box.

You should also get your employer (if you work as a programmer) or school, if any, to sign a copyright disclaimer for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

## B. Included software and data

### Included data

*Mathics* includes data from Wikipedia that is published under the Creative Commons Attribution-Sharealike 3.0 Unported License and the GNU Free Documentation License contributed by the respective authors that are listed on the websites specified in "data/elements.txt".

### MathJax

Copyright © 2009-2010 Design Science, Inc.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

### mpmath

Copyright (c) 2005-2018 Fredrik Johansson and mpmath contributors

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

`<ol>` `<li>`Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. `<li>`Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. `<li>`Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. `</ul>`

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### Prototype

Copyright © 2005-2010 Sam Stephenson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## **pymimemagic**

Copyright (c) 2009, Xiaohai Lu All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of the <ORGANIZATION> nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## **SciPy**

Copyright I 2001, 2002 Enthought, Inc. All rights reserved.

Copyright I 2003-2019 SciPy Developers. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Enthought nor the names of the SciPy Developers may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS AS IS AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (IN-

INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## scriptaculous

Copyright © 2005-2008 Thomas Fuchs (<http://script.aculo.us>, <http://mir.aculo.us>)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the Software), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## SymPy

Copyright (c) 2006-2020 SymPy Development Team

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of SymPy nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

Patches that were taken from the Diofant project (<https://github.com/diofant/diofant>) are licensed as:

Copyright (c) 2006-2018 SymPy Development Team, 2013-2020 Sergey B Kirpichev

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of Diofant or SymPy nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

Submodules taken from the multipledispatch project (<https://github.com/mrocklin/multipledispatch>) are licensed as:

Copyright (c) 2014 Matthew Rocklin

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of multipledispatch nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

The files under the directory sympy/parsing/autolev/tests/pydy-example-repo are directly copied from PyDy project and are licensed as:

Copyright (c) 2009-2020, PyDy Authors All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of this project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL PYDY AUTHORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## Three.js

Copyright I 2010-2020 Three.js authors.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

# Index

\$Aborted, 47  
\$Assumptions, 61  
\$BaseDirectory, 198  
\$ByteOrdering, 47  
\$CharacterEncoding, 103  
\$CommandLine, 47  
\$DateStringFormat, 30  
\$ExportFormats, 207  
\$Failed, 47  
\$HistoryLength, 211  
\$HomeDirectory, 203  
\$ImportFormats, 208  
\$InitialDirectory, 203  
\$Input, 192  
\$InputFileName, 192  
\$InstallationDirectory, 203  
\$Line, 212  
\$Machine, 48  
\$MachineEpsilon, 131  
\$MachineName, 48  
\$MachinePrecision, 131  
\$MaxPrecision, 131  
\$MinPrecision, 131  
\$OperatingSystem, 203  
\$Packages, 48  
\$ParentProcessID, 49  
\$Path, 203  
\$PathnameSeparator, 204  
\$Post, 211  
\$Pre, 211  
\$PrePrint, 212  
\$PreRead, 212  
\$ProcessID, 49  
\$ProcessorType, 49  
\$RandomState, 272  
\$RootDirectory, 204  
\$ScriptCommandLine, 49  
\$SyntaxHandler, 212  
\$SystemCharacterEncoding, 105  
\$SystemID, 49  
\$SystemMemory, 49  
\$SystemTimeZone, 31  
\$SystemWordLength, 49  
\$TemporaryDirectory, 204  
\$TimeZone, 32  
\$UserBaseDirectory, 205  
\$UserName, 50  
\$Version, 50  
\$VersionNumber, 50  
  
Abort, 42  
Abs, 60  
AbsoluteFileName, 198  
AbsoluteThickness, 91  
AbsoluteTime, 28  
AbsoluteTiming, 28  
Accumulate, 141  
AiryAi, 275  
AiryAiPrime, 275  
AiryAiZero, 275  
AiryBi, 276  
AiryBiPrime, 276  
AiryBiZero, 276  
All, 115  
Alphabet, 103  
Alternatives, 53  
AngerJ, 276  
AnglePath, 250  
AngleVector, 251  
Apart, 234  
Append, 226  
AppendTo, 226  
Apply, 84  
ApplyLevel, 84  
ArcCos, 251  
ArcCosh, 251  
ArcCot, 252  
ArcCoth, 252  
ArcCsc, 252  
ArcCsch, 252  
ArcSec, 252  
ArcSech, 252  
ArcSin, 252  
ArcSinh, 253  
ArcTan, 253  
ArcTanh, 253  
Arg, 60  
Array, 223  
ArrayDepth, 80  
ArrayQ, 80  
Arrow, 91



Arrowheads, 93  
 Association, 115  
 AssociationQ, 116  
 Assuming, 61  
 AtomQ, 84  
 Attributes, 75  
 Automatic, 108  
 Axes, 108  
 Axis, 108  
  
 BarChart, 177  
 BaseForm, 33  
 BernsteinBasis, 186  
 BesselI, 276  
 BesselJ, 277  
 BesselJZero, 277  
 BesselK, 277  
 BesselY, 277  
 BesselYZero, 277  
 BezierCurve, 186  
 BezierFunction, 186  
 Binarize, 168  
 BinaryImageQ, 168  
 BinaryRead, 189  
 BinaryWrite, 189  
 Binomial, 215  
 BitLength, 257  
 Black, 149  
 Blank, 54  
 BlankNullSequence, 54  
 BlankSequence, 54  
 Blend, 146  
 Blue, 149  
 Blur, 168  
 Boole, 61  
 Bottom, 109  
 BoxData, 33  
 BoxMatrix, 169  
 BrayCurtisDistance, 260  
 Break, 42  
 Brown, 150  
 Byte, 190  
 ByteArray, 116  
 ByteCount, 85  
  
 C, 249  
 CanberraDistance, 260  
 Cancel, 234  
 Cases, 226  
 Catalan, 247  
 Catch, 42  
 Catenate, 116  
 Ceiling, 257  
 Center, 34  
 CentralMoment, 116  
  
 Character, 190  
 CharacterRange, 288  
 Characters, 288  
 ChartLabels, 109  
 ChartLegends, 109  
 ChebyshevT, 284  
 ChebyshevU, 284  
 Check, 34  
 ChessboardDistance, 260  
 Chop, 130  
 Circle, 93  
 ClearAttributes, 75  
 Close, 191  
 Closing, 169  
 ClusteringComponents, 116  
 CMYKColor, 143  
 Coefficient, 234  
 CoefficientArrays, 235  
 CoefficientList, 235  
 Collect, 236  
 ColorCombine, 169  
 ColorConvert, 146  
 ColorData, 178  
 ColorDistance, 143  
 Colorize, 169  
 ColorNegate, 146  
 ColorQuantize, 169  
 ColorSeparate, 169  
 CombinatoricaOld'BinarySearch, 85  
 Compile, 70  
 CompiledFunction, 70  
 Complement, 116  
 Complex, 61  
 Complexes, 241  
 ComplexInfinity, 247  
 Composition, 68  
 CompoundExpression, 43  
 Condition, 54  
 ConditionalExpression, 61  
 Conjugate, 62  
 Constant, 76  
 ConstantArray, 223  
 ContainsOnly, 117  
 Continue, 43  
 ContinuedFraction, 267  
 CoprimeQ, 218  
 CopyDirectory, 198  
 CopyFile, 198  
 Correlation, 117  
 Cos, 253  
 Cosh, 253  
 CosineDistance, 260  
 Cot, 253  
 Coth, 253  
 Count, 227

Covariance, 117  
 CreateDirectory, 199  
 CreateFile, 199  
 CreateTemporary, 199  
 Cross, 261  
 Csc, 254  
 Csch, 254  
 CubeRoot, 137  
 Cuboid, 165  
 Cyan, 150  
 Cylinder, 165  
  
 D, 241  
 DamerauLevenshteinDistance, 162  
 Darker, 146  
 DateDifference, 29  
 DateList, 29  
 DateObject, 29  
 DatePlus, 30  
 DateString, 30  
 Default, 72  
 Degree, 247  
 Delete, 117  
 DeleteCases, 227  
 DeleteDirectory, 199  
 DeleteDuplicates, 118  
 DeleteFile, 199  
 Denominator, 236  
 DensityPlot, 178  
 Depth, 85  
 Derivative, 242  
 DesignMatrix, 261  
 Det, 261  
 DiagonalMatrix, 80  
 DiamondMatrix, 169  
 DiceDissimilarity, 215  
 DigitCharacter, 296  
 DigitCount, 257  
 DigitQ, 288  
 Dilation, 170  
 Dimensions, 81  
 DirectedInfinity, 62  
 Directory, 199  
 DirectoryName, 199  
 DirectoryQ, 199  
 DirectoryStack, 200  
 DiscreteLimit, 242  
 DisjointQ, 118  
 Disk, 94  
 DiskMatrix, 170  
 Dispatch, 55  
 Divide, 137  
 Divisors, 267  
 Do, 43  
 DominantColors, 147  
  
 Dot, 81  
 Drop, 227  
 DSolve, 249  
  
 E, 247  
 EasterSunday, 30  
 EdgeDetect, 170  
 EdgeForm, 95  
 EditDistance, 162  
 Eigensystem, 261  
 Eigenvalues, 261  
 Eigenvectors, 262  
 ElementData, 113  
 EndOfFile, 191  
 EndOfLine, 296  
 EndOfString, 296  
 Environment, 47  
 Erf, 280  
 Erfc, 280  
 Erosion, 170  
 EuclideanDistance, 262  
 EulerGamma, 247  
 EvenQ, 218  
 ExactNumberQ, 62  
 Except, 55  
 Exp, 254  
 Expand, 236  
 ExpandAll, 237  
 ExpandDenominator, 237  
 ExpandFileName, 200  
 ExpIntegralE, 282  
 ExpIntegralEi, 282  
 Exponent, 238  
 Export, 207  
 ExportString, 207  
 Expression, 191  
 Extract, 227  
  
 Factor, 238  
 Factorial, 63  
 Factorial2, 63  
 FactorInteger, 267  
 FactorTermsList, 238  
 Failure, 118  
 Fibonacci, 221  
 FileName, 200  
 FileBaseName, 200  
 FileByteCount, 200  
 FileDate, 200  
 FileExistsQ, 200  
 FileExtension, 201  
 FileFormat, 207  
 FileHash, 201  
 FileInformation, 201  
 FileNameDepth, 201  
 FileNameJoin, 201

FileNames, 202  
 FileNameSplit, 202  
 FileNameTake, 202  
 FilePrint, 191  
 FileType, 202  
 FilledCurve, 95  
 Filling, 109  
 FilterRules, 72  
 Find, 191  
 FindClusters, 118  
 FindFile, 202  
 FindList, 203  
 FindRoot, 243  
 First, 228  
 FirstCase, 228  
 FirstPosition, 228  
 FixedPoint, 43  
 FixedPointList, 43  
 Flat, 76  
 Flatten, 85  
 Floor, 257  
 Fold, 119  
 FoldList, 119  
 FontColor, 96  
 For, 44  
 Format, 34  
 FractionalPart, 267  
 FreeQ, 86  
 FresnelC, 280  
 FresnelS, 281  
 FromCharacterCode, 290  
 FromContinuedFraction, 268  
 FromDigits, 258  
 Full, 109  
 FullForm, 34  
 FullSimplify, 238  
 Function, 68  
  
 Gamma, 283  
 Gather, 119  
 GatherBy, 120  
 GaussianFilter, 170  
 GCD, 218  
 GegenbauerC, 284  
 General, 34  
 Get, 191  
 GetEnvironment, 47  
 Glaisher, 248  
 GoldenRatio, 248  
 Graphics, 96  
 Graphics3D, 166  
 Gray, 151  
 GrayLevel, 143  
 Green, 151  
 Grid, 34  
  
 HammingDistance, 163  
 HankelH1, 277  
 HankelH2, 278  
 HarmonicNumber, 221  
 Hash, 130  
 Haversine, 254  
 Head, 86  
 HermiteH, 284  
 HexadecimalCharacter, 103  
 Histogram, 179  
 HoldAll, 76  
 HoldAllComplete, 76  
 HoldFirst, 76  
 HoldPattern, 55  
 HoldRest, 76  
 HTML'DataImport, 302, 303  
 HTML'HyperlinksImport, 302, 303  
 HTML'ImageLinksImport, 302, 303  
 HTML'Parser'HTMLGetString, 302, 303  
 HTML'PlaintextImport, 302, 303  
 HTML'SourceImport, 302, 303  
 HTML'TitleImport, 302, 303  
 HTML'XMLObjectImport, 302, 303  
 Hue, 144  
  
 I, 63  
 Identity, 69  
 IdentityMatrix, 81  
 If, 44  
 Im, 63  
 Image, 171  
 ImageAdd, 170  
 ImageAdjust, 171  
 ImageAspectRatio, 171  
 ImageChannels, 171  
 ImageColorSpace, 171  
 ImageConvolve, 171  
 ImageData, 172  
 ImageDimensions, 172  
 ImageImport, 172  
 ImageMultiply, 172  
 ImagePartition, 172  
 ImageQ, 173  
 ImageReflect, 173  
 ImageResize, 173  
 ImageRotate, 173  
 ImageSize, 109  
 ImageSubtract, 174  
 ImageTake, 174  
 ImageType, 174  
 Import, 207  
 ImportExport'RegisterExport, 208  
 ImportExport'RegisterImport, 209  
 ImportString, 208  
 In, 212

Indeterminate, 248  
 InexactNumberQ, 63  
 Infinity, 248  
 Infix, 35  
 Inner, 81  
 InputForm, 35  
 InputStream, 192  
 Insert, 120  
 Integer, 64  
 IntegerDigits, 131, 258  
 IntegerExponent, 268  
 IntegerLength, 259  
 IntegerQ, 64  
 IntegerReverse, 259  
 Integers, 243  
 IntegerString, 259  
 Integrate, 243  
 Interrupt, 44  
 IntersectingQ, 120  
 Intersection, 120  
 Inverse, 263  
 InverseErf, 281  
 InverseErfc, 281  
 InverseHaversine, 254  
  
 JaccardDissimilarity, 215  
 JacobiP, 284  
 Join, 120  
 Joined, 110  
  
 KelvinBei, 278  
 KelvinBer, 278  
 KelvinKei, 278  
 KelvinKer, 278  
 Key, 121  
 Keys, 121  
 Khinchin, 248  
 Kurtosis, 121  
  
 LABColor, 144  
 LaguerreL, 285  
 Large, 97  
 Last, 228  
 LCHColor, 144  
 LCM, 218  
 LeafCount, 121  
 LeastSquares, 263  
 Left, 35  
 LegendreP, 285  
 LegendreQ, 285  
 Length, 228  
 LerchPhi, 286  
 LetterCharacter, 296  
 LetterNumber, 103  
 LetterQ, 288  
  
 Level, 121  
 LevelQ, 122  
 LightBlue, 152  
 LightBrown, 153  
 LightCyan, 153  
 Lighter, 148  
 LightGray, 153  
 LightGreen, 154  
 LightMagenta, 154  
 LightOrange, 155  
 LightPink, 155  
 LightPurple, 156  
 LightRed, 156  
 LightYellow, 157  
 Limit, 244  
 Line, 97  
 LinearModelFit, 263  
 LinearSolve, 264  
 List, 122  
 Listable, 77  
 ListLinePlot, 180  
 ListPlot, 180  
 ListQ, 122  
 Locked, 77  
 Log, 254  
 Log10, 255  
 Log2, 255  
 LogisticSigmoid, 255  
 Longest, 55  
 Lookup, 122  
 LowerCaseQ, 288  
 LUVColor, 144  
  
 MachineNumberQ, 64  
 MachinePrecision, 131  
 Magenta, 157  
 MakeBoxes, 35  
 ManhattanDistance, 264  
 MantissaExponent, 268  
 Map, 86  
 MapAt, 87  
 MapIndexed, 87  
 MapThread, 88  
 MatchingDissimilarity, 216  
 MatchQ, 55  
 MathicsVersion, 48  
 MathMLForm, 35  
 MatrixExp, 264  
 MatrixForm, 36  
 MatrixPower, 264  
 MatrixQ, 82  
 MatrixRank, 264  
 MaxFilter, 174  
 Maximize, 107  
 MaxRecursion, 110

Mean, 141  
Median, 122  
MedianFilter, 174  
Medium, 97  
MemberQ, 229  
MemoryAvailable, 48  
MemoryInUse, 48  
Mesh, 110  
Message, 36  
MessageName, 36  
MinFilter, 174  
MinimalPolynomial, 239  
Minimize, 107  
Minus, 137  
Mod, 219  
Most, 229  
Multinomial, 216  
  
N, 132  
Names, 48  
Nearest, 123  
Needs, 203  
Nest, 44  
NestList, 45  
NestWhile, 45  
NextPrime, 268  
NHoldAll, 77  
NHoldFirst, 77  
NHoldRest, 77  
NIntegrate, 133  
NonAssociative, 36  
None, 123  
Norm, 265  
Normal, 223  
Normalize, 265  
NotListQ, 123  
NotOptionQ, 72  
Now, 30  
Null, 88  
NullSpace, 265  
Number, 192  
NumberForm, 36  
NumberQ, 64  
NumberString, 104  
Numerator, 239  
NumericQ, 133  
  
O, 244  
OddQ, 219  
Off, 36  
On, 37  
OneIdentity, 77  
OpenAppend, 192  
Opening, 175  
OpenRead, 192  
OpenWrite, 192  
Operate, 88  
Optional, 55  
OptionQ, 73  
Options, 73  
OptionsPattern, 56  
OptionValue, 73  
Orange, 158  
Order, 88  
OrderedQ, 88  
Orderless, 78  
Out, 213  
Outer, 82  
OutputForm, 37  
OutputStream, 193  
  
PadLeft, 123  
PadRight, 124  
ParametricPlot, 181  
ParentDirectory, 203  
Part, 229  
Partition, 124  
PartitionsP, 268  
Pattern, 56  
PatternsOrderedQ, 88  
PatternTest, 56  
Pause, 31  
Permutations, 223  
Pi, 248  
Pick, 230  
Piecewise, 64  
PieChart, 181  
Pink, 158  
PixelValue, 175  
PixelValuePositions, 175  
Plot, 183  
Plot3D, 184  
PlotPoints, 111  
PlotRange, 111  
Plus, 138  
Pochhammer, 283  
Point, 97  
PointSize, 98  
PolarPlot, 185  
Polygon, 98  
PolynomialQ, 239  
Position, 124  
PossibleZeroQ, 65  
Postfix, 37  
Power, 138  
PowerExpand, 239  
PowerMod, 219  
Precedence, 37  
Precision, 133  
Prefix, 38

Prepend, 230  
 PrependTo, 231  
 Prime, 269  
 PrimePi, 269  
 PrimePowerQ, 269  
 PrimeQ, 219  
 Print, 38  
 Product, 65  
 ProductLog, 282  
 Protect, 78  
 Protected, 78  
 PseudoInverse, 265  
 Purple, 159  
 Put, 193  
 PutAppend, 193  
 PythonForm, 38  
  
 QRDecomposition, 265  
 Quantile, 124  
 Quartiles, 125  
 Quiet, 38  
 Quotient, 220  
 QuotientRemainder, 220  
  
 Random, 270  
 RandomChoice, 270  
 RandomComplex, 271  
 RandomImage, 175  
 RandomInteger, 271  
 RandomPrime, 269  
 RandomReal, 271  
 RandomSample, 272  
 Range, 224  
 RankedMax, 125  
 RankedMin, 125  
 Rational, 65  
 Rationalize, 134  
 Re, 66  
 Read, 194  
 ReadList, 195  
 ReadProtected, 79  
 Real, 66  
 RealDigits, 134  
 RealNumberQ, 66  
 Reals, 244  
 Reap, 224  
 Record, 195  
 Rectangle, 99  
 Red, 159  
 RegularExpression, 300  
 RegularPolygon, 100  
 RemoveDiacritics, 104  
 RenameDirectory, 204  
 RenameFile, 204  
 Repeated, 57  
 RepeatedNull, 57  
 Replace, 57  
 ReplaceAll, 58  
 ReplaceList, 58  
 ReplacePart, 231  
 ReplaceRepeated, 59  
 ResetDirectory, 204  
 Rest, 231  
 Return, 45  
 Reverse, 125  
 RGBColor, 144  
 Riffle, 125  
 Right, 39  
 RogersTanimotoDissimilarity, 216  
 Root, 244  
 RotateLeft, 126  
 RotateRight, 126  
 Round, 134  
 Row, 39  
 RowReduce, 266  
 RSolve, 52  
 Rule, 59  
 RuleDelayed, 59  
 Run, 49  
 RussellRaoDissimilarity, 216  
  
 Scan, 89  
 Sec, 255  
 Sech, 255  
 SeedRandom, 272  
 Select, 232  
 SequenceHold, 79  
 Series, 244  
 SeriesData, 245  
 SessionTime, 31  
 SetAttributes, 79  
 SetDirectory, 204  
 SetFileDate, 204  
 SetStreamPosition, 195  
 Share, 49  
 Sharpen, 175  
 Show, 100  
 Sign, 66  
 Simplify, 239  
 Sin, 255  
 SingularValueDecomposition, 266  
 Sinh, 256  
 Skewness, 126  
 Skip, 195  
 Slot, 69  
 SlotSequence, 69  
 Small, 101  
 SokalSneathDissimilarity, 216  
 Solve, 245  
 Sort, 89

SortBy, 89  
 Sow, 224  
 Span, 232  
 SparseArray, 51  
 Sphere, 167  
 SphericalHarmonicY, 285  
 Split, 126  
 SplitBy, 127  
 Sqrt, 139  
 SquaredEuclideanDistance, 266  
 StandardDeviation, 127  
 StandardForm, 39  
 StartOfLine, 297  
 StartOfString, 297  
 StirlingS1, 221  
 StirlingS2, 221  
 StreamPosition, 196  
 Streams, 196  
 String, 105  
 StringCases, 297  
 StringContainsQ, 104  
 StringDrop, 292  
 StringExpression, 298  
 StringForm, 39  
 StringFreeQ, 298  
 StringInsert, 292  
 StringJoin, 293  
 StringLength, 293  
 StringMatchQ, 298  
 StringPosition, 293  
 StringQ, 104  
 StringRepeat, 105  
 StringReplace, 293  
 StringReverse, 294  
 StringRiffle, 294  
 StringSplit, 294  
 StringTake, 295  
 StringToStream, 196  
 StringTrim, 295  
 StruveH, 279  
 StruveL, 279  
 Subscript, 39  
 SubsetQ, 127  
 Subsets, 217  
 Subsuperscript, 39  
 Subtract, 139  
 Sum, 66  
 Superscript, 39  
 Switch, 45  
 Symbol, 90  
 SymbolName, 89  
 SymbolQ, 89  
 SymPyForm, 40  
 Syntax, 40  
 System'Convert'B64Dump'B64Decode, 206  
 System'Convert'B64Dump'B64Encode, 206  
 System'Convert'CommonDump'RemoveLinearSyntax,  
 206  
 System'ConvertersDump'\$extensionMappings,  
 206  
 System'ConvertersDump'\$formatMappings, 206  
 Table, 225  
 TableForm, 40  
 Take, 232  
 TakeLargest, 127  
 TakeLargestBy, 127  
 TakeSmallest, 128  
 TakeSmallestBy, 128  
 Tally, 128  
 Tan, 256  
 Tanh, 256  
 TeXForm, 40  
 Text, 101  
 TextData, 40  
 TextRecognize, 176  
 Thick, 101  
 Thickness, 101  
 Thin, 102  
 Thread, 90  
 Threshold, 176  
 Through, 90  
 Throw, 46  
 TicksStyle, 111  
 TimeConstrained, 31  
 TimeRemaining, 31  
 Times, 139  
 TimeUsed, 31  
 Timing, 32  
 Tiny, 102  
 ToBoxes, 41  
 ToCharacterCode, 290  
 ToExpression, 105  
 ToFileName, 205  
 Together, 240  
 ToLowerCase, 289  
 Top, 112  
 ToString, 105  
 Total, 141  
 ToUpperCase, 289  
 Tr, 266  
 Transliterate, 106  
 Transpose, 82  
 Tuples, 225  
 Union, 128  
 UnitVector, 128  
 Unprotect, 79  
 UpperCaseQ, 289  
 URLFetch, 210

URLSave, 205

Values, 129

Variables, 240

Variance, 129

VectorAngle, 266

VectorQ, 83

Verbatim, 59

WeberE, 279

Which, 46

While, 46

White, 159

Whitespace, 106

WhitespaceCharacter, 298

Word, 196

WordBoundary, 299

WordCharacter, 299

WordCloud, 176

Write, 197

WriteString, 197

XML'Parser'XMLGetString, 304

XML'PlaintextImport, 304

XML'TagsImport, 304

XML'XMLObjectImport, 304

XYZColor, 145

Yellow, 160

YuleDissimilarity, 217

Zeta, 286