## Power Consumption Attacks in Wireless Sensor Networks

Micah Thornton Ryan Sligh Bobby Santoski

Computer Science & Engineering, Southern Methodist University, USA, mathornton@smu.edu rsligh@smu.edu rsantoski@smu.edu

CSE 4344: Networks and Distributed Systems
Dallas, Texas
April 26, 2014



# Outline of today's talk

- Introduction
  - Topics
  - Motivation
- 2 Methodology
  - Overview
  - Battery Behavior
  - Attack Simulations
- Results and Analysis
  - Simulation Results
  - Mitigation Strategies
- 4 Conclusion
  - Future Work



#### Outline


- Introduction
  - Topics
  - Motivation
- 2 Methodology
  - Overview
  - Battery Behavior
  - Attack Simulations
- Results and Analysis
  - Simulation Results
  - Mitigation Strategies
- 4 Conclusion
  - Future Work




# Wireless Sensor Networks(WSNs)

- A wireless sensor network(WSN) is a network of Sensor Nodes
- Sensor Nodes send and receive wide varieties of data.
- Sensor Nodes generally operate in one of two states:
  - Sleep Mode less power draw, but can't receive and transmit
  - Active Mode more power draw, and can receive and transmit


# WSN examples (1) - p.H. and flow



### WSN examples (2) - fire detection and prevention



# WSN examples (3) - security systems




### Attacks on WSN power supplies


- Sensor Nodes are developed in bulk for mass deployment
- Bulk production has robbed WSNs of more robust battery lives
- limited battery lives make sensor nodes easy targets for Power Consumption Attacks
- A Power Consumption Attack drains the battery power of sensor nodes by forcing meaningless active mode time.
- Attackers hope to gain something by compromising nodes:
  - Protocol information for other attacks
  - temporary system downing
  - permanent system downing
  - competitive advantage
- Here we show some of our attack models



## Attack Models (1) - standard denial of sleep



# Attack Models (2) - inverse denial of sleep



# Attack Models (3) - routing power draw

Time Attack Model 3 Attacker Packet flow to and From Arbitrary Network Node Targeted Sensor Node

#### Problem

 How do we defend against a wide range of Power Consumption Attacks?

#### Outline

- Introduction
  - Topics
  - Motivation
- 2 Methodology
  - Overview
  - Battery Behavior
  - Attack Simulations
- Results and Analysis
  - Simulation Results
  - Mitigation Strategies
- 4 Conclusion
  - Future Work



### Overview

- we simulated standard denial of sleep attacks and routing power draw attacks on WSNs
- we first examined different batteries
- we then simply examined the time to compromise a node under various different assumptions

### **Battery Tests**

- The logical conclusion to mitigate risks of Power
   Consumption Attacks is to use more powerful batteries
- The batteries tested were:
  - Lead-Acid Batteries
  - Alkaline Long-Life Batteries
  - Carbon-Zinc Batteries
  - NiMH Batteries
  - NiCad Batteries
  - Lithium Ion Batteries
- With weights varying from **0.1 mg** to **1 mg**
- And Packet sizes varying from 2 bits to 1 kb
- We got approximately 700 simulation results from NS3



### **Attack Simulation**

- The attacks were simulated in an environment that allowed user defined:
  - Packet Size (bits)
  - Initial Node Energy (joules)
  - Power To Transmit Messages (Watts)
  - Power To Receive Messages (Watts)
  - speed of Transmission radios (bps)
- Each of these were variate for **55,000** simulations


#### Outline

- Introduction
  - Topics
  - Motivation
- 2 Methodology
  - Overview
  - Battery Behavior
  - Attack Simulations
- Results and Analysis
  - Simulation Results
  - Mitigation Strategies
- 4 Conclusion
  - Future Work




### Lithium Ion Results

#### Lithium Ion Batteries



# Comparing Attacks

Time to Compromise for certain attacks



# Previous Strategies

- Some risk mitigation strategies have already been adopted for use in WSNs:
  - Predefined Transfer Windows
  - Node Reception Memory
  - Jamming Detection Protocols
  - Low Power Wake-up Radio
  - Defined Maximum Path Length
- Many strategies are developed with specific attacks in mind
- Even our proposed strategies have already been deployed

# **Proposed Strategies**

- Targeted the root problem of all Power Consumption attacks:
   pre-defined battery life
- Installation of solar panels and other similar power regeneration devices.
- Attacks can still be mounted on the network, but would have to fight a endlessly renewing power source
- This addition could be costly, and distributors would need to shrink the size of their network
- But it is up to the distributor to examine there expected net benefit



#### Outline

- Introduction
  - Topics
  - Motivation
- 2 Methodology
  - Overview
  - Battery Behavior
  - Attack Simulations
- Results and Analysis
  - Simulation Results
  - Mitigation Strategies
- 4 Conclusion
  - Future Work



### **Future Work**

- Model and test additional attack types
- Do a cost benefit analysis of different types of batteries and alternative power sources
- compare cost benefits of other mitigation strategies