

Homework 5 W80


Austin Harnsberger



1/19/2015


5)

A)

```
r library(ISLR) logfit = glm(default ~ . - student, data = Default, family= binomial)
plot(logfit)
```







B)

```
r set.seed(1) train = sample(1:2500,1250,replace = FALSE) lm.fit = lm(default ~ balance,
data=Default, subset=train)

## Warning in model.response(mf, "numeric"): using type = "numeric" with a ## factor
response will be ignored

## Warning in Ops.factor(y, z$residuals): '-' not meaningful for factors

r attach(Default) mean((default -predict(lm.fit,Default))[-train]^2)

## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors

## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors

## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors

## [1] NA C)

r set.seed(3) train = sample(1:2500,1250,replace = FALSE) lm.fit = lm(default ~ balance,
data=Default, subset=train)

## Warning in model.response(mf, "numeric"): using type = "numeric" with a ## factor
response will be ignored

## Warning in Ops.factor(y, z$residuals): '-' not meaningful for factors

r attach(Default)

## The following objects are masked from Default (pos = 3): ## ## balance, default,
income, student

r mean((default -predict(lm.fit,Default))[-train]^2)
```

```

## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## [1] NA
r set.seed(12) train = sample(1:2500,1250,replace = FALSE) lm.fit = lm(default ~ balance,
data=Default, subset=train)
## Warning in model.response(mf, "numeric"): using type = "numeric" with a ## factor
response will be ignored
## Warning in Ops.factor(y, z$residuals): '-' not meaningful for factors
r attach(Default)
## The following objects are masked from Default (pos = 3): ## ## balance, default,
income, student ## ## The following objects are masked from Default (pos = 4): ## ##
balance, default, income, student
r mean((default -predict(lm.fit,Default))[-train]^2)
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## [1] NA
r set.seed(89) train = sample(1:2500,1250,replace = FALSE) lm.fit = lm(default ~ balance,
data=Default, subset=train)
## Warning in model.response(mf, "numeric"): using type = "numeric" with a ## factor
response will be ignored
## Warning in Ops.factor(y, z$residuals): '-' not meaningful for factors
r attach(Default)
## The following objects are masked from Default (pos = 3): ## ## balance, default,
income, student ## ## The following objects are masked from Default (pos = 4): ## ##
balance, default, income, student ## ## The following objects are masked from Default
(pos = 5): ## ## balance, default, income, student
r mean((default -predict(lm.fit,Default))[-train]^2)
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors
## [1] NA

```

```

r logfit = glm(default ~ ., data = Default, family= binomial) set.seed(1) train = sample(1:2500,1250,rep
= FALSE) lm.fit = lm(default ~ balance, data=Default, subset=train)

## Warning in model.response(mf, "numeric"): using type = "numeric" with a ## factor
response will be ignored

## Warning in Ops.factor(y, z$residuals): '-' not meaningful for factors

r attach(Default)

## The following objects are masked from Default (pos = 3): ## ## balance, default,
income, student ## ## The following objects are masked from Default (pos = 4): ## ##
balance, default, income, student ## ## The following objects are masked from Default
(pos = 5): ## ## balance, default, income, student ## ## The following objects are
masked from Default (pos = 6): ## ## balance, default, income, student

r mean((default -predict(lm.fit,Default))[-train]^2)

## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors

## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors


## Warning in Ops.factor(default, predict(lm.fit, Default)): '-' not ## meaningful for
factors

## [1] NA 8)
A)

r set.seed(1) y=rnorm(100) x=rnorm(100) y=x-2*x^2+rnorm (100) p= 1 because it is the set.seed n=
the number of observations in the plot, so rnorm(100)
B)

r plot(x~y)

```



bell curve along the X-axis with the mean roughly in the middle at $x = 0$

C) `set.seed(1) glm.fit = glm(y~x, data = y) cv.err = cv.glm(y, glm.fit) names(cv.err)`

`set.seed(34) glm.fit = glm(y~x, data = y) cv.err = cv.glm(y, glm.fit) names(cv.err)`