

Python drops

Rodrigo Girão Serrão

10-11-2025

Contents

Introduction	6
What is this book?	6
How to read this book?	6
Tips	7
1 – zip’s keyword argument <code>strict</code>	7
2 – Case-insensitive string comparisons	7
3 – Type unions with the vertical bar in <code>isinstance</code>	8
4 – Parsing integers from different bases	8
5 – First element that satisfies a condition	9
6 – Last element that satisfies a condition	9
7 – Unique elements from a list	10
8 – Schedule cleanup actions	11
9 – <code>map</code> with multiple arguments	11
10 – Remove punctuation from a string	11
11 – Count characters in a file	12
12 – Run-length encoding	12
13 – String prefixes and suffixes	13
14 – Multiple options in a single case statement	13
15 – Round to pretty whole numbers	13
16 – Type statements	14
17 – Create context managers with <code>contextlib.contextmanager</code>	14
18 – Immutable dictionary	15
19 – Self-debugging f-strings	15
20 – Dunder attribute <code>__file__</code>	16
21 – Current date and time	16
22 – Set operations with <code>dict.keys()</code>	16
23 – Chain multiple dictionaries	17
24 – Longest word in a string	18
25 – Dynamic attribute manipulation	18
26 – Notify parent class when subclassing	18
27 – Enforce keyword arguments for options	19
28 – Flag enumerations	19
29 – Use <code>Literal</code> for options	20
30 – Return value of a generator	20
31 – Enumerations of string values	21
32 – Most recently-modified file	21
33 – Normalise strings by removing accents	22
34 – Transpose a list of lists	22

35 – Inline lists and tuples	23
36 – Typing iterables instead of lists	23
37 – Multi-dictionary	24
38 – Global enumeration members	24
39 – Automatic enumeration values	25
40 – OS-agnostic line splitting	26
41 – Longest and shortest	26
42 – Bounded cache	27
43 – Read files in chunks	27
44 – Format specifier !r	28
45 – Counting values that satisfy a predicate	28
46 – Dot product idiom	29
47 – Batching API calls	29
48 – Redacting email addresses	30
49 – Random choices	30
50 – Dynamic regex replacements	31
51 – String constants	31
52 – Case-insensitive regular expressions	32
53 – Module <code>itertools</code> categorisation	32
54 – t-strings need processing	32
55 – Structural unpacking	33
56 – Ergonomic multiline strings	33
57 – Underscore in the REPL	34
58 – Subclassing immutable types	34
59 – Idiomatic sequence slicing	35
60 – File tail	35
61 – One-shot file I/O	36
62 – Formatting big numbers	36
63 – Named groups in regex	37
64 – Resolving paths	37
65 – Formatting dates with f-strings	38
66 – Concatenate files from handlers	38
67 – Generator recipe	39
68 – Split strings in two halves	40
69 – Regex multiline flag	40
70 – Extract assignments from conditionals	41
71 – File discovery by name pattern	41
72 – Structural pattern matching with dictionaries	42
73 – Slicing generators for debugging	42
74 – Peek at an iterable	42
75 – Match the structure of custom objects	43
76 – Built-in <code>next</code> with a default value	43
77 – Match an exact dictionary structure	44
78 – Undoable iterator with value history	45
79 – Typing overloads	45
80 – Bulk renaming files	46
81 – Structural validation and homogenisation	47
82 – Verbose regular expressions	47
83 – Extracting text data into a dict	48
84 – Generics syntax	49
85 – Add lists together, fast	49
86 – File modes	50

87 – Caching sets and frozen sets	50
88 – Constrained generics	51
89 – Natural alphabetical sorting	51
90 – Preserving decorated function metadata	52
91 – Timestamp file names	53
92 – Temporary directories	54
93 – Non-local variables	54
94 – Dynamic width string formatting	55
95 – Docstring <code>__doc__</code> attribute	55
96 – Common <code>__hash__</code> implementation	56
97 – Match word boundaries	57
98 – Custom containment checks	57
99 – Readable object names	57
100 – Filtering Truthy values	58
101 – Pretty-printing nested data structures	58
102 – methods <code>__str__</code> and <code>__repr__</code>	59
103 – Typing <code>*args</code> and <code>**kwargs</code>	59
104 – AST parsing	60
105 – Dunder method <code>__missing__</code>	61
106 – Custom <code>enum</code> search behaviour	61
107 – <code>map</code> ’s keyword argument <code>strict</code>	62
108 – Dynamic module attribute look-up	62
109 – Add typing to decorators	63
110 – Non-greedy regex quantifiers	63
111 – Type hints that refer to functions	64
112 – Two-dimensional range	64
113 – Constant variables	65
114 – <code>dict.fromkeys</code>	65
115 – Double leading underscore	66
116 – Send data into generators	66
117 – Dictionary creation idiom	67
118 – Safely overriding methods	67
119 – Efficiently extending a list	68
120 – All equal	68
121 – Paginate results	69
122 – Ignore exceptions	69
123 – Using properties	70
124 – Operate on two lists of numbers	70
125 – Enforce positional arguments	71
126 – Integer literals in multiple bases	71
127 – Remove punctuation functionally	72
128 – <code>pairwise</code> generalisation	72
129 – Prevent subclassing/overriding	73
130 – Make numbers more readable	73
131 – Efficiently count words in a string	74
132 – Efficiently count characters in a string	74
133 – Find files in a directory	75
134 – Invertible flags	75
135 – Class and instance attributes	75
136 – Strict batching	76
137 – Read-only attributes	76
138 – Alternative constructors as class methods	77

139 – Reduce boilerplate with dataclasses	77
140 – Compute partial sums with <code>accumulate</code>	78
141 – Regex matches across newlines	79
142 – Using fractions	79
143 – Decimals	79
144 – Safe random tokens	80
145 – <code>NotImplemented</code>	80
146 – Cycling over an iterable	81
147 – String formatting field alignment	81
148 – Set operations with operators	82
149 – <code>NotImplementedError</code>	83
150 – Colour in the REPL	83
151 – copy files	83
152 – Find similar words	84
153 – Forward references in annotations	85
154 – Compression algorithms	85
155 – <code>json</code> CLI	86
156 – Custom t-string processing	86
157 – <code>asyncio</code> introspection	87
158 – Grouping digits in the fractional part	87
159 – Error handling with multiple types	87
160 – Parse dates from strings	88
161 – min-heaps and max-heaps	88
162 – Check for <code>None</code> functionally	89
163 – Remote interactive debugging	89
164 – Chaining comparison operators	90
165 – Controlled string splitting	90
166 – <code>strftime</code> vs <code>strptime</code>	90
167 – Private members	91
168 – Truthy and Falsy	91
169 – Oxford comma	92
170 – <code>assert</code> statements with custom message	92
171 – Creating temporary files	93
172 – Title case	93
173 – Using a list as a stack	94
174 – Moving average	94
Themed index	96
A	96
B	96
C	97
D	97
E	98
F	98
G	98
H	99
I	99
J	99
K	99
L	99
M	100

N	100
O	100
P	100
R	101
S	101
T	102
U	103
V	103
Z	103
-	103
Conclusion	104

Introduction

What is this book?

This book collects the daily Python tips that I send to the mathspg drops newsletter. Short and actionable tips to make you smarter about Python.

How to read this book?

Browse it. Open it in a random page. Pick a random number and read the tip corresponding to that number. Do whatever you want, the book is yours!

Tips

1 – zip’s keyword argument strict

The Python built-in `zip` has a keyword argument `strict` that will raise an error if the 2 (or more) iterables that you pass to `zip` don’t have the same length.

Use this whenever you are passing arguments that should have the same length: it helps catch errors early.

Beware that `zip` only raises the error when it reaches the end of the shortest iterable. In other words, it doesn’t validate the lengths upfront.

That’s why you are able to print the first two names, and only then `zip` raises a `ValueError` when the list `lasts` ends:

```
firsts = ["Luke", "Darth", "Obi-Wan"]
lasts = ["Skywalker", "Vader"]
for first_name, last_name in zip(firsts, lasts, strict=True):
    print(f"{first_name} {last_name}")

Luke Skywalker
Darth Vader
Traceback (most recent call last):
  File "<python-input-0>", line 3, in <module>
    for first_name, last_name in zip(firsts, lasts, strict=True):
                                ~~~~~~
ValueError: zip() argument 2 is shorter than argument 1
```

Further reading:

- [Article about zip](#)

2 – Case-insensitive string comparisons

To perform case-insensitive string comparisons in Python, use the method `str.casefold`. This method exists precisely to let you perform case-insensitive comparisons.

You need it because [some characters in some languages are kinda funky!](#) (That’s the technical term – funky.)

Using `lower` or `upper` for case-insensitive comparisons only works if you’re working with strings that are 100% guaranteed to only contain ASCII characters. If you are working with Unicode, you need `casefold`.

Here is a small example using the German word for “street”. First, note how the string “straße” appears to be lowercase, but if you uppercase it and then lowercase it, you end up with a different string:

```
print("straße".lower())  
# straÙe
```

```
print("straße".upper().lower())  
# strasse
```

Now, note how the method `casefold` works just fine:

```
print("STRASSE".casefold() == "straße".casefold())  
# True
```

```
print("straße".casefold())  
# strasse
```

Further reading:

- [How to work with case-insensitive strings](#)

3 – Type unions with the vertical bar in `isinstance`

The vertical bar `|` can be used to combine types (to create type unions) since Python 3.10. This lets you create type unions in a very ergonomic way.

You can use it, for example, inside `isinstance` checks. This lets you check if a value belongs to one of two or more types, like so:

```
isinstance(x, typ1 | typ2 | ...)
```

This is definitely nicer than

```
isinstance(x, typ1) or isinstance(x, typ2) or ...
```

And it is also nicer than the traditional alternative with a tuple of types:

```
isinstance(x, (typ1, typ2, ...))
```

Here is a complete example:

```
def is_number(x):  
    return isinstance(x, int | float | complex)  
  
print(is_number(42)) # True  
print(is_number("hey")) # False
```

4 – Parsing integers from different bases

The built-in `int` can be used to parse integers from binary, octal, hexadecimal, and many other bases. To do this, you need to specify the base you want as the second argument of `int`.

The valid bases are 2 through 36. (You use 2 for binary, 8 for octal, and 16 for hexadecimal.)

```
print(int("13")) # 13  
print(int("101", 2)) # 5  
print(int("ff", 16)) # 255
```

The second argument can also be the special value `0`, which tells `int` to “guess” the base by parsing the integer as it if were an integer literal. (It “guesses” the base if you use the base prefix: `0b` for binary, `0o` for octal, `0x` for hexadecimal, and no prefix for decimal.)

```
print(int("0b101", 0)) # 5
print(int("0xff", 0)) # 255
```

Further reading:

- [Base conversion in Python.](#)

5 – First element that satisfies a condition

When you have an iterable and need to find the first element that satisfies a condition, you can use a generator expression and the built-in `next` to fetch that first element.

The generic recipe looks like this:

```
first = next(elem for elem in iterable if condition(elem))
```

This is a good idea because the generator expression/`next` combo ensures you only search until you find the element you care about. This means that you don't have to compute the condition on the values that come after the value that you wanted.

```
important_numbers = [42, 73, 10, 16, 0]
print(
    next(n for n in important_numbers if n % 2)
) # 73
```

If there's no such element, you'll either

1. get a `StopIteration` you need to handle:

```
important_numbers = [42, 10, 16, 0]
try:
    print(
        next(n for n in important_numbers if n % 2)
    )
except StopIteration:
    print("No odd numbers found!")
# No odd numbers found!
```

2. pass a default/sentinel value to `next` as its second argument:

```
important_numbers = [42, 10, 16, 0]
print(
    next(
        n for n in important_numbers if n % 2,
        None,
    )
) # None
```

6 – Last element that satisfies a condition

If you have a condition, you can get the last element of an iterable that satisfies that condition with `collections.deque` and a generator expression:

```
from collections import deque
```

```
last = deque(
```

```
(elem for elem in iterable if condition(elem)),
maxlen=1,
).pop()
```

If there are no such elements, the deque will be empty and popping gives an `IndexError`, so you may need to account for that. You can either

1. check if the deque has any elements before popping:

```
from collections import deque

important_numbers = [42, 10, 16, 0]
dq = deque((num for num in important_numbers if num % 2), maxlen=1)
if not dq:
    print("No odd numbers found!")
# No odd numbers found!
```

2. or you can handle the `IndexError` that you might get when popping:

```
from collections import deque

important_numbers = [42, 10, 16, 0]
try:
    last_odd = deque(
        (num for num in important_numbers if num % 2),
        maxlen=1,
    ).pop()
except IndexError:
    print("No odd numbers found!")
# No odd numbers found!
```

Further reading:

- [Overview of the module collections](#)
- [deque tutorial](#)

7 – Unique elements from a list

The built-in type `set` can be used if you need to compute the unique values from an iterable, like a list.

Because sets are unordered, the result will contain the unique values in an arbitrary order.

```
nums = [42, 73, 42, 42, 0, 73, 10, 10, 16]
for unique_num in set(nums):
    print(unique_num, end=" ")
# 0 73 42 10 16
```

If the order is important and you're running Python 3.8 or later, you can use `dict.fromkeys` instead:

```
nums = [42, 73, 42, 42, 0, 73, 10, 10, 16]
for unique_num in dict.fromkeys(nums):
    print(unique_num, end=" ")
# 0 73 42 10 16
```

These two options are very efficient and only work with hashable values.

Further reading:

-
- [Itertools recipes for unique_justseen, unique_everseen, and unique](#)

8 – Schedule cleanup actions

If you need to clean up resources when your Python program terminates, (for example, disconnect from a server or database), you can use the function `register` from the module `atexit`.

You pass in a function to `register`, and the function you pass it is scheduled to run when your program terminates (even if it terminates because of an exception).

`register` can also be used as a decorator:

```
import atexit

@atexit.register
def cleanup():
    """Clean up program resources."""
    fake_db.close_connection()
    print("All cleaned up!")
```

9 – map with multiple arguments

The Python built-in `map` can be used with 2 or more iterable arguments.

The function being mapped will take one argument from each iterable:

```
bases = [2, 3, 4, 2, 3, 4]
exps = [2, 2, 2, 3, 3, 3]

for num in map(pow, bases, exps):
    print(num, end=" ")
# 4 9 16 8 27 64
```

This can be more convenient to use than a list comprehension/generator expression in some situations:

```
nums = (b ** exp for b, exp in zip(bases, exps))
# vs
nums = map(pow, bases, exps)
```

For a bonus crazy use, here is how to use this to create an infinite stream of perfect squares:

```
from itertools import count, repeat

squares = map(pow, count(), repeat(2))
```

10 – Remove punctuation from a string

Don't use the method `replace` to remove punctuation from a string. Instead, use the method `translate`.

The method `translate` is an efficient and general-purpose method for replacing (or removing) multiple characters in a string simultaneously.

The method `translate` expects a "translation table" argument in a very specific format, but the string class method `maketrans` can build that for us:

```
import string

# print(string.punctuation) # !"#$%&'()*+,-./:;<=>?@[\\]^_`{|}~
punctuation_removal = str.maketrans("", "", string.punctuation)

s = "Hello, world!"
print(s.translate(punctuation_removal))
# Hello world
```

Further reading:

- [String translate and maketrans methods](#)

11 – Count characters in a file

You can use `chain` from the module `itertools` to iterate over the characters of a file, with `chain.from_iterable(f)`.

Pair it with `Counter`, from the module `collections`, and you have a way to count all characters in a file with `Counter(chain.from_iterable(f))`:

```
from collections import Counter
from itertools import chain

with open("/Users/rodrigogs/.zshrc") as f:
    chars = Counter(chain.from_iterable(f))

print(chars.most_common(5))
# [(' ', 583), ('e', 314), ('t', 273), ('o', 264), ('n', 216)]
```

Now... It's unlikely that you'll have to count the characters in a file very often. But this fun example helps you understand what `chain` can do, and `chain` is quite useful!

(**Note:** by default, line endings of the form `\r\n` will get turned into `\n`, so `\r` won't be counted. This may or may not be desirable.)

Further reading:

- [Overview of the module collections](#)
- [Overview of the module itertools](#)

12 – Run-length encoding

The module `itertools` has a very funky iterable called `groupby`. If you're imaginative, you can use it for all sorts of things.

One possible use-case is to compute the run-length encoding of an iterable. All it takes is to go through the grouped iterable and then compute the length of each group:

```
from itertools import groupby

def run_length_encoding(iterable):
    for val, group in groupby(iterable):
        yield val, len(list(group))
```

Each group is a lazy iterable itself, so you can't use `len` directly on it. That's why you see `len(list(group))` in the code above.

Here's an example usage:

```
print(list(
    run_length_encoding("AABOAA")
)) # [('A', 3), ('B', 1), ('O', 1), ('A', 2)]
```

13 – String prefixes and suffixes

Strings have four convenience methods to replace some slicing: `startswith`, `endswith`, `removeprefix`, and `removesuffix`.

These methods are preferred over the slicing alternatives because they are more convenient and more readable. (The methods `removeX` require Python 3.9+.)

Here are two examples operating on the start of a string:

```
string = "Hello, world!"
print(string.startswith("Hello"))
# True
print(string.removeprefix("Hello"))
# , world!
```

The methods `startswith` and `endswith` also accept a tuple of strings to check:

```
string = "abracadabra"
possible_prefixes = ("aa", "ab", "ac")
print(string.startswith(possible_prefixes))
# True
```

14 – Multiple options in a single case statement

Structural pattern matching lets you specify multiple options in the same case statement.

You separate the multiple options with a vertical bar `|`. Here is an example:

```
def walk(direction):
    match direction:
        case NORTH | UP:
            return (0, -1)
    ...
```

Further reading:

- [Structural pattern matching tutorial](#)

15 – Round to pretty whole numbers

The built-in `round` can be used to round numbers to nice, pretty integers. More concretely, you can use `round` to round numbers to powers of 10.

For example, to round \$1374 to \$1400 you would do `round(1374, -2)`.

The second argument of `round`, which must be an integer, will give you the power of 0.1 that the number will be rounded to:

```
n | 0.1 ** n |  
||  
2 | 0.01 |  
1 | 0.1 |  
0 | 1 |  
-1 | 10 |  
-2 | 100 |
```

16 – Type statements

Since Python 3.12 that you can use type statements to create type aliases, which can also be generic.

For example, the statement below creates a type alias called `Pair` that holds pairs of values of the same type:

```
type Pair[T] = tuple[T, T]
```

This is much shorter than the equivalent pre-Python 3.12 code using `typing.TypeAlias` and `typing.TypeVar`:

```
from typing import TypeAlias, TypeVar
```

```
T = TypeVar("T")
```

```
Pair: TypeAlias = tuple[T, T]
```

For both versions of the code, the following assignment type-checks:

```
p: Pair[int] = (3, 4)
```

Further reading:

- [type statement and type aliases](#)

17 – Create context managers with `contextlib.contextmanager`

The module `contextlib` provides a decorator `contextmanager` that you can use to implement your own context managers.

For that, you just create a generator that yields once. The code before the `yield` is the setup and the code after the `yield` is the cleanup.

Whatever you yield (if anything) can be captured by the `as ...` part of the `with` statement.

Here is an example that reimplements the built-in `open`:

```
from contextlib import contextmanager  
  
@contextmanager  
def my_open(path, mode):  
    try:  
        file = open(path, mode)  
        yield file  
    finally:  
        file.close()
```

The trick is that the `finally` will ensure we close the file, regardless of whether there is an error while working with the open file.

18 – Immutable dictionary

The module `types` exposes `MappingProxyType`, a type that's essentially an immutable dictionary.

So, if you want an immutable dictionary, create a regular one and wrap it in `MappingProxyType`:

```
from types import MappingProxyType

my_dict = MappingProxyType(
    {
        "url": "mathspp.com",
        "email": "rodrigo@mathspp.com",
    }
)

print(my_dict["url"])  # mathspp.com

# TypeErrors:
my_dict["name"] = "Rodrigo"
my_dict["url"] = ""
```

Be careful not to keep references to the underlying dictionary, though... If you do, and if you modify the underlying dictionary, the changes are reflected in the immutable dictionary:

```
from types import MappingProxyType

base_dict = {
    "url": "mathspp.com",
    "email": "rodrigo@mathspp.com",
}
immutable = MappingProxyType(base_dict)

print(immutable["url"])  # mathspp.com

base_dict["url"] = "example.com"
print(immutable["url"])  # example.com
```

Further reading:

- [How to make an Immutable Dict in Python](#)

19 – Self-debugging f-strings

f-strings have an awesome feature: if you include an equals sign `=` at the end of the formatted value, the f-string will show you the code and the value that you're formatting.

Here is an example:

```
name = "RoDrIg0"
print(f"Method title: {name.title() = }")
# Method title: name.title() = 'Rodrigo'
```

Note that the spaces around the equals sign `=` are not necessary but the result usually looks better if you include them.

20 – Dunder attribute `__file__`

The dunder attribute `__file__` can be used to get the full path of your Python script or module.

This can be useful, for example, to locate a resources folder that is “next” to your code in your project directory:

```
from pathlib import Path

print(__file__)
# /Users/rodrigogs/Documents/my_project/example.py

RESOURCES = (Path(__file__).parent / "res").resolve()
print(RESOURCES)
# /Users/rodrigogs/Documents/my_project/res
```

21 – Current date and time

The module `datetime` has data types that you can use to represent pure dates or dates with times:

1. `datetime.date`
2. `datetime.datetime`

Each class has a class method that gives you an instance of that class with the current date (and time), respectively:

1. `datetime.date.today`
2. `datetime.datetime.now`

```
import datetime as dt

today = dt.date.today()
print(today) # 2025-04-05

now = dt.datetime.now()
print(now) # 2025-04-05 19:29:13.437736
```

22 – Set operations with `dict.keys()`

Dictionaries have a method `keys` that returns a view over the keys of the dictionary. These objects support set operations, which means you can manipulate dictionary keys very efficiently and conveniently.

For example, for two dictionaries `dict1` and `dict2`, you can easily compute:

1. the keys available simultaneously in both dictionaries with `dict1.keys() & dict2.keys()`;
2. the keys available in `dict1` but not in `dict2` with `dict1.keys() - dict2.keys()`; and
3. the keys available in either dictionary with `dict1.keys() | dict2.keys()`.

Here are the corresponding examples:

```
en_pt = { # dict1
    "yellow": "amarelo",
    "red": "vermelho",
}
```

```
en_fr = { # dict2
    "red": "rouge",
    "blue": "bleu",
}

# Keys in both:
print(en_pt.keys() & en_fr.keys())
# {'red'}

# Keys in en_pt but not in en_fr:
print(en_pt.keys() - en_fr.keys())
# {'yellow'}

# Keys in either:
print(en_pt.keys() | en_fr.keys())
# {'red', 'yellow', 'blue'}
```

23 – Chain multiple dictionaries

You can use the object ChainMap from the module collections to create a unified view over a hierarchy of dictionaries. The ChainMap object accesses the underlying dictionaries in order, stopping once it finds the key you are looking for:

```
from collections import ChainMap

default = {
    "user": "user",
    "theme": "light",
    "lan": "en",
}

local = {
    "theme": "dark",
}

user = {
    "user": "rodrigo",
}

settings = ChainMap(user, local, default)

print(settings["user"]) # rodrigo
print(settings["theme"]) # dark
print(settings["lan"]) # en

The underlying dictionaries can still be modified and the changes are reflected in the chained view:

user["lan"] = "pt"
print(settings["lan"]) # pt
```

Further reading:

- [Module collections overview](#)

24 – Longest word in a string

The built-in `max` has a keyword parameter `key` that determines how objects are compared, allowing flexible comparisons.

For example, the idiom `max(..., key=len)` lets you find the longest item in a collection, namely, the longest word in a string:

```
s = "These are just some sensational words"
print(
    max(s.split(), key=len)
) # sensational
```

The built-ins `min` and `sorted` also have this keyword parameter.

25 – Dynamic attribute manipulation

The built-ins `getattr`, `setattr`, and `delattr`, can be used to manipulate attributes dynamically.

Whenever possible, you will want to use the dot syntax to access attributes, set attributes, and delete attributes, but these dynamic functions can be used when you have the name of the attribute you want to work with as a string that you computed programmatically.

The built-in `setattr` accepts the object you want to set an attribute on, the attribute name as a string, and the value the attribute will be set to:

```
class Colour:
    pass

c = Colour()
setattr(c, "r", 255) # c.r = 255
setattr(c, "g", 125) # c.g = 125
setattr(c, "b", 0)   # c.b = 0
```

The built-in `getattr` accepts the object you want to get an attribute from and the attribute you want to fetch. Typically, you will have the attribute name in a variable:

```
attr = "g"
print(getattr(c, attr)) # 125
print(c.g)              # 125
```

If you use the built-in `getattr` to access an attribute that isn't there, you get an exception `AttributeError`. Alternatively, you can pass in a third argument to `getattr`:

```
print(getattr(c, "x", "heh")) # heh
```

Finally, the built-in `delattr` will take the given object and delete the attribute specified from it:

```
delattr(c, "g")
print(c.g) # AttributeError
```

26 – Notify parent class when subclassing

The dunder class method `__init_subclass__` can be used to notify a class when it's subclassed. This is effective for some metaprogramming without having to resort to metaclasses.

In this example, the class `ParentCls` will print a message whenever it is subclassed:

```
class ParentCls:
    def __init_subclass__(cls, **kwargs):
        print(f"{cls} created with {kwargs = }")
```

The argument `cls` will be the subclass, and the keyword arguments `kwargs` come from the subclass definition:

```
class ChildCls(ParentCls, example=True):
    pass
```

When the class `ChildCls` is created, the parent class automatically prints the following:

```
<class '__main__.ChildCls'> created with kwargs = {'example': True}
```

27 – Enforce keyword arguments for options

You can use a single asterisk `*` in a function definition to force all following arguments to be keyword-only.

This is particularly helpful for arguments that act as options or as configuration values. Here is an example with a function that can return the temperature in a room in two units, Celsius and Fahrenheit:

```
def get_temperature(room, *, unit)
```

By using `*`, the second argument must be passed as a keyword argument:

```
get_temperature("bedroom", unit="celsius") # This works.
```

If you don't, you get an exception `TypeError`:

```
get_temperature("bedroom", "celsius") # TypeError
```

28 – Flag enumerations

The module `enum` contains a type `Flag` that you can use for enumerations that should support the Boolean operations `&` (AND), `|` (OR), `^` (XOR), and `~` (INVERT):

```
from enum import Flag, auto
```

```
class Color(Flag):
    RED = auto()
    GREEN = auto()
    BLUE = auto()
```

```
# Purple is red with blue:
purple = Color.RED | Color.BLUE
```

Flag enumerations also support other useful operations, like containment check:

```
# Is the flag GREEN set?
print(Color.GREEN in purple) # False
```

In Python 3.11+, you can also get a list of the individual flags that are set:

```
# What flags is `purple` composed of?
print(list(purple)) # [<Color.RED: 1>, <Color.BLUE: 4>]
```

29 – Use Literal for options

Use the type `Literal` from the module `typing` when a function accepts a small number of specific values that represent configurations or options.

For example, instead of

```
def get_temperature(city: str, unit: str) -> float: ...
```

you can do

```
from typing import Literal
```

```
def get_temperature(
    city: str,
    unit: Literal["celsius", "fahrenheit"],
) -> float:
    ...
```

You would still use the function with the plain strings:

```
print(get_temperature("Lisbon", "celsiu")) # 18.0
print(get_temperature("Lisbon", "fahrenheit")) # 64.4
```

One of the side-benefits of using the type `Literal` is that you're documenting the valid values.

30 – Return value of a generator

Generators can return a final value once they're finished:

```
def my_generator_function():
    yield 1
    yield 2
    return 73
```

This final value is then attached to the exception `StopIteration` that is raised when the generator is exhausted:

```
gen = my_generator_function()
print(next(gen), next(gen)) # 1 2
```

```
next(gen) # StopIteration: 73
```

You can extract this final value from the attribute value:

```
gen = my_generator_function()
print(next(gen), next(gen)) # 1 2
```

```
try:
    next(gen)
except StopIteration as err:
    print(err.value) # 73
```

Useful, for example, if you want your generator to produce some final summary statistics.

31 – Enumerations of string values

You shouldn't use random, loose string values in Python:

```
UP = "UP"
DOWN = "DOWN"

def move(direction: str) -> None:
    if direction == UP:
        print("Going up.")
    elif direction == DOWN:
        print("Going down.")
    else:
        raise ValueError()
```

Instead, you should use StrEnum from the module enum:

```
from enum import StrEnum

class Direction(StrEnum):
    UP = "UP"
    DOWN = "DOWN"

def move(direction: Direction) -> None:
    if direction == Direction.UP:
        print("Going up.")
    elif direction == Direction.DOWN:
        print("Going down.")
    else:
        raise ValueError()
```

String enumerations let you group strings values together, keeping them organised.

It also helps the IDE provide proper autocompletion when using those values. This is ideal for argument options, for example.

Note: enum.StrEnum is only available from Python 3.11 onward. In earlier versions, you can define an enumeration that inherits from enum.Enum and str:

```
from enum import Enum

class Direction(str, Enum):
    ...
```

32 – Most recently-modified file

Due to flexibility of the built-in max, it takes one single line of code to find the most recently-modified file in a directory:

```
from pathlib import Path

folder_to_search = Path("/path/to/folder")
most_recent = max(folder.iterdir(), key=lambda p: p.stat().st_mtime)
print(most_recent)  # /path/to/folder/some_file.txt
```

This works by using the method `stat` that provides access to file statistics and then using the attribute `st_mtime` that contains the time of the last file modification.

This line of code is highly flexible!

Do you want to skip directories and only consider files? In that case, filter with a generator expression:

```
most_recent = max(
    (p for p in folder.iterdir() if p.is_file()),
    key=lambda p: p.stat().st_mtime,
)
```

Do you want the search to be recursive? Then, use `folder.rglob(*)` instead of `folder.iterdir()`.

33 – Normalise strings by removing accents

My name is “Rodrigo Girão Serrão” and the “~” on top of the As are standard in Portuguese... And just like the “~”, there are hundreds of other accents and weird marks used by hundreds of other languages!

If you don’t want any of it, you can write a short Python function that gets rid of those:

```
import unicodedata

def remove_accents(string):
    return "".join(
        char for char in unicodedata.normalize("NFD", string)
        if unicodedata.category(char) != "Mn"
    )
```

This function can be useful when writing a “slugify” function, for example:

```
def slugify(string):
    return remove_accents(string).lower().replace(" ", "-")

print(slugify("Rodrigo Girão Serrão")) # rodrigo-girao-serrao
```

The function `remove_accents` leverages the built-in module `unicodedata`, which provides tools to work with the Unicode standard.

(In case you are wondering, the call `unicodedata.normalize("NFD", string)` separates the accents from the letters:)

```
print(list(unicodedata.normalize("NFD", "ääääñ")))
# ['a', '´', 'a', '´', 'a', '´', 'a', '´', 'n', '´']
```

34 – Transpose a list of lists

The built-in `zip` can be used with the splat operator `*` to transpose a list of iterables.

For example, you can go from

```
persons = [{"Han", "Solo"}, {"Obi-Wan", "Kenobi"}, {"Darth", "Vader"}]

to

firsts = ('Han', 'Obi-Wan', 'Darth')
lasts = ('Solo', 'Kenobi', 'Vader')
```

You just need a simple line of code:

```
firsts, lasts = zip(*persons)
```

If you look closely, this is zip undoing what zip can do, since you can recreate persons by doing zip(firsts, lasts):

```
print(list(zip(firsts, lasts)))  
# [('Han', 'Solo'), ('Obi-Wan', 'Kenobi'), ('Darth', 'Vader')]
```

The only thing to note is that zip produces tuples, so the original variable persons contained a list of lists and the output from the snippet above is a list of tuples.

Further reading:

- [Article about zip](#)

35 – Inline lists and tuples

The splat operator * can be used to inline iterables inside other iterables. Just use the asterisk * when writing out a comma-separated list of values and whatever iterable the asterisk is next to will be “flattened” or unpacked in that position.

This means that using *iterable in a comma-separated list will be as if the values from iterable had been written explicitly in that place.

Even works with generators!

```
firsts = ("Han", "Obi-Wan", "Darth")
```

```
def more_firsts(): # Generator  
    yield "Frodo"  
    yield "Gandalf"
```

```
huge_crossover = [  
    "Harry", "Hermione", "Ron",  
    *firsts,  
    *more_firsts(),  
    "Guido",  
]
```

```
print(huge_crossover)  
# ['Harry', 'Hermione', 'Ron',  
#  'Han', 'Obi-Wan', 'Darth',  
#  'Frodo', 'Gandalf', 'Guido']
```

36 – Typing iterables instead of lists

Setting the type of function arguments to list when all you need is to be able to iterate over that value is a mistake:

```
# Why must `files` be a list?!  
def create_files(files: list[Path]) -> None:  
    for file in files:  
        ...
```

Thankfully, it's a mistake that is easy to fix: use `Iterable`:

```
from collections.abc import Iterable # Python 3.9+
```

```
def create_files(files: Iterable[Path]) -> None: ...
```

(In Python 3.8, use `typing.Iterable`. In Python 3.9+, use `collections.abc.Iterable`.)

Using `list` is bad because it prevents you from using tuples, generators, iterables from `itertools`, other collections, etc.

Note: keep in mind that if you need to be able to iterate twice or more over the same iterable, you might want to use `Sequence` instead of `Iterable` because of iterators. Iterators are iterables but they can only be iterated over once.

37 – Multi-dictionary

You can create a multi-dictionary in Python with `collections.defaultdict` and the built-in `list` with `multidict = collections.defaultdict(list)`:

```
from collections import defaultdict
```

```
multidict = defaultdict(list)
```

This creates a dictionary that maps every single key to an empty list by default, which is why you use `defaultdict` in the first place:

```
print(multidict["SW"]) # []  
print(multidict["LotR"]) # []
```

Then, when you want to “add a value to a key”, you instead append to the list mapped to by that key:

```
multidict["SW"].append("Han Solo")  
multidict["SW"].append("R2D2")  
print(multidict["SW"]) # ['Han Solo', 'R2D2']
```

However, it goes without saying that this is “cheating”: the dictionary still maps each key to a single list. You’re just leveraging the fact that lists can store multiple values in them to.

Further reading:

- [Module collections overview](#)

38 – Global enumeration members

The module `enum` has a lot of little-known useful tools. For example, you can use the decorator `enum.global_enum` to automatically export your enumeration members to the global namespace of your module.

This means that you can access enumeration members as `re.MULTILINE` instead of `re.RegexFlag.MULTILINE` (yup, the module `re` uses this!).

The decorator `global_enum` can be used on all types of enumerations; the snippet below applies it to a flag enumeration:

```
from enum import Flag, auto, global_enum
```

```
@global_enum
```

```
class FilePermissions(Flag):
    READ = auto()
    WRITE = auto()
    EXECUTE = auto()
```

After defining the enumeration, enumeration members can be used as if they were globals:

```
BASE_PERMISSIONS = READ | WRITE
```

Accessing members through the enumeration class still works, though.

Further reading:

- [Module enum overview](#)

39 – Automatic enumeration values

The module `enum` provides a function `auto` that you can use to automatically generate values for your enumeration members.

The default behaviour is to create successive integers starting at 1 for a standard enumeration:

```
from enum import Enum, auto
```

```
class Letter(Enum):
    A = auto()
    B = auto()
```

```
print(Letter.A.value) # 1
print(Letter.B.value) # 2
```

The function `auto` is also smart enough to specialise appropriately, depending on the type of enumeration.

For flag enumerations, it produces powers of 2 for the flags:

```
from enum import Flag, auto
```

```
class Permissions(Flag):
    READ = auto()      # 1
    WRITE = auto()     # 2
    EXECUTE = auto()   # 4
```

```
print(repr(Permissions.EXECUTE))
# <Permissions.EXECUTE: 4>
```

For string enumerations, it generates lowercase strings that match the member names:

```
from enum import StrEnum, auto
```

```
class Direction(StrEnum):
    NORTH = auto() # north
    SOUTH = auto() # south
    ...
```

```
print(repr(Direction.NORTH))
# <Direction.NORTH: 'north'>
```

Further reading:

-
- [Module enum overview](#)

40 – OS-agnostic line splitting

Do you want to split a piece of text into its lines?

You'd think `text.split("\n")` would do the trick, right..?

It kind of does, but not very well. If you're working with the contents of Windows files, that might not work perfectly because of carriage return characters.

The most robust way to split a string into its lines is with the method `str.splitlines`! If you want to preserve the line-ending characters, use `.splitlines(keepends=True)`.

For example, assume the file `some_file.txt` lives on a Windows machine:

```
windows_string = WindowsPath("some_file.txt").read_text()
```

The lines of this file might be terminated with `"\r\n"` instead of just `"\n"`. If that's the case, using `.split("\n")` will leave the invisible carriage returns:

```
print(windows_string.split("\n"))
# ['This is a\r',
#  'multiline string\r',
#  'from a Windows machine.']
```

Using `.splitlines` fixes that:

```
print(windows_string.splitlines())
# ['This is a',
#  'multiline string',
#  'from a Windows machine.']
```

If you set `keepends=True`, the line-ending characters are left on the lines:

```
print(windows_string.splitlines(keepends=True))
# ['This is a\r\n',
#  'multiline string\r\n',
#  'from a Windows machine.']
```

41 – Longest and shortest

The built-ins `max` and `min` have a keyword argument `key` that lets you change the frame of reference for comparisons.

If you then use `functools.partial` to attach another function to `key`, you essentially build new functions just like LEGOs.

My two favourite examples:

1. `max + key=len` builds the function `longest`; and
2. `min + key=len` builds the function `shortest`.

```
from functools import partial
```

```
longest = partial(max, key=len)
shortest = partial(min, key=len)
```

```
words = "This is a truly extraordinary sentence".split()
print(longest(words))  # extraordinary
print(shortest(words)) # a
```

42 – Bounded cache

If you have a deterministic function with no side-effects that gets called very often, consider caching its results. If said function lives in a long-running application (e.g., a web server), make sure you don't run out of memory by ensuring the cache has a maximum sizes.

You can do both of these things with the decorator `functools.lru_cache`, which accepts the cache size as an argument.

For example, `@lru_cache(1024)` in the snippet below creates a cache that saves up to 1024 different call results.

```
from functools import lru_cache

@lru_cache(1024)
def function_to_cache(*args): ...

# Some function calls...

print(function_to_cache.cache_info().currsize)  # 35
print(function_to_cache.cache_info())
# CacheInfo(hits=12, misses=35, maxsize=1024, currsize=35)
```

You can access cache information by using the method `.cache_info` that is added to the function that gets a cache.

43 – Read files in chunks

The built-in `iter` can be used to turn functions into iterables. In its not-so-well-known form, `iter(f, sentinel)` creates an iterable that calls the function `f` until the function returns the value `sentinel`.

For example, paired with `functools.partial`, you can use it to create a “chunk” reader that reads files in chunks:

```
from functools import partial

with open("bee-movie-script.txt", "r") as f:
    chunk_reader = iter(partial(f.read, 16), "")
    for chunk in chunk_reader:
        print(chunk)

"""
According to all
known laws of a
viation, there i
s no way a bee s
hould be able to
...
"""
```

Further reading:

- [Making an iterator out of a function](#)

44 – Format specifier !r

When you're using f-strings, you can use the format specifier !r to use a value's debugging representation instead of pretty-printing it.

Some values and types cannot be distinguished from one another if you pretty-print them, but can if you use their debugging representation. For example, if a string represents an integer, you can't distinguish it from the same integer when printing:

```
s = "3"
print(f"{s}") # 3
# !? Was `s` the string "3" or the integer 3?
```

Using !r makes it clearer what's being printed:

```
print(f"{s!r}") # '3'
```

Here's another example:

```
from fractions import Fraction

one_third = Fraction(1, 3)
print(f"{one_third}, {one_third!r}")
# 1/3, Fraction(1, 3)
```

Further reading:

- [str and repr](#)

45 – Counting values that satisfy a predicate

(This is my favourite line of Python code. Really.)

To count the values of an iterable that satisfy a given predicate (a function that returns True/False) or a given condition, use the built-in sum and a generator expression:

```
sum(predicate(value) for value in iterable)
```

This idiom works in 3 parts:

1. the generator expression goes over all values you want to consider;
2. predicate(value) evaluates the condition, producing True or False; and
3. the built-in sum accumulates all the Boolean values, effectively counting the number of Trues.

If you actually have a predicate function, you might prefer the version sum(map(predicate, iterable)). If you want to use an ad-hoc expression as the condition, then use the generator expression:

```
ages = [42, 73, 16, 10, 4, 6]

can_vote = sum(age > 18 for age in ages)
print(can_vote) # 2
```

46 – Dot product idiom

The **dot product** is a mathematical operation that can be computed with a simple Python idiom using the module operator:

```
import operator

sum(map(operator.mul, vec1, vec2))
```

The snippet above assumes `vec1` and `vec2` are iterables that represent vectors. This idiom was present in the documentation of the module `itertools` up to Python 3.11.

Then, in Python 3.12, the built-in `zip` got the keyword argument `strict`, which made the idiom evolve into something that looks a bit more complicated:

```
from itertools import starmap
import operator

sum(starmap(operator.mul, zip(vec1, vec2, strict=True)))
```

We're using `zip(..., strict=True)` to ensure the vectors have the same size and `zip` produces tuples, so `starmap` is being used to “unpack” that tuple into the two arguments to `operator.mul`.

Then, in Python 3.14, the built-in `map` got a similar keyword argument `strict`, which means the idiom can go back to its simpler form with the extra safety check:

```
import operator

sum(map(operator.mul, vec1, vec2, strict=True))
```

47 – Batching API calls

Since Python 3.12 that the module `itertools` has `batched`: it accepts an iterable and it produces batches of values from that iterable.

You can use this for all sorts of batch processing. For example, you can use `batched` to batch API calls.

Many APIs have ways to handle one request or multiple similar requests at the same time. For example, my newsletter subscriber has an API endpoint that allows me to add tags to a subscriber. However, there is a similar endpoint that allows me to do the same thing to multiple subscribers at the same time.

The second option means I hit the API fewer times, which makes my code run faster. There's less back-and-forth over the network.

Here's the pseudo-code for comparison. First, handling a single user per request:

```
users_to_update = [...]
for user in users_to_update:
    api.add_tag(user, "some tag")
```

Now, the pseudo-code for the batch updates:

```
from itertools import batched

users_to_update = [...]
# The API can't handle more than 50 users at a time.
for user_batch in batched(users_to_update, 50): # <--
    api.add_tag_to_users(user_batch, "some tag")
```

48 – Redacting email addresses

You can use f-strings and the string formatting specification language to create an effect of redacted or private data. For example, the function below redacts part of your email address:

```
def redact_email(email):
    user, _, domain = email.partition("@")
    return f"{user[:2]}*{<{len(user)}}@{domain}"

print(redact_email("rodrigo@mathspp.com"))
# ro*****@mathspp.com
```

The part that is doing the heavy lifting is the section `*{<{len(user)}}{}` inside the f-string formatting:

1. `{len(user)}` uses the length of the variable `user` to determine the width of the field where `user[:2]` (the first two characters of the user) will be inserted;
2. `<` tells Python to align `user[:2]` on the left of that field; and
3. `*` tells Python to fill empty space with the character asterisk.

You could modify the function to also mask the domain, for example.

Note: for very security-sensitive use-cases, you might want to randomise the number of asterisks shown, instead of making the string match the correct length.

49 – Random choices

Predictability is usually helpful, but it can also be quite boring. On the other hand, randomness isn't always helpful, but sometimes it's the only way to get something done.

(As a real-world example, the generic profile pictures in [the testimonials page on my website](#) have random patterns and random colours.)

To pick a random value from a list, you have two alternatives:

- Use `random.choices` if you want to pick values with replacement (values can be repeated):

```
import random

coin_sides = ["heads", "tails"]

print(random.choices(coin_sides, k=4))
# ['heads', 'tails', 'tails', 'tails']
```

- Use `random.sample` if you want to pick values without replacement (values cannot be repeated):

```
import random

colours = ["red", "green", "blue",
           "black", "white"]
print(random.sample(colours, k=3))
# ['black', 'green', 'blue']
```

For either, set `k` to specify how many values you want to draw from the given list.

Note: for security-sensitive randomness, use the module `secrets`; not the module `random`.

50 – Dynamic regex replacements

The module `re` allows you to do dynamic string replacements. That is, search and replace for certain patterns and then replace them with *other* things that are not constant.

For this, you need a function that accepts a regex match and returns a replacement.

For example, the function `replace` below (admittedly, a poorly-named function), accepts a match and returns a string of asterisks that is as long as the full match:

```
def replace(match):  
    return "*" * len(match.group(0))
```

Then, when using `re.sub`, pass it the function that does the replacements instead of specifying a fixed string:

```
import re  
  
text = "I know Python, C, C++, JavaScript, and Haskell."  
  
bad_words = r"C(\+\+)?|JavaScript"  
  
print(re.sub(bad_words, replace, text))  
# I know Python, *, ***, *****, and Haskell.
```

Further reading:

- [Dynamic string replacements with regex blog article](#)

51 – String constants

The module `string` defines many useful constants that you can, and should, use! These will save you the time of defining the constants yourself and prevent plenty of easily-avoidable bugs.

Here are three examples:

```
import string  
  
print(string.ascii_lowercase)  
# abcdefghijklmnopqrstuvwxyz  
  
print(string.digits)  
# 0123456789  
  
print(string.punctuation)  
# !"#$%&'()*+,-./:;<=>?@[\\]^_`{|}~
```

If you find that this tip is silly, consider the fact that I found over 10,000 repositories on GitHub with bugs because they had typos when defining constants with the full latin alphabet. These bugs could have been avoided by using `string.ascii_lowercase`...

Further reading:

- [Finding and fixing over 10,000 bugs on GitHub blog article.](#)

52 – Case-insensitive regular expressions

Regular expressions can start with the flag `(?i)`, marking them as case-insensitive:

```
import re

print(re.match(r"hey", "HeY"))
# None

print(re.match(r"(?i)hey", "HeY"))
# <re.Match object; span=(0, 3), match='HeY'>
```

53 – Module `itertools` categorisation

A good way to think about the module `itertools` is to remember it has five categories of iterables:

1. reshaping iterables: `batched`, `chain`, `groupby`, `islice`, and `pairwise`;
2. filtering iterables: `compress`, `dropwhile`, `filterfalse`, and `takewhile`;
3. combinatorial iterables: `combinations`, `combinations_with_replacement`, `permutations`, and `product`;
4. infinite iterables: `count`, `cycle`, and `repeat`; and
5. tool-complementing iterables: `accumulate`, `starmap`, and `zip_longest`.

Knowing these five categories should help you remember what tools you have available.

(There's also `tee` in `itertools`, which manipulates iterables but isn't an iterable itself!)

Further reading:

- [Module `itertools` overview](#) blog article.

54 – t-strings need processing

t-strings were introduced in Python 3.14.

t-strings are a generalisation of f-strings that let you control the formatting process a bit more. Their main use case is to allow for safer formatting when you're formatting user input that needs to be sanitised. (C.f. the [ever-relevant xkcd comic 327](#).)

It is up to the programmer to call a function that takes a t-string and processes its interpolated values. In the example below, the programmer needs to use a function `interpolate_html_safe` to interpolate HTML safely, so as to avoid potential security issues arising from including arbitrary JavaScript in the final HTML:

```
from string import Template

def interpolate_html_safe(template: Template) -> str:
    ... # Processes interpolated values...

to_format = "<script>alert('Malicious JS');</script>"
html_page = t"<html>{to_format}</html>"
print(interpolate_html_safe(html_page))
# <html>&lt;script&gt;alert('Malicious JS');&lt;/script&gt;</html>
#      ~~~~      ~~~~      ~~~~      ~~~~
# Script tags were escaped when interpolating the string.
```

55 – Structural unpacking

When doing an assignment, if the value on the right is an iterable (list, tuple, ...), you can unpack it. On the left, you can write as many variables as elements you expect to have on the right. You can also use the splat operator to capture lists of zero or more elements.

And you can nest these structural matches!

```
colour = ("AliceBlue", (240, 248, 255, 255))
name, (*rgb, alpha) = colour
```

```
print(rgb) # [240, 248, 255]
```

This also works with the assignment target in a for loop:

```
colours = [colour, ...]
```

```
for name, (*rgb, alpha) in colours:
    print(name, rgb, alpha)
```

```
# AliceBlue [240, 248, 255] 255
# ...
```

Further reading:

- [Structural unpacking blog article](#).

56 – Ergonomic multiline strings

When I'm writing multiline strings I like to have the `"""` by themselves, for readability. However, this creates an extra empty line at the beginning and end of the string:

```
string = """
Multiline string.
No escaped newlines
"""
```

```
print("> " + string + "!")
```

```
>
Multiline string.
No escaped newlines
!
```

This is not what I want... To fix this, I can use the backslash character `\` to escape those extra newlines:

```
string = """\
Multiline string.
First & last newlines escaped\
"""
```

```
print("> " + string + "!")
```

```
> Multiline string.
First & last newlines escaped!
```

57 – Underscore in the REPL

When working in the REPL, the result of the last non-None expression is saved in the special variable `_` (underscore).

This is especially useful if you run a slow piece of code and forget to assign the result. Just do `result = _`.

As someone who uses the REPL a lot, I find this to be very helpful!

Here is an example REPL session showcasing this feature:

```
>>> 3 ** 3 ** 3
7625597484987
>>> print(_)
7625597484987

>>> _
7625597484987

>>> sum([_, _, -, -])
0
>>> _
0
```

Note that functions that return `None` do not update the value stored in `_`.

Further reading:

- [The appearing built-in.](#)
- [Usages of the underscore.](#)

58 – Subclassing immutable types

How do you subclass immutable types? (For example, how would you subclass floats?)

The dunder method `__init__` alone isn't enough; you need something else...

You need the dunder method `__new__`, `__init__`'s big brother. The dunder method `__new__` is a class method that is responsible for creating the object, whereas `__init__` simply initialises/customises it.

Here is the skeleton for a float subclass:

```
class FloatSubclass(float):
    def __new__(cls, value, *args, **kwargs):
        print("__new__", value, args, kwargs)
        return super().__new__(cls, value)

    def __init__(self, value, *args, **kwargs):
        print("__init__", value, args, kwargs)
        # Do whatever with the args and kwargs

x = FloatSubclass(4.5)
# __new__ 4.5 ('hello',) {'foo': True}
# __init__ 4.5 ('hello',) {'foo': True}
print(x) # 4.5 <- looks like a float.
```

Further reading:

-
- [Customising object creation with `__new__`](#).

59 – Idiomatic sequence slicing

There are five slicing patterns that are fairly common and that have simple interpretations, and that's what an idiom is: a piece of code that you recognise for its meaning as a whole.

You should be able to interpret these five slicing idioms automatically without having to think:

1. `[:n]` – first `n` chars
2. `[n:]` – after first `n` chars
3. `[:-n]` – without last `n` chars
4. `[-n:]` – last `n` chars
5. `[::-1]` – reversed (but the built-in `reversed` is usually preferred)

```
string = "Slicing is easy!"

print(string[:4])  # Slic
print(string[4:])  # ing is easy!

print(string[:-4]) # Slicing is e
print(string[-4:]) # asy!

print(string[::-1]) # !ysae si gnicilS
```

Further reading:

- [Idiomatic sequence slicing blog article](#).

60 – File tail

You can get the last few lines of a file with `collections.deque`. You just have to set `maxlen` to the number of lines you want from the end of the file:

```
from collections import deque

with open("/path/to/python/lib/this.py", "r") as f:
    tail = deque(f, maxlen=4)

for line in tail:
    print(line)

#     for i in range(26):
#         d[chr(i+c)] = chr((i+13) % 26 + c)
#
# print("".join([d.get(c, c) for c in s]))
```

If the file has fewer lines than the ones you asked for, you get the full file.

Further reading:

- [deque tutorial](#).

61 – One-shot file I/O

For one-shot file I/O, like simply reading the full contents of a file or writing some text to a file, you can use the methods `read_text` and `write_text` from `pathlib.Path`.

Here is a short example:

```
from pathlib import Path

filepath = Path("hello_world.txt")

filepath.write_text("Python is cool!")

print(filepath.read_text())
# Python is cool!
```

Note that if the file exists, `write_text` will overwrite the contents of the file.

If you use a context manager and the built-in `open` you get more control, but these two methods get the job done most of the time.

Further reading:

- [Module `pathlib` overview](#).

62 – Formatting big numbers

When doing string formatting with big integers, you may want to include thousands separators to make numbers easier to read. You can add

- commas;
- underscores; or
- a locale-appropriate separator.

To do so, use the specifiers `,`, `_`, or `n`, respectively:

```
bignum = 123541241234

print(f"Big money ${bignum:,}")
# Big money $123,541,241,234

print(f"Big money ${bignum:_}")
# Big money $123_541_241_234

print(f"Big money ${bignum:n}")
# Big money $123541241234 # Might be different for you.
```

Note that the locale-appropriate separator might be “nothing” if the locale isn’t set appropriately beforehand, as seen above.

Since Python 3.14, you can also **group digits in the fractional part** of a number.

Further reading:

- [Thousands separators](#).

63 – Named groups in regex

If you're using regex (I'm sorry!) and you want to extract portions of patterns with groups, you can use named groups to make extraction easier.

To create a named group, start the group with `?P<...>` and put the group name inside the angled brackets `<>`, as the example below shows:

```
import re

pattern = r"(?P<user>\S+)@(?P<domain>\S+)"
```

Then, when you get a match, you can use the method `group` to extract groups by name:

```
match = re.match(pattern, "rodrigo@mathspp.com")

print(match.group("user"))    # rodrigo
print(match.group("domain"))  # mathspp.com
```

Note that this is a Python-specific feature and that are unlikely to have this feature when working with regex in other contexts/programming languages.

64 – Resolving paths

When working with paths, and especially if user input is involved, you often want to normalise and resolve your paths so you have absolute paths that are expanded.

For example, you might need to turn

- something `"~/Documents"` into `"/Users/rodrigogs/Documents"` (or whatever the equivalent is in your OS); or
- something like `"~/Documents/../Downloads"` into `"/Users/rodrigogs/Downloads"`, getting rid of the `~` and the `..`

To expand the `~` into your home folder, use the method `expanduser`:

```
from pathlib import Path

docs = Path("~/Documents")
abs_docs = docs.expanduser()
print(abs_docs)    # /Users/rodrigogs/Documents
```

To resolve references with `..` or `..`, use the method `resolve`:

```
downloads = abs_docs / ".." / "Downloads"
print(downloads)    # /Users/rodrigogs/Documents/../Downloads
print(downloads.resolve())    # /Users/rodrigogs/Downloads
```

To do everything in one go, use `Path(filepath).expanduser().resolve()`. And make sure you call `expanduser` first, since calling `resolve` first might lead to the wrong result:

```
downloads = docs / ".." / "Downloads"
print(downloads)    # ~/Documents/../Downloads

# Correct order:
print(downloads.expanduser().resolve())    # /Users/rodrigogs/Downloads
```

```
# Wrong order:
print(downloads.resolve().expanduser()) # /Users/rodrigogs/Documents/~Downloads
```

65 – Formatting dates with f-strings

Dates, times, and datetime objects, from the module `datetime`, can be formatted directly in f-strings.

You don't need to use `strftime`. Or `strptime`, whichever one of these two does the formatting.

The format specifier can contain the special codes with `%` to refer to parts of the date but anything else is left untouched.

```
from datetime import date

print(f"{date.today():%Y-%m-%d}")
# 2025-06-03

print(f"{date.today():%Y---%m :: %d}")
# 2025---06 :: 03
```

Further reading:

- [Datetime objects and f-strings](#).

66 – Concatenate files from handlers

Suppose you need to concatenate multiple files together, for example to write a long file composed of multiple other files or to search for a pattern across all files.

If you *already* have the file handlers in a list, use `chain.from_iterable` to go through the whole thing.

This is as memory efficient as possible since it only reads the lines from each file on demand and it doesn't hold the full contents of each file in memory.

For example, suppose you have three files:

1. `log1.log`:

```
08:12:03 [INFO] Starting the data sync process
08:12:04 [DEBUG] Loaded 142 user records from cache
```

2. `log2.log`:

```
08:12:06 [INFO] Connection to remote server established
08:12:08 [WARN] Response time exceeded threshold: 534ms
```

3. `log3.log`:

```
08:12:09 [DEBUG] Retry attempt #1 initiated
08:12:11 [INFO] Data sync completed successfully
```

If the files are already open in the variables `log1`, `log2`, and `log3`, respectively, then you can run

```
open_files = [log1, log2, log3]
```

```
from itertools import chain
```

```
with open("full_log.log", "w") as f:
    f.writelines(chain.from_iterable(open_files))
```

This produces the file `full_log.log` with the contents of all three files:

```
08:12:03 [INFO] Starting the data sync process
08:12:04 [DEBUG] Loaded 142 user records from cache
08:12:06 [INFO] Connection to remote server established
08:12:08 [WARN] Response time exceeded threshold: 534ms
08:12:09 [DEBUG] Retry attempt #1 initiated
08:12:11 [INFO] Data sync completed successfully
```

If the files haven't been opened yet, then the best thing to do is to open each one of them at a time, of course.

67 – Generator recipe

Generators are an awesome Python feature because their potential upside in terms of memory and time savings is infinite.

If you don't have experience writing generators, it's actually "easy" with this little trick.

First, you write a function that builds a list with the elements that you want to produce. Then, you follow these three steps:

1. Replace all calls to `.append(value)` with `yield value`.
2. Delete the line where you initialised the list with the results.
3. Delete the line where you return the list with the results.

That's it!

For example, start with this function:

```
def squares(stop):
    result = []
    for n in range(stop):
        result.append(n ** 2)
    return result

print(squares(5)) # [0, 1, 4, 9, 16]
```

Then, you should get this generator:

```
def squares(stop):
    # result = []
    for n in range(stop):
        yield n ** 2 # result.append(n ** 2)
    # return result

print(list(squares(5))) # [0, 1, 4, 9, 16]
```

This trick also works for infinite generators if you start by writing a loop that builds an infinite list. The function won't work because you can never build an infinite list, but the 3-step process can be applied and the resulting generator works.

68 – Split strings in two halves

Sometimes you'll need to split the string in two halves. When that's the case, you'll want to use the method `partition`:

```
email = "rodrigo@mathspp.com"
user, at, domain = email.partition("@")
```

```
print(user)    # rodrigo
print(at)      # @
print(domain)  # mathspp.com
```

If the split fails, the first item of the 3-item tuple contains the full string and the two other items are the empty string:

```
email = "mathspp.com"
user, at, domain = email.partition("@")
```

```
print(user)    # mathspp.com
print(at == domain == "") # True
```

This is better than using `.split(..., maxsplit=1)` because the return type makes it easier to check if the split was successful. With `partition`, it's enough to check if the middle element is truthy or not:

```
email = input(" >>> ")
user, at, domain = email.partition("@")
```

```
if at:
    print("Split successful!")
else:
    print("Split was not successful!")
```

If the separator occurs 2+ times, `partition` splits on the first. Use `rpartition` to split on the last:

```
print("aaa oi bbb oi ccc".partition("oi"))
# ('aaa ', 'oi', ' bbb oi ccc')

print("aaa oi bbb oi ccc".rpartition("oi"))
# ('aaa oi bbb ', 'oi', ' ccc')
```

69 – Regex multiline flag

Regular expressions have a multiline flag that can be used to change the behaviour of the special characters `^` and `$`. By default, `^` and `$` match the beginning and end of the string, respectively; with the multiline flag, they match the beginning and end of each line, respectively.

The flag can be used inline with `(?m)`, or passed in to the relevant functions of the module `re` with `re.MULTILINE`.

As an example, take the following string that spans across two lines:

```
The quick brown fox jumps over
the lazy dog.
```

The pattern `r"^[Tt]he"` will only match the first "The", while the pattern `r"(?m)^[Tt]he"` will match the two occurrences of the word "the".

70 – Extract assignments from conditionals

Instead of using a conditional to make an assignment, use a conditional expression. This extracts the important operation (the assignment) out of the nesting of the `if: ... else: ...` statement, making it easier to spot the relevant part of the code.

If you're not used to conditional expressions, it's a matter of learning how to read them in English (or in your language). The snippet below, using a conditional statement, reads "If the user is logged in, set their permissions to "full", otherwise set them to "guest".":

```
if logged_in:
    permissions = "full"
else:
    permissions = "guest"
```

If you use a conditional expression, it now reads as "Set the user permissions to "full" if the user is logged in, otherwise set them to "guest".":

```
permissions = "full" if logged_in else "guest"
# ~~~~~ Set permissions to `full`
#           if the user is logged in,
#           ~~~~~ otherwise set them to `guest`.
```

Further reading:

- [Conditional expressions.](#)

71 – File discovery by name pattern

When you need to find files based on a name pattern, you can use the method `glob` from `pathlib.Path`. Note that `glob` doesn't support complex (regex) patterns, though.

Suppose the filesystem contains the following folder `Downloads` and its given contents:

```
= Downloads/
- cat_and_dog.png
- cute_cat.jpg
- cute_dog.jpg
- two_cats.png
```

Then, the snippet below finds all files with the string "cat" in the name:

```
from pathlib import Path

cat_files = Path("Downloads").glob("*cat*")
# Finds cat_and_dog.png, cute_cat.jpg, two_cats.png
```

Similarly, the snippet below finds all files that end with ".jpg":

```
from pathlib import Path

jpg_imgs = Path("Downloads").glob("*.jpg")
# Finds cute_cat.jpg, cute_dog.jpg
```

Note that the method `glob` produces the file paths in an arbitrary order.

Further reading:

- [Module `pathlib` overview.](#)

72 – Structural pattern matching with dictionaries

The `match` statement can be used to match keys and values in a dictionary, effectively matching the structure of the dictionary.

The example below matches all dictionaries that contain a key "user" with a string value and a key "age" with an integer value:

```
match my_dict:
    case {"user": str(), "age": int()}:
        print("Match!")
```

Dictionaries that satisfy those restrictions will match, even if they have more key/value pairs, like the dictionary `my_dict` below:

```
my_dict = {"user": "John", "age": 47, "children": 2}
```

The dictionaries below won't match, respectively because they're missing the key/value pair for "age" or because the value for "age" doesn't have the correct type:

```
my_dict = {"user": "John"} # Missing `age`
my_dict = {"user": "John", "age": "47"} # `age` should be an integer.
```

Further reading:

- [Structural pattern matching tutorial](#).
- [Structural pattern matching cheatsheet](#).

73 – Slicing generators for debugging

When debugging with generators, you may want to use `itertools.islice`. This allows you to easily take a look at the first few elements of the generator.

You can wrap the call to `islice` in `print(list(...))` to print the elements, or you can loop over the slice and add a breakpoint immediately before.

Here is an example using `print(list(islice(..., n)))` to print the first `n` elements immediately:

```
from itertools import islice

gen = mysterious_generator()

print(list(islice(gen, 3))) # [0, 1, 4]
```

Remember that if you use `islice` again, you'll be slicing from the *remainder* of the generator:

```
print(list(islice(gen, 3)))
# [9, 16, 25]
print(list(islice(gen, 3)))
# [36, 49, 64]
```

74 – Peek at an iterable

To know the first element of a list, you index with `[0]`. However, not all iterables can be indexed.

In general, to get the first element of an iterable (to "peek" at it), you can use `next` to fetch that element and then you can use `chain` from the module `itertools` to "glue it back".

Here is an example of how to do this:

```
from itertools import chain

def peek(iterable):
    iterator = iter(iterable)
    first = next(iterator)
    return first, chain([first], iterator)
```

This specific implementation raises a `StopIteration` error if the iterable is empty. Other behaviours can be easily implemented.

75 – Match the structure of custom objects

Custom objects can have their structure matched by specifying the relevant attribute names in the dunder attribute `__match_args__`.

This dunder attribute must be a tuple of strings that specifies the attribute names used for matching. The object can have more attributes, but the ones that aren't included in `__match_args__` are irrelevant for the purposes of structural pattern matching.

For example, the class `Point` below has three attributes but the dunder attribute `__match_args__` only refers two:

```
class Point:
    __match_args__ = ("x", "y")

    def __init__(self, x, y, z):
        self.x, self.y = x, y
        self.z = z
```

```
p = Point(1, 2, 3)
```

When trying to match the structure of an instance of `Point`, you can match directly against the attributes `x` and `y`:

```
p = Point(1, 2, "")
match p:
    case Point(1, int()):
        print("match!")
# match!
```

Note how the case statement with the pattern `Point(1, int())` looks like an instantiation of the class `Point`, although that is not valid code for the purposes of class instantiation. It is valid code for the purposes of structural pattern matching, though.

Further reading:

- [Structural pattern matching tutorial](#).
- [Structural pattern matching cheatsheet](#).

76 – Built-in `next` with a default value

The built-in `next` can be given a second argument which is the default return value used when the given iterator is empty. A default value (of `None`, for example) tends to be more useful in idioms that use `next`. (For

example, see [this tip about the first element of an iterable that satisfies a condition.](#))

As an example, consider the generator expression assigned to `squares` and that is exhausted by calling the built-in `next` repeatedly:

```
squares = (x ** 2 for x in range(3))

print(next(squares)) # 0
print(next(squares)) # 1
print(next(squares)) # 4
```

The next time that the built-in `next` is called, Python raises a `StopIteration`:

```
print(next(squares))
# StopIteration
```

However, if you pass a second argument to the built-in `next`, that's the result you get:

```
print(next(squares, "hey"))
# hey
```

77 – Match an exact dictionary structure

Structural pattern matching can be used to match dictionaries with given keys and values.

By default, patterns with dictionaries only determine keys and values that a dictionary *must* contain to match. This means dictionaries can have more keys/values than the ones listed, and they still match.

If you wish to match a specific, restricted dictionary structure (that is, if you want to disallow dictionaries from having more key/value pairs), you can use a guard.

For example, consider the following `match` statement:

```
match d:
    case {"name": str()}:
        print("match!")
```

The two dictionaries below would match, even though the second one has a key `"age"` that is not mentioned in the pattern above.

```
{"name": "John"} # matches
{"name": "John", "age": 42} # matches
```

To only match dictionaries that have exactly that structure, introduce a guard with `**kwargs` that asserts that there are no extra keys:

```
match d:
    case {"name": str(), **kwargs} if not kwargs:
        print("match!")
```

With this guard, the longer dictionary will not match.

Further reading:

- [Structural pattern matching tutorial.](#)
- [Structural pattern matching cheatsheet.](#)

78 – Undoable iterator with value history

You can use a deque from the module `collections` to create an undoable iterator that keeps track of the history of seen values.

You use a deque to hold the history of values that have been seen and also create a deque to hold a queue of values that have been seen already but that were “undone”.

To fetch the next element from the iterator, ensure there’s at least one value in the queue – which you might need to fetch from the original iterable – and then produce that.

To undo a step, you take one element from the history deque and plop it into the queue deque.

This is a sample implementation of the iterator `undoable` with no validation/error-checking:

```
from collections import deque

class undoable:
    def __init__(self, iterable, hist_size=100):
        self.iterator = iter(iterable)
        self.history = deque(maxlen=hist_size)
        self.queued = deque(maxlen=hist_size)

    def __next__(self):
        if not self.queued:
            self.queued.append(next(self.iterator))
        item = self.queued.popleft()
        self.history.append(item)
        return item

    def undo(self):
        self.queued.appendleft(self.history.pop())

    def __iter__(self): return self # necessary for the iterator protocol
```

The snippet below shows an usage example with a generator expression:

```
squares = undoable(x ** 2 for x in range(3))
```

```
print(next(squares)) # 0
print(next(squares)) # 1
```

```
squares.undo()
squares.undo()
```

```
print(next(squares)) # 0
print(next(squares)) # 1
print(next(squares)) # 4
```

79 – Typing overloads

The usage of typing overloads allows you to declare relationships between the types of arguments and/or the return type of a function. This allows the type checker to use information that otherwise couldn’t be inferred from the function signature alone.

For example, the computation `2 * arg` works for strings and ints, and you know the result has the same type as the value used.

Wrapping that multiplication in a function and adding type hints in the naive way doesn't tell the type checker that there is a relationship between the argument type and the return value:

```
def double(arg: str | int) -> str | int:
    return 2 * arg
```

```
reveal_type(double("hey")) # str | int
```

Note how the type checker doesn't know whether the returned value is a string or an integer, although we know that it will be the string "heyhey".

However, if you use overloads, you can specify that the argument type is the same as the return value. Typing overloads can be as many as needed and they're decorated with `typing.overload`. You only need to specify the function signature with the restricted relationships. Then, you provide the full function signature and its body:

```
from typing import overload

# If you give it strings, you get strings:
@overload
def double(arg: str) -> str: ...

# If you give it integers, you get integers:
@overload
def double(arg: int) -> int: ...

# The general function with the function body:
def double(arg: str | int) -> str | int:
    return 2 * arg
```

```
reveal_type(double("hey")) # str
```

Note how the type checker knows that the return type is `str` because the argument is of the type `str`.

80 – Bulk renaming files

To change the name of a file while preserving its extension you can use the method `pathlib.PurePath.with_stem`. Note that this creates a new path object and doesn't do any file renaming automatically. That is why the method `with_stem` is defined in `PurePath`, although it is also available from `Path`.

If you pair `with_stem` with `rename`, you can easily bulk-rename files in a folder.

Suppose the folder `reports` contains multiple reports in different formats, like PDF files, Excel files, and the occasional screenshot(!). To rename all files, you could write something like

```
from pathlib import Path

report_folder = Path("reports") # PDFs, Excel files, ...

for idx, report in enumerate(report_folder.iterdir(), start=1):
    report.rename(report.with_stem(f"report{idx:03}"))

# Produces:
```

```
# reports/report001.pdf
# reports/report002.xlsx
# ...
```

Further reading:

- [Module pathlib overview](#).

81 – Structural validation and homogenisation

Some functions can accept arguments in many different formats. In that case, structural pattern matching can be used to validate the argument and to homogenise it.

For example, padding in CSS can be specified as a single integer, or as a tuple of 1, 2, or 4 integers. But in CSS the padding is always unwrapped into 4-item tuples.

Some valid examples and the conversions:

- 10 is converted to (10, 10, 10, 10)
- (5, 10) is converted to (5, 10, 5, 10)
- (1, 2, 3, 4) is converted to (1, 2, 3, 4)

Using the `match` statement you can easily write a function that validates this structure and does the conversion:

```
def unpack_padding(pad) -> tuple[int, int, int, int]:
    match pad:
        case int(p) | (int(p),):
            return (p, p, p, p)
        case (int(vert), int(horz)):
            return (vert, horz, vert, horz)
        case (int(top), int(right), int(bottom), int(left)):
            return (top, right, bottom, left)
        case _:
            raise ValueError(f"1, 2 or 4 integers required for padding; got {pad!r}.")
```

Further reading:

- [Structural pattern matching tutorial](#).
- [match statement cheatsheet](#).

82 – Verbose regular expressions

This is the best thing you can do for your regular expressions: use the verbose flag. Verbose regular expressions can be split across multiple lines and you can add comments to it. This makes it much easier to write readable regular expressions.

As an example, here is a not-so-complex regular expression:

```
pattern = r"---\ntitle: (?P<title>.*?)\nauthor: (?P<author>.*?)\n---"
```

Here is an equivalent regular expression after using the verbose flag (`?x`):

```
pattern = r"""(?x)
---\n                # frontmatter delimiter
title:\ (?P<title>.*?)\n    # book title
author:\ (?P<author>.*?)\n    # author name
```

```
---                                     # frontmatter delimiter
"""
```

Note that, since whitespace is ignored, you need the explicit "\n" to match newlines and you also need to escape spaces with a backslash \.

The beauty of this example is that the verbose regular expression now looks much more like the text that it matches, for example:

```
---
title: Moby Dick
author: Herman Melville
---
```

The verbose flag can also be used as `re.X` or `re.VERBOSE` when passing flags to the functions of the module `re`.

83 – Extracting text data into a dict

Regular expression matches from the module `re` have a method `groupdict` that allow you to create a dictionary with the named groups that your regular expression defines.

This is useful, for example, if you're extracting data from structured text and want to convert it to a more convenient format (a dictionary).

Suppose you have a number of files for copyright-free books with a frontmatter header and the markdown contents:

```
---
title: Moby Dick
author: Herman Melville
---
```

[...]

You can define a regex pattern to extract the title and author information:

```
pattern = r"""(?x)
---\n
title:\ (?P<title>.*?)\n
author:\ (?P<author>.*?)\n
---"""
```

Then, you can use the module `re` and any of its functions to search/find text. If you get a match, you can use the method `groupdict` to create a dictionary with key/value pairs for every **named group** you defined. In the example above, that would be a dictionary with keys "title" and "author":

```
import re

print(
    re.match(pattern, text).groupdict()
)
# {'title': 'Moby Dick',
#  'author': 'Herman Melville'}
```

Further reading:

- [re.Match.groupdict](#).

84 – Generics syntax

Python 3.12 introduced many typing improvements, namely an improved syntax to define generic functions and generic classes. Instead of having to define type variables beforehand, the type variables needed for the generic function/class can be defined with the object, making it more concise.

For example, instead of

```
from typing import TypeVar
```

```
T = TypeVar("T")
```

```
def into_list(value: T) -> list[T]:  
    return [value]
```

you can use [...] after the function name, and before the parameter list, to specify the type variables required:

```
def into_list[T](value: T) -> list[T]:  
    return [value]
```

Similarly, you can define a generic class over a type variable T by using [T] immediately after the class name:

```
class MyList[T]:  
    def __init__(self, values: list[T]):  
        self.values = list(values)  
  
    def append(self, value: T) -> None:  
        self.values.append(value)  
  
    def pop(self) -> T:  
        return self.values.pop()
```

85 – Add lists together, fast

Adding (concatenating) two lists together is a “slow” operation because it requires creating a new list and “copying” the values from the two source lists to the third resulting list. In performance-sensitive scenarios, it may be better to use `itertools.chain` to chain the two lists together, instead.

For example, suppose there’s a scenario where you have a node from a tree-like structure and you need to traverse the tree up, from the current node up until the root. You might write a `for` loop like the one below:

```
for node in [this_node] + list(this_node.parents):  
    pass
```

If this were performance-sensitive code, you’d be better off using `chain`:

```
from itertools import chain
```

```
for node in chain([this_node], this_node.parents):  
    pass
```

The second alternative is faster because:

1. `this_node.parents` doesn’t need to be converted to a list; and
2. chaining doesn’t copy values to a third container.

This piece of advice is generally applicable but if you're writing truly performance-sensitive code, don't forget to benchmark this change.

Further reading:

- [Module itertools overview](#).
- [CPython pull request #112406](#).

86 – File modes

There are 16 different file modes. The four base modes are

1. `r` for reading;
2. `w` for writing;
3. `a` for appending; and
4. `x` for exclusive creation and writing.

The mode `x` is like `w`, but fails if the file already exists. In other words, it ensures you're creating a new file.

The table below encodes the properties of each mode:

Mode	<code>r</code>	<code>w</code>	<code>a</code>	<code>x</code>
allows read	x			
allows write		x	x	x
must exist	x			
must not exist				x
positioned at start	x	x		x
positioned at end			x	
always writes to end			x	

These four base modes operate on files in text mode, by default, which is the same as appending a `t` to each mode. For example, the modes `r` and `rt` are the same. Instead, you can append a `b` to open the files in binary mode.

Finally, you can also append a `+` to any mode to enable writing and reading at the same time, although this is uncommon because it can be quite confusing.

Further reading:

- [File modes in Python](#).

87 – Caching sets and frozen sets

The built-in type `set` has a variant `frozenset` that is immutable and that you can use as a dictionary key, for caching purposes, or in other contexts where you require a hashable value.

As an example, suppose you have a function `products_with_tags` that searches for products in a store that have the given tags, and since the database of products is fairly stable, you want to cache these lookups.

You write the function with a cache:

```
from functools import cache
```

```
@cache
```

```
def products_with_tags(tags):
    ... # Send an API request,
    ... # process the results, etc.
```

Since sets aren't hashable, you can't call this function with an argument of the built-in type `set`:

```
tags = {"sale", "local"}
print(products_with_tags(tags)) # Exception
```

Since frozen sets are immutable, they can be made hashable, and thus they can be used here:

```
tags = frozenset({"sale", "local"})
print(products_with_tags(tags))
```

Frozen sets support all operations that sets support and, in particular, they support very fast look-ups/containment checks.

The only operations that frozen sets do not support are the set operations that modify the set in-place.

Further reading:

- [Sets and frozensets](#).

88 – Constrained generics

Generics (functions and classes) can be constrained. This means that the variable type must be one of two (or more) specified types.

Consider the function `double` as a motivating example:

```
def double[T](value: T) -> T:
    return 2 * value
```

The fact that the function `double` is generic explicitly states the relationship between the argument type and the return type, which is preserved in calls like `double(2)` or `double("hello")`.

However, with the given type hints, it's not immediately obvious to type hinters what types of values can be passed to the function `double`. To make that explicit, the type variable `T` can be annotated with a tuple of two or more types, therefore constraining `T` to be one of those types:

```
def double[T: (str, int, float)](value: T) -> T:
    return 2 * value
```

In this new definition, type checkers will only accept arguments of type `str`, `int`, or `float`, for the function `double`.

For example, if `None` is used, mypy will complain:

```
Value of type variable "T" of "double" cannot be "None" [type-var]
```

89 – Natural alphabetical sorting

Strings can be sorted in Python and the default behaviour is to sort lexicographically, character by character. However, characters are compared by their Unicode codepoint (which you can check with the built-in `ord`), which means upper case letters and lower case letters are separated because their codepoints are “far” apart:

```
fruits = ["banana", "APPLE", "Coconut"]
print(sorted(fruits))
# ['APPLE', 'Coconut', 'banana']
```

The lower case letters come after the upper case letters because the lower case letters have higher code-points:

```
print(ord("C")) # 67
print(ord("b")) # 98
```

If you want to sort a series of strings in a case-insensitive way, you can use the built-in `sorted` and set the keyword parameter `key` to the string method `str.casefold`:

```
fruits = ["banana", "APPLE", "Coconut"]
print(sorted(fruits, key=str.casefold))
# ['APPLE', 'banana', 'Coconut']
```

Further reading:

- [How to work with case-insensitive strings](#)

90 – Preserving decorated function metadata

The standard way of writing a decorator involves creating a wrapper function for the decorated function, like so:

```
def my_decorator(func):
    def wrapper(*args, **kwargs):
        ... # Decorator code goes here.
    return wrapper
```

Following this strategy has the drawback of “erasing” important function metadata.

Suppose you apply the decorator `my_decorator` to a function:

```
@my_decorator
def add(a, b):
    """Performs addition!"""
    return a + b
```

In doing so, the metadata of the function `add` was messed up. Printing the function now shows a funky result:

```
print(add) # <function my_decorator.<locals>.wrapper at 0x102cb4510>
```

Similarly, using the built-in `help(add)` will reveal a cryptic help message:

```
Help on function wrapper in module __main__:
```

```
wrapper(*args, **kwargs)
  Help on my_decorator.<locals>.wrapper line 1/3 (END) (press h for help or q to quit)
```

To fix this behaviour – which is technically correct but definitely unhelpful – you can use the decorator `functools.wraps` inside your decorator:

```
import functools

def my_decorator(func):
    @functools.wraps(func)
    def wrapper(*args, **kwargs):
```

```
... # Decorator code goes here...  
return wrapper
```

The usage of `functools.wraps` will ensure the metadata is passed on to the wrapper. If you reapply the decorator `my_decorator` to a fresh function add you will see the result looks good:

```
print(add) # <function add at 0x102db19b0>
```

And using `help(add)` reveals:

Help on function add in module `__main__`:

```
add(a, b)  
    Performs addition!  
Help on add line 1/4 (END) (press h for help or q to quit)
```

Further reading:

- [Decorators article](#).

91 – Timestamp file names

You can combine `datetime.datetime.now` with string formatting to add a timestamp to a file name. This is very helpful to create unique file names dynamically.

Here is an example function using this idea:

```
import datetime  
  
def make_file_name(prefix, extension):  
    ts = f"{datetime.datetime.now():%Y%m%d%H%M%S}"  
    return f"{prefix}-{ts}-{extension}"  
  
print(make_file_name("screenshot_", ".png"))  
# screenshot_20250707142204.png
```

The % specifiers determine what parts of the current date and time make it to the timestamp and this example uses six:

Specifier	Meaning
%Y	year
%m	month
%d	day
%H	hour
%M	minute
%S	second

All but %Y result in a 2-digit number which might be 0-padded.

For most applications, going down to the minutes or seconds is enough. If you need microseconds, you can add the specifier %f.

92 – Temporary directories

Use the module `tempfile` from the standard library to create a temporary directory. The context manager `TemporaryDirectory` cleans up the directory and its contents when closed.

```
import tempfile

with tempfile.TemporaryDirectory() as tmpdirname:
    print(f"Created temp directory {tmpdirname}.")
    ... # Do whatever you want inside this directory...
```

Once the context manager is closed, everything is cleaned up – including the contents of the directory – so you can use it to create and manipulate other files that will be automatically cleaned up.

For example, I used this to edit a video: my program creates a temporary directory and then copies the excerpts of the video that I care about into small segments that are saved in the temporary directory. Then, the segments are all pasted together into a single video that is saved elsewhere. Once the temporary directory goes away, the small segments are also cleaned up.

93 – Non-local variables

To access non-local variables in closures, use the keyword `nonlocal`. Non-local variables are variables that are neither local, nor global. For example, the variable `counter` from the point of view of the function `inner` in the snippet below:

```
def outer():
    counter = 0

    def inner():
        ... # From the point of view of `inner`,
        # `counter` is neither local nor global.
```

Non-local variables can be read from inner functions without any special keywords:

```
def outer():
    counter = 0

    def inner():
        print(counter)

    return inner
```

```
inner = outer()
inner() # 0
inner() # 0
```

To write to them, you need to declare the variable as non-local with the keyword `nonlocal`:

```
def outer():
    counter = 0

    def inner():
        nonlocal counter
        counter += 1
        print(counter)
```

```
    return inner

inner = outer()
inner() # 1
inner() # 2
```

By the way, since you can read the value of a variable without using the keyword `nonlocal`, you can also mutate the value of a variable without the keyword `nonlocal`:

```
def outer():
    my_list = []

    def inner():
        my_list.append(1)
        print(my_list)

    return inner

inner = outer()
inner() # [1]
inner() # [1, 1]
```

94 – Dynamic width string formatting

String formatting accepts formatting specifiers dynamically if you specify them within an extra set of curly braces `{}`. This is useful, for example, to compute the maximum width of a column from a list of strings to format them neatly:

```
fruits = ["banana", "cantalope", "pear"]
max_width = max(map(len, fruits))
# max_width is 9

for idx, fruit in enumerate(fruits, start=1):
    print(f"{fruit:<{max_width}} - {idx}")
#           ~~~~~~

banana      - 1
cantalope   - 2
pear        - 3
```

Note how all fruits are left aligned on a field that is as wide as the word “cantalope”, since the variable `max_width` has the value 9. To tell the string formatting that the width is supposed to be the value of the variable `max_width`, you specify the width as `{max_width}` *inside* the format.

95 – Docstring `__doc__` attribute

Docstrings are saved as an attribute `__doc__` on the objects they were defined in. (Both functions and classes.)

This `__doc__` is a string attribute that is both readable and writable. This is used by the built-in `help`, by `functools.wraps` in decorators, and more.

As an example, consider the function `fn` with a short docstring:

```
def fn():
    """Docstring!"""
```

If you use the built-in `help`, you'll see the docstring:

```
help(fn)
"""
fn()
    Docstring!
"""
```

You can read and write to this attribute:

```
print(fn.__doc__) # Docstring!
fn.__doc__ = "Bye!"
```

Then, things like the built-in `help` will see the new value for the docstring:

```
help(fn)
"""
fn()
    Bye!
"""
```

96 – Common `__hash__` implementation

The [dunder method](#) can be implemented to make your instances hashable. This will let you use your instances of your custom class in dictionaries, sets, caches, and other situations.

The most common approach to implement a reasonable `__hash__` is to create a tuple with all the “important attributes” of your instance and then using the hash of that tuple.

As a rule of thumb, these “important attributes” tend to be the ones you would use to determine if two instances of your class are equal. For example, consider the mockup class `Fraction`:

```
class Fraction:
    def __init__(self, numerator, denominator):
        self._num = numerator
        self._den = denominator
        self._is_simplified = ...
```

The attribute `_is_simplified` will flag whether the fraction has been simplified to its lowest terms, like in `Fraction(1, 3)`, or not, like in `Fraction(3, 9)`. (Note that $1/3$ and $3/9$ are the same number.)

The fractions `Fraction(1, 3)` and `Fraction(3, 9)` are equal, although their attribute `_is_simplified` is different, since you can use the attributes `_num` and `_den` to determine they have the same numerical value.

Hence, for the class `Fraction`, you would use the attributes `_num` and `_den` to implement `__hash__`:

```
class Fraction:
    # ...

    def __hash__(self):
        return hash((self._num, self._den))
```

Note that, if two instances are considered equal, then their hashes *must be the same*.

97 – Match word boundaries

The special character `\b` can be used to match word boundaries in regular expressions. The special character `\B`, on the other hand, only matches inside words.

By combining `\b` and `\B` you can match prefixes, suffixes, standalone words, and more.

As an example, consider the sentence “watermelon is 92% water!” and three different patterns:

1. The pattern `r"water"` matches the five characteres “water” in sequence, so it would match the two occurrences of “water” in the sentence given.
2. The pattern `r"\bwater\b"` matches “water” as a standalone word, so it would only match the word at the end of the string.
3. The pattern `r"\bwater\B"` matches “water” as a prefix, so it would only match the string “water” that is a substring of the word “watermelon” at the beginning of the sentence.

98 – Custom containment checks

The [dunder method](#) `__contains__` can be used to implement custom containment checks in your classes. This will allow instances of your classes to be used with the keywords `in` and `not in`.

As an example, consider the class `ClosedInterval` shown below, that represents all numbers between the left and right boundaries, inclusive:

```
class ClosedInterval:
    def __init__(self, left, right):
        self.left = left
        self.right = right

    def __contains__(self, value):
        return self.left <= value <= self.right
```

By defining the dunder method `__contains__`, instances of `ClosedInterval` can be used with `in` and `not in`:

```
interval = ClosedInterval(2.7, 4.5)

print(3 in interval)  # True
print(7 in interval)  # False
print(7 not in interval)  # True
```

The dunder method `__contains__` accepts the value that is being checked as its only argument and must return a Boolean value that must be `True` if the argument is contained in the instance and `False` if not.

99 – Readable object names

Functions and classes have a dunder attribute `__name__` that is a string with the readable/user-defined name of that object:

```
class Example:
    pass

print(Example.__name__)  # Example
print(int.__name__)  # int
```

```
def foo():
    pass

print(foo.__name__) # foo
print(print.__name__) # print
```

This is useful, for example, when defining a class's `__repr__`:

```
class Point:
    def __init__(self, x):
        self.x = x

    def __repr__(self):
        return f"{type(self).__name__}({self.x})"
```

By using the dunder attribute `__name__`, the implementation of `__repr__` will remain correct if the name of the class changes and it is also more likely to stay correct if `Point` is subclassed.

100 – Filtering Truthy values

The built-in filter accepts the special value `None` as its first argument, instead of a predicate function. When `None` is the first argument, `filter` will remove all Falsy values from the iterable passed as the second argument.

```
words = ["This", "", None, "list", "contains", "", "some", "words"]
```

```
for word in filter(None, words):
    print(f"Word {word!r} has length {len(word)}.")
```

```
Word 'This' has length 4.
Word 'list' has length 4.
Word 'contains' has length 8.
Word 'some' has length 4.
Word 'words' has length 5.
```

In the snippet above, by using `filter(None, ...)`, the loop skips over the empty strings `""` in the list `words` and also the value `None`, since those are all Falsy.

101 – Pretty-printing nested data structures

The module `pprint` from the standard library provides pretty-printing functionality. The most straightforward way of using it is through the function `pprint.pprint`, which pretty-prints its arguments. It is particularly useful when printing nested data structures:

```
>>> import pprint
>>> pprint.pprint(globals())
{'__builtins__': <module 'builtins' (built-in)>,
 '__doc__': None,
 '__loader__': <_frozen_importlib_external.SourceFileLoader object at 0x10324d910>,
 '__name__': '__main__',
 '__package__': None,
 '__spec__': None,
 'partial': <class 'functools.partial'>,
 'pprint': <function pprint at 0x10362c1a0>}
```

102 – methods `__str__` and `__repr__`

Objects can use two different dunder methods to create string representations for themselves:

- `__str__`
- `__repr__`

`__str__` is supposed to provide a “pretty” string representation and `__repr__` is supposed to provide a “debug” string representation.

If `Point` is a class used to represent a point in 3D space, here’s what its implementations of `__str__` and `__repr__` could be:

```
class Point:
    def __init__(self, x, y, z):
        self.x, self.y, self.z = x, y, z

    def __str__(self):
        return f"({self.x}, {self.y}, {self.z})"

    def __repr__(self):
        return f"Point({self.x}, {self.y}, {self.z})"
```

When using the built-in `print`, the pretty string representation (`__str__`) is used:

```
print(Point(1, 2, 3)) # (1, 2, 3)
```

When using the built-in `repr`, the formatter `!r` inside f-strings, or when instances of the class `Point` are inside other containers, the debugging string representation (`__repr__`) is used:

```
some_points = [Point(0, 0, 0), Point(1, 2, 3)]
print(some_points) # [Point(0, 0, 0), Point(1, 2, 3)]
```

As a good rule of thumb, you should be able to copy & paste the output of `__repr__` to recreate the object. Also, when in doubt, implement `__repr__`. I personally rarely implement `__str__`, and when `__repr__` is present, `__str__` falls back to `__repr__`.

Further reading:

- [str and repr](#)

103 – Typing `*args` and `**kwargs`

When typing functions with an arbitrary number of positional arguments (`*args`) or with an arbitrary number of keyword arguments (`**kwargs`), the type hints should target the values that you’ll accept. In other words, don’t add type hints for the tuple `args` as a whole or for the dictionary `kwargs` as a whole.

The signature below denotes a function `my_max` that accepts a variable number of integers and a variable number of keyword arguments that are Booleans:

```
def my_max(
    *args: int,
    **kwargs: bool,
) -> int:
    ...
```

On the other hand, the signature below denotes a function `my_max` that accepts a variable number of tuples of integers and a variable number of keyword arguments that are dictionaries that map strings to Booleans:

```
def my_max(  
    *args: tuple[int, ...],  
    **kwargs: dict[str, bool],  
) -> int:  
    ...
```

104 - AST parsing

The module `ast` has a function `parse` that you can use to parse code (in a string) into what's called an AST. An AST is an “Abstract Syntax Tree”, an intermediate representation of your code that Python operates on.

Studying the ASTs produced by the module `ast` can teach you a lot about the Python language. For example, by using `ast.parse` you can find out that the keyword `elif` is just syntactic sugar for a sequence of `else`: `if ...: elif ...: else ...:` at the language level:

```
import ast

code = """\
if a:
    pass
else:      # <--
    if b:  # <--
        pass
    else:
        pass
"""

print(ast.dump(
    ast.parse(code),
    indent=2,
))

Module(
    body=[
        If(
            test=Name(id='a', ctx=Load()),
            body=[
                Pass()],
            orelse=[
                If(
                    test=Name(id='b', ctx=Load()),
                    body=[
                        Pass()],
                    orelse=[
                        Pass()]]))]
    )

```

This structure is **identical** to the one you get if you use `elif` instead of `else`: `if ...:`

```
import ast

code = """\
if a:
    pass
elif b:    # <--
```

```

    pass
else:
    pass
"""

print(ast.dump(
    ast.parse(code),
    indent=2,
)) # Exact same output.

```

105 – Dunder method `__missing__`

The dunder method `__missing__` is part of the dict data model. If you look up a key that isn't in the dictionary, `__missing__` is called to let you handle the missing key.

```

class Test(dict):
    def __missing__(self, key):
        print(f"In __missing__ with {key = }.")

d = Test()
d[42] # Output: In __missing__ with key = 42.

```

This can be used, for example, to implement `collections.defaultdict` yourself:

```

class defaultdict_(dict):
    def __init__(self, factory, **kwargs):
        super().__init__(**kwargs)
        self.default_factory = factory

    def __missing__(self, key):
        """Populate the missing key and
        return its value."""
        self[key] = self.default_factory()
        return self[key]

```

```

# int() gives 0.
olympic_medals = defaultdict_(int)
olympic_medals["Phelps"] = 28

print(olympic_medals["Phelps"]) # 28
print(olympic_medals["me"]) # 0 :(

```

Further reading:

- [Module collections overview](#)

106 – Custom enum search behaviour

Similar to the dunder method `__missing__`, enumerations can have a class method `_missing_` (with a single underscore).

This class method is called when instantiating an enumeration with a value that's not legal. The class method

can implement custom search behaviour (e.g., error-tolerant search) to try and find/return the correct member.

As a silly example, the enum shown below uses a naive strategy to try and suppress a common difference between UK and US English spelling:

```
from enum import auto, StrEnum

class Proximity(StrEnum):
    NEIGHBOR = auto()
    DISTANT = auto()

    @classmethod
    def _missing_(cls, value):
        try_value = value.casefold().replace("ou", "o")
        for member in cls:
            if member.value.casefold() == try_value:
                return member
        return None
```

Here's `_missing_` in action:

```
#                               vv
print(Proximity("NEIGHBOUR"))
# <Proximity.NEIGHBOR: 'neighbor'>
#           ^           ^
```

107 – map's keyword argument strict

Akin to `zip`'s keyword argument `strict`, in Python 3.14 the built-in `map` got a keyword argument `strict`. By setting `strict=True`, you get a `ValueError` if the iterables have different lengths:

```
bases = [2, 3, 4, 2, 3, 4]
exps = [2, 2, 2]

for num in map(pow, bases, exps, strict=True):
    print(num, end=" ")
# 4 9 16
# ValueError
```

In 99% of the situations where you use **map with multiple arguments** you'll want to set this, so don't forget it!

108 – Dynamic module attribute look-up

Modules can implement the dunder method `__getattr__`, which can be used to dynamically load names into a module. This can be useful to create lazy imports or to issue warnings when certain things are imported.

Suppose `HeavyClass` is available from the module `my_module`, but suppose that `HeavyClass` takes a while to initialise/import and therefore you want to be able to import it lazily. Then, you'd define this `__getattr__` in `my_module`:

```
def __getattr__(name):
    if name == "HeavyClass":
        print("Lazy importing...")
```

```
from _module import HeavyClass
globals()[name] = HeavyClass
return HeavyClass
```

```
raise AttributeError(f"module {__name__!r} has no attribute {name!r}")
```

Then, you can use HeavyClass elsewhere. The first time you use it, you'll trigger `__getattr__`, but the second time you won't because the lazy import is then saved in the global namespace of the module.

```
import my_module
```

```
obj1 = my_module.HeavyClass()
# Lazy importing...
```

```
obj2 = my_module.HeavyClass()
```

This is used in the modules `typing` and `collections`, for example!

109 – Add typing to decorators

Decorators used to be nasty to type. How do you create an inner, general function that you then type in a way that depends on the function(s) you will be decorating?!

Python fixes this with `typing.ParamSpec` (added in Python 3.10), which allows you to refer to the signature of your original function in the signature of your new function.

In general, a decorator will look like this:

```
def decorator(f): # This decorator does nothing in practice.
    def wrapper(*args, **kwargs):
        return f(*args, **kwargs)
    return wrapper
```

Given this decorator, the diagram below shows a tiny usage example with the 3.12+ type parameter syntax:

```
from typing import Callable
```

```
def decorator[T, **P](f: Callable[P, T]) -> Callable[P, T]:
    def wrapper(*args: P.args, **kwargs: P.kwargs):
        return f(*args, **kwargs)

    return wrapper
```

The `[..., **P]` syntax creates a parameter specification (`typing.ParamSpec`) called `P`. Then, the signature `(f: Callable[P, T]) -> Callable[P, T]` means that the decorator accepts a function whose **parameter specification** is `P`, and returns a function with the same parameter specification. In other words, the decorator will preserve the signature of the function. More specifically, the `.args` and `.kwargs` attributes of the `ParamSpec` link the original types of the arguments of `f` to the types of the arguments of `wrapper`.

110 – Non-greedy regex quantifiers

The quantifiers `*`, `+`, and `?`, in regular expressions, are all greedy. This means that they will try to match as much as possible, while still allowing the full pattern to match:

```
import re

html = "<a href='mathspp.com'>My site</a>"
#           ^           ^
# Note how there are two '>' in the string.

greedy = re.compile(r"<a.*>")

print(re.match(greedy, html).group())
# <a href='mathspp.com'>My site</a>
```

However, sometimes you don't want to match as much as possible; you want to match as little as possible. When that's the case, you can add a question mark `?` to the quantifiers, making them `*?`, `+?`, and `??`. These are non-greedy and will try to match as few characters as possible:

```
non_greedy = re.compile(r"<a.*?>")

print(re.match(non_greedy, html).group())
# <a href='mathspp.com'>
```

111 – Type hints that refer to functions

When dealing with higher-order functions (functions that accept functions as arguments or that return functions), you can use `collections.abc.Callable` to add a type hint to the function that is an argument/the return value.

`Callable` takes two values:

1. the list of types of the arguments of the callable; and
2. the return type of the callable.

For example, `Callable[[str, bool], None]` is the type that refers to functions that accept a string and a Boolean value and return `None`.

112 – Two-dimensional range

You can build a two-dimensional range using the built-in `range` and `itertools.product`. This is useful when traversing 2D structures like grids.

It's also better than a nested for loop because it's easier to break out of:

```
def range_2d(n, m):
    return product(range(n), range(m))

for x, y in range_2d(10, 3):
    if x == 2:
        break
    print(x, y)

"""Output:
0 0
0 1
0 2
1 0
1 1
```

```
1 2
"""
```

113 – Constant variables

There is no way to create a true constant in Python. Instead, you can use other mechanisms to signal to people that some values shouldn't change.

PEP 8 establishes the convention that if a variable has its name written in ALL_UPPERCASE, then that's a constant and you shouldn't modify its value:

```
PI = 3.1415
```

Additionally, the module `typing` has the annotation `Final` that you can use to indicate to type checkers that a given name shouldn't be reassigned to. `Final` is a generic that takes the true type of the variable inside square brackets []:

```
PI: Final[float] = 3.1415
```

114 – `dict.fromkeys`

If you have an iterable of keys you can initialise a dictionary by using the class method `dict.fromkeys`, which creates a dictionary where all keys map to the value `None`:

```
keys = ["name", "age", "address"]
person_info = dict.fromkeys(keys)
```

```
print(person_info)

{
    'name': None,
    'age': None,
    'address': None,
}
```

If the default value `None` doesn't suit you, you can change it by passing a different default value as the second argument to `dict.fromkeys`:

```
person_info = dict.fromkeys(keys, "")

print(person_info)

{
    'name': "",
    'age': "",
    'address': "",
}
```

Be careful when passing mutable values as the default value, though:

```
keys = ["a", "b", "c"]
my_dict = dict.fromkeys(keys, [])

my_dict["a"].append("Hello")
my_dict["b"].append("there")
print(my_dict["c"]) # ['Hello', 'there']
```

Further reading:

- [Custom value in dict.fromkeys.](#)

115 – Double leading underscore

Name mangling is a Python feature that mangles the names of attributes and methods of functions that start with a leading double underscore, like `__value`.

Attributes/methods like this are accessible with their original name from inside the class:

```
class MyClass:
    def __init__(self):
        self.__value = 42

    def print_value(self):
        print(self.__value)
```

```
c = MyClass()
c.print_value() # 42
```

From outside the class, attributes/methods have their names mangled with a leading underscore `_` and the name of the class:

```
print(c.__value) # AttributeError
#          vvvvvvvv mangled
print(c._MyClass__value) # 42
```

This feature is not supposed to be used to create “private” attributes, since the attributes are still public. This is intended in OOP contexts like when writing mix-ins, to make it virtually impossible for attributes/methods to be overridden by mistake.

116 – Send data into generators

Generators have a method `send` that you can use to send data into the generator. Inside the generator, that data comes from the expression `yield`, that evaluates to the value that was sent into the generator.

The example below shows a generator that produces consecutive integers. However, if you send an integer into the generator, you’ll skip ahead that many integers:

```
def count():
    at = 0
    while True:
        skip = yield at
        if skip is not None:
            at += skip
        else:
            at += 1
```

Here’s an example usage:

```
counter = count()
print(next(counter)) # 0
print(next(counter)) # 1
```

```
print(counter.send(5)) # 6
```

```
print(next(counter)) # 7
```

Note how the return value of the method `send` is the next value produced by the generator.

When you use the built-in `next` to fetch the next value the result of the `yield` is `None`, because no value was sent to the generator.

117 – Dictionary creation idiom

Dictionaries can be created from iterables of key/value pairs, which naturally gives rise to a useful idiom to create dictionaries using the built-ins `zip` and `dict`.

Instead of iterating over two iterables, each containing all keys or all values:

```
my_dict = {}
for key, value in zip(keys, values):
    my_dict[key] = value
```

Or even instead of using a dictionary comprehension:

```
my_dict = {key: value for key, value in zip(keys, values)}
```

You can use the built-ins `dict` and `zip`:

```
my_dict = dict(zip(keys, values))
```

Here's a concrete example:

```
prompts = ["age", "country", "favourite language"]
answers = [28, "Portugal", "Python"]
```

```
info = dict(zip(prompts, answers))
print(info)

{
    'age': 28,
    'country': 'Portugal',
    'favourite language': 'Python',
}
```

118 – Safely overriding methods

The decorator `typing.overrides` can be used to mark that a method is overriding a method from a parent class. If it isn't, type checkers will complain.

Here's an example super class that implements two methods `sound` and `sleep`:

```
class Animal:
    def sound(self) -> str:
        ...

    def sleep(self) -> None:
        ...
```

Suppose you want to override this class to create a class `Cat`:

```
from typing import overrides
```

```
class Cat(Animal):
    @overrides
    def sound(self) -> str:
        ...

    @overrides
    def seep(self) -> None
    ...
```

A type checker will see that `Cat.sound` and `Cat.seep` are supposed to be overrides of methods from the parent class(es). Since a type checker won't find a method `seep` in a parent class (because it's supposed to be "sleep", with an extra L), you will get an error and you'll easily spot your typo.

Using `overrides` is also useful if you're inheriting from parent classes from other packages, since it will let you know if a method name changes; for example, if the API changes in a version upgrade.

119 – Efficiently extending a list

The method `extend` is the efficient way of adding multiple elements to a list in one go:

```
my_list = [...]
```

```
my_list.extend(other_list)
```

This also works with other iterables, even if they're not lists.

A common alternative that also works with non-list iterables is using a `for` loop that calls the method `append` repeatedly:

```
my_list = [...]
```

```
for value in other_list:
    my_list.append(value)
```

However, this is inefficient because the repeated calls to `append` will waste time constantly resizing the list.

Another alternative that may sound like a good idea but actually wastes time and memory computing a third list is concatenating the two lists:

```
my_list = [...]
```

```
my_list = my_list + other_list
```

CPython implementation detail: if you use augmented assignment `+=` then it's efficient again because it defers to the method `extend` at the C level.

120 – All equal

To check if all values of an iterable are equal (up to a key function), you can use `itertools.groupby` and check how many groups are found (under the same key function):

```
from itertools import groupby, islice
```

```
def take(iterable, n):
```

```
    return list(islice(iterable, n))

def all_equal(iterable, *, key=None):
    return len(take(
        groupby(iterable, key),
        2,
    )) <= 1
```

The function `all_equal` uses `groupby` to create runs of elements that are the same under the function `key`. Then, the function `take` is used to try and take the first 2 of those runs. If there are no runs, or if there is only one run, it's because all values were the same.

121 – Paginate results

You can use `itertools.batched` to paginate an arbitrary iterable. For example, you can take a generator that produces single values and turn it into a generator that produces “pages” of results.

You can even do this with an auxiliary generator:

```
def paginated(function):
    def wrapper(*args, **kwargs):
        yield from batched(function(*args, **kwargs), 10)
    return wrapper
```

Here's an example application:

```
@paginated
def evens():
    at = 0
    while True:
        yield at
        at += 2

for page in evens():
    print(page)
# (0, 2, 4, 6, 8, 10, 12, 14, 16, 18)
# (20, 22, 24, 26, 28, 30, 32, 34, 36, 38)
# ...
```

122 – Ignore exceptions

The module `contextlib` provides a context manager `suppress` that you can use to suppress (ignore) a given exception. Very helpful when you want to run some code, hoping it works, but when you really don't care if it ends up failing. You can read this idiom exactly as “it's ok if this fails”:

```
from contextlib import suppress

with suppress(SomeException):
    run_some_code()
```

This is better than using `except SomeException: pass` because `suppress` conveys the meaning “ignore the exception” immediately, whereas using `try: ... except: pass` only shows that information much later:

```
try:
    run_some_code()
except SomeException:
    pass
```

Further reading:

- [Ignoring exceptions with `contextlib.suppress`](#)

123 – Using properties

The built-in decorator `property` can be used to turn a method into an attribute. This means that properties look like attributes but actually run methods that compute the values that must be returned.

Useful, for example, if you have something that “looks” like an attribute but needs to be computed dynamically, like someone’s age based on their birthdate:

```
import datetime as dt

class Person:
    def __init__(self, name, birth_date):
        self.name = name
        self.birth_date = birth_date

    @property
    def age(self):
        y, m, d, *_ = dt.date.today().timetuple()
        by, bm, bd = self.birth_date
        return y - by - ((bm, bd) > (m, d))
```

```
john = Person("John", (1990, 8, 28))
```

```
# 27th August, 2025, it's John's birthday tomorrow
print(john.age)  # 34
```

```
# time.sleep(1 day)
```

```
# 28th August, 2025, it's John's 35th birthday
print(john.age)  # 35
```

Note how `Person.age` is implemented as a method, but because of the decorator `property`, it’s accessed as an attribute.

Further reading:

- [Properties](#)

124 – Operate on two lists of numbers

If you combine the module operator with `itertools.starmap` and `itertools.zip_longest`, you can write any function that merges two lists by operating on respective pairs of elements.

`zip_longest` allows you to operate until the end of the longer list and then `starmap` allows you to unpack the tuples into arguments of the operation you chose. If you don't need `zip_longest` to get to the end of the longer iterable, then you can just use the built-in `map(add, l1, l2)` and `starmap` ends up not being needed either.

The example below adds two lists, element by element, padding the shorter list with zeroes:

```
from itertools import starmap, zip_longest
from operator import add

def add_lists(l1, l2):
    """Function to add respective elements from two lists."""
    return list(starmap(add, zip_longest(l1, l2, fillvalue=0)))

add_lists(
    [1, 2, 3],
    [10, 20, 30, 40],
) # [11, 22, 33, 40]
```

125 – Enforce positional arguments

You can use the forward slash `/` in a function signature to force arguments to be passed in as positional only. In other words, use `/` to disallow arguments from being passed as keyword arguments.

This is useful when the names of the arguments are inconsequential. For example, in a mathematics context, `p` and `q` are very common names for polynomials, but the names themselves have no meaning. So, if you're defining a function that adds two polynomials (using [the idiom to operate on two lists of numbers](#)), you might want `p` and `q` to only be passed in positionally:

```
from itertools import starmap, zip_longest
from operator import add

def add_polynomials(p, q, /):
    """Function to add two polynomials as lists of coefficients."""
    return list(starmap(add, zip_longest(p, q, fillvalue=0)))

add_polynomials(poly1, poly2) # Ok.
add_polynomials(p=poly1, q=poly2) # TypeError!
```

Another example use case is from the [Cyclopts package](#), a package to create CLIs. In Cyclopts, you [use the forward slash / to declare that a parameter is an argument and not an option](#).

126 – Integer literals in multiple bases

Python integer literals are base 10 by default. But you can also use the prefixes `0b`, `0o`, and `0x`, to write integer literals in binary, octal, and hexadecimal, respectively:

Prefix	Base
0b	binary
0o	octal
0x	hexadecimal

```
feature_flags = 0b1101  # turn off *that* feature

file_permissions = 0o755  # default file permissions

magenta = 0xCE5D97  # accent colour used on my site
```

Further reading:

- [Base conversion in Python](#)

127 – Remove punctuation functionally

You **already know how to remove punctuation from a string**, but you can leverage `functools.Placeholder` (new in Python 3.14) and `functools.partial` to turn that into a function:

```
from functools import Placeholder as _P, partial
import string

remove_punctuation = partial(
    str.translate,
    _P,
    str.maketrans("", "", string.punctuation),
)
```

Now, you can pass a string into the function `remove_punctuation`, which puts it as the first argument to `str.translate` because of the usage of `Placeholder`:

```
print(remove_punctuation("Hello, world!"))
# Hello world
```

This wouldn't have been possible without `Placeholder` because `str.translate` only accepts positional-only arguments.

Further reading:

- [functools.Placeholder](#)
- [functools.partial](#)
- [String translate and maketrans methods](#)

128 – pairwise generalisation

`itertools.pairwise` accepts an iterable and produces overlapping pairs of consecutive elements:

```
from itertools import pairwise

my_list = [42, 73, 16, 0, 10]
for a, b in pairwise(my_list):
    print(a, b)
```

```
"""
Output:
42 73
73 16
16 0
"""
```

```
0 10
"""
```

If you need a similar behaviour but with tuples of an arbitrary size, you can implement that as a generator with `collections.deque` and `itertools.islice`:

```
from collections import deque
from itertools import islice

def n_tuples(data, n):
    """Produces overlapping tuples of size `n`."""
    data = iter(data)
    window = deque(islice(data, n - 1), maxlen=n)
    for value in data:
        window.append(value)
        yield tuple(window)
```

129 – Prevent subclassing/overriding

The decorator `typing.final` (lowercase **f**) can be used to mark classes that shouldn't be subclassed:

```
from typing import final

@final
class Base:
    pass

class C(Base): # Type checkers will complain.
    pass
```

The decorator can also be used to mark methods that shouldn't be overridden by subclasses:

```
from typing import final

class Base:
    @final
    def foo(self) -> None:
        pass

class C(Base): # This is fine...
    def foo(self) -> None: # But a type checker will complain here.
        pass
```

130 – Make numbers more readable

You can use the character underscore `_` in number literals (integers, floats, and complex numbers), to separate groups of digits. This works for **any base that Python supports**:

- grouping digits by thousands in base 10;
- grouping bits by 4 or 8 bits in base 2; and
- grouping RGB channels in colours represented in hexadecimal,

are just some examples:

```
x = 12_345_678 # integer
almost_x = 12_345_677.99 # float
complex_x = 1+23_456j # complex

binary = 0b1110_0100
octal = 0o7351_2242
hexadecimal = 0xff_d3_ab
```

131 – Efficiently count words in a string

You can efficiently count how many words a string has by using `itertools.groupby`:

```
from itertools import groupby

def count_words(s):
    return sum(is_alpha for is_alpha, _ in groupby(s, key=str.isalpha))
```

This is so efficient, you could use it to count words on files larger than your computer's RAM memory. But here's an example usage with a smaller string:

```
print(
    count_words("Hey there-how you doin'?")
) # 5
```

Note that, depending on the predicate you use as the keyword argument `key`, you get different definitions of “word”. By using `is_alpha`, you are implicitly defining a “word” to be a sequence of characters for which the string method `str.isalpha` returns `True`.

Under the hood, `groupby` is grouping characters in runs of characters for which `str.isalpha` is `True` and runs for which it is `False`, and then you're counting the number of runs associated with the value `True`.

132 – Efficiently count characters in a string

Python has a specialised dictionary for whenever you need to count things or represent counts: `collections.Counter`. The only restriction you need to keep in mind is that `Counter` can only count hashable objects, since it's dictionary-like.

You can initialise by passing in an iterable of elements to count:

```
from collections import Counter

counts = Counter("mississippi")
```

From there, you can access counts by key, even if the key isn't there:

```
print(counts["m"]) # 1
print(counts["z"]) # 0
```

Since it's a specialised dictionary, `Counter` also includes many useful methods to work with counts, like the method `most_common`:

```
print(counts.most_common(2))
# [('i', 4), ('s', 4)]
```

133 – Find files in a directory

You can use `pathlib.Path` together with the methods `iterdir` and `is_file` to find and list all files inside a directory:

```
from pathlib import Path

directory = Path("path/to/dir")
files = [p for p in directory.iterdir() if p.is_file()]
```

The method `iterdir` finds all directory contents but won't recurse into subdirectories and then `is_file` filters out anything that's not a file. You could replace it with `is_dir` to get all directories instead.

This is more robust than using something like `glob(*.*)` because files don't always have dots in their names.

134 – Invertible flags

The special values `True` and `False` are tightly connected: they mean the opposite of each other and you can negate one to get the other:

- `not True` gives `False`
- `not False` gives `True`

You can create the same behaviour and the same semantics of “two opposite values” by using a flag enumeration with only two members with values 0 and 1:

```
from enum import Flag

class DoorState(Flag):
    CLOSED = 0
    OPEN = 1

print(~DoorState.CLOSED)  # DoorState.OPEN
print(~DoorState.OPEN)    # DoorState.CLOSED
```

The bitwise operator `~` (NOT) negates the flag, turning it into the opposite member.

You can also use the keyword `not` to do the negation, but in that case you need to reinstantiate the flag to make it a member of the enumeration again:

```
print(DoorState(not DoorState.CLOSED))
# DoorState.OPEN
print(DoorState(not DoorState.OPEN))
# DoorState.CLOSED
```

Useful for user configurations where you want readable options!

135 – Class and instance attributes

In a typed project, you can specify the types of (instance) attributes by declaring them all in the body of the class (just like dataclasses do):

```
class Person:
    name: str
    ...
```

```
p = Person()
p.name = "Steve"  # Type checks.
p.name = 73       # Type error.
```

But if you want to declare a class attribute (one that shouldn't be modified from any instance) then you must use `typing.ClassVar` to distinguish from a normal instance attribute:

```
from typing import ClassVar

class Person:
    species: ClassVar[str] = "Homo sp"
    name: str
    ...

Person.species = "Homo sapiens"  # Type checks.
p = Person()
p.species = "..."  # Can't modify class attribute from instance.
p.name = "Steve"    # Still an instance attribute.
```

136 – Strict batching

When using `itertools.batched` with the purpose of reshaping a one-dimensional iterable into sections of a fixed size, set `strict=True` if you expect the iterable to contain a whole number of sections.

Without it, the final batch may be incomplete:

```
from itertools import batched

for batch in batched(range(10), 4):
    print(batch)
# (0, 1, 2, 3)
# (4, 5, 6, 7)
# (8, 9)
```

If you set `strict=True`, you get a `ValueError` if the final batch is smaller than the specified size:

```
from itertools import batched

for batch in batched(range(10), 4):
    print(batch)
# (0, 1, 2, 3)
# (4, 5, 6, 7)
# ValueError
```

Note that you only get the `ValueError` once you get to the end of the batched iterable and *not* when you create the batched iterable:

```
batched(range(10), 4)  # No error raised yet.
```

137 – Read-only attributes

The standard way of creating read-only attributes in Python is by creating a “private” attribute and then exposing it through a property:

```
class Person:
    def __init__(self, name):
        self._name = name

    @property
    def name(self):
        return self._name
```

This way, the property is read-only:

```
john = Person("John")

print(john.name) # John
john.name = "Steve" # AttributeError
```

However, the underlying “private” attribute is still accessible and could be modified:

```
john._name = "Steve"
print(john.name) # Steve
```

138 – Alternative constructors as class methods

A common use case for class methods is to provide alternative constructors for classes. (An example from the built-ins is `dict.fromkeys()`.)

A class method accepts the class as its first argument, not `self`. (Otherwise, it would be an instance method and not a class method.)

```
class Person:
    def __init__(self, first, last):
        self.first = first
        self.last = last

    @classmethod
    def from_name(cls, name):
        return cls(*name.split())
```

The class method `from_name` lets you create instances of the class `Person` by passing the full name directly:

```
john = Person.from_name("John Smith")

print(type(john)) # <__main__.Person object at 0x103a26e40>
print(john.first) # John
print(john.last) # Smith
```

139 – Reduce boilerplate with dataclasses

The module `dataclasses` provides a decorator `dataclass` that you’re supposed to use on classes. The decorator `dataclass` reduces the need to write boilerplate code by adding the dunder methods `__init__`, `__eq__`, and `__repr__`, to the class that is decorated.

To create a dataclass, all you need is to define the attributes that are relevant by listing them in the class body along with an annotation of their type:

```
from dataclasses import dataclass
```

```
@dataclass
class Person:
    first: str
    last : str
```

The four lines of code that define the class Person as a dataclass are roughly equivalent to the following handwritten definition:

```
class Person:
    def __init__(self, first, last):
        self.first = first
        self.last = last

    def __eq__(self, other):
        if isinstance(other, Person):
            return self.first == other.first and self.last == other.last
        return NotImplemented

    def __repr__(self):
        cls = type(self).__name__
        return f"{cls}(first={self.first!r}, last={self.last!r})"
```

140 – Compute partial sums with accumulate

`itertools.accumulate` computes partial sums of the given iterable. Or, in other words, `accumulate` computes prefix sums.

For example, if you give it a list of bank movements, `accumulate` computes the intermediate bank balances:

```
from itertools import accumulate

movements = [100, -200, 300, -450]
initial_balance = 1000

for balance in accumulate(movements, initial=initial_balance):
    print(balance)
# 1000
# 1100 (1000 + 100)
# 900 (1100 - 200)
# 1200 (900 + 300)
# 750 (1200 - 450)
```

This shows there is a relationship between `accumulate` and the built-in `sum` if you consider slices of the list `movements` with the initial balance at the front:

```
[1000, 100, -200, 300, -450]
sum(      )           # 1000
sum(      )           # 1100
sum(      )           # 900
sum(      )           # 1200
sum(      )           # 750
```

141 – Regex matches across newlines

The special character `.` (dot) matches anything in the context of a regular expression, except for the newline character:

```
import re

pattern = r"<!--.*-->" # HTML multiline comment.
text = """# Python drops <!--This
is a multiline comment.-->"""

print(re.search(pattern, text)) # None
```

If you want to use the special character `.` (dot) for matches that potentially span across multiple lines, you'll need to use flag `re.DOTALL`:

```
print(re.search(pattern, text, flags=re.DOTALL))
# <re.Match object; ...
```

142 – Using fractions

Floats are a bit annoying when you have to do computations because of the inaccuracies inherent to their representation.

For example, $49 * (1 / 49)$ should be 1.0 , but Python gives you a different result:

```
print(49 * (1 / 49)) # 0.9999999999999999
```

(In all fairness, most programming languages agree with Python here.)

In situations like this, if precision is important, you can use `fractions.Fraction` to perform 100% accurate computations and therefore having no errors or inaccuracies in your results:

```
from fractions import Fraction

print(49 * Fraction(1, 49)) # 1
```

Note, however, that arithmetic operations performed between fractions or integers and fractions return other fractions:

```
f = 43 + Fraction(1, 49)
print(f) # 2108/49
print(repr(f)) # Fraction(2108, 49)
```

But operations between fractions and floats produce floats:

```
print(49.0 * Fraction(1, 49)) # 0.9999999999999999
```

143 – Decimals

Fractions are very useful but sometimes it is not very helpful to compute $1 / 7$ and get $1/7$ as a result...

Instead, you may want to use the module `decimal` and its class `decimal.Decimal` to compute fast, correctly-rounded floating-point arithmetic:

```
from decimal import Decimal

print(1.1 + 2.2) # 3.3000000000000003
```

```
d = Decimal("1.1") + Decimal("2.2")
print(d)    # 3.3
print(repr(d))  # Decimal('3.3')
```

One good thing about the module `decimal` is that you can set the precision (number of decimal places) with which results are computed:

```
from decimal import getcontext

getcontext().prec = 6
print(Decimal(1) / Decimal(7))  # 0.142857

getcontext().prec = 28
print(Decimal(1) / Decimal(7))  # 0.1428571428571428571428571429
```

144 – Safe random tokens

To create a URL-safe token in your web server, use `secrets.token_urlsafe`:

```
from secrets import token_urlsafe

print(token_urlsafe())  # ScIFbN8NcONKLI40_8o0cMwkqRRFfVgGUE8kBgEkRf0
```

The function `token_urlsafe` accepts an integer for the number of random bytes to be generated, but that's not the same as the number of characters generated because of the way the random bytes are then turned into a URL-safe string:

```
print(token_urlsafe(4))
# ewtWsw
```

Remember that the module `random` is for modelling/simulations, not for security-sensitive operations or for cryptography!

145 – NotImplemented

The singleton built-in `NotImplemented` has one and only one very specific use case: binary dunder methods return this value when they don't know how to compute the result of the operation between the two given arguments.

In other words, the only correct way of implementing a binary dunder method is to return `NotImplemented` after handling all the cases you know and care about.

Here is an example with a class `Person`:

```
class Person:
    def __init__(self, name):
        self.name = name

    def __eq__(self, other):
        if isinstance(other, Person):
            return self.name == other.name
        return NotImplemented
```

One might think that the correct thing to do is to return `False` in `Person.__eq__` after concluding that `other` isn't an instance of `Person`, but that precludes you and others from writing classes in the future that can compare to `Person`.

For example, suppose the class `Employee` is implemented at a later date and it's independent of the class `Person`. Employees will only be comparable to persons if `return NotImplemented` is used in `Person.__eq__`:

```
class Employee:
    def __init__(self, name):
        self.name = name

    def __eq__(self, other):
        if isinstance(other, Person | Employee):
            return self.name == other.name
        return NotImplemented

print(Person("John") == Employee("John"))  # True
```

Give it a try. Replace the final return of `Person.__eq__` with `return False` and note how the value that is printed becomes `False` instead of `True`.

`NotImplemented` should not be confused with the built-in exception `NotImplementedError`.

146 – Cycling over an iterable

Whenever you need to cycle over an iterable use `itertools.cycle`:

```
from itertools import cycle

servers = [...]

for server in cycle(servers):
    server.ping()
```

This is preferred over the modulo operator trick:

```
servers = [...]
idx = 0

while True:
    idx = (idx + 1) % len(servers)
    servers[idx].ping()
```

The two main advantages are that

1. `cycle` is more readable because the name spells out what you are doing; and
2. the modulo operator trick has limitations, since it only works on iterables that you can index and compute the length of.

147 – String formatting field alignment

There are three main alignment options in string formatting:

Character	Meaning

```
< | align left |
> | align right |
^ | centre |

total = 123

print(f"Total: ${total:<7}.")
# Total: $123     .

print(f"Total: ${total:>7}.")
# Total: $      123.

print(f"Total: ${total:^7}.")
# Total: $   123   .
```

For most objects, the default is to align left:

```
obj = "hi"
print(f"--{obj:10}-")
# -hi          -
```

However, for numbers, the default is to align right:

```
obj = 42
print(f"--{obj:10}-")
# -          42-
```

(There is also a fourth alignment option = that only works with numbers!)

148 – Set operations with operators

Many set operations, like containment checks, can be written with Python's operators instead of method calls. This allows for succinct but expressive code:

```
import string

allowed_chars = set(string.ascii_letters)

s = "I like trains."

if not (used := set(s)) <= allowed_chars:
    print("Illegal characters found:")
    print(used - allowed_chars)

# Illegal characters found:
# {' ', '.', ' '}
```

The comparison `used <= allowed_chars` is the same as `used.issubset(allowed_chars)` and checks whether `used` is contained within `allowed_chars`.

The operation `used - allowed_chars` is the same as `used.difference(allowed_chars)` and computes all elements of `used` that are not in `allowed_chars`.

149 – NotImplementedError

The built-in exception `NotImplementedError` is supposed to be used in base classes to indicate that a given method must be implemented by the derived class:

```
class Parser:
    def parse(self, data):
        raise NotImplementedError
```

You can also use the exception `NotImplementedError` to create a stub for a method but also signal that its real implementation still needs to be added:

```
class MyParser(Parser):
    def parse(self, data):
        self._validate_data(data)
        # Parse the data...


    def _validate_data(self, data):
        raise NotImplementedError
```

The documentation also notes that you should **not** use `NotImplementedError` to indicate that a method isn't supposed to be supported at all by a (sub)class.

`NotImplementedError` should not be confused with [the built-in singleton `NotImplemented`](#).

150 – Colour in the REPL

Since Python 3.14 that the Python REPL has colours, giving you syntax highlighting directly in the terminal.



```
>>> from functools import cache
>>> @cache
... def fibonacci(n: int) -> int:
...     if n <= 1:
...         return 1
...     return fibonacci(n - 1) + fibonacci(n - 2)
...
>>> print("Hello, world!")
Hello, world!
>>> █
```

CLIs in the standard library like `argparse`, `json`, and `unittest`, also have coloured output now.

151 – copy files

You can copy files and directories to new locations by using `pathlib.Path.copy`.

Suppose your filesystem looks like this:

```
- base/
  - other/
  - myfile.txt
```

If your current working directory is base, then the snippet

```
from pathlib import Path
```

```
Path("myfile.txt").copy("myfile2.txt")
```

will create a copy of myfile.txt named myfile2.txt next to it:

```
- base/
  - other/
  - myfile.txt
  - myfile2.txt
```

However, if instead you run the snippet

```
from pathlib import Path
```

```
Path("myfile.txt").copy_into("other")
```

then the file myfile.txt is copied, with the same name, into the folder other:

```
- base/
  - other/
    - myfile.txt
  - myfile.txt
```

The methods `copy` and `copy_into` accept strings or `pathlib.Path` objects, although these two examples used strings.

152 – Find similar words

You can use the function `get_close_matches` from the module `difflib` to find words that are similar to another given word, for example in the context of an auto-correct feature.

Suppose you're trying to write a loop but misspell the keyword `while`:

```
>>> whille True:
      File "<python-input-7>", line 1
        whille True:
        ~~~~~
SyntaxError: invalid syntax. Did you mean 'while'?
```

The suggestion of the (correct) keyword `while` is done with `get_close_matches`:

```
from difflib import get_close_matches
import keyword

print(
    get_close_matches("whille", keyword.kwlist)
) # ['while']
```

The function `get_close_matches` also allows you to specify the maximum number of similar matches you want and the “similarity threshold” to be used.

153 – Forward references in annotations

Forward/cyclic references in Python type hints raise a `NameError` up until Python 3.13:

```
class Node:
    next_node: Node

# NameError: name 'Node' is not defined.
```

You can fix this by turning the type hint : `Node` into a string : `"Node"` or by using a future import:

```
from __future__ import annotations

class Node:
    next_node: Node
```

By using the future import, you are deferring the evaluation of the annotations and that allows you to write cyclic/forward references.

In Python 3.14, this became the default behaviour:

```
# Python 3.14
class Node:
    next_node: Node
# No `NameError`.
```

Further reading:

- [PEP 649 – Deferred Evaluation of Annotations Using Descriptors](#)

154 – Compression algorithms

Python 3.14 introduced a new module `compression` that provides a unified interface to access the five compression algorithms that Python supports:

- `bz2`
- `gzip`
- `lzma`
- `zlib`
- `zstd` (new in Python 3.14)

Here's an example usage of `zstd` to compress a sequence of bytes:

```
from compression import zstd

data = "3.141592653589793".encode() * 20
compressed = zstd.compress(data)
ratio = len(compressed) / len(data)
print(ratio) # 0.1 # <- 10 times smaller!
```

The algorithms `bz2`, `gzip`, `lzma`, and `zlib`, were already standalone modules in Python 3.13 and earlier, so they continue to be so, but you can also access them through the unified interface of the module `compress`.

155 – json CLI

The module `json` is your go-to tool when working with files or data in JSON format. In Python 3.14, the module got a new CLI that allows you to validate and pretty-print JSON data directly from the command line.

For example, if the file `mydata.json` contains the following data:

```
{
    "isActive": true,
    "balance": "$2,186.98",
    "age": 33
}
```

Then, the `json` CLI can be used to turn the JSON data into a more compact format by using its option `--compact` while also ordering keys:

```
$ python -m json mydata.json --compact --sort-keys
```

The output produced is the following:

```
{"age":33,"balance":"$2,186.98","isActive":true}
```

The prefix `python -m json` is the command you use to run the CLI of the module `json`; `mydata.json` specifies the input file; `--compact` is a flag that suppresses all whitespace separation; and `--sort-keys` sorts keys in dictionaries alphabetically.

Run `python -m json --help` to see all the options and flags that the CLI supports.

156 – Custom t-string processing

t-strings, introduced in Python 3.14, offer a flexible and safe way of doing string formatting in contexts where care must be taken with the interpolated values.

For example, you can think about SQL injection attacks or having to escape some characters when interpolating strings that contain HTML.

When you create a t-string you must process it in order to create the final string object. For example, the variable `s` doesn't hold a string yet:

```
greeting = "Hey, there"
num = 3

s = t"He said {greeting} and waved {num} times."
#      ~~~~~      ~~~~~      ~~~~~      # String literal parts.
#      ~~~~~      ~~~~~      ~~~~~      # Interpolated parts.
```

To process `s` into a string you can specify a function that iterates over the parts of the t-string and does whatever you need to each part. Parts that are interpolated values have an attribute `value` that is the original object being interpolated:

```
def auto_repr(tstring):
    parts = [
        part if isinstance(part, str) else repr(part.value)
        for part in tstring
    ]
    return "".join(parts)

print(auto_repr(s))
```

```
# "He said 'Hey, there' and waved 3 times."
# ~~~~~ ~
```

157 - asyncio introspection

You can use the `asyncio` CLI (new in Python 3.14) to inspect/debug running Python processes that use asynchronous tasks. For example, take this tiny example of an asynchronous program in the file `my_code.py`:

```
import asyncio

async def main():
    await asyncio.sleep(60)
```

```
asyncio.run(main())
```

If you run the program and the running process has the ID 12345, for example, then you can run

```
$ python -m asyncio pstree 12345
```

And you get a tree showing all currently-running `asyncio` tasks in a hierarchical format:

```
(T) Task-1
    main /path/to/my_code.py:4
    sleep /path/to/python/asyncio/tasks.py:702
```

The subcommand `ps` can be used instead of `pstree` to display this information in a table instead of in a tree.

158 – Grouping digits in the fractional part

You can **group digits in integers with underscores or commas**, but since Python 3.14 that you can also do the same to the digits of the fractional part of a number.

x = 12345.09876543

```
f"{x:.,}" # '12345.098,765,43'
f"{x:._}" # '12345.098_765_43'
```

The grouping can be specified independently for the digits before and after the decimal point by including a grouping character before or after the dot in the formatting specification:

```
f"{x:_.,}" # '12_345.098,765,43'
```

Remember that if you only specify the grouping character, it will only group the digits of the integral part (see “**Formatting big numbers**”):

```
f"{x: _}" # '12_345.09876543'
```

159 – Error handling with multiple types

When doing error handling with a `try: ... except: ...` block, you can handle different exception types in two different ways.

If you have two or more exception types that can be handled in the same way, you can group those exception types in the same `except` statement:

```
try:
    some_code()
except (ValueError, TypeError):
    do_something_universal()
```

In Python 3.14+, if you're not using the keyword `as`, you can omit the parentheses and write

```
# ...
except ValueError, TypeError:
    do_something_universal()
```

If different exception types need to be handled differently, you can have multiple `except` statements:

```
try:
    some_code()
except TypeError:
    do_something1()
except ValueError:
    do_something2()
```

160 – Parse dates from strings

You can use the class method `datetime.date.strptime` to parse a date from a string with the given format:

```
import datetime as dt

date_str = "26/10/2025"

when = dt.date.strptime(date_str, "%d/%m/%Y")
print(f"{when:%B %d, %Y}") # October 26, 2025
```

This method is new in Python 3.14 for the class `datetime.date`, but the classes `datetime.datetime` and `datetime.time` already supported `strptime`.

161 – min-heaps and max-heaps

The module `heapq` has support for min-heaps and max-heaps, providing a number of functions to work efficiently with priority queues:

```
from heapq import (
    heapify,
    heappush,
    heappop,
    heappushpop,
    heapreplace,
) # for min-heaps
```

For max-heaps, append the suffix `_max` to the name of each function:

```
from heapq import (
    heapify_max,
    heappush_max,
    heappop_max,
    heappushpop_max,
```

```
    heapreplace_max,  
) # for max-heaps
```

Support for min-heaps has been around for a while but support for max-heaps was only added in Python 3.14.

162 – Check for None functionally

Typically you use the expressions `... is None` and `... is not None` to check whether an object is or isn't None, respectively.

The module operator provides the functions `is_none` and `is_not_none` that perform the same checks:

```
from operator import is_none, is_not_none
```

```
print(is_none(None)) # True  
print(is_not_none(None)) # False
```

```
print(is_none(73)) # False  
print(is_not_none(73)) # True
```

These are useful when you're using higher-order functions.

163 – Remote interactive debugging

Since Python 3.14 that the module `pdb` has a CLI option that allows you to attach to a running Python process to debug interactively while it's running.

Suppose you have some buggy and complex business logic:

```
acc = 0  
  
while True:  
    acc += 1
```

You save this code in the file `myscript.py` and run it. The program never finishes, so you see it's running in the process with ID 12345 and you use the module `pdb` to attach to it:

```
$ python -m pdb -p 12345
```

Once you do, the debugger attaches to your program *while* it's running. Here, you can see you attached to the program as it was about to run the line `acc += 1`. Before you do, you may want to **print** the value of the variable `acc`:

```
> /path/to/script.py(4)<module>()  
-> acc += 1  
(Pdb) p acc  
559642795
```

Now, you may want to go to the next line of the function and print the value of the variable `acc` again:

```
(Pdb) next  
> /path/to/script.py(3)<module>()  
-> while True:  
(Pdb) p acc  
559642796
```

164 – Chaining comparison operators

Python has plenty of comparison operators:

- `<`, `<=`, `>`, `>=`
- `==`, `!=`
- `in`, `not in`
- `is`, `is not`

All of these comparison operators can be chained together. For example, writing `floor <= value <= ceiling` is the same as writing `floor <= value` and `value <= ceiling`.

Chaining comparison operators can improve code readability, but only if

- used in sequences of `<` / `<=` signs; or
- used in sequences of `>` / `>=` signs.

Mixing different comparison operators will lead to code that is hard to parse. For example, `value in mylist == True` looks like `(value in mylist) == True`, but it's actually `value in mylist` and `mylist == True`, which will always be false if `mylist` is a list.

Further reading:

- [Chaining comparison operators](#)

165 – Controlled string splitting

The string method `str.split` has a parameter `maxsplit` that determines the maximum number of splits that will be performed:

```
>>> "a/b/c/d".split("/", 1)
['a', 'b/c/d']
```

```
>>> "a/b/c/d".split("/", 2)
['a', 'b', 'c/d']
```

```
>>> "a/b/c/d".split("/", 3)
['a', 'b', 'c', 'd']
```

```
>>> "a/b/c/d".split("/", 4)
['a', 'b', 'c', 'd']
```

The call to the method returns a list with the splits and possibly the remainder of the string, which means that the maximum length of the list returned is `maxsplit + 1`.

166 – `strftime` vs `strptime`

The methods `strftime` and `strptime` can be used to convert dates/times into strings and vice-versa. Here's a mnemonic to help you remember which is which:

- `strptime` has a “P” for “Parse date/time”, so it'll accept a string and parse a date/time from it:

```
import datetime as dt

date = dt.date.strptime("2025-11-04", "%Y-%m-%d")
print(date)  # datetime.date(2025, 11, 4)
```

-
- `strftime` has an “F” for “Format date/time”, so it’ll accept a date/time and it will format it as a string:

```
print(date).strftime("%Y-%m-%d")
# 2025-11-04
```

167 – Private members

Python has a very well-known naming convention: names that start with a leading underscore `_` are considered “private”.

This means the outside world has no business using them. For example, attributes and methods starting with `_` in a class mean they’re for that class only. When that happens, it’s common to see other methods of the class use those private names, like is the case for `drive/_start_engine` in the class `Car`:

```
class Car:
    def __init__(self, ...):
        self._serial_number = ...

    def _start_engine(self): ...

    def drive(self):
        self._start_engine()
        ...
```

Sometimes, private attributes/methods are still used inside the same module:

```
def _validate_serial_number(serial_no):
    ...

def inspect_car(workshop, car):
    if not _validate_serial_number(car._serial_number):
        ...
```

But if you’re importing someone else’s code, you should be very careful about using objects whose name starts with an underscore `_`.

168 – Truthy and Falsy

All Python objects have a Truthy/Falsy value which dictates how that object will behave in a Boolean context.

Most objects are Truthy, with a few exceptions. For the built-in types, you usually have a specific value that is Falsy:

```
# Falsy values:
0          # zero
0.0        # zero, as a float
""         # empty string
[]         # empty list
{}         # empty dictionary
set()      # empty set
tuple()    # empty tuple
None      # None
```

Note how the Falsy values are “empty” or stand for “nothing”. All other values of the same corresponding types are Truthy:

```
1, 2, -43           # any non-zero integer
0.1, 3.4, -3.1      # any non-zero float
"hi", "bye", " "     # any non-empty string
[0], [], [1, 2]      # any non-empty list
{"a": "b"}           # any non-empty dictionary
{1, 2}, {False, True} # any non-empty set
(0,), ([], True)     # any non-empty tuple
```

In case you are not sure, you can use the built-in `bool` to check the Truthy/Falsy value of an object:

```
print(bool(None)) # False
```

But when used in Boolean contexts, like `if` statements or in expressions with the keywords `not`, `and`, and `or`, you don't need the built-in `bool` because the Truthy/Falsy values of objects are used automatically.

Further reading:

- [Truthy, Falsy, and bool](#)

169 – Oxford comma

The function below turns a list of strings into a Human-readable enumeration that uses the Oxford comma:

```
def oxford_comma(strings):
    prefix = ", ".join(strings[:-1])
    ox_comma = "," if len(strings) > 2 else ""
    and_ = " and " if len(strings) > 1 else ""
    last = strings[-1] if strings else ""
    return prefix + ox_comma + and_ + last
```

Example usages:

```
print(oxford_comma(["like"]))
# like
print(oxford_comma(["like", "comment"]))
# like and comment
print(oxford_comma(["like", "comment", "subscribe"]))
# like, comment, and subscribe
```

The function `oxford_comma` demonstrates a useful technique for when you're building complex strings.

Instead of using multiple `if` statements to conditionally append parts of the string to the result, build the final string out of smaller fragments. Then, a fragment that is unnecessary can be set to the empty string.

This keeps your code flatter and cleaner.

170 – assert statements with custom message

The keyword `assert` takes an expression on its right and then raises an `AssertionError` if that expression doesn't evaluate to `True` (or Truthy):

```
x = 73
y = 42

assert y > x
```

```
...
AssertionError
```

The error message can be customised if you add a string in front of the expression being checked, separating the two with a comma:

```
x = 73
y = 42

assert y > x, f"{y=} isn't > {x=}..."

...
AssertionError: y=42 isn't > x=73...
```

Clear error messages make life easier for the person who's dealing with the error (which is likely to be "you" from the future), so take a second to write a useful error message that you'll be thankful for.

Just remember to never use `assert` for security-related or sensitive checks, since there are ways to "turn off" the assertions and have Python run without verifying them.

171 – Creating temporary files

You can use `tempfile.TemporaryFile` as a context manager that opens a temporary file that you can write to and read from:

```
import tempfile

with tempfile.TemporaryFile() as f:
    f.write(b"Hello ")
    f.write(b"world!")

    f.seek(0)
    print(f.read().decode()) # Hello world!
```

The default mode for the file is "w+b":

- "w+" opens the file for writing *and* reading, so you can use `seek` to go back to the beginning of the file and read what you wrote to the file; and
- "b" opens the file in binary mode, meaning you'll write and read bytes.

Once the context manager is exited, the file is automatically deleted.

This is useful when testing functions that require file-like objects or as a buffer for when you're processing an amount of data so large that it doesn't fit into memory.

172 – Title case

Use the string method `title` to change a string's casing to title case:

```
print("star wars: the empire strikes back".title())
# Star Wars: The Empire Strikes Back
```

Title case will modify the case of each word so that its first letter is uppercase and all other letters are lowercase. For some reason, I always think that `title` will only make sure the first letter of each word is uppercase, but it will actively lowercase letters that are not at the start of a word:

```
print("CrAzY CAsInG".title())
# Crazy Casing
```

A “word” is a sequence of alphabetical characters, so you can have numbers or punctuation between the letters that `title` will still uppercase those as separate words:

```
print("1word2words3words".title())
# 1Word2Words3Words
```

173 – Using a list as a stack

When working with stacks, use the built-in `list` as the base class:

```
class stack(list):
    def put(self, value):
        self.append(value)

    def peek(self):
        return self[-1]
```

This allows you to inherit useful behaviours for free, like `length`:

```
s = stack()
s.put(1)
s.put(2)
s.put(3)

print(f"The stack has {len(s)} items.")
# The stack has 3 items.
```

Containment checks:

```
print(3 in s) # True
popped = s.pop()
print(3 in s) # False
```

Truthy/Falsy behaviour:

```
if s:
    print(f"{popped} was at the top.")
    print(f"Now it's {s.peek()}")
# 3 was at the top.
# Now it's 2.
```

And more.

174 – Moving average

To compute the moving average of an iterable of values, use `collections.deque` to manage the window. The parameter `maxlen` that the deque has makes it very easy to manage the window and its elements:

```
from collections import deque
from itertools import islice

def moving_average(values, n):
    source = iter(values)
```

```
window = deque(islice(source, n - 1), maxlen=n)
averages = []
for value in source:
    window.append(value)
    averages.append(sum(window) / n)
return averages
```

```
moving_average([10, 20, 30], 2)
# [15.0, 25.0]
```

When you append to the window inside the `for` loop, the window will automatically evict its leftmost element to keep its size at `n` elements.

Further reading:

- [Python deque tutorial](#)

Themed index

- `**kwargs`: 103, 109
- `*args`: 103, 109
- 3.10 (new in Python 3.10): 109
- 3.12 (new in Python 3.12): 16, 47, 84, 88, 109, 121
- 3.13 (new in Python 3.13): 136
- 3.14 (new in Python 3.14): 46, 54, 107, 127, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163
- `~` (tilde): 134

A

- abstract base classes: 149
- abstract syntax trees: 104
- algorithms: 12, 140, 161, 169, 174
- API: 47
- ASCII: 33
- `assert`: 170
- `ast.parse`: 104
- `ast` (module): 104
- asterisk `*`: 27, 34, 35, 55, 77, 103, 138
- asynchronous programming: 157
- `asyncio`: 157
- `atexit.register`: 8
- `atexit`: 8
- automatic cleanup: 8, 92, 171

B

- backslash `\`: 56, 82, 97
- bitwise operators: 134
- boilerplate: 139
- `bool`: 168
- built-ins: 1, 4, 5, 7, 9, 15, 24, 25, 32, 34, 41, 43, 44, 45, 46, 76, 86, 87, 96, 100, 107, 112, 116, 117, 123, 137, 138, 145, 149

C

- caching: 42, 87
- casing: 2, 89, 113, 172
- class methods: 106, 114, 138, 160
- classmethod: 106, 138
- CLI: 155, 157
- closures: 93
- collections.abc.Callable: 111
- collections.abc.Iterable: 36
- collections.abc: 36, 111
- collections.ChainMap: 23
- collections.Counter: 11, 132
- collections.defaultdict: 37, 105
- collections.deque: 6, 60, 78, 128, 174
- collections (module): 11, 23, 37, 60, 78, 128, 132, 174
- comma (,): 158
- comparison operators: 164
- compression (module): 154
- conditional expressions: 70
- context managers: 17, 122
- contextlib.contextmanager: 17
- contextlib.suppress: 122
- contextlib: 17, 122
- conventions: 113, 167

D

- data processing: 83, 155
- data structures: 132, 173, 174
- dataclasses.dataclass: 139
- dataclasses (module): 139
- date and time format specifiers: 65, 91, 160
- dates and times: 21, 65, 91, 160, 166
- datetime.date.strftime: 166
- datetime.date.strptime: 160, 166
- datetime.date.today: 21
- datetime.date: 160
- datetime.datetime.now: 21, 91
- datetime (module): 21, 65, 91, 160, 166
- debugging: 19, 44, 73, 102, 163, 170
- decimal (module): 143
- decorators: 42, 87, 90, 93, 109, 121, 123, 129, 137, 138, 139
- defensive programming: 115
- delattr: 25
- dict.fromkeys: 7, 114
- dict.keys: 22
- dict: 117
- dictionaries: 18, 22, 23, 37, 72, 77, 83, 105, 114, 117
- difflib.get_close_matches: 152
- difflib: 152

-
- docstrings: 95
 - dunder attributes: 95, 99
 - dunder methods: 96, 98, 102, 105, 108, 139, 145
 - dynamic code: 25, 94, 95, 108

E

- `enum.auto`: 39
- `enum.Flag`: 28, 134
- `enum.global_enum`: 38
- `enum.StrEnum`: 31
- `enum` (module): 28, 31, 38, 39, 106, 134
- `enumerate`: 80
- exception handling: 122, 159
- exceptions: 149, 170

F

- f-strings: 19, 44, 48, 62, 65, 147, 158
- falsy/truthy: 68, 100
- file I/O: 43, 60, 61, 66, 86, 92, 171
- `file.writelines`: 66
- filesystem: 64, 71, 80, 91, 92, 133, 151, 171
- `filter`: 100
- floats: 142, 143
- forward slash `/`: 125
- `fractions` (module): 142
- `frozenset`: 87
- functional programming: 93, 127, 162
- functions: 27, 84, 111, 125
- `functools.cache`: 87
- `functools.lru_cache`: 42
- `functools.partial`: 41, 43, 127
- `functools.Placeholder`: 127
- `functools.wraps`: 90
- `functools`: 41, 42, 43, 87, 90, 127
- `future import`: 153

G

- generation expression: 6
- generator expression: 5
- generator expressions: 45
- generators: 17, 30, 67, 73, 116, 121, 128
- generics: 16, 84, 88
- `getattr`: 25
- global names: 38
- `globals`: 108
- guards: 77

H

- hash: 96
- hashing: 96
- heapq: 161
- help: 95
- higher-order functions: 111

I

- I/O: 44, 101, 102
- idioms: 117, 120, 122
- immutability: 18, 58
- inheritance: 26, 58, 99, 149, 173
- int: 4
- integers: 15, 62, 126
- introspection: 39
- isinstance: 3
- iter: 43, 174
- iterables: 5, 6, 12, 24, 35, 36, 43, 60, 74, 76, 78, 112, 114, 116, 117, 119, 120, 121, 124, 128
- iterator protocol: 78
- itertools.accumulate: 140
- itertools.batched: 47, 121, 136
- itertools.chain.from_iterable: 66
- itertools.chain: 11, 74, 85
- itertools.cycle: 146
- itertools.groupby: 12, 120, 131
- itertools.islice: 73, 120, 128, 174
- itertools.product: 112
- itertools.starmap: 46, 124
- itertools.zip_longest: 124
- itertools: 11, 12, 46, 47, 53, 66, 73, 74, 85, 112, 120, 121, 124, 128, 131, 136, 140, 146, 174

J

- JSON: 155
- json (module): 155

K

- key (keyword argument): 24, 32, 41, 89, 131
- keyword arguments: 27
- keywords: 93
- kwargs: 77

L

- len: 24, 41
- list: 173

-
- lists: 85, 119

M

- map: 9, 45, 46, 107, 124
- match statement: 14, 72, 77, 81
- mathematics: 142, 143, 174
- max: 24, 41
- metaprogramming: 26
- min: 24, 41
- mix-ins: 115
- modules: 108
- modulo operator: 146
- multiline strings: 56, 69, 82

N

- named groups: 63, 83
- namespaces: 108
- naming: 113, 115, 167
- newlines: 40, 56, 82
- next: 5, 76, 116
- nonlocal: 93
- NotImplemented: 139, 145
- number bases: 4, 126, 130

O

- OOP: 58, 75, 84, 99, 102, 105, 115, 118, 123, 129, 135, 137, 138, 139, 145, 149, 167, 173
- operator.is_none: 162
- operator.is_not_none: 162
- operator.mul: 46
- operator (module): 46, 124, 162
- operators: 164
- overloads: 79

P

- pathlib.Path.copy_into: 151
- pathlib.Path.copy: 151
- pathlib.Path.expanduser: 64
- pathlib.Path.glob: 71
- pathlib.Path.is_file: 133
- pathlib.Path.isfile: 32
- pathlib.Path.iterdir: 32, 80, 133
- pathlib.Path.read_text: 61
- pathlib.Path.rename: 80
- pathlib.Path.resolve: 64

-
- `pathlib.Path.rglob`: 32
 - `pathlib.Path.stat`: 32
 - `pathlib.Path.write_text`: 61
 - `pathlib.Path`: 151
 - `pathlib.PurePath.with_stem`: 80
 - `pathlib`: 32, 61, 64, 71, 80, 133, 151
 - performance optimisation: 42, 47, 66, 85, 87, 119
 - positional arguments: 125
 - `pprint.pprint`: 101
 - `pprint`: 101
 - pretty printing: 101, 102
 - `print`: 44
 - productivity: 150
 - property: 123, 137
 - punctuation: 10, 127

R

- `random.choices`: 49
- `random.sample`: 49
- `random` (module): 49, 144
- `range`: 112
- `re.group`: 63
- `re.Match.groupdict`: 83
- `re.match`: 63, 83
- `re.sub`: 50
- `re`: 50, 52, 63, 69, 82, 83, 97, 110, 141
- readability: 27, 62, 82, 125, 126, 130, 158, 164
- `regex`: 50, 52, 63, 69, 82, 83, 97, 110, 141
- `regex flags`: 52, 69, 82, 83, 141
- `REPL`: 57, 150
- `repr`: 44
- `reversed`: 59
- `round`: 15

S

- `scoping`: 93
- `secrets.token_urlsafe`: 144
- `secrets` (module): 144
- security: 54, 144
- sequences: 59
- `set`: 7, 87
- `setattr`: 25
- `sets`: 7, 22, 87, 148
- slicing: 59, 73
- `sorted`: 89
- standard library: 8, 11, 12, 17, 18, 21, 23, 28, 29, 31, 32, 33, 36, 37, 38, 39, 41, 42, 43, 46, 47, 49, 50, 51, 52, 60, 61, 63, 64, 65, 66, 73, 74, 78, 82, 83, 85, 87, 90, 91, 92, 101, 104, 106, 110, 111, 112, 118, 120, 121, 122, 124, 127, 128, 131, 132, 134, 136, 140, 141, 142, 143, 146, 151, 152, 154, 155, 157, 160, 161, 162, 163,

-
- 166, 171, 174
 - StopIteration: 5, 30, 76
 - str.casefold: 2, 89
 - str.endswith: 13
 - str.isalpha: 131
 - str.partition: 48, 68
 - str.removeprefix: 13
 - str.removesuffix: 13
 - str.replace: 10, 127
 - str.rpartition: 68
 - str.split: 40, 68, 165
 - str.splitlines: 40
 - str.startswith: 13
 - str.title: 172
 - str.translate: 10, 127
 - strict (keyword argument): 1, 46, 107, 136
 - string formatting: 48, 62, 91, 94, 147, 156, 158
 - string formatting specification language: 48, 62, 147, 158
 - string.ascii_lowercase: 51
 - string.digits: 51
 - string.punctuation: 51
 - string (module): 10, 51, 127
 - strings: 2, 10, 13, 24, 31, 33, 40, 44, 48, 50, 51, 54, 56, 62, 68, 82, 83, 89, 94, 127, 131, 141, 147, 156, 158, 160, 165, 169, 172
 - structural pattern matching: 55, 72, 75, 77, 81
 - sum: 45, 46
 - syntax: 164

T

- t-strings: 54, 156
- tempfile.TemporaryDirectory: 92
- tempfile.TemporaryFile: 171
- tempfile: 92, 171
- text processing: 152, 169, 172
- truthy/falsy: 68, 100, 168
- tuples: 128
- type alias: 16
- type parameter syntax: 16, 84, 88, 109
- type unions: 3
- type variables: 84, 88
- types.MappingProxyType: 18
- types (module): 18
- typing.ClassVar: 135
- typing.final: 129
- typing.Final: 113
- typing.Iterable: 36
- typing.Literal: 29
- typing.overload: 79
- typing.overrides: 118
- typing.ParamSpec: 109

-
- typing/type hints: 3, 16, 29, 36, 79, 81, 84, 88, 103, 109, 111, 113, 118, 129, 135, 153
 - typing (module): 29, 36, 79, 109, 113, 118, 129, 135

U

- underscore `_`: 57, 62, 115, 130, 158, 167
- unexpected argument: 1, 15, 43, 76, 100, 107, 165
- Unicode: 33, 89
- `unicodedata.category`: 33
- `unicodedata.normalize`: 33
- `unicodedata` (module): 33
- uniqueness: 7
- unpacking: 35, 55, 138

V

- validation: 72, 81
- vertical bar `|`: 3, 14, 81

Z

- zip: 1, 34, 46, 117

-

- `__contains__`: 98
- `__doc__`: 95
- `__eq__`: 139
- `__file__`: 20
- `__getattr__`: 108
- `__hash__`: 96
- `__init__`: 58
- `__init_subclass__`: 26
- `__match_args__`: 75
- `__missing__`: 105
- `__name__`: 99, 139
- `__new__`: 58
- `__repr__`: 102, 139
- `__str__`: 102
- `_missing_`: 106

Conclusion

I hope you learned a thing or two by going through this book. If you have any feedback, [email me at rodrigo@mathspp.com](mailto:rodrigo@mathspp.com) or find me on social media:

- LinkedIn: <https://linkedin.com/in/rodrigo-girão-serrão>
- BlueSky: <https://bsky.app/profile/mathspp.com>
- YouTube: <https://www.youtube.com/@mathsppblog>
- X/Twitter: <https://x.com/mathsppblog>