ECE462 Multimedia Systems

Laboratory Assignment 1

Preparation Questions

Name: Mathura Shivakaran

Student Number: 1006879184

(Q1) 2 Marks

Write MATLAB code to create a 300×300 pure blue image (i.e. all pixels have the RGB values (0,0,255)) and draw a white cross (+) in the middle of the image, i.e. two perpendicular lines running the entire length of the image (300 pixels), each 2 pixels wide. You do not need to display the image. Your code shouldn't be more than four lines and you shouldn't use any loops. (Hint: look at the ":" operator explained in Section 6 of the reading material.)

% Creating blue image with white cross % Initializing a 300 x 300 matrix for RGB image imageBlue = zeros(300, 300, 3); imageBlue(:, :, 3) = 255; % Setting the B channel only to 255 throughout whole image imageBlue(:, 150:151, 1:3) = 255; imageBlue(150:151, :, 1:3) = 255; % Setting RGB channels all to 255 for two columns across all rows for white % Setting RGB channels all to 255 for two rows across all columns for white % Displaying the created image imageBlue = uint8(imageBlue); File Edit View Insert Tools Desktop Window Help image(imageBlue): axis image; 🖺 🗃 📓 🦫 🗒 📗 🔡 🖟 🗊 50 150 200 250

100

150


200

250

We start by initializing a 300x300 matrix full of zeroes. We then only set the third dimension (blue colour channel) to maximum intensity. This causes the colour channel to be (0, 0, 255), a pure blue image. In the third line, we are drawing the vertical white line in the middle (column pixels 150 and 151) across all rows. In the fourth line, we are drawing the horizontal white line to finish the cross in the middle (row pixels 150 and 151) across all columns. To draw the white lines, we use the ":" operator to manipulate all three dimensions, as white has a colour code of (255, 255, 255). This is completed in four lines. The rest of lines are for the purpose of displaying.

(**Q2**) 2 Marks


An image in the RGB color space is created and stored in the MATLAB variable A of type double. Using two lines of code, set the green intensity of A to zero and display the image.



We start by creating a random matrix A that displays a pastel purple image. In the first line of answer code, we set only dimension 2 to have all of its element equal to zero. This causes the second channel (green colour channel) to have an intensity of 0. In the second line of answer code, we convert the matrix into the uint8 data type for accuracy and display it in one line.

(Q3) 2 Marks

An image in the RGB color space is created and stored in the MATLAB variable A of type double. Using two lines of code, subtract from the blue component its mean (of the blue-component), and display the image.



We start by creating a random matrix A that displays a pastel purple image. In the first line of answer code, we use the "mean" operator in MATLAB which in our case, calculates the average of all the elements across dimension 3 (aka, the blue colour channel). We also use the keyword "all" to ensure it is applied to all elements in the dimension. We set the third channel (blue colour channel) to be equivalent to the CURRENT value of the blue channel subtract the average calculated. In the second line of answer code, we convert the matrix into the uint8 data type for accuracy and display it in one line.

(**Q4**) 2 Marks

Write the MATLAB code that draws a 1000×1000 image A like in Figure 3 and then displays then image. You should make an estimate of what the grey value should be.





Figure 3: Image with squares and rectangles



(Q5) 2 Marks You are given a vector S of size N. Split S into two vectors S1 and S2 such that S1 contains those elements of S that correspond to even indices i.e. S(2),S(4),S(6),... and S2 all the odd ones. You should do that without using any loops.

```
1
         % Vector S with N elements (Here, N = 6)
 2
         S = [11, 22, 33, 44, 55, 66];
 3
 4
         % To find the even indices, we save every second element of the original
 5
         % vector S into S1, starting from the SECOND vector element to the last
 6
         S1 = S(2:2:end);
                                 % Even Indices
 7
 8
         % To find the odd indices, we save every second element of the original
         % vector S into S2, starting from the FIRST vector element to the last
 9
         S2 = S(1:2:end);
                                 % Odd Indices
10
11
         % Printing the result
12
13
         disp(S1);
         disp(S2);
14
```

Command Window

New to MATLAB? See resources for Getting Started.

```
22 44 66
11 33 55
```

We first initialize a vector S and include some element values. To find the even indices, we use S1 = S(2:2:end). This essentially indirectly loops through the original vector S and saves every second element into S1. We start from the SECOND element and go till the last to ensure we are saving the even indices. To find the odd indices, we use S2 = S(1:2:end). This indirectly loops through S and saves every second element into S2. We start from the FIRST element and go till the last to ensure we are saving the odd indices. We then print S1 and S2 to the terminal.