Digital IO 2024-03-10

Digital Input & Output

114111C.	Name:	
----------	-------	--


Digital signals are either 0 or 1, the Arduino Uno has a total of 14 digital pins.

The first example demonstrates how to blink a LED.

The second example demonstrates how to read a button's state.

What You'll Need:

- 1 x Arduino Uno board
- 1 x Breadboard
- 1 x LED
- 1 x Button
- Jumper wires



This code would blink a LED on Pin 8

```
1 void setup() {
     // Configure Pin 8 as output pin
2
     pinMode(8, OUTPUT);
  }
4
5
6 void loop() {
7
     // Set LED on Pin 8 to ON
8
     digitalWrite(8, 1);
     delay(500);
9
10
     // Set LED on Pin 8 to OFF
11
12
     digitalWrite(8, 0);
     delay(500);
13
14 }
```

Challenge: Blink 3 LEDs one at a time. Imagine traffic lights running 2 seconds Green, 1 second Yellow, and 2 seconds Red.

Each LED must have a resistor.

Digital IO 2024-03-10

Read the Button State




Figure 1: Pin 4 Button Circuit

In this example, we print the value read on Pin 4 to the Serial Monitor

```
1 void setup() {
2
     // Configure Pin 4 as an Input for button
3
     pinMode(4, INPUT);
4
     // Configure Pin 8 as an Output for LED
     pinMode(8, OUTPUT);
6
7
   }
8
9
  void loop() {
10
     // If button is pressed
     if (digitalRead(4)) {
11
12
       // Turn on LED
       digitalWrite(8, 1);
13
14
     } else {
       // Turn on LED
15
       digitalWrite(8, 1);
16
17
18 }
```

Open the Serial Monitor with Ctrl + Shift + M

Digital IO 2024-03-10

Challenge: Make a counter with a button.

Each time the button is pressed, add 1 to the count.

Print the count in the serial monitor.

Hint; Create a count variable