

HB500 Battery Pack

5.12 kWh | 6,000+ Cycles



UL-Certified LiFePO₄ Cells

Safe, reliable performance with UL 1973 certification.



6,000+ Cycles Lifespan

Durable performance for long-term energy projects.



Scalable up to 327.68 kWh

Modular design supports expansion up to 64 units.



Broad Inverter Compatibility

Seamless integration with top inverter brands.



Flexible Mounting

Wall or floor installation to fit any space.

Specifications

No. of HB500 Units	HV6K	HV10K
1	6.2 kW 5.12 kWh	/
2	6.2 kW 10.24 kWh	10 kW 10.24 kWh
3	6.2 kW 15.36 kWh	10 kW 15.36 kWh
4		10 kW 20.48 kWh
Up to 64 Units	6.2 kW 327.68 kWh	10 kW 327.68 kWh

HB500	
Battery Type	LiFePO ₄
Rated Voltage	51.2 V
Rated Capacity	100 Ah
Rated Energy	5.12 kWh
Operating Voltage	44.8–57.6 V
Rated Charge Current	50 A
Rated Discharge Current	50 A
Max. Charge Current	80 A
Max. Discharge Current	100 A
Peak Discharge Current	150 A (2 min)
Cycle Life	6,000+ cycles
Depth of Discharge (DoD)	≥95%
Charging Temperature	0°C to 55°C
Discharging Temperature	-20°C to 55°C
Protection Rating	IP20
Dimensions (L × W × D)	402.6 × 158.7 × 708.5 mm
Weight	51 kg
Max. Parallel Units	Up to 64 units, total 327.68 kWh
App Connectivity	Bluetooth
Communication Interface	CAN/RS485
Data Storage	Optional hard drive, stores up to 5 years of operational records
Compliance & Certifications	UN38.3, CE-EMC, UL (battery cells)
Warranty	3 years