

HV6K & HV10K Off-Grid Inverter



HV6K
6.2 kW | Single Phase

HV10K
10 kW | Single Phase



Pure Sine Wave Power
Handle sensitive, high-demand devices with ease.



Strong Surge Power
200% surge capacity to run all home appliances.



Dust-Resistant Design
Removable, washable dust filter for easy maintenance.



High Solar Compatibility
1.4× PV input ratio with a wide 90–450 V input range.



Enhanced Safety
CE-certified and 6 layers of protection for peace of mind.



Smart & Flexible System
Control and monitor via app or LCD screen, compatible with lithium and lead-acid batteries.

Specifications

PV Input	HV6K	HV10K
Max. PV Array Power	6,500 W	14,000W
Nominal PV Voltage	320 Vdc	
Nominal MPPT Voltage Range	90 – 450 Vdc	
Max. PV Input Voltage	500 Vdc	
Max. Input Current	18 A	22 A*2
Battery Input		
Nominal Battery Voltage	51.2 V	
Max. Charging/Discharging Current	118 A	230 A
Charging Strategy for Li-ion Battery	Self-adaption to BMS	
AC Input		
Nominal Input Voltage	230 Vac±5%	
Frequency	50 Hz/60 Hz	
Input Current	27 A	43.5 A
Surge Current	54 A, 5s	87 A, 5s
AC output		
Rated Output Power	6,200 W	10,000 W
Surge Power	12,400 VA, 5s	20,000 VA, 5s
Output Voltage Regulation	230 Vac±5%	
Output Frequency	50 Hz / 60 Hz	
General		
Waveform	Pure sine wave	
Phase	Single-phase	
Grid Connection	Off-grid	
Switchover Time to Backup Power	≤10 ms	
Protection Rating	IP21	
Max. Efficiency (DC-AC)	>95%	
Operating Temperature	10°C to 50°C	
Humidity	5% to 95%	
Dimensions (W × D × H)	300 × 115 × 435 mm	322 × 141 × 497 mm
Net Weight	10.4 kg	16.3 kg
Connectivity	RS232/RS485	
Compliance & Certifications	IEC 61683, EN 55032, EN 55035, IEC 62109	
Warranty	2 Years	