THESIS RECAP

OCTOBER 2026

Introduction

Setting

Given a sample space Ω, let inputs and labels be generated by $X : \Omega \to \mathcal{X} = \{\bar{x}_1, \dots, \bar{x}_N\}$ and $Y : \Omega \to \mathcal{Y} = \{-1, 1\}$. Let p be a probability distribution on $\mathcal{X} \times \mathcal{Y}$, with

$$p_{j,y} = \Pr[X = \bar{x}_j, Y = y], \qquad p_{j,y} \geq 0, \qquad \sum_{j=1}^{N} \sum_{y \in \mathcal{Y}} p_{j,y} = 1.$$

Let $D = (X_i, Y_i)_{i=1}^n$ be a dataset of n indipendent copies of (X, Y) with common distribution p. We indicate the realizations of D with lower-case x and y. Let $\mathcal{H} \subseteq \{h : \mathcal{X} \to \mathcal{Y}\}$ be a nonempty, finite set of classifiers. Given a loss function $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}^+$, define the population and empirical risks by

$$R(h) = \mathbb{E}_D(\ell(h(X), Y)) = \sum_{\bar{x} \in \mathcal{X}} \sum_{\bar{y} \in \{-1,1\}} \ell(h(\bar{x}), \bar{y}) p(\bar{x}, \bar{y}).$$

and

$$\hat{R}_D(h) = \frac{1}{n} \sum_{i=1}^{n} \ell(h(X_i), Y_i).$$

We select the classifier that minimizes the empirical risk (ERM), i.e.

$$\hat{h}_D \in \arg\min_{h \in \mathcal{H}} \hat{R}_D(h)$$

which, importantly, is a random variable of the data D. Notice that at least one such $\hat{h}_D$ exists, since $\mathcal{H}$ is finite and nonempty.

Specifically, in this thesis

- ℓ is the counting loss $\ell(h(x), y) = \mathbf{1}(h(x) \neq y) = \frac{1 - h(x)y}{2}$;
- classifiers $h : \mathcal{X} \to \mathcal{Y}$ are binary decision trees;
- given a depth d, $\mathcal{H}_d$ is the set of binary decision trees of depth at most d, and we consider a number of such depths.

Research question

In machine learning, there exists a large number of algorithms, notably neural networks trained with gradient descent, which achieve great performances at prediction tasks on unseen data. A big question in learning theory is to understand the relationship between the behavior of such algorithms on the available data and their future behavior on unseen data (generalization). How can we predict how this future behavior will look like?

A number of results have tried to answer this question. Recent works seem to suggest that the classical theory fails to explain generalization, in particular they fail to describe the behavior of the test error of learning algorithms as the comlpexity of the hypotheses set increases. This thesis seeks to understand whether this is true by testing theoretical results against empirical evidences. We study the setting of a finite hypotheses set of binary decision trees. We look for a function that reproduces qualitatively the test error as the maximum depth of the decision trees (i.e. the complexity of the hypotheses space) increases. The contribution of identifying and empirically validating such a function is two-fold. On the one hand, it explains the shape of the test error curve of decision trees; on the other hand, it may allow to implement the same framework and techniques to study the generalization performance of more complex algorithms, like neural networks trained with gradient descent.

In particular, we study bounds on the expcted gap between the test and train error of the ERM,

$$\mathbb{E}_D\left[(R - \hat{R}_D)(\hat{h}_D)\right].$$

Notice that since $\hat{h}_D$ and $\hat{R}_D$ depend on the same dataset D, $\mathbb{E}_D[\hat{R}_D(\hat{h}_D)] \neq R(\hat{h}_D)$, i.e. the empirical risk is a biased estimate of the true risk. A proof of this fact is found in Appendix B.

We look for a bound that reproduces the shape of the empirical test error curve qualitatively. In particular, we want this function to have the same asymptotic behavior as $\mathbb{E}_D[R(\hat{h}_D)]$, as well as to be sensitive to changes in the structure of the learning problem which affect the test error curve.

All proofs are in Appendix B.

1. Union bound over $\mathcal{H}$

In this section, we study the first bound on the quantity $\mathbb{E}_D[(R - \hat{R}_D)(\hat{h}_D)]$, to which we refer as the *gap* for the rest of this work, without specifying that it is computed at $\hat{h}_D$ everytime. This result is obtained starting from a concentration result (Hoeffding's inequality, see Theorem **??** in the Appendix) on the random variable $\hat{R}_D(h)$ for a fixed function $h \in \mathcal{H}$. This is extended to a result on $\hat{h}_D$, which depends on the data D, by taking a union bound (see Proposition **??** in the Appendix) on the probability that the event holds for any function $h \in \mathcal{H}$.

Theorem 1.1.

$$\mathbb{E}_D[R(\hat{h}_D) - \hat{R}_D(\hat{h}_D)] \;\leq\; O\left(\sqrt{\frac{\log|\mathcal{H}|}{n}}\right) \tag{1}$$

Experimental design. The preliminary experiments are discussed in detail and plots are provided in Appendix A.

We create the support $\mathcal{X}$ as a discretization over $N = 10,000$ numbers of the interval $[0, 10]$. We sample from it with the uniform measure $p_{\mathcal{X}}(\bar{x}) = \sum_{\bar{y}\in\mathcal{Y}} p(\bar{x}, \bar{y}) = \frac{1}{N}$. The law to generate the labels is

$$y \leftarrow \text{sign}(h^*(x) + \sigma\varepsilon)$$

where $h^* : \mathcal{X} \to \mathcal{Y}$, is the data-generating function, $\varepsilon \sim \mathcal{N}(0, 1)$, is a Gaussian noise, and $\sigma > 0$. First, we generate the labels with a centered parabola, so that roughly half of them are 1 and half -1 in the interval

$[0, 10]$. Since an algorithm could learn such a function with few datapoints (see Section A.2), we switch to a sinusoid with varying frequency,

$$h^*(x) = 5 \sin\left(\frac{\pi\,(m+1)}{10}\,x\right)$$

where m is the number of times h^* crosses the x-axis in the open interval $(0, 10)$, yielding $m+1$ contiguous blocks of $1s$ and $-1s$. We set as default value $m = 10$.

We test a Bernoullian noise instead of a Gaussian one, concluding that there is no interesting difference in the performance of the algorithm as long as the portion of misclassified inputs due to the noise is the same. We find that for $m = 10$, $\sigma = 3.5$ achieves a noise of 20%, corresponding to $p = 0.8$. For now, we stick to a gaussian noise.

In the end, our labels are generated as

$$y \leftarrow \text{sign}\left(5 \sin\left(\frac{\pi\,(m+1)}{10}\,x\right) + \sigma\varepsilon\right)$$

with $\sigma = 3.5$ and $m = 10$. Notice that our $\text{sign}(\cdot)$ maps 0 to 1.

We proceed as follows. We generate a test set with size $n_{\text{test}} = 200,000$ sampling from $\mathcal{X}$ with $p_{\mathcal{X}}$ and generating the labels as above. Then, for each depth $d \in [1, 7\lceil\log_2 n\rceil] \subset \mathbb{N}$ we do the following. For a number $T = 100$ of iterations, we

- generate a train set ($n = 50$);
- fit a decision tree with depth at most d (DecisionTreeClassifier algorithm from the scikit-learn library);
- compute the train error, the test error, and the differene between the two (the gap).

Then, we average the resulting quantities over the T samples, obtaining empirical estimates of the expected values of the train error, test error, and gap over the disorder of the data.

To plot the theoretical bound, instead, we need to express $|\mathcal{H}_d|$ as a function of d. The exact computation gives

$$|\mathcal{H}_d| = 2 \sum_{k=0}^{\min N-1, 2^d-1} \binom{N-1}{k}$$

Disclaimer: the plots below have been obtained with $|\mathcal{H}_d| \leq 2^d$ which is incorrect, I need to fix it. I tried the formula above or something like $\min(2^N, N^{2^d} 2^{2^d})$ but dependence on d is awful.

As the maximum depth d increases, we plot the following:

(1) the train and the test error curves;

(2) the gap and the theoretical bound $\sqrt{\log|\mathcal{H}|/n}$;

(3) the test error and the sum of train error and the bound (moving $\hat{R}_D(\hat{h}_D)$ to the right).

We plot the bound (1) to compare it with the empirical behavior of the test error in Figure 1. The first thing catching the eye is that the bound diverges, while the test error saturates. This divergence is due to the dependence of the bound on $|\mathcal{H}_d|$, that is the number of binary trees with maximum depth d, which clearly increases with d. It follows immediately that a complexity measure of the hypotheses set that naively counts the functions it contains does not satisfy our requirements to find a qualitatively informative bound.




FIGURE 1. $n = 50, N = 10,000, n_{\text{test}} = 200,000, \sigma = 5$, h^* = sine with 10 sign changes

The test error of binary decision trees saturates because of a specific characteristic of the algorithm. As soon as the learned tree has only "pure" leaves, i.e. leaves containing inputs that have the same unique label in the training set, the algortihm ceases to split them and hence any additional allowed depth does not change the learned model. Clearly, the cardinality of the hypotheses sets $\mathcal{H}_d, d > 0$ does capture this property. Instead, a counting way that accounts for the finiteness of our problem might reproduce the saturation of the test error curve. Specifically, the configuration with only pure leaves can be achieved for two reasons: either all the possible values that the inputs can take are classified, or all the inputs in the sample are classified. Since, in our case, $n \ll N$, the second event happens much earlier than the first one. As a consequence, a complexity measure that counts the number of distinct classifications that the functions in $\mathcal{H}$ can give, i.e. the vectors $h(x_1), \ldots, h(x_n) : h \in \mathcal{H}$, instead of the functions themselves, could more faithfully represent the true complexity of the space of models that the algorithm can learn in practice.

2. Rademacher Complexity and Massart Lemma

In this section, we introduce a theoretical tool, the Rademacher complexity, which allows to leverage the viewpoint exposed in the last section and obtain a saturating bound on the gap.

Definition 2.1 (Rademacher complexity)**.** *Let $\xi_1, \dots, \xi_n$ be Rademacher variables taking value 1 or -1 with equal probability. The Rademacher complexity of the set $\mathcal{L} = \{\ell \circ h : h \in \mathcal{H}\}$ is*

$$\mathcal{R}_n(\mathcal{L}) = \mathbb{E}_{\xi,D}\left[\sup_{\ell_h \in \mathcal{L}} \frac{1}{n} \sum_{i=1}^{n} \xi_i \ell(h(X_i), Y_i)\right]$$

The Rademacher complexity measures the richness of a class of functions. The argument of the supremum $\frac{1}{n}\sum_i \xi_i \ell_h(x_i, y_i) = \langle \xi, \ell_h(x, y)\rangle$ is the correlation between ξ and $\ell_h(x, y)$.

Theorem 2.2 (Rademacher complexity bound)**.**

$$\mathbb{E}_D[(R - \hat{R})(\hat{h})] \leq 2\mathcal{R}_n(\mathcal{L})$$

Lemma 2.3 (Massart)**.**

$$\mathcal{R}_n(\mathcal{L}) \leq \mathbb{E}_D\left[\sqrt{\frac{2\log N_D(\mathcal{H})}{n}}\right]$$

where $N_D(\mathcal{H}) = |\{(\ell_h(X_1, Y_1), \dots, \ell_h(X_n, Y_n)) : h \in \mathcal{H}\}|$.

Lemma 2.4 (Counting inequalities)**.**

$$N_D(\mathcal{H}) \leq \min\{|\mathcal{H}|, 2^n\}.$$

Putting together this results, we obtain the final bound.

Theorem 2.5 (Rademacher and Massart bound)**.**

$$\begin{aligned}
\mathbb{E}_D[(R - \hat{R})(\hat{h}_d)] &\leq 2\mathbb{E}_D\left[\sqrt{\frac{2\log N_D(\mathcal{H})}{n}}\right] \\
&\leq 2\sqrt{\frac{2\min\{\log|\mathcal{H}_d|, \log 2^n\}}{n}} \\
&\leq \min\left\{O\left(\sqrt{\frac{\log|\mathcal{H}_d|}{n}}\right), O(1)\right\} \qquad (2)
\end{aligned}$$

We plot the bound (2), with as constant term 0.5, in Figures 2 and 3. The experimental design is the same as before.

Observations:

- ▷ the bound saturates,
- ▷ the bound does not change for different noise levels.

On one hand, bound (2) saturates mirroring the behavior of the test error curve. On the other hand, the bound and the saturating level are not sensitive to changes in the noise level, as Figure 3 shows. Indeed, the bound saturates because of Lemma 2.4, which bounds the number of loss vectors $N(D)$ with the minimum between the number of classifiers in $\mathcal{H}$, increasing in d, and 2^n, a constant. Hence, at some point the curve does not increase with depth d anymore. This reflects the fact that the Rademacher complexity is naturally bounded by 0.5 in our setting. At the same time, the Rademacher complexity is blind to the structure of our problem, specifically to the level of noise.




FIGURE 2. Identical parameters as Fig.1




FIGURE 3. Different noise levels

In the next section we implement a different theoretical viewpoint to look for a bound that better captures the structure of the learning problem.

3. Dependence on the Best Risk

Set

$$R^*_{\mathcal{H}} = \min_{h \in \mathcal{H}} R(h).$$

We aim at obtaining a bound on the gap at $\hat{h}_D$ in terms of the best risk $R^*_{\mathcal{H}}$. This is because the best risk can be decomposed as

$$R^*_{\mathcal{H}} = \underbrace{R^*}_{\text{Bayes risk}} + \underbrace{R^*_{\mathcal{H}} - R^*}_{\text{Approximation error}} =: \sigma^2 + A_{\mathcal{H}}$$

where

- $\sigma^2 = R^* := \inf_{h: \mathcal{X} \to \mathcal{Y}}$ measures the irreducible classification error due to noise, that we make no matter the hypotheses set we choose;
- $A_{\mathcal{H}}$ measures the excess error we make given that we consider a restricted set of classifiers, $\mathcal{H}$.

So, we hope to obtain a noise and structure-sensitive bound.

Theorem 3.1 (Bound with empirical risk)**.** *With probability at least* $1-\delta$*,*

$$R(\hat{h}) - \hat{R}(\hat{h}) \leq \sqrt{\frac{\hat{R}(\hat{h})\log(2N_{2n}(\mathcal{H})/\delta)}{n}} + 16\frac{\log(2N_{2n}(\mathcal{H})/\delta)}{n}$$

where $N_n(\mathcal{H}) := \sup_{(x_1,y_1),\ldots,(x_n,y_n)\in\mathcal{X}\times\mathcal{Y}} N_D(\mathcal{H})$*.*

Corollary 3.2 (Bound with best risk)**.** *With probability at least* $1-\delta$*,*

$$R(\hat{h}) - \hat{R}(\hat{h}) \leq \sqrt{\frac{R^*_{\mathcal{H}}\log(4N_{2n}(\mathcal{H})/\delta)}{n}} + 20\frac{\log(4N_{2n}(\mathcal{H})/\delta)}{n}$$

Corollary 3.3 (Noise and approximation error bound (high probability))**.** *With probability* $1-\delta$*,*

$$R(\hat{h}) - \hat{R}(\hat{h}) \leq \sqrt{\frac{(A_{\mathcal{H}}+\sigma^2)\log(4N_{2n}(\mathcal{H})/\delta)}{n}} + 20\frac{\log(4N_{2n}(\mathcal{H})/\delta)}{n}$$

Theorem 3.4 (Noise and approximation error bound)**.**

$$\mathbb{E}_D\left[R(\hat{h}) - \hat{R}(\hat{h})\right] \leq \min\left\{O\left(\sqrt{\frac{(A_{\mathcal{H}}+\sigma^2)\log|\mathcal{H}|}{n}} + \frac{\log|\mathcal{H}|}{n}\right), O\left(\sqrt{A_{\mathcal{H}}+\sigma^2}+1\right)\right\} \tag{3}$$

We plot bound (3) in Figure 4 and Figure 5.

Figure 6 shows the two terms of the minimum in the bound separately. The Bayes risk, the minimum risk over $\mathcal{H}$ and the approximation error (their difference) for different noise levels are shown in Figure 7.

Experimental design: The fundamental design is the same as before. The Bayes risk R^* is

$$R^* = 1 - p$$

for $p \geq 0.5$, and as before we sue $p \in \{0.6, 0.8, 0.95\}$. $R^*_{\mathcal{H}}$ is computed exactly using dynamic programming. We produce labels using our sine function and the Bernoulli error and we cluster the intervals where labels have the same sign, obtaining M contiguous blocks. We create a dp $k \times 2$ matrix that stores the minimum risk for each number of maximum splits k, up to $\min(M-1, 2^d)$ where d is the maximum depth we are considering, when the last assigned label is 1 or -1 (the columns). Then, for each contiguous block we dynamically update the dp matrix summing the minimum risk among all trees with at most k splits. In the end, we select the minimum risk among the tree predicting 1 or -1 in the very last block.

Disclaimer: For the second term in the min, we plot $\sqrt{A_{\mathcal{H}}+\sigma^2}$ directly without the $+1$, although I am not sure this is motivated, since $R^*_{\mathcal{H}} < 1$ as shown in Figure 7.

4. Growth function

Definition 4.1 (Growth function)**.** *The growth function of* $\mathcal{H}$ *is*

$$\Pi_n(\mathcal{H}) := \sup_{x_1,\ldots,x_n\in\mathcal{X}} \left|\{(h(x_1),\ldots,h(x_n)) : h \in \mathcal{H}\}\right|.$$

The following extends Lemma 2.4.

Lemma 4.2 (Counting inequalities with growth function)**.** *For every sample* D *of size* n*,*

$$1 \leq N_D(\mathcal{H}) \leq \Pi_n(\mathcal{H}) \leq \min\{|\mathcal{H}|, 2^n\}.$$




FIGURE 4. Same setting, with Bernoullian noise at 20%




FIGURE 5. Different noise levels

Moreover,

$$\Pi_n(\mathcal{H}) = N_n(\mathcal{H}) = \sup_{(x_1,y_1),\dots,(x_n,y_n)\in\mathcal{X}\times\mathcal{Y}} N_D(\mathcal{H})$$

The relation between N_D and Π_n makes it immediate to obtain growth-function versions of the bounds in Sections 2 and 3 (substitute $N(D) \le \Pi_n$ into Lemma 2.3 and $N_{2n} = \Pi_{2n}$ into Theorem 3.1). Substituting also $\Pi_n(\mathcal{H}) \le \min\{|\mathcal{H}|, 2^n\}$ yields bounds (2) and (3).

5. Going on

The growth function has the additional result that

$$\log \Pi_{\mathcal{H}}(2n) \le d \log \frac{2en}{d}$$

we need to understand if this is useful. Plus, we mentioned the localized Rademacher sometime this summer.

I still need to fix the matter of how to count $|\mathcal{H}|$ in terms of the depth d (the "disclaimer" in Section 1). Setting the constant term at 0.5 in bound (2) is heuristical because I know it works. Needs motivation. Similarly, the disclaimer after bound (3): I say $O(\sqrt{A_{\mathcal{H}} + \sigma^2} + 1) = O(\sqrt{A_{\mathcal{H}} + \sigma^2})$ and plot only $\sqrt{A_{\mathcal{H}} + \sigma^2}$ but it's heuristical as well, and since $A_{\mathcal{H}} + \sigma^2 \le 1$ probably wrong (however, con il +1 non fa nemmeno in tempo a saturare perché l'altro termine che dipende da d rimane più piccolo).




FIGURE 6. The two terms of the minimum in the noise and approx. error bound




FIGURE 7. Approximation error and Bayes risk

Appendix A. Preliminary experiments

A.1. **Noise structure.** We generate the labels with a centered parabola (see Section A.2), so that roughly half of them are 1 and half -1 in the interval $[0, 10]$. Then, we inspect what happens if we use a Bernoullian noise instead of a Gaussian one, i.e. when data is generated as

$$y \leftarrow sign(h^*(x))b$$

for $b \sim \text{Bernoulli}(p)$. Notice that this noise flips the labels with a probability of $1 - p$. While from the first experiments it seemed that the algorithm achieved a higher test error, we postulate that this may be due to the portion of misclassified inputs, rather than to the noise structure itself. Hence, fixing $p = 0.8$, we look for the value of σ that achieves roughly the same portion of mislcassified inputs (20%). Figure 8 shows that this happens for $\sigma = 5.5$, and Figures 9 and 10 show that the two noise structures then yield essentially the same train and test errors.




Figure 8. Average fraction of misclassified inputs against σ, over 100 samples of size $n = 50$, h^* = centered parabola




Figure 9. $n = 50, N = 10,000, n_{\text{test}} = 200,000$, Bernoulli noise with $p = 0.8$




Figure 10. $n = 50, N = 10,000, n_{\text{test}} = 200,000$, Gaussian noise with $\sigma = 5.5$

A.2. **Data-generating function.** Our first choice of h^* is a parabola centered horizontally at 5, the midpoint of the support $\mathcal{X}$, and vertically so that roughly half of the points fall above the x-axis and half below. I.e.,

$$h^*(x) = (x - 5)^2 - 6.25$$




FIGURE 11. A sample of size $n = 50$ generated with the centered parabola, for $\sigma \in \{10^{-4}, 1, 5.5, 10\}$

Figure 11 shows the data generated with the centered parabola, for different amounts of noise.

Because in theory an algorithm could learn such a classification pattern as soon as it sees 3 points (one point for each region), we investigate what happens when the underlying function is more complex. We study a sinusoid with varying frequency,

$$h^*(x) = 5 \sin\left(\frac{\pi\,(m+1)}{10}\,x\right)$$

We multiply the sine by 5 to allow for enough height to properly inspect the data, while the argument of the sine is such that m is the number of times h^* crosses the x-axis in the open interval $(0, 10)$, yielding $m + 1$ contiguous blocks of $1s$ and $-1s$.




FIGURE 12. $m = 10$




FIGURE 13. $m = 100$




FIGURE 14. $m = 1000$

We explore how a random sample and the performance of the algorithm change for different sine frequencies. In particular, we expect that for a high frequency the algorithm will not learn, as our datasize is $n = 50$. In Figures 12–14, we test a function that osciallets $10, 100$, and 1000 times with a noise level of $\sigma = 3$ (we reduce it compared to $\sigma = 5$, having increased the complexity of the function). We notice that for $m = 1000$ the algorithm fails to learn, and the test error stays stable at 0.5. This is because the labels change so frequently




FIGURE 15. $n = 50, N = 10,000, n_{\text{test}} = 200,000$, $\sigma = 3$, train and test error for different ratios $r = m/n$

with respect to the number of points in the training dataset n that it is as if we had random labels. Hence, we investigate the relation between the complexity of the underlying function m and the data size n. We find that for $\frac{m}{n} > 5$, roughly, the algorithm ceases to learn (Figure 15). In the following experiments, we fix $m = 10$ and $n = 50$, which is very far from the threshold.

We then verify whether a Gaussian noise with $\sigma = 5.5$ achieves the same portion of misclassified inputs on average as a Bernoullian noise with $p = 0.8$, as was the case for data generated with a parabola. Figure 16 shows that this is not the case on average (29% against 20%), while Figure 17 shows that the desired value is $\sigma = 3.5$.




FIGURE 16. Fraction of misclassified inputs over 100 samples of size $n = 50$, $h^* =$ sine with $m = 10$; dashed lines are the averages




FIGURE 17. Average fraction of misclassified inputs against σ, over 100 samples of size $n = 50$, $h^* =$ sine with $m = 10$

Finally, we investigate the afore-mentioned intuition about how easy it is for the algorithm to learn a simple function. We find that for $m = 2$ (which corresponds to a parabola, in terms of classification pattern) and sampling uniformly from $\mathcal{X}$, with $\sigma = 3.5$, $n = 1000$ training points are enough on average for the test error to get within 0.01 of the Bayes risk (≈ 0.20), both at depth 2 and 3 (Figure 18). Hence, although two splits are enough to represent the function, with this amount of noise the algorithm needs many points to place them correctly.

APPENDIX B. PROOFS

Proof of Theorem 1.1. Apply Hoeffding Lemma and a union bound over the hypotheses set $\mathcal{H}$. Tail integrate to obtain a result in expected value. □

Proof of Theorem 2.2. Symmetrization technique. □




FIGURE 18. $N = 10,000, n_{\text{test}} = 200,000, \sigma = 3.5$, $h^* =$ sine with $m = 2$: test error at depth 2 and 3 against n, averaged over 100 samples

Proof of Lemma 2.3. Pass to the supremum over *loss vectors* instead of functions $\ell \circ h$, and bound it with the sum, which makes the $N(D)$ term appear. Then, apply the exponential Hoeffding Lemma and optimize for the coefficient in the exponent. □

Proof of Lemma 2.4. Given a dataset, its realizations through ℓ_h are less than or equal to those through h because applying ℓ cannot increase the number of outputs, and the number of images of the functions in $\mathcal{H}$ are less than or equal to the number of functions $|\mathcal{H}|$. On the other hand, $N_D(\mathcal{H}) \leq 2^n$ because we have at most 2^n n-long sequences of $0s$ and $1s$. □

Proof of Theorem 2.5. Apply Theorem 2.2, Lemma 2.3 and Lemma 2.4. □

Proof of Theorem 3.1. Apply the relative deviation inequality (see Loz's file),

$$\Pr\left[\exists h \in \mathcal{H} : R(h) - \hat{R}(h) > \varepsilon\sqrt{R(h)}\right] \leq 2N_{2n}(\mathcal{H})e^{-2\varepsilon^2/16}$$

with the suitable ε and then isolate $\hat{R}(\hat{h})$ on the RHS. □

Proof of Corollary 3.2. Set $h_0 = \arg\min_{h\in\mathcal{H}} R(h)$, so that $R(h_0) = R^*_{\mathcal{H}}$. Then,

$$\hat{R}(\hat{h}) \leq \hat{R}(h_0). \tag{4}$$

Since h_0 is independent of the data, $\mathbb{E}_D[\hat{R}(h_0)] = R(h_0)$ and hence Bernstein gives, with probability at least $1 - \delta/2$,

$$\hat{R}(h_0) \leq R^*_{\mathcal{H}} + \sqrt{\frac{2R *_{\mathcal{H}} \log(2/\delta)}{n}} + \frac{\log(2/\delta)}{3n}.$$

Since $N_{2n}(\mathcal{H}) \geq 1$ and thus $\frac{\log(2/\delta)}{n} \leq \frac{\log(4N_{2n}(\mathcal{H})/\delta)}{n}$,

$$\hat{R}(h_0) \leq \left(\sqrt{R^*_{\mathcal{H}}} + \sqrt{\frac{4\log(N_{2n}(\mathcal{H})/\delta)}{n}}\right)^2 \tag{5}$$

Substitute (4) into (5), and apply the bound to $\hat{R}(\hat{h})$ in the RHS of Theorem 3.1 at confidence $1-\delta/2$. This yields the desired bound, which holds with probability at least $1-\delta$ by a union bound on the events ((5) and Theorem 3.1) that we require to hold simultaneously. □

Proof of Corollary 3.3. Substitute $R^*_{\mathcal{H}} = \sigma^2 + A_{\mathcal{H}}$ into Corollary 3.2. □

Proof of Theorem 3.4. Let $\text{gap} = (R - \hat{R}(\hat{h}))$ and $C = \sqrt{\frac{\log(4N_n(\mathcal{H})/\delta)}{n}}$. Corollary **??** gives

$$\Pr\left[\text{gap} \le \sqrt{R^*_{\mathcal{H}}}\, C + 20C^2\right] \ge 1-\delta$$
$$\implies \Pr\left[\text{gap} > \sqrt{R^*_{\mathcal{H}}}\, C + 20C^2\right] \le \delta$$

Set $\varepsilon = \sqrt{R^*_{\mathcal{H}}}\, C + 20C^2$. Let us now find $\delta(\varepsilon)$:

$$20C^2 + \sqrt{R^*_{\mathcal{H}}}\, C - \varepsilon = 0 \implies C = \frac{-\sqrt{R^*_{\mathcal{H}}} + \sqrt{R^*_{\mathcal{H}} + 80\varepsilon}}{40}$$

So we have

$$\frac{\log(4N_{2n}(\mathcal{H})/\delta)}{n} = \left(\frac{\sqrt{R^*_{\mathcal{H}} + 80\varepsilon} - \sqrt{R^*_{\mathcal{H}}}}{40}\right)^2$$
$$\frac{4N_{2n}(\mathcal{H})}{\delta} = \exp\left(n\left(\frac{\sqrt{R^*_{\mathcal{H}} + 80\varepsilon} - \sqrt{R^*_{\mathcal{H}}}}{40}\right)^2\right)$$

and hence

$$\delta(\varepsilon) = 4N_{2n}(\mathcal{H}) \exp\left(-\frac{n}{1600}\left(\sqrt{R^*_{\mathcal{H}} + 80\varepsilon} - \sqrt{R^*_{\mathcal{H}}}\right)^2\right).$$

Using that $\mathbb{E}[X] = \int_0^\infty \Pr[X \ge \varepsilon]\, d\varepsilon$ for $X \ge 0$, applied to $\text{gap}^+ \coloneqq \max\{\text{gap}, 0\}$,

$$\mathbb{E}_D[\text{gap}] \le \mathbb{E}_D[\text{gap}^+] = \int_0^\infty \Pr[\text{gap} \ge \varepsilon]\, d\varepsilon \le \int_0^\infty \min\{1, \delta(\varepsilon)\}\, d\varepsilon.$$

By a shift of perspective, looking at the integral as a sum of horizontal stripes instead of vertical stripes in the graph of $\varepsilon \mapsto \delta(\varepsilon)$, we obtain

$$\int_0^\infty \min\{1, \delta(\varepsilon)\}\, d\varepsilon = \int_0^1 \delta^{-1}(t)\, dt = \int_0^1 \varepsilon(\delta)\, d\delta$$

Hence, writing $\varepsilon(\delta) = \sqrt{R^*_{\mathcal{H}}}\, C + 20C^2$ explicitly,

$$\mathbb{E}_D[\text{gap}] \le \int_0^1 \varepsilon(\delta)\, d\delta = \sqrt{\frac{R^*_{\mathcal{H}}}{n}} \int_0^1 \sqrt{\log\frac{4N_{2n}(\mathcal{H})}{\delta}}\, d\delta + \frac{20}{n}\int_0^1 \log\frac{4N_{2n}(\mathcal{H})}{\delta}\, d\delta.$$

The logarithm is the only part depending on δ, and its integral is

$$\int_0^1 \log\frac{4N_{2n}(\mathcal{H})}{\delta}\, d\delta = \log(4N_{2n}(\mathcal{H})) - \int_0^1 \log\delta\, d\delta = \log(4N_{2n}(\mathcal{H})) + 1.$$

Applying Jensen's inequality to the square root term,

$$\int_0^1 \sqrt{\log\frac{4N_{2n}(\mathcal{H})}{\delta}}\, d\delta \le \sqrt{\int_0^1 \log\frac{4N_{2n}(\mathcal{H})}{\delta}\, d\delta} = \sqrt{\log(4N_{2n}(\mathcal{H})) + 1},$$

we obtain

$$\mathbb{E}_D[\text{gap}] \le \sqrt{\frac{R^*_{\mathcal{H}}\left(\log(4N_{2n}(\mathcal{H})) + 1\right)}{n}} + 20\,\frac{\log(4N_{2n}(\mathcal{H})) + 1}{n}.$$

Asymptotically,

$$\mathbb{E}_D\left[R(\hat{h}) - \hat{R}(\hat{h})\right] \leq O\left(\sqrt{\frac{(A_{\mathcal{H}} + \sigma^2)\ \log N_{2n}(\mathcal{H})}{n}} + \frac{\log N_{2n}(\mathcal{H})}{n}\right)$$

because, at the numerator,

$$\log(4N_{2n}(\mathcal{H})) + 1 = \log 4 + \log N_{2n}(\mathcal{H}) + 1 = \log N_{2n}(\mathcal{H}) + O(1)$$

and for large x,

$$\log x + O(1) \leq C \log x$$

for some constant $C > 0$. Plugging in the counting inequality from Lemma 2.4 with $2n$, we obtain and plot the following bound

$$\mathbb{E}_D\left[R(\hat{h}) - \hat{R}(\hat{h})\right] \leq \min\left\{O\left(\sqrt{\frac{(A_{\mathcal{H}} + \sigma^2)\log|\mathcal{H}|}{n}} + \frac{\log|\mathcal{H}|}{n}\right), O\left(\sqrt{A_{\mathcal{H}} + \sigma^2} + 1\right)\right\}$$

Remark: recall that $N_{2n}(\mathcal{H})$ is the maximum number of loss vectors over the union of two datasets D, D', or equivalently over a dataset with size $2n$. The counting lemma must be applied to $2n$-long loss vectors. Hence, we still have $N_{2n}(\mathcal{H}) \leq |\mathcal{H}|$ because the number of functions is still the same, and the bound counting all the possible sequences becomes $N_{2n}(\mathcal{H}) \leq 2^{2n}$.

□

Proof of Lemma 4.2. $N_D(\mathcal{H}) \leq \Pi_n(\mathcal{H})$ because the number of distinct loss vector can at most decrease, given prediction vectors. $\Pi_n(\mathcal{H}) \leq |\mathcal{H}|$ because the realizations of functions in h are at most as much as the functions in h (equality when functions in h are bijective). $\Pi_n(\mathcal{H}) \leq 2^n$ because we have at most 2^n sequences of n 1s and -1s. □