Black-Box Optimization Benchmarking Template for Noiseless Function Testbed

Draft version ³

Forename Name

ABSTRACT

to be written

Categories and Subject Descriptors

G.1.6 [Numerical Analysis]: Optimization—global optimization, unconstrained optimization; F.2.1 [Analysis of Algorithms and Problem Complexity]: Numerical Algorithms and Problems

General Terms

Algorithms

Keywords

Benchmarking, Black-box optimization

1. CPU TIMING

In order to evaluate the CPU timing of the algorithm, we have run the MY-ALGORITHM-NAME on the function f_8 with restarts for at least 30 seconds and until a maximum budget equal to 400(D+2) is reached. The code was run on a Mac Intel(R) Core(TM) i5-2400S CPU @ 2.50GHz with 1 processor and 4 cores. The time per function evaluation for dimensions 2, 3, 5, 10, 20, 40 equals x.x, x.x, x.x, x.x, x.x, x.x, and xxx milliseconds respectively.

2. RESULTS

Results of PSO DE from experiments according to [?] on the benchmark functions given in [?, ?] are presented in Figures 1, 2, 3, and 4 and in Tables 1.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

GECCO'13, July 6-10, 2013, Amsterdam, The Netherlands. Copyright 2013 ACM TBA ...\$15.00.




Figure 3: ERT loss ratio versus the budget in number of f-evaluations divided by dimension. For each given budget FEvals, the target value f_t is computed as the best target f-value reached within the budget by the given algorithm. Shown is then the ERT to reach f_t for the given algorithm or the budget, if the GECCO-BBOB-2009 best algorithm reached a better target within the budget, divided by the best ERT seen in GECCO-BBOB-2009 to reach f_t . Line: geometric mean. Box-Whisker error bar: 25-75%-ile with median (box), 10-90%-ile (caps), and minimum and maximum ERT loss ratio (points). The vertical line gives the maximal number of function evaluations in a single trial in this function subset. See also Figure 4 for results on each function subgroup.

2e5

2e5

2e5

2e5

RL_{US}/D

2e5

2e5

^{*}Submission deadline: March 28th.




Figure 1: Expected number of f-evaluations (ERT, lines) to reach $f_{\rm opt}+\Delta f$; median number of f-evaluations (+) to reach the most difficult target that was reached not always but at least once; maximum number of f-evaluations in any trial (×); interquartile range with median (notched boxes) of simulated runlengths to reach $f_{\rm opt}+\Delta f$; all values are divided by dimension and plotted as \log_{10} values versus dimension. Shown are $\Delta f=10^{\{1,0,-1,-2,-3,-5,-8\}}$. Numbers above ERT-symbols (if appearing) indicate the number of trials reaching the respective target. The light thick line with diamonds indicates the respective best result from BBOB-2009 for $\Delta f=10^{-8}$. Horizontal lines mean linear scaling, slanted grid lines depict quadratic scaling.




Figure 2: Empirical cumulative distribution functions (ECDF), plotting the fraction of trials with an outcome not larger than the respective value on the x-axis. Left subplots: ECDF of the number of function evaluations (FEvals) divided by search space dimension D, to fall below $f_{\rm opt} + \Delta f$ with $\Delta f = 10^k$, where k is the first value in the legend. The thick red line represents the most difficult target value $f_{\rm opt} + 10^{-8}$. Legends indicate for each target the number of functions that were solved in at least one trial within the displayed budget. Right subplots: ECDF of the best achieved Δf for running times of $0.5D, 1.2D, 3D, 10D, 100D, 1000D, \ldots$ function evaluations (from right to left cycling cyan-magenta-black...) and final Δf -value (red), where Δf and Df denote the difference to the optimal function value. Light brown lines in the background show ECDFs for the most difficult target of all algorithms benchmarked during BBOB-2009.

				5-D							2	0-D				
Δf	1e+1	1e+0	1e-1	1e-2	1e-3	1e-5	1e-7	#∆auf¢c	1e+1	1e+0	1e-1	1e-2	1e-3	1e-5	1e-7	#succ
f ₁	11	12	12	12	12	12	12	15f/15	43	43	43	43	43	43	43	15/15
	6.2(5)	38(9)	73(13)	123(19)	170(15)	267(25)	359(14)	15/15		69(9)	102(8)	134(8)	166(10)	234(7)	299(15)	15/15
$\mathbf{f_2}$	83	87	88	89	90	92	94	15f/215	385	386	387	388	390	391	393	15/15
	25(2)	32(2)	38(3)	44(4)	49(3)	62(2)	73(3)	15/15		22(1)	26(1)	29(2)	33(1)	40(1)	47(2)	15/15
f ₃	716	1622	1637	1642	1646	1650	1654	15 f3 15	5066	7626	7635	7637	7643	7646	7651	15/15
	2.6(0.3)		48(153)	48(0.7)	48(152)	49(152)	50(151)		2172(1577)	∞	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f_4	809	1633	1688	1758	1817	1886	1903	157415		7628	7666	7686	7700	7758	1.4e5	9/15
_	2.8(0.6)		220(591)	212(994)	205(412)	199(398)	198(263)		1847(26856)	∞	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f_5	10	10	10	10	10	10	10	15 f 515		41	41	41	41	41	41	15/15
_	11(4)	14(7)	16(6)	16(5)	16(3)	16(7)	16(7)	15/15		14(4)	14(3)	14(3)	14(4)	14(5)	14(5)	15/15
f_6	114	214	281	404	580 16(3)	1038	1332 14(1)	15f ₆ 15 15/15	1296 18(9)	2343	3413	4255	5220	6728 19(4)	8409	15/15
-	7.5(4)	11(5) 324	17(5) 1171	17(2) 1451	1572	13(1) 1572	1597	15f/15	1351	21(5) 4274	20(4) 9503	20(5) 16523	19(11) 16524	16524	20(3) 16969	15/15
f ₇	12(8)	3.4(1)	1.6(0.4)	2.0(0.3)	2.1(0.5)	2.1(0.5)	2.2(0.3)		4446(7403)	4274 ∞	9503	∞	16524	10524	0.0969 0.066	0/15
-	73	273	336	372	391	410	422	15f415	2039	3871	4040	4148	4219	4371	4484	15/15
f_8	15(11)	12(2)	14(3)	15(3)	17(2)	20(2)	23(2)	15/15		911(1803)	874(743)	853(963)		812(2738)		8/15
f_9	35	127	214	263	300	335	369	15f615	1716	3102	3277	3379	3455	3594	3727	15/15
19	33(5)	23(7)	20(3)	20(5)	20(4)	22(3)	24(3)	15/15		341(640)	328(306)	324(297)	322(291)	319(556)	317(804)	12/15
f ₁₀	349	500	574	607	626	829	880	15/65	7413	8661	10735	13641	14920	17073	17476	15/15
-10	8.7(2)	7.7(1)	8.3(1)	9.2(1)	10(1)	9.4(1)	11(1)	15/15		278(116)		4175(4881)		∞	$\infty 3.9e6$	0/15
f ₁₁	143	202	763	977	1177	1467	1673	15/15	1002	2228	6278	8586	9762	12285	14831	15/15
-11	13(2)	13(4)	4.6(0.4)	4.3(0.5)	4.2(0.5)	4.4(0.3)		15/15		31(7)	17(4)	18(6)	20(4)	27(4)	30(8)	15/15
$\overline{\mathbf{f_{12}}}$	108	268	371	413	461	1303	1494	15/15	1042	1938	2740	3156	4140	12407	13827	15/15
12	40(32)	27(22)	32(15)	35(14)	36(16)	17(6)	17(9)	15/15	350(873)	1777(4260)	3872(3230)	8303(6959)	∞	∞	∞ 3.7e6	0/15
f ₁₃	132	195	250	319	1310	1752	2255	15/35	652	2021	2751	3507	18749	24455	30201	15/15
	14(3)	17(2)	18(1)	18(2)	5.7(0.5)	6.2(0.3)	7.6(0.4)	15/15	450(1)	7904(10367)	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f ₁₄	10	41	58	90	139	251	476	15/45	75	239	304	451	932	1648	15661	15/15
	1.6(3)	9.4(5)	19(3)	21(5)	21(3)	20(2)	15(1.0)	15/15		12(2)	16(2)	17(2)	17(3)	124(67)	3795(7688)	0/15
f ₁₅	511	9310	19369	19743	20073	20769	21359	14/35	30378	1.5e5	3.1e5	3.2e5	3.2e5	4.5e5	4.6e5	15/15
	305(2)	∞	∞	∞	∞	∞	$\infty 1.0e6$	0/15		∞	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f ₁₆	120	612	2662	10163	10449	11644	12095	1 5/6 5		27265	77015	1.4e5	1.9e5	2.0e5	2.2e5	15/15
_	4.5(8)	7.9(4)	432(469)	∞	∞	∞	∞1.0e6		4333(7931)	∞	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f ₁₇	5.2	215	899	2861	3669	6351	7934	15/45	63	1030	4005	12242	30677	56288	80472	15/15
-	5.3(7)	4.1(0.9)	2.8(0.6)	1.7(0.3)	1.9(0.3)	80(118)	254(283)	4/15		956(1941)			∞	∞	$\infty 4.0e6$	0/15
f ₁₈	103 $3.5(2)$	378 5.1(0.8)	3968 40(0.3)	8451 178(502)	9280 700(673)	10905	12469 $\infty 1.0e6$	1 5/8 5	621 6.2(4)	3972 13964(8420)	19561	28555	67569	1.3e5	1.5e5 $\infty 4.0e6$	15/15 0/15
f ₁₉	3.3(2)	1	242	1.0e5	1.2e5	∞ 1.2e5	1.2e5	1 5/3 5	1	13904(8420)	∞ $3.4e5$	∞ 4.7e6	∞ 6.2e6	∞ 6.7e6	6.7e6	15/15
119	44(51)	-	242 11422(12298)	1.0es ∞	1.2e5	∞	$\infty 1.0e6$	0/15		1.6e6 (2e6)	∞	4.766	∞	∞	0.7e0 ∞3.8e6	0/15
f ₂₀	16	851	38111	51362	54470	54861	55313	11265	82	46150	3.1e6	5.5e6	5.5e6	5.6e6	5.6e6	14/15
120	10(8)	3.7(1)	23(26)	17(34)	16(23)	16(27)	16(18)	8/15		563(454)	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f ₂₁	41	1157	1674	1692	1705	1729	1757	14/15	561	6541	14103	14318	14643	15567	17589	15/15
-21	3.3(3)	988(1511)	895(1490)	886(738)	879(1463)	868(1588)	854(1563)		3562(7118)	2444(3818)			1092(1842)			3/15
$\overline{\mathbf{f_{22}}}$	71	386	938	980	1008	1040	1068	14/15		5580	23491	24163	24948	26847	1.3e5	12/15
	2.2(2)	943(1939)	1599(2129)	1530(1273)	1488(1981)	1443(2160)	1406(2338)		2145(4280)	4654(3580)	∞	∞	∞	∞	$\infty 4.0e6$	0/15
f ₂₃	3.0	518	14249	27890	31654	33030	34256	15/35	3.2	1614	67457	3.7e5	4.9e5	8.1e5	8.4e5	15/15
20	3.2(3)	18(5)	195(351)	503(439)	443(592)	424(779)	409(445)	1/15	2.7(2)	5149(4971)	∞	∞	∞	∞	$\infty 4.0e6$	0/15
$\overline{\mathbf{f_{24}}}$	1622	2.2e5	6.4e6	9.6e6	9.6e6	1.3e7	1.3e7	8245	1.3e6	7.5e6	5.2e7	5.2e7	5.2e7	5.2e7	5.2e7	3/15
	98(617)	∞	∞	∞	∞	∞	$\infty 1.0e6$	0/15	∞	∞	∞	∞	∞	∞	$\infty 4.0e6$	0/15

Table 1: Expected running time (ERT in number of function evaluations) divided by the best ERT measured during BBOB-2009. The ERT and in braces, as dispersion measure, the half difference between 90 and 10%-tile of bootstrapped run lengths appear in the second row of each cell, the best ERT in the first. The different target Δf -values are shown in the top row. #succ is the number of trials that reached the (final) target $f_{\rm opt} + 10^{-8}$. The median number of conducted function evaluations is additionally given in *italics*, if the target in the last column was never reached. Bold entries are statistically significantly better (according to the rank-sum test) compared to the best algorithm in BBOB-2009, with p = 0.05 or $p = 10^{-k}$ when the number k > 1 is following the \downarrow symbol, with Bonferroni correction by the number of functions.




Figure 4: ERT loss ratios (see Figure 3 for details). Each cross (+) represents a single function, the line is the geometric mean.