Black-Box Optimization Benchmarking Template for Noiseless Function Testbed

Draft version [*]

Forename Name

ABSTRACT

to be written

Categories and Subject Descriptors

G.1.6 [**Numerical Analysis**]: Optimization—*global optimization, unconstrained optimization*; F.2.1 [**Analysis of Algorithms and Problem Complexity**]: Numerical Algorithms and Problems

General Terms

Algorithms

Keywords

Benchmarking, Black-box optimization

1. CPU TIMING

In order to evaluate the CPU timing of the algorithm, we have run the MY-ALGORITHM-NAME on the function f_8 with restarts for at least 30 seconds and until a maximum budget equal to $400(D+2)$ is reached. The code was run on a Mac Intel(R) Core(TM) i5-2400S CPU @ 2.50GHz with 1 processor and 4 cores. The time per function evaluation for dimensions 2, 3, 5, 10, 20, 40 equals *x.x*, *x.x*, *x.x*, *xx*, *xxx*, and *xxx* milliseconds respectively.

2. RESULTS

Results of PSO DE from experiments according to [**?**] on the benchmark functions given in [**?, ?**] are presented in Figures 1, 2, 3, and 4 and in Tables 1.

---

[*] Submission deadline: March 28th.

$f1-f24$ in **5-D**, maxFE/D=394					
#FEs/D	best	10%	25%	**med**	75%	90%
2	1.5	1.8	2.4	3.5	5.4	10
10	2.6	3.2	3.6	4.9	6.8	50
100	4.2	4.8	9.1	14	20	88
1e3	3.0	6.7	14	29	60	1.2e2
RL$_{US}$/D	3e2	3e2	3e2	4e2	4e2	4e2

$f1-f24$ in **20-D**, maxFE/D=398					
#FEs/D	best	10%	25%	**med**	75%	90%
2	1.0	3.7	11	31	40	40
10	4.8	6.0	8.7	24	2.0e2	2.0e2
100	6.3	6.5	10	22	32	2.7e2
1e3	7.1	14	21	33	54	1.2e2
RL$_{US}$/D	3e2	3e2	3e2	4e2	4e2	4e2

Figure 3: ERT loss ratio versus the budget in number of f-evaluations divided by dimension. For each given budget FEvals, the target value f_t is computed as the best target f-value reached within the budget by the given algorithm. Shown is then the ERT to reach f_t for the given algorithm or the budget, if the GECCO-BBOB-2009 best algorithm reached a better target within the budget, divided by the best ERT seen in GECCO-BBOB-2009 to reach f_t. Line: geometric mean. Box-Whisker error bar: **25-75%-ile with median (box), 10-90%-ile (caps), and minimum and maximum** ERT loss ratio (points). **The vertical line gives the maximal number of function evaluations in a single trial in this function subset.** See also Figure 4 for results on each function subgroup.

Figure 1: Expected number of f-evaluations (ERT, lines) to reach $f_{\mathrm{opt}} + \Delta f$; median number of f-evaluations (+) to reach the most difficult target that was reached not always but at least once; maximum number of f-evaluations in any trial ($\times$); interquartile range with median (notched boxes) of simulated runlengths to reach $f_{\mathrm{opt}} + \Delta f$; all values are divided by dimension and plotted as $\log_{10}$ values versus dimension. Shown is the ERT for targets just not reached by the artificial GECCO-BBOB-2009 best algorithm within the given budget $k \times \mathrm{DIM}$, where k is shown in the legend. Numbers above ERT-symbols indicate the number of trials reaching the respective target. The light thick line with diamonds indicates the respective best result from BBOB-2009 for the most difficult target. Slanted grid lines indicate a scaling with $\mathcal{O}(\mathrm{DIM})$ compared to $\mathcal{O}(1)$ when using the respective 2009 best algorithm.

Figure 2: Empirical cumulative distribution functions (ECDF), plotting the fraction of trials with an outcome not larger than the respective value on the x-axis. Left subplots: ECDF of number of function evaluations (FEvals) divided by search space dimension D, to fall below $f_{\mathrm{opt}} + \Delta f$ where Δf is the target just not reached by the GECCO-BBOB-2009 best algorithm within a budget of $k \times \mathrm{DIM}$ evaluations, where k is the first value in the legend. Legends indicate for each target the number of functions that were solved in at least one trial within the displayed budget. Right subplots: ECDF of the best achieved Δf for running times of $0.5D, 1.2D, 3D, 10D, 100D, 1000D, \ldots$ function evaluations (from right to left cycling cyan-magenta-black...) and final Δf-value (red), where Δf and Df denote the difference to the optimal function value. Light brown lines in the background show ECDFs for the most difficult target of all algorithms benchmarked during BBOB-2009.

5-D

#FEs/D	0.5	1.2	3	10	50	#succ
f₁	2.5e+1:4.8	1.6e+1:7.6	1.0e-8:12	1.0e-8:12	1.0e-8:12	15/15
	2.3(2)	3.8(5)	∞	∞	∞1600	0/15
f₂	1.6e+6:2.9	4.0e+5:11	4.0e+4:15	6.3e+2:58	1.0e-8:95	15/15
	1.9(1)	1.2(1)	9.3(6)	16(3)	∞1600	0/15
f₃	1.6e+2:4.1	1.0e+2:15	6.3e+1:23	2.5e+1:73	1.0e+1:716	15/15
	2.3(2)	3.2(3)	7.7(5)	10(3)	3.2(2)	10/15
f₄	2.5e+2:2.6	1.6e+2:10	1.0e+2:19	4.0e+1:65	1.6e+1:434	15/15
	2.6(2)	2.9(6)	5.9(6)	10(4)	5.4(2)	10/15
f₅	6.3e+1:4.0	4.0e+1:10	1.0e-8:10	1.0e-8:10	1.0e-8:10	15/15
	3.3(3)	4.9(3)	17(4)	17(4)	17(6)	15/15
f₆	1.0e+5:3.0	2.5e+4:8.4	1.0e+2:16	2.5e+1:54	2.5e-1:254	15/15
	1.9(4)	2.0(2)	5.1(2)	6.4(4)	∞1800	0/15
f₇	1.6e+2:4.2	1.0e+2:6.2	2.5e+1:20	4.0e+0:54	1.0e+0:324	15/15
	3.1(3)	3.7(3)	5.3(3)	12(4)	3.8(3)	14/15
f₈	1.0e+4:4.6	6.3e+3:6.8	1.0e+3:18	6.3e+1:54	1.6e+0:258	15/15
	2.6(3)	2.3(3)	6.3(5)	10(3)	49(46)	2/15
f₉	2.5e+1:20	1.6e+1:26	1.0e+1:35	4.0e+0:62	1.6e-2:256	15/15
	39(10)	35(12)	32(25)	42(50)	∞1700	0/15
f₁₀	2.5e+6:2.9	6.3e+5:7.0	2.5e+5:17	6.3e+3:54	2.5e+1:297	15/15
	2.6(3)	2.3(2)	2.2(1)	11(8)	∞1900	0/15
f₁₁	1.0e+6:3.0	6.3e+4:6.2	6.3e+2:16	6.3e+1:74	6.3e-1:298	15/15
	1.4(1)	4.8(5)	11(12)	9.3(7)	∞1900	0/15
f₁₂	4.0e+7:3.6	1.6e+7:7.6	4.0e+6:19	1.6e+4:52	1.0e+0:268	15/15
	2.1(1)	2.6(3)	4.5(2)	26(3)	∞1800	0/15
f₁₃	1.0e+3:2.8	6.3e+2:8.4	4.0e+1:17	6.3e+1:52	6.3e-2:264	15/15
	3.1(2)	4.7(4)	5.8(3)	17(4)	∞1800	0/15
f₁₄	1.6e+1:3.0	1.0e+1:10	6.3e+0:15	2.5e-1:53	1.0e-5:251	15/15
	2.8(3)	2.0(2)	3.1(4)	16(3)	∞1700	0/15
f₁₅	1.6e+2:3.0	1.0e+2:13	6.3e+1:24	4.0e+1:55	1.6e+1:289	5/5
	4.3(3)	2.5(3)	4.5(2)	5.1(6)	7.4(12)	10/15
f₁₆	4.0e+1:4.8	2.5e+1:16	1.6e+1:46	1.0e+1:120	4.0e+0:334	15/15
	1.8(4)	1.4(0.5)	2.4(0.7)	3.5(4)	16(7)	5/15
f₁₇	1.0e+1:5.2	6.3e+0:26	4.0e+0:57	2.5e+0:110	6.3e-1:412	15/15
	4.0(5)	2.9(2)	3.5(3)	3.2(2)	3.1(3)	14/15
f₁₈	6.3e+1:3.4	4.0e+1:7.2	2.5e+1:20	1.6e+1:58	1.6e+0:318	15/15
	2.0(2)	3.1(2)	3.9(2)	2.9(3)	7.6(5)	10/15
f₁₉	1.6e-1:172	1.0e-1:242	6.3e-2:675	4.0e-2:3078	2.5e-2:4946	15/15
	∞	∞	∞	∞	∞1900	0/15
f₂₀	6.3e+3:5.1	4.0e+3:8.4	4.0e+1:15	2.5e+0:69	1.0e+0:851	15/15
	2.2(3)	2.0(1)	8.9(6)	8.8(5)	15(13)	2/15
f₂₁	4.0e+1:3.9	2.5e+1:11	1.6e+1:31	6.3e+0:73	1.6e+0:347	5/5
	1.5(0.8)	1.8(5)	2.0(2)	6.5(3)	6.8(15)	8/15
f₂₂	6.3e+1:3.6	4.0e+1:15	2.5e+1:32	1.0e+1:71	1.6e+0:341	5/5
	2.6(2)	2.6(5)	2.9(4)	4.8(6)	5.9(5)	10/15
f₂₃	1.0e+1:3.0	6.3e+0:9.0	4.0e+0:33	2.5e+0:84	1.0e+0:518	15/15
	3.3(2)	4.1(6)	3.4(1)	8.1(16)	∞2000	0/15
f₂₄	6.3e+1:15	4.0e+1:37	4.0e+1:37	2.5e+1:118	1.6e+1:692	15/15
	4.2(3)	8.6(5)	8.6(4)	8.0(5)	7.5(6)	5/15

20-D

#FEs/D	0.5	1.2	3	10	50	#succ
f₁	6.3e+1:24	4.0e+1:42	1.0e-8:43	1.0e-8:43	1.0e-8:43	15/15
	16(7)	16(3)	∞	∞	∞6600	0/15
f₂	4.0e+6:29	2.5e+6:42	1.0e+5:65	1.0e+4:207	1.0e-8:412	15/15
	1.6(2)	2.4(2)	21(4)	13(2)	∞6500	0/15
f₃	6.3e+2:33	4.0e+2:44	1.6e+2:109	1.0e+2:255	2.5e+1:3277	15/15
	4.2(4)	14(6)	25(6)	23(9)	∞7400	0/15
f₄	6.3e+2:22	4.0e+2:91	2.5e+2:250	1.6e+2:332	6.3e+1:1927	15/15
	19(14)	12(3)	8.1(2)	13(2)	57(44)	1/15
f₅	2.5e+2:19	1.6e+2:34	1.0e-8:41	1.0e-8:41	1.0e-8:41	15/15
	3.3(2)	3.8(2)	14(5)	14(2)	14(6)	15/15
f₆	2.5e+5:16	6.3e+4:43	1.6e+4:62	1.6e+2:353	1.6e+1:1078	15/15
	7.0(5)	6.0(3)	6.1(2)	27(19)	∞7500	0/15
f₇	1.0e+3:11	4.0e+2:39	2.5e+2:74	6.3e+1:319	1.0e+1:1351	15/15
	2.1(2)	7.6(6)	7.1(4)	5.9(2)	13(3)	6/15
f₈	4.0e+4:19	2.5e+4:35	4.0e+3:67	2.5e+2:231	1.6e+1:1470	15/15
	23(9)	17(3)	21(5)	15(4)	69(73)	1/15
f₉	1.0e+2:357	6.3e+1:560	4.0e+1:684	2.5e+1:756	1.0e+1:1716	15/15
	12(6)	9.2(0.6)	8.2(6)	8.4(3)	∞6800	0/15
f₁₀	1.6e+6:15	1.0e+6:27	4.0e+5:70	6.3e+4:231	4.0e+3:1015	15/15
	10(8)	13(10)	12(4)	14(3)	56(56)	2/15
f₁₁	4.0e+4:11	2.5e+3:27	1.6e+2:313	1.0e+2:481	1.0e+1:1002	15/15
	2.0(2)	3.9(4)	5.8(3)	6.0(5)	∞8000	0/15
f₁₂	1.0e+8:23	6.3e+7:39	2.5e+7:76	4.0e+6:209	1.0e+1:1042	15/15
	12(9)	15(4)	15(3)	11(2)	∞6700	0/15
f₁₃	1.6e+3:28	1.0e+3:64	6.3e+2:79	4.0e+1:211	2.5e+0:1724	15/15
	10(7)	13(4)	18(4)	25(2)	∞6800	0/15
f₁₄	2.5e+1:15	1.6e+1:42	1.0e+1:75	6.3e+0:219	6.3e-1:1106	15/15
	22(12)	13(7)	13(3)	12(2)	∞7000	0/15
f₁₅	6.3e+2:15	4.0e+2:67	2.5e+2:292	1.6e+2:846	1.0e+2:1671	15/15
	13(12)	9.0(6)	5.0(0.7)	4.8(0.9)	5.4(3)	11/15
f₁₆	4.0e+1:26	2.5e+1:127	1.6e+1:540	1.6e+1:540	1.0e+1:1384	15/15
	5.1(2)	16(4)	12(9)	12(5)	41(26)	2/15
f₁₇	1.6e+1:11	1.0e+1:63	6.3e+0:305	4.0e+0:468	4.0e+0:1030	15/15
	8.6(10)	7.1(5)	4.8(3)	5.8(3)	14(8)	7/15
f₁₈	4.0e+1:116	2.5e+1:252	1.6e+1:430	1.0e+1:621	4.0e+0:1090	15/15
	4.1(2)	4.5(3)	5.4(2)	5.5(2)	15(18)	6/15
f₁₉	1.6e-1:2.5e5	1.0e-1:3.4e5	6.3e-2:3.4e5	4.0e-2:3.4e5	2.5e-2:3.4e5	3/15
	∞	∞	∞	∞	∞7700	0/15
f₂₀	1.6e+4:38	1.0e+4:42	2.5e+2:62	2.5e+0:250	1.6e+0:2536	15/15
	8.6(4)	11(4)	21(6)	19(3)	14(12)	3/15
f₂₁	6.3e+1:36	4.0e+1:77	4.0e+1:77	1.6e+1:456	4.0e+0:1094	15/15
	21(9)	17(8)	17(9)	6.0(5)	20(11)	4/15
f₂₂	6.3e+1:45	4.0e+1:68	4.0e+1:68	1.6e+1:231	6.3e+0:1219	15/15
	17(7)	19(4)	19(7)	16(2)	8.4(9)	7/15
f₂₃	6.3e+0:29	4.0e+0:118	2.5e+0:306	2.5e+0:306	1.0e+0:1614	15/15
	2.7(4)	22(18)	35(34)	35(46)	∞7900	0/15
f₂₄	2.5e+2:208	1.6e+2:918	1.0e+2:6628	6.3e+1:9885	4.0e+1:31629	15/15
	5.9(2)	9.2(4)	17(15)	∞	∞7700	0/15

Table 1: Expected running time (ERT in number of function evaluations) divided by the best ERT measured during BBOB-2009. The ERT and in braces, as dispersion measure, the half difference between 90 and 10%-tile of bootstrapped run lengths appear in the second row of each cell, the best ERT (preceded by the target Δf-value in *italics*) in the first. #succ is the number of trials that reached the target value of the last column. The median number of conducted function evaluations is additionally given in *italics*, if the target in the last column was never reached. Bold entries are statistically significantly better (according to the rank-sum test) compared to the best algorithm in BBOB-2009, with $p = 0.05$ or $p = 10^{-k}$ when the number $k > 1$ is following the ↓ symbol, with Bonferroni correction by the number of functions.

Figure 4: ERT loss ratios (see Figure 3 for details). Each cross (+) represents a single function, the line is the geometric mean.