marantz®

SR8001

RS-232C Control Specification

Category	:	*A/V Receiver*
Document Version	:	*1.02*
Author(s)	:	*Marantz America, Inc.*
Date	:	2007/03/20
Number of Page	:	22

Table of Contents

1. Introduction

1-1. Purpose

This document was written as a reference specification of products that are controled by the host controller.

1-2. Scope

This document would be using by software or hardware engineers for production of the product.

1-3. Abbreviations

Abbreviation	Description

1-4. References

Hardware Software Interface Specification ver. 1.02 / author: N.Sakamoto

2. Global Description

2-1. Overview

A Host controller can control or watch out the product as a Slave very easily via the communication cable.

2-2. Block Diagram

HOST (Controller)	**RS232C cable (Straight)**	SLAVE (The product) Connector D-SUB (9pin, male)

* The product connector is using D-SUB 9pin male.

* RS232C cable must use D-SUB 9pin female to connect the products.

2-3. Interface connection specification of the product

uP Interface	Signal name	Connection device	D-Sub Pin	Connecter
-	N.C.	-	1	<The product connector> RS232C D-SUB (9pin,**Male)**
UART	TxD (output)	**RS232C Level shift driver**	2	
	RxD (input)		3	
-	N.C.	-	4	
-	**GND**	**GND**	**5**	
-	N.C.	-	6	
-	N.C.	-	7	
-	N.C.	-	8	
-	N.C.	-	9	

2-4. Assumptions and Dependencies

marantz®

3.   Detailed Description

The interface specification between the product and a Host controller is described below.

3-1. Connection format

3-1-1. Physical connection

Host (Controller)   Slave (the product)

TxD   RxD

RxD   TxD

GND   GND

(Serial setting <RS232C basic>)
Baud Rate   : 9600bps
Data Bits   : 8bit
Parity   : None
Stop bit   : 1bit
Handshaking   : None

3-1-1-1.   Data transmission sequence from Host to Slave

Host (Controller)   Slave (The product)

TxD ————————————————— → —————————————————— RxD

RxD ——————————————————— ← ——————————————————— TxD

1. Host starts a data transmission from TxD.
2. Host performs the data transmission of the number of required bytes, and ends a transmission.

3-1-1-2.   Data transmission sequence from Slave to Host

Host (Controller)   Slave (The product)

TxD ——————————————————— → ——————————————————— RxD

RxD ————————————————— ← —————————————————— TxD

1. Slave starts a data transmission from TxD.
2. Slave performs the data transmission of the number of required bytes, and ends a transmission.

3-2. Transmission data format

3-2-1. Transmission data format from Host to Slave

There are two kinds of transmission data form from Host shown below.

3-2-1-1. Form1: Command

Command is a data that requests some status change.

Start character   : '@'
COMMAND   : see "Command list"
End character (CR) : 0Dh

Start	Command	End
@	"xxx:"+"..."	0Dh

3-2-1-2. Form2: Status request

Status request is a data that requests a answer of some status.

Start character   : '@'
Request status   : see "Status request list"
Request character   : '?'
End character (CR) : 0Dh

Start	Command	End
@	"xxx:?"+"..."	0Dh

3-2-2. Transmission data format from Slave to Host

There are two kinds of transmission data form from Slave shown below.

3-2-2-1. Form1: ACK/NAK

ACK is a reply data from Slave when Slave got an acceptable command data from Host.
(ACK is sent to Host when Slave has no related status by the Command.)

Start character   : '@',   ACK   : 06h,   End character (CR) : 0Dh

Start	ACK	End
@	06h	0Dh

NAK is a reply data from Slave when Slave got an incorrect Command data, Status request data or some other data from Host.

Start character   : '@',   NAK   : 15h,   End character (CR) : 0Dh

Start	NAK	End
@	15h	0Dh

3-2-2-2. Form2: Status answer and Auto status feedback

Status answers are reply data when Slave got an acceptable Request status or Command data from Host. Auto status feedbacks are send to Host data when a Slave's status is changed.

Start character   : '@'
Answer character   : see "Status list"
End character (CR) : 0Dh

Start	Status	End
@	"xxx:"+"..."	0Dh

3-3. The transaction sequences and the regulations

3-3-1. The transaction sequences

The transactions have three kinds of sequence.

*A transaction is a Command from Host then Slave will be an answer by Status answer, ACK or NAK.

*A transaction is a Status request from Host then Slave will be an answer by Status answer or NAK.

*A transaction is Auto status feedback from Slave when a Slave's status changed. (If the auto status feedback is enabled.)

3-3-2. The transaction regulations

The transactions have some kinds of regulation.

* An answer (ACK, NAK or Status answer) transmittion by Slave has to finish within 500ms when got a Command or a Status request from Host.

 * Host must not transmit an another Command or Status request until "it receives a answer by a previous Command or Status request" or "it passes a term of waitinng time from a finishing of previous transmission of a Command or a Status request ".

* Slave has to finish a transaction under 500ms when it sends Auto status feedback data.

3-3-3. Specification of Auto status feedback

There are some specific regulations about Auto status feedback.

* The product status has segmented into **four layers of 1, 2, 3 and 4**.

* The status of layer 1 are assigned most kindly status to Host. (The statuses of layer 2 are assigned kindly status, the statuses of layer 3 are not so need status to Host and the statuses of layer 4 are probably no wished statuses.)

* Each layer status can control transmit enable or disable by Host command. (The product default would be all disables.)

* Slave sends auto status feedback by itself when the status is changed and if the status feedback is enabled.

* The product defined and segmentationed layers are takeing in status list.

3-3-4. Example of the transactions

Example of the transactions

3-3-5. Examples of the handshaking flowchart

3-3-5-1. Example of successful handshaking

HOST   SLAVE

Command → Command acceptable

Related Status answer

or   ACK

Status request → Request acceptable

Status answer

Changed some status!

Auto status feedback

The product can reply ACK instead of related status, if the product can not send the related status immediatly.

3-3-5-2. Examples of handshaking error

HOST   SLAVE

Command → Command incorrect

NAK

Status request → Request incorrect

NAK

4. Recommendations of Command, Status and Layer definition

- All Commands, Statuses and Layers will be defined other specific document.
- **[MANDATORY]** The product **MUST** have Commands and the Statuses same as a remote controller buttons (IR controller) of the product.
- All Commands are required working by discreate as ON/OFF commands. (It means that do not support TOGGLE command only.)
- All Commands and Statuses are defined same chharacter size except ACK/NAK on the product. (Recommended character length : 3~6 characters)
- It permits attaching 0x0A character to a reply characters from the product. In this case, must suppose that the object is followed altogether.
- Recommend to supports numbers or values direct setting command, if it has variable numbers or values.

5. Definitions of Command, Status and Layer
This section is told how to define "Command", "Status" and "Layer" of this product.

5-1. Normal Command List
This chapter will show the commands of this product.

5-1-1. Main function contents

	Command		Reply from Slave
POWER	TOGGLE	"PWR:0"	"PWR:1", "PWR:2"
	OFF	"PWR:1"	
	ON	"PWR:2"	
AUDIO ATT	TOGGLE	"ATT:0"	"ATT:0" (None) "ATT:1" (OFF) "ATT:2" (ON)
	OFF	"ATT:1"	
	ON	"ATT:2"	
AUDIO MUTE	TOGGLE	"AMT:0"	"AMT:1" "AMT:2"
	OFF	"AMT:1"	
	ON	"AMT:2"	
VIDEO MUTE	TOGGLE	"VMT:0"	"VMT:1" "VMT:2"
	OFF	"VMT:1"	
	ON	"VMT:2"	
VOLUME	VALUE	"VOL:0xxx"	"VOL:xxx" xxx = vol. value as +18~-80dB 00.0 = "VOL: 000" -∞= "VOL:-ZZZ"
	UP	"VOL:1"	
	DOWN	"VOL:2"	
	UP-FAST	"VOL:3"	
	DOWN-FAST	"VOL:4"	
TONE BASS	VALUE	"TOB:0xxx"	"TOB:xxx" xxx = vol. value as +06 ~-06
	UP	"TOB:1"	
	DOWN	"TOB:2"	
TONE TREBLE	VALUE	"TOT:0xxx"	"TOT:xxx" xxx = vol. value as +06 ~-06
	UP	"TOT:1"	
	DOWN	"TOT:2"	
SOURCE Select	TV	"SRC:1"	"SRC:va" (v ,a= '0' ~ 'Z') (v = video, a = audio.) v = 0 (V-OFF) a = N (7.1CH)
	DVD	"SRC:2"	
	VCR1	"SRC:3"	
	DSS/VCR2	"SRC:5"	
	AUX1	"SRC:9"	
	AUX2	"SRC:A"	
	CD/CD-R	"SRC:C"	
	TAPE	"SRC:E"	
	TUNER1	"SRC:F"	
	FM1	"SRC:G"	
	AM1	"SRC:H"	
	XM1	"SRC:J"	
7.1 Channel Input	TOGGLE	"71C:0"	"71C:1" (OFF) "71C:2" (ON)
	OFF	"71C:1"	
	ON	"71C:2"	

Command			Reply from Slave
SPEAKER Select	SPKR SEL	"SPK:0"	"SPK:ab", a=SPK-A, b=SPK-B
	SPKR-A OFF	"SPK:1"	"SPK:11" (A-OFF,B-OFF)
	SPKR-A ON	"SPK:2"	"SPK:21" (A-ON,B-OFF)
	SPKR-B OFF	"SPK:3"	"SPK:12" (A-OFF,B-ON)
	SPKR-B ON	"SPK:4"	"SPK:22" (A-ON,B-ON)
HDMI OUTPUT Select	TOGGLE	"HDM:0"	"HDM:1" (HDMI OUT 1)
	HDMI OUT 1	"HDM:1"	"HDM:2" (HDMI OUT2)
	HDMI OUT 2	"HDM:2"	

Command			Reply from Slave
SLEEP	VALUE	"SLP:0xx" (xx="00"~"90")	"SLP:01~90" (ON)
	OFF	"SLP:1"	"SLP:00" (OFF)
MENU	TOGGLE	"MNU:0" (work same as RC)	"MNU:1" (Not on Menu)
	OFF	"MNU:1"	"MNU:2" (On Menu)
	ON	"MNU:2"	
	ENTER	"MNU:3"	
CURSOR	UP	"CUR:1"	ACK
	DOWN	"CUR:2"	
	LEFT	"CUR:3"	
	RIGHT	"CUR:4"	

Command			Reply from Slave
DC TRG.	TRG. 1 OFF	"DCT:11" (DC TRG. 1 OFF)	"DCT:ab" (a: TRG.1=1, TRG.2=2) (b: OFF=1, ON=2)
	TRG. 1 ON	"DCT:12" (DC TRG. 1 ON)	
	TRG. 2 OFF	"DCT:21" (DC TRG.2 OFF)	e.g.) "DCT:11" (all OFF) "DCT:21" (TRG.1 ON)
	TRG. 2 ON	"DCT:22" (DC TRG.2 ON)	"DCT:12" (TRG.2 ON) "DCT:22" (all ON)

5-1-2. Surround contents

Command			Reply from Slave
Surr. Mode	AUTO	"SUR:00"	"SUR:x", (x = '0' ~'Z')
	STEREO	"SUR:01"	
	DOLBY	"SUR:02"	
	PL II (x) MOVIE	"SUR:03"	"SUR:0": AUTO
	PL II (x) MUSIC	"SUR:05"	"SUR:1": STEREO
	PL II (x) GAME	"SUR:07"	"SUR:2": DOLBY
	EX/ES	"SUR:0A"	"SUR:3": PL II (x) MOVIE
	DTS ES (DISC, MATRIX)	"SUR:0E"	"SUR:5": PL II (x) MUSIC
	NEO6 CINEMA	"SUR:0F"	"SUR:7": PL II (x) GAME
	NEO6 MUSIC	"SUR:0G"	"SUR:A": EX/ES
	Multi Ch. (MOVIE, MUSIC)	"SUR:0H"	"SUR:E": DTS ES (Discrete/ Matrix)
	CS II CINEMA	"SUR:0I	"SUR:F": NEO6 CINEMA
	CS II MUSIC	"SUR:0J"	"SUR:G": NEO6 MUSIC
	CS II MONO	"SUR:0K"	"SUR:H": Multi Ch. (MOVIE, MUSIC)
	VIRTUAL	"SUR:0L"	"SUR:I": CS II CINEMA
	DTS	"SUR:0M"	"SUR:J": CS II MUSIC
	DD+ PL II x MOVIE	"SUR:0O"	"SUR:K": CS II MONO
			"SUR:L": VIRTUAL
	DD+ PL II x MUSIC	"SUR:0P"	"SUR:M": DTS
			"SUR:O": DD + PL II (x) MOVIE
	SOURCE DIRECT	"SUR:0T"	"SUR:P": DD + PL II (x) MUSIC
	PURE DIRECT	"SUR:0U"	"SUR:T: SOURCE DIRECT
	NEXT	"SUR:1"	"SUR:U: PURE DIRECT
	PREV	"SUR:2"	

Command			Reply from Slave
THX	THX TOGGLE	"THX:0"	"THX:0": THX AUTO
	THX OFF	"THX:1"	"THX:3": PL II x MOVIE+THX
	THX ON	"THX:2"	"THX:4": PL II MOVIE+THX
	THX SURR EX	"THX:3"	"THX:C": THX SURR EX
	THX CINEMA	"THX:5"	"THX:E": DTS ES+THX
	THX GAMES	"THX:6"	"THX:F": NEO6 CINEMA+THX
	THX MUSIC	"THX:7"	"THX:b": THX MUSIC
	THX SELECT2 CINEMA	"THX:8"	"THX:c": THX GAMES
			"THX:e": THX CINEMA
	DTS NEO6 THX	"THX:9"	"THX:f": THX SELECT2 CINEMA
			"THX:g": DTS NEO6 THX

Command			Reply from Slave
Dolby Headphone Mode	BYPASS	"DHM:0"	"DHM:x"
	DH1(DH)	"DHM:1"	x = Dolby Headphone mode
		"DHM:2" (+PL II MOVIE)	
		"DHM:3" (+PL II MUSIC)	

marantz®

Command			Reply from Slave
NIGHT MODE	TOGGLE	"NGT:0"	"NGT:0" (invalid)
	OFF	"NGT:1"	"NGT:1" (OFF)
	ON	"NGT:2"	"NGT:2" (ON)
Lip Sync.	VALUE	"LIP:0xxx" (xxx = value ms)	"LIP:xxx" (xxx = value ms) xxx = "000" (OFF) xxx = "010" ~ "200" (ON)
	UP	"LIP:1" (up 10ms)	
	DOWN	"LIP:2" (down 10ms)	
Test Tone (Force start/stop Test Tone with Auto mode)	TOGGLE	"TTO:0"	"TTO:1xy" (OFF) "TTO:2xy" (ON) (x: Auto=0, Manual=1) (y=Ch.)
	OFF	"TTO:1"	
	ON	"TTO:2"	
	NEXT	"TTO:3"	
	PREV	"TTO:4"	

5-1-3. Tuner contents

Command			Reply from Slave
Tuner1 Frequency	VALUE	"TFQ:0xxxxx" (xxxxx = freq.)	"TFQ:xxxxx" (xxxxx = Frequency) if (xxxxx < 00256), band = XM; else if (xxxxx < 02000), band=AM; else band=FM; (ex."08750" = FM87.50MHz) *Auto-UP/DOWN dose not operate in XM *XM can be selected When Band is XM.
	UP	"TFQ:1"	
	DOWN	"TFQ:2"	
	Auto-UP	"TFQ:3"	
	Auto-DOWN	"TFQ:4"	
Tuner1 Preset	VALUE	"TPR:0ww"	"TPR:ww" (ww = current preset nr.) (ww = 01 ~ ??)
	UP	"TPR:1"	
	DOWN	"TPR:2"	
	P-Scan start	"TPR:3"	
	P-Scan stop	"TPR:4"	
Tuner1 mode	TOGGLE	"TMD:0"	"TMD:0"(-) "TMD:1" (MONO) "TMD:2" (AUTO)
	OFF(MONO)	"TMD:1"	
	ON(AUTO)	"TMD:2"	
Tuner Preset Info.	TOGGLE	"TPI:0"	"TPI:1" (OFF) "TPI:2" (ON)
	OFF	"TPI:1"	
	ON	"TPI:2"	
Tuner1 MEMO	-	"MEM:0"	ACK
Tuner1 CLEAR	-	"CLR:0"	ACK

5-1-4. XM Contents

Command			Reply from Slave
XM DispMode	TOGGLE	"XDP:0"	"XDP:1"(NORMAL) "XDP:2"(ART/SNG) "XDP:3"(CATEGORY) "XDP:4"(STATUS)
	NORMAL	"XDP:1"	
	ART/SNG	"XDP:2"	
	CATEGORY	"XDP:3"	
	STATUS	"XDP:4"	
XM Category	TOGGLE	"CAT:0"	"CAT:yxx" (y: Un search=1, in search=2) (xx: Category No. 00(none), 01 to 32)
	CH. UP	"CAT:1"	
	CH. DOWN	"CAT:2"	
	CAT. NEXT	"CAT:3"	
	CAT. PREV	"CAT:4"	

marantz®

5-1-5. Multi Room contents

Command			Reply from Slave
Multi Room A POWER	TOGGLE	"MPW:0"	"MPW:1" (OFF) "MPW:2" (ON)
	OFF	"MPW:1"	
	ON	"MPW:2"	
Multi Room A SPEAKER	TOGGLE	"MSP:0"	"MSP:1" (OFF) "MSP:2" (ON)
	OFF	"MSP:1"	
	ON	"MSP:2"	
Multi Room A AUDIO MUTE	TOGGLE	"MAM:0"	"MAM:1" "MAM:2"
	OFF	"MAM:1"	
	ON	"MAM:2"	
Multi Room A VOLUME	VALUE	"MVL:0xxx"	"MVL:xxx" xxx = vol. value as " 00" ~"-90"
	UP	"MVL:1"	
	DOWN	"MVL:2"	
Multi Room A VOLUME SET	VARIABLE	"MVS:1"	"MVS:1" (VARIABLE)
	FIXED	"MVS:2"	"MVS:2" (FIXED)
Multi Room A SOURCE Select	TV	"MSC:1"	"MSC:va" (v, a= '0' to 'Z') (v = video, a = audio.)
	DVD	"MSC:2"	
	VCR1	"MSC:3"	
	DSS/VCR2	"MSC:5"	
	AUX1	"MSC:9"	
	AUX2	"MSC:A"	
	CD/CDR	"MSC:C"	
	TAPE	"MSC:E"	
	TUNER1	"MSC:F"	
	FM1	"MSC:G"	
	AM1	"MSC:H"	
	XM1	"MSC:J"	
Multi Room A SLEEP	VALUE	"MSL:0xx" ("xx" = min)	"MSL:xx" (xx = min)
	OFF	"MSL:1"	"MSL:00"
Multi Room A Stereo/Mono	TOGGLE	"MST:0"	"MST:0"(-) "MST:1"(STEREO) "MST:2"(MONO)
	STEREO	"MST:1"	
	MONO	"MST:2"	
Multi Room A Tuner1 Frequency	VALUE	"MTF:0xxxxx" (xxxxx = freq.)	"MTF:xxxxx", (xxxxx = Frequency) if (xxxxx < 00256) band = XM; else if (xxxxx < 02000) band=AM; else band=FM; (e.g."08750" = FM87.50MHz) *Auto-UP/DOWN dose not operate in XM *XM can be selected When Band is XM.
	UP	"MTF:1"	
	DOWN	"MTF:2"	
	Auto-UP	"MTF:3"	
	Auto-DOWN	"MTF:4"	
Multi Room A Tuner1 Preset	VALUE	"MTP:0ww" (ww = preset nr.)	"MTP:ww" (ww = current preset nr.) (ww = 01 ~??)
	UP	"MTP:1"	
	DOWN	"MTP:2"	
	SCAN Start	"MTP:3"	
	SCAN Stop	"MTP:4"	
Multi Room A Tuner1 mode	TOGGLE	"MTM:0"	"MTM:0"(-) "MTM:1"(MONO) "MTM:2"(AUTO)
	OFF(MONO)	"MTM:1"	
	ON(AUTO)	"MTM:2"	

Command			Reply from Slave
Multi Room B POWER	TOGGLE	"MPW=0"	"MPW=1" (OFF) "MPW=2" (ON)
	OFF	"MPW=1"	
	ON	"MPW=2"	
Multi Room B SPEAKER	TOGGLE	"MSP=0"	"MSP=1" (OFF) "MSP=2" (ON)
	OFF	"MSP=1"	
	ON	"MSP=2"	
Multi Room B AUDIO MUTE	TOGGLE	"MAM=0"	"MAM=1" "MAM=2"
	OFF	"MAM=1"	
	ON	"MAM=2"	
Multi Room B VOLUME	VALUE	"MVL=0xxx"	"MVL=xxx" xxx = vol. value as " 00" ~"-90"
	UP	"MVL=1"	
	DOWN	"MVL=2"	
Multi Room B VOLUME SET	VARIABLE	"MVS=1"	"MVS=1" (VARIABLE) "MVS=2" (FIXED)
	FIXED	"MVS=2"	
Multi Room B SOURCE Select	TV	"MSC=1"	"MSC=va" (v ,a= '0' – 'Z') (v = video, a = audio.) *Video is always '0'.
	DVD	"MSC=2"	
	VCR1	"MSC=3"	
	DSS/VCR2	"MSC=5"	
	AUX1	"MSC=9"	
	AUX2	"MSC=A"	
	CD/CD-R	"MSC=C"	
	TAPE	"MSC=E"	
	TUNER1	"MSC=F"	
	FM1	"MSC=G"	
	AM1	"MSC=H"	
	XM1	"MSC=J"	
Multi Room B SLEEP	VALUE	"MSL=0xx" ("xx" = min)	"MSL=xx" (xx = min)
	OFF	"MSL=1"	"MSL=00"
Multi Room B Stereo/Mono	TOGGLE	"MST=0"	"MST=0"(-), "MST=1"(STEREO), "MST=2"(MONO)
	STEREO	"MST=1"	
	MONO	"MST=2"	
Multi Room B Tuner1 Frequency	VALUE	"MTF=0xxxxx" (xxxxx = freq.)	"MTF=xxxxx", (xxxxx = Frequency) if (xxxxx < 00256) band = XM; else if (xxxxx < 02000) band=AM; else band=FM; (e.g."08750" = FM87.50MHz) *Auto-UP/DOWN dose not operate in XM *XM can be selected When Band is XM.
	UP	"MTF=1"	
	DOWN	"MTF=2"	
	Auto-UP	"MTF=3"	
	Auto-DOWN	"MTF=4"	
Multi Room B Tuner1 Preset	VALUE	"MTP=0ww" (ww = preset nr.)	"MTP=ww" (ww = current preset nr.) (ww = 01 ~??)
	UP	"MTP=1"	
	DOWN	"MTP=2"	
	SCAN Start	"MTP=3"	
	SCAN Stop	"MTP=4"	
Multi Room B Tuner1 mode	TOGGLE	"MTM=0"	"MTM=0"(-), "MTM=1"(MONO) "MTM=2"(AUTO)
	OFF(MONO)	"MTM=1"	
	ON(AUTO)	"MTM=2"	

marantz®

Command			Reply from Slave
Multi Room A/B Speaker VOLUME	VALUE	"MSV=0xxx"	"MSV=xxx" xxx = vol. Value as +90 ~-90
	UP	"MSV=1"	
	DOWN	"MSV=2"	
Multi Room A/B Speaker VOLUME SET	VARIABLE	"MSS=1"	"MSS:1" (VARIABLE) "MSS:2" (FIXED)
	FIXED	"MSS=2"	
Multi Room A/B Speaker AUDIO MUTE	TOGGLE	"MSM=0"	"MSM=1" "MSM=2"
	OFF	"MSM=1"	
	ON	"MSM=2"	

5-2. Specific Commands

Command from Host		Reply from Slave
Auto status feedback

(The product default is disabled all auto status feedback.) | "AST:x" (x = '0' ~ 'F')

bit 3 : Layer 4 (1 = Enable, 0 = Disable) bit 2 : Layer 3 (1 = Enable, 0 = Disable) bit 1 : Layer 2 (1 = Enable, 0 = Disable) bit 0 : Layer 1 (1 = Enable, 0 = Disable) | same as command define |

marantz®

5-3. Status request and Status answer list

5-3-1. Normal Status request and Status (answer and feedback) list

Status request			Status answer and feedback	
POWER	"PWR:?"	OFF		"PWR:1"
		ON		"PWR:2"
AUDIO ATT	"ATT:?"	OFF		"ATT:1"
		ON		"ATT:2"
AUDIO MUTE	"AMT:?"	OFF		"AMT:1"
		ON		"AMT:2"
VIDEO MUTE	"VMT:?"	OFF		"VMT:1"
		ON		"VMT:2"
VOLUME	"VOL:?"	Volume value = xxxy (see command list)		"VOL:xxxy" (+18.0 ~ -80.0dB)
TONE BASS	"TOB:?"	Bass value = xxx (see command list)		"TOB:xxx"
TONE TREBLE	"TOT:?"	Treble value = xxx (see Command List)		"TOT:xxx"
SOURCE Select	"SRC:?"	Video+Audio source (see Command List)		"SRC:va" (v ,a= '0' ~ 'Z') (v = video, a = audio.)
7.1 Channel Input	"71C:?"	OFF		"71C:1"
		ON		"71C:2"
INPUT SIGNAL	"ISG:?"	ANALOG		"ISG:1"
		DIGITAL		"ISG:2"
		HDMI		"ISG:4"
SPEAKER Select	"SPK:?"	Speaker status = ab a = SPKR-A, b = SPKR-B		"SPK:ab" a,b (1 = OFF, 2 = ON)
HDMI OUTPUT	"HDM:?"	HDMI OUTPUT 1		"HDM:1"
		HDMI OUTPUT2		"HDM:2"

Status request			Status answer and feedback	
SLEEP	"SLP:?"	Sleep time (xx = 00 ~ 90)		"SLP:xx"
MENU	"MNU:?"	OFF		"MNU:1" (Not on Menu)
		ON		"MNU:2" (On Menu)

Status request			Status answer and feedback	
DC TRG.	"DCT:?"	"DCT:ab" (1 = OFF, 2 = ON) (a = TRG.1, b = TRG.2,)		"DCT:11", (all OFF) "DCT:12", (TRG.2 ON) "DCT:22" (all ON)

Status request			Status answer and feedback	
Surr. Mode	"SUR:?"	"SUR:x" , "THX:x"		same as command replay (see Command list)
THX	"THX:?"	"SUR:x" , "THX:x",		same as command reply (see Command list)
Dolby Headphone mode	"DHM:?"	"DHM:x"		same as command reply (see Command list)
Night Mode	"NGT:?"	OFF		"NGT:1"
		ON		"NGT:2"
Lip Sync.	"LIP:?"	VALUE (ms)		"LIP:xxx" (xxx = 000 ~ 200 ms)

Status request		Status answer and feedback	
Digital Signal Format	"SIG:?"	x = '0' :No detect '1' :D DIGITAL AC-3 '2' : D DIGITAL AC-3 PL '3' : D DIGITAL SURR. EX '4' : DTS '5' : DTS ES DISCREATE '6' : DTS ES MATRIX '7' : AAC '8' : MPEG '9' : M-PCM 'A' : PCM 'B' : HDCD 'C' : DSD 'D' : DTS 96/24 'E' : reserved 'F' : OTHER	"SIG:x" x = signal

Status request		Status answer and feedback	
Tuner1 Frequency	"TFQ:?"	"TFQ:xxxxx"	same as command reply (see Command list)
Tuner1 Preset	"TPR:?"	"TPR:ww"	same as command reply (see Command list)
Tuner1 mode	"TMD:?"	OFF (MONO)	"TMD:1"
		AUTO	"TMD:2"
Tuner Preset Info.	"TPI:?"	OFF	"TPI:1"
		ON	"TPI:2"

Status request		Status answer and feedback	
XM Ch Name	"CHN:?"	Channel Name	"CHN:xxxxxxxx" x=10Byte
XM Artist Name	"ARN:?"	Artist Name	"ARN:xxxxxxxx" x=16Byte
XM Son Title	"SON:?"	Song Title	"SON:xxxxxxxx" x=16Byte
XM Categoy Name	"CTN:?"	Category Name	"CTN:xxxxxxxx" x=8Byte
XM Signal Status	"SST:?"	Antenna Status	"SST:x" x= Status 0= CHECK ANTENNA 1= STRONG 2= MARGINAL 3= WEAK 4= NO

Status request		Status answer and feedback	
Multi Room A POWER	"MPW:?"	OFF	"MPW:1"
		ON	"MPW:2"
Multi Room A SPEAKER	"MSP:?"	OFF	"MSP:1"
		ON	"MSP:2"
Multi Room A AUDIO MUTE	"MAM:?"	OFF	"MAM:1"
		ON	"MAM:2"
Multi Room A VOLUME	"MVL:?"	Volume value = xxx	"MVL:xxx"
Multi Room A VOLUME SET	"MVS:?"	VARIABLE	"MVS:1"
		FIXED	"MVS:2"
Multi Room A SOURCE Select	"MSC:?"	Video+Audio source (v ,a= '0' – 'Z') (v = video, a = audio.)	"MSC:va"
Multi Room A SLEEP	"MSL:?"	Sleep time min : xx = '00' ~ '99'	"MSL:xx"
Multi Room A STEREO/MONO	"MST:?"	STEREO	"MST:1"
		MONO	"MST:2"

Status request		Status answer and feedback	
Multi Room A Tuner1 Frequency	"MTF:?"	xxxxx = frequency if (xxxxx < 00256) band = XM; else if (xxxxx < 02000) band=AM; else band=FM;	"MTF:xxxxx"
Multi Room A Tuner1 Preset	"MTP:?"	xx = preset number (01 ~ ??)	"MTP:xx"
Multi Room A Tuner1 Mode	"MTM:?"	- (None)	"MTM:0"
		OFF (MONO)	"MTM:1"
		ON (AUTO)	"MTM:2"
Multi RoomA Speaker VOLUME	"MSV:?"	Volume value = xxx	"MSV:xxx"
Multi RoomA Speaker Volume Set	"MSS:?"	VARIABLE	"MSS:1"
		FIXED	"MSS:2"
Multi RoomA Speaker AUDIO MUTE	"MSM:?"	OFF	"MSM:1"
		ON	"MSM:2"

marantz®

Status request		Status answer and feedback	
Multi Room B POWER	"MPW=?"	OFF	"MPW=1"
		ON	"MPW=2"
Multi Room B SPEAKER	"MSP=?"	OFF	"MSP=1"
		ON	"MSP=2"
Multi Room B AUDIO MUTE	"MAM=?"	OFF	"MAM=1"
		ON	"MAM=2"
Multi Room B VOLUME	"MVL=?"	Volume value = xxx	"MVL=xxx"
Multi Room B VOLUME SET	"MVS=?"	VARIABLE	"MVS=1"
		FIXED	"MVS=2"
Multi Room B SOURCE Select	"MSC=?"	Video+Audio source (v ,a= '0' – 'Z') (v = video, a = audio.)	"MSC=va"
Multi Room B SLEEP	"MSL=?"	Sleep time min : xx = '00' ~ '99'	"MSL=xx"
Multi Room B STEREO/MONO	"MST=?"	STEREO	"MST=1"
		MONO	"MST=2"

Status request		Status answer and feedback	
Multi Room B Tuner1 Frequency	"MTF=?"	xxxxx = frequency if (xxxxx < 00256) band = XM; else if (xxxxx < 02000) band=AM; else band=FM;	"MTF=xxxxx"
Multi Room B Tuner1 Preset	"MTP=?"	xx = preset number (01 ~ ??)	"MTP=xx"
Multi Room B Tuner1 Mode	"MTM=?"	- (None)	"MTM=0"
		OFF (MONO)	"MTM=1"
		ON (AUTO)	"MTM=2"
Multi RoomB Speaker VOLUME	"MSV=?"	Volume value = xxx	"MSV=xxx"
Multi RoomB Speaker Volume Set	"MSS=?"	VARIABLE	"MSS=1"
		FIXED	"MSS=2"
Multi RoomB Speaker AUDIO MUTE	"MSM=?"	OFF	"MSM=1"
		ON	"MSM=2"

marantz®

5-3-2. Layer of the statuses

Status		Layer
POWER	"PWR:"	1
AUDIO ATT	"ATT:"	3
AUDIO MUTE	"AMT:"	1
VIDEO MUTE	"VMT:"	1
VOLUME	"VOL:"	1
TONE BASS	"TOB:"	1
TONE TREBLE	"TOT:"	1
SOURCE Select	"SRC:"	1
7.1 Channel Input	"71C:"	1
INPUT SIGNAL SOURCE	"ISG:"	3
SPEAKER Select	"SPK:"	1

Status		Layer
SLEEP	"SLP:"	2
MENU	"MNU:"	4
DC TRIG.	"DCT:"	1

Status		Layer
Surr. Mode	"SUR:"	2
THX	"THX:"	2
Dolby Headphone Mode	"DHM:"	2
Night Mode	"NGT:"	3
Lip Sync.	"LIP:"	4
Test Tone	"TTO:"	1
Ch.Select	"CSL:"	4
Digital Signal Format	"SIG:"	4

Status		Layer
Tuner1 Frequency	"TFQ:"	3
Tuner1 Preset	"TPR:"	2
Tuner1 mode	"TMD:"	2
Tuner Preset Info.	"TPI:"	2

Status		Layer
XM Display mode	"XDP:"	1
XM Category Search	"CAT:"	4
XM Category Name	"CTN:"	4
XM Channel Name	"CHN:"	4
XM Artist Name	"ARN:"	4
XM Song Title	"SON:"	4
XM Signal Status	"SST:"	1

marantz®

Status		Layer
Multi Room A POWER	"MPW:"	1
Multi Room A SPEAKER	"MSP:"	2
Multi Room A AUDIO MUTE	"MAM:"	1
Multi Room A VOLUME	"MVL:"	1
Multi Room A VOLUME SET	"MVS:"	2
Multi Room A SOURCE Select	"MSC:"	1
Multi Room A SLEEP	"MSL:"	2
Multi Room A STEREO/MONO	"MST:"	2
Multi RoomA Speaker VOLUME	"MSV:"	1
Multi RoomA Speaker Volume Set	"MSS:"	2
Multi RoomA Speaker A-MUTE	"MSM:"	1

Status		Layer
Multi Room A Tuner1 Frequency	"MTF:"	3
Multi Room A Tuner1 Preset	"MPR:"	2
Multi Room A Tuner1 Mode	"MTM:"	2

Status		Layer
Multi Room B POWER	"MPW="	1
Multi Room B SPEAKER	"MSP="	2
Multi Room B AUDIO MUTE	"MAM="	1
Multi Room B VOLUME	"MVL="	1
Multi Room B VOLUME SET	"MVS="	2
Multi Room B SOURCE Select	"MSC="	1
Multi Room B SLEEP	"MSL="	2
Multi Room B STEREO/MONO	"MST="	2
Multi Room B Speaker VOLUME	"MSV:"	1
Multi Room B Speaker Volume Set	"MSS:"	2
Multi Room B Speaker A-MUTE	"MSM:"	1

Status		Layer
Multi Room B Tuner1 Frequency	"MTF="	3
Multi Room B Tuner1 Preset	"MPR="	2
Multi Room B Tuner1 Mode	"MTM="	2

6.   Revision history

Ver.	Date	Owner	Change description
1.0	08/18/06	Marantz America, Inc.	Issued Revision1.0
1.01	02/07/07	Marantz America, Inc.	Added Surrond mode Status information. Added Multi-room Speaker volume set commands. Command corrcection (DC trigger status, XM category name) Status layer information was corrected (XM Category Search)
1.02	03/19/07	Marantz America, Inc	Added HDMI Output select commands Corrected Volume value input comand