

Person and Turma:

simple example (with ChatGPT support)



“create java code for a Person and a Turma where Turma has Persons - use a Hash to index the Person but also provide a collection to store the Person. Assume a Person an unique id called nmec and is used an equality criteria”

```

class Person {
    private int nmec;
    private String name;

    public Person(int nmec, String name) {
        this.nmec = nmec;
        this.name = name;
    }

    public int getNmec() {...}
    public String getName() { (...) }

    @Override
    public boolean equals(Object obj) {
        if (this == obj) return true;
        if (obj == null || getClass() != obj.getClass()) return false;
        Person person = (Person) obj;
        return nmec == person.nmec;
    }

    @Override
    public int hashCode() { return Objects.hash(nmec); }

    @Override
    public String toString() {
        return "Person{" + "nmec=" + nmec + ", name='" + name + "'";
    }
}

```

```

class Turma {
    private Map<Integer, Person> personMap;
    private Collection<Person> personCollection;

    public Turma() {
        this.personMap = new HashMap<>();
        this.personCollection = new ArrayList<>();
    }

    public void addPerson(Person person) {
        if (!personMap.containsKey(person.getNmec())) {
            personMap.put(person.getNmec(), person);
            personCollection.add(person);
        }
    }

    public Person getPerson(int nmec) {
        return personMap.get(nmec);
    }

    public Collection<Person> getAllPersons() {
        return Collections.unmodifiableCollection(personCollection);
    }

    public void removePerson(int nmec) {
        Person person = personMap.remove(nmec);
        if (person != null) {
            personCollection.remove(person);
        }
    }
}

```

```

class Turma {
    private Map<Integer, Person> personMap;
    private Collection<Person> personCollection;

    public Turma() {
        this.personMap = new HashMap<>();
        this.personCollection = new ArrayList<>();
    }

    public void addPerson(Person person) {
        if (!personMap.containsKey(person.getMec())) {
            personMap.put(person.getMec(), person);
            personCollection.add(person);
        }
    }

    public Person getPerson(int mec) {
        return personMap.get(mec);
    }

    public Collection<Person> getAllPersons() {
        return Collections.unmodifiableCollection(personCollection);
    }

    public void removePerson(int mec) {
        Person person = personMap.remove(mec);
        if (person != null) {
            personCollection.remove(person);
        }
    }
}

```

Map for faster search

```
class Turma {
    private Map<Integer, Person> personMap;
    private Collection<Person> personCollection;
```

```
    public Turma() {
        this.personMap = new HashMap<>();
        this.personCollection = new ArrayList<>();
    }
```

```
    public void addPerson(Person person) {
        if (!personMap.containsKey(person.getId())) {
            personMap.put(person.getId(), person);
            personCollection.add(person);
        }
    }
```

```
    public Person getPerson(int nmec) {
        return personMap.get(nmec);
    }
```

```
    public Collection<Person> getAllPersons() {
        return Collections.unmodifiableCollection(personCollection);
    }
```

```
    public void removePerson(int nmec) {
        Person person = getPerson(nmec);
        if (person != null) {
            personCollection.remove(person);
        }
    }
```

```
}
```

```
public class Main {
    public static void main(String[] args) {
        Turma turma = new Turma();

        Person p1 = new Person(101, "Alice");
        Person p2 = new Person(102, "Bob");
        Person p3 = new Person(103, "Charlie");

        turma.addPerson(p1);
        turma.addPerson(p2);
        turma.addPerson(p3);

        System.out.println("All persons: " + turma.getAllPersons());
        System.out.println("Retrieve person with nmec 102: " +
            turma.getPerson(102));

        turma.removePerson(102);
        System.out.println("After removal, all persons: " + turma.getAllPersons());
    }
}
```



ChatGPT

“add the support to keep management of lecture presences of Persons in Lectures of a given Turma”

Question: Where do we need changes?

```

class Lecture {
    private String topic;
    private Date date;
    private Set<Integer> presentPersons;

    public Lecture(String topic, Date date) {
        this.topic = topic;
        this.date = date;
        this.presentPersons = new HashSet<>();
    }

    public String getTopic() { return topic; }
    public Date getDate() { return date; }

    public void markPresence(Person person) {
        presentPersons.add(person.getNmec());
    }

    public boolean isPersonPresent(Person person) {
        return presentPersons.contains(person.getNmec());
    }

    @Override
    public String toString() {
        return "Lecture{" + "topic='" + topic + "', date=" + date + ",
presentPersons=" + presentPersons + "}";
    }
}

```

New concept

“Usually” means a new class


```

class Turma {
    private Map<Integer, Person> personMap;
    private Collection<Person> personCollection;
    private List<Lecture> lectures;

    public Turma() {
        this.personMap = new HashMap<>();
        this.personCollection = new ArrayList<>();
        this.lectures = new ArrayList<>();
    }

    public void addPerson(Person person) { (...) }
    public Person getPerson(int nmec) { (...) }
    public Collection<Person> getAllPersons() { (...) }
    public void removePerson(int nmec) { (...) }

    private void addLecture(Lecture lecture) {
        lectures.add(lecture);
    }

    private List<Lecture> getAllLectures() {
        return Collections.unmodifiableList(lectures);
    }

    private void markPresence(int nmec, Lecture lecture) {
        Person person = personMap.get(nmec);
        if (person != null) {
            lecture.markPresence(person);
        }
    }
}

```

Different and unrelated features

=>

Only need to add ... No changes
In remaining code



“allow to see person that where present than
1/3 of the lectures “

In Turma.java

```
public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {
    int totalLectures = lectures.size();
    Map<Integer, Integer> attendanceCount = new HashMap<>();

    for (Lecture lecture : lectures) {
        for (Integer nmec : lecture.getPresentPersons()) {
            attendanceCount.put(nmec, attendanceCount.getOrDefault(nmec, 0) + 1);
        }
    }

    Set<Person> result = new HashSet<>();
    for (Map.Entry<Integer, Integer> entry : attendanceCount.entrySet()) {
        if (entry.getValue() > (fraction * totalLectures)) {
            result.add(personMap.get(entry.getKey()));
        }
    }
    return result;
}
```



adapt the `getPersonsWithAttendanceAboveThreshold` method to use streams

In Turma.java

```
public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {
    int totalLectures = lectures.size();
    Map<Integer, Long> attendanceCount = new HashMap<>();

    for (Lecture lecture : lectures) {
        for (Integer nmec : lecture.getPresentPersons()) {
            attendanceCount.put(nmec, attendanceCount.getOrDefault(nmec, 0L) + 1);
        }
    }


    return attendanceCount.entrySet().stream()
        .filter(entry -> entry.getValue() > (fraction * totalLectures))
        .map(entry -> personMap.get(entry.getKey()))
        .collect(Collectors.toSet());
}
```

In Turma.java

```
public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {
    int totalLectures = lectures.size();
    Map<Integer, Long> attendanceCount = new HashMap<>();

    for (Lecture lecture : lectures) {
        for (Integer nmec : lecture.getPresentPersons()) {
            attendanceCount.put(nmec, attendanceCount.getOrDefault(nmec, 0L) + 1);
        }
    }

    return attendanceCount.entrySet().stream()
        .filter(entry -> entry.getValue() > (fraction * totalLectures))
        .map(entry -> personMap.get(entry.getKey()))
        .collect(Collectors.toSet());
}
```



the attendance counter for each nmec registered in lecture

In Turma.java

```
public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {
    int totalLectures = lectures.size();
    Map<Integer, Long> attendanceCount = new HashMap<>();


    for (Lecture lecture : lectures) {
        for (Integer nmec : lecture.getPresentPersons()) {
            attendanceCount.put(nmec, attendanceCount.getDefault(nmec, 0L) + 1);
        }
    }

    return attendanceCount.entrySet().stream()
        .filter(entry -> entry.getValue() > (fraction * totalLectures))
        .map(entry -> personMap.get(entry.getKey()))
        .collect(Collectors.toSet());
}
```

Similar to `d.get(nmec, 0)` in Python dictionaries

In Turma.java

```
public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {  
    int totalLectures = lectures.size();  
    Map<Integer, Long> attendanceCount = new HashMap<>();  
  
    for (Lecture lecture : lectures) {  
        for (Integer nmec : lecture.getPresentPersons()) {  
            attendanceCount.put(nmec, attendanceCount.getOrDefault(nmec, 0L) + 1);  
        }  
    }  
  
    return attendanceCount.entrySet().stream()  
        .filter(entry -> entry.getValue() > (fraction * totalLectures))  
        .map(entry -> personMap.get(entry.getKey()))  
        .collect(Collectors.toSet());  
}
```



Filter all nmec that have the counter above % over total lectures



```

public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {
    int totalLectures = lectures.size();
    Map<Integer, Long> attendanceCount = new HashMap<>();

    for (Lecture lecture : lectures) {
        for (Integer nmec : lecture.getPresentPersons()) {
            attendanceCount.put(nmec, attendanceCount.getOrDefault(nmec, 0L) + 1);
        }
    }

    return attendanceCount.entrySet().stream()
        .filter(entry -> entry.getValue() > (fraction * totalLectures))
        .map(entry -> personMap.get(entry.getKey()))
        .collect(Collectors.toSet());
}

```




Get from that list the actual Person reference

In Turma.java

```
public Set<Person> getPersonsWithAttendanceAboveThreshold(double fraction) {
    int totalLectures = lectures.size();
    Map<Integer, Long> attendanceCount = new HashMap<>();

    for (Lecture lecture : lectures) {
        for (Integer nmec : lecture.getPresentPersons()) {
            attendanceCount.put(nmec, attendanceCount.getOrDefault(nmec, 0L) + 1);
        }
    }

    return attendanceCount.entrySet().stream()
        .filter(entry -> entry.getValue() > (fraction * totalLectures))
        .map(entry -> personMap.get(entry.getKey()))
        .collect(Collectors.toSet());
}
```



Place in a Set to avoid repetitions

```

public class Main {
    public static void main(String[] args) {
        (...)

        Set<Person> frequentAttendees =
            turma.getPersonsWithAttendanceAboveThreshold(1.0 / 3);
        System.out.println("Persons present in more than 1/3 of the lectures: "
            + frequentAttendees);
    }
}

```

Note that changes within Turma do not imply changes in the rest of the code...
 The method `getPersonsWithAttendanceAboveThreshold` abstracts for the implementation and focus on the purpose