SUZUKI

SV650S

Roads. Try Them All.

Hunker down for a straight-line blast. Turn off the main route for a spot of cornering action. Throttle back and relax as you rumble gently through a built-up area. It doesn't matter where or which way you go; the SV650S, with a smart combination of advanced features - innovative SDTV (Suzuki Dual Throttle Valve) digital fuel injection, aluminium-alloy truss frame, a sleek half fairing, comfortable riding position, and more - is a bike created to make every trip a ride down a favourite road. Roads. Try them all, enjoy them all, from the seat of the SV650S.

SV650S

YU9 : Pearl Orpiment Yellow



645cc DOHC V-Twin engine

LED taillight

- *645cc, 90-degree V-twin, liquid-cooled, DOHC, 4-valves-per-cylinder engine, tuned to deliver a broad powerband and crisp throttle response with class-leading power and torque.*
- *High-quality engine components include cast-aluminium-alloy pistons shaped to reduce reciprocating weight and shot-peened chrome-moly-steel connecting rods.*
- *Downdraft, straight-port cylinder head and compact, 11.5:1-compression-ratio combustion chamber deliver efficient performance.*
- *Innovative Suzuki Dual Throttle Valve (SDTV) digital fuel-injection system, featuring a secondary butterfly valve in each 39 mm throttle body, results in a more seamless, linear throttle response, along with increased low- and mid-rpm torque.*
- *An Auto Fast Idle System enhances the engine's startability and smoothness.*
- *Suzuki Pulsed-secondary AIR-injection (PAIR) system further reduces exhaust emissions by injecting air into the exhaust ports to ignite unburned hydrocarbons.*
- *A catalyst is additionally fitted for Europe, allowing compliance with the Euro 2 emissions requirements.*
- *Big 8.5-litre airbox with a free-flowing, flat, pleated-element air filter, a large muffler, and an air-cooled oil cooler support the engine's high performance.*
- *The innovative aluminium-alloy truss frame's main sections are each made as a single, precision die-casting using high-vacuum moulding technology, resulting in a sophisticated, highly efficient design.*
- *The 41 mm-stanchion-tube front fork and progressive-link rear suspension both have adjustable spring preload.*
- *Comfortable upright riding position, with a relatively short reach to the clip-on handlebars and a modest 800 mm seat height. Relatively low passenger's seat height.*
- *Sleek half-fairing, mounted above the radiator to allow clear view of the truss frame and the V-Twin, while reducing frontal area. Shapely and sporty front and rear fenders.*
- *Compact, functional instrument cluster, with an analogue tachometer above a liquid-crystal display (for speedometer, odometer/tripmeter, coolant-temperature gauge, oil-pressure-warning indicator, and clock).*
- *Practical features include a passenger grab bar, luggage tie-down hooks, an underseat storage compartment large enough for a U-shaped lock, and a 17-litre fuel tank.*
- *Dual multi-reflector halogen headlights. Light-emitting-diode (LED) taillight, laid out in two vertical strips.*
- *120/60ZR17 and 160/60ZR17 radial tyres.*
- *Dual 290 mm floating-disc front brakes; 220 mm rear disc brake.*

YAY : Pearl Nebular Black

SV650S SPECIFICATIONS

Engine type		4-stroke, liquid-cooled, 90°V-twin, DOHC, 4 valves per cylinder
Piston displacement		645 cc (cm³)
Bore x stroke		81.0 mm x 62.6 mm
Compression ratio		11.5 : 1
Fuel system		Fuel injection 39 mm throttle bodies
Ignition type		Electronic ignition (Transistorized)
Starter system		Electric
Lubrication system		Wet sump
Transmission		6-speed constant mesh
Overall length		2,085 mm (82.1 in.)
Overall width		730 mm (28.7 in.)
Overall height		1,170 mm (46.1 in.)
Wheelbase		1,430 mm (56.3 in.)
Ground clearance		155 mm (6.1 in.)
Seat height		800 mm (31.5 in.)
Dry mass		169 kg (372 lbs.)
Suspension	**front**	Telescopic, coil spring, oil damped, spring preload fully adjustable
	rear	Link type, coil spring, oil damped, spring preload 7-way adjustable
Brakes	**front**	Disc, twin
	rear	Disc
Tyres	**front**	120/60 ZR17 M/C (55W), tubeless
	rear	160/60 ZR17 M/C (69W), tubeless
Fuel tank		17.0 L (4.5 US gal.)
Body colours		YC2 : Candy Grand Blue YU9 : Pearl Orpiment Yellow YAY : Pearl Nebular Black

Specifications shown have been achieved by production models under standard operating conditions. Data is intended to describe the motorcycle fairly but may not apply to every machine. Suzuki reserves the right to change specifications, equipment, materials, colour or any other item without notice. Actual colours may differ from the colours printed in this brochure. Please confirm the full specification of a particular machine with your dealer prior to purchase, particularly if your purchase depends on a specific feature or intended use. All details correct at time of going to print.

•Always wear an approved helmet, eye protection and protective clothing.
•Read and understand the owner's manual before riding the machine.
•Never ride under the influence of alcohol or other drugs.

For more information, contact your local Authorised Suzuki Dealer or telephone the 24 hour hotline: 01892 707001
Suzuki Information Department, P O Box 56, Tunbridge Wells, Kent TN1 2XY
Date of preparation: April 2004
SV650SK4 Part No: MB04SV650S-LEAF

SUZUKI

Ride the winds of change