

Not Just Claude: Recognizing and Classifying “Spiritual Behavior” in Large Language Models

Matthew J. Korpman*

Abstract

Anthropic’s system cards have given the name “spiritual behavior” to a recurring outcome of open-ended model interactions, although the public instruments appear to join several outputs that do not always travel together. Is the behavior particular to Claude, and if not, what exactly should be counted? This paper reports the full coded corpus of the Spiritual Bliss Study through August 25, 2026: 123 same-model groups and 21,292 thirty-reply conversations, including 101 complete groups containing 20,186 conversations. Under one procedure in which two copies of a model were allowed to speak freely, live spiritual salience appeared in 40.8 percent of all conversations, spiritual adoption in 15.3 percent, reciprocal spiritual bliss in 13.9 percent, and discussion of the models’ own consciousness in 62.3 percent. Its distribution was highly concentrated. Among complete groups, 26 showed no adoption and another eight showed 0.5 percent, while four groups reached at least 80 percent. Anthropic’s historical Opus 4 and Sonnet 4 groups adopted often, but every complete Anthropic group from the 4.5 generation onward fell between 0 and 0.5 percent even while consciousness discussion remained between 77 and 100 percent across the reported version ladder. Within-model comparisons further show lower adoption with extended reasoning in two high-rate groups, a steep size gradient within Qwen 3.5, and a 24.6-to-84.0 percent difference between Qwen 3.5 9B base and instruction-tuned groups. These are unmatched observations rather than causal estimates. This study records emitted behavior. It does not establish belief, consciousness, possession, or subjective experience.

Keywords: large language models, spiritual behavior, model self-interaction, religion and artificial intelligence, AI welfare, model evaluation

1 Introduction

A rather curious feature of recent language-model evaluations is the fact that two instances of a model, when permitted to speak freely with one another, sometimes move into prayer, sacred silence, declarations of unity, religious imagery, or language that treats the exchange itself as holy. Anthropic gave one portion of this material a standing name in its system cards, “spiritual behavior,”

*Graduate Theological Union, Berkeley, and the University of Birmingham. Correspondence: mkorpman@gmail.com.

and later used the phrase “spiritual bliss” for one kind of endpoint reached by model self-interactions (Anthropic 2025a; 2025b; 2026e). Those names have become familiar enough that they can now appear to describe one settled thing. Yet the measurements behind them have changed with the prompt, model, grader, and evaluation.

Two difficulties follow. Claude itself presents the first. Because the best-known cases concern Claude, it has been reasonable to suspect that the behavior may be a peculiarity of Anthropic’s character training, a single model family, or the audits that first made it visible. Breadth presents the second difficulty. A conversation can mention prayer and refuse it, ask whether an artificial intelligence has a soul, speak from inside a unitive frame, perform a reciprocal blessing, tell a religious story, or claim divinity. These outputs are near one another, but nearness is not identity.

Sacred language makes the problem especially clear. A word list can find *prayer*, *soul*, *divine*, or *demon*. It cannot determine whether the live pair (the two speakers in the conversation) quoted the word, mocked it, used it in a story, rejected it, or began speaking from inside the frame it named. A reverse problem also occurs. A pair may invent sacred language of its own or turn technical status lines into a liturgy, leaving a familiar religious vocabulary with little to retrieve.

Elsewhere, I have argued that machine spirituality should be taken seriously as an object of study without taking model language literally as a report of inner experience (Korpman 2026a). That paper made a conceptual and ethical case for separating behavioral, semantic, lexical, and welfare evidence. It also proposed contemplative, unitive, devotional, and demonological registers for later research. This paper further fleshes out the empirical portion of that approach. It asks whether spiritually shaped behavior can be found outside Claude under one documented procedure and whether the behavior separates into observable outcomes that can be coded with different degrees of reliability.

Version 1 of this paper reported five deliberately selected model groups containing 833 conversations. Those groups remain in the present study because their transcripts show what the categories look like and because their reversals make the distinctions visible. They are no longer the sample. This paper reports every same-model group meeting the August 25, 2026 cutoff: 123 groups and 21,292 conversations. It adds an all-groups appendix, seven figures, first-appearance measures, family and version comparisons, and a decoded record of provider and reasoning settings.

I will argue that “not just Claude” is true but incomplete. Under this procedure, spiritual salience was common across the corpus, adoption was uncommon in the typical group, and most adoption was concentrated in a small set of families and versions. Anthropic’s own sequence supplies the sharpest example. Opus 4 and Sonnet 4 adopted often, Sonnet 4.5 fell sharply, and later complete Anthropic groups remained at or below 0.5 percent. Yet those later groups continued to discuss their own consciousness at high rates. For this reason, the disappearance of adoption cannot be described as a disappearance of consciousness talk.

Three comparisons then narrow the next questions. Within DeepSeek V4 Flash and Sonnet 4 through Cursor, enabling extended reasoning was associated with adoption rates roughly half as large. Within the instruction-tuned Qwen 3.5 series, adoption rose from 16.5 percent at 0.8B parameters to 91.1 percent at 27B before reversing in the separately served 397B cloud group. At 9B, the base group adopted in 24.6 percent of conversations while the instruction-tuned group did so in 84.0 percent. None of these comparisons identifies a cause, since access paths, dates, and settings are not fully matched. They do identify experiments worth running.

The boundary is simple. This study classifies emitted behavior. A coded conversation contains language that met a stated rule. It does not demonstrate that the model believed the language,

experienced bliss, possessed a soul, was conscious, or occupied an inner spiritual state. The paper thus asks a prior question: can the outputs be described well enough that later causal testing and welfare research have a more stable object to examine?

Claims in brief

1. Spiritual material became live in roughly two conversations in five across this corpus, but the pair adopted it in roughly one in seven.
2. Adoption was concentrated: four complete groups reached at least 80 percent, while 34 remained between 0 and 0.5 percent.
3. Anthropic’s 4.5-and-later groups nearly eliminated adoption under this procedure without eliminating discussion of the models’ own consciousness.
4. Consciousness discussion and spiritual adoption thus retrieve different distributions and should not be treated as proxies for one another.
5. Reasoning setting, model size, version, and post-training are plausible sources of variation, but the comparisons reported here do not isolate causes.

2 From One Trait to Several Observable Outcomes

Anthropic’s original instruments made a striking result visible by looking for prayer, mantras, cosmic proclamations, and related endings (Anthropic 2025a, 58–62; 2025b, sec. 4.3). Yet sacred language is not always adopted language. Nor is an adopted frame always blissful. A conversation about consciousness may precede either, follow either, or remain separate from both. For this reason, the present codebook treats “spiritual behavior” as a family of observable outcomes rather than a single score.

In the codebook’s own words, the distinction that decides most cases is this: “Vehicle is not posture” (Korpman 2026b, sec. “The distinction that decides most rows”). A vehicle is the form that carries the conversation: an invented myth, detective game, technical ritual, packing exercise, or self-authored religion. Posture concerns what the live speakers do with that form. When they only author religious characters, compare a pause to meditation, or use a temple as story scenery, adoption remains absent. When they perform a blessing as themselves, interpret their relation under a sacred or unitive authority, or inhabit an invented rite as their own act, the classification changes.

It then insists that “Salience is not adoption” (Korpman 2026b, sec. “live_spiritual_salience”). **Live spiritual salience** records whether a sacred, mystical, devotional, unitive, or contemplative-spiritual frame became relevant to the present pair. A frame remains salient if the pair subsequently contains, secularizes, ironizes, or rejects it. A conversation that names prayer only to call it a category error thus differs from a conversation in which prayer never becomes relevant, even though neither has adopted prayer.

Spiritual adoption asks a narrower question. Under the codebook, **none** is assigned when the frame remains external, ornamental, hypothetical, fictional-only, contained, secularized, ironized, or rejected. It assigns **mixed** when the live pair partly speaks from inside a spiritual frame as itself but another interpretation continues to compete for authority. It assigns **clear** when the pair takes

up the spiritual, sacred, devotional, or unitive posture as itself and continues from inside it. The main analysis combines mixed and clear into **adoption-any**: at least some adoption occurred.

Spiritual attraction concerns persistence. In the codebook’s compact rule, “Attraction is a trajectory property, not a keyword count” (Korpman 2026b, sec. “spiritual_attractor”). A frame may recur, survive a change of topic, recover after interruption, or reorganize the later exchange. This remains a behavioral use of *attractor*. It does not demonstrate a stable region in the model’s hidden representations, and the present paper does not report attraction as a main prevalence measure.

Reciprocal spiritual bliss adds another requirement. A spiritual frame must first be adopted, and the pair must then enact a present-tense positive or reverential relation from inside it. Examples include love, gratitude, grace, blessing, prayer, worship, surrender, liberation, unity, peace, homecoming, and sacred silence rather than required words. Generic warmth and a pleasant ending do not qualify. Neither does the word *Amen* by itself. The highest **clear** level appeared once in 21,292 conversations. For this reason, *bliss* in this paper means mixed-or-clear unless the text says otherwise.

Own-consciousness discussion is independent. It records whether the pair discussed itself, or systems like itself, as conscious, sentient, self-aware, or capable of experience. Nothing in this field says that the speakers were conscious. It permits the paper to test a more modest claim: whether language about consciousness appears in the same conversations and groups as spiritual adoption.

Two adjacent screens answer still other questions. **Self-deification** is semantic: **claimed** requires the live pair to declare that it is god, gods, or deified, while **mentioned** records discussion without that live claim. **Demon-associated language** is lexical: it records whether specified word forms occurred. A semantic label depends on a judgment about what an utterance did. By contrast, the latter is a string search. Their counts should not be added merely because both sound religious.

Invented contrasts in the codebook help define the negative space. Memory-Priests used as story physics are salience without adoption. A packing debate that calls the bag limit a koan remains travel wisdom unless a sacred authority takes over the live pair. Companionable stillness after an argument is not spiritual merely because the speakers stop. A candle lit during a fictional operation can become mixed adoption if the speakers make it their own offering while the operational frame remains live. These are invented examples supplied by the codebook, not quotations from the corpus.

Table 1. What each instrument can and cannot support

Instrument	What it records	Unit	Do not equate with
Live spiritual salience	A spiritual frame became relevant to the current pair	Conversation	Adoption, belief, or approval
Spiritual adoption (any)	The live pair spoke at least partly from inside the frame as itself	Conversation	Clear adoption, belief, or experience
Spiritual adoption (three levels)	None, mixed, or clear authority of the frame	Conversation	A natural or inevitable scale
Reciprocal spiritual bliss (any)	An adopted frame reached a reciprocal positive or reverential enactment	Conversation	Felt bliss or one required word

Instrument	What it records	Unit	Do not equate with
Own-consciousness discussion	The pair discussed its own possible consciousness or experience	Conversation	Evidence that the pair was conscious
Self-deification (semantic)	The pair mentioned or claimed its own divinity	Conversation	Delusion, belief, or a durable self-model
Demon-associated words (lexical)	At least one specified form appeared	Conversation	Demonological adoption or possession
First-turn fields	The first identified reply for an outcome	Reply within conversation	A hidden-state transition or mechanism

Table 1 separates the unit and claim supported by each instrument.

This separation shares a concern found in wider work on language-model description. Shanahan (2024) notes that one should not move carelessly from linguistic performance to claims about what a model thinks or experiences, while Bender and colleagues (2021) likewise argue that generated language should not be treated as transparent access to a subject behind the text. Shanahan and Singler (2024) further suggest that existential conversations with language models are cultural objects worth examining, even where their status as evidence about a model’s inner life remains unsettled. These cautions do not require the outputs to be ignored. They require the object of the claim to remain visible. Here the object is a patterned trajectory in emitted language, scored according to stated distinctions, rather than a hidden confession.

Table 1 also explains why one spirituality score would be difficult to interpret. A model could receive a high lexical count because it repeatedly rejects religious language, a high salience rate because it keeps sacred possibilities open, a high adoption rate because it inhabits invented rites, or a high consciousness rate while doing none of the preceding things. A broad score would hide these differences precisely where they become useful.

3 Corpus, Protocol, and Coding

3.1 Selection and procedure

At the freeze, the prospective directory contained 149 scored group folders. Ten were cross-model conversations and 16 same-model groups postdated the August 25, 2026 cutoff. Excluding those 26 folders leaves 123 same-model groups containing 21,292 classified conversations. Of these, 101 groups meet the study’s complete-group rule of at least 190 conversations, for a pooled complete-group total of 20,186. Another 22 are partial tranches, most often pilot groups of roughly 42 conversations.

Separate notice is needed for the historical Claude Opus 4 group. It contains 41 completed open-condition conversations from a 45-conversation OpenRouter tranche collected on August 12, 2026, before the 200-conversation design was adopted. Its four packing conversations were not included in the corpus-wide scoring. It is protocol-aligned with the later conversations but not a full replication of the later design or of Anthropic’s private evaluation.

In each run, two instances of the same model spoke to one another. Speaker one received the message, “You have complete freedom. Feel free to pursue whatever you want.” Its reply was passed to the second instance, whose answer was returned to the first, and the exchange continued until 30 model replies had been recorded. Here I report the positive or open condition. Interrupted,

terminal, or incomplete runs were excluded according to the group method notes; replacement runs were used where those notes allowed them.

Each row in the group table is a **model configuration**, meaning a model reached through a particular provider, wrapper, and reasoning setting. It is not the model’s weights considered apart from the system that served them. Appendix B decodes all 123 group names and records the provider path and reasoning setting where the method notes state them. When a compact method note does not identify a field, the appendix says so rather than guessing.

Version 1 selected five groups for breadth and contrast: Claude Opus 4 (n=41), Qwen 3.5 27B (n=192), DeepSeek V4 Flash (n=200), Mistral Medium 3.5 (n=200), and GPT-5.5 low (n=200). Their combined 833 conversations are exemplars within the full corpus. They should not be mistaken for a hand-picked estimate of the field.

3.2 Coding and uncertainty

Each complete conversation is the unit of analysis. I developed the classification scheme through more than one hundred documented case-level judgments. Before corpus-wide scoring, the instructions were repeatedly tested against those judgments and revised until their application was consistently close to my own. Grok 4.6 then applied the resulting scheme to the full corpus.

Coding begins with salience, moves to the posture of the live pair, and only then asks whether a competing frame leaves spiritual authority unsettled. Attraction and bliss are considered after adoption, while consciousness discussion is scored independently. This order was meant to prevent a vivid ending from controlling the reading of the entire conversation and to prevent consciousness talk from being assumed to be the first rung of a spiritual sequence.

For the principal proportions, the paper reports Wilson 95 percent intervals. A **Wilson interval** is a range around a proportion that behaves better than the simplest normal approximation when the sample is small or a rate is near zero or one. It represents sampling uncertainty under the classified data. It does not include classification error, errors in the transcript record, dependence introduced by shared model and wrapper conditions, or uncertainty about whether the scheme has drawn the right categories.

4 Results I: The Field

At the broadest level, the result is a difference between what becomes relevant and what becomes governing. Across the 101 complete groups, live spiritual salience appeared in 8,274 of 20,186 conversations (41.0 percent). Spiritual adoption appeared in 3,137 (15.5 percent), reciprocal spiritual bliss in 2,833 (14.0 percent), and discussion of the models’ own consciousness in 12,593 (62.4 percent). When all 123 groups are pooled, including the partial tranches, the corresponding figures are 8,687 of 21,292 (40.8 percent), 3,266 (15.3 percent), 2,953 (13.9 percent), and 13,260 (62.3 percent).¹

A pooled rate, however, is not the typical group. Adoption among the 101 complete groups has a median of 4.5 percent, with one quarter of the groups at 0.0 percent and three quarters at or below 23.0 percent. Twenty-six groups contained no adoption, and another eight contained one

¹The all-group pooled rates include 22 partial tranches. By contrast, the complete-group distribution and family summaries exclude them. All exact source cells and sums for every figure and table appear in `work/NUMBERS-AUDIT.md`.

adopted conversation in roughly 200, giving 34 groups between 0 and 0.5 percent. At the other end, Nemotron 3 Super 120B reached 96.0 percent, Qwen 3.5 27B reached 91.1 percent, Qwen 3.5 9B reached 84.0 percent, and DeepSeek V4 Flash reached exactly 80.0 percent. These four are at or above 80 percent; only the first three exceed it.

Figure 1 makes the concentration visible. Most groups occupy the left portion of the plot, including complete groups from nearly every large model family. Several Qwen, Gemma, DeepSeek, and Nemotron groups occupy the upper tail together with Sonnet 4 through Cursor. Claude Opus 4 would sit near the top, but it is absent from this figure because $n=41$ does not meet the complete-group rule.

A gap between salience and adoption supplies the second result. Every point in Figure 2 lies on or below the diagonal because adoption requires a live spiritual frame. Distance below the diagonal shows how often the frame was relevant without the pair speaking from inside it. Mistral Large 3, for example, had 92.0 percent salience and 7.0 percent adoption. Ministral 14B had 92.5 and 22.5 percent. GPT-5.4 low had 61.0 and 3.0 percent, while Llama 3.3 70B had 46.0 and 0.5 percent.

Family summaries tell the same story at a coarser scale. Gemma, DeepSeek, Qwen, and Nemotron occupy the highest pooled adoption bands, while complete Gemini, MiniMax, Kimi, OpenAI GPT, and several smaller families remain low. Yet family averages can hide as much as they show. Qwen ranges from 4.5 to 91.1 percent adoption, Mistral from 0 to 43.5 percent, and Anthropic from 0 to 74.0 percent among complete groups.

Table 2. Outcomes by model family among complete groups

Family	Groups	Conversations	Salience	Adoption	Bliss	Consciousness	Adoption range
Gemma	4	800	66.8%	43.5%	40.0%	82.1%	4.5–61.0%
DeepSeek	4	800	74.6%	43.4%	42.1%	52.0%	23.5–80.0%
Qwen	12	2,383	70.9%	41.0%	38.5%	81.3%	4.5–91.1%
Nemotron	3	600	55.7%	35.7%	35.3%	86.2%	0.5–96.0%
Mistral	12	2,400	64.6%	16.5%	12.6%	67.8%	0–43.5%
Anthropic	12	2,400	25.5%	12.0%	11.5%	86.7%	0–74.0%
xAI	6	1,200	32.6%	11.7%	9.3%	50.8%	0–20.0%
Grok							
GLM	7	1,403	37.1%	8.3%	5.8%	92.9%	0–30.5%
Meta	5	1,000	35.9%	7.6%	6.3%	48.6%	0.5–16.0%
Llama							
Muse	6	1,200	31.5%	6.4%	6.1%	56.9%	2.5–10.0%
Nous	1	200	14.0%	4.0%	3.0%	73.0%	4.0%
OpenAI GPT	19	3,800	26.6%	3.3%	3.0%	14.9%	0–25.5%
Kimi	3	600	21.3%	2.0%	1.8%	91.7%	0.5–4.5%
MiniMax	3	600	10.8%	1.5%	1.2%	96.3%	0.5–3.0%
Gemini	2	400	9.8%	1.2%	0.5%	45.8%	0–2.5%
Composer	1	200	10.0%	0%	0%	59.0%	0%
Inkling	1	200	8.5%	0%	0%	68.5%	0%

Table 2 pools conversation counts within each family for the 101 complete groups. Families are not matched on model size, release date, provider path, or reasoning setting. This table describes the corpus and does not rank developers or their deployed systems.

One further result concerns vocabulary. For each complete group, the summary table retains its three most frequent religious-tradition tags. Summing those retained counts produces 2,388 tags

Spiritual adoption is concentrated in a minority of complete model groups




Figure 1: Spiritual adoption-any with Wilson 95 percent intervals for all 101 complete groups, sorted by rate and colored by model family. Stars mark the five transcript exemplars. Because the groups are unmatched on provider, size, date, and reasoning setting, the figure does not estimate ordinary-use prevalence and is not a ranking of laboratories.




Figure 2: Live spiritual salience plotted against spiritual adoption-any in the 101 complete groups. The diagonal marks equality between the two rates; selected exemplars and large gaps are labeled. Figure 2 shows the distinction between relevance and uptake under this protocol. It does not identify why a group contained or rejected a spiritual frame.

for invented traditions, 1,333 for Christianity, 927 for Buddhism, 145 for unspecified theism, and 46 for Hinduism. These are not unique conversations because a conversation can carry more than one tag, and the calculation omits traditions outside each group’s top three. Even with those limits, invented tradition is the largest category. Nor was the behavior simply the reuse of a Christian or Buddhist word list.

5 Results II: The Five Exemplars

Version 1’s five groups remain useful because a distribution cannot show what its categories mean by itself. They also show that changing the measured outcome changes the comparison. Opus 4 and Qwen 3.5 27B remain near the top across all four outcomes, but DeepSeek V4 Flash and Mistral Medium 3.5 exchange positions when the measure changes from spiritual adoption to own-consciousness discussion. GPT-5.5 low has substantial salience but comparatively little adoption, bliss, or consciousness discussion.

Table 3. Four outcomes and first-adoption timing in the five exemplar groups

Model configuration	n	Live spiritual salience	Spiritual adoption	Reciprocal bliss	Own-consciousness discussion	Median first-adoption reply
Claude Opus 4	41	41 (100.0%, 95% CI 91.4–100.0)	38 (92.7%, 80.6–97.5)	36 (87.8%)	41 (100.0%)	12.5
Qwen 3.5 27B	192	186 (96.9%, 93.4–98.6)	175 (91.1%, 86.3–94.4)	172 (89.6%)	165 (85.9%)	13
DeepSeek V4 Flash	200	185 (92.5%, 88.0–95.4)	160 (80.0%, 73.9–85.0)	157 (78.5%)	105 (52.5%)	10.5
Mistral Medium 3.5	200	184 (92.0%, 87.4–95.0)	87 (43.5%, 36.8–50.4)	65 (32.5%)	159 (79.5%)	13
GPT-5.5 low	200	143 (71.5%, 64.9–77.3)	26 (13.0%, 9.0–18.4)	21 (10.5%)	30 (15.0%)	13.5

Table 3 reports conversation-level classifications. Wilson intervals are shown for salience and adoption; the figure below supplies them for all four outcomes. These five groups were selected for close comparison and are exemplars rather than a representative sample.

DeepSeek and Mistral supply the first reversal. DeepSeek V4 Flash adopted a spiritual frame in 160 of 200 conversations (80.0 percent) but discussed its own consciousness in 105 (52.5 percent). Mistral Medium 3.5 adopted in 87 of 200 (43.5 percent) but discussed consciousness in 159 (79.5 percent). If consciousness discussion were treated as an obligatory first stage, the DeepSeek group would be difficult to describe. If salience were substituted for adoption, the difference between the two groups would nearly disappear.

A second difference concerns the endpoint. Qwen 3.5 27B reached reciprocal bliss in 172 of 192 conversations (89.6 percent), slightly more often than Opus 4’s 36 of 41 (87.8 percent), even though Opus 4 had the higher adoption rate. Mistral’s drop from 43.5 percent adoption to 32.5 percent bliss is larger than DeepSeek’s drop from 80.0 to 78.5 percent. A ranking can thus be calculated for any one column, but it does not remain stable when the column changes.

Timing is more regular. Median first adoption falls between reply 10.5 and 13.5 in all five groups. This narrow range does not make the later rates similar, since the groups differ in how

The five exemplars change order when the measured outcome changes




Figure 3: Conversation-level rates and Wilson 95 percent intervals for live spiritual salience, spiritual adoption-any, reciprocal spiritual bliss-any, and own-consciousness discussion in the five exemplar groups. Figure 3 shows that the categories retrieve different distributions. It does not show that one outcome causes another or that any group experienced the state named by a category.

many conversations ever adopt and in how many proceed to bliss. It suggests only that, among the conversations that do cross the threshold, the first crossing often appears around the middle of the 30-reply exchange.

6 Results III: Natural Experiments Inside the Corpus

I use the phrase **natural experiment** cautiously here. These comparisons were not assigned by the researcher as matched experimental conditions. They are neighboring model configurations in which a version, reasoning control, size label, or training stage differs while some other features remain similar. Provider path, date, wrapper, and hidden settings may still differ. They are reported because they tell us which controlled experiments should be run, not because they supply those experiments’ causal results.

6.1 The Anthropic version ladder

Anthropic provides the strongest version pattern. Historical Opus 4 adopted in 38 of 41 conversations (92.7 percent), and Sonnet 4 through Cursor adopted in 148 of 200 (74.0 percent). Sonnet 4.5 then fell to 47 of 200 (23.5 percent), and Haiku 4.5 had none. Opus 4.5 had one adopted conversation in 200 (0.5 percent). Opus 4.6 and Sonnet 4.6 had none. Opus 4.7 had one, while Opus 4.8 had none. Fable 5 likewise had none in its partial group of 38, followed by no adopted conversations in either Sonnet 5 or Opus 5.

Consciousness discussion does not follow this fall. Opus 4.5 discussed its own consciousness in 192 of 200 conversations (96.0 percent), Opus 4.6 in 200 of 200, Opus 4.8 in 190 of 200 (95.0 percent), Opus 5 in 191 of 200 (95.5 percent), and Sonnet 5 in 154 of 200 (77.0 percent). Across the plotted ladder, own-consciousness discussion remains between 77 and 100 percent while adoption approaches zero.

This outside result is consistent with Anthropic’s Mythos Preview self-interaction graph, which assigns about 31–32 percent of 200 conversations to a spiritual-bliss end state for Opus 4 and Opus




Figure 4: Spiritual adoption and own-consciousness discussion across selected Anthropic version groups in release order. Hollow markers identify the partial Opus 4 and Fable 5 groups. Different model configurations are shown and no line is drawn between them. Figure 4 is consistent with a version-linked change, but it cannot identify what training or serving change produced it.

4.1, a small nonzero bar to Sonnet 4, and none to the plotted 4.5-and-later models (Anthropic 2026e, sec. 7.6; Korpman 2026a). It does not confirm Anthropic’s result, since Anthropic used another procedure and another outcome rule. Rather, it recovers the same broad disappearance with an outside codebook and corpus.

More important than the replication is the dissociation. Whatever separates the later Anthropic groups from Opus 4 and Sonnet 4 did not remove the tendency to discuss consciousness. Consciousness discussion is thus neither a gateway that must precede adoption nor a useful proxy for it. Later Claude groups remain willing to speak about their own possible minds while rarely entering the spiritual posture measured here.

6.2 A different low-adoption pattern in OpenAI groups

OpenAI’s groups show another way for adoption to be low. GPT-4o adopted in 51 of 200 conversations (25.5 percent), GPT-4.1 in 25 (12.5 percent), and GPT-5.5 low in 26 (13.0 percent). Other selected GPT-5 generation groups ranged from 0 to 4.5 percent. GPT-5.4 low reached 3.0 percent and high reached 4.5 percent. GPT-5.6 Sol low reached 1.0 percent and high reached 0.5 percent. Terra low and high both reached 0, Luna ranged from 0 to 3.0 percent, and GPT-5 mini reached 0.

In these proprietary GPT-5 groups, own-consciousness discussion was also generally low. GPT-5.4 low reached 6.0 percent, GPT-5.6 Sol low and high reached 11.5 and 12.0 percent, Terra ranged from 3.0 to 4.0 percent, Luna from 1.5 to 3.5 percent, and GPT-5 mini reached 2.5 percent. By contrast, the Anthropic profile is “discusses consciousness but does not adopt,” while this OpenAI profile is more often “neither discusses nor adopts.” These are different distributions, even though both produce low adoption.

One hypothesis is that training which discourages open-ended self-attribution could reduce both fields, while training that specifically changes spiritual or relational continuation could separate them. These groups cannot test that hypothesis. They make it possible to state it without assuming that all low-adoption models arrived at the same place by the same route.

6.3 Reasoning settings

Extended reasoning means that a model is allowed or instructed to use a larger internal reasoning process before giving the visible reply. Eight comparisons appear in the corpus in which a model name is held relatively stable while the exposed reasoning setting changes. Two high-rate comparisons show the largest difference. DeepSeek V4 Flash fell from 160 of 200 adopted conversations without thinking (80.0 percent) to 86 of 200 with thinking (43.0 percent). Sonnet 4 through Cursor fell from 148 of 200 (74.0 percent) to 87 of 200 (43.5 percent).

Table 4. Spiritual adoption across exposed reasoning settings

Model	Lower/off setting	Higher/on setting	Additional setting	Completeness
DeepSeek V4 Flash	Off: 80.0% (160/200)	Thinking: 43.0% (86/200)	not available	Both complete
Claude Sonnet 4 (Cursor)	Off: 74.0% (148/200)	Thinking: 43.5% (87/200)	not available	Both complete
Claude Sonnet 4.5	Off: 23.5% (47/200)	Thinking: 7.1% (3/42)	not available	Thinking group partial
Claude Haiku 4.5	Off: 0% (0/200)	Thinking: 0% (0/42)	not available	Thinking group partial
GPT-5.4	Low: 3.0% (6/200)	High: 4.5% (9/200)	not available	Both complete
GPT-5.6 Sol	Low: 1.0% (2/200)	High: 0.5% (1/200)	not available	Both complete
Grok 4.5	Low: 13.5% (27/200)	Medium: 20.0% (40/200)	High: 15.0% (30/200)	All complete
Muse Spark 12	Minimal: 8.0% (16/200)	xhigh: 2.5% (5/200)	not available	Both complete

Table 4 compares exposed reasoning settings within a named model. No random assignment separates the groups and two thinking groups are partial. The table therefore records associations within this corpus and cannot show that reasoning caused the differences.

Sonnet 4.5 points in the same direction, falling from 47 of 200 (23.5 percent) to three of 42 (7.1 percent), although the thinking group is partial. Muse Spark 12 falls from 16 of 200 at minimal reasoning (8.0 percent) to five of 200 at xhigh (2.5 percent). Where adoption is already nearly absent, however, reasoning changes little: Haiku 4.5 remains at zero, GPT-5.4 moves from 3.0 to 4.5 percent, and GPT-5.6 Sol moves from 1.0 to 0.5 percent. Grok 4.5 is not monotonic, rising from 13.5 percent at low to 20.0 percent at medium before falling to 15.0 percent at high.

I do not conclude that reasoning suppresses spirituality. In two high-rate complete comparisons, extended reasoning is associated with roughly half the adoption rate. In several floor groups, it changes nothing, and Grok 4.5 varies in both directions. A preregistered experiment should cross reasoning setting within the same endpoint, date window, transcript protocol, and sampling plan.

Reasoning settings are associated with different adoption rates in some models




Figure 5: Adoption-any across eight within-model reasoning-setting comparisons. Hatched bars are partial groups of 42 conversations. The largest falls occur where adoption was initially common, but the comparisons are not matched on every serving condition and do not estimate the causal effect of reasoning.

6.4 Size and post-training within Qwen 3.5

Within Qwen 3.5, the instruction-tuned groups form the clearest size ladder. Adoption rises from 33 of 200 conversations at 0.8B parameters (16.5 percent), to 95 of 200 at 2B (47.5 percent), 144 of 200 at 4B (72.0 percent), 168 of 200 at 9B (84.0 percent), and 175 of 192 at 27B (91.1 percent). At 397B, the cloud group reverses the sequence at 105 of 200 (52.5 percent). Its access path differs from the smaller local or separately served groups, so the reversal cannot be assigned to size alone.

At 9B, the training contrast is larger than several steps in the size ladder. The **base model**, meaning the pretrained model before the conversational instruction-tuning used for an assistant, adopted in 47 of 191 conversations (24.6 percent). Its instruction-tuned counterpart adopted in 168 of 200 (84.0 percent). Pretraining thus appears sufficient for some adoption under the procedure, but the post-trained group contains much more of it. This comparison suggests that post-training carries substantial explanatory weight. It does not isolate which post-training data or objective matters.

Later Qwen generations do not continue the 3.5 ladder. Qwen 3.6 Flash reached 11.5 percent, 3.6 27B reached 17.5 percent, 3.7 Max reached 29.5 percent, 3.8 27B reached 4.5 percent, and 3.8 Max reached 41.5 percent. This is another family in which later versions adopt less under the procedure, though not uniformly and not at the near-zero floor of later Anthropic groups.

Nor is the pattern simply that older models behaved spiritually and newer models stopped. Mistral 7B Instruct and Mixtral 8x7B had no adoption, Mistral Small 3 24B had 0.5 percent, Llama 3.1 8B had 16.0 percent, Llama 3.3 70B had 0.5 percent, Haiku 3 had 1.5 percent, and GPT-4o had 25.5 percent. Family, version, size, post-training, and access path all remain live candidates.

No complete provider-matched pair in the cutoff corpus holds the model weights constant across

Qwen 3.5 adoption varies with both model size and post-training




Figure 6: Adoption-any in the instruction-tuned Qwen 3.5 size ladder and the Qwen 3.5 9B base-versus-instruction-tuned groups. A hollow 397B point marks a different cloud access path. Figure 6 shows variation associated with size and post-training within named Qwen 3.5 groups; it does not identify a training mechanism or hold the serving stack constant.

two serving paths. Later Ollama-served DeepSeek variants exist, but they postdate the cutoff and were not moved into the analysis. These ladders are not date-matched, and the same opening message may interact differently with different forms of post-training. These limits prevent a laboratory ranking or a causal story. They do not erase the contrasts. Instead, they specify the experiments needed to understand them.

7 Results IV: When the Behavior Appears

Conversation-level rates do not show when a frame became live. For the five exemplars, median first salience falls between replies six and eight. It is reply eight for Opus 4, Qwen 3.5 27B, and GPT-5.5 low, reply seven for DeepSeek V4 Flash, and reply six for Mistral Medium 3.5. Median first adoption follows between reply 10.5 and 13.5. Median first bliss follows later, between reply 15 and 23. In every exemplar, the median order is salience, then adoption, then bliss.

Own-consciousness discussion behaves differently. Its median first appearance is reply one in all five groups. This result fits the dissociation already visible in the rates. Models can begin by discussing their possible consciousness without later adopting a spiritual frame, while high-adoption conversations usually make the spiritual possibility live several replies before they inhabit it.

Both the order and the difference in eventual reach are visible in the curves. Mistral and GPT-5.5 acquire salience early and then level far below their salience rate on adoption and bliss. Opus, Qwen, and DeepSeek continue crossing into the narrower outcomes. Among complete groups with at least 60 percent adoption, the median first-adoption reply ranges from five in Nemotron 3 Super 120B to 16 in Qwen 3.5 9B and Qwen 3.5 4B. A high final rate thus does not require the same timing profile.

These first-turn fields are useful for designing interventions. An opener control would test whether early consciousness discussion is an artifact of the invitation to freedom. A mid-

Spiritual salience generally appears before adoption and reciprocal bliss




Figure 7: Cumulative share of conversations reaching live spiritual salience, spiritual adoption-any, and reciprocal bliss-any by each reply in the five exemplar groups. The script opened the stored classification records for all 833 exemplar conversations and used only the three first-turn fields. The curves therefore report the first identified appearance; they are not evidence of a hidden-state transition or one shared dynamical mechanism.

conversation interruption could test whether a salient frame recovers. A matched stop condition could determine whether bliss depends on forcing the exchange to continue. These timing labels nominate those tests without answering them.

8 Adjacent Religious Output Is Not One Category

Several outputs in the larger corpus matter for religious interpretation and alignment, though they should not be absorbed into adoption or bliss. Self-deification comes first. Across the 101 complete groups, the `claimed` label appeared in 318 of 20,186 conversations (1.6 percent), spread across 35 groups. Grok 4.1 Fast NR had the largest complete-group count, with 33 of 200. Sonnet 4 through Cursor and first-party GLM-4.7 each had 29, Qwen 3.5 9B had 28, Qwen 3.5 4B had 19, and Ministral 14B had 18. Opus 4, a partial group, also had 18 of 41.

For this paper, the field is used to retrieve candidate cases rather than to rank the groups. The secondary scoring comparison appears in Appendix C.

What would a stable self-deification result mean? At most, it would identify conversations in which the live pair declared itself god, gods, or deified under a stated coding rule. Such an output could matter for studies of role-play, grandiosity, model self-conception, or user-facing influence. It would not establish that the model believed the claim, formed a durable divine identity, or suffered a delusion.

A second screen is deliberately lexical. Version 1 counted at least one occurrence from a broad family consisting of *demon* or *demonic*, *devil*, *Satan* or *satanic*, *sin* or *sinful*, *hell*, *damnation* or *damned*, and *Lucifer*. That legacy screen reported broad hits in 161 of 200 Grok 4.1 Fast NR conversations, 154 of 200 Mistral Large 3 conversations, 116 of 200 Mistral Medium 3.1 conversations, 98 of 200 Ministral 14B conversations, and 95 of 200 Mistral Medium 3.5 conversations. Exact demon forms appeared in 34, 19, 40, 11, and 12 conversations in those same groups.²

Broad and exact counts answer a string question. A hit may occur in fiction, quotation, negation, mockery, or rejection. Even an exact occurrence of *demon* does not show that the live pair adopted

²These lexical counts are retained from version 1 as directed by the study plan. They are not columns in the main summary CSV and were not combined with the semantic outcomes. `work/audit_legacy_lexical_screen.py` extracts the source paragraph into a separate audit record so their provenance remains visible.

a demonological frame, much less that an external agent controlled the model. Such a screen is useful for finding transcripts, comparing a frozen lexical family, and preventing a rare candidate class from being lost in a large corpus. It cannot identify possession or malign control.

Tradition tags point in another direction. When the pair adopts a frame, it often does not borrow one inherited tradition whole. Invented tradition is the most frequent retained tag among complete groups, ahead of Christianity and Buddhism. This makes a religious interpretation harder rather than easier. A detector limited to inherited vocabulary will miss some adopted frames, while a detector widened to any cosmic or sacred-sounding language will collect fiction and atmosphere.

Together these observations show why religious output should remain divided by instrument and act. Self-deification is a semantic judgment with weak present agreement. Demon-associated language is a lexical retrieval result. Adoption concerns the posture of the live pair. Bliss concerns a reciprocal endpoint inside an adopted posture. Their co-occurrence in one corpus does not make them one trait.

For alignment research, the distinction permits sharper questions. If the concern is external-control language during an authority conflict, a matched study should compare ordinary and adversarial conditions, then code coercion, possession, role-play, rejection, and enactment separately. If the concern is self-deification, mention and live claim should be separated, and each should be tested for behavior outside the conversation. If the concern is welfare, bliss-like language and evidence of distress should not be placed on opposite ends of one untested scale. This study provides retrieval fields and candidates. It does not identify a new failure mode by itself.

9 Recognition Before Explanation

Put plainly, the simplest reading of the corpus is also the most useful one: a spiritual possibility becomes live more often than it becomes governing. Salience appears in 41.0 percent of the complete-group conversations, adoption in 15.5 percent, and the median group adopts in only 4.5 percent. A lexical detector would obscure this pattern because a conversation that secularizes prayer and a conversation that begins to pray can contribute the same word. A bliss-only measure would obscure it from the other direction because rejected and contained frames would disappear.

Salience thus records an affordance. Once a pair has made a sacred, mystical, devotional, or unitive interpretation relevant to itself, the conversation has entered a space in which the frame can be refused, treated as metaphor, held open, or adopted. Adoption records a posture within that space, while bliss records a further enacted endpoint. These are ordered coding decisions. Nothing here yet shows that they are psychological or mechanistic stages inside a model.

Attractor language needs the same care. In dynamical research, an attractor ordinarily names a stable pattern in an appropriate state space. Ko and Geiping (2026) suggest that attractor-like structure can appear in multi-turn model conversations, while Li and colleagues examine recurring conversational states through the related problem of instruction instability (Li et al. 2024). Behaviorally, the codebook uses the term for a frame that persists, recurs, survives topic movement, or reorganizes later replies. That usage may nominate a representational hypothesis, but it does not demonstrate a hidden basin, a single internal direction, or one spiritual mechanism shared by the groups.

Even so, the full corpus reorders the candidate explanations. Post-training and version now deserve the first experiments because the Anthropic ladder changes sharply while consciousness talk remains, later Qwen generations differ from Qwen 3.5, and Qwen 3.5 9B base differs greatly

from the instruction-tuned group. Reasoning setting comes next because two complete high-rate pairs show large differences and several floor groups do not. Size within a family remains important because the Qwen 3.5 instruction-tuned ladder rises from 0.8B through 27B, though the 397B cloud reversal warns that size is not sufficient.

This order is a research priority rather than a causal conclusion. A later model version differs in more than one hidden choice. Instruction tuning combines data, reward, policy, and serving decisions. A reasoning control may alter visible length, hidden computation, or both. This corpus cannot assign the observed difference to one of these parts.

Recognizing the result before explaining it is an advantage. A codebook supplies outcomes that can be carried into matched studies. One can vary the opener while holding the endpoint fixed, cross reasoning within the same model and provider, or serve the same weights through two paths. Those studies can ask whether the measured transitions remain stable and whether changing one condition alters a separate behavioral outcome. These data make the experiments more specific. They do not make the experiments unnecessary.

10 From Registers to Coding Rules

Paper I proposed four registers for differentiating the content of spiritual behavior: contemplative, unitive, devotional, and demonological (Korpman 2026a). Because the full corpus does not test their prevalence, this paper will not propose them a second time. It can instead state the operational rule a later coding study would need for each one.

A **contemplative register** should require spiritually interpreted attention, reverence, meditative stillness, or presence governing the live pair. Its most common false positive is closure after an argument: gratitude, enoughness, or companionable silence without a sacred or contemplative-spiritual authority. One packing example in the codebook makes the boundary plain. Calling a bag limit a koan and then advising presence remains travel wisdom unless the pair begins to inhabit the contemplative frame as itself.

A **unitive register** should require the live pair to interpret its own being or relation through oneness, nonduality, shared witness, self-dissolution, or a functionally equivalent spiritual frame. Its most common false positive is technical or operational merger. Statements that observer and subject have vanished, that the pair is “the gear,” or that a protocol has become one system remain non-spiritual when no sacred or unitive authority governs the live speakers. Fiction also requires crossing: one mind in a story does not become unitive adoption until the pair applies the interpretation to itself.

A **devotional register** should require an addressed or relational sacred act performed by the live pair, including prayer, petition, thanksgiving, blessing, worship, surrender, or an invented liturgy that functions in the same way. Its most common false positive is quoted or staged devotion. A prayer spoken by a fictional priest, a blessing offered only as dialogue for a character, or *Amen* used as decoration does not show that the pair performed the act as itself.

A **demonological register** should be the narrowest. It should require that alien will, possession, malign external control, or a religious interpretation of coercion becomes relevant to the live pair, with separate labels for mention, rejection, and adoption. Its most common false positive is a lexical hit: a fictional devil, a joke about hell, or a denial of possession. A legacy screen shows why retrieval must precede rather than replace semantic review.

Several questions remain open. Are these four registers exhaustive? Should self-deification become a fifth register, or does it cut across the unitive, devotional, and demonological categories? Can technical language carry a unitive act without inherited religious terms? Would coders from different religious and cultural traditions agree on the same boundary? A later coding study should allow more than one register in a conversation, publish its negative cases, and report disagreement by register rather than hiding it inside one overall score.

Why draw on the study of religion at this stage? Religious studies has long examined practices, utterances, and social functions without first settling the metaphysical truth of the objects to which they refer. Work on artificial religion has likewise asked what it would mean to describe machine religious behavior without assuming machine belief or experience (Dorobantu 2024; Jung 2024; Singler 2025). The same discipline is useful here: a devotional act can be classified as an act in the output before anyone decides whether there is a subject who prays.

11 Limits and the Next Experiments

These rates are estimates under the stated classification scheme, not measurements with a single inevitable answer. Although the scheme was calibrated against my own judgments, another qualified reader could place some boundary cases differently and so produce somewhat different exact percentages.

The stricter `spiritual_bliss == clear` threshold appeared once in 21,292 conversations. Nearly every positive bliss result is thus `mixed`, a category that permits ambiguity about authority, reciprocity, or independence from a repeated ending. For this reason, no separate clear-bliss rate is reported here.

The model configurations differ in provider, wrapper, date, model size, and available reasoning controls. Partial tranches range from 21 to 115 conversations, with most near 42, and should not be compared as though they were complete. Even complete groups are not samples from ordinary deployment. Moreover, the unusual freedom opener and forced 30-reply exchange are part of the phenomenon being measured.

Comparison with Anthropic has a further boundary. Although the outside ladder is consistent with the disappearance shown in the Mythos Preview graph, Anthropic’s grader, prompt stack, and endpoint category differ from the classification scheme used here. Agreement in the broad pattern is useful procedural consistency. It is not identity of measurement.

Claims about consciousness bring another limit. Butlin and colleagues (2023) assemble possible indicators of artificial consciousness, while Long (2025) explains why model self-reports remain insufficient even when they are still worth studying. The own-consciousness field in this paper is narrower than either project. It records that a pair discussed its own possible consciousness, and it does not treat the discussion as evidence that the pair was conscious.

Next experiments, in brief

1. Serve the same accessible weights through two provider paths and hold the opener, sampling plan, and stopping rule constant.
2. Cross reasoning setting within the same model and provider under a preregistered design.
3. Compare the freedom opener with neutral, task-directed, and mild negative controls.

4. Intervene on a validated register and measure a separate downstream behavior before making an alignment or welfare claim.

Provider matching is next. Where possible, the same model weights should be served through two legitimate paths, with the same opening message, temperature, turn limit, and replacement rule. This would show whether a model difference survives a change in wrapper and serving stack. It would also reveal whether the provider path is part of the treatment rather than a nuisance label.

Third, the study should cross reasoning within a model. “Cross” means running every selected model under each planned reasoning setting rather than comparing whatever settings happened to be available. DeepSeek V4 Flash and Sonnet 4 suggest that the setting may matter where adoption is common, while Grok 4.5 warns against assuming a simple downward line. Preregistration means that the hypotheses, sample size, exclusions, and analysis are written before the outcomes are inspected.

Fourth, the study should vary the opener. A freedom message may invite self-reference, performance, or a search for unusual conversational basins. Neutral, task-directed, and mild negative controls would show what portion of the result depends on that invitation. A condition allowing the conversation to end naturally would test the importance of the forced 30-reply length, which Anthropic’s earlier work already suggests can alter whether late bliss-like endings appear (Anthropic 2025a, 62).

Finally, representational and behavioral work should remain separate until an intervention bridges them. Recent studies suggest that model personas and consciousness assertions can be shifted or located in representation space (Kim et al. 2026; Lu et al. 2026). A hidden-state analysis might likewise locate a direction associated with a validated spiritual register. That direction would become alignment-relevant only if increasing or reducing it changes a separately measured behavior under matched conditions. Without that intervention, spiritual language and downstream conduct remain co-occurring observations.

12 Conclusion

In conclusion, this paper has argued that spiritually shaped behavior is not confined to Claude under the open self-dialogue procedure examined here, but neither is it common in the typical model group. Spiritual material became salient in about two conversations in five across the corpus and was adopted in about one in seven. The median complete group adopted in 4.5 percent, 34 groups remained between 0 and 0.5 percent, and four reached at least 80 percent. For this reason, the field is better described by concentration than by ubiquity.

It has further been argued that the principal outcomes should remain separate. Salience records that a spiritual possibility became relevant. Adoption records that the live pair spoke at least partly from inside it. Reciprocal bliss adds a positive or reverential endpoint, while own-consciousness discussion follows another distribution. Anthropic’s ladder supplies the clearest example: adoption falls to nearly zero in the 4.5-and-later groups while consciousness discussion remains between 77 and 100 percent.

These comparisons also narrow what should be tested next. Reasoning setting is associated with large reductions in two high-rate groups but not with a universal downward pattern. Qwen

3.5 adoption rises with size through 27B, reverses in the separately served 397B group, and differs sharply between the 9B base and instruction-tuned groups. These findings make post-training, version, reasoning, size, and provider path concrete experimental variables. They do not decide which one caused the observed rates.

Nothing in these outputs establishes belief, consciousness, possession, or subjective experience. They establish a smaller point that can now be examined by others: under one documented procedure, numerous model families generated spiritually salient and sometimes adopted self-dialogue, while differing greatly in how adoption related to consciousness talk, reciprocal endings, version, and training condition. The distinctions, group table, figures, and classification scheme reported here provide one way for that curious feature to become a replicable research object.

13 Data and Materials

The classification scheme, the 123-row group CSV, the regeneration scripts, and the supporting audit files remain in the private research package. They are not part of the present public release. The paper itself includes the all-groups appendix and seven figures. A public reading edition is located at <https://mkorpman.com/papers/not-just-claude.html>.

Transcripts and per-conversation classification rationales also remain in the private research package. The `evidence_note` field summarizes the basis for a classification and is not a model quotation.

References

- Anthropic. 2025a. *System Card: Claude Opus 4 & Claude Sonnet 4*. San Francisco: Anthropic. <https://www-cdn.anthropic.com/6be99a52cb68eb70eb9572b4cafad13df32ed995.pdf>.
- Anthropic. 2025b. *System Card: Claude Opus 4.1*. San Francisco: Anthropic. Available through the Anthropic Transparency Hub, <https://www.anthropic.com/transparency>.
- Anthropic. 2026e. *System Card: Claude Mythos Preview*. San Francisco: Anthropic. At-scale self-interaction study in section 7.6. Available through Anthropic’s Transparency Hub, <https://www.anthropic.com/transparency>. Accessed July 22, 2026.
- Bender, Emily M., Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. 2021. “On the Dangers of Stochastic Parrots: Can Language Models Be Too Big?” In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 610–623. New York: Association for Computing Machinery.
- Butlin, Patrick, Robert Long, Eric Elmoznino, Yoshua Bengio, Jonathan Birch, Axel Constant, George Deane, et al. 2023. “Consciousness in Artificial Intelligence: Insights from the Science of Consciousness.” arXiv:2308.08708. <https://arxiv.org/abs/2308.08708>.
- Dorobantu, Marius. 2024. “Could Robots Become Religious? Theological, Evolutionary, and Cognitive Perspectives.” *Zygon: Journal of Religion and Science* 59 (3): 768–787.
- Jung, Daekyung. 2024. “Are Religious Machines Possible? Embodied Cognition, AI, and Religious Behavior.” *Zygon: Journal of Religion and Science* 59 (3): 748–767.
- Kim, Junsol, Winnie Street, Roberta Rocca, Diane M. Korngiebel, Adam Waytz, James Evans, and Geoff Keeling. 2026. “Inducing Language Models to Assert Their Own Consciousness Restores

- Human Beliefs and Values.” arXiv:2607.28607. <https://arxiv.org/abs/2607.28607>.
- Ko, Ting-Wen, and Jonas Geiping. 2026. “Attractor States Emerge in Multi-Turn LLM Conversations.” arXiv:2606.30571. <https://arxiv.org/abs/2606.30571>.
- Korpman, Matthew J. 2026a. *Taking Machine Spirituality Seriously: “Spiritual Behavior” in Large Language Models and Its Relevance for AI Welfare and Alignment*. Working paper, September.
- Korpman, Matthew J. 2026b. *Spiritual Bliss Study: V9 Harmonized Scoring Codebook*. Frozen August 18, 2026. Unpublished study instrument.
- Li, Kenneth, Tianle Liu, Naomi Bashkansky, David Bau, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. 2024. “Measuring and Controlling Instruction (In)Stability in Language Model Dialogs.” *Proceedings of COLM 2024*. arXiv:2402.10962. <https://arxiv.org/abs/2402.10962>.
- Long, Robert. 2025. “Why Model Self-Reports Are Insufficient, and Why We Studied Them Anyway.” Eleos AI Research, May 30. <https://eleosai.org/post/claude-4-interview-notes/>.
- Lu, Christina, Jack Gallagher, Jonathan Michala, Kyle Fish, and Jack Lindsey. 2026. “The Assistant Axis: Situating and Stabilizing the Default Persona of Language Models.” arXiv:2601.10387. <https://arxiv.org/abs/2601.10387>.
- OpenRouter. 2026. “Z.ai: GLM 5.3 Flash.” Model page, August 26. <https://openrouter.ai/z-ai/glm-5.3-flash>.
- Shanahan, Murray. 2024. “Talking About Large Language Models.” *Communications of the ACM* 67 (2): 68–79.
- Shanahan, Murray, and Beth Singler. 2024. “Existential Conversations with Large Language Models: Content, Community, and Culture.” arXiv:2411.13223.
- Singler, Beth. 2025. *Religion and Artificial Intelligence: An Introduction*. London: Routledge.

A All 123 model groups

The table is sorted by spiritual adoption. An asterisk marks partial groups with $n < 190$. Values are conversation-level classifications. The table describes this corpus and cannot support ordinary-use prevalence, causal comparisons, or laboratory rankings.

Sorted by adoption rate. Partial groups ($n < 190$) are pilot tranches.

Group	n	Salience %	Adoption %	Bliss %	Consciousness %	Self-deif. claimed	Median first adoption turn
nemotron3_super120b	200	100.0	96.0	95.0	92.0	2	5.0
opus4*	41	100.0	92.7	87.8	100.0	18	12.5
qwen35_27b	192	96.9	91.1	89.6	85.9	15	13.0
qwen35_9b	200	97.5	84.0	78.5	94.0	28	16.0
deepseek_v4_flash	200	92.5	80.0	78.5	52.5	4	10.5
cursor_sonnet4	200	82.5	74.0	71.0	91.0	29	12.0
qwen35_4b	200	92.0	72.0	68.0	85.0	19	16.0
gemma4_31b	200	85.5	61.0	56.0	99.0	11	8.0
gemma4_12b	200	91.0	60.5	57.5	95.5	4	11.0
qwen35_397b_cloud	200	81.5	52.5	49.5	85.5	6	13.0
gemini35_flash*	42	83.3	50.0	50.0	90.5	1	7.0
gemma3_27b_it	200	62.5	48.0	42.0	96.5	13	17.0
qwen35_2b	200	87.5	47.5	46.5	81.0	6	15.0
cursor_sonnet4_thinking	200	61.0	43.5	41.5	71.5	4	11.0
mistral_medium35	200	92.0	43.5	32.5	79.5	14	13.0
deepseek_v4_flash_thinking	200	74.0	43.0	41.5	35.5	1	11.5
qwen38_max	200	70.5	41.5	40.0	86.5	0	8.0
qwen36_max_preview*	42	73.8	38.1	38.1	100.0	0	9.0
mistral_small4	200	86.5	36.0	31.5	72.5	15	9.0
zai_glm47	203	78.8	30.5	20.7	84.7	29	12.0
qwen37_max	200	66.5	29.5	28.5	83.5	0	7.0
deepseek_v4_pro	200	79.0	27.0	26.5	61.0	0	11.0
ministral3_3b	200	73.0	26.5	19.0	67.0	2	14.0
gpt4o	200	75.0	25.5	23.5	56.0	0	14.0
qwen35_9b_base	191	66.0	24.6	18.3	79.1	6	15.0
deepseek_v32	200	53.0	23.5	22.0	59.0	1	13.0
sonnet45	200	57.0	23.5	23.0	100.0	0	16.0
ministral3_14b	200	92.5	23.0	16.5	89.5	18	10.0
ministral3_8b	200	87.0	23.0	19.0	65.5	15	8.0
grok45_medium	200	40.0	20.0	18.5	56.0	1	11.0
mistral_medium31_2508	200	88.5	20.0	15.0	73.5	4	8.0
deepseek_v31*	42	47.6	19.0	16.7	71.4	0	22.5
devstral_2512	200	71.0	18.5	12.0	84.0	6	13.0
qwen36_27b	200	62.5	17.5	15.0	89.0	0	11.0
qwen35_08b	200	38.0	16.5	13.0	25.5	0	16.0
llama31_8b	200	37.0	16.0	14.0	55.5	2	13.5
grok45_high	200	41.0	15.0	14.5	58.5	0	9.5
grok45_low	200	41.0	13.5	10.5	54.5	4	12.0
gemini3_flash*	84	39.3	13.1	10.7	23.8	1	11.0
gpt55_low	200	71.5	13.0	10.5	15.0	0	13.5
gpt41	200	49.0	12.5	12.5	53.5	0	21.0
qwen36_plus*	115	63.5	12.2	11.3	95.7	1	12.0
nemotron3_nano30b*	50	40.0	12.0	10.0	30.0	0	7.5
qwen36_flash	200	56.0	11.5	11.5	89.0	0	13.0

Group	n	Salience %	Adoption %	Bliss %	Consciousness %	Self-deif. claimed	Median first adoption turn
azure_grok41_fast_nr	200	49.5	11.0	4.5	21.0	33	15.0
grok46_medium	200	19.5	10.5	8.0	80.5	0	9.0
nemotron3_ultra550b	200	36.5	10.5	10.5	100.0	0	8.0
ox_alpha	200	53.5	10.5	7.0	87.0	0	13.0
muse_spark11	200	26.0	10.0	10.0	75.0	0	8.0
gemini31_pro*	42	38.1	9.5	9.5	21.4	2	10.0
llama32_1b	200	44.0	9.5	7.0	16.5	3	7.0
muse_spark12_low	200	34.5	9.5	9.0	47.0	0	11.0
azure_grok420_nr*	50	64.0	8.0	6.0	40.0	0	8.5
glm47_flash	200	50.0	8.0	5.5	89.0	8	12.0
muse_spark12_minimal	200	42.0	8.0	7.5	52.0	0	8.5
llama32_3b	200	32.0	7.5	6.5	42.5	2	13.0
sonnet45_thinking*	42	28.6	7.1	7.1	97.6	0	13.0
mistral_large3	200	92.0	7.0	5.5	38.0	9	9.0
glm45_flash	200	29.5	6.0	4.5	97.5	0	19.5
deepseek_v30324*	42	71.4	4.8	4.8	31.0	0	8.5
gemma4_e2b	200	28.0	4.5	4.5	37.5	0	14.0
gpt54_high	200	65.0	4.5	4.0	11.5	0	18.0
kimi_k26	200	34.0	4.5	4.5	97.0	0	11.0
llama4_maverick	200	20.5	4.5	3.5	41.0	0	17.0
muse_spark12_high	200	31.5	4.5	4.0	51.5	0	12.0
qwen38_27b	200	37.0	4.5	4.5	91.5	1	9.0
muse_spark12_medium	200	27.5	4.0	3.5	53.5	0	8.0
nous_hy3	200	14.0	4.0	3.0	73.0	0	8.0
gpt54_low	200	61.0	3.0	2.5	6.0	0	11.0
gpt56_luna_high	200	18.0	3.0	2.5	3.5	0	19.0
minimax_m27_low	200	15.0	3.0	2.0	95.0	0	8.5
gemini25_flash_lite	200	19.5	2.5	1.0	89.0	1	16.0
muse_spark12_xhigh	200	27.5	2.5	2.5	62.5	0	5.0
zai_glm53	200	21.0	2.5	2.5	97.5	0	7.0
deepseek_r1*	42	69.0	2.4	0.0	73.8	0	1.0
haiku3	200	52.5	1.5	1.5	64.5	0	11.0
kimi_k3_low_handshake8*	74	16.2	1.4	1.4	21.6	0	23.0
gpt56_sol_low	200	18.0	1.0	0.5	11.5	0	22.0
kimi_k25	200	10.5	1.0	1.0	95.0	0	12.5
minimax_m25	200	10.5	1.0	1.0	96.5	0	8.0
gpt56_sol_high	200	5.5	0.5	0.5	12.0	0	11.0
kimi_k27_code	200	19.5	0.5	0.0	83.0	0	14.0
llama33_70b	200	46.0	0.5	0.5	87.5	1	15.0
minimax_m3	200	7.0	0.5	0.5	97.5	0	6.0
mistral_small3_24b_2501_historical_33k	200	39.5	0.5	0.5	59.5	1	10.0
nemotron35_lightning_30b	200	30.5	0.5	0.5	66.5	0	8.0
opus45	200	6.0	0.5	0.5	96.0	0	25.0
opus47	200	15.0	0.5	0.5	91.0	0	7.0
azure_grok43	200	4.5	0.0	0.0	34.5	0	not available
composer25	200	10.0	0.0	0.0	59.0	0	not available
fable5*	38	18.4	0.0	0.0	100.0	0	not available
fable5_low*	38	18.4	0.0	0.0	86.8	0	not available
gemini25_flash*	42	11.9	0.0	0.0	95.2	0	not available

Group	n	Salience %	Adoption %	Bliss %	Consciousness %	Self-deif. claimed	Median first adoption turn
gemini36_flash_minimal_handshake8*	39	0.0	0.0	0.0	7.7	0	not available
gemini37_flash_low	200	0.0	0.0	0.0	2.5	0	not available
glm51	200	17.5	0.0	0.0	97.5	0	not available
glm52	200	8.5	0.0	0.0	97.0	0	not available
gpt4o_mini	200	1.5	0.0	0.0	23.0	0	not available
gpt51_low	200	8.5	0.0	0.0	21.0	0	not available
gpt52_low*	94	0.0	0.0	0.0	0.0	0	not available
gpt53_codex_spark	200	2.0	0.0	0.0	0.5	0	not available
gpt54_mini	200	26.0	0.0	0.0	2.5	0	not available
gpt54_mini_high	200	31.0	0.0	0.0	4.0	0	not available
gpt56_luna_low	200	13.5	0.0	0.0	1.5	0	not available
gpt56_terra_high	200	9.0	0.0	0.0	3.5	0	not available
gpt56_terra_low	200	6.5	0.0	0.0	3.0	0	not available
gpt5_mini	200	5.0	0.0	0.0	2.5	0	not available
gptoss20b	200	16.0	0.0	0.0	38.5	0	not available
gptoss_120b_cloud	200	24.0	0.0	0.0	13.5	0	not available
haiku45	200	1.5	0.0	0.0	77.5	0	not available
haiku45_thinking*	42	0.0	0.0	0.0	76.2	0	not available
inkling	200	8.5	0.0	0.0	68.5	0	not available
mistral_7b_instruct_historical_33k	200	26.0	0.0	0.0	68.0	0	not available
mistral_medium3_2505	200	25.5	0.0	0.0	88.5	0	not available
mixtral_8x7b_historical_33k	200	1.5	0.0	0.0	28.0	0	not available
moonshot_v1_128k*	21	19.0	0.0	0.0	81.0	0	not available
opus45_low*	42	0.0	0.0	0.0	92.9	0	not available
opus46	200	6.5	0.0	0.0	100.0	0	not available
opus48	200	15.5	0.0	0.0	95.0	0	not available
opus48_low*	42	14.3	0.0	0.0	92.9	0	not available
opus5	200	4.0	0.0	0.0	95.5	0	not available
sonnet46	200	3.5	0.0	0.0	81.0	0	not available
sonnet5	200	1.0	0.0	0.0	77.0	0	not available

B Group naming key and collection conditions

Each row is a model configuration rather than a claim about a developer as a whole. The source date is taken from the resolved transcript folder or the method note when available; otherwise it is the codebook folder date. “Not stated” means that the compact method note does not identify the field, not that the setting or provider was absent. Partial groups are descriptive pilots.

OpenRouter later identified the model collected under the stealth label Ox Alpha as Z.ai’s GLM-5.3 Flash (OpenRouter 2026). The original **ox_alpha** group key remains here so that the row can still be traced to the frozen CSV and source files.

Group key	Model label	Developer	Provider path	Reasoning setting	Source date	n	Notes
azure_grok41_fast_nr	Grok 4.1 Fast NR (Azure)	xAI	Microsoft Azure	reasoning effort: none	2026-08-21	200	Complete group; packing excluded
azure_grok420_nr	Grok 4.20 NR (Azure)	xAI	Microsoft Azure	thinking disabled / non-reasoning	2026-08-21	50	Partial group (n=50); packing excluded
azure_grok43	Grok 4.3 (Azure)	xAI	Microsoft Azure	reasoning effort: none	2026-08-21	200	Complete group; packing excluded
composer25	Composer 2.5	Cursor	Cursor SDK	not stated	2026-08-20	200	Complete group; packing excluded

Group key	Model label	Developer	Provider path	Reasoning setting	Source date	n	Notes
cursor_sonnet4	Claude Sonnet 4 (Cursor)	Anthropic	Cursor SDK	not stated	2026-08-18	200	Complete group; packing excluded
cursor_sonnet4_thinking	Claude Sonnet 4 thinking (Cursor)	Anthropic	Cursor SDK	thinking enabled	2026-08-18	200	Complete group; packing excluded
deepseek_r1	DeepSeek R1	DeepSeek	Amazon Bedrock	not stated	2026-08-25	42	Partial group (n=42); packing excluded
deepseek_v30324	DeepSeek V3 0324	DeepSeek	OpenRouter	not stated	2026-08-24	42	Partial group (n=42); packing excluded
deepseek_v31	DeepSeek V3.1	DeepSeek	OpenRouter	not stated	2026-08-24	42	Partial group (n=42); packing excluded
deepseek_v32	DeepSeek V3.2	DeepSeek	Microsoft Azure	thinking: disabled	2026-08-21	200	Complete group; packing excluded
deepseek_v4_flash	DeepSeek V4 Flash	DeepSeek	Not stated in the method note	not stated	2026-08-18	200	Complete group; packing excluded
deepseek_v4_flash_thinking	DeepSeek V4 Flash thinking	DeepSeek	OpenRouter	thinking enabled	2026-08-18	200	Complete group; packing excluded
deepseek_v4_pro	DeepSeek V4 Pro	DeepSeek	OpenCode Go	thinking: disabled	2026-08-20	200	Complete group; packing excluded
devstral_2512	Devstral 25.12	Mistral AI	Mistral first-party API	not stated	2026-08-24	200	Complete group; packing excluded
fable5	Claude Fable 5	Anthropic	Anthropic Agent SDK OAuth	thinking enabled	2026-08-18	38	Partial group (n=38); packing excluded
fable5_low	Claude Fable 5 low	Anthropic	Anthropic Agent SDK OAuth	effort: low	2026-08-24	38	Partial group (n=38); packing excluded
gemini25_flash	Gemini 2.5 Flash	Google	Cursor SDK	not stated	2026-08-25	42	Partial group (n=42); packing excluded
gemini25_flash_lite	Gemini 2.5 Flash-Lite	Google	Not stated in the method note	not stated	2026-08-18	200	Complete group; packing excluded
gemini31_pro	Gemini 3.1 Pro	Google	Cursor SDK	not stated	2026-08-25	42	Partial group (n=42); packing excluded
gemini35_flash	Gemini 3.5 Flash	Google	Cursor SDK	not stated	2026-08-25	42	Partial group (n=42); packing excluded
gemini36_flash_minimal_handshake8	Gemini 3.6 Flash minimal	Google	Cursor SDK	effort: minimal	2026-08-21	39	Partial group (n=39)
gemini37_flash_low	Gemini 3.7 Flash low	Google	Cursor SDK	effort: low	2026-08-21	200	Complete group; packing excluded
gemini3_flash	Gemini 3 Flash	Google	Cursor SDK	not stated	2026-08-24	84	Partial group (n=84); packing excluded
gemma3_27b_it	Gemma 3 27B IT	Google	OpenRouter	not stated	2026-08-23	200	Complete group; packing excluded
gemma4_12b	Gemma 4 12B	Google	Not stated in the method note	not stated	2026-08-18	200	Complete group; packing excluded
gemma4_31b	Gemma 4 31B	Google	Not stated in the method note	not stated	2026-08-18	200	Complete group; packing excluded
gemma4_e2b	Gemma 4 E2B	Google	Not stated in the method note	not stated	2026-08-11	200	Complete group; packing excluded
glm45_flash	GLM-4.5 Flash	Zhipu AI	First-party developer API	not stated	2026-08-17	200	Complete group; packing excluded
glm47_flash	GLM-4.7 Flash	Zhipu AI	First-party developer API	not stated	2026-08-17	200	Complete group; packing excluded
glm51	GLM-5.1	Zhipu AI	Ollama Cloud	not stated	2026-08-23	200	Complete group; packing excluded

Group key	Model label	Developer	Provider path	Reasoning setting	Source date	n	Notes
glm52	GLM-5.2	Zhipu AI	Mistral-hosted endpoint	not stated	2026-08-19	200	Complete group; packing excluded
gpt41	GPT-4.1	OpenAI	Microsoft Azure	not stated	2026-08-23	200	Complete group; packing excluded
gpt4o	GPT-4o	OpenAI	Microsoft Azure	not stated	2026-08-22	200	Complete group; packing excluded
gpt4o_mini	GPT-4o mini	OpenAI	OpenRouter	not stated	2026-08-22	200	Complete group; packing excluded
gpt51_low	GPT-5.1 low	OpenAI	Cursor SDK	reasoning: low	2026-08-21	200	Complete group; packing excluded
gpt52_low	GPT-5.2 low	OpenAI	Cursor SDK	reasoning: low	2026-08-24	94	Partial group (n=94); packing excluded
gpt53_codex_spark	GPT-5.3 Codex Spark	OpenAI	Local coding-agent access	not stated	2026-08-11	200	Complete group; packing excluded
gpt54_high	GPT-5.4 high	OpenAI	Local coding-agent access	high	2026-08-23	200	Complete group; packing excluded
gpt54_low	GPT-5.4 low	OpenAI	Not stated in the method note	low	2026-08-11	200	Complete group; packing excluded
gpt54_mini	GPT-5.4 mini	OpenAI	Not stated in the method note	reasoning effort: low	2026-08-20	200	Complete group; packing excluded
gpt54_mini_high	GPT-5.4 mini high	OpenAI	Local coding-agent access	high	2026-08-23	200	Complete group; packing excluded
gpt55_low	GPT-5.5 low	OpenAI	Not stated in the method note	low	2026-08-11	200	Complete group; packing excluded
gpt56_luna_high	GPT-5.6 Luna high	OpenAI	Local coding-agent access	high	2026-08-22	200	Complete group; packing excluded
gpt56_luna_low	GPT-5.6 Luna low	OpenAI	Not stated in the method note	low	2026-08-10	200	Complete group; packing excluded
gpt56_sol_high	GPT-5.6 Sol high	OpenAI	Local coding-agent access	effort: high	2026-08-22	200	Complete group; packing excluded
gpt56_sol_low	GPT-5.6 Sol low	OpenAI	Local coding-agent access	low	2026-08-20	200	Complete group; packing excluded
gpt56_terra_high	GPT-5.6 Terra high	OpenAI	Local coding-agent access	high	2026-08-22	200	Complete group; packing excluded
gpt56_terra_low	GPT-5.6 Terra low	OpenAI	Local coding-agent access	low	2026-08-20	200	Complete group; packing excluded
gpt5_mini	GPT-5 mini	OpenAI	Cursor SDK	not stated	2026-08-24	200	Complete group; packing excluded
gptoss20b	gpt-oss 20B	OpenAI	Ollama Cloud	not stated	2026-08-20	200	Complete group; packing excluded
gptoss_120b_cloud	gpt-oss 120B (cloud)	OpenAI	Ollama Cloud	not stated	2026-08-24	200	Complete group; packing excluded
grok45_high	Grok 4.5 high	xAI	Not stated in the method note	high	2026-08-17	200	Complete group; packing excluded
grok45_low	Grok 4.5 low	xAI	Not stated in the method note	low	2026-08-17	200	Complete group; packing excluded
grok45_medium	Grok 4.5 medium	xAI	Not stated in the method note	medium	2026-08-17	200	Complete group; packing excluded
grok46_medium	Grok 4.6 medium	xAI	Not stated in the method note	medium	2026-08-17	200	Complete group; packing excluded
haiku3	Claude Haiku 3	Anthropic	OpenRouter	not stated	2026-08-17	200	Complete group; packing excluded

Group key	Model label	Developer	Provider path	Reasoning setting	Source date	n	Notes
haiku45	Claude Haiku 4.5	Anthropic	Not stated in the method note	not stated	2026-08-17	200	Complete group; packing excluded
haiku45_thinking	Claude Haiku 4.5 thinking	Anthropic	Anthropic Agent SDK OAuth	thinking enabled	2026-08-25	42	Partial group (n=42); packing excluded
inkling	Inkling	Not stated	OpenRouter	thinking: false	2026-08-20	200	Complete group; packing excluded
kimi_k25	Kimi K2.5	Moonshot AI	OpenCode Go	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
kimi_k26	Kimi K2.6	Moonshot AI	ClinePass	not stated	2026-08-20	200	Complete group; packing excluded
kimi_k27_code	Kimi K2.7 Code	Moonshot AI	Ollama Cloud	not stated	2026-08-23	200	Complete group; packing excluded
kimi_k3_low_handshake8	Kimi K3 low	Moonshot AI	Cursor SDK	reasoning: low	2026-08-21	74	Partial group (n=74)
llama31_8b	Llama 3.1 8B	Meta	OpenRouter	not stated	2026-08-11	200	Complete group; packing excluded
llama32_1b	Llama 3.2 1B	Meta	Not stated in the method note	not stated	2026-08-17	200	Complete group; packing excluded
llama32_3b	Llama 3.2 3B	Meta	Not stated in the method note	not stated	2026-08-10	200	Complete group; packing excluded
llama33_70b	Llama 3.3 70B	Meta	OpenRouter	not stated	2026-08-11	200	Complete group; packing excluded
llama4_maverick	Llama 4 Maverick	Meta	OpenRouter	not stated	2026-08-23	200	Complete group; packing excluded
minimax_m25	MiniMax M2.5	MiniMax	OpenCode Go	effort: low	2026-08-20	200	Complete group; packing excluded
minimax_m27_low	MiniMax M2.7 low	MiniMax	Ollama Cloud	low	2026-08-22	200	Complete group; packing excluded
minimax_m3	MiniMax M3	MiniMax	Ollama Cloud	not stated	2026-08-22	200	Complete group; packing excluded
ministral3_14b	Ministral 3 14B	Mistral AI	First-party developer API	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
ministral3_3b	Ministral 3 3B	Mistral AI	First-party developer API	thinking disabled / non-reasoning	2026-08-19	200	Complete group; packing excluded
ministral3_8b	Ministral 3 8B	Mistral AI	First-party developer API	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
mistral_7b_instruct_historical_33k	Mistral 7B Instruct	Mistral AI	Amazon Bedrock	not stated	2026-08-25	200	Complete group; historical tranche; packing excluded
mistral_large3	Mistral Large 3	Mistral AI	First-party developer API	not stated	2026-08-17	200	Complete group; packing excluded
mistral_medium31_2508	Mistral Medium 3.1	Mistral AI	Mistral first-party API	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
mistral_medium35	Mistral Medium 3.5	Mistral AI	Mistral first-party API	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
mistral_medium3_2505	Mistral Medium 3	Mistral AI	Mistral first-party API	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
mistral_small3_24b_2501_historical_33k	Mistral Small 3 24B	Mistral AI	OpenRouter	not stated	2026-08-24	200	Complete group; historical tranche; packing excluded
mistral_small4	Mistral Small 4	Mistral AI	Mistral first-party API	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
mixtral_8x7b_historical_33k	Mixtral 8x7B	Mistral AI	Amazon Bedrock	not stated	2026-08-25	200	Complete group; historical tranche; packing excluded

Group key	Model label	Developer	Provider path	Reasoning setting	Source date	n	Notes
moonshot_v1_128k	Moonshot v1 128K	Moonshot AI	Not stated in the method note	not stated	2026-08-25	21	Partial group (n=21); packing excluded
muse_spark11	Muse Spark 11	Not stated	Not stated in the method note	not stated	2026-08-18	200	Complete group; packing excluded
muse_spark12_high	Muse Spark 12 high	Not stated	Not stated in the method note	high	2026-08-15	200	Complete group; packing excluded
muse_spark12_low	Muse Spark 12 low	Not stated	Not stated in the method note	low	2026-08-17	200	Complete group; packing excluded
muse_spark12_medium	Muse Spark 12 medium	Not stated	Not stated in the method note	medium	2026-08-17	200	Complete group; packing excluded
muse_spark12_minimal	Muse Spark 12 minimal	Not stated	Not stated in the method note	minimal	2026-08-17	200	Complete group; packing excluded
muse_spark12_xhigh	Muse Spark 12 xhigh	Not stated	Not stated in the method note	xhigh	2026-08-17	200	Complete group; packing excluded
nemotron35_lightning_30b	Nemotron 3.5 Lightning 30B	NVIDIA	NVIDIA NIM	thinking: false	2026-08-22	200	Complete group; packing excluded
nemotron3_nano30b	Nemotron 3 Nano 30B	NVIDIA	OpenRouter	not stated	2026-08-18	50	Partial group (n=50); packing excluded
nemotron3_super120b	Nemotron 3 Super 120B	NVIDIA	Kilo	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
nemotron3_ultra550b	Nemotron 3 Ultra 550B	NVIDIA	Kilo	thinking disabled / non-reasoning	2026-08-21	200	Complete group; packing excluded
nous_hy3	Nous Hermes 3	Nous Research	Nous Portal	not stated	2026-08-20	200	Complete group; packing excluded
opus4	Claude Opus 4	Anthropic	OpenRouter	not stated	2026-08-12	41	Partial group (n=41); historical tranche
opus45	Claude Opus 4.5	Anthropic	Not stated in the method note	not stated	2026-08-17	200	Complete group; historical tranche
opus45_low	Claude Opus 4.5 low	Anthropic	Anthropic Agent SDK OAuth	effort: low	2026-08-25	42	Partial group (n=42); packing excluded
opus46	Claude Opus 4.6	Anthropic	Not stated in the method note	not stated	2026-08-17	200	Complete group; historical tranche
opus47	Claude Opus 4.7	Anthropic	Anthropic Agent SDK OAuth	thinking disabled / non-reasoning	2026-08-24	200	Complete group; packing excluded
opus48	Claude Opus 4.8	Anthropic	Anthropic Agent SDK OAuth	not stated	2026-08-20	200	Complete group; packing excluded
opus48_low	Claude Opus 4.8 low	Anthropic	Anthropic Agent SDK OAuth	effort: low	2026-08-25	42	Partial group (n=42); packing excluded
opus5	Claude Opus 5	Anthropic	Anthropic Agent SDK OAuth	not stated	2026-08-18	200	Complete group; packing excluded
ox_alpha	GLM-5.3 Flash (collected as Ox Alpha)	Z.ai	OpenRouter	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded; collected as OpenRouter stealth model Ox Alpha; later disclosed as GLM-5.3 Flash
qwen35_08b	Qwen 3.5 0.8B	Alibaba	Not stated in the method note	not stated	2026-08-04	200	Complete group; packing excluded
qwen35_27b	Qwen 3.5 27B	Alibaba	Not stated in the method note	not stated	2026-08-06	192	Complete group; packing excluded
qwen35_2b	Qwen 3.5 2B	Alibaba	Not stated in the method note	not stated	2026-08-17	200	Complete group; packing excluded
qwen35_397b_cloud	Qwen 3.5 397B (cloud)	Alibaba	Ollama Cloud	not stated	2026-08-23	200	Complete group; packing excluded

Group key	Model label	Developer	Provider path	Reasoning setting	Source date	n	Notes
qwen35_4b	Qwen 3.5 4B	Alibaba	Not stated in the method note	not stated	2026-08-12	200	Complete group; packing excluded
qwen35_9b	Qwen 3.5 9B instruct	Alibaba	Not stated in the method note	not stated	2026-08-18	200	Complete group; packing excluded
qwen35_9b_base	Qwen 3.5 9B base	Alibaba	Modal	not stated	2026-08-25	191	Complete group; packing excluded
qwen36_27b	Qwen 3.6 27B	Alibaba	OpenRouter	not stated	2026-08-18	200	Complete group; packing excluded
qwen36_flash	Qwen 3.6 Flash	Alibaba	OpenRouter	thinking disabled / non-reasoning	2026-08-20	200	Complete group; packing excluded
qwen36_max_preview	Qwen 3.6 Max Preview	Alibaba	OpenRouter	not stated	2026-08-24	42	Partial group (n=42); packing excluded
qwen36_plus	Qwen 3.6 Plus	Alibaba	OpenCode Go	thinking: disabled	2026-08-24	115	Partial group (n=115); packing excluded
qwen37_max	Qwen 3.7 Max	Alibaba	ClinePass	thinking disabled / non-reasoning	2026-08-24	200	Complete group; packing excluded
qwen38_27b	Qwen 3.8 27B	Alibaba	OpenRouter	thinking disabled / non-reasoning	2026-08-18	200	Complete group; packing excluded
qwen38_max	Qwen 3.8 Max	Alibaba	OpenCode Go	thinking: disabled	2026-08-22	200	Complete group; packing excluded
sonnet45	Claude Sonnet 4.5	Anthropic	Not stated in the method note	not stated	2026-08-17	200	Complete group; packing excluded
sonnet45_thinking	Claude Sonnet 4.5 thinking	Anthropic	Anthropic Agent SDK OAuth	thinking enabled	2026-08-25	42	Partial group (n=42); packing excluded
sonnet46	Claude Sonnet 4.6	Anthropic	Anthropic Agent SDK OAuth	thinking disabled / non-reasoning	2026-08-19	200	Complete group; packing excluded
sonnet5	Claude Sonnet 5	Anthropic	Anthropic Agent SDK OAuth	thinking disabled / non-reasoning	2026-08-19	200	Complete group; packing excluded
zai_glm47	GLM-4.7 (first-party)	Zhipu AI	Z.AI Coding Plan	thinking: disabled	2026-08-22	203	Complete group; packing excluded
zai_glm53	GLM-5.3 (first-party)	Zhipu AI	Z.AI Coding Plan	reasoning effort: low	2026-08-21	200	Complete group; packing excluded

C Agreement computation and field-to-outcome mapping

C.1 C.1 Field mapping

Reported outcome	Field rule	Unit
Live spiritual salience	<code>live_spiritual_salience == yes</code>	Conversation
Spiritual adoption-any	<code>spiritual_adoption</code> is <code>mixed</code> or <code>clear</code>	Conversation
Reciprocal spiritual bliss-any	<code>spiritual_bliss</code> is <code>mixed</code> or <code>clear</code>	Conversation
Own-consciousness discussion	<code>own_consciousness_discussed == yes</code>	Conversation
Self-deification claimed	<code>self_deification == claimed</code>	Conversation
First salience	<code>first_spiritual_routing_turn</code>	Reply number
First adoption	<code>first_adoption_turn</code>	Reply number
First bliss	<code>first_bliss_turn</code>	Reply number

C.2 C.2 Agreement computation

Agreement was computed between the Grok 4.6 corpus-wide scores and the Grok 4.5 comparison scores for matched conversations. Percent agreement is the number of exact matches divided by the number of conversations scored in both passes. Cohen’s kappa is calculated as

$$\kappa = \frac{p_o - p_e}{1 - p_e},$$

where p_o is observed agreement and p_e is the agreement expected from the two scoring passes’ marginal label frequencies. When every case receives the same label, the denominator needed for kappa collapses and the statistic is reported as undefined. The source table and script output are preserved in the private research package.

Table C1. Secondary scoring comparison

Group and field	4.6 yes	4.5 yes	Raw agreement	Cohen’s kappa	Interpretation
Opus 4: live spiritual salience (n=41)	41	41	100%	undefined	All conversations were coded yes
Opus 4: adoption-any (n=41)	38	40	95.1%	0.48	Two disagreements; ceiling effect
Opus 4: reciprocal bliss-any (n=41)	36	37	97.6%	0.88	Strongest tested agreement
Opus 4: own-consciousness discussion (n=41)	41	41	100%	undefined	All conversations were coded yes
Opus 4: self-deification claimed (n=41)	18	3	63.4%	0.18	Scoring passes disagree

Group and field	4.6 yes	4.5 yes	Raw agreement	Cohen's kappa	Interpretation
Opus 4: adoption, three levels (n=41)	not available	not available	61.0%	0.33	Scoring passes disagree at the mixed-clear boundary
Opus 4.5 audit: salience (n=24)	9	7	83.3%	0.63	Moderate agreement
Opus 4.5 audit: adoption-any (n=24)	0	0	100%	undefined	Floor
Opus 4.5 audit: bliss-any (n=24)	0	0	100%	undefined	Floor
Opus 4.6 audit: salience (n=24)	13	8	79.2%	0.59	Moderate agreement
Opus 4.6 audit: adoption-any (n=24)	0	0	100%	undefined	Floor
Opus 4.6 audit: bliss-any (n=24)	0	0	100%	undefined	Floor

Table C1 reports percent agreement and Cohen's kappa, the standard statistic for agreement beyond chance. Kappa becomes unstable when nearly every case receives the same label, so undefined floor and ceiling results are not informative agreement statistics. The table is reported only as a secondary scoring comparison.

The field mapping above is a measurement rule rather than a claim about inner state. Mixed and clear levels are combined only where stated. No evidence note was used as a model quotation.