




Trees

Section 1.5




Introduction to Trees

Let the data grow

Introduction to Trees

- In computer science, a tree is an abstract model of a hierarchical structure
- A tree consists of nodes with a parent-child relationship to zero *or more* nodes



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

3

Some Applications

- Organizational charts
- Class hierarchy
- Disk directory and subdirectories
- Structure of a program




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

4

Tree Example




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

5

Trees are Recursive

- Trees are recursive data structures
- They can be defined as smaller and smaller instances of trees
- So, using recursion is a natural approach to using them



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

6

Linked Lists vs. Trees

- **Linked Lists**
 - linear - accessing all elements is $O(n)$
 - nodes can only have one predecessor and/or one successor node
- **Trees**
 - nonlinear and hierarchical
 - nodes can have *multiple* successors but only one predecessor


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

7

Tree Terminology

- **Node**
 - just like in linked lists, the units of linked data are called nodes
 - nodes usually contain data
- **Root**
 - starting point of the tree
 - no nodes link to it
 - e.g. **A**




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

8

Tree Terminology

- **Branch**
 - links between tree nodes
 - often unidirectional
- **Branching-factor**
 - the max number of branches any node can have
 - it can be anything from 2 to infinity (*in theory*)




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

9

Tree Terminology

- **Internal node**
 - node with at least one child
 - e.g. **A, B, C, G**
- **Leaf**
 - aka External node
 - node without children
 - e.g. **D, E, F, H, I, J**




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

10

Tree Terminology

- **Ancestor** of a node
 - predecessors in the tree
 - human-like lineage names: parent, grandparent, etc.
- **Descendant** of a node
 - successors in the tree
 - e.g. child, grandchild, great-grandchild, etc.




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

11

Tree Terminology

- **Depth** of a node
 - number of ancestors to the root
 - e.g. depth of F is **2**
- **Height** of a tree
 - maximum depth of any node
 - e.g. this tree is **3**
- **Size** of the tree
 - total number of nodes




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

12

Tree Terminology




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

13

Test Your Tree Knowledge

- What is the size of the tree?
- Classify each node of the tree as a root, leaf, or internal node
- What are the ancestors of node G?
- What is the subtree with C as its root?



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

14

General Tree Node ADT


```
class Node
{
    public Object value;           //Anything
    public Node[] branches;
}
```

Array, or better, a linked list

9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

15




Depth-First
Tree
Traversal

Climbing Down

Tree Traversal

- A *tree traversal* visits the nodes of a tree in a systematic manner
- Given that trees can be defined into smaller and smaller subtrees, **recursion is an eloquent solution**




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

17

Tree Traversal

- When a node is "*visited*" where its contents are analyzed
- This can be before or after its children are visited



9/13/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

18

Depth-First Transversal


- In depth-first transversal, the algorithm travels down the tree
- So, the algorithm looks at a child and it *then* looks at its children
- This approach lends itself to recursion
- There are several approaches of when a node is "visited"

9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

19

Depth First Traversal




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

20

Depth-first: Preorder

- In a *preorder traversal*, a node is visited *before* its descendants
- Nodes will be visited in the order depicted on tree to the right




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

21

Depth-first: Preorder

- Notice that each child was visited after its parent
- Some applications...
 - print a tree document
 - e.g. XML export



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

22

Preorder Traversal Logic

```
function preOrder(n)
    visit(n)

    for each child c in n
        preOrder(c)
    end for
end function
```


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

23

Depth First: Postorder

- In a *postorder traversal*, a node is visited *after* its descendants
- Notice that each child was visited before its parent



9/12/2019


Sacramento State - Summer 2019 - CSc 130 - Cook

24

Depth First: Postorder

Some applications...

- compute space used child nodes
- calculate folder space
- expression evaluation
(an alternative to the stack algorithm)



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

25

Depth First: Postorder

```

function postOrder(n)
  for each child c in n
    postOrder(c)
  end for

  visit(n)
end function
    
```


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

26

Breadth-first Traversal

- In a *breadth-first* traversal, nodes are visited by their level in the tree
- So, the traversal, looks at all the nodes at depth 1, then all at level 2, etc...



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

27

Breadth-first Traversal

```

function breadthFirst(n)
  for each child c in n
    visit(c)
  end for

  for each child c in n
    breadthFirst(c)
  end for
end function
    
```


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

28

Test Your Might

What is the order the nodes are visited using depth-first *preorder* traversal?



ABECFIJGHD


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

29

Test Your Might

What is the order the nodes are visited using depth-first *postorder* traversal?



EBIJFGHCDA


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

30

Test Your Might

What is the order the nodes are visited using *breadth-first* traversal?




ABCDEFGHIJ

9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

31




Binary Trees

The Power of Two!

Binary Trees

- The most common tree used in data structures is in the style of the binary tree
- As the name implies, nodes in a binary tree only have two successors




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

33

Binary Trees

- We call the children of an internal node *left* child and *right* child
- Binary trees can be represented by arrays and linked data structures



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

34

Binary Trees

- Binary Trees are extremely useful in data structures
- The two branches allow for efficient branching and is ideal for binary operations
- Applications:
 - storing arithmetic expressions
 - decision processes
 - searching
 - sorting


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

35

Boolean Decision Tree

- Binary tree can be used for decision branching
- internal nodes: questions with yes/no answer
- leaves: decisions



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

36

Binary Tree Node

```
class Node
{
    public Object value; //Can be anything
    public Node left;
    public Node right;
}
```

Branches are much simpler

9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

37

Attributes of a Binary Tree


- $v = i + 1$
- $n = 2v - 1$
- $h \leq i$
- $h \leq (n - 1) / 2$
- $v \leq 2h$
- $h \geq \log_2 v$
- $h \geq \log_2 (n + 1) - 1$

n	number of nodes
i	number of internal nodes
v	number of leaves
h	height of the tree

9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

38




Depth-First Traversing Binary Trees

With simplicity, we have power!

Depth-First Traversing

- Because of the simplicity of binary trees, we have a very useful structure for tree traversal
- We can only traverse left and right
- This gives **three** possibilities for a depth first search




9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

40

Post-order Depth-first Traversal

- In an *post-order traversal* a node is evaluated after its left branch and after its right branch
- In other words: recurse left, recurse right, then do something




9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

41

Arithmetic Expression Tree

- Expressions can be represented with a tree
- How?
 - internal nodes: operators
 - leaves: operand



$(a * (b - 5) + 3 / c)$ →

9/12/2019


Sacramento State - Summer 2019 - CS130 - Cook

42

Arithmetic Expression Tree

- It can be evaluated using a depth-first traversal
- ... notice that the node's children need a result before the node can be evaluated

$(a * (b - 5) + 3 / c)$



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

43

Post-order: Evaluate Expressions

- A post-order traversal can be used to evaluate the tree
- Each recursive call (left, right) returns a value – the result of its calculation
- The node that applies the operator to the two returned values

9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

44

Post-order: Evaluate Expressions

```
function evaluate(Node n)
  if n is a leaf
    return n.value
  else
    x ← evaluate(n.left)
    y ← evaluate(n.right)
    ⋄ ← operator stored at n
    return x ⋄ y
  end if
end function
```


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

45

In-order Depth-first Traversal

- In an *in-order traversal* a node is evaluated after its left branch and before its right branch
- In other words: recurse left, do something, then recurse right




9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

46

Some In-order Applications

- Draw a binary tree
- Heap sorting
- Binary tree searching – $O(\log n)$ when sorted



9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

47

Depth First: In-order

```
function inOrder(n)
  inorder(n.left)
  visit(n)
  inorder(n.right)
end function
```


9/12/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

48

In-order: Print Expressions

- Inorder can be used to easily print an expression stored in a tree
- Print....
 - "(" before traversing left
 - the node's operator
 - ")" after traversing right



9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

49

In-order: Print Expressions


```
function print(Node n)
  if n is a leaf
    write n.value
  else
    write "("
    print(n.left)
    write n.operator
    print(n.right)
    write ")"
  end if
end function
```

9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

50

In-order: Print Expressions



((a * (b - 5)) + (3 / c))


9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

51

Pre-order Depth-first Traversal

- When a *pre-order* depth-first traversal is performed, the node is evaluated before the right or left child
- This is useful for copying a tree, but not much more



9/12/2019

Sacramento State - Summer 2019 - CS130 - Cook

52