




## Abstract Data Types

Section 1.2, 1.3




## Data Structures

Return to CSC 15 and CSC 20

## Abstract Data Types

- Arrays and linked-lists are both *data structures*
- They are methods of storing and organizing data




9/5/2019

Sacramento State - Fall 2019 - CSC 130 - Cook

3

## Abstract Data Types

- Depending on how data is accessed, arrays and linked lists have areas where they excel and falter
- We will cover more later in the semester – some which have incredible in features



9/5/2019

Sacramento State - Fall 2019 - CSC 130 - Cook

4



## Array Data Structure

Hidden math = easy code

## Array Data Structure

- The array data structure is found in practically every programming language
- This is also one of the fundamental ways data is stored in memory



9/5/2019

Sacramento State - Fall 2019 - CSC 130 - Cook

6

## Behind the Scenes...

- Arrays are just continuous blocks of memory containing multiple instances of the same type
- Since the instances are continuous, values can be read/written randomly in  $O(1)$



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

7

## Array Math Example: 32-bit int

- Let's assume the array starts at address **2000**
- Each array element will take 4 bytes (for 32-bit integers)
- Array elements are stored continuous

2000	31302070
2004	74732074
2008	6F205261
2012	76656E63
2016	6C617721

9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

8

## Array Math Example: 32-bit int

- array[0]** is at **2000**
- array[1]** is at **2004**
- array[2]** is at **2008**
- array[3]** is at **2012**
- array[4]** is at **2016**
- etc...

2000	31302070
2004	74732074
2008	6F205261
2012	76656E63
2016	6C617721

9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

9

## Behind the Scenes...

- So, when an array element is read, internally, a mathematical equation is used
- It takes into account the start array, the array index, and the size of each element

	○
	○
<b>start + (index × size of type)</b>	○
	○
	○

9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

10

## Behind the Scenes...

- This is why the C Programming Languages uses zero as the first array element*
- If zero is used with this formula, it gets the start of the array

	○
	○
<b>start + (index × size of type)</b>	○
	○
	○

9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

11

## Behind the Scenes...

- Java uses zero-indexing because C does
- ... and C does so it can create efficient assembly!

	○
	○
<b>start + (index × size of type)</b>	○
	○
	○

9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

12

## Auxiliary Storage in arrays

- Also, because elements are calculated, there is no extra storage overhead based on the array size
- So, the *auxiliary storage* overhead is  $O(1)$



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

13

## Resizing Arrays

- A *dynamically allocated array* is resized anytime an object is added or removed
- Because arrays require all elements to be stored continuously...
- ...the old block of memory (old array) needs to be copied to a new one




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

14

## New Block Must Be Created

Current block



New block




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

15


## Copy Values to New Block

Current block



New element here

New block



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

16

## Resizing Arrays is $O(n)$



- While reading / writing elements takes only  $O(1)$ ...
- ... every time an array is resized, it will require  $O(n)$  time to copy the old array to the new one

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

17

## Fixed-Sized Arrays

- Arrays can have a fixed sized called a *capacity*
- In this case, the array is never resized
- The array is often only partially filled
- An "end" index is maintained




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

18

## Fixed-Size Array




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

19

## Fixed-Size Wrapping Around

- Sometimes, you might need an array that wraps
- These are useful if both the first and last items can be removed
- ... or older items can be discarded if space is needed




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

20

## Fixed-Size Wrapping Around

- In addition to a "end" index, a "start" index is maintained
- Once the end of the array is reached, the array "wraps" to index 0
- ... and continues until end is reached




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

21

## Fixed-Size Array



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

22



## Linked List Data Structure

CSC 20's Revenge

## Linked List Data Structure

- Linked lists are a fundamental data structure that was covered in CSC 20
- Data is stored in a series of nodes with connected with links



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

24

## Linked List Data Structure

- Unlike arrays, where the element can be found using a calculation, linked-lists require the list to be traversed
- So, finding an item in a linked list requires  $O(n)$




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

25

## Single-Linked List – Find D




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

26

## Single-Linked List – Find D




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

27

## Single-Linked List – Find D




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

28

## Single-Linked List – Find D



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

29

## Head and Tail Nodes




- Linked lists maintain a link to the head node
- Often, in a well-written linked lists, a link to the tail node is also maintained
- Why? It has a huge impact on time complexity

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

30

## Append Value – No Tail Node




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

31

## Append Value – No Tail Node




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

32

## Append Value – No Tail Node




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

33

## Append Value – No Tail Node



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

34

## Head and Tail Nodes




- Without a tail node, the entire list must be traversed to find the end
- This will require  $O(n)$
- Adding a tail node, will decrease it to  $O(1)$

9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

35

## Append Value – With Tail Node




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

36

## Append Value – With Tail Node




9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

37

## Append Value – With Tail Node



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

38

## Use a Tail Node!

- Unless you are only appending nodes at the head of a linked list, maintain a tail node
- For **all** the examples used in these slides... assume the linked list has a tail node



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

39

## Auxiliary Storage in Linked Lists

- Unlike arrays, linked lists must store links between nodes
- So, the *auxiliary storage* overhead is  $O(n)$ 
  - ...which is usually the size of an address
  - 64-bit system  $\rightarrow$  8 bytes



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

40

## Test Your Might...

```
LinkedList list;
```

```
for(i = 0; i < list.Count; i++)
{
    total += list.Find(i);
}
```

$O(n)$

$O(n^2)$

9/5/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

41

## Iterators

- To avoid accidental  $O(n^2)$ , mainly programming languages support iterator objects
- They store information about the current state when all items in a data structure are sequentially read



9/5/2019

Sacramento State - Cook - CSc 35 - Fall 2019

42

## Iterators

- This maintains  $O(n)$  for accessing all the list's elements
- This is the purpose of the For-Each Statement
- Notation varies greatly between languages (when they are supported)



9/5/2019

Sacramento State - Cook - CSc 130 - Fall 2019

43


## Array vs. Linked List

Operation	Array	Linked List
Find (to read or write)	$O(1)$	$O(n)$
Insert (arbitrary)	$O(n)$	$O(n)$
Add first/last	$O(n)$	$O(1)$
Remove first/last	$O(n)$	$O(1)$
Auxiliary storage	$O(1)$	$O(n)$

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

44




## Data Abstraction

### Section 1.2

## Abstract Data Types

- *Data types* are used in practically all programming languages
- The core data types found in language is known as a *primitive data type*




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

45

## Data Types Specify 2 Things

1. Set of possible values
2. Operations on the data
  - these are alternatively called *functions* or *methods*
  - data types often define the errors can occur during each operation



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

47

## Integer Example

- *int* is a type (found in most languages)
- The 32-bit version can contain values from  $-2^{31}$  to  $2^{31} - 1$

```
int n;
```

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

48



## Integer Example

- Operations include:  $+$ ,  $*$ ,  $-$ ,  $/$ ,  $\%$ , and many more (e.g. comparisons)


```
int n;
```

9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

49

## Abstract Data Types




- An *abstract data type (ADT)* hides how it is implemented from the *client* (programmer)
- The client only interacts with the defined operations
- This layer of abstraction separates implementation from behavior

9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

50

## ADTs vs Data Structures



- An ADT is implementation independent
- Can internally use any data structure
  - array, linked list, etc...
  - depending how the ADT works, some are better than others

9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

51

## ADTs vs Data Structures




- ADT *defines application program interface (API)*
- ... or just *interface* (for short)
- It defines:
  - operations (methods)
  - properties (public fields)

9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

52

## Data Structures



9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

53

## Example ADT: Cheese Trader

- Data stores orders of cheese
- The operations supported are
  - buy (cheese, count)
  - sell (cheese, count)
  - cancel (Order)
  - balance – current funds



9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

54

## Example ADT: Cheese Trader

### Error conditions:

- nonexistent cheese
- sell a cheese we don't have
- count is not greater than 0



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

55

## Cheese Trader API



```
public class CheeseTrader
```

```
    int buy(string name, int count) Returns order #
```

```
    int sell(string name, int count) Returns order #
```

```
    void cancel(int order)
```

```
    double balance()
```

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

56

## Reference Types




- Most languages are based on largely based on building abstract data types called *reference types*
- They are *links* to nebulous *objects* – whose contents & implementation are unknown

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

57

## Reference Types



- This is known as *object-oriented programming*
- ... and is the basis of all modern programming languages

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

58



## Bags

Just toss it in

## Bags

- A bag is one of the most simplistic ADT that stores multiple objects
- It can only add items
- Order doesn't matter – nor is it expected to be maintained



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

60

## Bags

- At its core, the class only requires one method (add)
- Other attributes, such as size, count, etc... and be inferred from return types (i.e. null)



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

61

## Bag API



```
public class Bag
```

```
    Bag ()
```

*Create an empty bag*

```
    void add(Item item)
```

```
    bool isEmpty ()
```

```
    int size ()
```

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

62

## Bag Summary


Operation	Fixed Array	Resizable Array	Linked List
Add()	$O(1)$	$O(n)$	$O(1)$

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

63


## Stacks



Piles of... Data

## Stack

- A stack is an abstract data type that stores objects
- Based on the concept of a stack of items – like a stack of dishes
- Data can only be added to or removed from the top of the stack




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

65

## Stack

- This gives a **first-in-last-out** logic (aka FILO)
- Same concept is also called **last-in-first-out** (LIFO)



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

66

## Examples of Stacks

- Page-visited "back button" history in a web browser
- Undo sequence in a text editor
- Deck of cards in Windows Solitaire




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

67

## Stack Operation: Push

- A value is added to the stack
- It is placed on the top location
- Rest of the items are "covered"




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

68

## Stack Operation: Pop

- Removes an item from the stack
- Last item added is removed
- 2<sup>nd</sup> item becomes the top



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

69

## Stack API



```
public class Stack
```

```
Stack ()
```

*Create an empty stack*

```
void push(Item item)
```

```
Item pop ()
```

```
bool isEmpty ()
```

```
int size ()
```

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

70

## Stacks: Error Conditions

- Attempting the execution of an operation of ADT may sometimes cause an error condition, called an exception
- Exceptions are said to be "thrown" by an operation that cannot be executed
- In the Stack ADT, operations pop and top cannot be performed if the stack is empty


9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

71

## Resizing an Array-Based Stack

- Resizing the stack is expensive
- If a dynamically allocated array is used, each push/pop will require  $O(n)$



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

72

## Some Stack-based solutions

- For a dynamic allocated array - grow/shrink by a specific # of elements each time in an attempt to minimize resizes
- ... or used a fixed-capacity array – but your stack will have a fixed capacity




9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

73

## Fixed-Capacity Stacks

- It can be implemented by keep track of a capacity value (usually an int)
- The stack would behave as normal until the capacity is reached
- In this case, one of two things will happen...



9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

74

## Full Fixed-Capacity Stack...

- Stack throws an *Overflow Error*
- Stack discards an object
  - the bottom of the stack is typically removed
  - this gives the space needed for the newly pushed object
  - e.g. the history feature of your web browser

9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

75

## Array-Based Fixed-Capacity Stack

- While using an array for a normal stack (no fixed capacity) has a number of drawbacks
- ... for fixed-capacity, an array is an excellent choice – in specific situations...



9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

76

## Array-Based Fixed-Capacity Stack

- When the capacity is reached, either an error occurs or the bottom of the stack is simply **discarded**
- ... this is the case for the "undo" feature found in most applications



9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

77


## Stack Summary

Operation	Fixed Array	Resizable Array	Linked List
Pop()	O(1)	O(n)	O(1)
Push()	O(1)	O(n)	O(1)
Top()	O(1)	O(1)	O(1)

9/5/2019

Sacramento State - Fall 2019 - CS130 - Cook

78




Queues

Conga-line of Data!

## Queues


- The *Queue ADT* stores list of arbitrary objects
- Based on the concept of a line – like what you do when you buy groceries
- Objects enter the back of the line, and have to wait for prior items to leave before they do



9/5/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 80

## Queues


- In most parts of the World, they call a "line" a "queue"
- Main queue operations:
  - *enqueue* (object): place on item on the queue
  - *dequeue*: removes and returns the first inserted object



9/5/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 81

## Examples of Queues


- Data being read from the keyboard or a file
- People waiting in line to go on Space Mountain
- Instructions on how to perform a task



9/5/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 82

## Queue Operation: Enqueue


- When an object is "enqueued", it is put on to the end of the queue
- The items on the top of the queue are not covered



9/5/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 83

## Queue Operation: Dequeue

- Dequeue removes the item from the front of the queue
- Second item becomes the new first item
- This gives a first-in-first-out logic (aka FIFO)



9/5/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 84

## Auxiliary Queue Operations

- Queues also tend to have some operations defined
- These are not necessary, but they are useful
- Auxiliary operations:
  - peek**: return the next object without removing it. This is also sometimes called "front"
  - size**: returns the number of objects on the queue
  - isEmpty**: indicates whether the queue contains no objects. This is an alternative to size()

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

85

## Queue API



```
public class Queue
```

```
Queue ()
```

*Create an empty queue*

```
void enqueue (Item item)
```

```
Item dequeue ()
```

```
bool isEmpty ()
```

```
int size ()
```

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

86


## Queue Summary

Operation	Fixed Array	Resizable Array	Linked List
Enqueue()	$O(1)$	$O(n)$	$O(1)$
Dequeue()	$O(1)$	$O(n)$	$O(1)$
Peek()	$O(1)$	$O(1)$	$O(1)$

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

87




The Deque ADT

Time to shuffle the "deck"

## Deque ADT

- There is a variant of the queue called a deque (pronounced "deck")
- The name is derived from double-ended queue (sometimes it is shorted more to DQ)




9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

89

## Deque ADT

- As the name implies, its queue allows insertions and removals from both ends
- It is a merging of a stack and queue data ADT and the operations are union of the two
- Be warned: the names of the operations vary greatly between languages



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

90

## Deque ADT

- **addFront**
  - place an object on the front of the deque
  - this is same as stack "push"
  - also called: offerFirst, pushFirst
- **addBack**
  - place an object on the end of the deque
  - this is the same as queue "enqueue"
  - also called: offerLast, pushLast

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

91

## Deque ADT

- **removeFront**
  - remove an object from the front of the deque
  - this is the same as queue "dequeue"
  - also called: pollFirst, popFront
- **removeBack**
  - this is unique – and not found in either a stack or queue ADT
  - also called pollLast, popBack

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

92

## Deque API



public class Queue	
Deque ()	Create an empty deque
void addFront (Item item)	
void addBack (Item item)	
Item removeFront ()	
Item removeBack ()	
bool isEmpty ()	
int size ()	

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

93

## Deque Example

1. addFront ('N')
2. addBack ('E')
3. addFront ('W')
4. addBack ('D')
5. addFront ('P')



9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

94

## Deque Advantages

- A deque can function as either a stack or queue
- "Add Front" operation can be used to "redo" or "undo" a queue removal – remove then put it back in line
- There are some scenarios where this logic is needed

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

95

## Deque Disadvantages

- While, Stacks/Queues can be created with a single-linked-list, *a Deque requires a double-linked-list*
- ...otherwise, removing items from the end of the list would require  $O(n)$  – even with an end pointer
- Also, the link overhead (memory requirements) is doubled

9/5/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

96



## Deque Summary

Operation	Fixed Array	Resizable Array	Single Linked List	Double Linked List
addFront()	$O(1)$	$O(n)$	$O(1)$	$O(1)$
addBack()	$O(1)$	$O(n)$	$O(1)$	$O(1)$
removeFront()	$O(1)$	$O(n)$	$O(1)$	$O(1)$
removeBack()	$O(1)$	$O(n)$	$O(n)$	$O(1)$

9/5/2019

Sacramento State - Fall 2019 - CS61B - Cook

97