

Two vertical bars, one dark green and one yellow, are positioned on the left side of the slide.

# 5\_UNIX

## The *make* Tool/Command



## The reasons for the *make* utility

In a large project, one doesn't want to re-compile *everything*, every time a change is made.

*make* keeps track of dependencies,  
of what needs re-compiling,  
of what needs re-linking.

**Syntax:** make [-f makefile]

Most programmers use a standard output name.

Examples:        > make  
                  > make -f Project23make

### Often Used Options:

- f       Tells **make** which file to use as its makefile  
         Without -f, it looks first for *makefile*  
                                 and then for *Makefile* by default.
- n       Tells **make** to print out what it would have done without  
         actually doing it.
- k       Tells **make** to keep going when an error is found, rather  
         than stopping as soon as the first problem is detected.

Two vertical bars, one dark green and one yellow, are positioned on the left side of the slide.

A simple code file & its make file

```
/* power.c      */
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
int main(void)
{
    float x, y;

    printf("\nThe program takes x and y from stdin and displays x^y.\n");

    printf("Enter integer x: ");
    scanf ("%f", &x);
    printf("Enter integer y: ");
    scanf ("%f", &y);

    printf("x^y is: %6.3f\n", pow((double)x,(double)y));
    return EXIT_SUCCESS;
}

/* The RUN is on the next slide */
```

[bielr@athena ~/csc60]30> **gcc power.c -o power**  
/tmp/ccEzY1AX.o(.text+0x83): In function `main':  
: undefined reference to `pow'  
collect2: ld returned 1 exit status  
[bielr@athena ~/csc60]31>

---

***Forgot to add... -lm ...to link to the math library.***

---

[bielr@athena ~/csc60]38> **gcc power.c -lm -o power**  
[bielr@athena ~/csc60]39> **power**

The program takes x and y from stdin and displays  $x^y$ .

Enter integer x: 9.82

Enter integer y: 2.3

$x^y$  is: 191.362

[bielr@athena ~/csc60]40>

## A makefile for the power program:


>vim makefile

```
# Sample makefile for the power program
# Remember: each command line starts with a TAB

power: power.c
    gcc power.c -o power -lm
```

Contents of the file  
named *makefile*

>




```
[bielr@athena ~/csc60]40> make  
make: `power' is up to date.  
[bielr@athena ~/csc60]41>
```

*Use touch to alter the dates to force recompilation*

```
[bielr@athena ~/csc60]44> touch power.c  
[bielr@athena ~/csc60]45> make  
gcc power.c -o power -lm  
[bielr@athena ~/csc60]46>
```



Dependency Chart: *Alter **power** so it is in two functions, two files.*



*/\* power2.c*

*Alter **power** so it is in two functions. \*/*

*/\* page 1 of 2 \*/*

#include <stdio.h>

#include <stdlib.h>

**double compute(double x, double y);**

int main(void)

{

float x, y;

printf("\nThe program takes x and y from stdin and displays x^y.\n");

printf("Enter integer x: ");

scanf ("%f", &x);


printf("Enter integer y: ");

scanf ("%f", &y);

printf("\nx^y is: %6.3f\n\n", **compute(x,y)**);

return EXIT\_SUCCESS;

}



```
/* The new function   page 2 of 2 */  
/* compute.c          */
```

```
#include <math.h>  
double compute(double x, double y)  
{  
    return (pow(x, y));  
}
```

*First pass at a makefile:*

>**cat makefile**

power2: power.o compute.o

gcc power.o compute.o -o power2 -lm

>

---

[bielr@athena ~/csc60]60> **make**

make: \*\*\* No rule to make target `power.o', needed by `power'. Stop.

[bielr@athena ~/csc60]61>

*/\* Second pass at a makefile: \*/*  
*/\* Look at its contents. We have no **p2.h** but it is included in light italics*  
*to show where it would be placed. \*/*

**>cat makefile**

```
power2: power2.o compute.o p2.h
    gcc power2.o compute.o -o power2 -lm
power2.o: power2.c p2.h
    gcc -c power2.c
compute.o: compute.c p2.h
    gcc -c compute.c
```

---

*/\* Run make using our new makefile \*/*

```
[bielr@athena ~/csc60]68> make
gcc -c power2.c
gcc -c compute.c
gcc power2.o compute.o -o power2 -lm
[bielr@athena ~/csc60]69>
```

# *Third and last pass at a makefile:*  
# **power2.h** is not needed but included in light *italics* to  
# show where it would be located if it was needed

---

# >**cat makefile**  
power2: power2.o compute.o *power2.h*  
      gcc power2.o compute.o -o power2 -lm  
  
power2.o: *power2.h*  
  
compute.o: *power2.h*  
>

## ***/\* Helpful Comments \*/***


- Start by opening *vim*, and typing in the commands to a file named *makefile*.  
Close *vim* and then at the prompt, type: *make*
- When you enter **vim**, type: **:set list**  
This will show the non-printable characters:  
    ^I = tab  
    \$ = end of line
- To reverse the setting, type: **:set list!**
- To create a tab on *athena*, you may have to hit the tab key **twice** in a row.



## Another Example



***Example with two functions and a \*.h file:***



## Makefile Contents:

sum: main.o sum.o	<i>dependency</i>
gcc -o sum main.o sum.o	<i>action</i>
main.o: main.c sum.h	<i>dependency</i>
gcc -c main.c	<i>action</i>
sum.o: sum.c sum.h	<i>dependency</i>
gcc -c sum.c	<i>action</i>

Dependency lines start in column 1.

Action lines must begin with a **tab**.

If anything on a dependency line has changed, then the associated action(s) take place.

A dependency and its actions together are called a **rule**.

## An alternate example of this makefile:

sum: main.o sum.o	<i>dependency</i>
gcc -o sum main.o sum.o	<i>action</i>

main.o: sum.h	<i>dependency</i>
gcc -c main.c	<i>action</i>

sum.o: sum.h	<i>dependency</i>
gcc -c sum.c	<i>action</i>

## A makefile with a macro:

sum: main.o sum.o	<i>dependency</i>
gcc -o sum main.o sum.o	<i>action</i>
main.o sum.o: sum.h	<i>dependency</i>
gcc -c \$*.c	<i>action</i>

*The second rule states that the two .o files depend on sum.h.  
If we edit sum.h, both main.o and sum.o must be remade.*

*The macro \$\*.c expands first to main.c and then to sum.c*



## ***Macros in a Makefile***

The *make* utility supports simple macros that allow simple text substitution.

The macro must be defined before use, and is usually placed at start of the file.

Syntax: Macro\_name = text

These are also called Macro Variables.



## A more complicated example

*The Compare\_Sorts makefile in its entirety:*  
*(Dissection of each line follows on the next slides.)*

# Makefile for compare\_sorts

#After excution, use prof to get a profile.

BASE = /c/c/blufox

CC = gcc

CFLAGS = -p

EFILE = \$(BASE)/bin/compare\_sorts

INCLS = -I\$(BASE)/include

LIBS = \$(BASE)/lib/g\_lib.a

OBJS = main.o chk\_arrays.o compare.o \  
prn\_arrays.o slow\_sort.o


\$(EFILE): \$(OBJS)

    @echo "linking. . . ."

    @\$(CC) \$(CFLAGS) \$(INCLS) -c \$\*.c

\$(OBJS): compare\_sorts.h

    \$(CC) \$(CFLAGS) \$(INCLS) -c \$\*.c




```
# Makefile for compare_sorts  
#After execution, use prof to get a profile.
```

---

*Comments start with # and go till end of line.*





BASE = /c/c/blufox

---

*a macro definition.*

*Syntax: macro\_name = replacement\_string*

*BASE represents our base of operations on the local computer.*

*Doesn't have to be home directory.*



CC = gcc

---

*The CC macro specifies the C compiler we are using.*



CFLAGS = -p

---

*The CFLAGS macro specifies the options, if any, that will be used with the **gcc** command.*

- p** = Generate extra code to write profile information.  
You must use this option when compiling the source files you want data about, and you must also use it when linking.

Two vertical bars, one dark green and one yellow, are positioned on the left side of the slide.

# What is profiling?

Profiling is an important aspect of software programming. Through profiling one can determine the parts in program code that are time consuming and need to be re-written. This helps make your program execution faster which is always desired.

In very large projects, profiling can save your day by not only determining the parts in your program which are slower in execution than expected but also can help you find many other statistics through which many potential bugs can be spotted and sorted out.



EFILE = \$(BASE)/bin/compare\_sorts

---

*Specifies the executable file.*

INCLS = -I\$(BASE)/include

---

*Specifies a directory for include files proceeded by the **-I** option.*

*-I dir, --include-dir=dir*

*Specifies a directory dir to search for included makefiles. If several -I options are used to specify several directories, the directories are searched in the order specified. Unlike the arguments to other flags of make, directories given with -I flags may come directly after the flag: -Idir is allowed, as well as -I dir. This syntax is allowed for compatibility with the C preprocessor's -I flag.*



`LIBS = $(BASE)/lib/g_lib.a`

---

*Tells the compiler where to find our programmer-constructed header file.*



```
OBJS    = main.o chk_arrays.o compare.o \  
        prn_arrays.o slow_sort.o
```

---

*In this macro definition the replacement string is the list of object files that occurs on the right side of the equal sign.*

*(Used backslash \ to continue the line.)*

*Order is unimportant.*



`$(EFILE): $(OBJS)`  
`@echo "linking. . . ."`  
`@$(CC) $(CFLAGS) $(INCLS) -c $*.c`

---

*The first line is a dependency line, and the other two specify the actions to be taken.*

*The @ symbol means that the action line itself is not to be echoed on the screen.*

*Macro invocation has form:*

*\$( macro\_name )*

So `$(EFILE)` is replaced by `$(BASE)/bin/compare_sorts`

which then becomes `/c/c/blufox/bin/compare_sorts`

`$(OBJS): compare_sorts.h`  
`$(CC) $(CFLAGS) $(INCLS) -c $*.c`

---

*\$(OBJS) will be replaced by the list of object files.*

*The second action line is expanded to:*

```
@gcc -p -o /c/c/blufox/bin/compare_sorts main.o \  
chk_arrays.o compare.o prn_array.o slow_sort.o \  
/c/c/blufox/lib/g_lib.a
```

*Because of the backslash \, the line acts as one line.*

*-p causes the compiler to generate extra code suitable for the profiler.*



## More details about **make** (these expand just before use):

- \$? List of prerequisites changed more recently than the current target
- \$@ Name of the current target
- \$< Name of the current prerequisite
- \$\* Name of the current prerequisite, without any suffix
- Tells **make** to ignore any errors.
- @ Tells **make** not to print the command to standard output before executing it.




The ***touch*** command:

Syntax: touch [options] *files*

Changes two timestamps associated with a file:

- its *modification time* (when the file's data was last changed)
- its *access time* (when the file was last read)

If a given file doesn't exist, *touch* creates it as an empty file.



If we had done a *touch* on *compare\_sorts.h*,  
we would have forced all the other files to be recompiled.

## Other Useful Tools:

- diff** Prints the lines that differ in two files.
- wc** Word Count. Counts lines, words, and characters in one or more files.
- awk** A pattern scanning and processing language.  
On Linux, it is ***gawk***, a superset of *awk*.
- lex** Generates C code for lexical analysis.  
On Linux, it is ***flex***, a superset of *lex*.
- sed** A stream editor that takes its commands from a file.
- yacc** A parser generator.
- bison** GNU Project parser generator (yacc replacement)



# 5\_UNIX

## The *make* Tool/Command

## The End