


Arguments

Part 7

1




Arguments

Proving a Point

2

Arguments

- A combination of true statements can be used to claim another as true
- An *argument* is a collection of statements (called *premises*), which, when all are true, imply a consequence



Spring 2020 Sacramento State - Cook - CSc 28 3

3

Example Argument

raining \rightarrow wet outside
not wet outside

?

Our conclusion goes here

Spring 2020 Sacramento State - Cook - CSc 28 4

4

Example Argument 2

raining \rightarrow wet outside
not raining

?

What conclusion goes here?
Does it work?

Spring 2020 Sacramento State - Cook - CSc 28 5

5

Example Argument 3

x is duck or x is swan
x isn't a swan

?

Obvious! But why?

Spring 2020 Sacramento State - Cook - CSc 28 6

6

When an Argument is Valid

- When all the premises are true then the consequence must be true
- If all the premises are true, but the conclusion can be false, the argument is disproven



Spring 2020

Sacramento State - Cook - CSc 28

7

7

When an Argument is Valid

- However, if any premise is false, then the argument is not disproven – *it is still valid*
- We can often prove arguments by building truth tables



Spring 2020

Sacramento State - Cook - CSc 28

8

8

Argument Notation

- Arguments can be written out several ways
- The most common approach is to write each premise on a different line
- The consequence is written below the premises separated with horizontal line




Spring 2020

Sacramento State - Cook - CSc 28

9

9

Common Notation



Spring 2020


Sacramento State - Cook - CSc 28

10

10

Another Argument Notation

- Arguments can be written on a single line
- Premises are separated with commas
- Consequence can use the symbol \vdash or \therefore



Spring 2020

Sacramento State - Cook - CSc 28

11

11

Let's Try This



Spring 2020

Sacramento State - Cook - CSc 28

12

12

Arguments and Implication

- Arguments are actually implications with each premise connected with \wedge
- So, if you have premises **A**, premise **B**, and conclusion **C**, then it has the following form

$$\mathbf{A} \wedge \mathbf{B} \rightarrow \mathbf{C}$$

Spring 2020

Sacramento State - Cook - CSc 28

13

13



Valid Arguments

Proving a Point

14

Valid Arguments

- Rules of Inference* are valid arguments that are commonly used in proofs
- Most of these are obvious to you... it is natural logical thought



Spring 2020

Sacramento State - Cook - CSc 28

15

15

Rules of Inference

- Modus Ponens* (aka Law of Detachment)
- Modus Tollens*
- Disjunctive Syllogism*
- Hypothetical Syllogism*



Spring 2020

Sacramento State - Cook - CSc 28

16

16

Modus Ponens

- Modus Ponens* is the most basic Rule of Inference
- Based on the logic that if:
 - an implication is true
 - implication's hypothesis is true
 - then the implication's conclusion must be true



Spring 2020

Sacramento State - Cook - CSc 28

17

17

Modus Ponens Example

○	If it is a fish, then it lives in water.
○	It is a fish.
○	Therefore, it lives in water!

Spring 2020

Sacramento State - Cook - CSc 28

18

18

Modus Ponens

$$\begin{array}{l} p \rightarrow q \\ p \\ \hline q \end{array}$$

Rules of Inference

Spring 2020 Sacramento State - Cook - CSc 28 19

19

Modus Ponens

p	q	$p \rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

Spring 2020 Sacramento State - Cook - CSc 28 20

20

Modus Tollens

- *Modus Tollens* is closely relate to modus ponens
- Based on the logic that if:
 - an implication is true
 - implication's conclusion is false
 - then the implication's hypothesis must be false

Spring 2020 Sacramento State - Cook - CSc 28 21

21

Modus Tollens Example

○ If it is a fish, then it lives in water.

○ It doesn't live in water.

○ Therefore, it is not a fish!

Spring 2020 Sacramento State - Cook - CSc 28 22

22

Modus Tollens

$$\begin{array}{l} p \rightarrow q \\ \neg q \\ \hline \neg p \end{array}$$

Rules of Inference

Spring 2020 Sacramento State - Cook - CSc 28 23

23

Modus Tollens

p	q	$p \rightarrow q$	$\neg p$	$\neg q$
T	T	T	F	F
T	F	F	F	T
F	T	T	T	F
F	F	T	T	T

Spring 2020 Sacramento State - Cook - CSc 28 24

24

Disjunctive Syllogism

- *Disjunctive Syllogism* is based on the \vee operator that
- Based on the logic that if:
 - an or-statement is true
 - one of the operands is false
 - then, the other operand must be true



Spring 2020 Sacramento State - Cook - CSc 28 25

25

Disjunctive Syllogism Example

- It breathes water or air.
- It doesn't breath water.
- Therefore, it breathes air.

Spring 2020 Sacramento State - Cook - CSc 28 26

26

Disjunctive Syllogism

$p \vee q$
 $\neg p$

Rules of Inference

q

Spring 2020 Sacramento State - Cook - CSc 28 27

27

Hypothetical Syllogism

- *Hypothetical Syllogism* is based on an implication chain
- Gives a logical "chain" of events
- So, if $a \rightarrow b$ and $b \rightarrow c$ then $a \rightarrow c$



Spring 2020 Sacramento State - Cook - CSc 28 28

28

Hypothetical Syllogism Example

- If is a trout, then it is a fish
- If it is a fish, then it lives in water.
- Therefore, a trout lives in water!

Spring 2020 Sacramento State - Cook - CSc 28 29

29

Hypothetical Syllogism

$p \rightarrow q$
 $q \rightarrow r$
 $p \rightarrow r$

Rules of Inference

Spring 2020 Sacramento State - Cook - CSc 28 30

30

Let's Apply The Logic

- Let's these rules on the argument below
- We can use either a truth table or logical deduction

If I study then I will an A
If I don't watch Netflix then I will study
I didn't get an A

I watched Netflix

Spring 2020

Sacramento State - Cook - CSc 28

31

31

Simply Logic: letters

- First, let's simply the structure of the argument so we can see the logic
- We will assign each part a letter

s = studied
a = got an A
n = watched Netflix

Spring 2020

Sacramento State - Cook - CSc 28

32

32

Simply Logic: New Form

1. $s \rightarrow a$
2. $\neg n \rightarrow s$
3. $\neg a$

n

Spring 2020

Sacramento State - Cook - CSc 28

33

33

Modus Tollens – study, no A

1. $s \rightarrow a$
2. $\neg n \rightarrow s$
3. $\neg a$

n

1 and 3:
Modus Tollens

Spring 2020

Sacramento State - Cook - CSc 28

34

34

Modus Tollens – study, no A

1. $\neg s$
2. $\neg n \rightarrow s$
3. $\neg a$

n

1 and 3:
Modus Tollens
"Did not study"

Spring 2020

Sacramento State - Cook - CSc 28

35

35

Modus Tollens – study, Netflix

1. $\neg s$
2. $\neg n \rightarrow s$
3. $\neg a$

n

1 and 2:
Modus Tollens

Spring 2020

Sacramento State - Cook - CSc 28

36

36

Modus Tollens – study, Netflix

1. $\neg s$
2. $\neg \neg n$
3. $\neg a$

n

1 and 2:
Modus Tollens

"Did not *not* watch Netflix"

Spring 2020 Sacramento State - Cook - CSc 28 37

37

Double Negation

1. $\neg s$
2. $\neg \neg n$
3. $\neg a$

n

Double negation

Spring 2020 Sacramento State - Cook - CSc 28 38

38

Double Negation

1. $\neg s$
2. n
3. $\neg a$


n

2:
Double Negation

"Watched Netflix"

Spring 2020 Sacramento State - Cook - CSc 28 39

39



Logical Fallacies

"This is most illogical" – Mr. Spock


40

Logical Fallacies

- There are a number of fallacious arguments that, while they might look logical, are wrong
- The following slides contain some of them
- For fun, apply them to current political discourse or *History Channel 2*

Spring 2020 Sacramento State - Cook - CSc 28 41

41



LOGIC

42

Fallacy of the Converse

- *Fallacy of the Converse* is based on assumption that if the conclusion is true then the hypothesis is true
- Also called:
 - *affirming the consequent*
 - *converse error*



Spring 2020

Sacramento State - Cook - CSc 28

43

43

Fallacy of the Converse Example

○	If it is a fish, then it lives in water.
○	It lives in water.
○	Therefore, it is a fish!

Spring 2020

Sacramento State - Cook - CSc 28

44

44

Fallacy of the Converse

$p \rightarrow q$
q

p

p can still be false

Spring 2020

Sacramento State - Cook - CSc 28

45

45

Fallacy of the Converse

p	q	$p \rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

Spring 2020

Sacramento State - Cook - CSc 28

46

46

Fallacy of the Inverse

- *Fallacy of the Inverse* is based on assumption that if the hypothesis is false, then the conclusion is also false
- Also called:
 - *denying the antecedent*
 - *inverse error*



Spring 2020

Sacramento State - Cook - CSc 28

47

47

Fallacy of the Inverse Example

○	If it is a cat, then it is furry.
○	It is not a cat.
○	Therefore, it is not furry!

Spring 2020

Sacramento State - Cook - CSc 28

48

48

Fallacy of the Inverse

$p \rightarrow q$
 $\neg p$

 $\neg q$

q can be either true or false

Spring 2020

Sacramento State - Cook - CSc 28

49

50

Fallacy of the Converse

p	q	$p \rightarrow q$	$\neg p$	$\neg q$
T	T	T	F	F
T	F	F	F	T
F	T	T	T	F
F	F	T	T	T

Spring 2020

Sacramento State - Cook - CSc 28

50

51

Fallacy of Affirming a Disjunct

- Fallacy of Affirming a Disjunct** is based on assumption that if there are two attributes and one is true, the other must be false
- Other names:
 - fallacy of the alternative
 - false exclusionary disjunct



Spring 2020

Sacramento State - Cook - CSc 28

51

52

Affirming a Disjunct Example

- Suspect is either a politician or a lawyer.
- Suspect is a politician.
- Therefore, the suspect isn't a lawyer.

Spring 2020

Sacramento State - Cook - CSc 28

52

53

Fallacy of Affirming a Disjunct

$p \vee q$
 p

 $\neg q$

Just because p is true, doesn't mean q has to be false.

Spring 2020

Sacramento State - Cook - CSc 28

53

54


Fallacy of the Converse

p	q	$p \vee q$	$\neg q$
T	T	T	F
T	F	T	T
F	T	T	F
F	F	F	T

Spring 2020

Sacramento State - Cook - CSc 28

54




Boolean Algebra & Proofs

Proofs and Logic are one

55

Boolean Algebra

- Remember Boolean algebra laws: Associative, Commutative, etc...
- These can be used to expand an expression... and then simplify it in a different form



Spring 2020 Sacramento State - Cook - CSc 28 56

56

Example

if "a or b" is true and
"a and b" is false

then

a = not b

Spring 2020 Sacramento State - Cook - CSc 28 57

57

Example (with a rewrite)

We can rewrite it as an argument:

$$\begin{array}{l} a \vee b = \text{true} \\ a \wedge b = \text{false} \\ \hline a = \neg b \end{array}$$

Spring 2020 Sacramento State - Cook - CSc 28 58

58

The Strategy

- We could use a Truth Table to prove this
- Let's use Boolean Algebra to prove if this is correct

$$\begin{array}{l} a \vee b = \text{true} \\ a \wedge b = \text{false} \\ \hline a = \neg b \end{array}$$

Spring 2020 Sacramento State - Cook - CSc 28 59

59

The Approach

- Start with a
- Try to change it into $\neg b$
- Use the premises to replace values

$$\begin{array}{l} a \vee b = \text{true} \\ a \wedge b = \text{false} \\ \hline a = \neg b \end{array}$$

Spring 2020 Sacramento State - Cook - CSc 28 60

60

$a \vee b = \text{true}$
 $a \wedge b = \text{false}$

$a = a$		
$= a \wedge \text{true}$		Identity
$= a \wedge (b \vee \neg b)$		Complement
$= a \wedge b \vee a \wedge \neg b$		Distributive
$= \text{false} \vee a \wedge \neg b$		Premise
$= b \wedge \neg b \vee a \wedge \neg b$		Complement
$= \neg b \wedge (b \vee a)$		Distributive
$= \neg b \wedge \text{true}$		Premise
$= \neg b$		Identity

Spring 2020
Sacramento State - Cook - CSC 28
61

61