



Lab 10 Slides

Redirection & `execvp()`

exit Function

```
#include<stdlib.h>
```

```
void exit(int status);    // The _exit call is often used by the child.
```

Example: `exit(EXIT_SUCCESS);`

In `stdlib.h`:

```
#define EXIT_SUCCESS 0
```

```
#define EXIT_FAILURE 1
```

- The `exit()` function causes normal process termination and the value of status & 0377 is returned to the parent.
- All open `stdio(3)` streams are **flushed and closed**.
(C standard library - from `man 3 exit`). (informally)
clean shutdown, flush streams, close files, etc

`_exit` Function – Use in code for the *child*

- `_exit()`

- - The function `_exit()` terminates the calling process "immediately".
- Any open file descriptors belonging to the process are closed; any children of the process are inherited by process 1, `init`, and the process's parent is sent a **SIGCHLD** signal.
- (System call - from `man 2 _exit`)
(informally) drop out, files are closed but **streams are not flushed**

Note:

Child and parent could have buffers with a copy of the unflushed data.

If both call `exit()`, the pending stdio buffers to be **flushed twice**.

Thus, child should call `_exit()` instead.

execvp Function

```
#include<unistd.h>
```

```
int execvp(const char *filename, *const argv[] );
```

Returns nothing on success, or -1 on error.

Example: return_value = execvp(argv[0], argv);



open call (1 of 5)

- Opening a file informs the kernel that an application wants to access a file
- Allows the kernel to set aside resources
- Returns file descriptor on success, or -1 on error

open call (2 of 5)

Call:

```
#include <sys/stat.h>
#include <fcntl.h>

int open (const char *pathname, int flags, ... /* mode_t mode */);
```

Example:

```
/* Open new or existing file for reading and writing, truncating
to zero bytes; file permissions read+write for owner, nothing
for all others */

fd = open("myfile", O_RDWR | O_CREAT |
          O_TRUNC, S_IRUSR | S_IWUSR);
if (fd == -1)
    perror("Error opening file");
```

Note: a const char *pathname means that the program can't change the data that pathname points to through the pathname pointer!

open call (3 of 5)

- Flags indicating access type:
 - O_RDONLY : read only
 - O_WRONLY : write only
 - O_RDWR: read/write
 - O_CREAT: create the file if doesn't exist
 - O_APPEND: write at end
 - O_TRUNC: Truncate exist file to zero length
 - etc.
- Can also bitwise – inclusive – or them
 - i.e. O_WRONLY | O_APPEND
- **See: Table 4-3 (in LPI, page 74)**

open call (4 of 5)

- Different mode values (file permissions)
- S_IRUSR: read permission, owner
- S_IWUSR: write permission, owner
- S_IROTH: read permission, others
- S_IWOTH: write permission, others
- etc

Note: for more information, please do a
man 2 open to get all modes values.

open call (5 of 5)

- Open returns a small integer called a *file descriptor (fd)*
- Application passes this value back to the kernel in subsequent requests to work with a file
- Each process created starts with three open files:
 - **0: standard input (stdin)**
 - **1: standard output (stdout)**
 - **2: standard error (stderr)**

<inistd.h> contains constants

STDIN_FILENO, STDOUT_FILENO, STDERR_FILENO for them

dup2 Function

```
#include <unistd.h>
```

```
int dup2(int oldfd, int newfd);
```

Returns (new) file descriptor on success, or -1 on error

Example: **dup2**(fd, 1); // Redirect from stdout (1) to the file (fd).

More in 9-Unix, slide 44-46

close - Closing Files

- Closing a file tells the kernel it may free resources associated with managing the file

• The Call:

```
#include <unistd.h>
```

```
int close (int fd);
```

Returns 0 on success,
-1 on error

Examples:

```
if (close(fd) == -1) {  
    perror("close file error");  
    exit(EXIT_FAILURE);  
}
```

```
int returnvalue = close(fd);  
if (returnvalue == -1) {  
    perror("close file error");  
    exit(EXIT_FAILURE);  
}
```

Dealing with Errors

You have at least two choices:

- *Use a `fprintf`* for non-system call errors, as in the redirection code.
 - *Example:* `fprintf(stderr, "No command");`
- *Use `perror` function* for system calls errors.
 - *Example:* `perror("Error executing command");`

The book shows a function named: `errExit`

It will `not` work for us unless we include the appropriate code from the text book

perror System Call

```
#include <stdio.h>
```

```
void perror (const char *msg);
```

perror also will print the associated *errno*

More information in the text on pages 48-50



Review

Debugging

Two vertical bars, one dark green and one yellow, are positioned on the left side of the slide.

What is gdb?

- **gdb** is the GNU Project debugger
- **gdb** provides some helpful functionality
 - Allows you to stop your program at any given point.
 - You can examine the state of your program when it's stopped.
 - Change things in your program, so you can experiment with correcting the effects of a bug.
- Also a command-line program

Using gdb:

- Compile with the **-g** flag to set up for debugging
- To start gdb with your hello program type:
`gdb HelloProg`
- When gdb starts, your program is not actually running.
- You have to use the ***run*** command to start execution.
- Before you do that, you should place some break points.
- Once you hit a break point, you can examine any variable.

Useful gdb commands

run *command-line-arguments*

Begin execution of your program with arguments

break *place*

place can be the name of a function or a line number

For example: **break main** will stop execution at the first instruction of your program

delete *N*

Removes breakpoints, where *N* is the number of the breakpoint

step

Executes current instruction and stops on the next one

Gdb commands cont.

next

Same as **step** except this doesn't step into functions

print *E*

Prints the value of any variable in your program when you are at a breakpoint, where *E* is the name of the variable you want to print

print/x var (i.e p/x S_IFREG where x is the hex value),
other
options include: d (decimal), o (octal), t(two - binary), etc.

help *command*

Gives you more information about any command or all if you leave out command

quit

Exit gdb

GDB debugger with *fork* (1 of 2)

GDB Commands using with fork	Description
(gdb) set follow-fork-mode (child or parent)	<p>Set debugger response to a program call of fork.</p> <p>follow-fork-mode can be:</p> <ul style="list-style-type: none">parent - the original process is debugged after a forkchild - the new process is debugged after a fork <p>The unfollowed process will continue to run. By default, the debugger will follow the parent process.</p>
(gdb) set detach-on-fork (on or off)	<p>Specifies whether GDB should debug both parent and child process after a call to fork() - Default is on: The child process (or parent process, depending on the value of follow-fork-mode) will be detached and allowed to run independently. This is the default.</p>

GDB debugger with *fork* (2 of 2)

GDB Commands using with fork	Description
(gdb) catch fork	Catch calls to fork.
(gdb) info inferiors	Display IDs of currently known inferiors.
(gdb) inferior N	Use this command to switch between inferiors. The new inferior ID must be currently known (See above command).



Lab 10 Slides

The End